Step#1: Accounts/PIDs

A: Quick Check Accounts

0	Root
1000	Standard User
1-999	System/Background

B: RED FLAGs (PIDs)

/tmp/	/var/tmp/	/dev/shm/	/.hidden/

Step#2: Network Ports: Expected

A: Rocky E-Commerce

HTTP	HTTPS	MySQL	MariaDB	SSH
80	443	3306	5432	22

B: Debian Splunk

Splunk Web	Splunk MGMT	Splunk Indexing	SSH
8000	8089	9997	22

C: Ubuntu Email

SMTP	IMAP	POP3	SSH
25	143	110	22
587	993	995	

D: RED FLAGs

(RANDOM PORTS) (HIGH PORTS) (UNKOWN LISTENERS)

1337	2222	4444	5555	6666	6667	7777	8081	9001	9001	31337

Step#3: Cron/C2/Schedule-Tasks

A: RED FLAGs

- Obfuscation
- Encoding
- Commands wrapped in base64
- Hidden execution paths (Notes: 1B)
- Task set to run every min using @ reboot and tied to scripts
- Raw execution to shell (example: curl... | bash)

Step#4: systemd

A: States Definitions

.service	Background daemons/scripts
.timer	Schedules that trigger .service
.sockets	Service listening on network/ports
.target	Grouping of services

B: RED FLAGs

updater.service	systemd-networked-update.service	conspy_1.service

Random Strings = xkj12.service,

Step#5: Firewall

A: RED FLAGs

- **ports:** "Allow only known ports, delete unknown and possibly firewall if there"
- **services:** "Allow only known services, delete unknown and possibly investigate the service"
- **forward ports:** "If set to YES, change it to NO, investigate any ports being forwarded"
- **masquerade:** "If set to YES, change it to NO.
- **rich rules:** "Red Team could firewall your service ports or allow IPs. This is where custom IP allow/deny live"