The UDUNITS-2 C API

Copyright 2011 University Corporation for Atmospheric Research. All rights reserved.

Access and use of this software shall impose the following obligations and understandings on the user. The user is granted the right, without any fee or cost, to use, copy, modify, alter, enhance and distribute this software, and any derivative works thereof, and its supporting documentation for any purpose whatsoever, provided that this entire notice appears in all copies of the software, derivative works and supporting documentation. Further, UCAR requests that the user credit UCAR/Unidata in any publications that result from the use of this software or in any product that includes this software, although this is not an obligation. The names UCAR and/or Unidata, however, may not be used in any advertising or publicity to endorse or promote any products or commercial entity unless specific written permission is obtained from UCAR/Unidata. The user also understands that UCAR/Unidata is not obligated to provide the user with any support, consulting, training or assistance of any kind with regard to the use, operation and performance of this software nor to provide the user with any updates, revisions, new versions or "bug fixes."

THIS SOFTWARE IS PROVIDED BY UCAR/UNIDATA "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL UCAR/UNIDATA BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE ACCESS, USE OR PERFORMANCE OF THIS SOFTWARE.

Table of Contents

1	Synopsis	1
2	What's a Unit Package Good For?	5
3	Unit-Systems 3.1 Obtaining a Unit-System 3.2 Extracting Units from a Unit-System 3.3 Adding Units to a Unit-System 3.4 Adding Unit-Prefixes to a Unit-System 3.5 Miscelaneous Operations on Unit-Systems	. 6 . 7 . 8 . 9
4	Converting Values Between Units	11
5	Parsing a String into a Unit	13
6 7	6.1 Unit Specification Examples	14 14
8		19
9	9.1 Names	25 26
10	G	
1	1 Error Handling 11.1 Status of Last Operation 11.2 Error-Messages	29
1:	2 The Units Database	31
1	3 Data Types	32
Τı	ndev	33

1 Synopsis

Coding:

```
#include <udunits2.h>
      ut_system*
                                  ut_read_xml (const char* path);
      ut_system*
                                  ut_new_system(void);
      voi d
                                 ut_free_system(ut_system* sys-
                                 tem);
                                  ut_get_system(const ut_unit* unit);
      ut_system*
      ut unit*
                                 ut_get_dimensionless_unit_one(const ut_system* sys-
                                 tem);
      ut_uni t*
                                  ut_get_unit_by_name(const ut_system* sys-
                                 tem, const char* name);
      ut_uni t*
                                 ut_get_unit_by_symbol(const ut_system* sys-
                                 tem, const char* symbol);
                                  ut_set_second(const ut_unit* sec-
      ut_status
                                ond);
                                  ut_add_name_prefix(ut_system* sys-
      ut status
                                 tem, const char* name, double value);
                                  ut_add_symbol_prefix(ut_system* sys-
      ut status
                                tem, const char* symbol, double value);
      ut_uni t*
                                 ut_new_base_unit(ut_system* sys-
                                 tem);
      ut_unit*
                                 ut new dimensionless unit(ut system* sys-
                                 tem);
                                  ut_clone(const ut_unit* unit);
      ut_uni t*
      voi d
                                  ut_free(ut_unit* unit);
                                 ut_get_name(const ut_unit* unit, ut_encoding en-
      const char*
                                 coding);
```

ut_status	<pre>ut_map_name_to_unit(const char* name, const ut_encodi coding, const ut_unit* unit);</pre>
ut_status	<pre>ut_unmap_name_to_unit(ut_system* sys- tem, const char* name, const ut_encoding en- coding);</pre>
ut_status	<pre>ut_map_unit_to_name(const ut_unit* unit, const char* coding);</pre>
ut_status	<pre>ut_unmap_unit_to_name(const ut_unit* unit, ut_encodin coding);</pre>
const char*	<pre>ut_get_symbol(const ut_unit* unit, ut_encoding en- coding);</pre>
ut_status	ut_map_symbol_to_unit(const char* sym- bol, const ut_encoding encoding, const ut_unit* unit);
ut_status	<pre>ut_unmap_symbol_to_unit(ut_system* sys- tem, const char* symbol, const ut_encoding en- coding);</pre>
ut_status	<pre>ut_map_unit_to_symbol(const ut_unit* unit, const char bol, ut_encoding encoding);</pre>
ut_status	<pre>ut_unmap_unit_to_symbol(const ut_unit* unit, ut_encod coding);</pre>
int	ut_is_dimensionless(const ut_unit* unit);
int	ut_same_system(const ut_unit* unit1, const ut_unit* u
int	ut_compare(const ut_unit* unit1, const ut_unit* unit2
int	ut_are_convertible(const ut_unit* unit1, const ut_uni
cv_converter*	ut_get_converter(ut_unit* from, ut_unit* to);
ut_uni t*	<pre>ut_scale(double factor, const ut_unit* unit);</pre>
ut_uni t*	<pre>ut_offset(const ut_unit* unit, dou- ble offset);</pre>

voi d

ut_uni t*	<pre>ut_offset_by_time(const ut_unit* unit, dou- ble origin);</pre>
ut_uni t*	ut_multiply(const ut_unit* unit1, const ut_unit* unit
ut_uni t*	ut_invert(const ut_unit* unit);
ut_uni t*	<pre>ut_divide(const ut_unit* numer, const ut_unit* de- nom);</pre>
ut_uni t*	ut_raise(const ut_unit* unit, int power);
ut_uni t*	ut_root(const ut_unit* unit, int root);
ut_uni t*	<pre>ut_log(double base, const ut_unit* ref- erence);</pre>
ut_uni t*	<pre>ut_parse(const ut_system* sys- tem, const char* string, ut_encoding en- coding);</pre>
char*	<pre>ut_trim(char* string, ut_encoding en- coding);</pre>
int	ut_format(const ut_unit* unit, char* buf, size_t size signed opts);
ut_status	<pre>ut_accept_visitor(const ut_unit* unit, const ut_visit itor, void* arg);</pre>
doubl e	<pre>ut_encode_date(int year, int month, int day);</pre>
doubl e	<pre>ut_encode_clock(int hours, int min- utes, double seconds);</pre>
doubl e	<pre>ut_encode_time(int year, int month, int day, int hou: ble second);</pre>
void	<pre>ut_decode_time(double value, int* year, int* month, i ble* second, double* resolution);</pre>
ut_status	ut_get_status(void);

ut_set_status(ut_status status);

Linking:

c89 ... -Llibdir - Ludunits2 - Lexpat ... - Lm

Where *libdir* is the installation-directory for object code libraries (e.g., /usr/local/lib).

```
ut_handle_error_message(const char* fmt, ...);
           int
           ut_error_message_handler
                                       ut_set_error_message_handler(ut_error_message_handler
                                      dler);
           int
                                       ut_write_to_stderr(const char* fmt, va_list args);
                                       ut_ignore(const char* fmt, va_list args);
           int
           float
                                       cv_convert_float(const cv_converter* con-
                                      verter, float value);
                                       cv_convert_double(const cv_converter* con-
           doubl e
                                      verter, double value);
                                       cv_convert_floats(const cv_converter* con-
           float*
                                      verter, const float* in, Size_t count, float* out);
           double*
                                      cv_convert_doubles(const cv_converter* con-
                                      verter, const double* const in, size_t count, dou-
                                      ble* out);
                                       cv_free(cv_converter* conv);
           voi d
  Compiling:
     c89 - I includedir ...
  Where includedir is the installation-directory for C header files (e.g.,
/usr/local/include).
```

2 What's a Unit Package Good For?

The existance of a software package is justified by what you can do with it. The three main things you can do with the UDUNIT-2 package are

- 1. Chapter 4 [Value Conversion], page 11.
- 2. Convert a string representation of a unit into a binary one enabling the programatic manipulation of units. There are three ways to do this:
 - Section 3.2 [Extracting], page 7 from a [unit-system], page 5. This requires that you know the unit's name or symbol and that the unit is in a unit-system.
 - Chapter 5 [Parsing], page 13. This requires that the string be parsable by [ut_parse()], page 13.
 - Chapter 8 [Operations], page 19.
- 3. Chapter 7 [Formatting], page 18 enabling the printing and storing of units in a human-readable form.

While the above might seem to be trivial activities, their general availability at the time might have helped prevent the Mars Climate Orbiter fiasco.

3 Unit-Systems

A unit-system is a set of units that are all defined in terms of the same set of base units. In the SI system of units, for example, the base units are the meter, kilogram, second, ampere, kelvin, mole, and candela. (For definitions of these base units, see http://physics.nist.gov/cuu/Units/current.html.)

In the UDUNITS-2 package, every accessible unit belongs to one and only one unitsystem. It is not possible to convert numeric values between units of different unit-systems. Similarly, units belonging to different unit-systems always compare unequal.

There are several categories of operations on unit-systems:

3.1 Obtaining a Unit-System

Typically, you would obtain a unit-system of predefined units by reading the default unit database using [ut_read_xml()], page 6 with a NULL pathname argument. If this doesn't quite match your needs, then there are alternatives. Together with the typical solution, the means for obtaining a useful unit-system are (in order of increasing difficulty):

- Obtain the default unit-system using [ut_read_xml()], page 6(NULL).
- Copy and customize the unit database and then call [ut_read_xml()], page 6 with the pathname of the customized database to obtain a customized unit-system.
- Same as either of the above but then adding new units to the unit-system using [ut_new_base_unit()], page 8 and [ut_new_dimensionless_unit()], page 8.
- Same as the above but also deriving new units using Chapter 8 [Operations], page 19 and then adding them to the unit-system using Chapter 9 [Mapping], page 25.
- Same as the above but starting with an empty unit-system obtained from [ut_new_system()], page 7, in which case you will definitely have to start with [ut_new_base_unit()], page 8 and [ut_new_dimensionless_unit()], page 8.

You should pass every unit-system pointer to [ut_free_system()], page 9 when you no longer need the corresponding unit-system.

ut_system* ut_read_xml (const char* path)

[Function]

Reads the XML-formatted unit-database specified by *path* and returns the corresponding unit-sytem. If *path* is NULL, then the pathname specified by the environment variable UDUNITS2_XML_PATH is used if set; otherwise, the compile-time pathname of the installed, default, unit database is used. You should pass the returned pointer to ut_free_system() when you no longer need the unit-system. If an error occurs, then this function writes an error-message using [ut_handle_error_message()], page 30 and returns NULL. Also, [ut_get_status()], page 29 will return one of the following:

UT_OPEN_ARG

path is non-NULL but the file couldn't be opened. See errno for the reason

UT_OPEN_ENV

path is NULL and environment variable UDUNITS2_XML_PATH is set but the file couldn't be opened. See errno for the reason.

UT OPEN DEFAULT

path is NULL, environment variable UDUNITS2_XML_PATH is unset, and the installed, default, unit database couldn't be opened. See errno for the reason.

UT_0S Operating-system error. See errno.

UT_PARSE The database file couldn't be parsed.

ut_system* ut_new_system (void)

[Function]

Creates and returns a new unit-system. On success, the unit-system will be empty except for the dimensionless unit one. You should pass the returned pointer to ut_free_system() when you no longer need the unit-system. If an error occurs, then this function writes an error-message using [ut_handle_error_message()], page 30 and returns NULL. Also, [ut_get_status()], page 29 will return the following:

UT_OS Operating-system error. See errno.

3.2 Extracting Units from a Unit-System

NOTE: This section covers low-level access to the indidual units of a [unit-system], page 5. General parsing of arbitrary unit specifications is coverted in the section Chapter 5 [Parsing], page 13.

A [unit-system], page 5 contains mappings from identifiers to units (and vice versa). Consequently, once you have a unit-system, you can easily obtain a unit for which you know the name or symbol using the function [ut_get_unit_by_name()], page 7 or [ut_get_unit_by_symbol()], page 7.

Returns the unit to which name maps from the unit-system referenced by system or NULL if no such unit exists. Name comparisons are case-insensitive. If this function returns NULL, then [ut_get_status()], page 29 will return one of the following:

UT_SUCCESS

name doesn't map to a unit of system.

UT_BAD_ARG

system or name is NULL.

```
ut_unit* ut_get_unit_by_symbol (const ut_system* system, [Function] const char* symbol)
```

Returns the unit to which *symbol* maps from the unit-system referenced by *system* or NULL if no such unit exists. Symbol comparisons are case-sensitive. If this function returns NULL, then [ut_get_status()], page 29 will return one of the following:

UT SUCCESS

symbol doesn't map to a unit of system.

UT BAD ARG

system or symbol is NULL.

[Function]

Returns the dimensionless unit one of the unit-system referenced by *system*. While not necessary, the returned pointer may be passed to ut_free() when you no longer need the unit. If *system* is NULL, then this function writes an error-message using [ut_handle_error_message()], page 30 and returns NULL. Also, [ut_get_status()], page 29 will return UT_BAD_ARG.

3.3 Adding Units to a Unit-System

If you use [ut_read_xml()], page 6, then you should not normally need to add any new units to a unit-system.

Because you get units via their names or symbols, adding a unit to a unit-system actually means mapping one or more identifiers (i.e., names or symbols) to the unit. Thereafter, you can use [ut_get_unit_by_name()], page 7 and [ut_get_unit_by_symbol()], page 7 to retrieve the unit. The mapping of identifiers to units is covered Chapter 9 [Mapping], page 25.

Having said that, it is possible to create a new base or dimensionless unit within a unit-system using [ut_new_base_unit()], page 8 or [ut_new_dimensionless_unit()], page 8—you'll just also have to map identifiers to the newly-created unit in order to be able to retrieve it later by identifier.

ut_unit* ut_new_base_unit (ut_system* system)

Creates and adds a new base-unit to the unit-system referenced by system. This function returns the new base-unit. You should pass the returned pointer to ut_free() when you no longer need the unit. If an error occurs, then this function writes an error-message using [ut_handle_error_message()], page 30 and returns NULL. Also, [ut_get_status()], page 29 will return one of the following:

UT BAD ARG

system is NULL.

UT_OS Operating-system failure. See errno.

If you use [ut_read_xml()], page 6, then you should not normally need to call this function.

ut_unit* ut_new_dimensionless_unit (ut_system* system) [Function]
Creates and adds a new dimensionless-unit to the unit-system referenced by system. This function returns the new dimensionless-unit. You should pass the returned pointer to ut_free() when you no longer need the unit. If an error occurs, then this function writes an error-message using [ut_handle_error_message()], page 30 and returns NULL. Also, [ut_get_status()], page 29 will return one of the following:

UT BAD ARG

system is NULL.

UT_OS Operating-system failure. See errno.

If you use [ut_read_xml()], page 6, then you should not normally need to call this function.

[Function]

3.4 Adding Unit-Prefixes to a Unit-System

A prefix is a word or symbol that is appended to the beginning of a word or symbol that represents a unit in order to modify the value of that unit. For example, the prefix "kilo" in the word "kiloamperes" changes the value from one ampere to one-thousand amperes.

If you use [ut_read_xml()], page 6, then you should not normally need to add any new prefixes to a unit-system.

Adds the name-prefix name with the value value to the unit-system system. A name-prefix is something like "mega" or "milli". Comparisons between name-prefixes are case-insensitive. This function returns one of the following:

UT_SUCCESS

Success.

UT BAD ARG

system or name is NULL, or value is 0.

UT EXISTS

name already maps to a different value.

UT_OS Operating-system failure. See errno.

Adds the symbol-prefix *symbol* with the value value to the unit-system *system*. A symbol-prefix is something like "M" or "m". Comparisons between symbol-prefixes are case-sensitive. This function returns one of the following:

UT_SUCCESS

Success.

UT_BAD_ARG

system or symbol is NULL, or value is 0.

UT_EXISTS

symbol already maps to a different value.

UT_OS Operating-system failure. See errno.

3.5 Miscelaneous Operations on Unit-Systems

```
void ut_free_system (ut_system* system)
```

Frees the unit-system referenced by *system*. All unit-to-identifier and identifier-to-unit mappings are removed. Use of system after this function returns results in undefined behavior.

[ut_status], page 29 ut_set_second (const ut_unit* second) [Function]
 Sets the "second" unit of a unit-system. This function must be called before the
 first call to ut_offset_by_time() for a unit in the same unit-system. [ut_read_
 xml()], page 6 calls this function if the unit-system it's reading contains a unit
 named "second". This function returns one of the following:

UT_SUCCESS

The "second" unit of system was successfully set.

UT_EXI STS

The "second" unit of system is set to a different unit.

UT_BAD_ARG

second is NULL.

4 Converting Values Between Units

You can convert numeric values in one unit to equivalent values in another, compatible unit by means of a converter. For example

```
#include <udunits2.h>
...

ut_unit* from = ...;
ut_unit* to = ...;
cv_converter* converter = ut_get_converter(from, to);
double fromValue = ...;
double toValue = cv_convert_double(converter, fromValue);

cv_free(converter);
```

The converter API is declared in the header-file <converter. h>, which is automatically included by the UDUNITS-2 header-file (<uduni ts2. h>) so you don't need to explicitly include it.

Indicates if numeric values in unit unit1 are convertible to numeric values in unit unit2 via [ut_get_converter()], page 11. In making this determination, dimensionless units are ignored. This function returns a non-zero value if conversion is possible; otherwise, 0 is returned and [ut_get_status()], page 29 will return one of the following:

```
UT BAD ARG
```

unit1 or unit2 is NULL.

```
UT NOT SAME SYSTEM
```

unit1 and unit2 belong to different [unit-system], page 5s.

UT SUCCESS

Conversion between the units is not possible (e.g., *unit1* refers to a meter and *unit2* refers to a kilogram.

Creates and returns a converter of numeric values in the *from* unit to equivalent values in the *to* unit. You should pass the returned pointer to CV_free() when you no longer need the converter. If an error occurs, then this function writes an error-message using [ut_handle_error_message()], page 30 and returns NULL. Also, [ut_get_status()], page 29 will return one of the following:

```
UT_BAD_ARG
```

from or to is NULL.

```
UT NOT SAME SYSTEM
```

The units from and to don't belong to the same unit-system.

UT_MEANI NGLESS

The units belong to the same unit-system but conversion between them is meaningless (e.g., conversion between seconds and kilograms is meaningless).

UT_OS Operating-system failure. See errno.

float cv_convert_float (const cv_converter* converter, const float value) [Function]

Converts the single floating-point value value and returns the new value.

Converts the single double-precision value value and returns the new value.

float* cv_convert_floats (const cv_converter* converter, const float* in, size_t count, float* out) [Function]

Converts the *count* floating-point values starting at *in*, writing the new values starting at *out* and, as a convenience, returns *out*. The input and output arrays may overlap or be identical.

Converts the *count* double-precision values starting at *in*, writing the new values starting at *out* and, as a convenience, returns *out*. The input and output arrays may overlap or be identical.

Void cv_free (cv_converter* conv); [Function]

Frees resources associated with the converter referenced by conv. You should call this function when you no longer need the converter. Use of conv upon return results in undefined behavior.

5 Parsing a String into a Unit

```
Here's an example of parsing a string representation of a unit into its binary representation:
```

```
#include <stdlib.h>
#include <udunits2.h>
...

ut_system* unitSystem = [ut_read_xml()], page 6;
const char* string = "kg.m2/s3";
ut_unit* watt = [ut_parse()], page 13(unitSystem, string, UT_ASCII);

if (watt == NULL) {
    /* Unable to parse string. */
}
else {
    /* Life is good. */
}
```

Returns the binary unit representation corresponding to the string unit representation string in the character-set encoding using the unit-system system. string must have no leading or trailing whitespace (see [ut_trim()], page 13). If an error occurs, then this function returns NULL and [ut_get_status()], page 29 will return one of the following:

```
\begin{tabular}{ll} {\tt UT\_BAD\_ARG} \\ & system \ {\tt or} \ string \ {\tt is} \ {\tt NULL}. \\ \\ {\tt UT\_SYNTAX} \end{tabular}
```

string contained a syntax error.

UT_UNKNOWN

string contained an unknown identifier.

UT_OS Operating-system failure. See errno for the reason.

```
Size_t ut_trim (char* string, ut_encoding encoding) [Function]
Removes all leading and trailing whitespace from the NUL-terminated string string.
Returns string, which is modified if it contained leading or trailing whitespace.
```

6 Unit Syntax

For the most part, the UDUNITS-2 package follows the syntax for unit-strings promulgated by the US National Institute for Standards and Technology (NIST). Details, of which, can be found at http://physics.nist.gov/cuu/Units/index.html. The one general exception to this is the invention of a syntax for "offset"-units (e.g., the definition of the degree Celsius is "K @ 273.15").

6.1 Unit Specification Examples

String Type	Using Names	$egin{aligned} ext{Using} \ ext{Symbols} \end{aligned}$	Comment
Simple	meter	m	
Raised	meter ²	m2	higher precedence than multiplying or dividing
Product	newton meter	N.m	
Quotient	meter per second	m/s	
Scaled	60 second	60 s	
Prefixed	kilometer	km	
Offset	kelvin from 273.15	$\mathbf{K} @ 273.15$	lower precedence than multiplying or dividing
Logarithmic	lg(re milliwatt)	$\lg(\text{re mW})$	"lg" is base 10, "ln" is base e, and "lb" is base 2
Grouped	(5 meter)/(30 second)	(5 m)/(30	
		s)	

The above may be combined, e.g., "0.1 $\lg(\text{re m}/(5 \text{ s})^2) @ 50$ ".

You may also look at the <def> elements in Chapter 12 [Database], page 31 to see examples of string unit specifications.

You may use the $\langle undefined \rangle$ [udunits2], page $\langle undefined \rangle$ utility to experiment with string unit specifications.

6.2 Unit Grammar

Here is the unit-syntax understood by the UDUNITS-2 package. Words printed *Thusly* indicate non-terminals; words printed THUSLY indicate terminals; and words printed <thusly>indicate lexical elements.

```
Unit-Spec: one of
nothing
Shift-Spec

Shift-Spec: one of
Product-Spec
Product-Spec SHIFT REAL
Product-Spec SHIFT INT
Product-Spec SHIFT Timestamp

Product-Spec: one of
Power-Spec
Product-Spec Power-Spec
```

```
Product-Spec MULTIPLY Power-Spec
        Product-Spec DIVIDE Power-Spec
Power-Spec: one of
        Basic-Spec
        Basic-Spec INT
        Basic-Spec EXPONENT
        Basic-Spec RAISE INT
Basic-Spec: one of
        "(" Shift-Spec ")"
       LOGREF Product_Spec ")"
        Number
Number: one of
        INT
        REAL
Timestamp: one of
        DATE
        DATE CLOCK
        DATE CLOCK CLOCK
        DATE CLOCK INT
        DATE CLOCK ID
        TIMESTAMP
        TIMESTAMP INT
        TIMESTAMP ID
SHIFT:
        <space>* <shi ft_op> <space>*
<shift_op>: one of
        "@"
        "after"
        "from"
        "since"
        "ref"
REAL:
        the usual floating-point format
INT:
        the usual integer format
MULTIPLY: one of
```

```
"."
        II * II
        <space>+
        <centered middot>
DI VI DE:
        <space>* <di vi de_op> <space>*
<divide_op>: one of
        per
        PER
        "/"
EXPONENT:
        ISO-8859-9 or UTF-8 encoded exponent characters
RAISE: one of
        11 * * 11
ID: one of
        <i d>
        n i n
        "\""
        degree sign
        greek mu character
<i d>:
        <al pha> <al phanum>*
<al pha>:
        [A-Za-z_]
        ISO-8859-1 alphabetic characters
        non-breaking space
<al phanum>: one of
        <al pha>
        <di gi t>
<digit>:
        [0-9]
LOGREF:
        <log> <space>* <logref>
<log>: one of
```

```
" l og"
" l g"
" l n"
<logref>:
    "(" <space>* <re> ":"? <space>*
DATE:
        <year> "-" <month> ("-" <day>)?
<year>:
         [+-]?[0-9]{1,4}
<month>:
        "0"?[1-9]|1[0-2]
<day>:
        "0"?[1-9]|[1-2][0-9]|"30"|"31"
CLOCK:
        <hour> ":" <mi nute> (":" <second>)?
TIMSTAMP:
        <year> (<month> <day>?)? "T" <hour> (<mi nute> <second>?)?
<hour>:
         [+-]?[0-1]?[0-9]|2[0-3]
<mi nute>:
         [0-5]?[0-9]
<second>:
         (< mi nute > | 60) (\. [0-9]*)?
```

7 Formatting a Unit into a String

Use the [ut_format()], page 18 function to obtain the string representation of a binary unit. For example, the following gets the definition of the unit "watt" in ASCII characters using unit-symbols rather than unit-names:

```
ut_unit* watt = ...;
char buf[128];
unsigned opts = [ut_encoding], page 32 | UT_DEFINITION;
int len = [ut_format()], page 18(watt, buf, sizeof(buf), opts);

if (len == -1) {
    /* Couldn't get string */
}
else if (len == sizeof(buf)) {
    /* Entire buffer used: no terminating NUL */
}
else {
    /* Have string with terminating NUL */
}
```

Formats the unit *unit* (i.e., returns its string representation) into the buffer pointed-to by *buf* of size *size*. The argument *opts* specifies how the formatting is to be done and is a bitwise OR of a [ut_encoding], page 32 value and zero or more of the following:

UT_NAMES Use unit names instead of symbols.

UT DEFINITION

The formatted string should be the definition of *unit* in terms of basic-units instead of stopping any expansion at the highest level possible.

On success, this function returns either the number of bytes – excluding the terminating NUL – that were written into buf or the number of bytes that would have been written. The difference is due to the runtime Snprinf() function that was used.

On failure, this function returns -1 and [ut_get_status()], page 29 will return one of the following:

UT BAD ARG

unit or buf is NULL, or opts contains the bit patterns of both <code>UT_LATIN1</code> and <code>UT_UTF8</code>.

UT_CANT_FORMAT

unit can't be formatted in the desired manner (e.g., opts contains UT_ASCII but unit doesn't have an identifier in that character-set or opts doesn't contain UT_NAMES and a necessary symbol doesn't exist).

8 Unit Operations

You can use unit operations to construct new units, get information about units, or compare units.

8.1 Unary Unit Operations

```
void ut_free (ut_unit* unit)
```

[Function]

Frees resources associated with *unit*. You should invoke this function on every unit that you no longer need. Use of *unit* upon return from this function results in undefined behavior.

ut_unit* ut_scale (double factor, const ut_unit* unit) [Function]
Returns a unit equivalent to another unit scaled by a numeric factor. For example:

```
const ut_unit* meter = ...
const ut_unit* kilometer = ut_scale(1000, meter);
```

The returned unit is equivalent to *unit* multiplied by *factor*. You should pass the returned pointer to [ut_free()], page 19 when you no longer need the unit.

ut_unit* ut_offset (const ut_unit* unit, double offset) [Function]

Returns a unit equivalent to another unit relative to a particular origin. For example:

```
const ut_unit* kelvin = ...
const ut_unit* celsius = ut_offset(kelvin, 273.15);
```

The returned unit is equivalent to *unit* with an origin of *offset*. You should pass the returned pointer to [ut_free()], page 19 when you no longer need the unit. If an error occurs, then this function returns NULL and [ut_get_status()], page 29 will return one of the following:

```
UT_BAD_ARG
```

unit is NULL.

UT OS Operating-system error. See errno for the reason.

Returns a timestamp-unit equivalent to the time unit *unit* referenced to the time-origin *origin* (as returned by [ut_encode_time()], page 28). For example:

```
const ut_unit* second = ...
const ut_unit* secondsSinceTheEpoch =
   ut_offset_by_time(second, ut_encode_time(1970, 1, 1, 0, 0, 0.0));
```

Leap seconds are not taken into account. You should pass the returned pointer to [ut_free()], page 19 when you no longer need the unit. If an error occurs, then this function returns NULL and [ut_get_status()], page 29 will return one of the following:

```
UT BAD ARG
```

unit is NULL.

UT_OS Operating-system error. See errno for the reason.

UT_MEANINGLESS

Creation of a timestamp unit based on *unit* is not meaningful. It might not be a time-unit, for example.

UT_NO_SECOND

The associated unit-system doesn't contain a "second" unit. See [ut_set_second()], page 9.

CAUTION: The timestamp-unit was created to be analogous to, for example, the degree celsius—but for the time dimension. I've come to believe, however, that creating such a unit was a mistake, primarily because users try to use the unit in ways for which it was not designed (such as converting dates in a calendar whose year is exactly 365 days long). Such activities are much better handled by a dedicated calendar package. Please be careful about using timestamp-units. See also the section on Chapter 10 [Time], page 28.

ut_unit* ut_invert (const ut_unit* unit)

[Function]

Returns the inverse (i.e., reciprocal) of the unit *unit*. This convenience function is equal to [ut_raise()], page 20. You should pass the returned pointer to [ut_free()], page 19 when you no longer need the unit. If an error occurs, then this function writes an error-message using [ut_handle_error_message()], page 30 and returns NULL. Also, [ut_get_status()], page 29 will return one of the following:

UT BAD ARG

unit is NULL.

UT_OS Operating-system error. See errno for the reason.

ut_unit* ut_raise (const ut_unit* unit, int power)

[Function]

Returns the unit equal to unit *unit* raised to the power *power*. You should pass the returned pointer to ut_free() when you no longer need the unit. If an error occurs, then this function writes an error-message using [ut_handle_error_message()], page 30 and returns NULL. Also, [ut_get_status()], page 29 will return one of the following:

UT_BAD_ARG

unit is NULL.

UT_OS Operating-system error. See errno for the reason.

ut_unit* ut_root (const ut_unit* unit, int root)

[Function]

Returns the unit equal to the *root* root of unit *unit*. You should pass the returned pointer to ut_free() when you no longer need the unit. If an error occurs, then this function writes an error-message using [ut_handle_error_message()], page 30 and returns NULL. Also, [ut_get_status()], page 29 will return one of the following:

UT BAD ARG

unit is NULL.

UT_MEANINGLESS

It's meaningless to take the given root of the given unit. This could be because the resulting unit would have fractional (i.e., non-integral) dimensionality, or because the unit is, for example, a logarithmic unit.

UT_OS Operating-system error. See errno for the reason.

ut_unit* ut_log (double base, const ut_unit* reference) [Function]

Returns the logarithmic unit corresponding to the logarithmic base base and a reference level specified as the unit reference. For example, the following creates a decibel unit with a one milliwatt reference level:

You should pass the returned pointer to ut_free() when you no longer need the unit. If an error occurs, then this function writes an error-message using [ut_handle_error_message()], page 30 and returns NULL. Also, [ut_get_status()], page 29 will return one of the following:

UT_BAD_ARG

reference is NULL.

UT_OS Operating-system error. See errno for the reason.

UT BAD ARG

base is invalid (e.g., it must be greater than one).

Returns the name to which the unit referenced by *unit* maps in the character-encoding specified by *encoding*. If this function returns NULL, then [ut_get_status()], page 29 will return one of the following:

UT_BAD_ARG

name is NULL.

UT SUCCESS

unit doesn't map to a name in the given character-set.

Returns the symbol to which the unit referenced by *unit* maps in the character-encoding specified by *encoding*. If this function returns NULL, then [ut_get_status()], page 29 will return one of the following:

UT_BAD_ARG

symbol is NULL.

UT SUCCESS

unit doesn't map to a symbol in the given character-set.

ut_system* ut_get_system (const ut_uni t* unit)

[Function]

Returns the unit-system to which the unit referenced by *unit* belongs. If *unit* is NULL, then this function writes an error-message using [ut_handle_error_message()], page 30 and returns NULL. Also, [ut_get_status()], page 29 will return UT_BAD_ARG.

int ut_is_dimensionless (const ut_unit* unit)

[Function]

Indicates if unit *unit* is dimensionless (like "radian"). This function returns a non-zero value if the unit is dimensionfull; otherwise, 0 is returned and [ut_get_status()], page 29 will return one of the following:

UT BAD ARG

unit1 is NULL.

UT SUCCESS

The unit is dimensionless.

ut unit* ut clone (const ut unit* unit)

[Function]

Returns a copy of the unit referenced by *unit*. You should pass the returned pointer to ut_free() when you no longer need the unit. If an error occurs, then this function writes an error-message using [ut_handle_error_message()], page 30 and returns NULL. Also, [ut_get_status()], page 29 will return one of the following:

UT_BAD_ARG

unit is NULL.

UT_OS Operating-system failure. See errno.

If you use [ut_read_xml()], page 6, then you should not normally need to call this function.

Accepts the visitor visitor to the unit unit. The argument arg is passed to the visitor's functions. This function returns one of the following:

UT_BAD_ARG

visitor or unit is NULL.

UT VISIT ERROR

An error occurred in visitor while visiting unit.

UT_SUCCESS

Success.

ut_vi si tor int foo(int) int bar(int, int)

[Data type]

You pass a pointer to a data object of this type if and when you call [ut_accept_visitor()], page 22. It contains the following pointers to functions that implement your unit-visitor:

[ut_status], page 29 (*visit_basic)(const ut_unit* unit, void* arg);

Visits the basic-unit *unit*. A basic-unit is a base unit like "meter" or a non-dimensional but named unit like "radian". This function returns [ut_status], page 29 on and only on success.

[ut_status], page 29 (*visit_product)(const ut_unit* unit, int count, const ut_unit* const* basicUnits, const int* powers, void* arg);

Visits the product-unit *unit*. The product-unit is a product of the *count* basic-units referenced by *basicUnits*, each raised to their respective, nonzero power in *powers*. This function returns [ut_status], page 29 on and only on success.

[ut_status], page 29 (*visit_galilean)(const ut_unit* unit, double scale, const ut_unit* underlyingUnit, double origin, void* arg);

Visits the Galilean-unit unit. The Galilean-unit has the underlying unit underlyingUnit and either the non-unity scale factor scale or the non-zero origin origin, o(091 08xig[(n)+550 (T628)-372 (function)-372 (re3urns)]TJET1 0 0 1 393.977 4

UT BAD ARG

unit1 or unit2 is NULL.

UT NOT SAME SYSTEM

unit1 and unit2 belong to different [unit-system], page 5s.

UT_OS Operating-system error. See errno for the reason.

Returns the result of dividing unit *numer* by unit *denom*. You should pass the pointer to [ut_free()], page 19 when you no longer need the unit On failure, this function returns NULL and [ut_get_status()], page 29 will return one of the following:

UT_BAD_ARG

numer or denom is NULL.

UT NOT SAME SYSTEM

unit1 and unit2 belong to different [unit-system], page 5s.

UT OS Operating-system error. See errno for the reason.

Int ut_compare (const ut_unit* unit1, const ut_unit* unit2) [Function] Compares two units. Returns a value less than, equal to, or greater than zero as unit1 is considered less than, equal to, or greater than unit2, respectively. Units from different [unit-system], page 5s never compare equal. The value zero is also returned if both unit pointers are NULL.

Indicates if two units belong to the same unit-system. This function returns a non-zero value if the two units belong to the same [unit-system], page 5; otherwise, 0 is returned and [ut_get_status()], page 29 will return one of the following:

UT BAD ARG

unit1 or unit2 is NULL.

UT_SUCCESS

The units belong to different [unit-system], page 5s.

9 Mapping Between Identifiers and Units

Within a unit-system, you can map an identifier to a unit and vice versa. If an identifier maps to a unit, then the unit can be retrieved from the unit-system via the identifier. Similarly, if a unit maps to an identifier, then the unit can be printed using the identifier.

There a two kinds of identifiers: names and symbols.

9.1 Names

You can map a name to a unit and vice versa. If you use [ut_read_xml()], page 6, then you shouldn't normally need to do this.

Maps the name referenced by *name*, in character-set *encoding*, to the unit referenced by *unit* in the unit-system that contains *unit*. This function returns one of the following:

UT SUCCESS

Success.

UT BAD ARG

name or unit is NULL.

UT_OS Operating-system failure. See errno.

UT EXISTS

name already maps to a different unit.

Removes any mapping from name name, in character-set encoding, to a unit in unitsystem system. This function returns one of the following:

UT_SUCCESS

Success.

UT_BAD_ARG

system or name is NULL.

Maps the unit *unit* to the name *name*, which is in character-set *encoding*, in the unit-system that contains the unit. This function returns one of the following:

UT SUCCESS

Success.

UT BAD ARG

unit or name is NULL, or name is not in the character-set encoding.

UT_OS Operating-system failure. See errno.

UT_EXISTS

unit already maps to a different name.

Removes any mapping from unit *unit* to a name in character-set *encoding* from the unit-system that contains the unit. This function returns one of the following:

UT SUCCESS

Success.

UT BAD ARG

unit is NULL.

9.2 Symbols

You can map a symbol to a unit and vice versa. If you use [ut_read_xml()], page 6, then you shouldn't normally need to do this.

Maps the symbol referenced by *symbol*, in character-set *encoding*, to the unit referenced by *unit* in the unit-system that contains *unit*. This function returns one of the following:

UT_SUCCESS

Success.

UT BAD ARG

symbol or unit is NULL.

UT_OS Operating-system failure. See errno.

UT_EXISTS

symbol already maps to a different unit.

Removes any mapping from symbol symbol, in character-set encoding, to a unit in unit-system system. This function returns one of the following:

UT SUCCESS

Success.

UT_BAD_ARG

system or symbol is NULL.

Maps the unit *unit* to the symbol *symbol*, which is in character-set *encoding*, in the unit-system that contains the unit. This function returns one of the following:

UT SUCCESS

Success.

UT BAD ARG

unit or symbol is NULL.

UT_BAD_ARG

Symbol symbol is not in the character-set encoding.

UT_OS Operating-system failure. See errno.

UT_EXI STS

unit already maps to a different symbol.

[Function]

Removes any mapping from unit *unit* to a symbol in character-set *encoding* from the unit-system that contains the unit. This function returns one of the following:

UT_SUCCESS

Success.

UT_BAD_ARG

unit is NULL.

10 The Handling of Time

You should use a true calendar package rather than the UDUNITS-2 package to handle time. Having said that, many people use the time-handling capabilities of the UDUNITS-2 package because it supports "units" like "seconds since 1970-01-01". You should be aware, however, that the hybrid Gregorian/Julian calendar used by the UDUNITS-2 package cannot be changed. Dates on or after 1582-10-15 are assumed to be Gregorian dates; dates before that are assumed to be Julian dates. In particular, the year 1 BCE is immediately followed by the year 1 CE.

In general, the UDUNITS-2 package handles time by encoding it as double-precision value, which can then be acted upon arithmetically.

Encodes a time as a double-precision value. This convenience function is equivalent to

```
[ut_encode_date()], page 28(year, month, day) + [ut_encode_clock()],
page 28(hour, minute, second)
```

- double ut_encode_date (int year, int month, int day) [Function] Encodes a date as a double-precision value. You probably won't use this function. Dates on or after 1582-10-15 are assumed to be Gregorian dates; dates before that are assumed to be Julian dates. In particular, the year 1 BCE is immediately followed by the year 1 CE.
- double ut_encode_clock (int hour, int minute, double second) [Function] Encodes a clock-time as a double-precision value. You probably won't use this function

Decodes a time from a double-precision value into its individual components. The variable referenced by *resolution* will be set to the resolution (i.e., uncertainty) of the time in seconds.

11 Error Handling

Error-handling in the units module has two aspects: the status of the last operation performed by the module and the handling of error-messages:

11.1 Status of Last Operation

UDUNITS-2 functions set their status by calling [ut_set_status()], page 29. You can use the function [ut_get_status()], page 29 to retrieve that status.

[ut_status], page 29 ut_get_status (void) [Function]

Returns the value specified in the last call to [ut_set_status()], page 29

void ut_set_status ([ut_status], page 29 status) [Function] Set the status of the units module to status.

ut_status [Data type]

This enumeration has the following values:

UT SUCCESS

Success

UT BAD ARG

An argument violates the the function's contract (e.g., it's NULL).

UT_EXISTS

Unit, prefix, or identifier already exists

UT NO UNIT

No such unit exists

UT_OS Operating-system error. See errno for the reason.

UT_NOT_SAME_SYSTEM

The units belong to different unit-systems

UT_MEANINGLESS

The operation on the unit or units is meaningless

UT_NO_SECOND

The unit-system doesn't have a unit named "second"

UT_VISIT_ERROR

An error occurred while visiting a unit

UT CANT FORMAT

A unit can't be formatted in the desired manner

UT_SYNTAX

String unit representation contains syntax error

UT_UNKNOWN

String unit representation contains unknown word

UT OPEN ARG

Can't open argument-specified unit database

UT OPEN ENV

Can't open environment-specified unit database

UT OPEN DEFAULT

Can't open installed, default, unit database

UT_PARSE Error parsing unit database

11.2 Error-Messages

int ut_handle_error_message (const char* fmt, ...)

[Function]

Handles the error-message corresponding to the format-string fmt and any subsequent arguments referenced by it. The interpretation of the formatting-string is identical to that of the UNIX function printf(). On success, this function returns the number of bytes in the error-message; otherwise, this function returns -1.

Use the function [ut_set_error_message_handler()], page 30 to change how error-messages are handled.

[ut_error_message_handler], page 30

[Function]

ut_set_error_message_handler ([ut_error_message_handler],
page 30 handler)

Sets the function that handles error-messages and returns the previous error-message handler. The initial error-message handler is [ut_write_to_stderr()], page 30.

int ut_write_to_stderr (const char* fmt, va_list args)

Function

Writes the variadic error-message corresponding to formatting-string *fmt* and arguments *args* to the standard-error stream and appends a newline. The interpretation of the formatting-string is identical to that of the UNIX function printf(). On success, this function returns the number of bytes in the error-message; otherwise, this function returns -1.

int ut_ignore (const char* fmt, va_list args)

[Function]

Does nothing. In particular, it ignores the variadic error-message corresponding to formatting-string fmt and arguments args. Pass this function to [ut_set_error_message_handler()], page 30 when you don't want the unit module to print any error-messages.

ut_error_message_handler

[Data type]

This is the type of an error-message handler. It's definition is

typedef int (*ut_error_message_handler)(const char* fmt, va_list args);

12 The Units Database

The database of units that comes with the UDUNITS-2 package is an XML-formatted file that is based on the SI system of units. It contains the names and symbols of most of the units that you will ever encounter. The pathname of the installed file is <code>datadir/udunits2.xml</code>, where <code>datadir</code> is the installation-directory for read-only, architecture-independent data (e.g., /usr/local/share). This pathname is the default that <code>[ut_read_xml()]</code>, <code>page 6</code> uses.

Naturally, because the database is a regular file, it can be edited to add new units or remove existing ones. Be very careful about doing this, however, because you might lose the benefit of exchanging unit-based information with others who haven't modified their database.

13 Data Types

```
The data types [ut_visitor], page 23, [ut_status], page 29, and [ut_error_message_handler], page 30 are documented elsewhere.
```

ut_encodi ng
This enumeration has the following values:

UT_ASCII US ASCII character-set.

UT_IS0_8859_1
The ISO-8859-1 character-set.

UT_LATIN1
Synonym for UT_IS0_8859_1.

UT_UTF8 The UTF-8 encoding of the Unicode character-set.

Index 33

Index

A	0
adding prefixes to a unit-system	operations, unit
	P
В	parsing a string into a unit
base unit	prefixes, adding to a unit-system
	\mathbf{S}
\mathbf{C}	status of last operation
converting values between units 11 cv_convert_double 12 cv_convert_doubles 12 cv_convert_float 12 cv_convert_floats 12 cv_free 12	string, formatting a unit into a 18 string, parsing into a unit 13 symbols 26 synopsis 1 syntax, unit 14 system of units 6
	\mathbf{T}
D	time, handling of
data types	types, data
database, unit, obtaining predefined 6 database, units	\mathbf{U}
\mathbf{E}	unary unit operations
	unit conversion
error handling	unit grammar
examples, unit specification	unit operations
examples, unit specification	unit specification examples
_	unit syntax
\mathbf{F}	unit, adding to a unit-system 8
formatting a unit into a string	unit, base
0	unit, formatting into a string
	unit, getting by symbol
G	unit-system
getting a unit by its name	unit-system, adding a unit to
getting a unit by its symbol	unit-system, adding prefixes to a
grammar, unit	unit-system, obtaining predefined
	units, mapping to identifiers
\mathbf{M}	units, obtaining predefined 6
	ut_accept_visitor
mapping identifiers	ut_add_name_prefix 9
mapping units	${\tt ut_add_symbol_prefix} \dots 9$
messages, error	ut_are_convertible 11
1110 ctate 5000 cts	ut_clone
TN T	ut_compare 24 ut_decode_time 28
$\mathbf N$	ut_divide
names	ut_encode_clock
	ut_encode_date

Index 34

ut_encode_time	ut_new_base_unit 8
ut_encoding 32	ut_new_dimensionless_unit 8
ut_error_message_handler 30	ut_new_system 7
ut_format	ut_offset
ut_free	ut_offset_by_time
ut_free_system 9	ut_parse
ut_get_converter	ut_raise
ut_get_dimensionless_unit_one 8	ut_read_xml
ut_get_name	ut_read_xml(), discussion of
ut_get_status	ut_root
ut_get_symbol	ut_same_system
ut_get_system	ut_scale
ut_get_unit_by_name 7	ut_set_error_message_handler
ut_get_unit_by_symbol7	
ut_handle_error_message30	ut_set_second
ut_ignore 30	ut_set_status
ut_invert	ut_status
ut_is_dimensionless	ut_trim
ut_log	$\mathtt{ut_unmap_name_to_unit} \ldots 25$
ut_map_name_to_unit	ut_unmap_symbol_to_unit
ut_map_symbol_to_unit	ut_unmap_unit_to_name
ut_map_unit_to_name	ut_unmap_unit_to_symbol
ut_map_unit_to_symbol	ut_visitor
ut multiply	ut write to stderr