

# CCT College Dublin

## Assessment Cover Page

---

Module Title:	Strategy Thinking
Assessment Title:	Project Report
Lecturer Name:	James Garza
Student Full Name:	Giulio Calef, Kevin Byrne and Victor Ferreira Silva
Student Number:	sba22314, sba22264, 2021324
Assessment Due Date:	7th May 2023
Date of Submission:	7th May 2023

### Declaration

By submitting this assessment, I confirm that I have read the CCT policy on Academic Misconduct and understand the implications of submitting work that is not my own or does not appropriately reference material taken from a third party or other source. I declare it to be my own work and that all material from third parties has been appropriately referenced. I further confirm that this work has not previously been submitted for assessment by myself or someone else in CCT College Dublin or any other higher education institution.

# **Detection and Prediction Severe Slugging**

Strategic Thinking Capstone Project

**Giulio Calef  
Kevin Byrne  
Victor F Silva**

Strategic Thinking Capstone Project

Higher Diploma in Science in Artificial Intelligence Applications  
CCT College Dublin  
Ireland  
May 2023

# 1 Introduction

Introduction to be inserted here

## 1.1 Business Understanding

### 1.1.1 Hypothesis

Hypothesis here

### 1.1.2 General Goal

Goal here

### 1.1.3 Success criteria/indicators

Success criteria/indicators here

### 1.1.4 Selected Processes and Technologies

Libraries, Models and machine learning algorithms.

### 1.1.5 Accomplishments

- Extracted and prepared data from Petrobras 3W
- Two models with a very high accuracy (Random Forest and Decision Tree)

# 2 Data Understanding

Preprocessing a dataset through data characterisation involves summarising the features and characteristics present in the data using statistical measures and visualisations techniques such as bar charts and scatter plots. After this stage, it should be possible to identify biases, patterns, trends, and any missing or irrelevant data in the data set that may need to be addressed.

This dataset is composed by instances of eight types of undesirable events characterized by eight process variables from three different sources: real instances, simulated instances and hand-drawn instances. All real instances were taken from the plant information system that is used to monitor the industrial processes at an operational unit in Brazilian state of Espírito Santo. The simulated instances were all generated using <https://www.software.slb.com/products/olga>, a dynamic multiphase flow simulator that is widely used by oil companies worldwide (Andreolli, 2016). Finally, the hand-drawn instances were generated by a specific tool developed by Petrobras researchers for this dataset to incorporate undesirable events classified as rare.

Ultimately, only the data from the real instances were select for this project, as simulated data and hand-drawn instances did not present any record for two relevant features, namely Gas Lift Flow Rate and Pressure Variable Upstream Of the Gas Lift Choke.

## 2.1 Data Characterisation

The data consists of over 50 million observations, with 13 columns of data for each observation. The first column, label, indicates the event type for each observation. The second column, well, contains the name of the well the observation was taken from. Hand-drawn and simulated instances have fixed names for in this column, while real instances have names masked with incremental id. The third column, id, is an identifier for the observation and it is incremental for hand-drawn and simulated instances, while each real instance has an id generated from its first timestamp. The columns representing the process variables are:

- P-PDG: pressure variable at the Permanent Downhole Gauge (PDG) - installed on Christmas Tree;

- P-TPT: pressure variable at the Temperature and Pressure Transducer (TPT) - installed on Christmas Tree;
- T-TPT: temperature variable at the Temperature and Pressure Transducer (TPT);
- P-MON-CKP: pressure variable upstream of the production choke (CKP) - located on platform;
- T-JUS-CKP: temperature variable downstream of the production choke (CKP);
- P-JUS-CKGL: pressure variable upstream of the gas lift choke (CKGL);
- T-JUS-CKGL: temperature variable upstream of the gas lift choke (CKGL);
- QGL: gas lift flow rate;

The pressure features are measured in Pascal (Pa), the volumetric flow rate features are measured in standard cubic meters per second (SCM/s), and the temperature features are measured in degrees Celsius (°C).

Other information are also loaded into each pandas Dataframe:

- label: instance label (event type) - target variable;
- well: well name. Hand-drawn and simulated instances have fixed names (respectively, drawn and simulated. Real instances have names masked with incremental id;
- id: instance identifier. Hand-drawn and simulated instances have incremental id. Each real instance has an id generated from its first timestamp;
- class: Although it can be used to identify periods of normal operation, fault transients, and faulty steady states, which can help with diagnosis and maintenance, it is a category which results from label, which is our target here

The labels are:

- 0 - Normal Operation = Normal
- 1 - Abrupt Increase of BSW = AbrIncrBSW
- 2 - Spurious Closure of DHSV = SpurClosDHSW
- 3 - Severe Slugging = SevSlug
- 4 - Flow Instability = FlowInst
- 5 - Rapid Productivity Loss = RProdLoss
- 6 - Quick Restriction in PCK = QuiRestrPCK
- 7 - Scaling in PCK = ScalingPCK
- 8 - Hydrate in Production Line = HydrProdLine

In order to maintain the realistic aspects of the data, the dataset was built without preprocessing, including the presence of NaN values, frozen variables due to sensor or communication issues, instances with varying sizes, and outliers (R.E.V. Vargas, et al. 2019).

A concise summary of this data set generated by *pandas.DataFrame.info* method can be seen on Table 1.

## 2.2 Exploratory Data Analysis

A bar chart was generated displaying the percentage of present values in each column of the data frame - see Figure 1. It contained missing values in several columns, thus some columns and row were deleted in order to obtain accurate and reliable results.

Three boxplots were plotted to show how the data was distributed before any data cleaning - see Figure 2. They were divided according the feature measurement unit: the pressure features were measured in Pascal (Pa), the temperature features are measured in degrees Celsius (°C) and one feature about volumetric flow rate which was measured in standard cubic meters per second (SCM/s).

Column	pandas.Dtype
timestamp	datetime64[ns]
label	int64
well	object
id	int64
P-PDG	float64
P-TPT	float64
T-TPT	float64
P-MON-CKP	float64
T-JUS-CKP	float64
P-JUS-CKGL	float64
T-JUS-CKGL	float64
QGL	float64
class	float64
source	object

Table 1: Summary of the data set compiled from real instances




Figure 1: Proportion of available data per column, in %.




Figure 2: Box plots showing the distribution of pressure, temperature, and QGL (SCM/s) data for a set of oil wells.

### 3 Data Preparation

Data preparation included Data Cleaning, Feature Engineering, Train/Test Splitting and Handling Imbalanced Data, Data Scaling, and an analysis of the chosen approach regarding dimensionality reduction for some models.

#### 3.1 Data Cleaning

The missing data from the following columns were removed: class, P-PDG, P-TPT, T-JUS-CKP, P-MON-CKP, T-TPT, P-MON-CKP, QGL and P-JUS-CKGL. After this, the columns class, T-JUS-CKGL (an empty column), id, source were dropped. Column class is a column which brings more details about label. Consider that columns timestamp, label were kept at this stage. Finally all duplicates were removed.

```

1 # dropping rows with missing or null class column
2 df_clean = df.dropna(subset=[
3     'class', 'P-PDG', 'P-TPT', 'T-JUS-CKP', 'P-MON-CKP', 'T-TPT',
4     'P-MON-CKP', 'QGL', 'P-JUS-CKGL'
5 ])
6
7 # removing redundant columns
8 df_clean = df_clean.drop(['class', 'T-JUS-CKGL', 'id', 'source'], axis=1)
9
10 # checking duplicated rows after removing ids
11 df_clean = df_clean.drop_duplicates()
12
13 df_clean.info()

```

```

<class 'pandas.core.frame.DataFrame'>
Int64Index: 10003580 entries, 0 to 13952910
Data columns (total 10 columns):
#   Column      Dtype
---  -
0   timestamp   datetime64[ns]
1   label       int64
2   well        object
3   P-PDG       float64
4   P-TPT       float64
5   T-TPT       float64
6   P-MON-CKP   float64
7   T-JUS-CKP   float64
8   P-JUS-CKGL  float64

```




Figure 3: Box plots showing the distribution of pressure, temperature, and QGL (SCM/s) data without extreme outliers.

```

9    QGL          float64
dtypes: datetime64[ns](1), float64(7), int64(1), object(1)
memory usage: 839.5+ MB

```

Also, as it can be seen on Figure 2, features P-PDG and P-TPT had the presence of extreme outliers. These outliers were also removed with the following code:

```

1 # removing extreme outliers from P-PDG
2 Q1 = df_clean['P-PDG'].quantile(0.25)
3 Q3 = df_clean['P-PDG'].quantile(0.75)
4 IQR = Q3 - Q1
5 lower_bound = Q1 - (3 * IQR)
6 df_no_outliers = df_clean[(df_clean['P-PDG'] >= lower_bound)]
7
8 # removing extreme outliers from P-TPT
9 Q1 = df_no_outliers['P-TPT'].quantile(0.25)
10 Q3 = df_no_outliers['P-TPT'].quantile(0.75)
11 IQR = Q3 - Q1
12 upper_bound = Q3 + (3 * IQR)
13 df_no_outliers = df_no_outliers[(df_no_outliers['P-TPT'] <= upper_bound)]
14
15 df_no_outliers.shape

```

```
(9780901, 10)
```

These rows with presence of extreme outliers represented 2.26% of the resulting rows so far. As a result the distribution of values in P-PDG and P-TPT were modified, as Figure 3 shows.

### 3.2 Feature Engineering

Given the label feature contains 8 possible numeric labels for each undesirable event and 1 label value 0 for normal observations, 8 new boolean columns were created for each one undesirable event, including for Severe Slugging, which is this project's target.

```

1 dt_feat = df_no_outliers
2
3 # Changing 'label' column to object dtype
4 dt_feat['label'] = dt_feat['label'].astype('object')
5
6 # Creating uint8 columns for each label
7 label_dummies = pd.get_dummies(dt_feat['label'], prefix='label')
8 dt_feat = pd.concat([dt_feat, label_dummies], axis=1)
9
10 # Renaming uint8 columns
11 column_names = {

```

```

12     'label_0': 'Normal',
13     'label_1': 'AbrIncrBSW',
14     'label_2': 'SpurClosDHSW',
15     'label_3': 'SevSlug', # target
16     'label_4': 'FlowInst',
17     'label_5': 'RProdLoss',
18     'label_6': 'QuiRestrPCK',
19     'label_7': 'ScalingPCK',
20     'label_8': 'HydrProdLine'
21 }
22 dt_feat = dt_feat.rename(columns=column_names)
23
24 # Dropping the original 'label' column and Normal column,
25 # since all other events must be 0
26 dt_feat = dt_feat.drop(['label', 'Normal'], axis=1)
27 dt_feat.info()

```

```

<class 'pandas.core.frame.DataFrame'>
Int64Index: 9780901 entries, 0 to 13952910
Data columns (total 16 columns):
#   Column      Dtype
---  -
0   timestamp   datetime64[ns]
1   well         object
2   P-PDG        float64
3   P-TPT        float64
4   T-TPT        float64
5   P-MON-CKP    float64
6   T-JUS-CKP    float64
7   P-JUS-CKGL   float64
8   QGL          float64
9   AbrIncrBSW   uint8
10  SpurClosDHSW uint8
11  SevSlug       uint8
12  FlowInst      uint8
13  RProdLoss     uint8
14  QuiRestrPCK   uint8
15  ScalingPCK     uint8
dtypes: datetime64[ns](1), float64(7), object(1), uint8(7)
memory usage: 811.5+ MB

```

Then all undesirable events columns were deleted but the column which denotes the observations presents Severe Slugging. The column *HydrProdLine* concerned to Hydrate in Production line, however this event was not found in the data set resulting from real instances.

```

1 dt_feat_target = dt_feat.drop([
2     #     , 'SevSlug', 'HydrProdLine',
3     'AbrIncrBSW', 'SpurClosDHSW', 'FlowInst', 'RProdLoss', 'QuiRestrPCK', 'ScalingPCK'
4 ], axis=1)
5
6 dt_feat_target.info()

```

```

<class 'pandas.core.frame.DataFrame'>
Int64Index: 9780901 entries, 0 to 13952910
Data columns (total 10 columns):
#   Column      Dtype
---  -
0   timestamp   datetime64[ns]
1   well         object
2   P-PDG        float64
3   P-TPT        float64

```



```

4   T-TPT          float64
5   P-MON-CKP      float64
6   T-JUS-CKP      float64
7   P-JUS-CKGL     float64
8   QGL            float64
9   SevSlug        uint8
dtypes: datetime64[ns](1), float64(7), object(1), uint8(1)
memory usage: 755.6+ MB

```

### 3.3 Train/Test Splitting and Handling Imbalanced Data

The following code defined how the data set was split in Train and Test data sets. Additionally, the columns *timestamp* and *well* were removed and at the end the percentual distribution of the records according the presence or absence of Severe Slugging was computed.

```

1  # defining features (X) and label (y)
2  target = 'SevSlug'
3
4  X = dt_feat_target.drop([target, 'timestamp', 'well'], axis=1)
5  y = dt_feat_target[target]
6
7  # splitting data into train and test sets
8  X_train_u, X_test, y_train_u, y_test = train_test_split(X, y, test_size=0.3,
9                                                         random_state=42)
10
11 class_names = {0: 'Non Sev Slug', 1: 'SEV SLUGGING'}
12 print(y_train_u.value_counts(normalize=True).rename(index=class_names))

```

```

Non Sev Slug    0.94194
SEV SLUGGING    0.05806
Name: SevSlug, dtype: float64

```

### 3.4 Data Scaling

### 3.5 Dimensionality Reduction

## 4 Modeling

Modeling here

## 5 Evaluation

Evaluation here

## 6 Conclusion

### 6.1 How to add Comments and Track Changes

Comments can be added to your project by highlighting some text and clicking “Add comment” in the top right of the editor pane. To view existing comments, click on the Review menu in the toolbar above. To reply to a comment, click on the Reply button in the lower right corner of the comment. You can close the Review pane by clicking its name on the toolbar when you’re done reviewing for the time being.

Track changes are available on all our [premium plans](#), and can be toggled on or off using the option at the top of the Review pane. Track changes allow you to keep track of every change made to the document, along with the person making the change.

## 6.2 How to add Lists

You can make lists with automatic numbering ...

1. Like this,
2. and like this.

...or bullet points ...

- Like this,
- and like this.

## 6.3 How to write Mathematics

L<sup>A</sup>T<sub>E</sub>X is great at typesetting mathematics. Let  $X_1, X_2, \dots, X_n$  be a sequence of independent and identically distributed random variables with  $E[X_i] = \mu$  and  $\text{Var}[X_i] = \sigma^2 < \infty$ , and let

$$S_n = \frac{X_1 + X_2 + \dots + X_n}{n} = \frac{1}{n} \sum_i^n X_i$$

denote their mean. Then as  $n$  approaches infinity, the random variables  $\sqrt{n}(S_n - \mu)$  converge in distribution to a normal  $\mathcal{N}(0, \sigma^2)$ .

## 6.4 How to change the margins and paper size

Usually the template you're using will have the page margins and paper size set correctly for that use-case. For example, if you're using a journal article template provided by the journal publisher, that template will be formatted according to their requirements. In these cases, it's best not to alter the margins directly.

If however you're using a more general template, such as this one, and would like to alter the margins, a common way to do so is via the geometry package. You can find the geometry package loaded in the preamble at the top of this example file, and if you'd like to learn more about how to adjust the settings, please visit this help article on [page size and margins](#).

## 6.5 How to change the document language and spell check settings

Overleaf supports many different languages, including multiple different languages within one document.

To configure the document language, simply edit the option provided to the babel package in the preamble at the top of this example project. To learn more about the different options, please visit this help article on [international language support](#).

To change the spell check language, simply open the Overleaf menu at the top left of the editor window, scroll down to the spell check setting, and adjust accordingly.

## 6.6 How to add Citations and a References List

You can simply upload a `.bib` file containing your BibTeX entries, created with a tool such as JabRef. You can then cite entries from it, like this: [Gre93]. Just remember to specify a bibliography style, as well as the filename of the `.bib`. You can find a [video tutorial here](#) to learn more about BibTeX.

If you have an [upgraded account](#), you can also import your Mendeley or Zotero library directly as a `.bib` file, via the upload menu in the file-tree.

## 6.7 Good luck!

We hope you find Overleaf useful, and do take a look at our [help library](#) for more tutorials and user guides! Please also let us know if you have any feedback using the Contact Us link at the bottom of the Overleaf menu — or use the contact form at <https://www.overleaf.com/contact>.

## References

- [Gre93] George D. Greenwade. The Comprehensive Tex Archive Network (CTAN). *TUGBoat*, 14(3):342–351, 1993.