

Lets Code!

Exceptions

Exceptions, Assertions, Logging

What we'll cover

What we'll cover

Throwable Class

What we'll cover

Throwable Class

Basic Exception Handling

What we'll cover

Throwable Class

Basic Exception Handling

Better Exception Handling

What we'll cover

Throwable Class

Basic Exception Handling

Better Exception Handling

Finally Keyword

What we'll cover

Throwable Class

Basic Exception Handling

Better Exception Handling

Finally Keyword

Assertions

What we'll cover

Throwable Class

Basic Exception Handling

Better Exception Handling

Finally Keyword


Assertions

Logging

Throwable Class

- Throwable Hierarchy
- Errors
- Checked Exceptions
- Unchecked Exceptions

Throwable Hierarchy



Errors

- The `Error` hierarchy describes internal errors and resource exhaustion situations.
- Do not advertise internal java errors; Any code can potentially throw an `Error`.
- `IOException`, `StackOverflowError`, and `OutOfMemoryError` are a few of the commonly encountered `Errors`
 - `IOException` - serious I/O error has occurred
 - `StackOverflowError` - application recurses too deeply.
 - `OutOfMemoryError` - JVM cannot allocate an object because it is out of memory

Unchecked Exceptions

- Any exception which derives from `Error` or `RuntimeException` class.
- An Exception subclassing `RuntimeException` is considered to be the programmer's fault.
 - `ArrayIndexOutOfBoundsException` can be avoided by testing array index against array bounds
 - `NullPointerException` can be avoided by testing for null values.

Checked Exceptions

- An Exception subclassing `IOException` is *potentially* not the programmer's fault.
 - `FileNotFoundException` can be thrown when trying to read from a remote file that a person incidentally removes.
 - `SQLException` can be thrown as a result of a faulty network connection.

Basic Exception Handling

- What is Exception Handling?
- Unhandled Exception Example
- Handled Exception Example

What is Exception Handling?

- For exceptional situations, Java uses a form of error trapping called, *exception handling*.
- Exception handling enables the author of the code to record and handle errors in their program.

Unchecked Unhandled Exception Example; Compile Error

```
import java.io.*;
class FilePrinter {
    private final BufferedReader reader;

    public FilePrinter(String fileDirectory) {
        // What if the file does not exist?
        this.reader = new BufferedReader(new FileReader(fileDirectory));
    }

    public void printFile() {
        String line = null;
        do {
            // What if the System fails to read in the next line?
            // (For example if the file was suddenly closed, modified, or deleted)
            line = reader.readLine();
            System.out.println(line);
        } while (line != null);
    }
}
```

Exception Handling; Signature Throw Clause

```
import java.io.*;
class FilePrinter {
    private final BufferedReader reader;

    public FilePrinter(String fileDirectory) throws FileNotFoundException {
        this.reader = new BufferedReader(new FileReader(fileDirectory));
    }

    public void printFile() throws IOException {
        String line = null;
        do {
            line = reader.readLine();
            System.out.println(line);
        } while (line != null);
    }
}
```

Exception Handling; Try / Catch

```
import java.io.*;
class FilePrinter {
    private final BufferedReader reader;

    public FilePrinter(String fileDirectory) throws FileNotFoundException {
        this.reader = new BufferedReader(new FileReader(fileDirectory));
    }

    public void printFile() throws IOException {
        String line = null;
        do {
            line = reader.readLine();
            System.out.println(line);
        } while (line != null);
    }

    public void tryPrintFile() {
        try {
            printFile();
        } catch (IOException ioe) {
            ioe.printStackTrace();
        }
    }
}
```

Better Exception Handling

- Multi-Exception Handling
- Dynamic Exception Handling
- Uniform Exception Handling (Good)
- Uniform Exception Handling (Bad)
- How to throw an Exception
- Recursion ~~and~~ Exception Handling

Multi-Exception Handling

- Consider the case where multiple exceptions may be thrown.
- For example, in our `FilePrinter` class, the
 - constructor throws a `FileNotFoundException`
 - `printFile()` throws an `IOException`
- What if we wanted to create a `FilePrinter` object, then print its contents?

Multi-Exception Handling Examples

```
public class FilePrinterTest {
    private static final String invalidFileName = "";

    @Test(expected = FileNotFoundException.class)
    public void testInstantiation() throws FileNotFoundException {
        FilePrinter fpt = new FilePrinter(invalidFileName);
    }

    // Attempt to instantiate FilePrinter with invalid name
    // Attempt to invoke method on uninstantiated FilePrinter object
    @Test(expected = NullPointerException.class)
    public void testNullPointer() throws NullPointerException {
        FilePrinter fpt = null;
        try {
            fpt = new FilePrinter(invalidFileName);
        } catch (FileNotFoundException e) {
            System.out.println("Printing stack trace...");
            e.printStackTrace();
        }
        fpt.tryPrintFile();
    }

    @Test(expected = NullPointerException.class)
    public void testMultiThrowSignature() throws NullPointerException, FileNotFoundException {
        testNullPointer();
    }
}
```

Dynamic Exception Handling; Expanded

```
public class FilePrinterTest {  
    private static final String invalidFileName = "";  
    public void testInstantiateAndPrint() {  
        FilePrinter fpt = null;  
        try {  
            fpt = new FilePrinter(invalidFileName);  
        } catch (FileNotFoundException fnfe) {  
            fnfe.printStackTrace();  
        }  
  
        try {  
            fpt.printFile();  
        } catch (IOException e) {  
            e.printStackTrace();  
        }  
    }  
}
```

Dynamic Exception Handling; Compressed

```
public class FilePrinterTest {  
    private static final String invalidFileName = "";  
    public void testInstantiateAndPrint() {  
        FilePrinter fpt = null;  
        try {  
            fpt = new FilePrinter(invalidFileName);  
            fpt.printFile();  
        } catch (FileNotFoundException fnfe) {  
            // handle FileNotFoundException  
            fnfe.printStackTrace();  
        } catch (IOException ioe) {  
            // handle IOException  
            ioe.printStackTrace();  
        }  
    }  
}
```


Uniform Handling Of Exceptions (Good)

```
public class FilePrinterTest {
    private static final String invalidFileName = "";
    public void testInstantiateAndPrint() {
        FilePrinter fpt = null;
        try {
            fpt = new FilePrinter(invalidFileName);
            fpt.printFile();

            // bit-wise operator supported by java 1.7+
        } catch (FileNotFoundException | IOException exception) {
            // handle all exceptions the same way
            exception.printStackTrace();
        }
    }
}
```

- Each expected exception in this class is explicitly named.
- The handling of each of them is uniform.

Uniform Handling Of Exceptions (Bad)

```
public class FilePrinterTest {
    private static final String invalidFileName = "";
    public void testInstantiateAndPrint() {
        FilePrinter fpt = null;
        try {
            fpt = new FilePrinter(invalidFileName);
            fpt.printFile();
        } catch (Exception exception) {
            // handle all exceptions the same way
            exception.printStackTrace();
        } catch (IllegalArgumentException iae) {
            iae.printStackTrace();
        }
    }

    public void parseIntegerInput(String s) {
        try {
            Long.parseLong(s);
        } catch (NumberFormatException e) {
            e.printStackTrace();
            throw new IllegalArgumentException();
        }
    }
}
```

Recursion and Exception Handling

- DON'T DO IT!
- Recursion and Exception Handling do not go together
- Exceptions keep track of all pending method calls
- By nature, recursion pends method calls n levels deep, where n is the recursive depth of the method call.
- Combining recursion and exception handling can result in very strange `StackTraces`

Finally Keyword

- Purpose
- Conditions under which `finally` block is executed
- Syntax
- Decoupling `finally` clause from `try/catch` clauses

Purpose

- When code throws an exception, it stops processing the remaining code in the scope, then exits the method.
- If the method has acquired some local resource, then this can become an issue; The program will cease execution, and hold the resource indefinitely.
- The finally clause executes whether or not an exception was code.

Conditions under which `finally` block is executed

1. If no exception are thrown.
2. If exception outside `try` block is thrown.
3. If an exception is thrown in a `catch` clause.
4. The program skips to the `finally` clause, if the `catch` clause does not throw an exception.

Decoupling finally clause from try/catch clauses

```
class BookExample {  
    public void example1() {  
        InputStream in = ... ;  
        try {  
            try {  
                // code that may throw exception  
            } finally {  
                in.close();  
            }  
        } catch (IOException ioe) {  
            /// handle exception some way  
        }  
    }  
}
```

Assertions

- Assertions are commonly used idiom of defensive programming.
- Java has a keyword `assert`, which takes two forms:
 1. `assert condition;`
 2. `assert condition : expression;`
- `assert` evaluates a condition, then throws an `AssertionError` if it is false. The second argument *expression* is a message String.

Toggling Assert Statements

- By default, assertions are disabled; If an assert statement is passed `false`, no exception is thrown.
- Assertions can be enabled by running the program with the `-ea` option.
- `java -ea MyProject` enables for entire project
- `java -ea:MyClass -ea:com.codedifferently.MyProject` enables for `MyClass`

When To Use

- Assertion failures are intended to be fatal, unrecoverable errors
- Assertion checks are turned on only during development and testing
- As an additional check against uncanny method returns.

Logging

- It's common to use `System.out.println` to check against troublesome code.
- Once the issue is resolved, these statements are usually removed, or commented out.
- Later, if the issue persists, the print statements are re-inserted.
- The Logging API is designed to overcome this issue.

Principal advantages of Logging API

- It's easy to (un)suppress all log records, or just those below a certain level.
- Suppressed logs are inexpensive; The penalty for leaving them in your code is minimal.
- Log records can be directed to different handlers; Console display, writing to file / database, etc.
- Log records can be formatted; For example, plain text, or XML
- Logging configuration is controlled by configuration file; Applications can replace this mechanism

The 7 Logging Levels

- By default, loggers will log all messages of `INFO` or higher to console.
- `SEVERE`
- `WARNING`
- `INFO`
- `CONFIG`
- `FINE`
- `FINER`
- `FINEST`

Syntax

```
public class LogDemo {  
    // it is advised that you name your logger the same as your Main Application package  
    Logger logger = Logger.getLogger("com.codedifferently.MainApplication");  
    public void logTest() {  
        logger.setLevel(Level.SEVERE); // log severe  
        logger.setLevel(Level.WARNING); // log severe, warning  
        logger.setLevel(Level.INFO); // log severe, warning, info  
        logger.setLevel(Level.CONFIG); // log severe, warning, info, config  
        logger.setLevel(Level.FINE); // log severe, warning, info, config, fine  
        logger.setLevel(Level.FINER); // log severe, warning, info, config, fine, finer  
        logger.setLevel(Level.FINEST); // log severe, warning, info, config, fine, finer, finest  
    }  
}
```