



Process eCR

JavaScript REST Client (v.1) (Output Mode)

Communication Point

Configuration Properties	
REST Client	eCR Viewer
<pre>/** Perform a POST request to process-ecr. */ var config = { 'relative-url': '/process-ecr', 'content-type': 'application/json' }; // JWT authentication, for use with NBS integrated without eCR library config.headers = [{ 'header': 'Authorization', 'value': 'Bearer ' + getVariable('dibbsToken', true) }] // OAuth, for use with standalone and NBS integrated with eCR library // config.headers = [{ 'header': 'Authorization', 'value': 'Bearer ' + input.getProperty('accessToken') }] var body = { 'ecr': input.getProperty('eICR'), }; if (input.getProperty('RR')) { body.rr = input.getProperty('RR'); } var data = JSON.stringify(body); var response = client.post(config, data); logger.info(response.status); logger.info(response.response);</pre>	
Read Timeout (ms)	10000
Used on Routes	
2. Use token to save eCR..... Route	

Details

Retries	
Retry Type	None
Properties	
Idle Timeout (ms)	0
Number of Connections	1
Startup State	Manual Restart Required
Continue Routing Enabled	False

REST Clients

eCR Viewer	
Hostname	<your eCR Viewer hostname>
Port	443
Relative URL	/ecr-viewer/api
Description	
Default Content Type	
Proxy Enabled	False
Proxy Hostname	
Proxy Port	
Proxy Username	
Proxy Password	<i>encrypted value</i>
Protocol	HTTPS
SSL Protocol	TLSv1_2
SSL Cipher Suites	FIPS
Authentication	NONE