

Circuits

Rated voltage/current

Operating temperature

Dynamic contact resistance

Dielectric strength

Contact material

Housing material

Insulation resistance

SLIPRING ASSEMBLIES

SVTS C 00692						
Number of rings	23 circuits					
Voltage(max)	60VDC					
Current(max)	30A					
Produce Date	09/2022					
S/N	00000000					
Imported by: Servotecnica SnA - ITALY a.a.						

Servotecnica

Operating speed				0-30rpm			
Sealing				IP51			
TRATIANTE					4 3		
TRATTAMENTO TREATMENT:				2	20/09/2022	Removed circuits from 15 to 22	
					1	06/09/2022	Added 12 circuits
	MATERIALE				0	27/07/2021	Prima Emissione / First Issue
MATERIA		IAL:			REV. Nr REV N°	DATA/DATE	DESCRIZIONE/DESCRIPTION
PESO WEIGHT: 0,8Kg	/	Tolleranze/Tollerances UNI EN 22768-1				PN MODELLO - MC	
	0,8Kg		FINE MEDIA	Х			SVTS C 0069
			CDOCCOLANIA				

MODEL PN 592 SH. FG. CODICE SERVOTECNICA 1/2 27/07/2021 SCALE: N.A. H11096 DRAW. DIS. FORM A3 CHECK CONTR. ES AB PROPERTY SERVOTECNICA S.P.A. - VIA MAJORANA,4 - NOVA MILANESE(MB) - www.servotecnica.com

Technical specification

500Vac@50Hz, 60s

min 500MOhm/500Vdc

Signal 1

3-14

max 0,01 Precious metal

Engineering plastics

-20°C~+80°C

240Vac/2A

Signal2

15-18

24Vdc/2A 200Vac@50Hz, 60s

min 200M Ohm/200V dc

Bus field

19-23

Power

1-2

60Vdc/30A



