



CDL Quantum Hackathon 2021

Solving Maximun Entropy Method as QUBO problem

Inés Corte, Federico Holik, Marcelo Losada, Lorena Rebón, <u>Diego Tielas</u>

Quantum Vision Team:

Ines Corte



Marcelo Losada



Lorena Rebón



Federico Holik



Diego Tielas







Outlook:

- a) Maximum Entropy Principle
- b) Potential Applications
- c) Solving MaxEnt as a QUBO problem
- d) Proof of concept
- f) Business proposal

Maximum Entropy Principle

General idea of the Principle
Suppose that the available information is not sufficient to determine the distribution function of the system

General idea of the Principle

- Suppose that the available information is not sufficient to determine the distribution function of the system
- That is, there is more than one distribution compatible with the available information.


General idea of the Principle

- Suppose that the available information is not sufficient to determine the distribution function of the system
- That is, there is more than one distribution compatible with the available information
- Which one should we choose?

General idea of the Principle

- Suppose that the available information is not sufficient to determine the distribution function of the system
- That is, there is more than one distribution compatible with the available information
- Which one should we choose?
- Jaynes: We choose the one with maximum entropy!

Potential Applications




Continuous-scale gold prospectivity map of the Tangbale-Hatu belt generated from MaxEnt model


Quantum Systems:


$$|GHZ(\alpha\beta)\rangle = \frac{|\alpha\alpha\alpha\rangle + |\beta\beta\beta\rangle}{\sqrt{2}}$$

$$|\alpha\rangle = \frac{|0\rangle + i|1\rangle}{\sqrt{2}}$$

with $|\alpha\rangle = \frac{|0\rangle + i|1\rangle}{\sqrt{2}}$ $|\beta\rangle = \frac{|0\rangle - i|1\rangle}{\sqrt{2}}$







Solving MaxEnt as a QUBO problem

$$Cost(\bar{p}) = constraints(\bar{p}) + Entropy(\bar{p})$$

$$Cost(\bar{p}) = constraints(\bar{p}) + \sum_{i} p_{i}log(p_{i})$$

Change the entropy for a linearized version

$$Entropy(\bar{p}) = 2(1 - \bar{p} \cdot \bar{p})$$

- Change the entropy for a linearized version
- Binarize the probabilities

$$p_i = \sum_{i=1}^{Nb} 2^{-i} x_i$$

- Change the entropy for a linearized version
- Binarize the probabilities
- Build the QUBO problem

$$Cost(\bar{P}) = X^T Q X + C^T X$$

- Change the entropy for a linearized version
- Binarize the probabilities
- Build the QUBO problem

$$Cost(\bar{P}) = X^T Q X + C^T X$$

Solve with D-Wave system

Proof of concept

Proof of concept




Example 1: with fair mean value



$$\sum_{i=1}^{6} i \ p_i = 3, 5$$

Example 1: with fair mean value






Example 2: Loaded dice



$$\sum_{i=1}^{6} i \ p_i = 6$$

Example 2: Loaded dice






Example 3: Dice with one face with fixed probability



$$p_2 = 0, 8$$

Example 3: Dice with one face with fixed probability






Example 4: Dice with two faces summing a fixed probability



$$p_1 + p_2 = 0,7$$

Example 4: Dice with two faces summing a fixed probability





Business Proposal

• Probabilistic models ready for use.

- Probabilistic models ready for use.
- Easily implementable set of constrains

- Probabilistic models ready for use.
- Easily implementable set of constrains
- Simple protocol for uploading data

- Probabilistic models ready for use.
- Easily implementable set of constrains
- Simple protocol for uploading data
- Simple-setting solvers.

Thank for your atention!