

NAME

nam – set, get, and delete Namaste tag files

SYNOPSIS

```
nam [-vh] [-o fmt] [-d dir] set integer string [[maxlen] ellipsis]  
nam [-vh] [-o fmt] [-d dir] get [integer ...]  
nam [-vh] [-o fmt] [-d dir] del [integer ...]  
nam [-vh] [-o fmt] [-d dir] delall
```

DESCRIPTION

The **nam** command manages Namaste tag files. A Namaste (Name-as-text) tag file holds a single meta-data value and its filename is derived from the metadata value.

OPTIONS

- d, --directory**
Use *directory* instead of the current directory to look for tag files.
- o, --outformat**
Output in format *fmt*, one of bare (unlabeled), anvl, or xml. Default format is bare.
- v, --verbose**
Output ancillary information (the tag filename itself) as a comment.
- help, -?**
Print extended help documentation.
- man**
Print full documentation.
- version**
Print the current version number and exit.

EXAMPLES

```
nam set 0 bagit_0.98  
nam set 1 'Mark Twain'  
nam set 2 'Adventures of Huckleberry Finn' 13m  
nam get  
nam delall
```

SEE ALSO

rm(1)

AUTHOR

John Kunze *jak at ucop dot edu*

COPYRIGHT

Copyright 2009 UC Regents. Open source Apache License, Version 2.