DMP Electronics Inc. 瞻營全電子股份有限公司
No.15, Wugong 5th Rd., Xinzhuang Dist., New Taipei City, #24890, Taiwan, R.O.C
Tel:+886-2 22980770 Fax:+886-2 22991883 email:info@dmp.com.tw.

Errata

Doc No. :EXD130611

Date: 2013/06/11

Subject: Errata for Vortex86EX datasheet version 1.3

Content: The Vortex86EX datasheet version 1.3 has following mistakes. Version 1.4 correct the mistakes with this errata instead of the full datasheet update.

REV 1.4	2013/06/11	1. Remove information I2C1 .from SB F[0] Internal I2C Control Register (D7h-D4h). 2, Modify M3 & N3 to AVDD_PERX12 and AVSS_PERX12. 3, Correct page 31, SATA Power, PIN L13 to PIN L3, PIN L14 To PIN L4 4, Correct page 34, 1.2V Power, PIN R5 to PIN P5

Description:

1, Vortex86EX has only one set of I2C which is I2C0 on datasheet, the information of I2C1 should be deleted.

2, The M3 and N3 was NC pins on version 1.3, here correct the pin definition.
PIN M3 : From NC (wrong) to AVDD_PERX12 (correct)
PIN N3 : From NC (wrong) to AVSS_PERX12 (correct)

3, The pin number was wrong on version 1.3, below is the correct one.

SATA Power (7 PINs)

PIN No.	Symbol	Type	Description
L5	AVDD_SATA33	P	***Analogue Power*** *SATA PHY*: 3.3V Analogue Power
M2	AVDD_SATA12	P	***Analogue Power*** *SATA PHY*: 1.2V Analogue Power
M1	AVSS_SATA	G	***Analogue Ground*** *SATA PHY*: Analogue Ground
K3	AVDD_SATARX12	P	***Analogue Power*** *SATA PHY*: Receiver 1.2V Analogue Power
L3	AVSS_SATARX12	G	***Analogue Ground*** *SATA PHY*: Receiver Analogue Ground
K4	AVDD_SATAPLL12	P	***Analogue Power*** *SATA PHY*: PLL 1.2V Analogue Power
L4	AVSS_SATAPLL12	G	***Analogue Ground*** *SATA PHY*: PLL Analogue Ground

Anritsu

4, The pin number was wrong on version 1.3, below is the correct one.

1.2V POWER (8 PINs)

PIN No.	Symbol	Type	Description
J10, J11, J9, L10, L11, L9, P5, R7	VDD12	P	***Core power.***

----------END----------