

Data Structures

Dictionaries

DataLab

November 12, 2016

Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - GetValue
 - Contains
 - Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - GetValue
 - Contains
 - Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

Dictionaries

Definition

The **ADT dictionary**—also called a map, table, or associative array—contains entries that each have two parts:

- A keyword—usually called a search key—such as an English word or a person's name
- A value—such as a definition, an address, or a telephone number—associated with that key

Dictionaries

Definition

The **ADT dictionary**—also called a map, table, or associative array—contains entries that each have two parts:

- A keyword—usually called a search key—such as an English word or a person's name
- A value—such as a definition, an address, or a telephone number—associated with that key

Dictionaries

Definition

The **ADT dictionary**—also called a map, table, or associative array—contains entries that each have two parts:

- A keyword—usually called a search key—such as an English word or a person's name
- A value—such as a definition, an address, or a telephone number—associated with that key

Example

Dictionary with Duplicates

Pairs are of the form (word, meaning).

Example

Dictionary with Duplicates

Pairs are of the form (word, meaning).

More than a single meaning

- (bolt, a threaded pin)
- (bolt, a crash of thunder)
- (bolt, to shoot forth suddenly)
- (bolt, a gulp)
- (bolt, a standard roll of cloth)
- etc.

Example

Dictionary with Duplicates

Pairs are of the form (word, meaning).

More than a single meaning

- (bolt, a threaded pin)
- (bolt, a crash of thunder)
- (bolt, to shoot forth suddenly)
- (bolt, a gulp)
- (bolt, a standard roll of cloth)
- etc.

Example

Dictionary with Duplicates

Pairs are of the form (word, meaning).

More than a single meaning

- (bolt, a threaded pin)
- (bolt, a crash of thunder)
- (bolt, to shoot forth suddenly)
- (bolt, a gulp)
- (bolt, a standard roll of cloth)
- etc.

Example

Dictionary with Duplicates

Pairs are of the form (word, meaning).

More than a single meaning

- (bolt, a threaded pin)
- (bolt, a crash of thunder)
- (bolt, to shoot forth suddenly)
- (bolt, a gulp)
- (bolt, a standard roll of cloth)

• etc.

Example

Dictionary with Duplicates

Pairs are of the form (word, meaning).

More than a single meaning

- (bolt, a threaded pin)
- (bolt, a crash of thunder)
- (bolt, to shoot forth suddenly)
- (bolt, a gulp)
- (bolt, a standard roll of cloth)
- etc.

Thus

We have possibly in a dictionary

- Sorted keys
- Duplicate keys

Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

• The Operations

- Add
- Remove
- GetValue
- Contains
- Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

Operation in the ADT dictionary

Common operations with most databases

- **insert** adds a new entry to the dictionary, given a search key and associated value.
- **delete** removes an entry, given its associated search key
- **retrieve** retrieves the value associated with a given search key
- **search** sees whether the dictionary contains a given search key
- **traverse**
 - ▶ It traverse all the search keys in the dictionary
 - ▶ It traverse all the values in the dictionary

Operation in the ADT dictionary

Common operations with most databases

- **insert** adds a new entry to the dictionary, given a search key and associated value.
- **delete** removes an entry, given its associated search key
- **retrieve** retrieves the value associated with a given search key
- **search** sees whether the dictionary contains a given search key
- **traverse**
 - ▶ It traverse all the search keys in the dictionary
 - ▶ It traverse all the values in the dictionary

Operation in the ADT dictionary

Common operations with most databases

- **insert** adds a new entry to the dictionary, given a search key and associated value.
- **delete** removes an entry, given its associated search key
- **retrieve** retrieves the value associated with a given search key
- **search** sees whether the dictionary contains a given search key
- **traverse**
 - ▶ It traverse all the search keys in the dictionary
 - ▶ It traverse all the values in the dictionary

Operation in the ADT dictionary

Common operations with most databases

- **insert** adds a new entry to the dictionary, given a search key and associated value.
- **delete** removes an entry, given its associated search key
- **retrieve** retrieves the value associated with a given search key
- **search** sees whether the dictionary contains a given search key
- **traverse**
 - ▶ It traverse all the search keys in the dictionary
 - ▶ It traverse all the values in the dictionary

Operation in the ADT dictionary

Common operations with most databases

- **insert** adds a new entry to the dictionary, given a search key and associated value.
- **delete** removes an entry, given its associated search key
- **retrieve** retrieves the value associated with a given search key
- **search** sees whether the dictionary contains a given search key
- **traverse**

- ▶ It traverse all the search keys in the dictionary
- ▶ It traverse all the values in the dictionary

Operation in the ADT dictionary

Common operations with most databases

- **insert** adds a new entry to the dictionary, given a search key and associated value.
- **delete** removes an entry, given its associated search key
- **retrieve** retrieves the value associated with a given search key
- **search** sees whether the dictionary contains a given search key
- **traverse**
 - ▶ It traverse all the search keys in the dictionary
 - ▶ It traverse all the values in the dictionary

Operation in the ADT dictionary

Common operations with most databases

- **insert** adds a new entry to the dictionary, given a search key and associated value.
- **delete** removes an entry, given its associated search key
- **retrieve** retrieves the value associated with a given search key
- **search** sees whether the dictionary contains a given search key
- **traverse**
 - ▶ It traverse all the search keys in the dictionary
 - ▶ It traverse all the values in the dictionary

In addition

We have the following extra operations

- Detect whether a dictionary is empty
- Get the number of entries in the dictionary
- Remove all entries from the dictionary

In addition

We have the following extra operations

- Detect whether a dictionary is empty
- Get the number of entries in the dictionary
- Remove all entries from the dictionary

In addition

We have the following extra operations

- Detect whether a dictionary is empty
- Get the number of entries in the dictionary
- Remove all entries from the dictionary

Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - GetValue
 - Contains
 - Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

Specifications: Add

Pseudocode

```
add(key, value)
```

Task

It adds the pair (key , value) to the dictionary.

Specifications: Add

Pseudocode

```
add(key, value)
```

Task

It adds the pair (key , value) to the dictionary.

Input and Output

Input: key is an object search key, value is an associated object.

Specifications: Add

Pseudocode

```
add(key, value)
```

Task

It adds the pair (key , value) to the dictionary.


Input and Output

Input: key is an object search key, value is an associated object.

Output: None.

Example

Adding something



Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - GetValue
 - Contains
 - Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

Specifications: Remove

Pseudocode

```
remove(key)
```


Specifications: Remove

Pseudocode

```
remove(key)
```

Task

It removes from the dictionary the entry that corresponds to a given search key.

Specifications: Remove

Pseudocode

```
remove(key)
```

Task

It removes from the dictionary the entry that corresponds to a given search key.

Input and Output

Input: key is an object search key.

Output: Returns either the value that was associated with the search key or null if no such object exists.

Specifications: Remove

Pseudocode

```
remove(key)
```

Task

It removes from the dictionary the entry that corresponds to a given search key.


Input and Output

Input: key is an object search key.

Output: Returns either the value that was associated with the search key or null if no such object exists.

Example

Removing something



Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - **GetValue**
 - Contains
 - Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

Specifications: GetValue

Pseudocode

```
getValue(key)
```

Specifications: GetValue

Pseudocode

```
getValue(key)
```

Task

It retrieves from the dictionary the value that corresponds to a given search key.

Specifications: GetValue

Pseudocode

```
getValue(key)
```

Task

It retrieves from the dictionary the value that corresponds to a given search key.

Input and Output

Input: key is an object search key.

Output: Returns either the value associated with the search key or null if no such object exists.

Specifications: GetValue

Pseudocode

```
getValue(key)
```

Task

It retrieves from the dictionary the value that corresponds to a given search key.

Input and Output

Input: key is an object search key.

Output: Returns either the value associated with the search key or null if no such object exists.

Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

• The Operations

- Add
- Remove
- GetValue
- **Contains**
- Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

Specifications: Contains

Pseudocode

contains(key)

Specifications: Contains

Pseudocode

`contains(key)`

Task

It sees whether any entry in the dictionary has a given search key.

Specifications: Contains

Pseudocode

`contains(key)`

Task

It sees whether any entry in the dictionary has a given search key.

Input and Output

Input: key is an object search key.

Output: Returns true if an entry in the dictionary has key as its search key.

Specifications: Contains

Pseudocode

`contains(key)`

Task

It sees whether any entry in the dictionary has a given search key.

Input and Output

Input: key is an object search key.

Output: Returns true if an entry in the dictionary has key as its search key.

Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

• The Operations

- Add
- Remove
- GetValue
- Contains

• Iterators

- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

Specifications: GetKeylterator

Pseudocode

```
getKeylterator()
```


Specifications: GetKeylterator

Pseudocode

getKeylterator()

Task

It creates an iterator that traverses all search keys in the dictionary.

Specifications: GetKeylterator

Pseudocode

getKeylterator()

Task

It creates an iterator that traverses all search keys in the dictionary.

Input and Output

Input: None.

Output: Returns an iterator that provides sequential access to the search keys in the dictionary.

Specifications: GetKeylterator

Pseudocode

```
getKeylterator()
```

Task

It creates an iterator that traverses all search keys in the dictionary.

Input and Output

Input: None.

Output: Returns an iterator that provides sequential access to the search keys in the dictionary.

Specifications: GetValueIterator

Pseudocode

```
getValueIterator()
```

Task

It creates an iterator that traverses all values in the dictionary.

Specifications: GetValueIterator

Pseudocode

```
getValueIterator()
```

Task

It creates an iterator that traverses all values in the dictionary.

Input and Output

Input: None.

Specifications: GetValueIterator

Pseudocode

```
getValueIterator()
```

Task

It creates an iterator that traverses all values in the dictionary.

Input and Output

Input: None.

Output: Returns an iterator that provides sequential access to the values in the dictionary.

Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - GetValue
 - Contains
 - Iterators
- Other Operations
 - Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

Other Operations

`isEmpty()`

It sees whether the dictionary is empty.

`getSize()`

It gets the size of the dictionary.

`clear()`

It removes all entries from the dictionary.

Other Operations

isEmpty()

It sees whether the dictionary is empty.

getSize()

It gets the size of the dictionary.

clear()

It removes all entries from the dictionary.

Other Operations

`isEmpty()`

It sees whether the dictionary is empty.

`getSize()`

It gets the size of the dictionary.

`clear()`

It removes all entries from the dictionary.

Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - GetValue
 - Contains
 - Iterators
- Other Operations
- **Scenarios About the Keys**

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

However, we have two scenarios

Distinct search keys

Case 1 You can refuse to add another key-value.

Case 2 You can change the existing value associated with key to the new value. Then, you return the old value

However, we have two scenarios

Distinct search keys

- Case 1 You can refuse to add another key-value.
- Case 2 You can change the existing value associated with key to the new value. Then, you return the old value

Duplicate search keys

if the method add adds every given key-value entry to a dictionary

- The methods **remove** and **getValue** must deal with multiple entries that have the same search key.
- What do you remove or return!!!

However, we have two scenarios

Distinct search keys

Case 1 You can refuse to add another key-value.

Case 2 You can change the existing value associated with key to the new value. Then, you return the old value

Duplicate search keys

if the method add adds every given key-value entry to a dictionary

- The methods remove and getValue must deal with multiple entries that have the same search key.
- What do you remove or return!!!

However, we have two scenarios

Distinct search keys

Case 1 You can refuse to add another key-value.

Case 2 You can change the existing value associated with key to the new value. Then, you return the old value

Duplicate search keys

if the method `add` adds every given key-value entry to a dictionary

- The methods **`remove`** and **`getValue`** must deal with multiple entries that have the same search key.

• What do you remove or return!!!

However, we have two scenarios

Distinct search keys

Case 1 You can refuse to add another key-value.

Case 2 You can change the existing value associated with key to the new value. Then, you return the old value

Duplicate search keys

if the method add adds every given key-value entry to a dictionary

- The methods **remove** and **getValue** must deal with multiple entries that have the same search key.
- What do you remove or return!!!

Interface

We have the following interface

```
interface DictionaryInterface
{
    add(k, Item);
    remove(k);
    getValue(k);
    contains(k);
    getKeyIterator();
    getValueIterator();
    isEmpty();
    getSize();
    clear();
}
```

Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - GetValue
 - Contains
 - Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

Where we can use this ADT?

In the phone directory problem

It is a directory that uses a name as the key and adds and returns a phone number

For example

Name	Number
Suzanne Nouveaux	401-555-1234
Andres Mendez-Vazquez	301-123-2345
...	...

Where we can use this ADT?

In the phone directory problem


It is a directory that uses a name as the key and adds and returns a phone number

For example

Name	Number
Suzanne Nouveaux	401-555-1234
Andres Mendez-Vazquez	301-123-2345
...	...

Thus, we have the following diagram

A class Diagram



Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - GetValue
 - Contains
 - Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

Now, the Big Question

It is a big one

How do we implement this data structure?

Now, the Big Question

It is a big one

How do we implement this data structure?

Possible ways

- Linear List
- Skip List
- Hash Tables
- ...

Now, the Big Question

It is a big one

How do we implement this data structure?

Possible ways

- Linear List
- Skip List

• Hash Tables

• ...

Now, the Big Question

It is a big one

How do we implement this data structure?

Possible ways

- Linear List
- Skip List
- Hash Tables

• ...

Now, the Big Question

It is a big one

How do we implement this data structure?

Possible ways

- Linear List
- Skip List
- Hash Tables
- ...

Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - GetValue
 - Contains
 - Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- **Using an Linear List**

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

First: Represent It As A Linear List

You have

$$L = (e_0, e_1, \dots, e_{n-1})$$

Where

Each e_i is a pair (key, element).

We can use the following representations

Array or linked representation.

First: Represent It As A Linear List

You have

$$L = (e_0, e_1, \dots, e_{n-1})$$

Where

Each e_i is a pair (key, element).

We can use the following representations:

Array or linked representation.

First: Represent It As A Linear List

You have

$$L = (e_0, e_1, \dots, e_{n-1})$$

Where

Each e_i is a pair (key, element).

We can use the following representations

Array or linked representation.

Array Representation

Our classic array

b	c	d	e	a										
0	1	2	3	4	5	6								

We have then

Operation in Array Representation	Complexity
<code>getValue(theKey)</code>	$O(\text{size})$
<code>add(theKey, theItem)</code>	$O(\text{size})$ to find duplicate $O(1)$ to add at right end
<code>remove(theKey)</code>	$O(\text{size})$

Array Representation

Our classic array

b	c	d	e	a										
0	1	2	3	4	5	6								

We have then

Operation in Array Representation	Complexity
getValue(theKey)	$O(\text{size})$
add(theKey, theItem)	$O(\text{size})$ to find duplicate
	$O(1)$ to add at right end
remove(theKey)	$O(\text{size})$

What if we sort the array?

Sorted Keys

a	b	c	d	e										
0	1	2	3	4	5	6								

We have then

Operation in Array Representation	Complexity
<code>getValue(theKey)</code>	$O(\log \text{size})$ Using Binary Search
<code>add(theKey, theItem)</code>	$O(\log \text{size})$ to find duplicate $O(\text{size})$ to add
<code>remove(theKey)</code>	$O(\text{size})$

What if we sort the array?

Sorted Keys


a	b	c	d	e										
0	1	2	3	4	5	6								

We have then

Operation in Array Representation	Complexity
getValue(theKey)	$O(\log \text{size})$ Using Binary Search
add(theKey, theItem)	$O(\log \text{size})$ to find duplicate $O(\text{size})$ to add
remove(theKey)	$O(\text{size})$

Unsorted Chain

Our Structure




Complexity

Operation in Chain Representation	Complexity
<code>getValue(theKey)</code>	$O(\text{size})$
<code>add(theKey, theItem)</code>	$O(\text{size})$ to find duplicate $O(1)$ to add
<code>remove(theKey)</code>	$O(\text{size})$

Unsorted Chain

Our Structure




Complexity

Operation in Chain Representation	Complexity
getValue(theKey)	$O(\text{size})$
add(theKey, theItem)	$O(\text{size})$ to find duplicate $O(1)$ to add
remove(theKey)	$O(\text{size})$

Sorted Chain

Our Structure




Complexity

Operation in Chain Representation	Complexity
<code>getValue(theKey)</code>	$O(\text{size})$
<code>add(theKey, theItem)</code>	$O(\text{size})$ to find duplicate $O(1)$ to add
<code>remove(theKey)</code>	$O(\text{size})$

Sorted Chain

Our Structure




Complexity

Operation in Chain Representation	Complexity
getValue(theKey)	$O(\text{size})$
add(theKey, theItem)	$O(\text{size})$ to find duplicate $O(1)$ to add
remove(theKey)	$O(\text{size})$

Skip Lists: we will skip it - It is for an advance class of analysis of algorithms

We have something like this




Complexity

Operation	Complexity - Worst Case	Complexity - Expected
<code>getValue(theKey)</code>	$O(\text{size})$	$O(\log \text{size})$
<code>add(theKey, theItem)</code>	$O(\text{size})$	$O(\log \text{size})$
<code>remove(theKey)</code>	$O(\text{size})$	$O(\log \text{size})$

Skip Lists: we will skip it - It is for an advance class of analysis of algorithms

We have something like this



Complexity

Operation	Complexity - Worst Case	Complexity - Expected
getValue(theKey)	$O(\text{size})$	$O(\log \text{ size})$
add(theKey, theItem)	$O(\text{size})$	$O(\log \text{ size})$
remove(theKey)	$O(\text{size})$	$O(\log \text{ size})$

Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - GetValue
 - Contains
 - Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- **Introduction**
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

We will concentrate our efforts in the Hash Tables

Definition

- A hash table or hash map T is a data structure, most commonly an array, that uses a hash function to efficiently map certain identifiers of keys (e.g. person names) to associated values.

Why?

Operation in Array Representation	Complexity - Worst Case	Complexity - Expected
<code>getValue(theKey)</code>	$O(\text{size})$	$O(1 + O)$
<code>add(theKey, theItem)</code>	$O(\text{size})$	$O(1 + O)$
<code>remove(theKey)</code>	$O(\text{size})$	$O(1 + O)$

We will concentrate our efforts in the Hash Tables

Definition

- A hash table or hash map T is a data structure, most commonly an array, that uses a hash function to efficiently map certain identifiers of keys (e.g. person names) to associated values.

Why?

Operation in Array Representation	Complexity - Worst Case	Complexity - Expected
<code>getValue(theKey)</code>	$O(\text{size})$	$O(1 + C)$
<code>add(theKey, theItem)</code>	$O(\text{size})$	$O(1 + C)$
<code>remove(theKey)</code>	$O(\text{size})$	$O(1 + C)$

Then

Advantages

- They have the advantage of having a expected complexity of operations of $O(1 + C)$
 - Still, be aware of C because this will change depending on which overflow policy you use...

Then

Advantages

- They have the advantage of having a expected complexity of operations of $O(1 + C)$
 - ▶ Still, be aware of C because this will change depending on which overflow policy you use...

Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - GetValue
 - Contains
 - Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- **Number of Keys**
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

You have two cases for this data structure

First

Small universe of keys.

Second

Large number of keys

You have two cases for this data structure

First

Small universe of keys.

Second

Large number of keys

When you have a small universe of keys, U

We can do the following

- Key values are direct addresses in the array.
- Direct implementation or Direct-address tables.

When you have a small universe of keys, U

We can do the following

- Key values are direct addresses in the array.
- Direct implementation or Direct-address tables.

Operations

- Direct-Address-Search($Table, key$)
 - ▶ return $Table[key]$
- Direct-Address-Search($Table, key, value$)
 - ▶ $Table[key] = value$
- Direct-Address-Delete(T, x)
 - ▶ $Table[key] = null$

When you have a small universe of keys, U

We can do the following

- Key values are direct addresses in the array.
- Direct implementation or Direct-address tables.

Operations

1 Direct-Address-Search(Table, key)

► return Table[key]

2 Direct-Address-Search(Table, key, value)

► Table[key]=value

3 Direct-Address-Delete(T , x)

► Table[key]=null

When you have a small universe of keys, U

We can do the following

- Key values are direct addresses in the array.
- Direct implementation or Direct-address tables.

Operations

1 Direct-Address-Search(Table, key)

- ▶ return Table[key]

2 Direct-Address-Search(Table, key, value)

- ▶ Table[key]=value

3 Direct-Address-Delete(T , x)

- ▶ Table[key]=null

When you have a small universe of keys, U

We can do the following

- Key values are direct addresses in the array.
- Direct implementation or Direct-address tables.

Operations

- 1 Direct-Address-Search(Table, key)
 - ▶ return Table[key]
- 2 Direct-Address-Search(Table, key, value)
 - ▶ Table[key]=value
- 3 Direct-Address-Delete(T, x)
 - ▶ Table[key]=null

When you have a small universe of keys, U

We can do the following

- Key values are direct addresses in the array.
- Direct implementation or Direct-address tables.

Operations

- 1 Direct-Address-Search(T , key)
 - ▶ return $T[key]$
- 2 Direct-Address-Search($T, key, value$)
 - ▶ $T[key] = value$

- 3 Direct-Address-Delete(T, x)
 - ▶ $T[key] = null$

When you have a small universe of keys, U

We can do the following

- Key values are direct addresses in the array.
- Direct implementation or Direct-address tables.

Operations

- 1 Direct-Address-Search(Table , key)
 - ▶ return $\text{Table}[\text{key}]$
- 2 Direct-Address-Search(Table , key , value)
 - ▶ $\text{Table}[\text{key}] = \text{value}$
- 3 Direct-Address-Delete(T , x)

▶ $\text{Table}[\text{key}] = \text{null}$

When you have a small universe of keys, U

We can do the following

- Key values are direct addresses in the array.
- Direct implementation or Direct-address tables.

Operations

- 1 Direct-Address-Search(Table , key)
 - ▶ return $\text{Table}[\text{key}]$
- 2 Direct-Address-Search(Table , key , value)
 - ▶ $\text{Table}[\text{key}] = \text{value}$
- 3 Direct-Address-Delete(T , x)
 - ▶ $\text{Table}[\text{key}] = \text{null}$

When you have a large universe of keys, U

Then

Then, it is impractical to store a table of the size of $|U|$.

You can use a special function for mapping

$$h : U \rightarrow \{0, 1, \dots, m-1\} \quad (1)$$

When you have a large universe of keys, U

Then

Then, it is impractical to store a table of the size of $|U|$.

You can use a especial function for mapping

$$h : U \rightarrow \{0, 1, \dots, m - 1\} \quad (1)$$

Example

Imagine that you have

A 1D array (or table) $\text{table}[0 : m - 1]$.

Thus

$h(k)$ is the home bucket for key k .

Then

Every dictionary pair (key, Item) is stored in its home bucket $\text{table}[h[\text{key}]]$.

Example

Imagine that you have

A 1D array (or table) $\text{table}[0 : m - 1]$.

Thus

$h(k)$ is the home bucket for key k .

Then

Every dictionary pair (key, Item) is stored in its home bucket $\text{table}[h[\text{key}]]$.

Example

Imagine that you have

A 1D array (or table) $\text{table}[0 : m - 1]$.

Thus

$h(k)$ is the home bucket for key k .

Then

Every dictionary pair (key, Item) is stored in its home bucket $\text{table}[h[\text{key}]]$.

Example

Push the following pairs in a hash table of size $m = 8$
(22,a), (33,c), (3,d), (73,e), (85,f).

Hash function is

$$\text{key} / 11$$

Then, we have that

Example

Push the following pairs in a hash table of size $m = 8$

$(22,a)$, $(33,c)$, $(3,d)$, $(73,e)$, $(85,f)$.

Hash function is

$$key/11$$

Then, we have that

Example

Push the following pairs in a hash table of size $m = 8$

$(22,a)$, $(33,c)$, $(3,d)$, $(73,e)$, $(85,f)$.

Hash function is

$$key/11$$

Then, we have that

(3,d)		(22,a)	(33,c)			(73,e)	(85,f)
[0]	[1]	[2]	[3]	[4]	[5]	[6]	[7]

What Can Go Wrong?

What if we add?

Where does (26,g) go?

What Can Go Wrong?

What if we add?

Where does (26,g) go?

Then

(3,d)		(22,a)	(33,c)			(73,e)	(85,f)
[0]	[1]	[2]	[3]	[4]	[5]	[6]	[7]

What Can Go Wrong?

What if we add?

Where does (26,g) go?

Then

(3,d)		(22,a)	(33,c)			(73,e)	(85,f)
[0]	[1]	[2]	[3]	[4]	[5]	[6]	[7]

PROBLEM!!!

- Keys that have the same home bucket are synonyms.
- 22 and 26 are synonyms with respect to the hash function that is in use.
- This is known as collision or overflow.

What Can Go Wrong?

What if we add?

Where does (26,g) go?

Then

PROBLEM!!!

- Keys that have the same home bucket are synonyms.
- 22 and 26 are synonyms with respect to the hash function that is in use.

• This is known as collision or overflow.

What Can Go Wrong?

What if we add?

Where does (26,g) go?

Then

PROBLEM!!!

- Keys that have the same home bucket are synonyms.
- 22 and 26 are synonyms with respect to the hash function that is in use.
- This is known as **collision or overflow**.

Collisions

This is a problem

We might try to avoid this by using a suitable hash function h .

Collisions

This is a problem

We might try to avoid this by using a suitable hash function h .

Idea

Make appear to be “random” enough to avoid collisions altogether (**Highly Improbable**) or to minimize the probability of them.

Collisions

This is a problem

We might try to avoid this by using a suitable hash function h .

Idea

Make appear to be “random” enough to avoid collisions altogether (**Highly Improbable**) or to minimize the probability of them.

You still have the problem of collisions

Possible Solutions to the problem:

- Chaining
- Open Addressing

Collisions

This is a problem

We might try to avoid this by using a suitable hash function h .

Idea

Make appear to be “random” enough to avoid collisions altogether (**Highly Improbable**) or to minimize the probability of them.

You still have the problem of collisions

Possible Solutions to the problem:

① Chaining

② Open Addressing

Collisions

This is a problem

We might try to avoid this by using a suitable hash function h .

Idea

Make appear to be “random” enough to avoid collisions altogether (**Highly Improbable**) or to minimize the probability of them.

You still have the problem of collisions

Possible Solutions to the problem:

- 1 Chaining
- 2 Open Addressing

Collisions

This is a problem

We might try to avoid this by using a suitable hash function h .

Idea

Make appear to be “random” enough to avoid collisions altogether (**Highly Improbable**) or to minimize the probability of them.

You still have the problem of collisions

Possible Solutions to the problem:

- 1 Chaining
- 2 Open Addressing

Other Issues

First Issue

The choice of the possible hash function.

Second

The collision handling method

Third

The size (number of buckets) at the hash table

Other Issues

First Issue

The choice of the possible hash function.

Second

The collision handling method

Third

The size (number of buckets) at the hash table

Other Issues

First Issue

The choice of the possible hash function.

Second

The collision handling method

Third

The size (number of buckets) at the hash table

Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - GetValue
 - Contains
 - Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- **Hash Functions**

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

Hash Functions

They have two parts

- ① The conversion of the key into an integer in the case the key is not an integer.
- ② The mapping to the home bucket.

Hash Functions

They have two parts

- ① The conversion of the key into an integer in the case the key is not an integer.
- ② The mapping to the home bucket.

Analysis of hashing: Which hash function?

Consider that:

Good hash functions should maintain the property of simple uniform hashing!

- The keys have the same probability $1/m$ to be hashed to any bucket!!!
- A uniform hash function minimizes the likelihood of an overflow when keys are selected at random.

Analysis of hashing: Which hash function?

Consider that:

Good hash functions should maintain the property of simple uniform hashing!

- The keys have the same probability $1/m$ to be hashed to any bucket!!!
- A uniform hash function minimizes the likelihood of an overflow when keys are selected at random.

Analysis of hashing: Which hash function?

Consider that:


Good hash functions should maintain the property of simple uniform hashing!

- The keys have the same probability $1/m$ to be hashed to any bucket!!!
- A uniform hash function minimizes the likelihood of an overflow when keys are selected at random.

What if...?

Question:

What about something with keys in a normal distribution?



Hashing By Division

Universe of keys

keySpace = all integers.

Thus, we have that

For every m , the number of integers that get mapped (hashed) into bucket i is approximately $2^{32}/m$.

Properties

The division method results in a uniform hash function when keySpace = all integers.

Hashing By Division

Universe of keys

keySpace = all integers.

Thus, we have that

For every m , the number of integers that get mapped (hashed) into bucket i is approximately $2^{32}/m$.

Properties

The division method results in a uniform hash function when keySpace = all integers.

Hashing By Division

Universe of keys

keySpace = all integers.

Thus, we have that

For every m , the number of integers that get mapped (hashed) into bucket i is approximately $2^{32}/m$.

Properties

The division method results in a uniform hash function when keySpace = all integers.

However

Problem

In practice, keys tend to be correlated.

Thus

The choice of the divisor b affects the distribution of home buckets.

Then

Because of this correlation, applications tend to have a bias towards keys that map into odd integers (or into even ones).

However

Problem

In practice, keys tend to be correlated.

Thus

The choice of the divisor b affects the distribution of home buckets.

Hint

Because of this correlation, applications tend to have a bias towards keys that map into odd integers (or into even ones).

However

Problem

In practice, keys tend to be correlated.

Thus

The choice of the divisor b affects the distribution of home buckets.

Then

Because of this correlation, applications tend to have a bias towards keys that map into odd integers (or into even ones).

Examples

Odd number and m an even number

Odd integers hash into odd home buckets

- $15\%14 = 1$, $3\%14 = 3$, $23\%14 = 9$

Even number and m an even number

Even integers into even home buckets.

- $20\%14 = 6$, $30\%14 = 2$, $8\%14 = 8$

Properties

The bias in the keys results in a bias toward either the odd or even home buckets.

Examples

Odd number and m an even number

Odd integers hash into odd home buckets

- $15\%14 = 1$, $3\%14 = 3$, $23\%14 = 9$

Even number and m an even number

Even integers into even home buckets.

- $20\%14 = 6$, $30\%14 = 2$, $8\%14 = 8$

Properties

The bias in the keys results in a bias toward either the odd or even home buckets.

Examples

Odd number and m an even number

Odd integers hash into odd home buckets

- $15\%14 = 1$, $3\%14 = 3$, $23\%14 = 9$

Even number and m an even number

Even integers into even home buckets.

- $20\%14 = 6$, $30\%14 = 2$, $8\%14 = 8$

Properties

The bias in the keys results in a bias toward either the odd or even home buckets.

What if we use an Odd number?

Odd number and m an odd number

odd integers may hash into any home.

- $15\%15 = 0$, $3\%15 = 3$, $23\%15 = 8$

and m an odd number

Even integers may hash into any home.

- $20\%15 = 5$, $30\%15 = 0$, $8\%15 = 8$

Thus:

The bias in the keys does not result in a bias toward either the odd or even home buckets.

What if we use an Odd number?

Odd number and m an odd number

odd integers may hash into any home.

- $15\%15 = 0$, $3\%15 = 3$, $23\%15 = 8$

Even number and m an odd number

Even integers may hash into any home.

- $20\%15 = 5$, $30\%15 = 0$, $8\%15 = 8$

Thus

The bias in the keys does not result in a bias toward either the odd or even home buckets.

What if we use an Odd number?

Odd number and m an odd number

odd integers may hash into any home.

- $15\%15 = 0$, $3\%15 = 3$, $23\%15 = 8$

Even number and m an odd number

Even integers may hash into any home.

- $20\%15 = 5$, $30\%15 = 0$, $8\%15 = 8$

Thus

The bias in the keys does not result in a bias toward either the odd or even home buckets.

Bias

Something Notable

The bias in the keys does not result in a bias toward either the odd or even home buckets.

Then, we have

We have a better chance of uniformly distributed home buckets.

Thus

So do not use an even divisor.

Bias

Something Notable

The bias in the keys does not result in a bias toward either the odd or even home buckets.

Then, we have

We have a better chance of uniformly distributed home buckets.

Hint:

So do not use an even divisor.

Bias

Something Notable

The bias in the keys does not result in a bias toward either the odd or even home buckets.

Then, we have

We have a better chance of uniformly distributed home buckets.

Thus

So do not use an even divisor.

Selecting The Divisor

Another Problem

Similar biased distribution of home buckets is seen, in practice, when the divisor is a multiple of prime numbers such as 3, 5, 7, ...

However:

The effect of each prime divisor p of m decreases as p gets larger.

Rules of choosing m :

- Ideally, choose m so that it is a prime number.
- Not too close to a power of 2.

Selecting The Divisor

Another Problem

Similar biased distribution of home buckets is seen, in practice, when the divisor is a multiple of prime numbers such as 3, 5, 7, ...

However

The effect of each prime divisor p of m decreases as p gets larger.

Rules for Choosing m

- Ideally, choose m so that it is a prime number.
- Not too close to a power of 2.

Selecting The Divisor

Another Problem

Similar biased distribution of home buckets is seen, in practice, when the divisor is a multiple of prime numbers such as 3, 5, 7, ...

However

The effect of each prime divisor p of m decreases as p gets larger.

Rules of Choosing m

- Ideally, choose m so that it is a prime number.
- Not too close to a power of 2.

However

Something Notable

Even with this hash function, we can have problems

However

Something Notable

Even with this hash function, we can have problems

Remember

The Gaussian Keys...

Universal Hashing

Issues

- In practice, keys are not randomly distributed.
- Any fixed hash function might yield retrieval $O(n)$ time.

Universal Hashing

Issues

- In practice, keys are not randomly distributed.
- Any fixed hash function might yield retrieval $O(n)$ time.

Universal Hashing

Issues

- In practice, keys are not randomly distributed.
- Any fixed hash function might yield retrieval $O(n)$ time.

Goal

To find hash functions that produce uniform random table indexes irrespective of the keys.

Idea

To select a hash function at random from a designed class of functions at the beginning of the execution.

Universal Hashing

Issues

- In practice, keys are not randomly distributed.
- Any fixed hash function might yield retrieval $O(n)$ time.

Goal


To find hash functions that produce uniform random table indexes irrespective of the keys.

Idea

To select a hash function at random from a designed class of functions at the beginning of the execution.

Universal Hashing

Example



Example of Universal Hash

Proceed as follows:

- Choose a primer number p large enough so that every possible key k is in the range $[0, \dots, p - 1]$

$$\mathbb{Z}_p = \{0, 1, \dots, p - 1\} \text{ and } \mathbb{Z}_p^* = \{1, \dots, p - 1\}$$

- Define the following hash function:

$$h_{a,b}(k) = ((ak + b) \bmod p) \bmod m, \forall a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p$$

- The family of all such hash functions is:

$$H_{p,m} = \{h_{a,b} : a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p\}$$

Example of Universal Hash

Proceed as follows:

- Choose a primer number p large enough so that every possible key k is in the range $[0, \dots, p-1]$

$$\mathbb{Z}_p = \{0, 1, \dots, p-1\} \text{ and } \mathbb{Z}_p^* = \{1, \dots, p-1\}$$

- Define the following hash function:

$$h_{a,b}(k) = ((ak + b) \bmod p) \bmod m, \forall a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p$$

- The family of all such hash functions is:

$$H_{p,m} = \{h_{a,b} : a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p\}$$

Important:

- a and b are chosen randomly at the beginning of execution.
- The class $H_{p,m}$ of hash functions is universal.

Example of Universal Hash

Proceed as follows:

- Choose a primer number p large enough so that every possible key k is in the range $[0, \dots, p-1]$

$$\mathbb{Z}_p = \{0, 1, \dots, p-1\} \text{ and } \mathbb{Z}_p^* = \{1, \dots, p-1\}$$

- Define the following hash function:

$$h_{a,b}(k) = ((ak + b) \bmod p) \bmod m, \forall a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p$$

- The family of all such hash functions is:

$$H_{p,m} = \{h_{a,b} : a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p\}$$

Important:

- a and b are chosen randomly at the beginning of execution.
- The class $H_{p,m}$ of hash functions is universal.

Example of Universal Hash

Proceed as follows:

- Choose a primer number p large enough so that every possible key k is in the range $[0, \dots, p-1]$

$$\mathbb{Z}_p = \{0, 1, \dots, p-1\} \text{ and } \mathbb{Z}_p^* = \{1, \dots, p-1\}$$

- Define the following hash function:

$$h_{a,b}(k) = ((ak + b) \bmod p) \bmod m, \forall a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p$$

- The family of all such hash functions is:

$$H_{p,m} = \{h_{a,b} : a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p\}$$

Important:

- a and b are chosen randomly at the beginning of execution.
- The class $H_{p,m}$ of hash functions is universal.

Example of Universal Hash

Proceed as follows:

- Choose a primer number p large enough so that every possible key k is in the range $[0, \dots, p-1]$

$$\mathbb{Z}_p = \{0, 1, \dots, p-1\} \text{ and } \mathbb{Z}_p^* = \{1, \dots, p-1\}$$

- Define the following hash function:

$$h_{a,b}(k) = ((ak + b) \bmod p) \bmod m, \forall a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p$$

- The family of all such hash functions is:

$$H_{p,m} = \{h_{a,b} : a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p\}$$

Important

- a and b are chosen randomly at the beginning of execution.
- The class $H_{p,m}$ of hash functions is universal.

Example of Universal Hash

Proceed as follows:

- Choose a primer number p large enough so that every possible key k is in the range $[0, \dots, p-1]$

$$\mathbb{Z}_p = \{0, 1, \dots, p-1\} \text{ and } \mathbb{Z}_p^* = \{1, \dots, p-1\}$$

- Define the following hash function:

$$h_{a,b}(k) = ((ak + b) \bmod p) \bmod m, \forall a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p$$

- The family of all such hash functions is:

$$H_{p,m} = \{h_{a,b} : a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p\}$$

Important

- a and b are chosen randomly at the beginning of execution.
- The class $H_{p,m}$ of hash functions is universal.

Example of Universal Hash

Proceed as follows:

- Choose a primer number p large enough so that every possible key k is in the range $[0, \dots, p - 1]$

$$\mathbb{Z}_p = \{0, 1, \dots, p - 1\} \text{ and } \mathbb{Z}_p^* = \{1, \dots, p - 1\}$$

- Define the following hash function:

$$h_{a,b}(k) = ((ak + b) \bmod p) \bmod m, \forall a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p$$

- The family of all such hash functions is:

$$H_{p,m} = \{h_{a,b} : a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p\}$$

Important

- a and b are chosen randomly at the beginning of execution.

The class $H_{p,m}$ of hash functions is universal.

Example of Universal Hash

Proceed as follows:

- Choose a primer number p large enough so that every possible key k is in the range $[0, \dots, p - 1]$

$$\mathbb{Z}_p = \{0, 1, \dots, p - 1\} \text{ and } \mathbb{Z}_p^* = \{1, \dots, p - 1\}$$

- Define the following hash function:

$$h_{a,b}(k) = ((ak + b) \bmod p) \bmod m, \forall a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p$$

- The family of all such hash functions is:

$$H_{p,m} = \{h_{a,b} : a \in \mathbb{Z}_p^* \text{ and } b \in \mathbb{Z}_p\}$$

Important

- a and b are chosen randomly at the beginning of execution.
- The class $H_{p,m}$ of hash functions is universal.


Example: Universal hash functions

Example

- $p = 977$, $m = 50$, a and b random numbers
 - ▶ $h_{a,b}(k) = ((ak + b) \bmod p) \bmod m$



Example of key distribution

Example, mean = 488.5 and dispersion = 5





Example with 10 keys

Universal Hashing Vs Division Method





Example with 50 keys

Universal Hashing Vs Division Method





Example with 100 keys

Universal Hashing Vs Division Method



Example with 200 keys

Universal Hashing Vs Division Method



Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - GetValue
 - Contains
 - Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

Overflow Handling

Overflow

An overflow occurs when the home bucket for a new pair (key, element) is full.

Overflow Handling

Overflow

An overflow occurs when the home bucket for a new pair (key, element) is full.

One strategy to handle overflow, small universe of keys

Search the hash table in some systematic fashion for a bucket that is not full.

- Linear probing (linear open addressing).
- Quadratic probing.
- Random probing.

Overflow Handling

Overflow

An overflow occurs when the home bucket for a new pair (key, element) is full.

One strategy to handle overflow, small universe of keys

Search the hash table in some systematic fashion for a bucket that is not full.

- Linear probing (linear open addressing).
- Quadratic probing.
- Random probing.

Another strategy, a large universe of keys

Eliminate overflows by permitting each bucket to keep a list of all pairs for which it is the home bucket.

- Array linear list.
- Chain

Overflow Handling

Overflow

An overflow occurs when the home bucket for a new pair (key, element) is full.

One strategy to handle overflow, small universe of keys

Search the hash table in some systematic fashion for a bucket that is not full.

- Linear probing (linear open addressing).
- Quadratic probing.
- Random probing.

Another strategy, a large universe of keys

Eliminate overflows by permitting each bucket to keep a list of all pairs for which it is the home bucket.

- Array linear list.
- Chain

Overflow Handling

Overflow

An overflow occurs when the home bucket for a new pair (key, element) is full.

One strategy to handle overflow, small universe of keys

Search the hash table in some systematic fashion for a bucket that is not full.

- Linear probing (linear open addressing).
- Quadratic probing.
- Random probing.

The other strategy, a large universe of keys

Eliminate overflows by permitting each bucket to keep a list of all pairs for which it is the home bucket.

- Array linear list.
- Chain

Overflow Handling

Overflow

An overflow occurs when the home bucket for a new pair (key, element) is full.

One strategy to handle overflow, small universe of keys

Search the hash table in some systematic fashion for a bucket that is not full.

- Linear probing (linear open addressing).
- Quadratic probing.
- Random probing.

The other strategy, a large universe of keys

Eliminate overflows by permitting each bucket to keep a list of all pairs for which it is the home bucket.

- Array linear list.

• Chain

Overflow Handling

Overflow

An overflow occurs when the home bucket for a new pair (key, element) is full.

One strategy to handle overflow, small universe of keys

Search the hash table in some systematic fashion for a bucket that is not full.

- Linear probing (linear open addressing).
- Quadratic probing.
- Random probing.

The other strategy, a large universe of keys

Eliminate overflows by permitting each bucket to keep a list of all pairs for which it is the home bucket.

- Array linear list.
- Chain.

Outline

1 Introduction

- Dictionary

2 Operation in a ADT dictionary

- The Operations
 - Add
 - Remove
 - GetValue
 - Contains
 - Iterators
- Other Operations
- Scenarios About the Keys

3 Example

- Using a Dictionary

4 Implementation

- How Do We Implement a Dictionary?
- Using an Linear List

5 Hash Tables

- Introduction
- Number of Keys
- Hash Functions

6 Overflow Handling

- Too Many Keys Repeat Buckets
- Chaining

Linear List Of Synonyms


Thus

- Each bucket keeps a linear list of all pairs for which it is the home bucket.
- The linear list may or may not be sorted by key.
- The linear list may be an array linear list or a chain.

Collision Handling: Chaining

A Possible Solution

Insert the elements that hash to the same slot into a linked list.



Example Sorted Chains

Add to a hash table with $m = 11$

Put in pairs whose keys are 6, 17, 12, 23, 28, 5, 16, 3, 8

So, we have

Home bucket = key % 11.

Example Sorted Chains

Add to a hash table with $m = 11$

Put in pairs whose keys are 6, 17, 12, 23, 28, 5, 16, 3, 8

So, we have

Home bucket = key % 11.

Example

The Table

6, 17, 12, 23, 28, 5, 16, 3, 8

0	
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	

Example

The Table

6, 17, 12, 23, 28, 5, 16, 3

A vertical number line is shown, ranging from 0 to 10. The numbers 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, and 10 are listed on the left side of the line. The line itself is a vertical bar with horizontal tick marks corresponding to each number. At the number 8, there is a small black dot on the line. An arrow points from this dot to a rounded rectangle. Inside the rectangle, the number 8 is written on the left, and a small black dot is on the right.

Example

The Table


6, 17, 12, 23, 28, 5, 16

0	
1	
2	
3	● → 3 ●
4	
5	
6	
7	
8	● → 8 ●
9	
10	

Example

The Table


6, 17, 12, 23, 28, 5



Example

The Table


6, 17, 12, 23, 28, 5



Example

The Table


6, 17, 12, 23, 28



Example


The Table

6, 17, 12, 23




Example

The Table




Example

The Table




Example

The Table





Example

The Table



Do You Remember This?

Universal Hashing Vs Division Method



Expected Complexity of Hash Table under Chaining

We have for unsuccessful search

$$U_n = O(1 + \alpha) \quad (2)$$

We have for successful search

$$S_n = O(1 + \alpha) \quad (3)$$

Expected Complexity of Hash Table under Chaining

We have for unsuccessful search

$$U_n = O(1 + \alpha) \quad (2)$$

We have for successful search

$$S_n = O(1 + \alpha) \quad (3)$$

Now, Back to the real world

java.util.Hashtable

- It uses unsorted chains.
- It uses a default initial $m = \text{divisor} = 101$
- It uses a default $\alpha \leq 0.75$
- When loading density exceeds a max permissible threshold, It rehash with new $m = 2m+1$.

Now, Back to the real world

java.util.Hashtable

- It uses unsorted chains.
- It uses a default initial $m = \text{divisor} = 101$
- It uses a default $\alpha \leq 0.75$
- When loading density exceeds a max permissible threshold, It rehash with new $m = 2m+1$.

Now, Back to the real world

java.util.Hashtable

- It uses unsorted chains.
- It uses a default initial $m = \text{divisor} = 101$
- It uses a default $\alpha \leq 0.75$
- When loading density exceeds a max permissible threshold, It rehash with new $m = 2m+1$.