

AVERAGE STATES ARIMAX MODEL - Influenza hospitalization data

Victor Felix

April 01, 2025

This function utilizes ensembles and single automatic ARIMAX models which have mean hospitalization on U.S. states as exogenous variables. The function fits on a rolling window of previous 104 weeks for the state under analysis and a rolling windows with the same size with 1 week-lag for the exogenous variables to generate forecasts. It return some metrics that evaluate the performance of the models: target_end_date, abs_error, cases, forecast, 'N_of_models', weighted interval score (WIS), predictive quantiles. The user can choose a single best automatic ARIMAXs (auto=TRUE), or ensembles of 27 permutations of 0,1,2 pdq's (ES27=TRUE) or 64 permutations of 0,1,2,3 pdq's (ES64=TRUE). The user also chooses the number of weeks ahead for each forecast, and the size of the rolling window which is set as 2 years (104 weeks).

```
knitr::opts_chunk$set(echo = TRUE)
```

!!!!!!!!!!!!!!!!!!!! LOADING THE DATASET !!!!!!!!!!!!!!!!!!!!!

```
library("tidyr")
library("MMWRweek")
library("data.table")
library("caret")
```

```
## Loading required package: ggplot2
```

```
## Loading required package: lattice
```

```
library("purrr")
```

```
##
```

```
## Attaching package: 'purrr'
```

```
## The following object is masked from 'package:caret':
```

```
##
```

```
## lift
```

```
## The following object is masked from 'package:data.table':
```

```
##
```

```
## transpose
```

```
library("dplyr")
```

```
##  
## Attaching package: 'dplyr'  
  
## The following objects are masked from 'package:data.table':  
##  
##     between, first, last  
  
## The following objects are masked from 'package:stats':  
##  
##     filter, lag  
  
## The following objects are masked from 'package:base':  
##  
##     intersect, setdiff, setequal, union
```

```
library("tseries")
```

```
## Registered S3 method overwritten by 'quantmod':  
##   method      from  
## as.zoo.data.frame zoo
```

```
library("gtools")  
library("forecast")  
library("scoringutils")
```

```
## Note: scoringutils is currently undergoing major development changes (with an update planned for the
```

```
library("covidHubUtils")  
library("parallel")  
library("future")#https://cran.r-project.org/web/packages/future/vignettes/future-4-issues.html
```

```
##  
## Attaching package: 'future'  
  
## The following object is masked from 'package:tseries':  
##  
##     value  
  
## The following object is masked from 'package:caret':  
##  
##     cluster
```

```
library("listenv")
```

```
##  
## Attaching package: 'listenv'
```

```
## The following object is masked from 'package:purrr':
##
##      map
```

```
library("epitools")
```

!!!!!!!!!!!!!!!!!!!!!!!!!!!! LOADING DATASET AND FUNCTIONS !!!!!!!!!!!!!!!!!!!!!!!!!!!!!

```
#####
#      LOADING AND CLEANING THE DATASET      #
#####

# Loads the AVERAGE states models
source("ES_AVERAGE_48.R", local = TRUE, chdir = TRUE)

# Loads the ILI dataset
my_data = read.csv("treated_influenza_hosp_dataframe_v2.csv")
my_data$target_end_date<-as.Date(my_data$target_end_date) # set the dates as dates

list_of_states <- split(my_data, my_data$state_name)
```

AUTO AVERAGE WEEK1 - ALL STATES

IF YOU WANT A FAST RESULT RUN ONLY THE AUTO_example, the others take longer.

```
start_time <- Sys.time()

AUTO_AVERAGE_WEEK1_list <- mclapply(list_of_states, ES_AVERAGE, auto=TRUE, n_weeks_ahead=1,list_of_states=list_of_states,
  setNames(names(list_of_states)))

end_time <- Sys.time()
run_time <- end_time - start_time

print(run_time)
```

Time difference of 7.705524 mins

```
# FINAL DATAFRAME
AUTO_AVERAGE_WEEK1 <- bind_rows(AUTO_AVERAGE_WEEK1_list, .id = "State")
```

AUTO AVERAGE WEEK2 - ALL STATES

```
start_time <- Sys.time()

# RUN MODEL
AUTO_AVERAGE_WEEK2_list <- mclapply(list_of_states, ES_AVERAGE, auto=TRUE, n_weeks_ahead=2,list_of_states=list_of_states,
  setNames(names(list_of_states)))

end_time <- Sys.time()
run_time <- end_time - start_time

print(run_time)
```

```
## Time difference of 7.711537 mins
```

```
# FINAL DATAFRAME
```

```
AUTO_AVERAGE_WEEK2 <- bind_rows(AUTO_AVERAGE_WEEK2_list, .id = "State")
```

AUTO AVERAGE WEEK3 - ALL STATES

```
start_time <- Sys.time()
```

```
AUTO_AVERAGE_WEEK3_list <- mclapply(list_of_states, ES_AVERAGE, auto=TRUE, n_weeks_ahead=3, list_of_states=list_of_states,
  setNames(names(list_of_states)))
```

```
end_time <- Sys.time()
```

```
run_time <- end_time - start_time
```

```
print(run_time)
```

```
## Time difference of 7.514967 mins
```

```
# Combine the list of data frames into a single data frame with names as a column
```

```
AUTO_AVERAGE_WEEK3 <- bind_rows(AUTO_AVERAGE_WEEK3_list, .id = "State")
```

AUTO AVERAGE WEEK4 - ALL STATES

```
start_time <- Sys.time()
```

```
AUTO_AVERAGE_WEEK4_list <- mclapply(list_of_states, ES_AVERAGE, auto=TRUE, n_weeks_ahead=4, list_of_states=list_of_states,
  setNames(names(list_of_states)))
```

```
end_time <- Sys.time()
```

```
run_time <- end_time - start_time
```

```
print(run_time)
```

```
## Time difference of 7.691914 mins
```

```
# Combine the list of data frames into a single data frame with names as a column
```

```
AUTO_AVERAGE_WEEK4 <- bind_rows(AUTO_AVERAGE_WEEK4_list, .id = "State")
```

```
save.image("AVERAGE_MODELS_influenza_hospitalization.Rdata")
```

ES27 AVERAGE WEEK1 - ALL STATES

```
start_time <- Sys.time()
```

```
ES27_AVERAGE_WEEK1_list <- mclapply(list_of_states, ES_AVERAGE, ES27=TRUE, n_weeks_ahead=1, list_of_states=list_of_states,
  setNames(names(list_of_states)))
```

```
end_time <- Sys.time()
```

```
run_time <- end_time - start_time
```

```
print(run_time)
```

```
## Time difference of 13.04053 mins
```

```
# FINAL DATAFRAME
```

```
ES27_AVERAGE_WEEK1 <- bind_rows(ES27_AVERAGE_WEEK1_list, .id = "State")
```

ES27 AVERAGE WEEK2 - ALL STATES

```
start_time <- Sys.time()
```

```
ES27_AVERAGE_WEEK2_list <- mclapply(list_of_states, ES_AVERAGE, ES27=TRUE, n_weeks_ahead=2, list_of_states=list_of_states,
  setNames(names(list_of_states)))
```

```
end_time <- Sys.time()
```

```
run_time <- end_time - start_time
```

```
print(run_time)
```

```
## Time difference of 12.88676 mins
```

```
# FINAL DATAFRAME
```

```
ES27_AVERAGE_WEEK2 <- bind_rows(ES27_AVERAGE_WEEK2_list, .id = "State")
```

ES27 AVERAGE WEEK3 - ALL STATES

```
start_time <- Sys.time()
```

```
ES27_AVERAGE_WEEK3_list <- mclapply(list_of_states, ES_AVERAGE, ES27=TRUE, n_weeks_ahead=3, list_of_states=list_of_states,
  setNames(names(list_of_states)))
```

```
end_time <- Sys.time()
```

```
run_time <- end_time - start_time
```

```
print(run_time)
```

```
## Time difference of 12.87422 mins
```

```
# FINAL DATAFRAME
```

```
ES27_AVERAGE_WEEK3 <- bind_rows(ES27_AVERAGE_WEEK3_list, .id = "State")
```

ES27 AVERAGE WEEK4 - ALL STATES

```
start_time <- Sys.time()
```

```
ES27_AVERAGE_WEEK4_list <- mclapply(list_of_states, ES_AVERAGE, ES27=TRUE, n_weeks_ahead=4, list_of_states=list_of_states,
  setNames(names(list_of_states)))
```

```
end_time <- Sys.time()
```

```
run_time <- end_time - start_time
```

```
print(run_time)
```

```
## Time difference of 12.94913 mins
```

```
# FINAL DATAFRAME
ES27_AVERAGE_WEEK4 <- bind_rows(ES27_AVERAGE_WEEK4_list, .id = "State")
```

```
save.image("AVERAGE_MODELS_influenza_hospitalization.Rdata")
```

ES64 AVERAGE WEEK1 - ALL STATES

```
start_time <- Sys.time()

ES64_AVERAGE_WEEK1_list <- mclapply(list_of_states, ES_AVERAGE, ES64=TRUE, n_weeks_ahead=1, list_of_states=list_of_states,
  setNames(names(list_of_states)))

end_time <- Sys.time()
run_time <- end_time - start_time

print(run_time)
```

Time difference of 37.8289 mins

```
# FINAL DATAFRAME
ES64_AVERAGE_WEEK1 <- bind_rows(ES64_AVERAGE_WEEK1_list, .id = "State")
```

ES64 AVERAGE WEEK2 - ALL STATES

```
start_time <- Sys.time()

ES64_AVERAGE_WEEK2_list <- mclapply(list_of_states, ES_AVERAGE, ES64=TRUE, n_weeks_ahead=2, list_of_states=list_of_states,
  setNames(names(list_of_states)))

end_time <- Sys.time()
run_time <- end_time - start_time

print(run_time)
```

Time difference of 36.9812 mins

```
# Combine the list of data frames into a single data frame with names as a column
ES64_AVERAGE_WEEK2 <- bind_rows(ES64_AVERAGE_WEEK2_list, .id = "State")
```

ES64 AVERAGE WEEK3 - ALL STATES

```
start_time <- Sys.time()

ES64_AVERAGE_WEEK3_list <- mclapply(list_of_states, ES_AVERAGE, ES64=TRUE, n_weeks_ahead=3, list_of_states=list_of_states,
  setNames(names(list_of_states)))

end_time <- Sys.time()
run_time <- end_time - start_time

print(run_time)
```

```
## Time difference of 37.312 mins
```

```
# Combine the list of data frames into a single data frame with names as a column  
ES64_AVERAGE_WEEK3 <- bind_rows(ES64_AVERAGE_WEEK3_list, .id = "State")
```

ES64 AVERAGE WEEK4 - ALL STATES

```
start_time <- Sys.time()
```

```
ES64_AVERAGE_WEEK4_list <- mclapply(list_of_states, ES_AVERAGE, ES64=TRUE, n_weeks_ahead=4, list_of_states = list_of_states,  
  setNames(names(list_of_states)))
```

```
end_time <- Sys.time()
```

```
run_time <- end_time - start_time
```

```
print(run_time)
```

```
## Time difference of 37.05493 mins
```

```
# Combine the list of data frames into a single data frame with names as a column  
ES64_AVERAGE_WEEK4 <- bind_rows(ES64_AVERAGE_WEEK4_list, .id = "State")
```

```
save.image("AVERAGE_MODELS_influenza_hospitalization.Rdata")
```