

# API for Shongo

Petr Holub, Jan Růžička, Miloš Liška, Martin Šrom, Ondřej Pavelka, Ondřej Bouda

© CESNET z. s. p. o.  
2012

# Contents

<b>1</b>	<b>Use Cases</b>	<b>3</b>
1.1	Common . . . . .	3
1.2	Resources . . . . .	3
1.3	Reservations . . . . .	4
1.4	Operations . . . . .	8
1.4.1	Room Management . . . . .	8
1.5	Monitoring & Management . . . . .	10
1.5.1	Shongo management and monitoring . . . . .	10
1.5.2	Server management and monitoring . . . . .	11
<b>2</b>	<b>Common Data Types and Object Classes</b>	<b>12</b>
2.1	Failure Related . . . . .	12
2.2	Security and Identity Related . . . . .	13
2.3	Time Related . . . . .	14
2.4	Other . . . . .	15
2.5	XML-RPC . . . . .	16
<b>3</b>	<b>Controller API Specification</b>	<b>17</b>
3.1	Data types . . . . .	17
3.2	Common . . . . .	23
3.3	Resources . . . . .	23
3.3.1	Failures . . . . .	24
3.4	Reservations . . . . .	24
3.4.1	Failures . . . . .	25
3.5	Room Operations . . . . .	25
3.5.1	Failures . . . . .	25
<b>4</b>	<b>Connector API Specification</b>	<b>26</b>
4.1	Communication Protocol . . . . .	26
4.2	Data Types . . . . .	27
4.3	Common API . . . . .	30
4.4	Multipoint Device . . . . .	30
4.4.1	Room Management . . . . .	30
4.4.2	User Management . . . . .	31
4.4.3	Room Content Management . . . . .	32
4.4.4	Monitoring . . . . .	32
4.4.5	Recording . . . . .	32
4.5	Endpoint Device . . . . .	33

4.6 Technology Specific API . . . . .	33
<b>5 Inter-Controller API Specification</b>	<b>34</b>
<b>A User Interface API Usage</b>	<b>35</b>
A.1 Perl programming language . . . . .	35
A.1.1 Connect to Controller . . . . .	35
A.1.2 Create reservation . . . . .	36
A.1.3 Modify reservation . . . . .	37
A.1.4 List reservations . . . . .	38
A.1.5 Exception handling . . . . .	39
<b>B JADE Command Encoding Example</b>	<b>42</b>

# Chapter 1

## Use Cases

### 1.1 Common

#### UC-1 (com:identification) Entity identification

Each entity in Shongo (e.g., resource, or reservation) is identified by a unique identifier. The identifier follows the URI standard [1]:

`shongo:<domain>(.<subdomain>)*:<id>`

The <domain> component represents the full name of a **domain** to which the entity belongs (or where it was created in case of reservation). Each **domain** will run its own controller platform. The <id> component represents an identification of the entity in the specified domain.

### 1.2 Resources

#### UC-2 (res:types) Types of resources

Basic resource types include the following:

**A managed endpoint** This is an endpoint, that is managed by Shongo – the endpoint is both managed (calls are automatically dialed when involved in reservation, directory is updated, etc.) and monitored (availability and status).

**A unmanaged endpoint** This is an endpoint, which is not available for Shongo management for either technical or administrative reason. It may be, e.g., a software H.323 client or web browser acting as a Adobe Connect client. Its specification by a user (e.g., providing attributes like H.323 number or H.323 ID), however, allows for specific adjustments during implementation of the reservation – e.g., monitoring of participants in the calls and allowing only participants calling from specific H.323 number or ID.

**A managed infrastructure element** This is one of the infrastructure resources, that is managed, monitored and typically also scheduled by the Shongo. It includes things such as H.323 MCUs, H.323 gatekeepers, Adobe Connect servers, recording servers, streaming servers, and various types of gateways and translators.

**A virtual room** A virtual room is a private compartment on a specific multi-point infrastructure element. Typically, this is comes as a product of a scheduling process. Virtual

rooms are often not licensed, only their participants are (this is a concurrent user license model). However, other models may also exist and this abstraction allows for them.

**A license** This is typically the limiting factor of infrastructure elements in a concurrent user licensing model. Utilization of the licenses is scheduled by Shongo, while some licenses may be put aside as a part of permanent reservations by a resource owner (see UC-10).

**A physical room** This is a representation of a physical meeting room and Shongo thus allows for reserving physical rooms. Its representation among the resources enables also more advanced uses: a physical room may contain multiple videoconferencing devices and reserving a room also means that those devices become unavailable for other reservations than the one which contains the physical room.

**A specific identifier** A user may reserve a specific identifier, typically Adobe Connect URL, H.323 number, or streaming server URL. This allows for reuse of such an identifier in irregularly recurring and *ad hoc* events.

### UC-3 (res:management) Management of resources

The resource owner should be able to create new resources that will be managed by Shongo. Owner should be able to modify the managed resource parameters and also should be able to delete the managed resource.

### UC-4 (res:identification) Resource identification

Each resource is identified by a unique identifier as defined in UC-1. The identifier will be automatically assigned to the resource when it is being created.

## 1.3 Reservations

### UC-5 (rsv:specifications) Types of specifications

Specification of a resource, being object of a reservation, may be of the following types:

- a *fully-qualified explicit specification (FQESpec)* – specifies exactly one element; it may refer to a specific device (e.g., H.323 endpoint, web browser as an endpoint for Adobe Connect), a specific server (e.g., a specific Adobe Connect server or H.323 MCU), a specific physical room, or a specific virtual room (e.g., a specific room running on specific H.323 MCU),

FQESpec may be managed by Shongo or not; for resources that Shongo does not manage or knows about, i.e., unmanaged resources, the user needs to specify type of the resource (e.g., generic H.323 endpoint). The unmanaged resources should have some form of identification (e.g., H.323 number, H.323 ID, or Shibboleth identity for Adobe Connect) so that Shongo can verify if they are connected to the virtual room or not during the conference.

Anonymous unmanaged resources may also be available (completely generic H.323 endpoint without a number or H.323 ID, or guest user in Adobe Connect), but some functionality may not be available – when maximum room capacity is achieved (or exceeded), anonymous users not be allowed in (or even be disconnected in LIFO mode until maximum amount of participants is obeyed).

- a *partially-qualified explicit specification (PQESpec)* – specifies a class/type of a resource (e.g., H.323 endpoint) and it is up to the scheduling to find suitable one (combination of availability and access-level for given user),
- a *implicit specification (ISpec)* – the user does not specify such a resource, but the resource is needed to implement user's request (e.g., if user specifies Connect and H.323 endpoints, a gateway/connector is needed to implement the translation; if user specifies multiple H.323 endpoints beyond MCU-capability of each of them, some MCU is needed to be included).

Generally, Shongo should use the technology to limit number of participants in the rooms created based on the reservations—e.g., H.323 MCUs allow for setting an upper limit on number of participant in each room.

#### UC-6 (rsv:roles) User roles

Each reservation should have at least two types of possible user roles:

- *owner/administrator*, who can modify or even delete the reservation,
- *manager*, who can control the room (e.g., disconnect participants, mute participants, etc.),
- *participant*, who can only view the reservation including coordinates necessary for participation.

The roles can be delegated, which is important especially in case of owner/administrator: the original reservation creator can delegate this role to other users and any of them can then modify or delete the reservation.

#### UC-7 (rsv:identification) Reservation identification

Each reservation is identified by a unique identifier as defined in UC-1. The identifier is assigned to reservation automatically when it is being created.

#### UC-8 (rsv:reservation:one) One time reservation

Common type of reservation, where a user requests certain resources for limited time duration. Unlimited reservations are not assumed by this scenario (see UC-10).

Start time of a reservation may be any time in the future or *now*, which is also called *ad hoc* reservation.

Reserved resources may be given as FQESpec, PQESpec, or ISpec. FQESpec are either accepted or denied by the scheduler, while other types of the specifications are looked for their best match. PQESpec may include the following:

- user may request a general endpoint and Shongo should try to find the closest matching endpoint available to the user (e.g., user requests a H.323 endpoint for a conference since she has no personal endpoint, and she is assigned a room-based H.323 endpoint provided the room is available),

while examples of ISpec are as follows:

- amount of central resources (such as H.323 MCU ports or Connect licenses) based on specified number of (H.323/SIP or web-browser) participants,

- any interconnecting elements (e.g., gateways) to interconnect the endpoints specified by the user; if only part of the endpoints can be interconnected, the user should be notified what parts can be interconnected and what parts are disconnected.

Each reservation has to be given a unique identifier that is further used for any references to it. If the reservation is denied, reasons for denying should be communicated to the requester. In case that the reservation succeeds, all the users involved should be notified.

Each reservation has to include:

- unique identifier,
- timespan definition,
- requester's identifier,
- name,
- links to the resources involved, including specification of the amount of resources consumed,
- list of users involved.

Reservations may be compounded to form another reservation. This allows to reuse elements that are already reserved (e.g., a specified identifier or allocation of a physical room) to implement a larger reservation. As a part of the scheduling process, the scheduler has to check whether the reservation times and durations are compatible.

#### **UC-9 (rsv:reservation:periodic) Periodic reservation**

UC-8 extended with periodicity. Expressiveness of the periodicity language should be equivalent to cron plus start time, stop time or number of repetition, and explicit lists for recurring aperiodic requests.

#### **UC-10 (rsv:reservation:permanent) Permanent reservation**

This is specific type of reservation that can be only made by an owner of the resource as it permanently removes the reserved capacity from the dynamic Shongo scheduling.

Even permanent reservations must not threaten what has already been reserved for any user. In case of priority requests (see UC-11), Shongo must be able to migrate the reservation to other resources.

The difference between permanent and periodic reservation is that for permanent reservations is not applied the maximum future time as defined in UC-12. The permanent reservation also has bigger priority than periodic reservation (e.g., in scheduler input queue).

#### **UC-11 (rsv:priority) Priority reservations**

Priority reservations are only allowed by an owner of the resources and they may affect reservations already present on the resources. However, priority reservation should only be allowed if there is some other resource(s) (maybe even in another domain) that can take over the prior reservation. In case of reservation migration, all the involved users must be notified (see UC-17).

**TODO: We need to decide, whether to allow this or not.**

#### **UC-12 (rsv:max-future) Maximum future time for reservations**

Each resource owner should set a date/time limit in the future (e.g., 2 months), above which reservations are not allowed. That should be done for each owned resource. Whole reservation duration must fit in that limit. This limit ensures there is some time point in the future, where there are no reservations on the resource—e.g., for maintenance purposes, removal of the device, special events the device will be used for, etc.

#### **UC-13 (rsv:lookup:time) Lookup available time**

User may look up available time slots for given amount of requested resources, with either inter-domain negotiation turned off or on (i.e., tell the user when resources are available within the domain or when merging resources of all the domains).

#### **UC-14 (rsv:list) List all the reservations**

Some querying/filtering language needs to be supported to limit list to

- room types (H.323, SIP, Connect, etc.),
- equipment (be it class of equipment or a specific device).
- reservation owner(s),
- users involved (may be humans as well as resources, such as rooms with equipment) involved in the room as participants.

#### **UC-15 (rsv:modify) Modification of a reservation**

Any attribute of a reservation may be requested to change. The request may be accepted or denied by the scheduler. In case of the denial, reasons for denial should be communicated to the requester. If the modification succeeds, all the users involved should be notified.

#### **UC-16 (rsv:release) Release/canceling of a reservation**

All the users involved should be notified.

#### **UC-17 (rsv:migration) Migration of a reservation**

If the change is visible to the users (e.g., typically this would include change of the server/MCU the users connect to), all the users involved should be notified.

#### **UC-18 (rsv:notification) Notification of participants**

In case of making, modifying, or canceling a reservation, all the users involved should be notified, as specified in UC-8, UC-9, UC-10, UC-15, UC-16, and UC-17. By default, the users should be notified via email, but it would be interesting to provide also SMS notification service.

#### **UC-19 (rsv:service-users) Reservations of rooms, public or semi-private endpoints, etc.**

Each reservation may include endpoint resources (beyond human users with private endpoints—H.323/SIP/web), which represent entities such as rooms, non-personal endpoints, etc., that can be scheduled in a similar way to central resources.



This type of reservation may be either part of some infrastructure reservation (see UC-8, UC-9, UC-10) or standalone reservation (e.g., reservation of a meeting room with H.323 equipment to disable the room from scheduling for given time duration).

#### **UC-20 (rsv:recording) Reservation of recording capacity**

Usually part of some infrastructure reservation (see UC-8, UC-9, UC-10), but may be completely standalone in case that only recording server is used of the Shongo-managed infrastructure.

#### **UC-21 (rsv:streaming) Reservation of streaming capacity**

May part of some infrastructure reservation (see UC-8, UC-9, UC-10), but may be completely standalone in case that only streaming server is used of the Shongo-managed infrastructure.

## **1.4 Operations**

#### **UC-22 (ops:migration) Live migration of a virtual room**

This use case is intended for migration due to planned server maintenance or unplanned server outage. Ideally, all the room settings and content should be transferred to the target room—but some content may be lost in case of unplanned server failure (namely content migration).

Being able to transfer room settings to another server in case of unplanned failure also requires that the settings needs to be stored in the Shongo middleware.

Clients should be automatically redirected to the new server, if technology permits, or at least notified of the migration (email, SMS—see UC-18).

Some functionality will be common UC-17.

### **1.4.1 Room Management**

#### **UC-23 (ops:room:shongo-options) Get room information on Shongo level**

This information typically includes name, owner, date/periodicity, duration and type.

#### **UC-24 (ops:room:users-list) List users**

Each user should be given a unique identifier in the output list that can be used for further querying. It should also provide means to identify the same user (e.g., if the user disconnects–reconnects, it should contain a part that is common and that denotes the specific user and a part that is specific for the session, so that if the user is connected twice (one session is in timeout state and the other session has just been established), we can differentiate between the two sessions).

#### **UC-25 (ops:room:user-info) Print detailed info about a user in a room**

Print all the statistics we can get about a user participating in the room. It should contain technology agnostic part (e.g., when the user joined) and technology specific part (i.e., H.323 statistics, H.245/SIP capabilities negotiation info, H.239 content information, etc.).

**TODO:** Could the use case be more specific regarding the technology specific part? What does H.323 statistics and others look like? Should a class be defined for each such a technology-specific information?

#### **UC-26 (ops:room:layout) Set room layout**

Shongo should be able to set up global layout of a room and user-specific layout, if available through API of virtual room provider.

#### **UC-27 (ops:room:user-disconnect) Disconnect a user**

Immediate disconnection of a user.

#### **UC-28 (ops:room:disable-user-content) Disable H.239 content from a specific user**

Disable content the user to be H.239 content provider for the given room.

#### **UC-29 (ops:room:specific-user-content) Enable H.239 content only from a specific user**

Enable H.239 content only from the specific user, typically by disabling content from all other users. Normally, users may fight who is going to be the content provider.

#### **UC-30 (ops:room:user-mute) Mute a user**

Mutes user on the room level. Optionally if user's endpoint is also controlled by Shongo, it should provide means to mute the endpoint (which can be easily unmuted by the user).

#### **UC-31 (ops:room:user-miclevel) Set microphone audio level for a user**

Sets the audio from the user on the room level. Optionally, if user's endpoint is also controlled by Shongo, it should provide means to control mic level on the endpoint. In this case, audio should be normalized on the endpoint before doing modifications on room level (if the sound is too low or too high and distorted, it may not be corrected on the MCU).

#### **UC-32 (ops:room:user-playlevel) Set playback audio level for a user**

This functionality is typically available only when user's endpoint is also controlled by Shongo.

#### **UC-33 (ops:room:user-video-off) Disable video of a user**

#### **UC-34 (ops:room:user-video-snap) Video snapshot for a user**

If provided by the room provider (MCU, web conferencing, etc.), we should be able to get video snapshot of:

- video sent by the user,
- video received by the user.

**UC-35 (ops:room:user-layout) Set layout specific for a user**

**TODO:** How does this use-case differ from use-case 26? Is this use-case a subset of use-case 26, which mentions also user-specific layout?

**UC-36 (ops:room:settings-down-up) Download and upload room settings**

We should provide an API that allows for downloading settings of the room to the maximum extent possible, in order to back it up and reupload it later on. This is a convenient way to back up setting as well as to reset a newly created room (e.g., as a part of a new reservation) to old settings.

**UC-37 (ops:room:content-down-up) Download and upload room content (if technology permits)**

If technology and access policy permits, we should be able to download and upload content of the room (e.g., documents, notes, polls, etc.). See UC-36.

**UC-38 (ops:room:room-techspec) Get/set technology-specific properties for a room**

This may include specific attributes of the room (typically on room provider level), such as enabled codecs.

**UC-39 (ops:room:user-techspec) Get/set technology-specific properties for a user**

**UC-40 (ops:recordings-management) Management of recording archives**

It should be possible to work with the recorded video through Shongo, e.g., migrate it from a content server to a storage of a streaming server. Plus it should be possible for owner/administrator or manager to access URLs of the recorded content to send them via email. Also, it should be possible to automatically notify all the (non-anonymous) participants about the recording via email.

## **1.5 Monitoring & Management**

### **1.5.1 Shongo management and monitoring**

**UC-41 (mgmt:shng:list-agents) List of all the agents in the system**

The listing API must include querying language that allows selection of only a subset based on similar properties like those defined in UC-14.

**UC-42 (mgmt:shng:list-controllers) List primary and backup controllers**

List all the controllers (primary and backup) for current domain.

#### **UC-43 (mgmt:shng:list-domains) List domains**

List of all other known domains including references to their domain controllers and state of connections to them.

### **1.5.2 Server management and monitoring**

#### **UC-44 (mgmt:srv:get-load) Get server load**

The API should provide means to get load on the server machine, containing at least the following:

- CPU load
- memory load
- disk occupancy

Obviously, this information may or may not be available for specific device. In case that the information is not available, the API should report this in a consistent way (specific exception or unique return value).

#### **UC-45 (mgmt:srv:schedule-downtime) Schedule server downtime**

Downtime scheduling must include change/migration of all the reservations and live events influenced by the downtime. Conceptually, this is similar to permanent reservations a bit (UC-10)—the major difference is that during the downtime, the resource is not available to Shongo for management and this state is intentional. Downtime is also per-resource and does not have participants.

#### **UC-46 (mgmt:export-stats) Export Shongo stats**

Export reservation stats in some common format like CDR. **TODO: Specify in more detail - what stats?**

## Chapter 2

# Common Data Types and Object Classes

In this chapter common atomic types, enum types and object classes for Shongo API are described. At the end of the chapter there is described a mapping to XML-RPC of introduced data types.

### 2.1 Failure Related

Each failure in API is reported by **faultCode** (number value) and **faultString** (description text). List of common faults:

- **faultCode = 0**  
Unknown fault which is described by **faultString**.
- **faultCode = 10**  
The class is not defined, the **faultString** specifies which class.
- **faultCode = 11**  
The class cannot be instantiated, the **faultString** specifies which class.
- **faultCode = 12**  
The attribute is not defined, the **faultString** specifies which attribute in which class.
- **faultCode = 13**  
The attribute type is wrong, the **faultString** specifies which attribute in which class and also it specifies the present and required type.
- **faultCode = 14**  
The attribute wasn't present and is required, the **faultString** specifies which attribute in which class.
- **faultCode = 15**  
The collection is empty and is required, the **faultString** specifies which collection in which class.
- **faultCode = 16**  
The attribute was present but is read-only, the **faultString** specifies which attribute in which class.
- **faultCode = 17**  
Wrong value for attribute was present, the **faultString** specifies which value in which attribute in which class.
- **faultCode = 20**

The value of an enum attribute is wrong, the **faultString** specifies which value.

- **faultCode = 21**  
Failed to parse date/time value, the **faultString** specifies which date/time value.
- **faultCode = 22**  
Failed to parse period value, the **faultString** specifies which period value.
- **faultCode = 23**  
Failed to parse interval value, the **faultString** specifies which interval value.
- **faultCode = 24**  
Failed to parse partial date/time value, the **faultString** specifies which partial date/time value.
- **faultCode = 30**  
Item with wrong type was present in collection, the **faultString** specifies which item in which collection and types which are allowed.
- **faultCode = 31**  
Null value cannot be used as item in collection, the **faultString** specifies which collection.
- **faultCode = 40**  
Entity was not found, the **faultString** specifies which entity.
- **faultCode = 41**  
Entity validation failed, the **faultString** specifies which entity.
- **faultCode = 99**

The request is not implemented yet. An application log must be checked for more details.

These are only common faults that are independent on specific API section. Other business logic faults can be generated and are described in appropriate API section.

## 2.2 Security and Identity Related

- **class** `UserIdentity`

Each user that accesses shongo or participates in shongo managed videoconference should be identified by `UserIdentity` definition.

Attributes:

- **String id (Required)**  
Equals to eduID identity. In future there can be unique identifier that associates multiple eduID for the same person.

**TODO: Consider usage of Person instead of UserIdentity or vice versa**

- **class** `SecurityToken`

Contains identity and credentials of a user performing the requested operation.

Attributes:

- **TODO: Authorization data**

- **class** `Person`

Represents a person that can access a Shongo videoconference.

Attributes:

- **String name (Required)**  
Name to be displayed.
- **String email (Required)**  
Email to which a videoconference invitation should be sent.

## 2.3 Time Related

- **atomic\_type Period = String**

Used for representing period or duration. Format is specified by ISO8601 period (e.g., P3Y6M4DT12H30M5S which is *3 years, 6 months, 4 days, 12 hours, 30 minutes, and 5 seconds* or P4W which is *4 weeks*). The first character "P" means period and it comes from the ISO8601 standard. Components can be omitted (e.g., P3YT12H which is *3 years and 12 hours*). The zero duration is represented by PT0S value (which is *0 seconds*).

**Example:** We want to set videoconference duration:

```
duration = PT2H
```

- **atomic\_type DateTime = String**

Used for representing an absolute date/time. Format is specified by ISO8601 date/time in UTC (e.g., 20120130T10:09:55) or with explicit timezone specification (e.g., 20120130T10:09:55+02:00).

**Example:** We want to create a new reservation for resources at the precise date. We can specify it by **DateTime**:

```
dateTime = 2012-12-31T12:00
```

- **atomic\_type RelativeDateTime = Period**

Used for representing a relative date/time. Relative date/time can be evaluated to absolute date/time by specifying a referenced absolute date/time.

**Example:** We want to define a maximum future to which a resource can be scheduled. We can specify it by **RelativeDateTime** as follows:

```
relativeDateTime = P4M
```

The relativeDateTime can be evaluated by using reference date/time 2012-01-01T00:00 to 2012-05-01T00:00.

- **class PeriodicDateTime**

It can be used for events that takes place repeatedly, but also for events that take place only once.

**Attributes:**

- **DateTime start (Required)**  
Defines the first occurrence of an event.
- **Period period (Optional)**  
Defines the period in which the repeated events take place. See **Period** for format specification.
- **DateTime end (Optional)**  
Ending date/time for events to not occur forever (not required, we can specify infinite periodic date/time).
- **Rule[] rules (Optional)**

List of rules, which can define an extra events out of the periodicity or cancel specified periodical events. **Rule** can be one of the following types:

- \* **Enable/Disable** event(s) in the specified **dateTime** or interval by **start** and **end**.
- \* **Extra** event in the specified **dateTime**

Rules contains implicit definition of **Enable** rule for whole **PeriodicDateTime** interval. Conflicts are solved by *last-match* policy.

**Example:** Only one lecture on 20.3.2012.

```
periodicDateTime.start = 20110908T12:00:00
```

**Example:** A lecture on every Thursday at 12:00 with extra lecture on 20.3.2012 and Christmas holidays.

```
periodicDate.start = 20110908T12:00:00
periodicDate.period = P1W
periodicDate.end = 20120631
periodicDate.rules = {
    { type = Disable, from = 20111219, to = 20120101 },
    { type = Extra, dateTime = 20120320 }
}
```

- **atomic\_type** Interval = String

Represents the time between two instants. Values must be in format <start>, <duration> where <start> is in **DateTime** format and <duration> in **Period** format.

## 2.4 Other

- **enum** Technology

Enumeration of supported (or planned to be supported) videoconference technologies.

Enumeration values:

- H323
- SIP
- ADOBE\_CONNECT
- SKYPE
- BIG\_BLUE\_BUTTON
- OPEN\_MEETING
- WEBEX

- **class** RoomUser

Represents an active user in a virtual room on a server.

Attributes:

- **String** **userId** (**ReadOnly**)  
User identification in room (technology specific).
- **String** **roomId** (**ReadOnly**)  
Room unique identifier. **TODO:** The identifier should contain a part denoting the user and a part denoting his/her session - as requested by use case 24. resolved on the **UserIdentity** level
- **UserIdentity** **userIdentity** (**ReadOnly**)



User identity which in some cases may be null (e.g., when the user is calling from cell phone).

- **DateTime joinTime (ReadOnly)**  
Date and time when the user joined the room.
- **boolean muted (ReadOnly)**  
Is the user muted?
- **int microphoneLevel (ReadOnly)**  
Microphone level.
- **int playbackLevel (ReadOnly)**  
Playback level (speakers volume)
- **RoomLayout layout (Optional)**  
User layout, overriding the room default layout.

## 2.5 XML-RPC

In XML-RPC types are represented as follows:

- Values of atomic types are represented by their's equivalent in XML-RPC (e.g., integer value 42 as `<i4>42</i4>` or string value Hello as `<string>Hello</string>`).
- Enum values are represented as strings (e.g., `ReservationRequestType.PERMANENT` as `<string>PERMANENT</string>`).
- Arrays are represented as XML-RPC **arrays**, e.g.

```
[101, 202]                                <array><data>
                                           <value><i4>101</i4></value>
                                           <value><i4>202</i4></value>
                                           </data></array>
```

- Object instances are represented as XML-RPC **struct** types with special class attribute specifying object type, e.g.

```
Person {                                <struct>
  name: "Martin Srom",                  <member>
  email: "srom@cesnet.cz"              <name>class</name>
}                                       <value><string>Person</string></value>
                                     </member>
                                     <member>
                                     <name>name</name>
                                     <value><string>Martin Srom</string></value>
                                     </member>
                                     <member>
                                     <name>email</name>
                                     <value><string>srom@cesnet.cz</string></value>
                                     </member>
                                     </struct>
```

- Null values are represented as empty XML-RPC **struct** type (`<struct></struct>`). It is useful e.g., when the user want to clear attribute value by any **modify** API method. He should set the attribute value to empty **struct** and the value will be cleared on the server.
- Failures are propagated through XML-RPC by **faultCode** and **faultString** values.

## Chapter 3

# Controller API Specification

### 3.1 Data types

- **class** Controller

Information about the domain controller.

Attributes:

- **Domain domain** (**ReadOnly**)  
Domain which is controlled by the controller.

- **enum** Status

Status of domain/connector.

Enumeration values:

- **AVAILABLE**  
Means that domain/connector is available to controller.
- **NOT\_AVAILABLE**  
Means that domain/connect is not currently available to the controller.

- **class** Domain

Information about a domain.

Attributes:

- **String name** (**Required**)  
A unique domain name.
- **String organization** (**Optional**)  
Organization owning the domain.
- **Status status** (**Required**)  
Status whether the domain controller is available.

- **class** Connector

Information about a connector which is managing a resource.

Attributes:

- **String name** (**ReadOnly**)

A unique connector name within the domain (Jade agent name).

- **String resourceIdentifier** (**ReadOnly**)  
Identifier of a resource which is managed by the connector.
- **Status status** (**Required**)  
Status whether the connector is available.

- **class DateTimeSlot**

Date/time slot can represent one or more **Interval** values. Definition of date/time slot is a pair of starting date/time and duration, where starting date/time can be periodic and thus can result into multiple absolute date/times.

**Attributes:**

- **DateTime|PeriodicDateTime start** (**Required**)  
Defines the start of date/time slot (or multiple starts in case of periodic date/time).
- **Period duration** (**Required**)  
Defines the duration of date/time slot.

For reservation purposes, the array **DateTimeSlot[]** should be used to provide the ability to reserve multiple date/times with different periods (e.g., on every Monday from 14:00 to 15:00 and every Thursday from 16:00 to 18:00).

If date/time slot contains **PeriodicDateTime**, all periodic events can be listed by evaluating date/time slot to **Interval[]**.

- **enum AliasType**

Enumeration for types of **Aliases**.

**Enumeration values:**

- **E164**  
See <http://en.wikipedia.org/wiki/E.164>.
- **IDENTIFIER**  
e.g., H.323 ID.
- **URI**  
e.g., H.323 or SIP URI.

- **class Alias**

Represents an alias for a video conferencing device.

**Attributes:**

- **Technology technology** (**Required**)  
Technology of the alias.
- **AliasType type** (**Required**)  
Type of the alias.
- **String value** (**Required**)  
Value of the alias.

- **enum CallInitiation**

Represents enumeration of who should initiate a video conference call.

**Enumeration values:**

- **TERMINAL**

A terminal should initiate the call to a virtual room.

- **VIRTUAL\_ROOM**

A virtual room should initiate the call to a terminal.

- **class Capability**

Base class for all specific capabilities which a device resource can support. A device resource can support zero, one or multiple capabilities.

Attributes:

- **Set<Technology> technologies (Required)**

Set of technologies for which the capability is supported by the device. If the set is empty all device technologies are supported.

- **class Resource**

This class represents a complete resource definition. This class is used for creating and modifying resources.

Attributes:

- **String identifier (Required)**

Resource unique identifier as defined in UC-4.

- **String parentIdentifier (Optional)**

A parent resource identifier in which is the resource located (e.g., identifier of a physical room).

- **String name (Required)**

Short name which describes the resource.

- **Set<Technology> technologies (Required)**

Set of technologies which are supported by the resource. If the set is not empty the resource is considered as device resource and thus it can participate in videoconferences.

- **Capability[] capabilities (Optional)**

Capabilities of the resource.

- **String description (Optional)**

Long description depicting the resource.

- **boolean allocatable (Optional, default: false)**

Specifies whether the resource can be allocated to a reservation by a scheduler. When creating a new resource, it is useful to set **allocatable** to false and restrict the time when the resource can be used for public scheduling (e.g., setup permanent reservations) and then modify the **allocatable** to true.

- **DateTime maxFuture (Optional)**

The maximum future time for reservations as defined in UC-12.

- **String[] childResourceIdentifiers (Optional)**

List of child resources identifiers (e.g., the resource is physical room and **childResourceIdentifiers** contains all videoconferencing devices in the room).

- **class VirtualRoomsCapability extends Capability**

Capability for devices which allows for creating virtual rooms for connecting multiple endpoints (e.g., H.323 MCU will support **VirtualRoomsCapability**).

Attributes:

- **Integer portCount (Required)**

Maximum number of ports which can be allocated for all virtual rooms.

- **class ResourceSummary**

This class represents a summary of a resource. The summary of resource is lightweight and does not contain all resource attributes. It contains some useful additional "calculated" attributes. It is suitable when listing a lot of resources from controller database where the detail information about resource is not appropriate.

Attributes:

- **String identifier (ReadOnly)**  
Resource unique identifier.
- **String name (ReadOnly)**  
Resource name which can be displayed.
- **String technologies (ReadOnly)**  
Enumeration of supported technologies (separated by comma).
- **String parentIdentifier (Optional)**  
A parent resource identifier in which is the resource located.

- **enum ReservationRequestType**

Enumeration values:

- **NORMAL**  
One time or periodic reservation as defined in UC-8 and UC-9 (one time reservation is a special case of periodic reservation).
- **PERMANENT**  
Permanent reservation as defined in UC-10.

- **enum ReservationRequestPurpose**

Enumeration values:

- **SCIENCE**  
Reservation will be used for research purposes.
- **EDUCATION**  
Reservation will be used for education purposes (e.g., for a lecture).

- **class AbstractReservationRequest**

This class represents a base class for all specific reservation requests. It contains only common attributes for all reservation requests.

Attributes:

- **String identifier (ReadOnly)**  
Reservation request unique identifier as defined in UC-7.
- **DateTime created (ReadOnly)**  
Date/time when the reservation request was created.
- **ReservationRequestType type (Required)**  
Type of reservation request, see **ReservationRequestType**.
- **String name (Required)**  
Name of reservation request.
- **ReservationRequestPurpose purpose (Required)**  
Purpose of reservation request, see **ReservationRequestPurpose**.
- **String description (Optional)**  
Long reservation description.
- **boolean interDomain (Optional, default: false)**

Specify whether the scheduler should try allocate resources from other domains.

- **class** `ReservationRequestSet` **extends** `AbstractReservationRequest`

Represents a request for one or multiple reservations. It specifies one or more date/time slots and one or more specifications and for each combination (slots x specifications) will be created one `ReservationRequest`.

Attributes:

- `List<DateTimeSlot> slots` (**Required**)  
List of requested `slots`.
- `List<Specification> specifications` (**Required**)  
List of requested `specifications`.
- `List<ReservationRequest> reservationRequests` (**Required**)  
List of already created `reservationRequests`.

- **class** `ReservationRequest` **extends** `AbstractReservationRequest`

Represents a reservation request for single specification at one specific date/time slot. It represents a minimum unit which is processed by the Scheduler and which is allocated to a `Reservation`.

Attributes:

- `Interval slot` (**Required**)  
Requested date/time `slot`.
- `Specification specification` (**Required**)  
Requested `specification` for a target which should be allocated.
- `ReservationRequest.State state` (**ReadOnly**)  
Current state of the reservation request.
- `String stateReport` (**ReadOnly**)  
Description for the current state (can contain reason, e.g., why the allocation failed).
- `String reservationIdentifier` (**ReadOnly**)  
Identifier of allocated reservation for this request.

- **enum** `ReservationRequest.State`

Enumeration of possible reservation request states.

Enumeration values:

- `NOT_COMPLETE`  
A specification in the request need to be additionally filled.
- `NOT_ALLOCATED`  
The request was not processed by the Scheduler yet.
- `ALLOCATED`  
The request was successfully allocated to a reservation.
- `ALLOCATION_FAILED`  
Allocation of the request has failed.

- **class** `Specification`

Represents a base class for all specific specifications.

- **class** `CompartmentSpecification` **extends** `Specification`

Represents a group of endpoints which should be interconnected by the Scheduler.

**Attributes:**

- **List<Specification> specifications (Required)**  
List of specifications which should be interconnected in the compartment.
- **CallInitiation callInitiation (Optional)**  
Default **CallInitiation** in the compartment.

- **class ExternalEndpointSpecification extends Specification**

Represents a specification for external endpoint resource(s) that is/are requested for a reservation.

**Attributes:**

- **Technology technology (Required)**  
Technology of the resource(s).
- **Integer count (Optional)**  
Number of same resources.

- **class ExistingEndpointSpecification extends Specification**

Represents a specification for an existing resource (known to controller) that is requested for a reservation.

**Attributes:**

- **String resourceIdentifier (Required)**  
Identifier of the requested endpoint resource.

- **class LookupEndpointSpecification extends Specification**

Represents a specification for any existing endpoint resource with given **technology** in the controller resource database.

**Attributes:**

- **Technology technology (Required)**  
Technology of the resource.

- **class AliasSpecification extends Specification**

Represents a specification that requests a reservation for an alias for a video conferencing device.

**Attributes:**

- **Technology technology (Optional)**  
Technology of the requested alias.
- **AliasType aliasType (Optional)**  
Type of the requested alias.
- **String resourceIdentifier (Optional)**  
Identifier of a resource with **AliasProviderCapability** which is preferred to be used as the alias provider.

- **class PersonSpecification extends Specification**

Represents a specification for a person that should participate in a video conference.

**Attributes:**

- **Person person (Required)**  
Requested person.

- **class ReservationRequestSummary**

This class represents a summary of a reservation request. The summary is lightweight and does not contain all reservation request attributes. It contains some useful additional "calculated" attributes. It is suitable when listing a lot of reservation requests from the controller database where the detail information about reservation request is not appropriate.

Attributes:

- **String identifier (ReadOnly)**  
Reservation request unique identifier as defined in UC-7.
- **ReservationRequestType type (ReadOnly)**  
Type of reservation request, see **ReservationRequestType**.
- **String name (ReadOnly)**  
Name of the reservation request.
- **ReservationRequestPurpose purpose (ReadOnly)**  
Purpose of reservation request, see **ReservationRequestPurpose**.
- **String description (ReadOnly)**  
Description of reservation request.
- **Interval earliestSlot (ReadOnly)**  
Specifies the first future date/time slot when the reservation takes place.

## 3.2 Common

- **Controller getController()**

Get information about the domain controller. See **Controller** class.

- **Domain[] listDomains()**

Lists all known domains with status if they are available to the domain controller.

- **Connector[] listConnectors()**

Lists all known connectors in the controlled domain.

## 3.3 Resources

- **String createResource(SecurityToken token, Resource resource)**

Create a new resource that will be stored in the domain controller. The new resource identifier is returned as a result. The user with given **token** will be the resource owner. The **resource** must contain all attributes marked as **Required**.

- **modifyResource(SecurityToken token, Resource resource)**

Modify the given resource. Attribute **identifier** must be filled and identifies the resource to be modified. That operation is permitted only when the user with given **token** is the resource owner. The **resource** should contain only attributes to be modified.

- **deleteResource(SecurityToken token, String resourceId)**

Delete the resource with specified **resourceIdentifier** from Shongo management. That operation is permitted only when the user with given **token** is the resource owner and only when the resource is not used in any future reservation.



- **ResourceSummary[] listResources(SecurityToken token)**  
List of resource summaries managed by Shongo, that a user with given **token** is entitled to see.
- **Resource getResource(SecurityToken token, String resourceId)**  
Get the complete resource object for specified **resourceIdentifier** that a user with given **token** is entitled to see. See **Resource** for details.
- **boolean isResourceActive(SecurityToken token, String resourceId, AbsoluteDateTime dateTime)**  
**TODO: Not implemented yet** Checks whether the resource with specified **resourceId** is in given **dateTime** used by any reservation.
- **AbsoluteDateTimeSlot[] findResourceAvailableSlots(SecurityToken token, String resourceId)**  
**TODO: Not implemented yet** Lookup date/time slots when the resource with specified **resourceId** is not allocated to any reservation.

### 3.3.1 Failures

**TODO: No special faults yet**

## 3.4 Reservations

- **String createReservationRequest(SecurityToken token, ReservationRequest reservationRequest)**  
Create a new reservation. The new reservation identifier is returned as a result. The **reservationRequest** must contain all attributes marked as **Required**.
- **modifyReservationRequest(SecurityToken token, ReservationRequest reservationRequest)**  
Modify the reservation. Attribute **identifier** must be filled and identifies the reservation request to be modified. The **reservationRequest** should contain only attributes to be modified.
- **deleteReservationRequest(SecurityToken token, String reservationRequestIdentifier)**  
Release the reservation with specified **reservationIdentifier**. The child reservations remain untouched.
- **ReservationSummary[] listReservationRequests(SecurityToken token)**  
List all the reservations that a user with given **token** is entitled to see. Only the lightweight definitions of reservation requests are returned, see **ReservationRequestSummary** for details.
- **Reservation getReservationRequest(SecurityToken token, String reservationRequestIdentifier)**  
Get the reservation object for specified **reservationIdentifier** that a user with given **token** is entitled to see. The returned object contains requested time slots, requested compartments, child reservations and all other attributes that can be modified. It does not contain the read only scheduler allocation information which can be obtained by **getReservationAllocation**.

- **ReservationAllocation** `getReservationAllocation(SecurityToken token, String reservationRequestIdIdentifier)`

**TODO: Not implemented yet** List all the date/time slots that were allocated by a scheduler for the reservation and for all child reservation (recursive). Each date/time slot contains list of identifiers for resources that are allocated for the date/time slot.

- **ResourceSummary[]** `listReservationSlotResources(SecurityToken token, String reservationId, AbsoluteDateTimeSlot slot, Map filter)`

**TODO: Not implemented yet** Get a list of allocated resources for the given date/time slot in a reservation with specified **reservationId** (one reservation can have multiple date/time slots in which the reservation takes place and the list of allocated resources may vary). The list of resources is filtered by specified **filter** map that should contain only attributes specified in **ResourceSummary**.

- **AbsoluteDateTimeSlot[]** `findReservationAvailableSlots(SecurityToken token, Period duration, Resource[] resources, boolean interDomain)`

**TODO: Not implemented yet** Lookup available date/time slots for specified reservation **duration** and **resources**. Argument **interDomain** specifies whether inter-domain lookup should be performed.

### 3.4.1 Failures

**TODO: No special faults yet**

## 3.5 Room Operations

**TODO: Not implemented yet**

- **RoomUser[]** `listRoomUsers(SecurityToken token, String roomId)`

Get the list of users that currently participate in the room with specified **roomId**.

- **RoomUser** `getRoomUser(SecurityToken token, String roomId, String userId)`

Gets a concrete room user.

- `modifyRoomUser(SecurityToken token, String roomId, String userId, Map attributes)`

Modifies the user with specified **userId** in the room with given **roomId** (suitable for setting microphone/playback level, muting/unmuting...).

- `disconnectRoomUser(SecurityToken token, String roomId, String userId)`

Disconnect the user with specified **userId** from the room with given **roomId**.

### 3.5.1 Failures

**TODO: No special faults yet**

## Chapter 4

# Connector API Specification

### 4.1 Communication Protocol

**TODO:** Merge with XML-RPC description. Afterwards, just state, what is used for which communication acts (XML-RPC for user interface, Jade ontologies for Jade messaging). Use common failure codes. Groups of failure codes: Shongo-connections, connections between a connector and its device, failures reported by the devices themselves

Communication among controllers and connectors is implemented using JADE [2]. The communication is **synchronous**, i.e., the controller sends a command to a connector and waits until the connector replies. All messages are encoded using the FIPA SL content language [3]. An ontology, called **ShongoOntology**, is used by communicating agents to give the same meaning to the symbols used in messages. This section describes the way commands defined by this API are composed to messages and interpreted by Shongo agents.

The ontology used by all agents consists of concepts, predicates, and agent actions.

**An agent action**, tagged by **jade.content.AgentAction** interface, expresses a request what should the receiving agent do. Each of the commands specified in this API document is defined by a class implementing **AgentAction**, declaring all the command arguments as attributes accessed by public getters and setters.

**A predicate**, tagged by **jade.content.Predicate** interface, expresses a claim about a fact. In this API, we use just two predicates defined in the JADE framework, for the purpose of expressing result of a command. We use no custom predicates.

**A concept**, tagged by **jade.content.Concept** interface, is any entity which may be a part of an agent action or a predicate. All object types of arguments or return values must be specified as concepts for the agent content manager to be able to properly encode them in messages. In particular, any such a class must implement the **jade.content.Concept** interface and reside within the **cz.cesnet.shongo.jade.ontology** package for the **ShongoOntology** class to be able to find it and comprise it in the ontology used for encoding messages.

For example, the **setMicrophoneLevel(int level)** command, defined in section 4.5, might be specified by the following class:

```
package cz.cesnet.shongo.jade.ontology;

public class SetMicrophoneLevel implements AgentAction {
```

```

private int level = 0;

public int getLevel() {
    return level;
}
public void setLevel(int level) {
    this.level = level;
}
}

```

The **setMicrophoneLevel** call implementation instantiates a new **SetMicrophoneLevel** object, sets up the **level** attribute, and passes the object to a controller agent content manager to send it to an endpoint as a **request** communicative act [4]. The corresponding endpoint agent creates the **SetMicrophoneLevel** object received from the controller agent and implements the requested functionality according to it. The message sent during such a call might be similar to the following:

```

(REQUEST
:receiver (set ( agent-identifier :name dev@127.0.0.1:1099/JADE ) )
:content  "((action (agent-identifier :name
    Controller-Main-Container@127.0.0.1:1099/JADE :addresses (sequence
    http://localhost:7778/acc)) (SET-MICROPHONE-LEVEL :level 46)))"
:language fipa-sl :ontology shongo-ontology )

```

The agent receiving a command should always send a reply as an **inform** [4] message. In case of commands without any return value, a **Done** predicate from the package **jade.content.onto.basic** should be sent as a reply, denoting a successful command execution. When a return value is expected, a **Result** predicate, defined in [3], is sent, filled with the value to be returned. The same requirements apply to the class of the object to be returned as for command object arguments – the class must reside within the **cz.cesnet.shongo.jade.ontology** interface and be tagged by the **Concept** interface.

An example of a complex command is shown in appendix B.

## 4.2 Data Types

- **class ConnectorInfo**

Information about connector.

Attributes:

- **String name (ReadOnly)**  
the connector name
- **Resource device (ReadOnly)**  
the device managed by this connector (must be a resource of type **ManagedDevice** – see chapter 2.4)
- **ConnectionState connectionState (ReadOnly)**  
connection state to the device
- **DeviceState deviceState (ReadOnly)**  
state of the device, maintained by the connector for performance reasons

- **enum** ConnectionState

State of connection between a connector and a device it manages.

Enumeration values:

- Connected
- Disconnected

- **class** DeviceState

State description of a device. **TODO**

- **class** DeviceLoadInfo

Current device load information. A negative value in any attribute means the value could not be determined.

Attributes:

- **float** cpuLoad (**ReadOnly**)
- **long** memoryOccupied (**ReadOnly**)
- **long** memoryAvailable (**ReadOnly**)
- **long** diskSpaceOccupied (**ReadOnly**)
- **long** diskSpaceAvailable (**ReadOnly**)

- **class** Room

Represents a virtual room on a multipoint server device.

Attributes:

- **RoomUser[]** users (**Required**)  
List of allowed users.
- **boolean** allowGuests (**Required**)  
A flag indicating whether to allow guest users to join the room.
- **int** licenseCount (**Required**)  
Number of licenses that multipoint server can utilize for this room.
- **RoomLayout** layout (**Required**)  
The default room layout (used for all participants who did not specify a layout of their own choice).
- **String[]** configuration (**Optional**)  
Platform specific configuration.

**TODO:** Room settings should be auto-modified in time be uploaded calendar

- **class** UsageStats

Usage stats of a given multipoint device.

Attributes:

- **byte[]** callLog (**ReadOnly**)  
Call log in CDR. Should contain at least start time and duration of each call.

- **class** RoomInfo

A brief info about a virtual room at a server.

Attributes:

- **String** name (**Required**)

Name of the room.

- **String owner** (**ReadOnly**)  
Identification of the room owner.
- **AbsoluteDateTime creation** (**ReadOnly**)  
Date and time when the room was created.
- **Reservation reservation** (**ReadOnly**)  
Reservation for which this room was created (to satisfy use-case 23).
- **Technology type** (**ReadOnly**)  
Type of the room.

- **enum RoomLayout**

Layout of a virtual room.

Enumeration values:

- **SingleParticipant** (only a single, fixed participant is displayed)
- **VoiceSwitchedSingleParticipant** (only a single, currently speaking participant is displayed)
- **SpeakerCorner** (a fixed participant is in the upper-left corner, other participants around)
- **VoiceSwitchedSpeakerCorner** (the currently speaking participant is in the upper-left corner, other participants around)
- **Grid** (all participants are spread in a regular grid)

- **class MediaData**

Custom media data, typically used for uploading or downloading some content (images, documents, etc.).

Attributes:

- **ContentType contentType** (**Required**)  
Type of the data.
- **byte[] data** (**Required**)  
The content. To be interpreted according to the content type.
- **CompressionAlgorithm compression** (**Optional**)  
Algorithm used to compress **data**.

- **class ContentType**

Description of a media type. Any MIME Media Type listed by IANA [5], e.g. image/jpeg.

Attributes:

- **String type** (**Required**)  
Textual name of the type (e.g., **image** or **text**).
- **String subtype** (**Required**)  
Textual name of the subtype (e.g., **jpeg** or **html**).

- **enum CompressionAlgorithm**

A compression algorithm used to compress data files.

Enumeration values:

- **ZIP** (zip compression, as specified by the application/zip MIME type)
- **RAR** (rar archive)
- **TAR\_GZIP** (a gzip-compressed tar archive)
- **TAR\_BZIP2** (a bzip2-compressed tar archive)

## 4.3 Common API

- **ConnectorInfo getConnectorInfo()**  
Get information about connector.
- **muteRoomUser(SecurityToken token, String RoomUserId)**  
Mutes a user in a room.
- **unmuteRoomUser(SecurityToken token, String RoomUserId)**  
Unmutes a user in a room.
- **setMicrophoneLevel(SecurityToken token, String RoomUserId, int level)**  
Sets microphone audio level of a user in a room to a given value. Note that the implementation differs between multipoint and endpoint types of devices. On an endpoint, the playback level is set using the device amplifier, while calling this on a multipoint device results in software adaptation of the output sound data (which may result in a distorted sound).
- **setPlaybackLevel(SecurityToken token, String RoomUserId, int level)**  
Sets playback audio level of a user in a room to a given value. Note that the implementation differs between multipoint and endpoint types of devices. On an endpoint, the playback level is set using the device amplifier, while calling this on a multipoint device results in software adaptation of the output sound data (which may result in a distorted sound).
- **enableUserVideo(SecurityToken token, String RoomUserId)**  
Enables video from a user in a room.
- **disableUserVideo(SecurityToken token, String RoomUserId)**  
Disables video from a user in a room.

## 4.4 Multipoint Device

### 4.4.1 Room Management

- **RoomInfo getRoomInfo(SecurityToken token, String roomId)**  
Gets info about an existing room.
- **String createRoom(SecurityToken token, Room room)**  
Create a new virtual room on a multipoint device that is managed by this connector. The **room** parameter specifies the room settings, see the **Room** definition. Returns an identifier of the created room, unique for the device (not necessarily unique within the whole domain, though), to be used for further identification of the room as the **roomId** parameter. The returned identifier of the room is a synthetic one – generated by the concrete connector and passed back to the controller. The controller should use this identifier for further reference of the room, the connector is responsible for passing the correct identifier to the concrete device.  
  
E.g., a Codian MCU identifies the rooms by their names, the room name may be changed, though. Thus, the controller passes the room name to the **createRoom** function within

the **room** specification, the connector generates a new, synthetic, Shongo-level ID for the room and returns it. The connector maintains the mapping of the synthetic IDs to the room names. In further calls to functions working with the room, the room is identified by the synthetic ID (the **roomId** parameter to the functions mentioned below), the connector is responsible for translating the synthetic ID to some room identifier required by the underlying conference system.

- **modifyRoom(SecurityToken token, String roomId, Map attributes)**

Modifies a room identified by **roomId**. The **attributes** map specifies **Room** attribute names mapped to new values.

- **deleteRoom(SecurityToken token, String roomId)**

Delete an existing virtual room on a multipoint device that is managed by this connector.

- **String exportRoomSettings(SecurityToken token, String roomId)**

Gets current settings of a room exported to XML.

**TODO:** Specify schema of the exported XML document in RelaxNG. It should contain at least room name, technology (H.323/SIP/Connect...) settings, and version of the format of the exported document (for further extensions).

- **importRoomSettings(SecurityToken token, String roomId, String settings)**

Sets up a room according to given **settings** previously exported by the **exportRoomSettings** method.

#### 4.4.2 User Management

- **RoomUser[] listRoomUsers(SecurityToken token, String roomId)**

- **RoomUser getRoomUser(SecurityToken token, String roomId, String roomId)**

Gets user information and settings in a room.

- **modifyRoomUser(SecurityToken token, String roomId, String roomId, Map attributes)**

Modifies user settings in the room (suitable for setting microphone/playback level, muting/unmuting, user layout...).

- **disconnectRoomUser(SecurityToken token, String roomId, String roomId)**

Disconnect user from the room.

- **enableContentProvider(SecurityToken token, String roomId)**

Enables a given room user as a content provider in the room. This is typically enabled by default.

- **disableContentProvider(SecurityToken token, String roomId)**

Disables a given room user as a content provider in the room. Typically, all users are allowed to fight for being the content provider. Using this method, a user is not allowed to do this.



### 4.4.3 Room Content Management

- **MediaData getRoomContent(SecurityToken token, String roomId)**  
Gets all room content (e.g., documents, notes, polls, etc.) as a single archive (see the **compression** attribute of the returned object).
- **addRoomContent(SecurityToken token, String roomId, String name, MediaData data)**  
Adds a data file to room content under a given name.
- **removeRoomContentFile(SecurityToken token, String roomId, String name)**  
Removes a file of a given name from room content.
- **clearRoomContent(SecurityToken token, String roomId)**  
Clears all room content.

### 4.4.4 Monitoring

- **DeviceLoadInfo getDeviceLoadInfo()**  
Gets info about current load of the device.
- **UsageStats getUsageStats()**  
Gets the multipoint usage stats.
- **RoomInfo[] getRoomList()**  
Gets a list of all rooms at a given server.
- **MediaData getReceivedVideoSnapshot(SecurityToken token, String RoomUserId)**  
Gets a snapshot of the video stream received by a user in a room. See the **contentType** of the returned object to get the image format returned.
- **MediaData getSentVideoSnapshot(SecurityToken token, String RoomUserId)**  
Gets a snapshot of the video stream that a user is sending in a room. See the **contentType** of the returned object to get the image format returned.

### 4.4.5 Recording

- **int startRecording(SecurityToken token, String roomId, ContentType format, RoomLayout layout)**  
Immediately starts recording in a room to format **format** using a given **layout** (or the default room layout, if **layout** is not specified). Returns an identifier for further reference, unique among other recordings on the device. Does not have any effect and returns 0 if the room is already being recorded.
- **stopRecording(SecurityToken token, int recordingId)**  
Stops recording. The **recordingId** parameter, specifying what to stop, is an identifier previously returned by **startRecording**.
- **String getRecordingDownloadURL(SecurityToken token, int recordingId)**  
Returns a URL from where it is possible to download a recording. The **recordingId** parameter is an identifier previously returned by **startRecording**.

- **notifyParticipants(SecurityToken token, int recordingId)**  
Sends an e-mail to all non-anonymous participants present in the room recorded. Participants present in any moment of the recording must be notified, not just the registered users.
- **downloadRecording(SecurityToken token, String downloadURL, String targetPath)**  
Starts downloading a recording from **downloadURL**. The recording is stored on the server under **targetPath**.
- **deleteRecording(SecurityToken token, int recordingId)**  
Deletes a given recording. The **recordingId** parameter is an identifier previously returned by **startRecording**. If the recording is being worked with somehow (still being recorded, being uploaded, etc.), the operation is deferred to the moment when current operations are completed.

## 4.5 Endpoint Device

- **dial(SecurityToken token, String server)**  
Dials a server.
- **resetDevice(SecurityToken token)**  
Resets the device.

## 4.6 Technology Specific API

**TODO:** Cover use cases 38 and 39.

**TODO:** How to structure this section? List the supported commands for each technology separately, or list them on a single place, stating the technologies supporting a functionality for each command?

- **dial(SecurityToken token, String deviceAddress)**  
Dials a device, multipoint or endpoint. Dialing a client is available only on **H.323** and **SIP**.

## **Chapter 5**

# **Inter-Controller API Specification**

# Appendix A

## User Interface API Usage

### A.1 Perl programming language

#### A.1.1 Connect to Controller

```
#!/usr/bin/perl

require RPC::XML;
require RPC::XML::Client;

$client = RPC::XML::Client->new('http://localhost:8008');

$response = $client->send_request(...);

if ( ref($response) ) {
    use XML::Twig;
    $xml = XML::Twig->new(pretty_print => 'indented');
    $xml->parse($response->as_string());
    $xml->print();
} else {
    print($response . "\n");
}
```

### A.1.2 Create reservation

```
$response = $client->send_request(  
    'Reservation.createReservationRequest',  
    RPC::XML::struct->new(  
        'class' => RPC::XML::string->new('SecurityToken'),  
        ...  
    ),  
    RPC::XML::struct->new(  
        'class' => RPC::XML::string->new('ReservationRequest'),  
        'slot' => RPC::XML::string->new('20120101T12:00/PT2H'),  
        'type' => RPC::XML::string->new('NORMAL'),  
        'purpose' => RPC::XML::string->new('EDUCATION')  
        ...  
    )  
);
```

#### Response

```
<struct>  
  <member>  
    <name>class</name>  
    <value><string>ReservationRequest</string></value>  
  </member>  
  <member>  
    <name>id</name>  
    <value>  
      <string>shongo:cz.cesnet:1</string>  
    </value>  
  </member>  
  <member>  
    <name>slot</name>  
    <value><string>20120101T12:00:00/PT2H</string></value>  
  </member>  
  ...  
</struct>
```

### A.1.3 Modify reservation

```
$response = $client->send_request(  
    'Reservation.modifyReservationRequest',  
    RPC::XML::struct->new(  
        'class' => RPC::XML::string->new('SecurityToken'),  
        ...  
    ),  
    RPC::XML::string->new('shongo:cz.cesnet:1'),  
    RPC::XML::struct->new(  
        'description' => RPC::XML::struct->new() # set description to null  
    )  
);
```

#### Response

```
<struct>  
  <member>  
    <name>id</name>  
    <value><string>shongo:cz.cesnet:1</string></value>  
  </member>  
  <member>  
    <name>class</name>  
    <value><string>ReservationRequest</string></value>  
  </member>  
  <member>  
    <name>type</name>  
    <value><string>20120101T12:00:00/PT2H</string></value>  
  </member>  
  ...  
</struct>
```

### A.1.4 List reservations

```
$response = $client->send_request(  
    'Reservations.listReservationRequests',  
    RPC::XML::struct->new(  
        'class' => RPC::XML::string->new('SecurityToken'),  
        ...  
    )  
);
```

#### Response

```
<array><data>  
  <value><struct>  
    <member>  
      <name>id</name>  
      <value><string>shongo:cz.cesnet:1</string></value>  
    </member>  
    <member>  
      <name>class</name>  
      <value><string>ReservationRequest</string></value>  
    </member>  
    <member>  
      <name>type</name>  
      <value><string>20120101T12:00:00/PT2H</string></value>  
    </member>  
    ...  
  </struct></value>  
</data></array>
```

## A.1.5 Exception handling

### Wrong class

```
$response = $client->send_request(  
    'Reservations.listReservationRequests',  
    RPC::XML::struct->new(  
        'class' => RPC::XML::string->new('SecurityTokenX'),  
        ...  
    )  
);
```

### Response

```
<fault>  
  <value><struct>  
    <member>  
      <name>faultString</name>  
      <value><string>Class 'SecurityTokenX' is not defined.</string></value>  
    </member>  
    <member>  
      <name>faultCode</name>  
      <value><i4>10</i4></value>  
    </member>  
  </struct></value>  
</fault>
```

### Wrong attribute name

```
$response = $client->send_request(  
    'Reservations.createReservationRequest',  
    RPC::XML::struct->new(  
        'class' => RPC::XML::string->new('SecurityToken'),  
        ...  
    ),  
    RPC::XML::struct->new(  
        'typeX' => RPC::XML::string->new('PERMANENT')  
    )  
);
```

### Response

```
<fault>  
  <value><struct>  
    <member>  
      <name>faultString</name>  
      <value><string>Attribute 'typeX' in class 'Reservation' is not defined.</string></value>  
    </member>  
    <member>  
      <name>faultCode</name>  
      <value><i4>12</i4></value>  
    </member>  
  </struct></value>  
</fault>
```



### Wrong attribute value

```
$response = $client->send_request(
    'Reservations.createReservationRequest',
    RPC::XML::struct->new(
        'class' => RPC::XML::string->new('SecurityToken'),
        ...
    ),
    RPC::XML::struct->new(
        'type' => RPC::XML::struct->new(
            'class' => RPC::XML::string->new('SecurityToken')
        )
    )
);
```

### Response

```
<fault>
  <value><struct>
    <member>
      <name>faultString</name>
      <value><string>Attribute 'type' in class 'ReservationRequest' has type
        'ReservationRequestType' but 'SecurityToken' was presented.</string></value>
    </member>
    <member>
      <name>faultCode</name>
      <value><i4>13</i4></value>
    </member>
  </struct></value>
</fault>
```

### Wrong enum

```
$response = $client->send_request(
    'Reservations.createReservationRequest',
    RPC::XML::struct->new(
        'class' => RPC::XML::string->new('SecurityToken'),
        ...
    ),
    RPC::XML::struct->new(
        'type' => RPC::XML::string->new('PERMANENTX')
    )
);
```

### Response

```
<fault>
  <value><struct>
    <member>
      <name>faultString</name>
      <value><string>Enum value 'PERMANENTX' is not defined in enum
        'ReservationRequestType'.</string></value>
    </member>
    <member>
      <name>faultCode</name>
```

```
      <value><i4>20</i4></value>
    </member>
  </struct></value>
</fault>
```

## Appendix B

# JADE Command Encoding Example

Consider the following command required by this API:

- **RoomUser[] listRoomUsers(SecurityToken token, String roomId)**

The following classes should be defined to represent the command and all objects used by it:

```
package cz.cesnet.shongo.jade.ontology;
```

```
public class ListRoomUsers implements AgentAction {
    private SecurityToken token;
    private String roomId;

    public String getRoomId() {
        return roomId;
    }
    public void setRoomId(String roomId) {
        this.roomId = roomId;
    }
    public String getToken() {
        return token;
    }
    public void setToken(String token) {
        this.token = token;
    }
}
```

```
public class SecurityToken implements Concept {
    private UserIdentity user;

    public UserIdentity getUser() {
        return user;
    }
    public void setUser(UserIdentity user) {
        this.user = user;
    }
}
```

```

}

public class UserIdentity implements Concept {
    private String id;

    public String getId() {
        return id;
    }
    public void setId(String id) {
        this.id = id;
    }
}

public class RoomUser implements Concept {
    private String userId;
    private String roomId;
    private UserIdentity userIdentity;
    private boolean muted;
    private int microphoneLevel;
    private int playbackLevel;

    // getters and setters ...
}

```

The command might be encoded in the following message:

```

(REQUEST
:receiver (set ( agent-identifier :name dev@127.0.0.1:1099/JADE ) )
:content  "((action (agent-identifier :name
    Controller-Main-Container@127.0.0.1:1099/JADE :addresses
    (sequence http://localhost:7778/acc)) (ListRoomUsers))))"
:language fipa-sl :ontology shongo-ontology )

```

A successful reply would then be encoded as follows:

```

(INFORM
:sender ( agent-identifier :name dev@127.0.0.1:1099/JADE :addresses (sequence
    http://localhost:7778/acc ))
:receiver (set ( agent-identifier :name Controller-Main-Container@127.0.0.1:1099/JADE
    :addresses (sequence http://localhost:7778/acc )) )
:content  "((result (action (agent-identifier :name
    Controller-Main-Container@127.0.0.1:1099/JADE :addresses (sequence
    http://localhost:7778/acc)) (ListRoomUsers)) (sequence (RoomUser :microphoneLevel 45
    :muted false :playbackLevel 0 :roomId konf :userId Azurit :userIdentity
    (UserIdentity :id shongololo)) (RoomUser :microphoneLevel 57 :muted false
    :playbackLevel 0 :roomId konf :userId Shongololo :userIdentity (UserIdentity))))))"
:reply-with Controller-Main-Container@127.0.0.1:1099/JADE1336527079398 :language
    fipa-sl :ontology shongo-ontology )

```

# Bibliography

- [1] T. Berners-Lee, R. Fielding, L. Masinter, Rfc 3986, uniform resource identifier (uri): Generic syntax (2005).  
URL <http://rfc.net/rfc3986.html>
- [2] Java Agent Development Framework (May 2012).  
URL <http://jade.tilab.com>
- [3] Foundation for Intelligent Physical Agents, FIPA SL Content Language Specification, FIPA00008 (December 2002).  
URL <http://www.fipa.org/specs/fipa00008/>
- [4] Foundation for Intelligent Physical Agents, FIPA Communicative Act Library Specification, FIPA00037 (December 2002).  
URL <http://www.fipa.org/specs/fipa00037/>
- [5] Internet Assigned Numbers Authority, MIME Media Types (March 2012).  
URL <http://www.iana.org/assignments/media-types/index.html>