

Exploring High Dimensional Data Through Locally Optimized Viewpoint Selection




Fig. 1. Teaser here.

Abstract—Dimension reduced projection is usually obtained via a global optimization. It gives a good overview of the data, but cannot satisfy different users with different focuses. That’s because any local data could be distorted and misleading due to projection errors. To address this problem, we propose an interactive visualization method, to customize projections for better local analysis. First, we allow users to define their point of interest (POI) data. Then we generate local projections to minimize distortions regarding the POI. Multiple optimizations are provided for different analyses. We also reveal relationships among different POIs, by comparing their local projections. At last, our method is proved effective via case studies with a real-world dataset.

Index Terms—Dimension-reduced projection, local analysis, high-dimensional data

1 INTRODUCTION

2 RELATED WORK

2.1 Dimension-Reduced Projection

2.2 Projection Manipulation

[6]

2.3 High-dimensional Local Data Analysis

[9] [5] [10] [7] [4] [2] [3] [8] [9] [1]




Fig. 2. The overview of delivery system.

3 OVERVIEW

4 HIGH-DIMENSIONAL EXPLORATION VIA LOCALLY OPTIMIZED VIEWPOINTS

4.1 Find a Focus

4.1.1 Focus in Different Granularities

4.1.2 Distortion Hints

4.1.3 Focus Suggestion

4.2 Featured Viewpoints for the Focus

4.2.1 Desirable Local Features

4.2.2 Feature Enhanced Projections

4.2.3 Subspace Suggestion

4.3 From Focus to Cluster

4.3.1 Focus Improvement

4.3.2 Cluster Comparison via Viewpoint Map

5 CASE STUDY

6 DISCUSSION

7 CONCLUSION

ACKNOWLEDGMENTS

The authors wish to thank A, B, C. This work was supported in part by a grant from XYZ.

REFERENCES

- [1] P.-A. Absil, R. Mahony, and R. Sepulchre. Riemannian geometry of grassmann manifolds with a view on algorithmic computation. *Acta Applicandae Mathematica*, 80(2):199–220, 2004.
- [2] N. Elmqvist, P. Dragicevic, and J. Fekete. Rolling the dice: Multidimensional visual exploration using scatterplot matrix navigation. *IEEE Trans. Vis. Comput. Graph.*, 14(6):1139–1148, 2008.
- [3] J. H. Friedman and J. W. Tukey. A projection pursuit algorithm for exploratory data analysis. *IEEE Trans. Computers*, 23(9):881–890, 1974.
- [4] X. Hu, L. Bradel, D. Maiti, L. House, C. North, and S. Leman. Semantics of directly manipulating spatializations. *IEEE Trans. Vis. Comput. Graph.*, 19(12):2052–2059, 2013.
- [5] D. H. Jeong, C. Ziemkiewicz, B. Fisher, W. Ribarsky, and R. Chang. ipca: An interactive system for pca-based visual analytics. In *Computer Graphics Forum*, volume 28, pages 767–774. Wiley Online Library, 2009.
- [6] D. J. Lehmann and H. Theisel. Orthographic star coordinates. *IEEE Trans. Vis. Comput. Graph.*, 19(12):2615–2624, 2013.
- [7] J. E. Nam and K. Mueller. Tripadvisor^{n-d}: A tourism-inspired high-dimensional space exploration framework with overview and detail. *IEEE Trans. Vis. Comput. Graph.*, 19(2):291–305, 2013.
- [8] J. Seo and B. Shneiderman. A rank-by-feature framework for interactive exploration of multidimensional data. *Information Visualization*, 4(2):96–113, 2005.
- [9] M. Sips, B. Neubert, J. P. Lewis, and P. Hanrahan. Selecting good views of high-dimensional data using class consistency. *Comput. Graph. Forum*, 28(3):831–838, 2009.

- [10] X. Yuan, D. Ren, Z. Wang, and C. Guo. Dimension projection matrix/tree: Interactive subspace visual exploration and analysis of high dimensional data. *IEEE Trans. Vis. Comput. Graph.*, 19(12):2625–2633, 2013.