

OpenAI Platform

Files

Files are used to upload documents that can be used with features like [Assistants](#), [Fine-tuning](#), and [Batch API](#).

Upload file

POST <https://api.openai.com/v1/files>

Upload a file that can be used across various endpoints. Individual files can be up to 512 MB, and the size of all files uploaded by one organization can be up to 1 TB.

The Assistants API supports files up to 2 million tokens and of specific file types. See the [Assistants Tools guide](#) for details.

The Fine-tuning API only supports `.jsonl` files. The input also has certain required formats for fine-tuning [chat](#) or [completions](#) models.

The Batch API only supports `.jsonl` files up to 200 MB in size. The input also has a specific required [format](#).

Please [contact us](#) if you need to increase these storage limits.

Request body

file file **Required**

The File object (not file name) to be uploaded.

purpose string **Required**

The intended purpose of the uploaded file. One of: - `assistants` : Used in the Assistants API - `batch` : Used in the Batch API - `fine-tune` : Used for fine-tuning - `vision` : Images used for vision fine-tuning - `user_data` : Flexible file type for any purpose - `evals` : Used for eval data sets

expires_after object **Optional**

Assistant

The expiration policy for a file. By default, files with `purpose=batch` expire after 30 days and all other files are persisted until they are manually deleted.

› Show properties

Returns

The uploaded [File](#) object.

Example request

curl ↕



```
1 curl https://api.openai.com/v1/files \  
2   -H "Authorization: Bearer $OPENAI_API_KEY" \  
3   -F purpose="fine-tune" \  
4   -F file="@mydata.jsonl" \  
5   -F expires_after[anchor]="created_at" \  
6   -F expires_after[seconds]=2592000
```

Response



```
1 {  
2   "id": "file-abc123",  
3   "object": "file",  
4   "bytes": 120000,  
5   "created_at": 1677610602,  
6   "expires_at": 1677614202,  
7   "filename": "mydata.jsonl",  
8   "purpose": "fine-tune",  
9 }
```

List files

GET <https://api.openai.com/v1/files>

Returns a list of files.

Query parameters

after string Optional

A cursor for use in pagination. `after` is an object ID that defines your place in the list. For instance, if you make a list request and receive 100 objects, ending with `obj_foo`, your subsequent call can include `after=obj_foo` in order to fetch the next page of the list.

limit integer Optional Defaults to 10000

A limit on the number of objects to be returned. Limit can range between 1 and 10,000, and the default is 10,000.

order string Optional Defaults to desc

Sort order by the `created_at` timestamp of the objects. `asc` for ascending order and `desc` for descending order.

purpose string Optional

Only return files with the given purpose.

Returns

A list of [File](#) objects.

Example request

curl ↕



```
1 curl https://api.openai.com/v1/files \  
2   -H "Authorization: Bearer $OPENAI_API_KEY"
```

Response



```
1 {  
2   "object": "list",  
3   "data": [  
4     {  
5       "id": "file-abc123",  
6       "object": "file",  
7       "bytes": 175,  
8       "created_at": 1613677385,  
9       "expires_at": 1677614202,  
10      "filename": "salesOverview.pdf",  
11      "purpose": "assistants",  
12    },  
13    {  
14      "id": "file-abc456",  
15      "object": "file",  
16      "bytes": 140,
```

```
17     "created_at": 1613779121,  
18     "expires_at": 1677614202,  
19     "filename": "puppy.jsonl",  
20     "purpose": "fine-tune",  
21   }  
22 ],  
23   "first_id": "file-abc123",  
24   "last_id": "file-abc456",  
25   "has_more": false  
26 }
```

Retrieve file

GET https://api.openai.com/v1/files/{file_id}

Returns information about a specific file.

Path parameters

file_id string Required

The ID of the file to use for this request.

Returns

The [File](#) object matching the specified ID.

Example request

curl 

```
1 curl https://api.openai.com/v1/files/file-abc123 \  
2   -H "Authorization: Bearer $OPENAI_API_KEY"
```

Response 

```
1 {  
2   "id": "file-abc123",  
3   "object": "file",  
4   "bytes": 120000,  
5   "created_at": 1677610602,  
6   "expires_at": 1677614202,  
7   "filename": "mydata.jsonl",
```

```
8  "purpose": "fine-tune",  
9  }
```

Delete file

```
DELETE https://api.openai.com/v1/files/{file_id}
```

Delete a file and remove it from all vector stores.

Path parameters

file_id string Required

The ID of the file to use for this request.

Returns

Deletion status.

Example request

curl ↕



```
1 curl https://api.openai.com/v1/files/file-abc123 \  
2 -X DELETE \  
3 -H "Authorization: Bearer $OPENAI_API_KEY"
```

Response



```
1 {  
2   "id": "file-abc123",  
3   "object": "file",  
4   "deleted": true  
5 }
```

Retrieve file content

```
GET https://api.openai.com/v1/files/{file_id}/content
```

Returns the contents of the specified file.

Path parameters

file_id string Required

The ID of the file to use for this request.

Returns

The file content.

Example request

curl ↕



```
1 curl https://api.openai.com/v1/files/file-abc123/content \
2   -H "Authorization: Bearer $OPENAI_API_KEY" > file.jsonl
```

The file object

The `File` object represents a document that has been uploaded to OpenAI.

bytes integer

The size of the file, in bytes.

created_at integer

The Unix timestamp (in seconds) for when the file was created.

expires_at integer

The Unix timestamp (in seconds) for when the file will expire.

filename string

The name of the file.

id string

The file identifier, which can be referenced in the API endpoints.

object string

The object type, which is always `file` .

purpose string

The intended purpose of the file. Supported values are `assistants` , `assistants_output` , `batch` , `batch_output` , `fine-tune` , `fine-tune-results` , `vision` , and `user_data` .

status Deprecated string

Deprecated. The current status of the file, which can be either `uploaded` , `processed` , or `error` .

status_details Deprecated string

Deprecated. For details on why a fine-tuning training file failed validation, see the `error` field on `fine_tuning.job` .

OBJECT The file object



```
1 {
2   "id": "file-abc123",
3   "object": "file",
4   "bytes": 120000,
5   "created_at": 1677610602,
6   "expires_at": 1680202602,
7   "filename": "salesOverview.pdf",
8   "purpose": "assistants",
9 }
```

< PREVIOUS
Batch

NEXT >
Uploads