

cyclaw-user -- exit codes and --password risk

From `utils/authn_cli.py` on origin/main 57e052ed9222d42a20b95ceb4dec71d21e169f57. No HTTP. There is no remote admin API for these commands. Equivalent: `python -m utils.authn_cli`. Default `--config config.yaml` is repo-rooted (not cwd).

Exit codes

Code	Name	When
0	EXIT_OK	Command succeeded.
2	EXIT_FAIL	Operation failed: duplicate/unknown user, password policy, AuthError. <code>argparse</code> also exits 2 on usage errors (missing subcommand, bad flags).
3	EXIT_ENV	<code>config.yaml</code> unreadable / not a mapping, or AuthManager could not open the store.

Commands

Command	Notes
<code>cyclaw-user add USER [--role operator] [--password ...]</code>	Default role operator. Roles: admin, operator, audit.
<code>cyclaw-user list</code>	username, role, enabled/disabled, LOCKED, failed_count.
<code>cyclaw-user role USER ROLE</code>	Set admin / operator / audit.
<code>cyclaw-user disable USER / enable USER</code>	Disable does not delete.
<code>cyclaw-user passwd USER [--password ...]</code>	Same store as HTTP bootstrap for admin.
<code>cyclaw-user token create USER LABEL</code>	Prints plaintext once. Device Bearer for /query when auth is on. Not CYCLAW_API_KEY.
<code>cyclaw-user token list USER / revoke USER LABEL</code>	Label is the only revoke handle.

--password scripting risk

add and passwd accept --password for scripts. The module docstring says omitting it and answering `getpass` is the recommended path: not echoed, not in shell history, not in `ps`. Putting the secret on `argv` means any local process list, shell history file, or copied command log can read it. Do not paste --password into tickets, PR bodies, or the audit JSONL.

```
# recommended
cyclaw-user add alice --role operator
Password:          # getpass, not echoed
Confirm password:
```

```
# scripting only -- secret is on the command line
cyclaw-user passwd alice --password 'REDACTED_MIN_12_CHARS'
```

Password policy (`utils/authn.py`): min 12, max 1024, length only. First account is username admin (pending hash until `passwd` or `POST /auth/bootstrap-password`). Lockout 5 failures then delay, ceiling 900s.

Verified from the CLI file. Not verified: running `cyclaw-user` against a live `auth.db` on this host.