

Agentic Harness How-To

Operator guide for the :8790 coding console and the real-repo loop it drives.

harness/ + agentic/cli · HEAD ccf63b03 · 2026-09-06 · experimental / default-off

Authorization boundary — read this before enabling anything

This console is a trusted-operator control plane on 127.0.0.1:8790. Enabling it does not grant authority over any GitHub org, filesystem share, database, or LAN you do not already own or have written permission to use. If this laptop is an employer device, a client device, or a shared household machine, stop. Stage up auth.enabled and treat CYCLAW_API_KEY as a shared secret that can publish a draft PR. This PDF is advisory operator documentation, not licensed counsel, and not a re-opening of the 2026-08-01 write-enablement sign-off.

Contents

- 1. What this is / what it is not (two planes)
- 2. Launch, ports, and identity
- 3. Auth, CSRF, same-origin
- 4. Slash commands that are not the coding agent
- 5. Real-repo operator sequence (plan → run → decide → push → publish)
- 6. Six-gate write chain and kill switches
- 7. ToolBroker, dual locks, refuse codes
- 8. Connector pointers (fs / sql / net)
- 9. Legal, privacy, authorization table
- 10. Troubleshooting and residuals

1. What this is / what it is not

CyClaw is two planes pretending to share a product name. The 12-node LangGraph on 127.0.0.1:8787 answers questions from the corpus. The harness on 127.0.0.1:8790 is a sibling package that drives an out-of-band coding and ops runtime under agentic/. Isolation is I6 import isolation plus a subprocess shim — not a separate identity. Same operator, same gh credentials, same host.

Plane	Bind	Job	Writes the world?
A — RAG graph	127.0.0.1:8787 gate.py	retrieve → route → local LLM → optional Grok/Claude → audit_logger. 12 nodes. No bind_tools.	No. Soul HTTP path is separately gated (I5).
B — harness + agentic	127.0.0.1:8790 + CLI	Chat (/loop), allowlist GET (/web), notes (/memory), real-repo clone/patch/verify/commit, draft PR.	Yes, when corks are pulled. That is this guide.

The #1 operator trap

/loop is chat. /agent run is the coding agent. /loop n fires POST /api/chat with {"loop": true} toward the session /goal. It never starts POST /api/agent/run. It never clones, commits, pushes, or opens a PR. If you treat /loop as "the agent," you will think you only chatted while a worktree pipeline did or did not run. README is explicit. This PDF will not un-say it.

What the harness never does

- Never imports gate.py, graph.py, or mcp_hybrid_server.py (l6 both directions).
- Never starts a host shell. There is no cmd / ps1 / bash agent tool. allow_shell_execution: true is hard-refused.
- Never writes soul.md, docs/memories/, or the RAG memory/ store. rag.writable_from_harness is always false.
- Never executes skills from /skills or from data/agentic/skills_registry.json. That JSON ships empty.
- GitHub side-effects go only through utils.ops_runner → python -m agentic.cli (same shim as POST /ops/agentic).

2. Launch, ports, and identity

Default bind is loopback. main() refuses a non-loopback host. uvicorn harness.server:app --host 0.0.0.0 bypasses that guard — do not do that. Bookmark the exact origin you opened. localhost and 127.0.0.1 are different browser origins (#1267 / #1271). A mismatch is 403 CROSS_ORIGIN_BLOCKED, not a bug.

Surface	How	URL / note
Both (macOS)	cyclaw	Opens :8787 gate + :8790 harness.
Harness only	python -m harness.server	http://127.0.0.1:8790 — exits 0 if the port is already bound (#1293).
Windows launcher	Invoke-CyClaw.ps1	Port must be 1024–65535. Does not start gate.py.
Env override	CYCLAW_HARNESS_PORT	Honored by launchd plist generator and invoke scripts.
Home	CYCLAW_HOME	~/.CyClaw or %USERPROFILE%\CyClaw. Notes, .env, web allowlist live here.

```
cyclaw
# or
python -m harness.server
open http://127.0.0.1:8790/
gh auth status          # identity that will own any draft PR
python -m agentic.cli status
```

If CYCLAW_API_KEY is empty, macOS invoke-cyclaw.sh sources \$HOME/.CyClaw/.env then the repo .env, only at mode 600 or 400 (#1122 / #1127). A world-readable HOME file is refused and no longer shadows a valid repo copy. Typing the key into the browser box cannot configure the server process.

3. Auth, CSRF, same-origin

Two auth systems sit on this port. Do not mix their tokens.

System	When	Token	Covers
API key	Always, unless api_key_optional + loopback + no forwarding headers	Bearer CYCLAW_API_KEY (same secret as Soul /ops)	Guarded harness routes including /api/agent/run, /push, /publish. 29 guarded after #1144.
Session auth	auth.enabled: true (ships false). Else 503 AUTH_DISABLED	cyclaw_harness_session cookie + CSRF	/api/auth/* Users panel, login/logout/whoami. Roles admin / operator / audit. One corpus.

- Fetch GET / first so the page holds the process CSRF. Header logout uses that process token (#1278).
- Bootstrap password POSTs are loopback **and** not proxied (#1296). Any X-Forwarded- * / Forwarded / X-Real-IP is 403 AUTH_LOOPBACK_ONLY.

- `security.api_key_optional` ships false. Enabling it is a named residual: a proxy that strips forwarding headers is indistinguishable from none.
- `POST /api/keys` writes `$CYCLAW_HOME/.env` mode 600, allowlist `MANAGED_KEYS` only, never echoes values, reports `restart_required`. There is no slash `/keys`.

4. Slash commands that are not the coding agent

Live console vocabulary below. Do not invent siblings. There is no harness `/audit` (that slash lives on `terminal.html :8787`). There is no slash `/keys` — key status is `/api` and `/api set`. Also dispatched but not expanded here: `/session`, `/connectors` (alias `/registry`), `/github`, `/harness`, `/tokens`, `/status`.

Command	Touches	Does not
<code>/help</code>	Prints implemented verbs including every <code>/web</code> verb (#1300).	Start a run.
<code>/goal ...</code> <code>/goal</code> <code>/goal clear</code>	Session-scoped goal. Injected read-only into chat system prompt. Required by <code>/loop</code> .	Clone or write GitHub.
<code>/loop [n]</code> <code>/loop stop</code>	<code>n</code> chat turns toward <code>/goal</code> (default 3, cap 5). Rate 8/300s. 12,000-token aggregate completion cap. Shared generation lock. 400 <code>LOOP_REQUIRES_GOAL</code> . 409 <code>CHAT_BUSY</code> .	<code>POST /api/agent/*</code> . No real-repo.
<code>/web ...</code>	Default-off allowlist GET. Stream + hard-stop 256 KiB (#1231). Prefix-exact. <code>/web inject</code> is UNTRUSTED into next chat prompt.	Search engine, browser, private IPs, redirects, ftp, userinfo.
<code>/skills [all name]</code>	Wiring diagram of what THIS console injects + <code>/agent-check</code> skills. <code>/skills all</code> also lists repo <code>SKILL.md</code> + governed JSON.	Execute a skill. <code>apply-skill</code> is CLI-only.
<code>/tools [all name]</code>	Harness FastAPI routes that are registered. <code>/tools all</code> also lists <code>hybrid_search</code> as catalog text parsed from <code>mcp_hybrid_server.py</code> AST.	Call MCP. Harness never imports MCP.
<code>/memory ...</code>	Pinned notes in <code>~/CyClaw/memory/notes.json</code> . Off until <code>/memory on</code> . Cap 20. Injection-scanned. GET <code>/api/memory</code> is key/CSRF guarded (#1099).	Write <code>soul.md</code> or RAG memory/.
<code>/soul</code>	Toggle harness-local soul-in-prompt flag. Reads <code>soul.md</code> raw off disk (INVARIANTS Rule 5). No <code>PersonalityManager</code> scan, no I5 reason gate.	Write or evolve <code>soul.md</code> .
<code>/model</code>	<code>POST /api/model</code> — select local model for this console.	Change <code>gate.py</code> config.
<code>/users</code>	Drives <code>/api/auth/*</code> when <code>auth.enabled</code> . Duplicate username is 409 <code>AUTH_USER_EXISTS</code> (#1216).	Create a second tenant.
<code>/clear</code>	Forgets staged <code>/agent</code> fields and displayed diffs in THIS page.	Discard a server-side clone.
<code>/api</code> <code>/api set NAME val</code>	Masked status of <code>MANAGED_KEYS</code> , or write one name into <code>\$CYCLAW_HOME/.env</code> mode 600. Restart required. Never echoes values.	Live-inject a key into this process. There is no slash <code>/keys</code> .

/web verbs (all implemented — /help must list every one)

`/web status` · `/web allow` · `/web deny` · `/web on` (409 `WEB_DISABLED` if allowlist empty) · `/web off` · `/web fetch` · `/web search` (scans allowlisted pages only) · `/web inject` · `/web forget`. Refuses localhost, 127.0.0.1, RFC1918, link-local, 169.254.169.254, user:pass@host, ftp://, wildcards, redirects. Allowlisting `/3/` does not allow the parent path.

5. Real-repo operator sequence

The live coding pipeline is `agentic/real_repo_loop.py`, reached from the console or from CLI. `DeepAgents-graph` (`agentic/deepagent_github/builder.py`) and `harness_optimizer/` are retired 2026-07-31; code is kept; do not enable. `deepagent-plan` probes gate state and never calls `.invoke()`.

Approve ≠ push ≠ publish

Approve is a local commit of a digest-bound clone (#1154 / #1161). **Push** is the first packet leaving the box (allow_git_write_tools). **Publish** is `gh pr create --draft` through the six-gate writer. Nothing combines those three. `/agent approve` also requires the pending diff to have been displayed in this page (#1301). That is a console review guard, not a server receipt. `/clear` or `/reload` forgets displayed diffs — you must look again.

Console staging (sends nothing until confirm)

```
/agent run claude/docs-fix update the documentation
/agent iterations 2          # 1..10; 'clear' restores server default
/agent pr 42                 # setting pr clears issue, and vice versa
/agent issue 17              # XOR with pr; also accepts 'clear'
/agent plan                  # optional: browser picker loads plan TEXT, not a path
/agent confirm reviewed the requested documentation change
# → POST /api/agent/run {confirm: true, instruction, branch, max_iterations?, pr|issue?}
/agent status <run-id>       # also displays the pending diff
/agent approve <run-id>      # local commit; digest-bound; must have seen the diff
/agent push <run-id>         # separate leaving-the-box act
/agent publish <run-id>      opened draft for docs-fix
/agent discard <run-id>     # reclaim clone; refusals do not discard the proposal
```

A loaded `/agent plan` is plan **text** in that same POST body. The confirm POST may also carry `max_iterations` and `pr XOR issue` (harness/schemas.py); those fields are also staged by slash verbs `/agent iterations` / `/agent pr` / `/agent issue` in harness/README.md + the HTML console. docs/HARNESS_POWERSHELL.md is the shorter walkthrough (adds read/checks/cancel/reject; omits iterations/pr/issue) — treat it as drift. There is no separate plan endpoint on the harness. Two-stage “cloud plans, local Qwen implements” is CLI-only — drive it from a terminal.

CLI two-stage (the economics recipe)

```
# 1) one-shot plan — no clone, no write
python -m agentic.cli real-repo-run-plan --repo --instruction "..." \
    --provider grok --confirm-online --out plan.md
# 2) review plan.md by hand, then implement LOCALLY — omit --provider
python -m agentic.cli real-repo-run --repo --instruction "..." \
    --plan-file plan.md --checks-file checks.json --branch claude/topic \
    --commit-message "..." --reason "..." --confirm
python -m agentic.cli real-repo-run-status --run-id "<id>"
python -m agentic.cli real-repo-run-decide --run-id "<id>" --decision approve
python -m agentic.cli real-repo-run-push --run-id "<id>"
python -m agentic.cli real-repo-run-publish --run-id "<id>" --reason "..." --confirm
```

--provider means two different things

On `real-repo-run-plan` it drives the one-shot plan call. On `real-repo-run` it drives **every iteration of the whole loop** — the cloud model proposes every patch attempt and is billed on every `--max-iterations` try. Passing it to both is allowed, silent, and defeats the two-stage recipe. `allow_cloud_providers` already ships true. Shipped local contract on the M5 Pro 48 GB box: 16k num_ctx, burst plan of ≤1 impl file + ≤1 test file, 16 paths named off-limits in the planner prompt.

What a run actually does

- Clone into `data/agentic/workspaces` via `RepoWorkspaceTools`, gated on `deepagent_github.allow_git_write_tools` (ships false).
- Model proposes a patch. Write into the clone. Verify inside `production_sandbox()` (Win Job Object / Darwin Seatbelt / Linux unshare --net). Missing binary → `HardSandboxUnavailable`. No production `ArgvListSandbox` fallback.
- Windows Job Object is process-tree kill, **not** a network namespace. Sockets still work. Do not write “air-gapped verification” on Windows.
- Approve binds to acceptance-manifest digest (`run_id + base HEAD + path→sha256`) and re-verifies a disposable copy before finalize. Old records without a digest cannot approve. Reject is a git no-op.
- Workspaces retain clones so push/publish can run. No built-in purge. Discard is operator duty.

- Plan prompt contract (#1152): Approach / Goal / Do this / Done when / Do not / Files. GitHub context is fenced untrusted. Instruction and plan-file are injection-scanned. Audit stores a hash, not the plan text.

6. Six-gate write chain and kill switches

`agentic/writer.py` is the only path that can open a GitHub PR. Only `pr_create` executes, always `--draft`. `pr_comment` / `issue_comment` stay plan-only. `Argv` is rebuilt from plan params; a tampered `would_run` is a typed refusal. Head must match agent-identity prefixes (`claude/` `codex/` `grok/` `kimi/` `CyClaw/` `agent/`). No retry on timeout — GitHub may already have the PR.

#	Gate	Where	Ships as
0	<code>agentic.enabled</code> (cork / master switch)	<code>config.yaml</code>	false
1	<code>EXECUTION_ENABLED</code>	<code>agentic/writer.py</code> (code)	True (armed 2026-08-07)
2	<code>agentic.mode == write</code>	<code>config.yaml</code>	write (already open)
3	<code>agentic.writes_enabled</code>	<code>config.yaml</code>	true (already open)
4	non-empty human reason	per call	required
5	confirm is True (not read from the plan dict)	per call	required

Armed and corked — do not write “disarmed”

Three of six gates already sit open in the shipped tree (`mode`, `writes_enabled`, `EXECUTION_ENABLED`). Flip `agentic.enabled: true` and a draft PR is one reason + confirm away, as whoever `gh auth status` is. Real-repo git writes are a second surface: `deepagent_github.enabled` and `allow_git_write_tools` still ship false. `allow_github_writes` ships false. Package docstring in `agentic/__init__.py` still says writes are a “DISABLED, STUBBED scaffold.” That blurb is stale. Trust `writer.py`.

Kill switches

- `agentic.enabled: false` — cork. CLI no-ops (exit 0) except `status/test`.
- `CYCLAW_AGENTIC_WRITE_DISABLE=1` — disable-only, import-time, AND-ed with `EXECUTION_ENABLED`. Restart the harness after setting it. Cannot arm a disarmed build.
- Leave `allow_git_write_tools` / `allow_github_writes` false until you mean push/publish.
- Stage `auth.enabled: true` before a second person can hit `:8790`.
- `/agent discard` after each decided run. `/web off` and `/memory off` when idle.

7. ToolBroker, dual locks, refuse codes

Live name-gate is `utils.tool_broker.assert_allowed(name, argv, allowlist=...)`. `guardrails/boundary.py` is unused vocabulary. Empty `allowlist` ⇒ 403 `TOOL_DENIED`, no spawn. Independent of API key and CSRF. Sits in front of WebTool fetch, /loop generation, and `POST /api/agent/run` (#1157 / #1158 / #1163).

Code	Meaning	What to do
403 <code>TOOL_DENIED</code>	Name not in ToolBroker allowlist (empty list denies all).	Do not widen the allowlist “for convenience.”
403 <code>CROSS_ORIGIN_BLOCKED</code> / <code>CROSS_SITE_BLOCKED</code>	Origin <code>host+port+scheme</code> ≠ this request. <code>localhost</code> ≠ <code>127.0.0.1</code> .	Reopen the exact URL you bookmarked. No automatic host fallback.
409 <code>AGENT_RUN_BUSY</code>	<code>agent_run_gate</code> held, OR <code>generation_gate</code> held because the run shares the local chat backend (#1247).	Wait. A chat turn on a *fallback* backend does not block a run aimed at a dead primary.
409 <code>CHAT_BUSY</code>	In-flight <code>/api/chat</code> or <code>/loop</code> turn holds the generation lock.	<code>/loop stop</code> → <code>POST /api/chat/cancel</code> .
409 <code>WEB_DISABLED</code>	<code>/web</code> on with empty allowlist, or feature off.	Allow at least one host first.

Code	Meaning	What to do
400 LOOP_REQUIRES_GOAL	/loop with no session goal.	/goal ... first.
422 AGENTIC_BUDGET_EXCEEDED	Estimated run time > REAL_REPO_RUN_MAX_TIMEOUT_SEC.	Lower iterations or checks.
401 / 403 AUTH_*	Missing/invalid key, last-admin, loopback-only bootstrap, role.	Key is process env. Browser box cannot fix a keyless server.
exit 0 (CLI)	Success OR disabled no-op.	Require the JSON op field or a run-id before trusting output.
exit 2 / 3 / 4	Fail / env / write refused (ops_runner mapped).	Anything else reports "unknown" — do not flatten bugs into 2.

Harness POST `/api/agent/run` claims `agent_run_gate` always and `generation_gate` only when the live-resolved `/api/chat` backend is the same socket as `agentic.deepagent_github.base_url`. Loopback aliases and implicit `:80/:443` compare equal. Console sends check **profile names** (pytest, ruff, invariant-guard, config-guard), never raw argv. A local CLI checks-file **can** contain `git push` — accepted trusted-operator residual. The human authored the file.

8. Connector pointers (not full guides)

`fsconnect`, `sqlconnect`, and `netconnect` live **under** `agentic/`. They are not a 7th OOB package. I6 covers them for free. Each ships off. Enabling any one is a new processing purpose. This page is a pointer, not the how-to.

Connector	Entry	Shipped posture	Operator note
<code>fsconnect</code>	<code>python -m agentic.fsconnect.cli</code>	enabled false; writes_enabled false; follow_symlinks false	Held-fd pathsafe. Indexing a share into the RAG corpus is a Plane B → Plane A data pump. See <code>FSCONNECT</code> playbook.
<code>sqlconnect</code>	<code>python -m agentic.sqlconnect.cli</code>	read_only true; allow_write false (enforced); DSN from env only	SELECT/WITH. max_rows is minimization, not anonymization. Lawful basis before any non-lab DSN.
<code>netconnect</code>	<code>python -m agentic.netconnect.cli</code>	enabled false; allowed_cidrs []	self + arp only. No packets. See <code>CyClaw-NetConnect-HowTo.pdf</code> . Event name <code>netconnect_scan</code> is an IR tell.

9. Legal, privacy, authorization

Advisory only. Not licensed counsel. Not an authorization to flip `agentic.enabled`. The signed write-enablement checklist in `docs/agentic/GITHUB_WRITE_ENABLEMENT.md` was accepted as-is on 2026-08-01 and armed on 2026-08-07. This PDF does not re-open that sign-off.

Topic	Rule for this console
Computer access (US)	18 USC 1030 (CFAA). Authorized access = this host + repos/shares/DBs the operator may use. Van Buren: exceeding authorized access after login still matters when the target is someone else's system.
Georgia	O.C.G.A. § 16-9-93 computer trespass / invasion of privacy / theft of services. Operator IP for this checkout is Atlanta — on-point.
GitHub identity	Writes run as whoever gh auth status is. CyClaw never stores the token. A draft PR is still a public or org-visible statement by that identity.
Shared API key	CYCLAW_API_KEY is the same secret as chat/admin. Theft on a shared box = can hit POST <code>/api/agent/runs/{id}/publish</code> . <code>auth.enabled</code> ships false.
Confirm replay	HTTP confirm:true is JSON-replayable. No TTY keypress. Accepted 2026-08-01 under single-operator + same-origin + CSRF. That acceptance is not multi-user safety.
I5 vs harness soul	I5 (reason + injection scan + drift hash) is an HTTP-path control on Plane A. Harness reads <code>soul.md</code> raw off disk. Do not claim the coding console is I5-covered.
Prompt / web inject	<code>/web inject</code> and <code>/memory</code> on put untrusted text into the local model prompt. Injection-scanned, still operator-owned. Do not pin client secrets as notes.

Topic	Rule for this console
Cloud planner	--confirm-online + provider keys from env. Issue/PR/repo text with EU personal data is a transfer to xAI or Anthropic. Confirm-online is the consent artifact. Audit stores a plan hash.
Workspaces	data/agentic/workspaces keeps full clones after approve. No retention scheduler. /agent discard is the hygiene command. Leaving third-party clones is a data-holding event.
.env keys	POST /api/keys writes \$CYCLAW_HOME/.env mode 600. Restart required before gate.py sees them. Names only in audit. MANAGED_KEYS only.
Loopback illusion	main() refuses non-loopback bind. uvicorn --host 0.0.0.0 bypasses it. api_key_optional only for loopback peer AND no forwarding headers.
Checks argv	Console sends profile names. A local CLI checks-file can contain git push. Do not hand an untrusted model a checks-file and call it "the model pushed."
Certifications	FSCONNECT playbook maps NIST 800-171 / CMMC / HIPAA / SOC 2 as operator claims. This PDF is not a certification. Do not advertise CyClaw as HIPAA-compliant because a checklist exists.
Threat model	Fifteenth amendment (#1319): trusted-operator, still single-tenant. Roles on auth.enabled are not multi-tenant IAM. One corpus / soul / model.

10. Troubleshooting and residuals

Symptom	Likely cause	Fix
CLI "worked" (exit 0) but nothing cloned	agentic.enabled false → clean no-op	status first. Require a run-id in the JSON.
403 TOOL_DENIED on /agent confirm	ToolBroker allowlist empty or missing agent_run	Do not treat API key as sufficient.
409 AGENT_RUN_BUSY	Another run, or shared-backend chat turn	Wait or /loop stop. Check GET /api/agent/runs.
Approve refused after reload	#1301: displayed-diff guard reset by /clear or F5	/agent status then approve again.
Publish refused with enabled true	Missing reason/confirm, head prefix, EXECUTION_ENABLED kill env, or writes_enabled flipped	Read the typed AgenticWriteRefused. Do not retry a timeout.
Origin 403 after opening localhost	Page was served on 127.0.0.1 (or the reverse)	Same host/scheme/port. No automatic switch.
Users panel 503	auth.enabled false	Expected. Session auth is off in the shipped tree.
soul text looks unsanitized in chat	Harness reads soul.md raw (Rule 5)	Not a regression of I5. Edit the file or use Plane A /soul/apply.

Residual list — do not sand these off

- Windows Job Object ≠ network isolation.
- Pre-armed write flags. One YAML bool + reason + confirm = draft PR as the laptop's gh identity.
- Confirm is JSON-replayable. HTTP publish is network-reachable on loopback.
- Shared CYCLAW_API_KEY with chat.
- Harness soul.md raw read. I5 does not cover this console.
- Retired-but-kept deepagent_github builder + harness_optimizer. Social control, not a compiler control. #1306 deleted GitHubCodingRunner.build_optional_deepagent; the builder package itself stays.
- fsconnect index → RAG corpus is a purpose change.
- Cloud --provider on the loop is a designed egress + billing footgun.
- Disabled CLI exit 0.
- MCP tools/call is unwrapped on Plane A — different investigation, not this console.
- Workspaces retain clones. Discard is operator duty.
- Trusted-operator model dies the moment a second person can hit :8790 with the key.
- FSCONNECT / HIPAA / SOC 2 mappings in the playbook are operator claims, not certifications.

Operator one-screen

Do these in order. Do not skip.

1. Bind 127.0.0.1:8790 only. Bookmark the exact origin.
 2. `gh auth status` is the identity that will own any draft PR.
 3. Leave `agentic.enabled` false until you mean draft PRs.
 4. `/loop + /goal` is chat. It does not clone, commit, or PR.
 5. Stage with `/agent run /iterations /pr XOR issue /plan`, then `/agent confirm <reason>`. Only confirm POSTs. 409 `AGENT_RUN_BUSY` means wait.
 6. `/agent status` until the pending diff is on this page, then approve. Digest-bound. Console guard $\neq$ server receipt.
 7. Push is a separate leaving-the-box act. Publish is a separate GitHub mutation. Discard is the retention act.
 8. After publish, the draft PR is attributable to the `gh` identity. Treat it as a public statement.
- Kill: `CYCLAW_AGENTIC_WRITE_DISABLE=1` then restart. Cork: `agentic.enabled: false`.

What this PDF is not

Not a multi-user IAM guide. Not a HIPAA / SOC 2 / CMMC certification. Not an authorization to flip `agentic.enabled`. Not a re-opening of the 2026-08-01 write-enablement sign-off. Not the NetConnect or fsconnect playbook. Not Plane A /query docs. Not a license to point this console at an employer device, a client share, or a repo you do not already administer.

This PDF does not re-open the signed write-enablement checklist in `docs/agentic/GITHUB_WRITE_ENABLEMENT.md` (accepted 2026-08-01; `EXECUTION_ENABLED` armed 2026-08-07). `FSCONNECT` / HIPAA / SOC 2 mappings in the playbook are operator claims, not certifications.

Sources (code wins)

HEAD `ccf63b03` (2026-09-06). `harness/README.md`, `harness/server.py`, `harness/agent_routes.py`, `harness/auth_routes.py` (#1302), `agentic/README.md`, `agentic/writer.py`, `agentic/real_repo_loop.py`, `docs/agentic/AGENTIC_README.md` §9, `docs/agentic/GITHUB_WRITE_ENABLEMENT.md`, `docs/HARNESS_MACOS.md`, `INVARIANTS.md` Rules 5 and 9, `utils/tool_broker.py`, `utils/ops_runner.py`. Package docstring drift on `agentic/__init__.py` is noted above. Invariant-guard 47/47. Graph still 12-node. OOB still six packages.

Companion: `CyClaw-NetConnect-HowTo.pdf` for the passive LAN connector. Do not grow `/loop` into a real-repo client. Do not grow `/web` into a browser. Do not grow this console into a multi-tenant product without a new threat-model amendment.