

These are the new choices added to the menu:

7 – Update Attendee Details: Allows updating the details of an existing attendee (name, DOB, gender, company).

8 – Delete Attendee: Removes an attendee from both MySQL and Neo4j databases after confirmation.

9 – Show Connected Attendees in the same Session: Displays all connected attendees who share at least one session with the selected attendee, including session details (title, date, speaker, room).

An example in the database is attendee ID 101 which is connected to 107, 111 and 109, and they are sharing sessions as follows:

Connected to Mia O'Brien, attendee ID: 107

Session ID	Title	Date	Speaker	Room Name
201	Modern Data Pipelines	2025-05-12	Dr. Niamh Burke	Main Hall
202	Scaling Neo4j for Recommendations	2025-05-12	Prof. Alan Shaw	Graph Lab

Connected to Grace Power, attendee ID: 111

Session ID	Title	Date	Speaker	Room Name
202	Scaling Neo4j for Recommendations	2025-05-12	Prof. Alan Shaw	Graph Lab

Note: Attendee ID 109 (not showed in the results) is attending session IDs 209 204, which are not shared with attendee ID 101.

Docker Compose and Seeding:

The `resources/docker-compose.yml` file starts the MySQL and Neo4j services used by the application.

MySQL loads the schema and sample data from `appdbproj.sql` when the container starts.

Neo4j uses `NEO4J\_AUTH` for authentication and a healthcheck to wait until the database is ready.

The `neo4j-seed` service runs `resources/neo4j\_seed.sh` after Neo4j becomes healthy.

The seeding script imports data from `appdbprojNeo4j.json` into Neo4j.

If the Neo4j data volume is removed, the database is reinitialized and reseeded on the next startup.