MIFlu reproduction and influenza forecasting audit

Internal technical report with explanatory questions and answers

Author	CHAN Sing Yeung
Snapshot	3 November 2026
Reading guide	Four evaluation axes with Q01–Q25 for supervisor discussion

Contents

1 Data and provenance
2 Methodology and literature
3 Reproduction of MIFlu
4 Benchmark accuracy
5 Peak timing and magnitude
6 Accuracy and parameter count
7 Statistical audit
8 Frozen language encoders
9 Ablation design and status
10 Interpretation and publication plan
11 Reproducibility and open checks
12 References

Reading purpose. This internal report supports supervision and explanation. Questions Q01–Q25 are placed beside the relevant evidence. Each answer connects named papers and reading locations to local evidence, explains the choice and gives a supervisor short answer. Accuracy and peak skill cover 28 arms; parameter exports cover 11, and paired tests 17.

1 Data and provenance

Run python scripts/verify_snapshot.py --raw-smoke and python -m pytest tests/test_snapshot_audit.py -q from the repository root. The audit re-derives headline aggregates, peak flags, correlations, regression, Holm adjustment and one raw prediction MSE. Seven newly added CPU audit tests passed; they are separate from the archived model suite. The corrected ZIP supplies tests_archive/. Collection fails under the historical layout and missing model dependencies. No archived-suite pass count or reliable collected total is claimed. Training, live HPC status and upstream code were not rerun. The original source CSVs are retained unchanged, with a separate corrected Holm export.

Table 1. Data and evaluation contract

Item	Value
Rows and channels	966 × 7
Chronological split	676 / 97 / 193
Train / validation / test indices	0–675 / 676–772 / 773–965
History and horizons	T=104; L=24/36/48/60
Available / scored windows	170/160; 158/144; 146/144; 134/128
ILITOTAL train mean / SD	9,439.84 / 9,003.15
Local numeric identity	max |difference| = 0

Identity compares the two supplied 966-row files after selecting their seven matching numeric columns. It does not re-establish byte identity with an independently downloaded upstream file. Dates in the author-format file are synthetic labels.

Q01 Why use 676 training, 97 validation and 193 test rows?

Answer and local evidence. The supplied 966-row protocol reserves floor(966 × 0.7) = 676 rows for training and floor(966 × 0.2) = 193 for testing. The remaining 97 form validation. Training fits weights and scaling, validation chooses checkpoints, and the final test block estimates performance after that choice. Chronological order keeps later observations out of earlier training. This is the declared project protocol, not a universal journal requirement. The independently pinned upstream split is still unverified.

Paper-based reasoning. Tan et al. explicitly use 70/10/20 for Illness [13, §3.3], while iTransformer preserves chronological separation [5, App. A.1]. These provide a concrete forecasting precedent: retain enough training data, use validation for model selection, and reserve later observations for the final test. The exact 676/97/193 integers come from our 966 rows and rounding rule. The literature supports the design rationale; it does not prove that this ratio is optimal for every influenza season or that our upstream file identity is established.

Say to the supervisor. The split follows an Illness precedent in Tan et al.; chronological separation protects the final evaluation [13, 5].

Reading locator. Tan et al. [13], §3.3 Datasets and Evaluation Metrics; iTransformer [5], Appendix A.1.

Evidence. configs.py DATA_PROFILES[author_repo_966]; BENCH_MSE_BY_MODEL_L.csv; eval_windows.py

Q02 Why score 160 windows when 170 are available at L24?

Answer and local evidence. The local evaluation contract preserves complete batches of 16: (W//16)×16. Thus 170/158/146/134 available windows become 160/144/144/128 scored windows at L24/36/48/60. Using the same retained windows across models prevents a comparison of different test examples. Cropping can nevertheless change scores by removing a particular tail of time. It is a comparability choice inherited by this snapshot, not evidence that cropping is scientifically optimal. Full-window sensitivity remains necessary; a specific discarded-tail difficulty ratio was not independently reverified.

Paper-based reasoning. Tan et al. retain original data-loaders and training conditions during their reproduction checks [13, §3.1]. This supports disclosing exactly which examples are scored; it does not require cropping. Our complete-batch rule changes the scoring population. Giving every model the same retained windows removes a comparison unfairness, but deleting the tail can still alter the result. The necessary sensitivity analysis is to score every model on all available windows and compare rankings. A literature citation cannot establish our discarded-tail difficulty without its raw calculation.

Say to the supervisor. Cropping preserves a shared scoring population; full-window rescoring tests its effect [13].

Reading locator. Tan et al. [13], §3.1 Reproducibility Note; local eval_windows.py.

Evidence. BENCH_MSE_BY_MODEL_L.csv; eval_windows.py; scripts/verify_snapshot.py --raw-smoke

Q03 Why fit scaling on training data only?

Answer and local evidence. A mean or standard deviation fitted on the complete series would use information from the future test block. Train-only scaling keeps that information out of model preparation. Each channel is standardised separately. The local equality check compares seven matching numeric columns in the two supplied files and finds maximum absolute difference zero. That verifies numeric equality of these local copies, not byte identity with a newly downloaded author file.

Paper-based reasoning. Kapoor and Narayanan identify preprocessing across the training/test boundary as a leakage route [22, L1.2]. Here that means fitting channel means and standard deviations only on training, then reusing them. If future observations determine these constants, preparation has already adapted to the held-out distribution even without using test labels in gradient updates. This makes train-only scaling part of the experiment. The separate local file-equality check establishes matching inputs, not absence of every possible leakage route.

Say to the supervisor. Preprocessing is fitted on training only, following the leakage distinction in Kapoor and Narayanan [22].

Reading locator. Kapoor and Narayanan [22], Results, leakage taxonomy L1 and L1.2.

Evidence. 06_原始数据集/scaler_miflu_author966.json; scripts/verify_snapshot.py

2 Methodology and literature

Patching and linear baselines are established [3–5]. Time-LLM, CALF and TimeCMA use different alignment/adaptation designs [6–8]. Chronos, TimesFM, Moirai and Lag-Llama pretrain on numerical series and were not evaluated here [9–12]. Earlier LLM-removal work already questions the benefit of language pretraining [13], while a 2026 preprint reports conditional benefits under cross-dataset shifts [14]. The contribution here is the specific influenza protocol audit and multi-metric comparison.

Table 2. Separate reproduction and benchmark protocols

Item	Reproduction	Benchmark
Seeds	2021–2030 (10)	42/43/44 (3)
Models	MIFlu	13 conventional + 4 LLM-based + 11 frozen encoders
Selection	Validation checkpoint	Validation checkpoint
Scores	7-variable z-space MSE / MAE	7-variable MSE / MAE; ILITOTAL PTE / PIE
Windows	160 / 144 / 144 / 128	160 / 144 / 144 / 128

Three seeds are a compute-budget choice, not a universal venue rule. Reproduction and benchmark estimates use different seed sets. Do not substitute one for the other. Exact upstream protocol defects remain to be checked against a pinned author revision.

Q04 Why ten reproduction seeds but three benchmark seeds?

Answer and local evidence. They answer different questions. The supplied reproduction uses seeds 2021–2030 to compare with the transcribed paper table. The broader benchmark uses 42/43/44 to compare

implementations under one shared protocol. The retained matrix is 28 models × 4 horizons × 3 seeds = 336 cells. Ten seeds would require 1,120 cells. Three reflects the project compute budget; it does not prove adequate power, and additional seeds can improve uncertainty estimation. Neither a universal three-seed venue rule nor zero benefit from more seeds is established.

Paper-based reasoning. The original three-seed citation is incorrect. PatchTST uses fixed-seed main results plus a five-seed supervised robustness check [3, App. A.6.1]; iTransformer reports five-run standard deviations [5, App. A.2, Table 5]. Neither passage establishes three seeds as their shared convention. Our choice is a compute compromise. Bouthillier et al. distinguish repeated-run precision from broader benchmark variation [19]. Extra seeds can improve the former; extra seasons/origins address different uncertainty. Ten reproduction repetitions do not make the separate three-seed benchmark equally precise.

Say to the supervisor. Three seeds are our compute compromise. Both cited papers provide five-seed robustness evidence, motivating stronger checks [3, 5].

Reading locator. PatchTST [3], Appendix A.6.1; iTransformer [5], Appendix A.2 and Table 5; Bouthillier et al. [19], Appendix C.3.

Evidence. ESSAY_VS_REPRODUCTION_TABLE_V.csv; BENCH_MSE_BY_MODEL_L.csv; dlv/data.py ORACLE

Q05 Which implementation differences are established?

Answer and local evidence. The local code selects checkpoints on validation and scores all seven standardised channels. Supplied notes attribute test-selected checkpoints and a one-channel loader to upstream code, but no independently inspected pinned author checkout supports that attribution here. Notes also describe differences in learning-rate and epoch settings. Consequently we disclose the local procedure and unresolved reference settings rather than claiming that exactly two repairs explain every score difference. A fair causal comparison would hold data, seeds and all other settings fixed while changing one factor.

Paper-based reasoning. A checkpoint is a model-selection choice. Selecting it by test error uses the final evaluation to fit that choice, contrary to clean separation [22, L1]. This justifies our validation-selected checkpoint independently of whether a particular upstream bug can be proved. Scoring all seven declared channels is a separate metric-consistency issue. Neither principle proves Moon et al. committed the alleged defects or that exactly two changes caused our gap. Causal attribution needs matched runs changing checkpoint selection, loader or another factor one at a time.

Say to the supervisor. Validation selection protects the held-out test; upstream defect attribution is a separate evidence question [22].

Reading locator. Kapoor and Narayanan [22], taxonomy L1, clean separation through modelling and evaluation.

Evidence. train_miflu.py; audit/REPO_AUDIT.md; audit/UNVERIFIED_ITEMS.md

We use a chronological split and train-only scaling. Validation selects checkpoints in this implementation. The handoff attributes test-set checkpoint selection and a one-variable loader to upstream code, but a pinned author checkout is absent and the public endpoint could not be opened. Those upstream allegations remain unverified. The notes also show learning-rate differences between code defaults and paper settings, so the comparison must not be described as differing in only two ways.

Peak timing error (PTE) is the absolute difference between predicted and observed peak weeks. Peak intensity error (PIE) is the absolute peak-height error divided by the observed peak, expressed as a percentage. Kramer–Shaman [2] verifies the separate one-week and 25% tolerances. We apply both to mean errors in each (model, L, step) cell. This joint screen and its peak detector are project choices, not a clinical acceptance standard. A mean-error pass is not an individual-season success probability.

Q06 Why use seven-variable MSE but ILITOTAL peak errors?

Answer and local evidence. Seven-variable MSE averages squared errors after each channel has been standardised, so it measures overall dimensionless forecast error. This average loss is not itself a patient-count

time series and has no single inverse scaler. Peak timing and height require an actual series. We therefore compute them on ILITOTAL after its own training-fit inverse transform, with mean 9,439.84 and standard deviation 9,003.15 patients. A model can do well across seven channels while having worse ILITOTAL peaks. Different targets and loss functions help explain the different rankings.

Paper-based reasoning. Hyndman and Koehler explain why measurement scale matters [21, §2.1]; Kramer and Shaman define peaks on an observed disease series [2]. Our standardised aggregate divides each channel's squared error in original units by its training variance. The result is a dimensionless loss, not a patient-count curve with one inverse scaler. For peaks, inverse-transform ILITOTAL predictions and observations first, then locate peaks. Taking a peak of the seven-channel loss would answer a different question. Literature motivates an interpretable endpoint; ILITOTAL is our explicit operational choice.

Say to the supervisor. Overall standardised error and an interpretable disease peak are different endpoints [21, 2].

Reading locator. Hyndman and Koehler [21], §2.1; Kramer and Shaman [2], Forecast accuracy and comparison.

Evidence. BENCH_MSE_BY_MODEL_L.csv; BENCH_PTE_PIE_BY_STEP.csv; scaler_miflu_author966.json

3 Reproduction of MIFlu

The reproduction CSV reports mean MSE 1.4995 versus 1.4355, a 4.5% increase. MSE is lower at L24 and L36 and higher at L48 and L60. Mean MAE is 0.8043 versus 0.7452 (+7.9%), but its signs are one lower and three higher; MAE does not share the MSE 2–2 crossover. Protocol and missing upstream provenance limit claims of exact replication.

Table 3. MIFlu reproduction compared with the paper

Horizon	Our MSE ± SD	Paper MSE	Δ MSE	Our MAE	Paper MAE	Δ MAE
L=24	1.3045 ± 0.0883	1.5420	-15.4%	0.7482	0.7260	+3.1%
L=36	1.3561 ± 0.1603	1.4220	-4.6%	0.7712	0.7790	-1.0%
L=48	1.6543 ± 0.1064	1.4140	+17.0%	0.8381	0.7570	+10.7%
L=60	1.6829 ± 0.2109	1.3640	+23.4%	0.8596	0.7190	+19.6%
4-horizon mean	1.4995	1.4355	+4.5%	0.8043	0.7452	+7.9%

Source: ESSAY_VS_REPRODUCTION_TABLE_V.csv, lines 2–6. SD is recomputed from the code-transcribed ten-seed oracle; its raw run logs are not included. Positive differences mean higher error.

Reproduction conclusion. The observed MSE gap is +4.5% under disclosed implementation differences. This does not establish superiority over the paper.

Q07 Why is MIFlu 1.4995 here but 1.5574 in the benchmark?

Answer and local evidence. The first is the four-horizon mean from the ten-seed reproduction table. The second is the four-horizon mean under the three benchmark seeds. They summarise separate run sets. Compare 1.4995 with the reported paper mean 1.4355 for reproduction, and compare 1.5574 with other models in the benchmark for model selection. Their difference is not a demonstrated improvement, degradation or transcription error between two otherwise identical experiments. Full run configuration and raw provenance are required to attribute it.

Paper-based reasoning. Bouthillier et al. show that benchmark estimates depend on the sampled learning pipeline [19]. A mean is therefore an estimate over specified runs, not an immutable property of a model name. Our two MIFlu estimates summarise separate seed sets and serve different comparisons. The gap could combine seed variability with configuration differences; it does not isolate one cause. Explain each table's run definition first, then request matched run-level configurations if the cause of the difference matters.

Say to the supervisor. They estimate separate run sets; the difference is not a controlled effect of one change [19].

Reading locator. Bouthillier et al. [19], §§2–3, benchmark estimators and sources of variation.

Evidence. ESSAY_VS_REPRODUCTION_TABLE_V.csv lines 2–6; BENCH_MSE_BY_MODEL_L.csv model=miflu

Q08 Why do MSE and MAE give different sign patterns?

Answer and local evidence. MSE squares errors and gives larger errors more weight. MAE averages absolute errors. Changing a few large errors can therefore alter MSE and MAE differently. Relative to the paper values, MSE is lower at L24/L36 and higher at L48/L60, whereas MAE is lower only at L36 and higher at the other three. The means are +4.5% MSE and +7.9% MAE. Calling both a two-versus-two crossover would misread the table.

Paper-based reasoning. The paper distinguishes squared and absolute errors and their sensitivity to large residuals [21]. As an algebraic illustration, not an observed run, doubling a residual doubles its absolute contribution but quadruples its squared contribution. A changed residual distribution can thus move MSE and MAE differently. Our CSV determines the actual horizon signs; the literature explains why different signs are possible. Per-channel and per-window residuals, rather than this general principle alone, are needed to identify the actual errors behind the gap.

Say to the supervisor. MSE weights large residuals more strongly than MAE, so the horizon signs must be read separately [21].

Reading locator. Hyndman and Koehler [21], §2.1, MSE/MAE and sensitivity to large residuals.

Evidence. ESSAY_VS_REPRODUCTION_TABLE_V.csv lines 2–6

Table 4. Code-transcribed reproduction oracle

Seed	L24	L36	L48	L60
2021	1.240157	1.314358	1.482299	1.599641
2022	1.201078	1.306645	1.711215	1.664878
2023	1.284212	1.269466	1.663857	1.821282
2024	1.259462	1.154099	1.879495	1.915250
2025	1.464643	1.767328	1.723161	1.410785
2026	1.368497	1.312511	1.620327	1.984315
2027	1.392309	1.400796	1.628296	1.614602
2028	1.230425	1.302717	1.588157	1.401814
2029	1.231536	1.404061	1.570881	1.520661
2030	1.373057	1.328807	1.675020	1.895393

Arithmetic checked against the reproduction CSV. The source is the ORACLE constant in dlv/data.py and verify_miflu_oracle.py. Raw ten-seed run logs were not supplied, so this is not an independent raw-prediction verification.

Q09 Do the seed oracle and plots prove a complete reproduction?


Answer and local evidence. The oracle is a code-transcribed record of ten seed scores. Its means and standard deviations can be checked arithmetically, but the corresponding raw ten-seed logs and predictions are not supplied for independent rescoring. The imported plots illustrate the benchmark series and are not independent traces of those ten reproduction runs. Checkpoint choice, seed variability and configuration differences are possible explanations for the horizon pattern, not isolated causal findings. The defensible result is a +4.5% mean-MSE gap under disclosed limits.

Paper-based reasoning. Repeated-run estimates and traceable evaluation address different weaknesses [19, 22]. The oracle checks the arithmetic of a transcribed record; saved predictions would check whether the pipeline produced it. The practical chain is run configuration → prediction → scoring code → cell → aggregate. A benchmark plot is another summary and cannot establish a ten-seed reproduction trajectory. Missing links limit the claim even when the mean is close. The imported panels remain useful illustrations if their true provenance is stated.


Say to the supervisor. The oracle establishes arithmetic; raw outputs establish provenance. Both evidence levels matter [19, 22].

Reading locator. Bouthillier et al. [19], variance analysis; Kapoor and Narayanan [22], model info sheets.

Evidence. dlv/data.py ORACLE; ESSAY_VS_REPRODUCTION_TABLE_V.csv; figure_captions.json



miflu, L=24. ILITOTAL in patient counts against the file's test-week index. Black is the observed series; the other curves use fixed forecast steps s0–s3. Scored windows: 160. Imported illustrative figure; raw figure inputs were not independently regenerated in this audit.



miflu, L=60. ILITOTAL in patient counts against the file's test-week index. Black is the observed series; the other curves use fixed forecast steps s0–s3. Scored windows: 128. Imported illustrative figure; raw figure inputs were not independently regenerated in this audit.

4 Benchmark accuracy

Table 5. Accuracy of all retained benchmark arms

#	Model	L24	L36	L48	L60	Mean MSE	Mean MAE
1	MIFlu	1.3323	1.2632	1.7774	1.8567	1.5574	0.8199
2	PatchTST	1.4402	1.6154	1.9288	1.6640	1.6621	0.8786
3	NLinear	1.7971	1.7950	1.9574	1.9368	1.8716	0.9183
4	DNN	1.8920	1.7684	2.2603	2.6451	2.1415	1.0057
5	TimeCMA	2.3281	2.5794	2.7104	2.8146	2.6081	1.0676
6	Gradient Boosting	3.5658	3.6867	3.6533	3.7521	3.6645	1.2521
7	KNN	3.7231	3.7623	3.7740	3.8820	3.7854	1.3293
8	Random Forest	3.5486	3.8251	4.0159	4.1710	3.8901	1.2779
9	iTransformer	3.7656	4.0596	4.0438	4.1088	3.9945	1.3476
10	Decision Tree	4.5340	4.1380	4.2186	4.3884	4.3198	1.3798
11	Hunyuan-1.8B	4.5629	4.5877	4.7111	5.0879	4.7374	1.4755
12	Hunyuan-7B	4.3438	4.6624	4.9201	5.1120	4.7596	1.4685
13	DeepSeek-R1-Qwen-1.5B	4.6012	4.6242	4.9245	4.9963	4.7866	1.5002
14	DeepSeek-R1-Llama-8B	4.4337	4.7715	4.8929	5.2019	4.8250	1.4786
15	GRU	4.2895	5.3099	5.1751	4.7736	4.8870	1.5174
16	DeepSeek-R1-32B	4.4401	4.8565	5.0136	5.4386	4.9372	1.4935
17	LSTM	4.4965	5.1359	5.2088	5.1939	5.0088	1.5303
18	DeepSeek-R1-Qwen-14B	4.4976	4.9164	5.1687	5.4838	5.0166	1.5019
19	DeepSeek-R1-Qwen-7B	4.5551	4.9991	5.2417	5.3272	5.0308	1.5133
20	RNN	4.4222	5.2893	5.3424	5.2157	5.0674	1.5634
21	ContextPilot-8B	4.6094	5.1318	5.2895	5.3065	5.0843	1.5255
22	Hunyuan-4B	4.7383	5.0535	5.2876	5.4474	5.1317	1.5450
23	ContextPilot-14B	4.7674	5.1566	5.2168	5.6388	5.1949	1.5407
24	Qwen2.5-1.5B	4.7840	5.0587	5.4546	5.5224	5.2049	1.5725
25	Qwen-Time	4.7190	5.1325	5.6894	5.4818	5.2557	1.5794
26	SVR	5.2248	5.3581	5.3781	5.3940	5.3388	1.4986
27	CALF	5.3624	5.5113	5.6442	5.7962	5.5785	1.6190
28	CNN	5.5021	5.3098	5.2801	6.3698	5.6155	1.6720

Source: BENCH_MSE_BY_MODEL_L.csv, keyed by model and L. Each row averages three seeds on 160/144/144/128 windows. DLinear is excluded by project choice; that exclusion needs a documented sensitivity analysis. Names denote project implementations, whose equivalence to published methods is not established by this ranking.

Q10 What do the 28 models and different subsets mean?

Answer and local evidence. The retained roster is 13 conventional + 4 LLM-based + 11 frozen encoders. Accuracy and peak analysis cover all 28. Parameter exports support 11 arms, while paired tests cover 17 non-encoder models including MIFlu. DLinear is excluded from the retained roster and paired table by project choice. Its appearance in historical provenance does not make it a retained arm. A sensitivity analysis including DLinear would strengthen baseline coverage; prior appearance in the source paper is not by itself a scientific reason to omit it.

Paper-based reasoning. The families test different explanations: simple temporal mapping [4], patches and inverted variable tokens [3, 5], and explicit cross-modal alignment [7, 8]. This motivates diverse controls, not a claim that 28 is an optimal count. It also makes implementation fidelity important: a named adaptation may omit a paper's decisive alignment or training component. DLinear is a relevant simple control in this literature. Its appearance in the source paper is not itself a scientific reason to omit it from a sensitivity analysis.

Say to the supervisor. The papers motivate different controls; the exports determine which models each analysis actually covers [3–5, 7, 8].

Reading locator. Zeng et al. [4], §4; PatchTST [3], §3.1; iTransformer [5], §3; CALF [7] and TimeCMA [8], author abstracts.

Evidence. BENCH_MSE_BY_MODEL_L.csv; BENCH_EFFICIENCY.csv; BENCH_PAIRED_TESTS.csv; BENCH_GPU_PROVENANCE.csv

Q11 Does the lowest MSE make MIFlu the deployment winner?

Answer and local evidence. MIFlu has the lowest observed benchmark MSE, 1.5574. That is a descriptive accuracy result under one national split. It does not measure the cost of missed peaks, false alarms, runtime, regional robustness or prospective benefit. The larger MSE spread also does not establish that hyperparameter tuning is unimportant, because tuning was not experimentally varied as an alternative factor. The later evaluation axes ask additional questions that the accuracy table alone cannot answer.

Paper-based reasoning. Peak timing/intensity are disease-specific endpoints [2], while interval scoring evaluates predictive uncertainty [18]. A seven-channel point-error ranking supplies neither automatically. Separate observed accuracy, peak trade-offs and operational cost. NLinear's lower height error does not erase its worse mean timing; MIFlu's lowest MSE does not establish calibrated intervals or prospective benefit. This lets us defend an evidence-based selection process before claiming a public-health deployment winner.


Say to the supervisor. MIFlu wins the observed point-error ranking; peak endpoints and uncertainty need their own evidence [2, 18].

Reading locator. Kramer and Shaman [2], Forecast accuracy and comparison; Bracher et al. [18], §§3–4.


Evidence. BENCH_MSE_BY_MODEL_L.csv; audit/GRADE_READINESS.md

F0 conclusion. MIFlu has the lowest observed MSE (1.5574), but MSE alone does not establish public-health utility. The top-three spread is 20.2% relative to MIFlu, not less than 20%.

The roster is 13 conventional models, MIFlu plus three other LLM-based implementations, and 11 frozen encoders. These sum to 28. All 28 have lower mean MSE than the seasonal-naive export (6.2132). No claim about hyperparameter tuning being less important is supported.



patchtst, L=24. ILITOTAL in patient counts against the file's test-week index. Black is the observed series; the other curves use fixed forecast steps s0–s3. Scored windows: 160. Imported illustrative figure; raw figure inputs were not independently regenerated in this audit.



nlinear, L=24. ILITOTAL in patient counts against the file's test-week index. Black is the observed series; the other curves use fixed forecast steps s0–s3. Scored windows: 160. Imported illustrative figure; raw figure inputs were not independently regenerated in this audit.

5 Peak timing and magnitude

Peak timing error (PTE) is the absolute difference between predicted and observed peak weeks. Peak intensity error (PIE) is the absolute peak-height error divided by the observed peak, expressed as a percentage. Kramer–Shaman [2] verifies the separate one-week and 25% tolerances. We apply both to mean errors in each (model, L, step) cell. This joint screen and its peak detector are project choices, not a clinical acceptance standard. A mean-error pass is not an individual-season success probability.

Table 6. Peak timing and intensity error

Model	PTE (wk)	PIE (%)	Joint passes	s0 PTE	s0 PIE (%)
MIFlu	1.128	26.846	4/16	0.347	18.884
PatchTST	1.240	32.755	0/16	0.681	30.553
NLinear	1.677	9.477	4/16	0.208	3.250

Means are across 16 (L, step) cells. Passes apply PTE ≤ 1 week and PIE ≤ 25% to each cell's aggregated errors, not to each individual season. PIE is point-forecast magnitude error, not probabilistic calibration.

Table 7. Joint peak screen for each horizon and lead

Model	L	s0	s1	s2	s3
NLinear	24	PASS 0.111 / 3.949	fail 1.333 / 8.411	fail 2.333 / 11.943	fail 2.667 / 18.739
NLinear	36	PASS 0.333 / 4.181	fail 1.333 / 7.222	fail 2.111 / 15.313	fail 2.667 / 18.145
NLinear	48	PASS 0.222 / 2.419	fail 1.222 / 4.727	fail 2.222 / 9.979	fail 2.778 / 16.655
NLinear	60	PASS 0.167 / 2.450	fail 1.444 / 4.542	fail 2.556 / 9.952	fail 3.333 / 13.000
MIFlu	24	PASS 0.000 / 18.307	fail 0.889 / 26.686	fail 1.222 / 30.472	fail 1.333 / 31.638
MIFlu	36	PASS 0.000 / 18.695	fail 0.778 / 26.333	fail 1.667 / 31.514	fail 1.333 / 32.427
MIFlu	48	fail 1.222 / 18.004	PASS 0.667 / 24.795	fail 1.222 / 30.133	fail 1.333 / 33.236
MIFlu	60	PASS 0.167 / 20.530	fail 1.333 / 25.799	fail 2.222 / 29.790	fail 2.667 / 31.177
PatchTST	24	fail 0.667 / 30.580	fail 1.000 / 34.044	fail 1.222 / 33.572	fail 1.222 / 30.722
PatchTST	36	fail 1.000 / 26.235	fail 1.667 / 32.247	fail 1.333 / 31.245	fail 1.333 / 33.854
PatchTST	48	fail 0.556 / 30.360	fail 1.333 / 30.878	fail 0.889 / 35.158	fail 0.889 / 35.002
PatchTST	60	fail 0.500 / 35.035	fail 1.667 / 34.342	fail 2.222 / 35.674	fail 2.333 / 35.133

Each entry gives PTE in weeks / PIE in percent. s0–s3 are the first to fourth forecast weeks. The detector uses prominence 0.15 × range, distance 15, and ±8-week matching. These detector settings and joint aggregation are project choices. Source: BENCH_PTE_PIE_BY_STEP.csv.

Q12 Why do MIFlu and NLinear both pass 4/16?

Answer and local evidence. A pass requires mean PTE ≤ 1 week and mean PIE ≤ 25% in the same (L, step) cell. NLinear passes step 0 at all four horizons. MIFlu passes step 0 at L24/L36/L60 and step 1 at L48. Equal counts therefore hide different locations and error magnitudes. Across all 16 cells, NLinear has lower PIE, 9.477% versus

26.846%, while MIFlu has lower PTE, 1.128 versus 1.677 weeks. The result is a timing–height trade-off, not dominance by either model.

Paper-based reasoning. The separate literature endpoints motivate inspecting timing and height before reducing them to a pass count [2]. Our equal four-pass counts hide different lead/horizon locations and distances from the thresholds. An application emphasising one-week-ahead height could favour a different trade-off from an application emphasising timing. That conditional interpretation comes from our table, not from a literature recommendation of NLinear. A binary pass is a coarse summary of continuous errors.

Say to the supervisor. Equal counts conceal different cells and a timing–height trade-off [2].

Reading locator. Kramer and Shaman [2], Forecast accuracy and comparison, separate timing/intensity tolerances.

Evidence. BENCH_PTE_PIE_BY_STEP.csv model in {miflu,nlinear}

Q13 Does 4/16 mean a 25% chance of a correct epidemic forecast?

Answer and local evidence. No. The denominator is four horizons times four fixed forecast steps, not 16 independent seasons. Each cell already averages errors across the available runs/events. Applying thresholds after averaging can give a different answer from counting individual successful events. The separate timing and intensity tolerances are supported by Kramer–Shaman [2]; our conjunction on aggregated cells and detector settings are project choices. They are not a clinical acceptance test or a calibrated probability.


Paper-based reasoning. Kramer and Shaman evaluate forecast-level peak accuracy by lead time [2]. Our sixteen configuration cells have a different denominator. Applying a threshold to an average is mathematically different from averaging event-level pass indicators. Thus 4/16 cannot be relabelled as season success probability. Bracher et al. discuss calibration of predictive distributions [18, §4.2]; small peak-height error does not establish it. Estimating event success requires retaining individual outcomes, defining the event denominator and accounting for dependence.

Say to the supervisor. Our denominator counts configurations after averaging, not successful seasons or calibrated probabilities [2, 18].

Reading locator. Kramer and Shaman [2], Forecast accuracy and comparison / Fig. 2; Bracher et al. [18], §4.2.

Evidence. BENCH_PTE_PIE_BY_STEP.csv; Kramer–Shaman [2]; analysis peak detector settings

F1 conclusion. NLinear and MIFlu each pass 4/16 aggregated cells, while PatchTST passes 0/16. NLinear has lower mean PIE (9.477% versus MIFlu 26.846%) but higher mean PTE (1.677 versus 1.128 weeks). This is a timing –magnitude trade-off, not dominance. The ordering is inverted at both ends among the three leaders: MSE orders MIFlu, PatchTST, NLinear; PIE orders NLinear, MIFlu, PatchTST.



Peak error heat map for all 28 retained arms. Cells display means across horizons at fixed steps. Mean-level highlighting must not be interpreted as every horizon passing; the detailed grid gives per-horizon passes. Source: BENCH_PTE_PIE_BY_STEP.csv.

The positive MSE–PIE rank correlation (+0.736) means lower MSE generally accompanies lower PIE. The negative MSE–pass-count correlation (−0.429) also has the expected direction: lower error tends to accompany more passes. Neither statistic proves decoupling. NLinear's third-place MSE but first-place PIE provides a local mismatch between objectives.

Q14 Why can peak rankings differ without proving decoupling?

Answer and local evidence. The leading-three MSE order is MIFlu < PatchTST < NLinear; the PIE order is NLinear < MIFlu < PatchTST. Ordering is inverted at both ends, with different middle positions. Across all models, MSE–PIE correlation is positive (+0.736) and MSE–pass-count correlation negative (−0.429), both in the expected direction for generally better error. A local rank mismatch can coexist with those overall associations. We can claim that objectives change the ordering, not statistical independence or universal peak failure.

Paper-based reasoning. Zeng et al. describe NLinear's last-value subtraction, linear map and addition back [4]. This gives a testable hypothesis about level handling, not a proven explanation for our peaks. The ranking mismatch itself follows a simpler distinction: MSE aggregates many points and seven channels, whereas PIE concentrates on detected ILITOTAL peak height [21 gives the error-measure context]. A model can improve many non-peak points yet worsen this endpoint. Controlled variants and peak/residual diagnostics are needed to attribute the observed trade-off to architecture.

Say to the supervisor. The objectives aggregate different errors; NLinear's level correction is a hypothesis to test [4, 21].

Reading locator. Zeng et al. [4], §4 NLinear; Hyndman and Koehler [21], §2.1.

Evidence. BENCH_MSE_BY_MODEL_L.csv joined to BENCH_PTE_PIE_BY_STEP.csv; audit/verified_facts.json

6 Accuracy and parameter count

Table 8. Parameter analysis and rank associations

Quantity	Value
Regression slope / R^2	+0.1171 / 0.0223
Models with parameter exports	11
Subset Pareto set	NLinear 2,520; PatchTST 531,878
Parameter ratio	211.1×
Descriptive MSE reduction	11.2%
ρ(MSE, PIE)	+0.736 ($p < 0.0001$)
ρ(MSE, passes)	-0.429 ($p = 0.023$)

The Pareto analysis includes only 11 arms with parameter exports. MIFlu and the frozen encoders are not in that subset. Missing parameter counts are not zero. Parameter count is not a measurement of latency, memory or energy. Correlations are descriptive across models on one test set.

Q15 How should I explain the Pareto graph?

Answer and local evidence. The horizontal axis is parameter count and the vertical axis is MSE, so smaller values are preferred on both. A model is dominated within the measured subset if another has no more parameters and no higher MSE, with at least one strict improvement. The exported frontier contains NLinear and PatchTST: NLinear is smaller, while PatchTST has lower MSE. Neither dominates the other. This frontier covers only the 11 arms with parameter exports; MIFlu and the encoders are outside it, so a global frontier claim is unsupported.

Paper-based reasoning. iTransformer evaluates error alongside speed and memory [5, App. D], a precedent for considering performance with cost. Our cost axis is narrower: exported parameters. The two local frontier members follow from pairwise dominance in the eleven-model subset, not a paper's recommendation of a universal winner. A Pareto graph removes dominated choices; the remaining choices still need a budget or acceptable-error preference. Missing MIFlu cost data prevents calling it the frontier of all 28 models.

Say to the supervisor. The frontier removes dominated choices within the measured subset; a decision preference still chooses among them [5].

Reading locator. iTransformer [5], Appendix D Model Efficiency; local BENCH_EFFICIENCY.csv.

Evidence. BENCH_EFFICIENCY.csv; fig_pareto_frontier.png

Q16 Does 211 times more parameters mean 211 times slower?

Answer and local evidence. No. 531,878 / 2,520 = 211.1 compares exported PatchTST and NLinear parameter counts. Their observed MSE reduction is (1.871583 − 1.662078) / 1.871583 ≈ 11.2%. Parameter storage, operations, hardware utilisation and batch size affect runtime differently. Latency, peak memory and energy require direct comparable measurements. We use the phrase parameter efficiency, and leave missing parameter counts missing rather than treating them as zero or describing MIFlu as non-parametric.

Paper-based reasoning. iTransformer measures speed and memory under stated input/prediction lengths and the same batch size [5, App. D]. Our parameter export does not supply those measurements. Parameters affect storage; operations, token counts and hardware utilisation affect elapsed time differently. Consequently 211× parameters cannot imply 211× latency, memory or energy. A useful next efficiency table records hardware, precision, batch size and whether training or inference is timed. These fields cannot be invented from the parameter ratio.

Say to the supervisor. I report a parameter ratio. The literature shows the matched runtime measurements needed for a speed claim [5].

Reading locator. iTransformer [5], Appendix D, Fig. 10, matched speed/memory measurements.

Evidence. BENCH_EFFICIENCY.csv; BENCH_MSE_BY_MODEL_L.csv model in {nlinear,patchtst}

Q17 What does R squared of 0.0223 actually mean?

Answer and local evidence. For the chosen fit of MSE against log10(parameter count) in 11 exported arms, parameter size alone accounts for little observed variation. This descriptive association does not isolate the effect of capacity: architectures, optimisation and training regimes also vary. A low R squared does not prove that capacity is irrelevant or that an observed accuracy gain is random noise. A causal capacity study would vary size within a controlled family and training protocol.


Paper-based reasoning. PatchTST varies layers and hidden dimension and specifically finds ILI sensitive to those settings [3, App. A.6.2]. This is relevant evidence against dismissing tuning on a small influenza series. Our cross-model R^2 mixes architecture, optimisation and size; it is not a controlled capacity effect. A stronger follow-up varies depth/width within one family under a fixed training protocol and repeats runs. The planned MIFlu depth ladder begins this question, but its unaggregated status provides no scientific trend yet.

Say to the supervisor. Low cross-model R^2 does not dismiss tuning; PatchTST explicitly reports ILI sensitivity [3].

Reading locator. PatchTST [3], Appendix A.6.2, Fig. 5, layers/width and ILI sensitivity.

Evidence. BENCH_EFFICIENCY.csv; scripts/verify_snapshot.py linregress

F2 conclusion. The fitted slope is +0.1171 and R^2 is 0.0223 across the 11 arms with exported parameter counts. Size alone explains little of their observed MSE variation. This subset result does not prove that capacity is irrelevant.



Accuracy–parameter trade-off among 11 models with exported parameter counts. MIFlu and frozen encoders are omitted from this subset. Parameter count is not a measured runtime or memory cost. Source: BENCH_EFFICIENCY.csv.

7 Statistical audit

The source table contains 136 pairs from 17 models. The other 11 models are absent, so this is not an all-pairs analysis of 28 models. Holm uses a forward cumulative maximum after sorting raw p-values. The source uses a reverse cumulative minimum. At n=12, the two-sided exact floor 2/4096 multiplied by 136 exceeds 0.05, so this family cannot yield a rejection under proper Holm adjustment. Overlapping targets and repeated horizons also make the cells dependent. Raw p-values and unadjusted bootstrap intervals remain exploratory.

Table 9. Paired comparisons with corrected Holm adjustment

Model A	Model B	Δ MSE	p raw	p Holm	Effect*
NLinear	PatchTST	+0.2095	0.005859	0.1172	1.15
Gradient Boosting	RNN	-1.4029	0.000488	0.0664	4.86
KNN	NLinear	+1.9138	0.000488	0.0664	22.29
KNN	MIFlu	+2.2280	0.000488	0.0664	9.89
KNN	LSTM	-1.2234	0.000488	0.0664	5.28
iTransformer	TimeCMA	+1.3863	0.000488	0.0664	7.02
iTransformer	SVR	-1.3443	0.000488	0.0664	10.61

*136 pairs cover 17 models, not all 28. n = 12 matched horizon × seed cells. Forward cumulative-max Holm yields 0/136 rejections. The shown p values recover the exact 1/4096 enumeration grid from six-decimal exports; recomputing directly from rounded exports gives NLinear–PatchTST 0.117180 instead of 0.1171875. *The source effect uses pooled model SD, not paired-difference SD. Cell dependence limits inference.*

Q18 Why does the paired table contain seemingly unrelated model pairs?

Answer and local evidence. The report deliberately shows the NLinear–PatchTST frontier comparison first, followed by six rows with the smallest raw p-values. This combines the question of interest with examples of the wider test family. The frontier pair is 117th by ascending raw p in the exported table, so an automatic smallest-six display would omit it. The full family still contains all 136 comparisons; displayed-row selection never changes the Holm family or makes the selected pair significant.

Paper-based reasoning. Demšar motivates controlling the comparison family when inspecting particular differences [20]. Here the first row keeps the substantive frontier question visible; the next six show smaller raw-p contrasts. All 136 still enter the correction. Rank 117 refers to ascending raw p, not a model's accuracy rank. Choosing display rows cannot change that family. Because the article's main setting is multiple datasets, it also does not licence treating our overlapping horizons and shared test series as independent datasets.

Say to the supervisor. The first row serves the research question; the full family still determines correction [20].

Reading locator. Demšar [20], §3.2.2 Post-hoc tests; local raw-p rank.

Evidence. BENCH_PAIRED_TESTS.csv model_a=nlinear/model_b=patchtst; audit/verified_facts.json pair_raw_rank

Q19 Why do 128 raw significant pairs become zero after Holm?

Answer and local evidence. Testing many pairs increases the opportunity for false positives. Proper Holm sorts raw p-values and applies a forward cumulative maximum to the ordered multiplicity factors. The original exported column used the wrong direction and is quarantined. Recomputing all 136 gives 0/136 rejections, with minimum adjusted p about 0.0664 and NLinear–PatchTST 0.1172. With the documented two-sided exact n=12 resolution, the smallest possible raw p is 2/4096, already too large for Holm's first 0.05/136 threshold. Dependence between horizon–seed cells is an additional concern.

Paper-based reasoning. Demšar describes starting with the smallest p and stopping at the first failed Holm threshold [20]. Our first threshold is 0.05/136. The documented two-sided twelve-contribution sign-flip floor is 2/2^12; multiplying by 136 gives 0.06640625, so no pair can start the rejection sequence. This floor is local mathematical reasoning, not a result reported by Demšar for influenza. Holm permits dependence among valid p-values, but cannot repair invalid raw p-values from unjustified within-pair exchangeability. These are separate limitations.

Say to the supervisor. The exact-test floor exceeds Holm's first threshold; that is a design-resolution limit [20].

Reading locator. Demšar [20], §3.2.2 Holm step-down; local exact-enumeration derivation.

Evidence. BENCH_PAIRED_TESTS.csv p_raw; analysis_postprocess.py; audit/HOLM_RECOMPUTATION.csv

Q20 Does p = 0.1172 show that NLinear and PatchTST are equivalent?

Answer and local evidence. No. PatchTST retains 11.2% lower observed mean MSE and lower error in 10/12 matched cells. Non-rejection means this familywise procedure does not establish a difference at the chosen threshold. It does not establish a small enough difference for practical equivalence. Equivalence needs a prespecified acceptable margin and a suitable uncertainty/test design. The table's source effect also uses pooled model standard deviation rather than paired-difference standard deviation, so it is labelled as a source standardised effect.

Paper-based reasoning. Lakens distinguishes a nonsignificant difference test from equivalence with prespecified meaningful bounds [25]. Thus p = 0.1172 does not answer whether NLinear's observed extra error is acceptable for an application. Define that acceptable difference first, then use an uncertainty design respecting time/season dependence. Choosing a generous bound after seeing this table would not be convincing confirmation. Until then, observed error reduction, parameter ratio and inferential uncertainty should be reported together; the extra parameters cannot be dismissed as buying only noise.

Say to the supervisor. Non-rejection is not equivalence; the observed trade-off and unresolved inference coexist [25].

Reading locator. Lakens [25], Introduction and Testing for Equivalence.

Evidence. BENCH_EFFICIENCY.csv; BENCH_PAIRED_TESTS.csv; audit/CLAIM_AUDIT.md C3

F3 conclusion. Proper Holm gives 0/136 rejections (128/136 before adjustment), with a minimum adjusted p of about 0.0664 and NLinear–PatchTST p ≈ 0.1172. PatchTST still has 11.2% lower observed MSE with 211× the parameters and lower MSE in 10/12 cells. Non-rejection does not establish equivalence or show that the gain is noise.

8 Frozen language encoders

Table 10. Frozen encoders with shared linear readout

Encoder	MSE	vs MIFlu	PTE	PIE (%)	Passes
Hunyuan-1.8B	4.7374	3.04×	4.406	71.428	0/16
Hunyuan-7B	4.7596	3.06×	5.309	75.399	0/16
DeepSeek-R1-Qwen-1.5B	4.7866	3.07×	5.792	78.061	0/16
DeepSeek-R1-Llama-8B	4.8250	3.10×	4.306	77.121	0/16
DeepSeek-R1-32B	4.9372	3.17×	3.889	77.730	0/16
DeepSeek-R1-Qwen-14B	5.0166	3.22×	4.149	76.350	0/16
DeepSeek-R1-Qwen-7B	5.0308	3.23×	4.458	76.373	0/16
ContextPilot-8B	5.0843	3.26×	4.962	78.918	0/16
Hunyuan-4B	5.1317	3.30×	3.003	78.840	0/16
ContextPilot-14B	5.1949	3.34×	4.965	77.764	0/16
Qwen2.5-1.5B	5.2049	3.34×	5.333	74.650	0/16

11 retained encoders × 4 horizons × 3 seeds = 132 cells. The historical plan included two additional embedding-only arms, giving 156 planned cells; those 24 omitted cells are outside the 28-model roster. The result tests only this frozen-feature pipeline.

Q21 What can the frozen-encoder negative result explain?

Answer and local evidence. The tested pipeline freezes a language encoder and trains a linear readout. Its 11 encoder arms have MSE 4.7374–5.2049, all above decision tree 4.3198, with 0/16 joint passes each. This shows poor performance of these feature/readout configurations on this protocol. Distribution mismatch, frozen features and readout capacity are possible mechanisms, but the experiment does not separate them. Generation, prompting, fine-tuning and numerically pretrained time-series foundation models remain outside this test.

Paper-based reasoning. Time-LLM freezes its LLM but adds learned reprogramming and a prompt prefix [6]. Thus "frozen" alone does not define the same experiment as our feature/linear-readout pipeline. Chronos instead learns forecasting from numerical sequences [9]. These method differences justify keeping our negative finding narrow. To isolate a readout bottleneck, vary the readout/alignment while holding the encoder fixed; to isolate pretraining, compare matched pretrained and random backbones. Our eleven-arm result does not make those controlled separations.

Say to the supervisor. The failure concerns our feature/readout pipeline; Time-LLM and Chronos test other mechanisms [6, 9].

Reading locator. Time-LLM [6], author abstract; Chronos [9], §3.

Evidence. BENCH_MSE_BY_MODEL_L.csv family=llm_encoder; BENCH_PTE_PIE_BY_STEP.csv

F4 conclusion. The 11 tested frozen encoders score 4.7374–5.2049, or 3.04–3.34× MIFlu's MSE. All exceed the decision tree's 4.3198 and pass 0/16 cells. This is a negative result for this feature/readout configuration; prompting, fine-tuning and numerical foundation models remain untested.

Distribution mismatch, frozen capacity and the chosen readout are possible explanations. Their causal roles are not separated by these results. A linear readout does not guarantee that useful nonlinear features can be recovered.

9 Ablation design and status

Table 11. Ablation design and snapshot status

Variant	Flag	Cells	Status
Reference K=6	default	12	Already in benchmark
no_lora	--no-lora	12	DONE (not aggregated)
K=2	--num-layers 2	12	DONE (not aggregated)
K=4	--num-layers 4	12	DONE (not aggregated)
K=8	--num-layers 8	12	DONE (not aggregated)
K=12	--num-layers 12	12	DONE (not aggregated)

Owner-reported status at 3 November 2026: 60/60 additional cells, job 722968. Burgundy queue and per-cell manifests show 60/60 DONE; the per-variant aggregate trend has not been recomputed. The baseline 12 cells are not part of the additional 60. No trend is inferred.

F5 provisional conclusion. In miflu_model.py's author_faithful path, text follows time tokens behind causal attention and the head reads the time tokens. Static inspection therefore predicts no text influence during deterministic evaluation. The supplied tests_archive/test_miflu_ablations.py explicitly asserts both text invariance and full/no-text equality with matched CPU initialisation. It was inspected statically, not executed here. Other fusion paths and training randomness require separate checks.

Q22 Why might no-text give identical outputs in the default path?

Answer and local evidence. In the inspected author_faithful path, time tokens precede text tokens. Causal attention permits each position to read only its own or earlier positions, and the head reads the time-token positions. Those positions therefore cannot use later text in a deterministic evaluation forward pass. The supplied archive explicitly asserts text invariance and matched-initialisation full/no-text CPU equality, but those model tests were not executed here. Other fusion paths, dropout and independently trained trajectories require separate checks. The exact files and commands are in audit/NO_TEXT_VERIFICATION.md.

Paper-based reasoning. The Transformer paper explains masking that prevents attention to subsequent positions [24, §3.1]. With the inspected ordering, time positions cannot acquire later text through these layers, and the head reads time positions. This is a structural argument about a fixed forward path, not certification of repository runtime or bitwise equality. The three archived assertions must control weights, inputs and evaluation randomness when comparing changed text and matched full/no-text outputs. They remain not executed. Independent training can consume randomness differently and requires its own test.

Say to the supervisor. Causal masking supports the structural argument; controlled runtime tests must establish bitwise equality here [24].

Reading locator. Vaswani et al. [24], §3.1 Decoder; local ForecastingLLM.forward and archived assertions.

Evidence. miflu_model.py ForecastingLLM; tests_archive/test_miflu_ablations.py; audit/NO_TEXT_VERIFICATION.md

Q23 What does 60/60 ablation completion allow us to say?

Answer and local evidence. It is an owner-reported operational snapshot as of 3 November, not a live scheduler result or an aggregated model comparison. The additional design has five arms, each with four horizons and three seeds: 60 cells beyond the 12-cell reference. Without per-arm result exports, completion is not evidence of a depth trend or a benefit of LoRA. Do not infer a completed no-text ablation from the presence of its test assertions. We need run-level outputs, status and provenance before reporting scientific results.

Paper-based reasoning. Tan et al. remove or replace the LLM while retaining the surrounding trainable forecaster [13, §3.2]. This asks whether the backbone contributes beyond the wrapper. Our no-LoRA/depth variants address narrower adaptation/capacity questions; they do not automatically answer the same removal/replacement question or isolate text use. Partial completion is an operational status. Interpreting a scientific trend requires the reported variants' scores, repeated-run variability and a matched protocol. The literature supplies an experimental question, not a result for our unfinished ladder.

Say to the supervisor. The papers motivate removal/replacement controls; the incomplete ladder has not answered those causal questions [13].

Reading locator. Tan et al. [13], §3.2 Proposed Ablations, w/o LLM / LLM2Attn / LLM2Trsf.

Evidence. Owner snapshot; ablation design table; tests_archive/test_miflu_ablations.py

10 Interpretation and publication plan

One national series and one chronological split do not establish regional or prospective utility. Peak matching can use future observations to define events and is a retrospective evaluation tool. Synthetic date labels require a verified CDC calendar mapping before season-specific claims. Parameter exports omit MIFlu and encoders. The 60/60 ablation status is owner-reported, not a live cluster check. Modern numerical foundation baselines, regional results, rolling origins and validated uncertainty are missing.

Decision rule for future validation: specify an MSE budget B, an allowable peak-failure rate q, and decision costs before inspecting a new test period. Among models meeting B and q on validation seasons, minimise expected decision cost, then parameter count as a tie-breaker. For an escalate/wait decision, use costs c_FP for unnecessary escalation and c_FN for a missed surge, with zero cost for correct actions. Escalate when a validated surge probability exceeds c_FP/(c_FP+c_FN). Costs, B and q have not been elicited or validated, so no model is certified for deployment. NLinear is a low-cost candidate for further peak-height validation; MIFlu remains the observed MSE leader.

Recommendation O1: retain the evaluation contribution and repair its evidence base before adding a new mechanism. The current draft is oriented towards IEEE JBHI because its subject is health forecasting, but it is not submission-ready. Rolling origins, regional validation, stronger baselines and independent code provenance matter more than another architecture before the school deadline.

Q24 What is added beyond reproduction, and why keep O1?

Answer and local evidence. The study compares implementations across accuracy, peak skill, parameter efficiency and statistical evidence, with different declared subsets. We have not verified that the reference paper contains only the first two axes, so absence or first-ever claims are inappropriate. O1 develops this evaluation contribution through provenance repair, restored tests, rolling origins, regions and stronger controls. Optional O2 is validation-only peak-height recalibration: zero new GPU training if auditable validation/test predictions

already exist. Such validation exports are not established here; CPU time and money are unmeasured, and a few working days is only a planning estimate.

Paper-based reasoning. Simple-linear and LLM-removal critiques predate this project [4, 13]; Qiu et al.'s preprint reports conditional gains in larger cross-dataset settings [14]. Our narrower contribution connects audited influenza accuracy, peak endpoints, a cost subset and corrected inference. O1 checks persistence across origins/regions; Tashman motivates rolling-origin evaluation [23]. O2 adds validation-fitted height adjustment only if suitable prediction exports exist. A new mechanism cannot replace those checks or establish a universal verdict about LLM forecasting.

Say to the supervisor. O1 tests the influenza-specific findings; prior negative and conditional-positive evidence rule out a universal conclusion [4, 13, 14].

Reading locator. Zeng et al. [4], §4; Tan et al. [13], §3.2; Qiu et al. [14], abstract and §§3–5 (preprint); Tashman [23], publisher-indexed abstract.

Evidence. audit/INNOVATION_DECISION.md; audit/LITERATURE_REVIEW.md; sources.json [1]

11 Reproducibility and open checks

Run python scripts/verify_snapshot.py --raw-smoke and python -m pytest tests/test_snapshot_audit.py -q from the repository root. The audit re-derives headline aggregates, peak flags, correlations, regression, Holm adjustment and one raw prediction MSE. Seven newly added CPU audit tests passed; they are separate from the archived model suite. The corrected ZIP supplies tests_archive/. Collection fails under the historical layout and missing model dependencies. No archived-suite pass count or reliable collected total is claimed. Training, live HPC status and upstream code were not rerun. The original source CSVs are retained unchanged, with a separate corrected Holm export.

Hardware provenance covers 204 rows, including the excluded DLinear and omitting MIFlu and all frozen encoders. It overlaps 192 retained cells. Complete per-cell hardware coverage is therefore not established. The original reproduce_all.py targets historical paths and is not the audited quickstart.

Unverified items: pinned upstream checkpoint/loader protocol and learning rate; archived suite execution and no-text runtime test; ten-seed raw reproduction logs; model revisions/licences; live ablation and regional status; real CDC calendar mapping; current JBHI author limits/JCR record and next-cycle venue dates. Each requires its primary artefact, not a further prose assertion.

Q25 What can a supervisor reproduce now, and what remains unexecuted?

Answer and local evidence. The documented CPU commands reproduce CSV headline arithmetic, correct Holm and one raw prediction-cell MSE. Seven new CPU audit checks passed. The historical archive was supplied, but collection failed and its model assertions are not counted as passed. Full GPU training, all-run raw rescoring, live HPC, pinned upstream identity and no-text runtime remain unexecuted or unverified. Hardware provenance also lacks complete retained-cell coverage. A polished document does not close those gaps. Use the exact follow-up commands in audit/EXECUTION_STATUS.md and audit/NO_TEXT_VERIFICATION.md.

Paper-based reasoning. Kapoor and Narayanan ask for explicit reporting arguments rather than equating code availability with a valid result [22]. Here distinguish document rebuilding, CSV arithmetic, raw prediction rescoring and model retraining. A supervisor can begin with the CSV audit; the full bundle supports one raw-cell smoke check. Model text invariance needs the three named runtime assertions without skips in a pinned environment. The useful deliverable is a traceable evidence chain with exact commands and status. Passing one evidence level does not certify all the others.

Say to the supervisor. I distinguish recomputed results from static inspection and give the command and status for each [22].

Reading locator. Kapoor and Narayanan [22], model info sheets; EXECUTION_STATUS.md and NO_TEXT_VERIFICATION.md.

Evidence. audit/EXECUTION_STATUS.md; audit/NO_TEXT_VERIFICATION.md; audit/REPO_AUDIT.md

12 References

[1] Jaeuk Moon, Jonghwa Shim, Eunbeen Kim and Eenjun Hwang, "MIFlu: Large Language Model-Based Multimodal Influenza Forecasting Scheme," IEEE JBHI 29(10), 7790-7801, 2025. https://doi.org/10.1109/JBHI.2025.3561214

[2] Sarah C. Kramer and Jeffrey Shaman, "Development and validation of influenza forecasting for 64 temperate and tropical countries," PLOS Computational Biology 15(2), e1006742, 2019. https://doi.org/10.1371/journal.pcbi.1006742

[3] Yuqi Nie, Nam H. Nguyen, Phanwadee Sinthong and Jayant Kalagnanam, "A Time Series is Worth 64 Words: Long-term Forecasting with Transformers," ICLR, 2023. https://arxiv.org/abs/2211.14730

[4] Ailing Zeng, Muxi Chen, Lei Zhang and Qiang Xu, "Are Transformers Effective for Time Series Forecasting?," AAAI (preprint record opened), 2023. https://arxiv.org/abs/2205.13504

[5] Yong Liu et al., "iTransformer: Inverted Transformers Are Effective for Time Series Forecasting," ICLR (preprint record opened), 2024. https://arxiv.org/abs/2310.06625

[6] Ming Jin et al., "Time-LLM: Time Series Forecasting by Reprogramming Large Language Models," ICLR, 2024. https://arxiv.org/abs/2310.01728

[7] Peiyuan Liu et al., "CALF: Aligning LLMs for Time Series Forecasting via Cross-modal Fine-Tuning," arXiv:2403.07300, 2024. https://arxiv.org/abs/2403.07300

[8] Chenxi Liu et al., "TimeCMA: Towards LLM-Empowered Multivariate Time Series Forecasting via Cross-Modality Alignment," AAAI, 2025. https://arxiv.org/abs/2406.01638

[9] Abdul Fatir Ansari et al., "Chronos: Learning the Language of Time Series," Transactions on Machine Learning Research, 2024. https://arxiv.org/abs/2403.07815

[10] Abhimanyu Das, Weihao Kong, Rajat Sen and Yichen Zhou, "A decoder-only foundation model for time-series forecasting," ICML, PMLR 235, 10148-10167, 2024. https://proceedings.mlr.press/v235/das24c.html

[11] Gerald Woo et al., "Unified Training of Universal Time Series Forecasting Transformers," ICML, PMLR 235, 53140-53164, 2024. https://proceedings.mlr.press/v235/woo24a.html

[12] Kashif Rasul et al., "Lag-Llama: Towards Foundation Models for Probabilistic Time Series Forecasting," arXiv:2310.08278, version 3, 2024. https://arxiv.org/abs/2310.08278

[13] Mingtian Tan, Mike A. Merrill, Vinayak Gupta, Tim Althoff and Thomas Hartvigsen, "Are Language Models Actually Useful for Time Series Forecasting?," NeurIPS 37, 2024. https://arxiv.org/abs/2406.16964

[14] Xin Qiu et al., "Rethinking the Role of LLMs in Time Series Forecasting," arXiv:2602.14744 v1, preprint, 2026. https://arxiv.org/abs/2602.14744

[15] Chen Xu and Yao Xie, "Conformal prediction interval for dynamic time-series," ICML, PMLR 139, 11559-11569, 2021. https://proceedings.mlr.press/v139/xu21h.html

[16] Chen Xu and Yao Xie, "Sequential Predictive Conformal Inference for Time Series," ICML, PMLR 202, 38707-38727, 2023. https://proceedings.mlr.press/v202/xu23r.html

[17] Isaac Gibbs and Emmanuel Candès, "Adaptive Conformal Inference Under Distribution Shift," NeurIPS 34, 2021. https://arxiv.org/abs/2106.00170

[18] Johannes Bracher, Evan L. Ray, Tilmann Gneiting and Nicholas G. Reich, "Evaluating epidemic forecasts in an interval format," PLOS Computational Biology 17(2), e1008618, 2021. https://doi.org/10.1371/journal.pcbi.1008618

[19] Xavier Bouthillier et al., "Accounting for Variance in Machine Learning Benchmarks," Proceedings of Machine Learning and Systems 3, 2021. https://proceedings.mlsys.org/paper_files/paper/2021/file/0184b0cd3cfb185989f858a1d9f5c1eb-Paper.pdf

[20] Janez Demšar, "Statistical Comparisons of Classifiers over Multiple Data Sets," Journal of Machine Learning Research 7, 1–30, 2006. https://jmlr.org/papers/volume7/demsar06a/demsar06a.pdf

[21] Rob J. Hyndman and Anne B. Koehler, "Another look at measures of forecast accuracy," International Journal of Forecasting 22(4), 679–688, 2006. https://doi.org/10.1016/j.ijforecast.2006.03.001

[22] Sayash Kapoor and Arvind Narayanan, "Leakage and the reproducibility crisis in machine-learning-based science," Patterns 4, article 100804, 2023. https://doi.org/10.1016/j.patter.2023.100804

[23] Leonard J. Tashman, "Out-of-sample tests of forecasting accuracy: an analysis and review," International Journal of Forecasting 16(4), 437–450, 2000. https://doi.org/10.1016/S0169-2070(00)00065-0

[24] Ashish Vaswani et al., "Attention Is All You Need," Advances in Neural Information Processing Systems 30, 2017. https://papers.neurips.cc/paper/7181-attention-is-all-you-need.pdf

[25] Daniël Lakens, "Equivalence Tests: A Practical Primer for t Tests, Correlations, and Meta-Analyses," Social Psychological and Personality Science 8(4), 355–362, 2017. https://doi.org/10.1177/1948550617697177

V7 addendum — new 1120-cell common panel / V7 附录 – 新 1120 单元共同面板

Status: the national panel is complete at 1120/1120 cells; MIFlu seven-channel recovery is 40/40. Historical revision-9.2 numbers remain the old snapshot and are not overwritten.

状态：全国面板 1120/1120 完成；MIFlu 七通道恢复 40/40。旧 revision-9.2 数字仍是旧快照，未被覆盖。

New leading MSE (all-valid): MIFlu 1.7944 < PatchTST 1.9521 < NLinear 2.0782. Crop panel: 1.4994 / 1.6352 / 1.9027; the MIFlu crop mean 1.4994 reproduces the old 1.4995.

新 MSE（all-valid）：MIFlu 1.7944 < PatchTST 1.9521 < NLinear 2.0782；crop 1.4994 / 1.6352 / 1.9027，MIFlu crop 1.4994 重现旧值 1.4995。

Peak step passes (of 1680 per model): MIFlu 252 (15.0%), PatchTST 215 (12.8%), NLinear 57 (3.4%). The historical NLinear peak-champion claim is not reproduced; the old 16-unit table is a different population.

峰值 step passes（每模型 1680）：MIFlu 252（15.0%）、PatchTST 215（12.8%）、NLinear 57（3.4%）。旧「NLinear 峰值冠军」在新面板不成立；旧 16 单元表是不同总体。

Ablation is non-monotonic: K4 1.4989 best, K6 1.5457 (n=10), K2 1.5813, K8 1.6124, no_lora 1.6330, K12 1.7604 worst.

消融非单调：K4 1.4989 最佳，K6 1.5457（n=10），K2 1.5813，K8 1.6124，no_lora 1.6330，K12 1.7604 最差。

Regional Table VI: 51/53 valid; walk-forward only 473/1020 valid (329 non-finite, 218 missing), so walk-forward is partial. Paired Wilcoxon/Holm is exploratory (349/378 rejections; cells are not independent).

区域 Table VI：51/53 有效；walk-forward 仅 473/1020 有效（329 non-finite、218 missing），仍是部分。Paired Wilcoxon/Holm 属探索性（349/378 拒绝；cell 非独立）。

Do not claim full walk-forward, monotonic depth, or submission readiness. See v7/MESSAGE_TO_CHATGPT.md and SCIENTIFIC_AUDIT.md.

不得声称完整 walk-forward、单调深度或投稿就绪。详见 v7/MESSAGE_TO_CHATGPT.md 与 SCIENTIFIC_AUDIT.md。

Model	MSE all-valid	MSE crop	Peak passes /1680
MIFlu	1.7944	1.4994	252 (15.0%)
PatchTST	1.9521	1.6352	215 (12.8%)
NLinear	2.0782	1.9027	57 (3.4%)