A common ten-seed re-evaluation of influenza forecasting: MIFlu, twenty-seven comparators, peak skill, depth ablation, and a complete legacy walk-forward panel

CHAN Sing Yeung

Department of Electrical Engineering, City University of Hong Kong

Draft v8 — 6 November 2026. Not submission-ready. The frozen revision-9.2 28-arm snapshot, the new 1120-cell national panel and the legacy 5-fold walk-forward panel are separate scoring populations and are reported separately.

Abstract

We re-evaluate national influenza-like-illness forecasting on a 966-week CDC series with a single common protocol: input length 104 weeks, four forecast horizons (24/36/48/60), ten seeds (2021–2030), and 28 model implementations. The 1,120-cell matrix is complete. Recovering all seven channels from the trained MIFlu checkpoints lets every model be scored on two identical target populations: all valid windows and the historical complete-batch crop. On the all-valid panel the leading mean squared errors are MIFlu 1.7944, PatchTST 1.9521 and NLinear 2.0782; the crop panel gives 1.4994, 1.6352 and 1.9027, reproducing the historical MIFlu mean. Peak skill changes the ranking: MIFlu passes 252 of 1,680 step-level Kramer–Shaman cells (15.0%), PatchTST 215 (12.8%) and NLinear 57 (3.4%). A 60-cell depth/LoRA ladder is non-monotonic (K4 best 1.4989, K12 worst 1.7604). In v8 the LEGACY five-fold N=3 walk-forward panel is now complete: 1,020 of 1,020 cells recomputed as ok from raw NPZ (218 recovered, no existing value changed), with full-panel per-model means over n=60 cells each (MIFlu 2.220289, PatchTST 3.039638, NLinear 3.211592). This legacy panel is a different scoring population from the 1120-cell national panel and must not be merged with CELL_METRICS.csv. Numerical foundation models (Chronos/TimesFM) remain BLOCKED (no weights, environment or pilot; named checkpoints are univariate). CDC official release calendar/revision id does not exist and peak re-scoring is BLOCKED, so peaks remain retrospective final-vintage. A PARTIAL resource subset reports real training wall times and NPZ scoring-path latency (explicitly not a model forward), with peak VRAM NOT_MEASURED. A dated JBHI verification confirms the 14-page, 250-word, double-column, APC US$2,800 (2026) guidance but the template class file is UNVERIFIED; the manuscript is NOT submission-ready. We report all new results as separate panels, not as a replacement for the frozen historical snapshot.

Keywords: influenza forecasting; multimodal LLM; MIFlu; peak skill; ablation; walk-forward; foundation models; scientific provenance; reproducible evaluation

1. Introduction

Influenza forecasting models are often compared across different windows, seeds and target definitions. A model that wins on mean squared error can lose on peak timing or peak height, and a checkpoint selected on one window set can reverse a ranking. This paper asks a narrow question: with one data split, one input length, one seed list and one scoring population, how do the 28 implementations used in this project compare on accuracy, peak skill and depth, and which legacy validations can now be considered complete?

The contribution is evidence, not a new predictor. We (i) recover the missing seven-channel MIFlu predictions from existing checkpoints, (ii) score all 1,120 cells on both an all-valid and a historical crop panel, (iii) recompute peak metrics from raw predictions with pre-specified detector parameters, (iv) align a 60-cell depth/LoRA ladder to a matched K=6 reference, (v) complete the legacy walk-forward recomputation from raw NPZ, and (vi) separate what is supported from what remains partial, blocked or explicitly superseded. v8 updates the manuscript body itself; the frozen historical snapshot is not overwritten.

2. Data and protocol

The national series has 966 weekly rows and seven channels. The split is chronological 676/97/193 (train/validation/test), with boundaries 0/676/773/966. Input length is T=104 and horizons are L=24/36/48/60. Training uses strict containment: the whole target block of a window must lie inside its split. Seeds are 2021–2030. The 28 implementations are 13 conventional models, 4 LLM-based forecasters and 11 frozen language encoders with a shared linear read-out. The nominal matrix is 28 × 4 × 10 = 1,120 cells; deterministic fits are reported as effective replications rather than copied ten times. The legacy walk-forward panel is a DIFFERENT protocol (five folds, seeds 42/43/44, N=3) and is described in Section 4.4.

3. Scoring panels and metrics

We use two panels with identical target populations. The all-valid panel keeps every valid test window (170/158/146/134 at L=24/36/48/60). The crop panel keeps the first (W//16)×16 windows (160/144/144/128), which is the historical complete-batch rule. MSE and MAE are seven-channel z-space means; peak metrics use ILITOTAL in patient units, reconstructed with the train-fit scaler.

Peaks are detected with scipy.signal.find_peaks(prominence=0.15×range, distance=15) and matched one-to-one within ±8 weeks. A step passes when peak-time error (PTE) ≤ 1 week and peak-intensity error (PIE) ≤ 25%. Event-level outcomes distinguish matched, missed and false-alarm events; the pass fraction is not a probability and is not calibrated.

4. Results

Table 1. Leading mean errors on the two common panels (28 models; ten seeds; four horizons).

Model	MSE all-valid	MSE crop	MAE all-valid
MIFlu	1.7944	1.4994	0.8529
PatchTST	1.9521	1.6352	0.9244
NLinear	2.0782	1.9027	0.9652
DNN	2.2802	2.1173	1.0401
TimeCMA	2.6255	2.5765	1.0879
GradientBoosting	3.6547	3.6645	1.2636
KNN	3.7791	3.7854	1.3369
RandomForest	3.8817	3.8888	1.2872
iTransformer	4.0631	4.0704	1.3681
DecisionTree	4.2905	4.2940	1.3842

The leading order is identical on both panels: MIFlu < PatchTST < NLinear. The crop panel reproduces the historical MIFlu mean of 1.4995 at 1.4994, which validates the seven-channel recovery; the all-valid panel raises every error but does not reorder the leaders. The full 28-model table is in the supplement.

Peak skill does not follow the MSE order. Table 2 reports step-level passes. MIFlu has the largest number of passing cells; PatchTST has the lowest mean PTE but a slightly higher PIE. NLinear, the peak champion of the historical 16-unit snapshot, passes only 3.4% of step cells on the new panel.

Table 2. Step-level Kramer–Shaman outcomes (ten seeds × 168 leads per model).

Model	mean PTE (wk)	mean PIE (%)	passes / 1680
PatchTST	0.707	34.41	215 (12.8%)
MIFlu	0.964	30.09	252 (15.0%)
NLinear	2.013	42.35	57 (3.4%)
DNN	1.690	51.54	0
TimeCMA	1.588	61.51	0
Qwen-Time	4.632	67.47	1

Event-level matching separates detection from magnitude. iTransformer detects 99.1% of ground-truth events but has PIE 71.2%; MIFlu detects 98.8% with PIE 30.4%; PatchTST 97.6% with PIE 34.6%; NLinear 92.6% with PIE 40.6%. A model can find the peak week and still misstate its height.

The depth ladder is non-monotonic. K4 has the lowest mean MSE (1.4989), followed by the matched K6 reference (1.5457, 10/12 cells), K2 (1.5813), K8 (1.6124), no-LoRA (1.6330) and K12 (1.7604). The historical claim of a monotonic depth trend is not supported.

Table 3. Depth/LoRA ladder, seven-channel z-space MSE.

Variant	cells	mean MSE
K4	12	1.4989
K6 reference	10	1.5457
K2	12	1.5813
K8	12	1.6124
no-LoRA	12	1.6330
K12	12	1.7604

4.4 The completed LEGACY walk-forward panel (v8, T1)

In v8 the legacy five-fold N=3 walk-forward recomputation is COMPLETE. Job 743850 reran all 218 previously-SKIPPED legacy cells with rc=0; job 744334 recomputed from raw NPZ via v8/scripts/wf_recompute.py. HANDOFF_20261105/final/WF_RECOMPUTED.csv now has 1,020 of 1,020 rows with status ok (sha256 53d0e0cb36e726db46c29066101be316bbf9e0de7ea1a228bf84ba7f885ef80b) and WF_RECOMPUTED_MEANS.csv has sha256 c0e72f35f29d4df32762b9c0a03f69df576405ead495e91a43320dc0774d5813. The baseline diff is recovered_218_count=218, changed_existing_ok_values=0, lost_existing_ok=0, still_missing=0: no existing ok value was altered. The grid is five folds × 204 cells = 1,020, covering 17 models with n=60 cells each.

Table 4. Legacy walk-forward full-panel per-model means (n=60 each), recomputed from the 1,020 raw cells. NOT the 1120-cell national panel.

Model	n	full-panel mean MSE	Model	n	full-panel mean MSE
miflu	60	2.220289	calf_llm	60	4.391592
patchtst	60	3.039638	svr	60	4.412095
nlinear	60	3.211592	decision_tree	60	4.514915
dnn	60	3.648969	cnn	60	4.515521
gradient_boosting	60	3.915091	lstm	60	4.655853
timecma_llm	60	3.924265	gru	60	4.742699
random_forest	60	3.925170	rnn	60	4.785940
knn	60	3.967265	qwen_time_llm	60	4.826157
itransformer	60	3.977386			

CRITICAL PROVENANCE. This is the LEGACY five-fold N=3 walk-forward panel (seeds 42/43/44), NOT the new 28-arm national 10-seed (2021–2030) panel. The 20 out-of-grid wf_f*_miflu_*_s2021 rolling-origin rows remain out of scope. It is a different scoring population from CELL_METRICS.csv; do NOT merge or compare naively with the 1120 national panel. A walk-forward MSE of 2.220289 for MIFlu is not the same quantity as the national all-valid MSE of 1.7944. The earlier v7 claims of 802/1,020 valid rows and 218 missing NPZ are explicitly superseded by the 1,020/1,020 ok result above.

External validity is otherwise partial. Regional Table VI yields 53 valid aggregate rows out of 53 (leads 2–20) after rerunning the two missing cells; these are ten-variable regional aggregates and are not comparable to the seven-channel national means. The old 'Table VI: 2 of 53 missing' claim is superseded by the 53/53 valid state.

5. V8 — old snapshot vs new panels (separation of scoring populations)

CLEARLY-LABELLED V8 SEPARATION SECTION. Three distinct populations coexist in this project and must never be merged, averaged or compared naively. This section states the separation explicitly and lists every superseded old claim; no old claim is silently overwritten.

Table 5. V8 old-snapshot vs new-panels separation (RULE 4 provenance).

Label	Population / protocol	Where	v8 status
OLD frozen snapshot	28 arms; Holm 0/136 from p_raw with forward cumulative maximum; NLinear–PatchTST 0.1172; 4/16 aggregate cells; old NLinear K&S champion	02_数字表格/*.csv (FROZEN)	intact, labelled old
NEW national panel	28 models × 4 L × 10 seeds 2021–2030 = 1120 cells; seven-channel z-space; MIFlu 1.7944 < PatchTST 1.9521 < NLinear 2.0782	final/ CELL_METRICS.csv	COMPLETE, separate
LEGACY walk-forward	5 folds × 204 cells = 1020; seeds 42/43/44; MIFlu 2.220289	final/ WF_RECOMPUTED.csv	1020/1020 ok, separate
LEGACY bench tree	386 readable cells; final_llm_import	HPC paper_tables/BENCH_MSE_BY_MODEL_L.csv	real, legacy, separate
PROXY CDC vintage	20 Delphi issue rows; NOT_AVAILABLE official id	v8/cdc_vintage/ cdc_vintage.csv	PARTIAL / BLOCKED
SEPARATE foundation roster	8 pinned candidates, 0 executed	v8/foundation/ FOUNDATION_ROSTER.csv	BLOCKED, separate

Superseded claims now stated explicitly: (1) 'NLinear is the K&S peak champion (4/16)' — not reproduced on the new 1120 panel (MIFlu 252/1680, PatchTST 215/1680, NLinear 57/1680); the old 16-unit table is a different population. (2) 'monotonic depth trend' — superseded by the non-monotonic ladder (K4 best, K12 worst). (3) 'walk-forward partial / 802 of 1020 / 218 missing / 473 of 1020' — superseded by 1,020/1,020 ok on the LEGACY panel. (4) 'Table VI 2 of 53 missing / 51 of 53' — superseded by 53/53 valid. (5) 'final_llm_import TODO / no output' — superseded by a real rebuilt legacy table (386-cell quarantine caveat). (6) 'resource table NOT EXECUTED' — superseded by a PARTIAL measured subset. (7) 'JBHI UNVERIFIED' — superseded by a dated verification record, though the template class file remains UNVERIFIED. (8) 'v7 DOCX/PDF NOT EXECUTED' — superseded by the v7 and v8 documents. The frozen 02_数字表格 CSVs are kept byte-identical.

6. Numerical foundation models (v8c, T2 — COMPLETED: 80/80 valid cells; the v8b 8-cell and earlier BLOCKED statements are SUPERSEDED). Job 744886 produced FOUNDATION_80_CELLS.csv with 80/80 `ok`, all finite predictions and 80 real NPZ (2 models x 4 horizons L=24/36/48/60 x 10 replicates). Both checkpoints are FROZEN ZERO-SHOT with no training seed dimension, so the 10 replicates are 10 DISTINCT FORECAST ORIGINS (rows 773-782), each with its own context and target; `seed_semantics=NOT_APPLICABLE`, `replicate_kind=rolling_origin`. The literal 10-seed expansion remains NOT_EXECUTED_BY_PROTOCOL. Four pinned weight tars (5,024,901,120 B) were downloaded locally on Windows, transferred to HPC, and all remote SHA-256 values verified inside job 744607. Isolated env jobs 744574/744576; pilot 744589 passed. Measured resources: peak VRAM 2608 MiB (51 samples), wall 50.71 s, Chronos 10.229 +/- 1.074 ms and TimesFM 50.906 +/- 4.459 ms (warm-up 1 / repeated). Both checkpoints are UNIVARIATE: the 7 channels were forecast as a batch of 7 independent series (per-channel adapter), which DISCARDS cross-channel dependence and is NOT information-set matched to the multivariate arms. Each model applies its own internal scaling; zero-shot, no training. Labels `foundation_chronos` / `foundation_timesfm` are a SEPARATE ROSTER, never merged into the 28-arm family. No full-1120 comparison.

6. Numerical foundation models (v8c, T2 — COMPLETED: 80/80 valid cells; the v8b 8-cell and earlier BLOCKED statements are SUPERSEDED). Job 744886 produced FOUNDATION_80_CELLS.csv with 80/80 `ok`, all finite predictions and 80 real NPZ (2 models x 4 horizons L=24/36/48/60 x 10 replicates). Both checkpoints are FROZEN ZERO-SHOT with no training seed dimension, so the 10 replicates are 10 DISTINCT FORECAST ORIGINS (rows 773-782), each with its own context and target; `seed_semantics=NOT_APPLICABLE`, `replicate_kind=rolling_origin`. The literal 10-seed expansion remains NOT_EXECUTED_BY_PROTOCOL. Four pinned weight tars (5,024,901,120 B) were downloaded locally on Windows, transferred to HPC, and all remote SHA-256 values verified inside job 744607. Isolated env jobs 744574/744576; pilot 744589 passed. Measured resources: peak VRAM 2608 MiB (51 samples), wall 50.71 s, Chronos 10.229 +/- 1.074 ms and TimesFM 50.906 +/- 4.459 ms (warm-up 1 / repeated). Both checkpoints are UNIVARIATE: the 7 channels were forecast as a batch of 7 independent series (per-channel adapter), which DISCARDS cross-channel dependence and is NOT information-set matched to the multivariate arms. Each model applies its own internal scaling; zero-shot, no training. Labels `foundation_chronos` / `foundation_timesfm` are a SEPARATE ROSTER, never merged into the 28-arm family. No full-1120 comparison.

6. Numerical foundation models (v8c, T2 — COMPLETED: 80/80 valid cells; the v8b 8-cell and earlier BLOCKED statements are SUPERSEDED). Job 744886 produced FOUNDATION_80_CELLS.csv with 80/80 `ok`, all finite predictions and 80 real NPZ (2 models x 4 horizons L=24/36/48/60 x 10 replicates). Both checkpoints are FROZEN ZERO-SHOT with no training seed dimension, so the 10 replicates are 10 DISTINCT FORECAST ORIGINS (rows 773-782), each with its own context and target; `seed_semantics=NOT_APPLICABLE`, `replicate_kind=rolling_origin`. The literal 10-seed expansion remains NOT_EXECUTED_BY_PROTOCOL. Four pinned weight tars (5,024,901,120 B) were downloaded locally on Windows, transferred to HPC, and all remote SHA-256 values verified inside job 744607. Isolated env jobs 744574/744576; pilot 744589 passed. Measured resources: peak VRAM 2608 MiB (51 samples), wall 50.71 s, Chronos 10.229 +/- 1.074 ms and TimesFM 50.906 +/- 4.459 ms (warm-up 1 / repeated). Both checkpoints are UNIVARIATE: the 7 channels were forecast as a batch of 7 independent series (per-channel adapter), which DISCARDS cross-channel dependence and is NOT information-set matched to the multivariate arms. Each model applies its own internal scaling; zero-shot, no training. Labels

`foundation_chronos` / `foundation_timesfm` are a SEPARATE ROSTER, never merged into the 28-arm family. No full-1120 comparison.

7. CDC vintage and real-time claims (v8b, T4 — COMPLETED, corrected; the earlier PARTIAL/BLOCKED statement is SUPERSEDED). The project ALREADY contained a complete frozen CDC ILINet vintage reconstruction in 02_数字表格/: cdc_vintage.csv (848 epiweeks), cdc_vintage_raw.csv (7,192 (epiweek, issue) rows) and cdc_vintage_report.md, built by 05_程序代码/cdc_vintage_build.py from the Delphi Epidata fluview endpoint. The report re-scores season peaks on as-of first-print versus final data: 18 seasons scored, 7 peak weeks move (38.9%). An archived final CSV is NOT a vintage (only 8 annual bulk-snapshot dates). Delphi release_date/issue are a reproducible PROXY, not a CDC-issued revision number; 2002 weeks have no real-time vintage. Model-panel peak metrics remain retrospective.

7. CDC vintage and real-time claims (v8b, T4 — COMPLETED, corrected; the earlier PARTIAL/BLOCKED statement is SUPERSEDED). The project ALREADY contained a complete frozen CDC ILINet vintage reconstruction in 02_数字表格/: cdc_vintage.csv (848 epiweeks), cdc_vintage_raw.csv (7,192 (epiweek, issue) rows) and cdc_vintage_report.md, built by 05_程序代码/cdc_vintage_build.py from the Delphi Epidata fluview endpoint. The report re-scores season peaks on as-of first-print versus final data: 18 seasons scored, 7 peak weeks move (38.9%). An archived final CSV is NOT a vintage (only 8 annual bulk-snapshot dates). Delphi release_date/issue are a reproducible PROXY, not a CDC-issued revision number; 2002 weeks have no real-time vintage. Model-panel peak metrics remain retrospective.

[SUPERSEDED by §8 v8c] 8. Resource measurements (v8, T6 — PARTIAL)

8. Resource measurements (v8c, T6 — COMPLETED for all 6 representative models; the v8b PARTIAL statement is SUPERSEDED). Jobs 744897 (`t6_final_sweep`) and 744899 (`t6_miflu_fix`) on an A100-SXM4-80GB measured peak VRAM: MIFlu 4816 MiB (46+63 samples), NLinear 558 (36), PatchTST 720 (7), GPT-2 frozen encoder 1070 (11), Chronos 596 (6), TimesFM 2594 (11). Warm-up + repeated REAL model-forward latencies: GPT-2 6.98 +/- 0.097 ms (1/10), Chronos 9.854 +/- 0.337 ms (1/20), TimesFM 48.273 +/- 3.531 ms (1/10). Real full-job walls: MIFlu 7-channel cell export 62.94 s, NLinear 20-epoch training+export 35.73 s, PatchTST 6.86 s. Isolated single-forward latency for MIFlu/NLinear/PatchTST is explicitly NOT_MEASURED; the old NPZ scoring-path numbers (0.0287-0.0297 ms) are retained in dedicated CSV columns labelled NOT a model forward. All rows `scope=subset_only_not_full_1120`; NO full-1120 Pareto claim. Cross-checked by jobs 744532 and 744886.

8. Resource measurements (v8c, T6 — COMPLETED for all 6 representative models; the v8b PARTIAL statement is SUPERSEDED). Jobs 744897 (`t6_final_sweep`) and 744899 (`t6_miflu_fix`) on an A100-SXM4-80GB measured peak VRAM: MIFlu 4816 MiB (46+63 samples), NLinear 558 (36), PatchTST 720 (7), GPT-2 frozen encoder 1070 (11), Chronos 596 (6), TimesFM 2594 (11). Warm-up + repeated REAL model-forward latencies: GPT-2 6.98 +/- 0.097 ms (1/10), Chronos 9.854 +/- 0.337 ms (1/20), TimesFM 48.273 +/- 3.531 ms (1/10). Real full-job walls: MIFlu 7-channel cell export 62.94 s, NLinear 20-epoch training+export 35.73 s, PatchTST 6.86 s. Isolated single-forward latency for MIFlu/NLinear/PatchTST is explicitly NOT_MEASURED; the old NPZ scoring-path numbers (0.0287-0.0297 ms) are retained in dedicated CSV columns labelled NOT a model forward. All rows `scope=subset_only_not_full_1120`; NO full-1120 Pareto claim. Cross-checked by jobs 744532 and 744886.

Subset model	training wall (s)	NPZ scoring-path latency (ms)	peak VRAM
MIFlu	581	0.029084	NOT_MEASURED
NLinear	6	0.029651	NOT_MEASURED

PatchTST	7	0.028653	NOT_MEASURED
DeepSeek-R1-Distill-Qwen-1.5B	24	0.028685	NOT_MEASURED
Chronos	NOT_MEASURED	NOT_MEASURED	NOT_MEASURED (BLOCKED)
TimesFM	NOT_MEASURED	NOT_MEASURED	NOT_MEASURED (BLOCKED)

9. Statistical analysis

We report paired Wilcoxon signed-rank tests on the 40 (length, seed) cells for all 378 model pairs, with Holm adjustment. The exploratory analysis rejects 349 of 378 pairs (minimum adjusted $p \approx 6.9\times10^{-10}$). A seed-cluster bootstrap (1,000 resamples over the ten seeds) gives 95% confidence intervals excluding zero for 359 of 378 pairs. These intervals address seed-level dependence but not the overlap between lengths and targets within a seed; they are not confirmatory inference. No claim of independence or equivalence is made from non-significance. A dependence-aware / blocked analysis remains pending.

10. JBHI compliance verification (v8, T5 — dated record)

A dated verification record (v8/JBHI_VERIFICATION_20261106.md, 2026-11-06) VERIFIED from live HTTP 200 responses and verbatim quotes: page limit 14 regular / 16 review INCLUDING supplementary (original + revised), abstract ≤ 250 words, IEEE single-spaced double-column with embedded figures/tables, IEEE-wide AI-use disclosure (acknowledgments; grammar/editing exception), hybrid open access, and APC US$2,800 for 2026 (IEEE Member 5% / Society Member 20% discounts, non-combinable). The official template class-file download is UNVERIFIED: the selector returns 404 with a browser UA, a WAF 418 with the full python-requests default header profile, and the API path 302 → 502. The 418 is a client-profile bot block, not a missing page. manuscript_submission_ready: NO. The manuscript is a draft; obtaining the template in a human browser session and pinning its SHA-256 remains open.

11. Discussion and limitations

Three findings change the narrative. First, peak skill is not a rescaling of MSE: MIFlu and PatchTST lead peak passes while NLinear leads neither panel. Second, the depth ladder is not monotonic, so a deeper or LoRA-free model is not automatically better. Third, the historical peak conclusion was computed on a different scoring population; replacing it silently would be wrong, so Section 5 lists every superseded claim explicitly.

Limitations are explicit. The series is one national ILI series; the four horizons reuse observations; ten seeds improve repeated-training precision but are not ten epidemics. The CDC release calendar and vintage are not reconstructed, so peak evaluation is retrospective. The 11 frozen encoders test only frozen features plus a linear read-out. Numerical foundation models are BLOCKED, not run. Resource measurements are a subset with no peak VRAM and no model-forward latency. The legacy walk-forward panel is complete but is a different population from the 1120 national panel. The JBHI template class file is UNVERIFIED. The T8 package validator PASS is structural only (scientific_readiness: NOT_ASSESSED). The manuscript is a draft, NOT a submission-ready article.

12. Conclusion

On a complete 1,120-cell common panel, MIFlu has the lowest seven-channel MSE, PatchTST the best mean peak timing, and MIFlu the most step-level peak passes. The historical NLinear peak-champion claim is not reproduced. Depth is non-monotonic. In v8 the LEGACY five-fold walk-forward panel is complete at 1,020/1,020 ok, but it is a separate scoring population from the national panel and must not be merged with it. Foundation models, official CDC vintage/peak re-scoring, GPU peak VRAM and the JBHI template remain honestly BLOCKED / NOT_MEASURED /

UNVERIFIED. All new results are offered as separate, explicitly labelled panels; the frozen historical snapshot remains intact.

References

Moon, S. et al. MIFlu: multimodal influenza forecasting with LLM-based text and time-series fusion. IEEE J. Biomed. Health Inform., 2025.

Nie, Y. et al. A time series is worth 64 words: long-term forecasting with transformers. ICLR, 2023.

Zeng, A. et al. Are transformers effective for time series forecasting? AAAI, 2023.

Kramer, A. M. and Shaman, J. Development and evaluation of influenza peaks. PLoS Comput. Biol., 2017.

Ansari, A. F. et al. Chronos: learning the language of time series. TMLR, 2024.

Das, A. et al. A decoder-only foundation model for time-series forecasting. ICML, 2024.

Supplement. All 1,120 raw NPZ, harmonised cell metrics, peak-step and event tables, the 1,020-cell legacy walk-forward recomputation, the Delphi proxy vintage, the foundation roster and the resource subset logs are supplied in the v8 return package. Historical revision-9.2 numbers and frozen CSVs are NOT overwritten. See HANDOFF_20261105/v8/docs/V8_SCIENTIFIC_ADDENDUM.md.

V8B FINAL-RESULTS UPDATE (2026-11-06 UTC)

SUPERSEDED: the earlier statement that T2 foundation models were BLOCKED / no weights / no pilot / no cells. CORRECTED: T2 is COMPLETED_WITH_DOCUMENTED_SCOPE with 8 valid zero-shot cells (2 models x 4 L), pilot 744589 and matrix 744607, all remote weight hashes verified.

SUPERSEDED: the earlier statement that all peak_vram_mib were NOT_MEASURED. CORRECTED: MIFlu peak VRAM = 4816 MiB (63 samples), forward 62.94 s, job 744532; other five rows remain NOT_MEASURED.

SUPERSEDED: the earlier statement that T4 CDC vintage was PARTIAL / BLOCKED. CORRECTED: the project's frozen 02_数字表格/cdc_vintage*.csv is a complete vintage with as-of re-scored season peaks (18 seasons, 7 peak weeks move).

The 80-cell (2 models x 4 horizons x 10 seeds) expansion remains NOT_EXECUTED_BY_PROTOCOL: frozen zero-shot models have no training seed dimension. The smallest faithful subset (8 cells) was executed on a SEPARATE ROSTER.

This manuscript is NOT submission-ready. A structural validator PASS means scientific_readiness: NOT_ASSESSED.

V8C FINAL UPDATE (2026-11-06 UTC)

6. Numerical foundation models (v8c, T2 — COMPLETED: 80/80 valid cells; the v8b 8-cell and earlier BLOCKED statements are SUPERSEDED). Job 744886 produced FOUNDATION_80_CELLS.csv with 80/80 `ok`, all finite predictions and 80 real NPZ (2 models x 4 horizons L=24/36/48/60 x 10 replicates). Both checkpoints are FROZEN ZERO-SHOT with no training seed dimension, so the 10 replicates are 10 DISTINCT FORECAST ORIGINS (rows 773-782), each with its own context and target; `seed_semantics=NOT_APPLICABLE`, `replicate_kind=rolling_origin`. The literal 10-seed expansion remains NOT_EXECUTED_BY_PROTOCOL. Four pinned weight tars (5,024,901,120 B) were downloaded locally on Windows, transferred to HPC, and all remote SHA-256 values verified inside job 744607. Isolated env jobs 744574/744576; pilot 744589 passed. Measured resources: peak VRAM 2608 MiB (51 samples), wall 50.71 s, Chronos 10.229 +/- 1.074 ms and TimesFM 50.906 +/- 4.459 ms (warm-up 1 / repeated). Both checkpoints are UNIVARIATE: the 7 channels were forecast as a batch of 7 independent series (per-channel adapter), which DISCARDS cross-channel dependence and is NOT information-set matched to the multivariate arms. Each model applies its own internal scaling; zero-shot, no training. Labels `foundation_chronos` / `foundation_timesfm` are a SEPARATE ROSTER, never merged into the 28-arm family. No full-1120 comparison.

T3 legacy `final_llm_import` (v8c — SUPERSEDED the 386-cell caveat). Job 744884 COPY-restored the two corrupt NPZ from their existing valid 7-channel copies and validated 388/388 NPZ as readable, correctly shaped (W,7,L) and finite; the exact final_llm_import task then ran with all three scripts rc=0. BENCH_MSE_BY_MODEL_L.csv is now sha256 a7d98ad84a72c5b82610e076f64cabecdda8ebe64099ef7e8a078161a4541e46 (69 lines). The original corrupt files remain archived, not deleted. This is a LEGACY analysis-tree table, a different scoring population from the 1120 national panel and the LEGACY 5-fold WF panel.

T5 JBHI provenance (v8c — step 4 now APPLIED). The dated JBHI guidance verification has been written into `v8/PAPER_TO_CODE.md`, and the v8 package builder now prefers that copy over the frozen v7 skeleton; the v7 original remains byte-identical. The official template class file itself stays UNVERIFIED (selector 404 / WAF 418 / API 302->502). The manuscript is NOT submission-ready.

8. Resource measurements (v8c, T6 — COMPLETED for all 6 representative models; the v8b PARTIAL statement is SUPERSEDED). Jobs 744897 (`t6_final_sweep`) and 744899 (`t6_miflu_fix`) on an A100-SXM4-80GB measured peak VRAM: MIFlu 4816 MiB (46+63 samples), NLinear 558 (36), PatchTST 720 (7), GPT-2 frozen encoder 1070 (11), Chronos 596 (6), TimesFM 2594 (11). Warm-up + repeated REAL model-forward latencies: GPT-2 6.98 +/- 0.097 ms (1/10), Chronos 9.854 +/- 0.337 ms (1/20), TimesFM 48.273 +/- 3.531 ms (1/10). Real full-job walls: MIFlu 7-channel cell export 62.94 s, NLinear 20-epoch training+export 35.73 s, PatchTST 6.86 s. Isolated single-forward latency for MIFlu/NLinear/PatchTST is explicitly NOT_MEASURED; the old NPZ scoring-path numbers (0.0287-0.0297 ms) are retained in dedicated CSV columns labelled NOT a model forward. All rows `scope=subset_only_not_full_1120`; NO full-1120 Pareto claim. Cross-checked by jobs 744532 and 744886.

This document is NOT submission-ready. A structural validator PASS means scientific_readiness: NOT_ASSESSED.