

Lab12

Chan-yu Kuo

```
library(BiocManager)
library(DESeq2)
```

Loading required package: S4Vectors

Loading required package: stats4

Loading required package: BiocGenerics

Attaching package: 'BiocGenerics'

The following objects are masked from 'package:stats':

IQR, mad, sd, var, xtabs

The following objects are masked from 'package:base':

anyDuplicated, aperm, append, as.data.frame, basename, cbind,
colnames, dirname, do.call, duplicated, eval, evalq, Filter, Find,
get, grep, grepl, intersect, is.unsorted, lapply, Map, mapply,
match, mget, order, paste, pmax, pmax.int, pmin, pmin.int,
Position, rank, rbind, Reduce, rownames, sapply, setdiff, sort,
table, tapply, union, unique, unsplit, which.max, which.min

Attaching package: 'S4Vectors'

The following objects are masked from 'package:base':

expand.grid, I, unname

Loading required package: IRanges

Loading required package: GenomicRanges

Loading required package: GenomeInfoDb

Loading required package: SummarizedExperiment

Loading required package: MatrixGenerics

Loading required package: matrixStats

Attaching package: 'MatrixGenerics'

The following objects are masked from 'package:matrixStats':

colAlls, colAnyNAs, colAnys, colAvgPerRowSet, colCollapse,
colCounts, colCummaxs, colCummins, colCumprods, colCumsums,
colDiffs, colIQRDiffs, colIQRs, colLogSumExps, colMadDiffs,
colMads, colMaxs, colMeans2, colMedians, colMins, colOrderStats,
colProds, colQuantiles, colRanges, colRanks, colSdDiffs, colSds,
colSums2, colTabulates, colVarDiffs, colVars, colWeightedMads,
colWeightedMeans, colWeightedMedians, colWeightedSds,
colWeightedVars, rowAlls, rowAnyNAs, rowAnys, rowAvgPerColSet,
rowCollapse, rowCounts, rowCummaxs, rowCummins, rowCumprods,
rowCumsums, rowDiffs, rowIQRDiffs, rowIQRs, rowLogSumExps,
rowMadDiffs, rowMads, rowMaxs, rowMeans2, rowMedians, rowMins,
rowOrderStats, rowProds, rowQuantiles, rowRanges, rowRanks,
rowSdDiffs, rowSds, rowSums2, rowTabulates, rowVarDiffs, rowVars,
rowWeightedMads, rowWeightedMeans, rowWeightedMedians,
rowWeightedSds, rowWeightedVars

Loading required package: Biobase

Welcome to Bioconductor

Vignettes contain introductory material; view with
'browseVignettes()'. To cite Bioconductor, see
'citation("Biobase")', and for packages 'citation("pkgname")'.

Attaching package: 'Biobase'

The following object is masked from 'package:MatrixGenerics':

rowMedians

The following objects are masked from 'package:matrixStats':

anyMissing, rowMedians

```
counts <- read.csv("airway_scaledcounts.csv", row.names=1)
metadata <- read.csv("airway_metadata.csv")
```

```
head(counts)
```

	SRR1039508	SRR1039509	SRR1039512	SRR1039513	SRR1039516
ENSG000000000003	723	486	904	445	1170
ENSG000000000005	0	0	0	0	0
ENSG000000000419	467	523	616	371	582
ENSG000000000457	347	258	364	237	318
ENSG000000000460	96	81	73	66	118
ENSG000000000938	0	0	1	0	2
	SRR1039517	SRR1039520	SRR1039521		
ENSG000000000003	1097	806	604		
ENSG000000000005	0	0	0		
ENSG000000000419	781	417	509		
ENSG000000000457	447	330	324		
ENSG000000000460	94	102	74		
ENSG000000000938	0	0	0		

```
head(metadata)
```

	id	dex	celltype	geo_id
1	SRR1039508	control	N61311	GSM1275862
2	SRR1039509	treated	N61311	GSM1275863
3	SRR1039512	control	N052611	GSM1275866
4	SRR1039513	treated	N052611	GSM1275867
5	SRR1039516	control	N080611	GSM1275870
6	SRR1039517	treated	N080611	GSM1275871

How many genes are in this dataset?

```
nrow(counts)
```

```
[1] 38694
```

How many 'control' cell lines do we have?

```
4
```

```
#metadata[,"dex"]=="control"
control <- metadata[metadata[,"dex"]=="control",]
head(control)
```

	id	dex	celltype	geo_id
1	SRR1039508	control	N61311	GSM1275862
3	SRR1039512	control	N052611	GSM1275866
5	SRR1039516	control	N080611	GSM1275870
7	SRR1039520	control	N061011	GSM1275874

```
control.counts <- counts[,control$id]
#control.counts
control.mean <- rowSums( control.counts )/4
head(control.mean)
```

ENSG000000000003	ENSG000000000005	ENSG000000000419	ENSG000000000457	ENSG000000000460
900.75	0.00	520.50	339.75	97.25
ENSG0000000000938				
0.75				

- **Q4.** Follow the same procedure for the **treated** samples (i.e. calculate the mean per gene across drug treated samples and assign to a labeled vector called **treated.mean**)

```
treated <- metadata[metadata[, "dex"]=="treated",]
head(treated)
```

```
      id      dex celltype      geo_id
2 SRR1039509 treated   N61311 GSM1275863
4 SRR1039513 treated   N052611 GSM1275867
6 SRR1039517 treated   N080611 GSM1275871
8 SRR1039521 treated   N061011 GSM1275875
```

```
treated.counts <- counts[ ,treated$id]
#control.counts
treated.mean <- rowSums( treated.counts )/4
head(treated.mean)
```

```
ENSG000000000003 ENSG000000000005 ENSG000000000419 ENSG000000000457 ENSG000000000460
      658.00           0.00          546.00          316.50           78.75
ENSG000000000938
      0.00
```

- **Q3.** How would you make the above code in either approach more robust?
- add more sample, we reduce the effect of the outlier, getting more robust result

```
library(dplyr)
```

Attaching package: 'dplyr'

The following object is masked from 'package:Biobase':

combine

The following object is masked from 'package:matrixStats':

count

The following objects are masked from 'package:GenomicRanges':

intersect, setdiff, union

The following object is masked from 'package:GenomeInfoDb':

```
intersect
```

The following objects are masked from 'package:IRanges':

```
collapse, desc, intersect, setdiff, slice, union
```

The following objects are masked from 'package:S4Vectors':

```
first, intersect, rename, setdiff, setequal, union
```

The following objects are masked from 'package:BiocGenerics':

```
combine, intersect, setdiff, union
```

The following objects are masked from 'package:stats':

```
filter, lag
```

The following objects are masked from 'package:base':

```
intersect, setdiff, setequal, union
```


```
control <- metadata %>% filter(dex=="control")
control.counts <- counts %>% select(control$id)
control.mean <- rowSums(control.counts)/4
head(control.mean)
```

```
ENSG000000000003 ENSG000000000005 ENSG000000000419 ENSG000000000457 ENSG000000000460
          900.75           0.00           520.50           339.75           97.25
ENSG0000000000938
          0.75
```

```
meancounts <- data.frame(control.mean, treated.mean)
plot(meancounts[,1],meancounts[,2], xlab="Control", ylab="Treated",log="xy")
```

Warning in xy.coords(x, y, xlabel, ylabel, log): 15032 x values <= 0 omitted from logarithmic plot

Warning in xy.coords(x, y, xlabel, ylabel, log): 15281 y values <= 0 omitted from logarithmic plot



Q5 (b). You could also use the **ggplot2** package to make this figure producing the plot below. What **geom_?()** function would you use for this plot?

`geom_points`

Q6. Try plotting both axes on a log scale. What is the argument to **plot()** that allows you to do this?

`log=="xy"`

```
meancounts$log2fc <- log2(meancounts[, "treated.mean"] / meancounts[, "control.mean"])
head(meancounts)
```

	control.mean	treated.mean	log2fc
ENSG000000000003	900.75	658.00	-0.45303916
ENSG000000000005	0.00	0.00	NaN
ENSG000000000419	520.50	546.00	0.06900279
ENSG000000000457	339.75	316.50	-0.10226805
ENSG000000000460	97.25	78.75	-0.30441833
ENSG000000000938	0.75	0.00	-Inf

```
head(meancounts[,1:2]==0)
```

	control.mean	treated.mean
ENSG000000000003	FALSE	FALSE
ENSG000000000005	TRUE	TRUE
ENSG000000000419	FALSE	FALSE
ENSG000000000457	FALSE	FALSE
ENSG000000000460	FALSE	FALSE
ENSG000000000938	FALSE	TRUE

```
## this return a group of index that is equal to 0
to.keep <- rowSums(meancounts[,1:2]==0)==0
mycounts <- meancounts[to.keep,]
head(mycounts)
```

	control.mean	treated.mean	log2fc
ENSG000000000003	900.75	658.00	-0.45303916
ENSG000000000419	520.50	546.00	0.06900279
ENSG000000000457	339.75	316.50	-0.10226805
ENSG000000000460	97.25	78.75	-0.30441833
ENSG000000000971	5219.00	6687.50	0.35769358
ENSG000000001036	2327.00	1785.75	-0.38194109

```
#zero.vals <- which(meancounts[,1:2]==0, arr.ind=TRUE)
#to.rm <- unique(zero.vals[,1])

#mycounts <- meancounts[-to.rm,]
#head(mycounts)
```

- **Q7.** What is the purpose of the `arr.ind` argument in the `which()` function call above? Why would we then take the first column of the output and need to call the `unique()` function?

`arr.ind` is the array indices if the input is an array.

here is the Upregulated log2fc with cutoff of 2

314 upregulated


```
#mycounts[mycounts$log2fc>=2,]  
sum(mycounts$log2fc>=2)
```

[1] 314

Here is the downregulated ;

485 downregulated

```
#mycounts[mycounts$log2fc<=-2,]  
sum(mycounts$log2fc<=-2)
```

[1] 485

Q8 and Q9

```
up.ind <- mycounts$log2fc > 2  
down.ind <- mycounts$log2fc < (-2)  
sum(up.ind)
```

[1] 250

```
sum(down.ind )
```

[1] 367

Q10

No, fold can be large without being statistically significant, meaning the fold change result might be due to randomness.

we should filter out any result with high p_value, when using fold change to inspect result

```
library(DESeq2)  
citation("DESeq2")
```

To cite package 'DESeq2' in publications use:

Love, M.I., Huber, W., Anders, S. Moderated estimation of fold change and dispersion for RNA-seq data with DESeq2 Genome Biology 15(12):550 (2014)

A BibTeX entry for LaTeX users is

```
@Article{,
  title = {Moderated estimation of fold change and dispersion for RNA-seq data with DESeq2},
  author = {Michael I. Love and Wolfgang Huber and Simon Anders},
  year = {2014},
  journal = {Genome Biology},
  doi = {10.1186/s13059-014-0550-8},
  volume = {15},
  issue = {12},
  pages = {550},
}
```

```
dds <- DESeqDataSetFromMatrix(countData=counts,
                              colData=metadata,
                              design=~dex)
```

converting counts to integer mode

Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in design formula are characters, converting to factors

```
dds
```

```
class: DESeqDataSet
dim: 38694 8
metadata(1): version
assays(1): counts
rownames(38694): ENSG000000000003 ENSG000000000005 ... ENSG00000283120
               ENSG00000283123
rowData names(0):
colnames(8): SRR1039508 SRR1039509 ... SRR1039520 SRR1039521
colData names(4): id dex celltype geo_id
```

```
dds <- DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship

final dispersion estimates

fitting model and testing

```
res<- results(dds)
res
```

log2 fold change (MLE): dex treated vs control

Wald test p-value: dex treated vs control

DataFrame with 38694 rows and 6 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG000000000003	747.1942	-0.3507030	0.168246	-2.084470	0.0371175
ENSG000000000005	0.0000	NA	NA	NA	NA
ENSG000000000419	520.1342	0.2061078	0.101059	2.039475	0.0414026
ENSG000000000457	322.6648	0.0245269	0.145145	0.168982	0.8658106
ENSG000000000460	87.6826	-0.1471420	0.257007	-0.572521	0.5669691
...
ENSG00000283115	0.000000	NA	NA	NA	NA
ENSG00000283116	0.000000	NA	NA	NA	NA
ENSG00000283119	0.000000	NA	NA	NA	NA
ENSG00000283120	0.974916	-0.668258	1.69456	-0.394354	0.693319
ENSG00000283123	0.000000	NA	NA	NA	NA
	padj				
	<numeric>				
ENSG000000000003	0.163035				
ENSG000000000005	NA				
ENSG000000000419	0.176032				

```


ENSG00000000457 0.961694
ENSG00000000460 0.815849
...
ENSG00000283115 NA
ENSG00000283116 NA
ENSG00000283119 NA
ENSG00000283120 NA
ENSG00000283123 NA

```

volcano plots

flip the y-axis so the value we care (low p-value)


```
plot(res$log2FoldChange, -log(res$padj))
```



```

mycols<-rep("grey",nrow(res))
mycols[abs(res$log2FoldChange)>=2]<-"blue"
mycols[abs(res$padj)>=0.05]<-"gray"
plot(res$log2FoldChange, -log(res$padj), col=mycols)

```



Annotation

```
library("AnnotationDbi")
```

Attaching package: 'AnnotationDbi'

The following object is masked from 'package:dplyr':

```
select
```

```
library("org.Hs.eg.db")
```

```
columns(org.Hs.eg.db)
```

[1]	"ACCNUM"	"ALIAS"	"ENSEMBL"	"ENSEMBLPROT"	"ENSEMBLTRANS"
[6]	"ENTREZID"	"ENZYME"	"EVIDENCE"	"EVIDENCEALL"	"GENENAME"
[11]	"GENETYPE"	"GO"	"GOALL"	"IPI"	"MAP"
[16]	"OMIM"	"ONTOLOGY"	"ONTOLOGYALL"	"PATH"	"PFAM"
[21]	"PMID"	"PROSITE"	"REFSEQ"	"SYMBOL"	"UCSCKG"
[26]	"UNIPROT"				

```
res$symbol <- mapIds(org.Hs.eg.db,
                     keys=row.names(res), # Our genenames
                     keytype="ENSEMBL",   # The format of our genenames
                     column="SYMBOL",     # The new format we want to add
                     )
```

'select()' returned 1:many mapping between keys and columns

```
res$entrez <- mapIds(org.Hs.eg.db,
                     keys=row.names(res), # Our genenames
                     keytype="ENSEMBL",   # The format of our genenames
                     column="ENTREZID",    # The new format we want to add
                     )
```

'select()' returned 1:many mapping between keys and columns

```
res$uniprot <- mapIds(org.Hs.eg.db,
                      keys=row.names(res), # Our genenames
                      keytype="ENSEMBL",   # The format of our genenames
                      column="UNIPROT",    # The new format we want to add
                      )
```

'select()' returned 1:many mapping between keys and columns

```
res$genename <- mapIds(org.Hs.eg.db,
                       keys=row.names(res), # Our genenames
                       keytype="ENSEMBL",   # The format of our genenames
                       column="GENENAME",   # The new format we want to add
                       )
```

'select()' returned 1:many mapping between keys and columns

```
library(pathview)
```

```
#####
Pathview is an open source software package distributed under GNU General
Public License version 3 (GPLv3). Details of GPLv3 is available at
http://www.gnu.org/licenses/gpl-3.0.html. Particullary, users are required to
formally cite the original Pathview paper (not just mention it) in publications
or products. For details, do citation("pathview") within R.
```

The pathview downloads and uses KEGG data. Non-academic uses may require a KEGG license agreement (details at <http://www.kegg.jp/kegg/legal.html>).

```
#####
```

```
library(gage)
```

```
library(gageData)
```

```
data(kegg.sets.hs)
```

```
# Examine the first 2 pathways in this kegg set for humans
head(kegg.sets.hs, 2)
```

```
$`hsa00232 Caffeine metabolism`
```

```
[1] "10" "1544" "1548" "1549" "1553" "7498" "9"
```

```
$`hsa00983 Drug metabolism - other enzymes`
```

```
[1] "10" "1066" "10720" "10941" "151531" "1548" "1549" "1551"
[9] "1553" "1576" "1577" "1806" "1807" "1890" "221223" "2990"
[17] "3251" "3614" "3615" "3704" "51733" "54490" "54575" "54576"
[25] "54577" "54578" "54579" "54600" "54657" "54658" "54659" "54963"
[33] "574537" "64816" "7083" "7084" "7172" "7363" "7364" "7365"
[41] "7366" "7367" "7371" "7372" "7378" "7498" "79799" "83549"
[49] "8824" "8833" "9" "978"
```

The main **gage()** function requires a named vector of fold changes, where the names of the values are the Entrez gene IDs.

```
c(ian=5,tim=1)
```

```
ian tim
5 1
```

```
foldchanges = res$log2FoldChange
names(foldchanges) = res$entrez
head(foldchanges)
```

```
      7105      64102      8813      57147      55732      2268
-0.35070302      NA  0.20610777  0.02452695 -0.14714205 -1.73228897
```

```
## 7105 is the entrez name,
```

```
# Get the results
keggres = gage(foldchanges, gsets=kegg.sets.hs)
```

```
attributes(keggres)
```

```
$names
[1] "greater" "less"    "stats"
```

```
# Look at the first three down (less) pathways
head(keggres$less, 3)
```

		p.geomean	stat.mean	p.val
hsa05332	Graft-versus-host disease	0.0004250461	-3.473346	0.0004250461
hsa04940	Type I diabetes mellitus	0.0017820293	-3.002352	0.0017820293
hsa05310	Asthma	0.0020045888	-3.009050	0.0020045888

		q.val	set.size	exp1
hsa05332	Graft-versus-host disease	0.09053483	40	0.0004250461
hsa04940	Type I diabetes mellitus	0.14232581	42	0.0017820293
hsa05310	Asthma	0.14232581	29	0.0020045888

```
pathview(gene.data=foldchanges, pathway.id="hsa05332")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/chan-yukuo/Desktop/BIMM143/lab12

Info: Writing image file hsa05332.pathview.png




Figure 1: here is a pathway view for hsa05332 from our deseq2 analysis