
CS1010E Lecture 5

Value-Returning Functions


Henry Chia (hchia@comp.nus.edu.sg)

Semester 1 2016 / 2017

Lecture Outline

- ❑ Math library functions
- ❑ Function expression and evaluation
- ❑ User defined functions
- ❑ Pass-by-value
- ❑ Lexical scoping
- ❑ Boolean function
- ❑ Function interface comments

Math Functions



- Given the lengths of two sides of a triangle b and c , and the angle between them α , compute a

$$a^2 = b^2 + c^2 - 2bc \cos \alpha$$

or

$$a = \sqrt{b^2 + c^2 - 2bc \cos \alpha}$$

Math Library Functions

- To use C math library functions, include the preprocessor directive

```
#include <math.h>
```

- Refer to http://www.acm.uiuc.edu/webmonkeys/book/c_guide for a list of functions in <math.h>
 - Example: cos function declaration

```
double cos(double x);
```
 - cos function takes in `double` argument (say x) and produces another `double` value ($\cos(x)$)

Program: Side of a Triangle

```
#include <stdio.h>
#include <math.h>

#define PI 3.14159

int main(void) {
    double a, b, c, alpha;


    printf("Enter b, c and alpha(deg): ");
    scanf("%lf%lf%lf", &b, &c, &alpha);

    /* cos takes in angle in radians */
    a = sqrt((b * b) + (c * c) -
             (2 * b * c * cos(alpha * PI / 180)));

    printf("Length of side a is %f\n", a);

    return 0;
}
```

Functions – Motivation from Life



- Suppose you have a trustworthy friend whom you know can compute the cosine of an angle given in radians
- How to “call” him/her to find the cosine of say, π ?
 - What do you say (or “pass”) to your friend?
 - What does he/she give (or “return”) back to you?
 - Do you need to know how he/she computes the answer?



Function Evaluation

- Evaluate a function expression \Rightarrow “call” the function

argument value(s) \rightarrow function \rightarrow evaluated value

- Suppose $\alpha = 90$, to evaluate `cos(alpha*PI/180)`
 1. Arguments are evaluated: `cos(1.570795)`
 2. Argument values 1.570795 passed to function `cos`
 3. `cos` function performs desired computation
 4. `cos` returns the value 0.0 as the function evaluation
- Only one function executes at any one time

Function Expression




User-Defined Function

- Program template with user defined functions


```
/* preprocessor directives */  
  
/* function prototypes */  
  
int main(void) {  
    /* declarations */  
  
    /* statements */  
  
    return 0;  
}  
  
/* user defined function definitions */
```

User-Defined Function


functionDefn



parameter-decl



function-body



Function Definition

- *functionDefn*
 - type: type of value returned from the function
 - function-id: meaningful function identifier
 - parameter-decl: parameter (variable) declaration
- *parameter-decl*
 - Variables declared to store the values passed from the “caller”
 - One variable per declaration separated by commas
- *function-body*
 - Defines the function implementation
 - **return** statement included as the last logical statement in the function body

return Statement




- Upon executing the return statement,
 1. the expression is evaluated to a value
 2. the function returns the value to the “caller” and terminates
 3. the “caller” function resumes execution with the value returned


Function Prototype

- A function prototype declares the proper usage of the function in terms of function identifier, number/type of arguments and return values
- Hence, it is placed before the corresponding function calls and the definition of the function
- Almost the same as the corresponding function header, but need only specify the parameter type (parameter name is encouraged but not necessary)
- Keep in mind the semicolon at the end

functionPrototype



Example: Surface Area of a Flat Washer



- Given the diameters d_1 and d_2 , find the surface area of the hollow disc
 - E.g. $d_1 = 1.2$ units and $d_2 = 2.4$ units gives a surface area of 3.392917 square units
-
- Area of circle of radius r , $f_{area}(r) = \pi r^2$
 - Surface area of the flat washer is $f_{area}(\frac{d_2}{2}) - f_{area}(\frac{d_1}{2})$
 - In general, $f(x_1, x_2, \dots, x_n)$ is analogous to passing arguments (x_1, x_2, \dots, x_n) to the function f

Program: Surface Area of a Flat Washer

```
#include <stdio.h>

#define PI 3.14159

double areaCircle(double);

int main(void) {
    double d2, d1, area;

    printf("Enter d2 and d1 diameters: ");
    scanf("%lf%lf", &d2, &d1);

    area = areaCircle(d2 / 2.0) - areaCircle(d1 / 2.0);

    printf("The surface area is %f\n", area);

    return 0;
}


double areaCircle(double radius) {
    double area;

    area = PI * radius * radius;

    return area;
}
```

Pass-by-Value


- During a function call, each argument expression is evaluated and the **value** passed to the function and stored in each input parameter



- In the example above, upon initiating the function call in **main**, **areaCircle** **activates** while execution in **main** **suspends**


Lexical Scoping

- The scope of accessibility of a variable is within the function in which the variable is declared
- Variables within a function are **local** to that function
- Variables of the same name can co-exist across functions



Return Value

- Function terminates with a return **value** to the caller



- In the example above, `areaCircle` returns the value to the caller function and **terminates**; `main` then **resumes** execution

Program: Surface Area of a Flat Washer

```
#include <stdio.h>
#define PI 3.14159
double areaCircle(double radius);
double surfaceArea(double dOut, double dIn);

int main(void) {
    double d2, d1, area;

    printf("Enter washer and hole diameters: ");
    scanf("%lf%lf", &d2, &d1);

    area = surfaceArea(d2,d1);
    printf("The surface area is %f\n", area);

    return 0;
}

double surfaceArea(double dOut, double dIn) {
    return areaCircle(dOut/2.0) - areaCircle(dIn/2.0);
}

double areaCircle(double radius) {
    return PI * radius * radius;
}
```

Boolean Functions

- *Boolean* functions — return `true` or `false` values
- Defined with `bool` return type with identifier names preferably starting with `is...`, e.g. `isPrime`
- Example: Primality testing
 - Given an integer $n(> 1)$, determine if n is prime
 - Loop through all divisors from 2 to $p - 1$
 - If there is a divisor that divides p , p is **not prime**
 - p is prime only when **all** divisors from 2 to $p - 1$ **do not** divide p

Program: Primality Testing

```
#include <stdio.h>
#include <stdbool.h>
bool isPrime(int n);


int main(void) {
    int n;

    printf("Enter a number: ");
    scanf("%d", &n);

    if (isPrime(n)) {
        printf("%d is prime\n", n);
    } else {
        printf("%d is not prime\n", n);
    }
    return 0;
}

bool isPrime(int n) {
    int i; bool prime=true;

    for (i = 2; i < n; i++) {
        if (n%i == 0) {
            prime = false;
        }
    }
    return prime;
}
```



Early Return

- The isPrime function can be defined to return early

```
bool isPrime(int n) {  
    int i;  
    for (i = 2; i < n; i++) {  
        if (n%i == 0) {  
            return false;  
        }  
    }  
    return true;  
}
```

- Preferred alternative that maintains single-entry-single-exit

```
bool isPrime(int n) {  
    int i; bool prime=true;  
    for (i = 2; i < n && prime; i++) {  
        if (n%i == 0) {  
            prime = false;  
        }  
    }  
    return prime;  
}
```

Function Interface Comments

- A function should contain a comment on
 - Pre-condition – condition that should hold true before the function is called
 - Post-condition – condition that must hold true after the function completes (can be the purpose of the function)
- Example:

```
/*  
    isPrime function returns true if n is prime,  
    false otherwise.  
    Precondition: n > 1  
*/  
bool isPrime(int n) {  
    ...  
}
```

Lecture Summary

- When working with functions, ensure **type consistency**
 - Between the argument values and the input parameters

```
double areaCircle(double radius); /* parameter type is double */
...
area = areaCircle(1.23); /* argument type is double */
```
 - Between the type of return expression and the function return type

```
double areaCircle(double radius) { /* return type is double */
    return PI * radius * radius; /* expression type is double */
}
```
 - Between the function return type and how it is used, e.g.

```
printf("%f\n", areaCircle(radius));
/* %f prints double-type return value */
```
- Appreciate the concepts of pass-by-value and lexical scoping