# CS1010E Lecture 9 Arrays and Matrices (Part II)

Joxan Jaffar


Block COM1, Room 3-11, +65 6516 7346 www.comp.nus.edu.sg/~joxan cs1010e@comp.nus.edu.sg

Semester II, 2016/2017

#### **Lecture Outline**

- Two-Dimensional Arrays
- Matrix Algorithms
  - Addition, Subtraction, Dot Product, Transpose
  - Solving Linear Equations (non-examinable)
- Higher-Dimensional Arrays (non-examinable)


- A set of data values that is visualized as a row or column is easily represented by a one-dimensional array.
- However, there are many examples in which the best way to visualize a set of data is with a grid or a table of data, which has both rows and columns.
- A two-dimensional array with four rows and three columns is shown in the next slide.



- In C, a grid or table of data is represented with a two-dimensional array.
- Each element in a two-dimensional array is referenced using an identifier followed by two subscripts—a row subscript and a column subscript.
- The subscript values for both rows and columns begin with 0, and each subscript has its own set of brackets.

- Thus, assuming that the previous array has an identifier x, the value in position x[2][1] is 6.
- Common errors in array references include using parentheses instead of brackets as in x(2)(3), or using only one set of brackets or parentheses as in x[2,3] or x(2,3).

- We can also visualize this grid or table of data as a one-dimensional array, where each element is also an array.
- Thus, the array in the previous diagram can be interpreted as a one-dimensional array with four elements, each of which is a one-dimensional array with three elements, as shown on the next slide.



- All values in an array must have the same type.
- An array cannot have a column of integers followed by a column of floating-point numbers, and so on.

- To define a two-dimensional array, we specify the number of rows and the number of columns in the declaration statement.
- The row number is written first.
- Both the row number and the column number are in brackets, as shown in this statement:
  - int x[4][3];

- A two-dimensional array can be initialized with a declaration statement.
- The values are specified in a sequence separated by commas, and each row is contained in braces.
- An additional set of braces is included around the complete set of values, as shown in the following statement:

```
• int x[4][3] = \{\{2,3,-1\},\{0,-3,5\},\{2,6,3\},\{-2,10,4\}\};
```

- If the initializing sequence is shorter than the array, then the rest of the values are initialized to zero.
- If the array is specified with the first subscript empty, but with an initializing sequence, the size is determined by the sequence.
- $\bullet$  Thus, the array x can also be defined with the following statement

```
• int x[][3] = \{\{2,3,-1\},\{0,-3,5\},\{2,6,3\},\{-2,10,4\}\};
```

- Arrays can also be initialized with program statements.
- For two-dimensional arrays, two nested for loops are usually required to initialize an array; i and j are commonly used as subscripts.
- To define and initialize an array such that each row contains the row number, use the following statements:

```
• int i, j, t[5][4];
...
for (i=0; i<=4; i++)
    for (j=0; j<=3; j++)
        t[i][j] = i;</pre>
```

 After these statements are executed, the values in the array t are as follows:

```
0 0 0 0 0
1 1 1 1
2 2 2 2
3 3 3 3
4 4 4 4
```

- Two-dimensional arrays can also be initialized with values read from a data file.
- In the next set of statements, we assume that a data file contains 50 temperature values that we read and store in the array.
- Symbolic constants NROWS and NCOLS are used to represent the number of rows and columns.
- Changing the size of an array is easier to do when the numbers of rows and columns are specified as symbolic constants; otherwise the change requires modifications to several statements.

```
#define NROWS 10
#define NCOLS 5
#define FILENAME "engine1.txt"
. . .
/* Declare variables. */
int i, j;
double temps[NROWS][NCOLS];
FILE *sensor;
/* Open file and read data into array. */
sensor = fopen(FILENAME, "r");
for (i=0; i\leq NROWS-1; i++)
    for (j=0; j<=NCOLS-1; j++)
        fscanf(sensor, "%lf", &temps[i][j]);
```

- Computations and output with two-dimensional arrays must always specify two subscripts when referencing an array element.
- Consider a program that reads a data file containing power output for an electrical plant for an eight-week period.
- Each line of the data file contains seven values representing the daily power output for a week.
- The data are stored in a two-dimensional array.
- Then a report provides the average power for the first day of the week during the period, the average power for the second day of the week during the period, and so on.

```
Program chapter5_6
/*
/*
   This program computes daily power averages over eight
  weeks.
#include <stdio.h>
#define NROWS 8
#define NCOLS 7
#define FILENAME "power1.txt"
int main (void)
   /* Declare variables. */
   int i, j;
    int power[NROWS][NCOLS], col_sum;
   FILE *file_in;
  Code on Next Slide
   /* Exit program. */
   return 0; }
```

```
/* Read information from a data file. */
file in = fopen(FILENAME, "r");
if (file_in == NULL)
    printf("Error opening input file. \n");
else
    for (i=0; i \le NROWS-1; i++)
        for (j=0; j<=NCOLS-1; j++)
            fscanf(file_in, "%d", &power[i][j]);
    /* Compute and print daily averages. */
    for (j=0; j \le NCOLS-1; j++)
        col sum = 0:
        for (i=0; i \le NROWS-1; i++)
            col sum += power[i][i];
        printf("Day %d: Average = %.2f \n",
                j+1, (double) col sum/NROWS);
    /* Close file. */
    fclose(file_in);
```

- Note that the daily averages are computed by adding each column and then dividing the column sum by the number of rows (which is also the number of weeks).
- The column number is then used to compute the day number.
- A sample output from this program is as follows:

```
Day 1: Average = 253.75
Day 2: Average = 191.50
Day 3: Average = 278.38
Day 4: Average = 188.62
Day 5: Average = 273.12
Day 6: Average = 321.38
Day 7: Average = 282.50
```

- Writing information from a two-dimensional array to a data file is similar to writing the information from a one-dimensional array.
- In both cases, a newline indicator must be used to specify when the values are to begin a new line.
- To write a set of distance measurements to a data file named dist1.txt with five values per line, see the next slide.
- Note that the space after the conversion specifier in the fprintf statement is necessary in order to have the values separated by a space.

```
/* Declare variables. */
int i, j;
double dist[20][5];
FILE *file out;
/* Write information from the array to a */
/* file.
file out = fopen("dist1.txt", "w");
for (i=0; i<=19; i++) {
    for (j=0; j<=4; j++)
        fprintf(file_out, "%f ", dist[i][j]);
    fprintf(file out, "\n");
fclose(file out);
```

- When arrays are used as function parameters, the references are call-by-address instead of call-by-value.
- When discussing one-dimensional arrays, we learned that array references in a function refer to the original array and not to a copy of the array.
- Thus, we must be careful so we do not unintentionally change values in the original array.
- Of course, an advantage of a call-by-address reference is that we can make changes in the array values, in addition to returning a value from the function call.

- When using a one-dimensional array as a function argument, the function needs only the address of the array, which is specified by the array name.
- When using a two-dimensional array as a function argument, the function also needs information about the size of the array.
- In general, the function declaration and prototype statement should give complete information about the size of a two-dimensional array.

- Suppose that we need to write a program that computes the sum of the elements in an array containing four rows and four columns.
- Here is the function prototype statement:

```
• int sum(int x[4][4]);
```

 The program can then reference the function with a single statement:

```
• int a[4][4];
...
printf("Array sum = %i \n", sum(a));
```

 We can use this function for several two-dimensional arrays of the same size:

```
• int a[4][4], b[4][4];
...
printf("Sum of a = %i \n", sum(a));
printf("Sum of b = %i \n", sum(b));
```

- Note that the actual parameter consists of simply a.
- Anything else (for example, int a[4][4] or a[4][4] or a[][]) is incorrect.

```
/* This function returns the sum of the values */
/* in an array with four rows and four columns. */
int sum(int x[4][4])
    /* Declare and initialize variables. */
    int i, j, total=0;
   /* Compute a sum of the array values. */
   for (i=0; i<=3; i++)
       for (i=0; i<=3; i++)
           total += x[i][j];
    /* Return sum of array values. */
    return total;
```

 We can use this function for several two-dimensional arrays of the same size:

```
• int a[4][4], b[4][4];
...
printf("Sum of a = %i \n", sum(a));
printf("Sum of b = %i \n", sum(b));
```

- Note that the actual parameter consists of simply a.
- Anything else (for example, int a[4][4] or a[4][4] or a[][]) is incorrect.

#### **Partial Sum**

Now suppose we want to compute only a *partial sum* of the elements in an array. The subarray shall be at the *top-left* corner of the original array.

2	3	-1	9
0	<b>.</b>	5	7
2	6	3	2
-2	10	4	6

#### **Partial Sum**

```
/* This function returns the sum of the values in an
/* SUB-array of an array with four rows and
                                                           */
/\star four columns. The subarray has r rows and c columns. \star/
int partial_sum(int x[4][4], int r, int c)
{
    /* Declare and initialize variables. */
   int i, j, total = 0;
    /* Compute a sum of the array values. */
    for (i = 0; i \le r-1; i++)
        for (j = 0; j \le c-1; j++)
            total += x[i][i];
    /* Return sum of SUB-array values. */
    return total;
```

#### **Array Size Declarations**

 With one-dimensional arrays (eg. foo) we could abbreviate the prototype definition as well as the function definition such as

```
int foo(int a[100]);
by
int foo(int a[], int n);
```

For two-dimensional arrays, we can also abbreviate

```
int foo(int a[100][200]);
by
int foo(int a[][200], int n);
Note that only the first size is abbreviated.
```

Main advantage: can use function over arrays of different sizes.

In order to use the function over two-dimensional arrays of varying sizes, we require pointers, covered later.

## **Example: Terrain Navigation**

- Given: a grid representation of rectangular piece of land, and for each grid element, the elevation of the land at the the corresponding point.
- Represent the grid as a two dimensional array grid[M][N].
- Problem: determine all *peaks*, ie. all grid positions whose elevation is higher than that of its neighbours.

	grid[m-1][n]	
grid[m][n-1]	grid[m][n]	grid[m][n+1]
	grid[m+1][n]	

#### **Pseudocode**

```
Refinement in Pseudocode
         read nrows and ncols from the data file
main:
         read the terrain data into an array called elevation
         set i to 1
         while i \leq nrows - 2
                  set j to 1
                  while j \leq ncols - 2
                          if elevation[i][j] > its four neighbors
                                         print peak location
                          increment j by 1
                  increment i by 1
```

## **C Program Code**

```
#include <stdio.h>
#define N 25
int main(void) {
int nrows, ncols, i, j;
double elev[N][N];
FILE *grid;
    if ((grid = fopen("grid.txt", "r")) == NULL)
        printf("Error opening file\n");
    else {
        fscanf (grid, "%d %d", &nrows, &ncols);
        for (i = 0; i \leq nrows-1; i++)
            for (j = 0; j \le ncols-1; j++)
                 fscanf(grid, "%lf", &elev[i][j]);
  Code on Next Slide
   /* Exit program. */
    fclose (grid);
    return 0:
```

#### **Body code**

```
printf("Top left point is row 0 column 0\n");
for (i = 1; i <= nrows-2; i++)
    for (j = 1; j <= ncols-2; j++)
        if (elev[i-1][j] < elev[i][j] &&
            elev[i+1][j] < elev[i][j] &&
            elev[i][j-1] < elev[i][j] &&
            elev[i][j])
        printf("Peak at row %d col %d\n", i, j);</pre>
```

## **Sample Data**

#### Input:

5039	5127	5238	5259	5248	5310	5299
5150	5392	5410	5401	5320	5820	5321
5290	<u>5560</u>	5490	5421	5530	<u>5831</u>	5210
5110	5429	5430	5411	5459	5630	5319
4920	5129	4921	<u>5821</u>	4722	4921	5129
5023	5129	4822	4872	4794	4862	4245

#### Output:

```
Top left point defined as row 0 column 0
```

Peak at row: 2 column 1
Peak at row: 2 column 5
Peak at row: 4 column 3

#### **Matrices and Vectors**

 A matrix is a set of numbers arranged in a rectangular grid with rows and columns. Example of a 4 × 3 matrix:

$$\mathbf{A} = \begin{bmatrix} -1 & 0 & 0 \\ 1 & 1 & 0 \\ 1 & -2 & 3 \\ 0 & 2 & 1 \end{bmatrix}$$

- A matrix with one row is a row vector.
   A matrix with one column is a column vector.
   A matrix with the same number of rows and columns is a square matrix.
- A two-dimesional array is naturally used to store a matrix.
- We next exemplify some operations on matrices.

#### **Dot Product**

The dot product<sup>a</sup> is a number computed from two vectors A, B of the same size.

Suppose **A** is  $[a_1, a_2, \cdots, a_n]$  and **B** is  $[b_1, b_2, \cdots, b_n]$ . Then the dot product **A** . **B** of **A** and **B** is:

$$\mathbf{A}.\mathbf{B} = \sum_{i=1}^{n} a_i b_i$$

• Example: suppose  $\mathbf{A} = \begin{bmatrix} 4 & -1 & 3 \end{bmatrix}$  and  $\mathbf{B} = \begin{bmatrix} -2 & 5 & 2 \end{bmatrix}$ , then:

**A.B** = 
$$4.(-2)+(-1).5+3.2$$
  
 $(-8)+(-5)+6$   
 $-7$ 

<sup>&</sup>lt;sup>a</sup>Also called an *inner product*.

```
double dot_product(double a[], double b[], int n)
{
    int k;
    double sum = 0;

    for (k = 0; k <= n-1; k++)
        sum += a[k] * b[k];

    return sum;
}</pre>
```

#### IMPORTANT NOTE ABOUT NOTATION:

Matrix entries are denoted using subscripts starting from 1. Arrays in C however use subscripts starting from 0.

#### **Transpose**

 The tranpose of a matrix is a new matrix in which the rows of the original matrix are columns of the new matrix.
 Notation: the tranpose of a matrix B is written B<sup>T</sup>.

Example:

$$\mathbf{B} = \begin{bmatrix} 2 & 5 & 1 \\ 7 & 3 & 8 \\ 4 & 5 & 21 \\ 16 & 13 & 0 \end{bmatrix} \qquad \mathbf{B}^T = \begin{bmatrix} 2 & 7 & 4 & 16 \\ 5 & 3 & 5 & 13 \\ 1 & 8 & 21 & 0 \end{bmatrix}$$

```
/* Transpose a matrix.
/* Symbolic constants NROWS and NCOLS are declared
/* in the calling program
void transpose(int b[NROWS][NCOLS], int bt[NCOLS][NROWS])
    int i, j;
    for (i = 0; i \le NROWS-1; i++)
        for (j = 0; j \le NCOLS-1; j++)
            bt[j][i] = b[i][j];
    return;
```

#### **Matrix Addition and Subtraction**

- Addition/Subtraction for matrices of the same size.
- operations defined by adding/subtracting elements in corresponding positions.
- Examples:

$$\mathbf{A} = \begin{bmatrix} 2 & 5 & 1 \\ 0 & 3 & -1 \end{bmatrix} \qquad \mathbf{B} = \begin{bmatrix} 1 & 0 & 2 \\ -1 & 4 & -2 \end{bmatrix}$$

$$\mathbf{A} + \mathbf{B} = \begin{bmatrix} 3 & 5 & 3 \\ 0 & 3 & -1 \end{bmatrix} \qquad \mathbf{A} - \mathbf{B} = \begin{bmatrix} 1 & 5 & -1 \\ 1 & -1 & 1 \end{bmatrix}$$

$$\mathbf{B} - \mathbf{A} = \begin{bmatrix} -1 & -5 & 1 \\ -1 & 1 & -1 \end{bmatrix}$$

#### **Matrix Multiplication**

The product C = AB of two matrices A and B is defined as follows:
 c<sub>i,j</sub> is the dot product of row i of A and column j of B:

$$c_{i,j} = \sum_{k=1}^n a_{i,k} b_{k,j}$$

- Thus the row size of A must equal the column size of B:
   if A is M × K and B is L × N, then K = L and AB is M × N.
- Example:

$$\mathbf{A} = \begin{bmatrix} 2 & 5 & 1 \\ 0 & 3 & -1 \end{bmatrix} \quad \mathbf{B} = \begin{bmatrix} 1 & 0 & 2 \\ -1 & 4 & -2 \\ 5 & 2 & 1 \end{bmatrix}$$
$$\mathbf{C} = \mathbf{A}\mathbf{B} = \begin{bmatrix} 2 & 22 & 5 \\ -8 & 10 & -7 \end{bmatrix}$$

The product BA does not exist.

```
/* Matrix Multiplication of two NxN matrices.
/* N is a symbolic constant defined in the calling program.
void matrix mult(int a[N][N], int b[N][N], int c[N][N])
    int i, j, k;
    for (i = 0; i \le N-1; i++)
        for (j = 0; j \le N-1; j++) {
            c[i][i] = 0;
            for (k = 0; k \le N-1; k++)
                c[i][i] += a[i][k] * b[k][i];
    return;
```

**Exercise:** Modify this function for matrices A[N][K] and B[K][M].

# **Solving Simultaneous Linear Equations** (Non-Examinable)

A linear equation is of the form

$$a_1 x_1 + a_2 x_2 + \cdots + a_n x_n$$

where the  $x_i$  are variables and the  $a_i$  are coefficients.

- A linear equation with 2 variables defines a *line*. Eg. y = 2x + 3 is a line whose *slope* is 2 and *y-intercept* is 3.
- A linear equation with 3 or more variables defines a hyperplane.
- Given a system of *m* equations in *n* unknowns (variables).

If m < n: system is *underspecified* and there is no unique solution.


If m = n: unique solution if none of the equations define *parallel* hyperplanes.

If m > n: system is *overspecified* and there is no solution if none of the equations define parallel hyperplanes.

A system with a unique solution is called *nonsingular*.


## **Solving Simultaneous Linear Equations**

Intersecting, Parallel and Overlapping Lines



## **Solving Simultaneous Linear Equations**

Intersecting, Parallel and Overlapping Planes



## **Solving Simultaneous Linear Equations**

$$3x + 2y - z = 10$$
• Example:  $-x + 3y + 2z = 5$ 
 $x - y - z = -1$ 

Can represent as the matrix product AX = B where

$$\mathbf{A} = \begin{bmatrix} 3 & 2 & -1 \\ -1 & 3 & 2 \\ 1 & -1 & -1 \end{bmatrix} \qquad \mathbf{X} = \begin{bmatrix} x \\ y \\ z \end{bmatrix} \qquad \mathbf{B} = \begin{bmatrix} 10 \\ 5 \\ -1 \end{bmatrix}$$

We will describe the Gaussian Method.

## **Gauss Elimination (Non-Examinable)**

$$3x + 2y - z = 10$$
 (eqn 1)  
 $-x + 3y + 2z = 5$  (eqn 2)  
 $x - y - z = -1$  (eqn 3)

#### **Gauss Elimination**

$$-x - \frac{2}{3}y + \frac{1}{3}z = -\frac{10}{3} \text{ (eqn 1 times } -\frac{1}{3}\text{)}$$

$$x - y - z = -1 \text{ (eqn 3)}$$

$$0x - \frac{5}{3}y - \frac{2}{3}z = -\frac{13}{3} \text{ sum}$$

Variable x is now eliminated from all but the first equation.

#### **Gauss Elimination**

 Variables x, y is now eliminated from all but the first and second equations.

#### **Back Substitution (Non-Examinable)**

- In the last equation  $\frac{3}{33}z = -\frac{18}{33}$ , ie z = -6.
- Substituting this into the second last equation  $\frac{11}{3}y \frac{5}{3}z = \frac{25}{3}$  we get  $y = \frac{165}{33}$ , ie. y = 5.
- Substituting both z = -6 and y = 5 into the first equation 3x + 2y z = 10 we get x = -2.
- So we have our solution: x = -2, y = 5, z = -6.

## Summary on Gauss Elimination and Back Substitution

- The Gaussian Method consisted of two parts: Gauss Elimination E and BS.
- **Gauss Elimination** Equations are modified so that the  $k^{th}$  variable is eliminated from all equations *after* the  $k^{th}$  equation.
- Back Substitution Starting with the last equation, we compute the
  value of the last variable. Using this last value and the second-last
  equation, we compute the value of the second-last variable. This
  process terminates successfully if the system has a unique solution,
  in which case all the variable values are computed.
- The above process fails when all the coefficients of one variable is zero. We also say that the system of equations is ill-conditioned.


#### **Example: Electrical Circuit Analysis**

Analysis of an electrical circuit often involves solving a set of simultaneous equations. These equations are either

- current equations describing currents entering and leaving a node, or
- voltage equations describing voltages around mesh loops in the circuit.

We next provide an example using voltages:

## **Example: Electrical Circuit Analysis**



The voltages around the three loops can be described with the following equations<sup>a</sup>:

$$-V_1$$
 +  $R_1i_1$  +  $R_2(i_1 - i_2)$  = 0,  
 $R_2(i_2 - i_1)$  +  $R_3i_2$  +  $R_4(i_2 - i_3)$  = 0,  
 $R_4(i_3 - i_2)$  +  $R_5i_3$  +  $V_2$  = 0.

<sup>&</sup>lt;sup>a</sup>You are not required to understand why this is so.

## **Example: Electrical Circuit Analysis**

Assuming the values of the resistors  $(R_1, R_2, R_3, R_4, R_5)$  are known and the voltage sources  $(V_1, V_2)$  are known, we can rearrange the equations as follows:

$$(R_1 + R_2)i_1$$
 -  $R_2i_2$  +  $0i_3$  =  $V_1$ ,  
 $-R_2i_1$  +  $(R_2 + R_3 + R_4)i_2$  -  $R_4i_3$  =  $0$ ,  
 $0i_1$  -  $R_4i_2$  +  $(R_4 + R_5)i_3$  =  $-V_2$ .

For example, suppose that each of the resistor values is 1 ohm, and assume the both the voltage sources are 5 volts. Then the corresponding set of equations is:

$$2i_1 - i_2 + 0i_3 = 5,$$
  
 $-i_1 + 3i_2 - i_3 = 0,$   
 $0i_1 - i_2 + 2i_3 = -5.$ 

#### **Pseudocode**

```
main: read resistor values and voltage values specify array coefficients, a[i][j] set index to zero while index \leq n-2 eliminate(a,n,index) increment index by 1 back_substitute(a,n,soln) print current values
```

#### **Pseudocode**

```
eliminate(a,n,index):
             set row to index +1
             while row \le n - 1
                   set scale_factor to \frac{-a[row][index]}{a[index][index]}
                   set a[row][index] to zero
                   set col to index + 1
                   while col \leq n
                         add a[index][col] · scale_factor
                               to a[row][col]
                         increment col by 1
                   increment row by 1
```

#### **Pseudocode**

```
back_substitute(a,n,soln):
         set soln[n-1] to \frac{-a[n-1][n]}{a[n-1][n-1]}
         set row to n-2
         while row \geq 0
                set col to n-1
                while col > row + 1
                      subtract soln[col] · a[row][col]
                           from a[row][n]
               subtract 1 from col
         set soln[row] to \frac{a[row][n]}{a[row][row]}
         subtract 1 from row
```

```
Program chapter5 8
   This program uses Gauss elimination to determine the
   mesh currents for a circuit.
#include <stdio.h>
#define N 3 /* number of unknown currents */
int main(void)
      Declare variables and function prototypes. */
   int index:
  double r1, r2, r3, r4, r5, v1, v2, a[N][N+1], soln[N];
  void eliminate(double a[N][N+1],int n,int index);
  void back_substitute(double a[N][N+1],int n,
                       double soln[N]):
  /* Get user input. */
  printf("Enter resistor values in ohms: \n");
  printf("(R1, R2, R3, R4, R5) \n"):
   scanf("%lf %lf %lf %lf",&r1,&r2,&r3,&r4,&r5);
  printf("Enter voltage values in volts: \n");
  printf("(V1, V2) \n");
   scanf("%1f %1f",&v1,&v2):
```

```
/* Specify equation coefficients. */
a[0][0] = r1 + r2;
a[0][1] = a[1][0] = -r2;
a[0][2] = a[2][0] = a[1][3] = 0;
a[1][1] = r2 + r3 + r4:
a[1][2] = a[2][1] = -r4;
a[2][2] = r4 + r5:
a[0][3] = v1;
a[2][3] = -v2;
```

```
/* Perform elimination step. */
for (index=0; index<=N-2; index++)
   eliminate(a,N,index);
/* Perform back substitution step. */
back_substitute(a,N,soln); --
/* Print solution. */
printf("\n"):
printf("Solution: \n");
for (index=0, index<=N-1; index++)
  printf("Mesh Current %d: %f \n",index+1,soln[index]);
/* Exit program. */
return 0;
```

```
This function performs the elimination step.
void eliminate(double a[N][N+1],int n,int index)
{
   /* Declare variables. */
   int row, col;
   double scale factor:
   /* Eliminate variable from equations. */
   for (row=index+1; row<=n-1; row++)</pre>
      scale_factor = -a[row][index]/a[index][index];
      a[row][index] = 0:
      for (col=index+1; col<=n; col++)</pre>
         a[row][col] += a[index][col]*scale_factor;
   /* Void return. */
   return:
```

```
This function performs the back substitution.
void back_substitute(double a[N][N+1],int n,
                     double soln[N])
  /* Declare variables. */
  int row, col:
  /* Perform back substitution in each equation.
  soln[n-1] = a[n-1][n]/a[n-1][n-1];
  for (row=n-2: row>=0: row--)
      for (col=n-1; col>=row+1; col--)
        a[row][n] -= soln[col]*a[row][col];
      soln[row] = a[row][n]/a[row][row];
  /* Void return. */
  return;
```

#### **Testing**

```
Enter resistor values in ohms:
(R1, R2, R3, R4, R5)
1 1 1 1 1
Enter voltage values in volts:
(V1. V2)
Solution:
Mesh Current 1: 2.500000
Mesh Current 2: 0,000000
Mesh Current 3: -2.500000
```

## **Higher Dimensional Arrays**


#### (Non-Examinable)

C allows arrays to be defined with more than two subscripts.

For example, the following declares a three-dimensional array:


The three subscripts correspond to the x, y, z coordinates.

Positioning the array at the origin, the shaded area corresponds to b[2][0][1]:




## **Higher Dimensional Arrays**

A four-dimensional area is depicted as follows:



A five-dimensional area is depicted as follows:



**Note:** Arrays with over three subscripts are seldom used. Instead, *structures* are used – this is covered later.

#### References

Etter Sections 5.8 to 5.13

#### **Next Lecture**

## Programming with Pointers