

UUEE/SVO
SHEREMETYEVO

JEPPESEN
13 FEB 26

20-1P

Eff 19 Feb

MOSCOW, RUSSIA
AIRPORT BRIEFING

1. GENERAL

1.1. ATIS

ATIS Departure 125.125
126.375 (Russian)
ATIS Arrival 122.075
120.375 (Russian)

1.2. NOISE ABATEMENT PROCEDURES

1.2.1. GENERAL

Noise abatement procedures shall be executed by all ACFT but not at the expense of flight safety.

Daily from 2200-0600LT take-off and landing of Tu-134, Tu-154, Il-86, Il-76, An-12, An-26 which do not comply with noise standards stated in ICAO Annex 16 are restricted, except VIP, medical, emergency and SAR flights.

1.2.2. PREFERENTIAL RWYs

RWYs 06C, 06R, 24C and 24L shall be used to the maximum possible degree.

1.3. LOW VISIBILITY PROCEDURES (LVP)

1.3.1. GENERAL

RWYs 06L/24R, 06C/24C and 06R/24L are available for take-off in low visibility conditions, if LVP are in progress.

LVP shall be applied when RVR is less than 550m at least at one of the three observation sites (touchdown zone, mid-point and stop-end of RWY).

In case of LVP implementation, AN-124 must not be present on TWY N11.

When RVR is less than 550m:

- Stop bar lights shall be switched on at pattern A and B RWY holding position marking on TWY B1, B2, B3, B4, B5, B6, B7, G1, G2, G3, G4, G5, A1, A9, E1, E2, E3, E4, E5 and MAIN TWY A.
- RWY guard lights shall be switched on at pattern A RWY holding position marking on TWYs A2, A3, A4, A5, A6, A7 and A8.

When RVR is less than 300m:

- Intermediate holding position lights shall be switched on at the intermediate holding position marking on TWY N2, N3, N5, N6, N7, N8, B, S1, S2, S3, S4, S5, S6, S7, S8, S9, S10, S11, S12.
- Stop bar lights shall be switched on at the intermediate holding position marking on TWY B, N1, A2, A3, A4, A5, A6, A7, A8, D, E and MAIN TWY A.
- TWY centerline LGT shall be illuminated on TWY N1, N3, N5, N6, N7, N8, N9, B, B1, B7, G1, G5, A1, A6, A7, A9, D, E, E1, E2, E3, E4, E5, E7 and MAIN TWYA.
- TWY B1, B7, B, G5, G1, A1, A6, A7, A9, N9, N8, N7, N6, N5, N3, N1, E1, E2, E3, E4, E5, E7, E, D, D1, MAIN TWY A, S1, S2, S3, S4, S5, S6, S7, S8, S9, S10, S11, S12, S13 shall be used.
- Exit lights of de-icing pad shall be illuminated on TWY E7.
- ACFT shall taxi via TWY S1, S2, S3, S4, S5, S6, S7, S8, S9, S10, S11, S12, S13 and along the apron only under assistance of the Follow-me car equipped with two-way ground-to-air and ground-ground radio communication, flashing lights and Follow-me LED display.
- ACFT shall take-off only from the RWY beginning.

UUEE/SVO
SHEREMETYEVO

JEPPESEN

13 FEB 26

20-1P1

Eff 19 Feb

MOSCOW, RUSSIA
AIRPORT BRIEFING

1. GENERAL

1.3.2. ARRIVAL

After landing, flight crew must report RWY and ILS critical area vacated to Tower controller.

The following standard taxi routes are established for arriving ACFT, when RVR is less than 300m:

- **For RWY 06L:**

- to aprons of terminals A, B, C and Aviation Scientific and Technical Center apron:
TWY (E3, E4, E5) - TWY E - TWY D - TWY B - TWY (N1, N3, N5, N6, N7, N8, N9) - stand.
- to sectors on apron of terminal D:
TWY (E1, E2) - TWY E - TWY D - TWY B - TWY B1 - TWY G1 - TWY A1 - MAIN TWY A - TWY (S1, S2, S3) - stand.
- to aprons of terminals E and F:
TWY (E1, E2) - TWY E - TWY D - TWY B - TWY B1 - TWY G1 - TWY A1 - MAIN TWY A - TWY (S4, S5, S6, S7, S8, S9, S11, S12, S13) - stand.

- **For RWY 06R:**

- to aprons of terminals A, B, C and Aviation Scientific and Technical Center apron:
TWY G5 - TWY B7 - TWY B - TWY (N1, N3, N5, N6, N7, N8, N9) - stand.
- to sectors on apron of terminal D:
TWY A9 - MAIN TWY A - TWY (S1, S2, S3) - stand.
- to aprons of terminal E and F:
TWY (A6, A7, A9) - MAIN TWY A - TWY (S4, S5, S6, S7, S8, S9, S11, S12, S13) - stand.

- **For RWY 24C:**

- to aprons of terminals A, B, C and Aviation Scientific and Technical Center apron:
TWY B1 - TWY B - TWY (N1, N3, N5, N6, N7, N8, N9) - stand.
- to aprons of terminals D, E and F:
TWY G1 - TWY A1 - MAIN TWY A - TWY (S1, S2, S3, S4, S5, S6, S7, S8, S9, S11, S12, S13) - stand.

- **For RWY 24R:**

- to aprons of terminals A, B, C and Aviation Scientific and Technical Center apron:
TWY (E1, E2) - TWY E - TWY D - TWY B - TWY (N1, N3, N5, N6, N7, N8, N9) - stand.
- to sectors on apron of terminal D:
TWY (E1, E2) - TWY E - TWY D - TWY B - TWY B1 - TWY G1 - TWY A1 - MAIN TWY A - TWY (S1, S2, S3) - stand.
- to aprons of terminals E and F:
TWY (E1, E2) - TWY E - TWY D - TWY B - TWY B1 - TWY G1 - TWY A1 - MAIN TWY A - TWY (S4, S5, S6, S7, S8, S9, S11, S12, S13) - stand.

UUEE/SVO
SHEREMETYEVO

JEPPESEN
10 MAY 24

20-1P2

Eff 16 May

MOSCOW, RUSSIA
AIRPORT BRIEFING

1. GENERAL

1.3.3. START-UP AND TAXIING

Pilots shall request start-up clearance when ready for start-up indicating the number of stand (apron).

The following standard taxi routes are established for departing ACFT, when RVR is less than 300m:

- **For RWY 06L:**

- from aprons of terminals A, B, C:
stand - TWY (N1, N3, N5, N6, N7, N8, N9) - TWY B - TWY D - TWY E - TWYE1.
- from sectors on apron of terminal D:
stand - TWY (S1, S2, S3) - MAIN TWY A - TWY A1 - TWY G1 - TWY B1 - TWY B - TWY D - TWY E - TWY E1.
- from aprons of terminals E and F:
stand - TWY (S4, S5, S6, S7, S8, S9, S11, S12) - MAIN TWY A - TWY A1 - TWY G1 - TWY B1 - TWY B - TWY D - TWY E - TWY E1.
- from De-icing area 1:
stand (82, 82A, 83, 83A, 84) - MAIN TWY A - TWY A1 - TWY G1 - TWY B1 - TWY B - TWY D - TWY E - TWY E1.

- **For RWY 06C:**

- from aprons of terminals A, B, C :
stand - TWY (N1, N3, N5, N6, N7, N8, N9) - TWY B - TWY B1.
- from aprons of terminals D, E and F:
stand - TWY (S1, S2, S3, S4, S5, S6, S7, S8, S9, S10, S11, S12) - MAIN TWY A - TWY A1 - TWY G1.
- from De-icing area 1:
stand (82, 82A, 83, 83A, 84) - MAIN TWY A - TWY A1 - TWY G1.
- from De-icing area 1:
stand (82A, 83A) - TWY A9 - TWY G5 - TWY B7 - TWY B - TWY B1.

- **For RWY 06R:**

- from aprons of terminals A, B, C and Aviation Scientific and Technical Center apron:
stand - TWY (N1, N3, N5, N6, N7, N8, N9) - TWY B - TWY B1 - TWY G1.
- from aprons of terminals D, E and F:
stand - TWY (S1, S2, S3, S4, S5, S6, S7, S8, S9, S10, S11, S12) - MAIN TWY A - TWY A1.
- from De-icing area 1:
stand (82, 83, 84) - MAIN TWY A - TWY A1.
- from De-icing area 1:
stand (82A, 83A) - TWY A9 - TWY G5 - TWY B7 - TWY B - TWY B1 - TWY G1.

- **For RWY 24L:**

- from aprons of terminals A and B:
stand - TWY N9 - TWY B7 - TWY G5.
- from aprons of terminals B and C:
stand - TWY (N1, N3, N5, N6, N7, N8, N9) - TWY B - TWY B7 - TWY G5.
- from aprons of terminals D, E and F:
stand - TWY (S1, S2, S3, S4, S5, S6, S7, S8, S9, S10, S11, S12) - MAIN TWY A - TWY A9.
- from De-icing area 1:
stand (82, 82A, 83, 83A, 84) - MAIN TWY A - TWY A9.
- from Aviation Scientific and Technical Center apron:
TWY (N1, N3) - TWY B - TWY B7 - TWY G5.

UUEE/SVO
SHEREMETYEVO

JEPPESEN
10 MAY 24

20-1P3

Eff 16 May

MOSCOW, RUSSIA
AIRPORT BRIEFING

1. GENERAL

- **For RWY 24C:**
 - from aprons of terminals A and B:
stand - TWY N9 - TWY B - TWY B7.
 - from aprons of terminals B and C:
stand - TWY (N1, N3, N5, N6, N7, N8, N9) - TWY B - TWY B7.
 - from aprons of terminals D, E and F:
stand - TWY (S1, S2, S3, S4, S5, S6, S7, S8, S9, S10, S11, S12) -
MAIN TWY A - TWY A9 - TWY G5.
 - from De-icing area 1:
stand (82, 82A, 83, 83A, 84) - MAIN TWY A - TWY A9 - TWY G5.
 - from Aviation Scientific and Technical Center apron:
TWY (N1, N3) - TWY B - TWY B7.
- **For RWY 24R:**
 - from aprons of terminals A, B, C:
stand - TWY (N1, N3, N5, N6, N7, N8, N9) - TWY B - TWY D - TWY E -
TWYE5.
 - from sectors of apron of terminal D:
stand - TWY (S1, S2, S3) - MAIN TWY A - TWY A1 - TWY G1 - TWY B1 -
TWY B - TWY D - TWY E - TWY E5.
 - from aprons of terminals E and F:
stand - TWY (S4, S5, S6, S7, S8, S9, S11, S12) - MAIN TWY A - TWY A1 -
TWY G1 - TWY B1 - TWY B - TWY D - TWY E - TWY E5.
 - from De-icing area 1:
stand (82, 82A, 83, 83A, 84) - MAIN TWY A - TWY A1 - TWY G1 - TWY B1 -
TWY B - TWY D - TWY E - TWY E5.

1.4. TAXI PROCEDURES

1.4.1. GENERAL

It is prohibited to occupy MAIN TWY A and TWY B without permission of GND controller.

Taxiing into hangar area and into/out of Aviation Scientific and Technical Center apron MAX wingspan of 105'/32m. Taxiing of ACFT with more than wingspan of 105'/32m shall be executed by towing.

Taxiing in front of stands 74 thru 81 with MAX wingspan 164'/50m.

Taxiing between stands 66 and 68 (taxi route F4) with MAX wingspan 213'/64.8m.

Simultaneous use of taxi routes T3 and T5 available for ACFT with MAX wingspan 118'/36m.

Simultaneous use of taxi routes T3 and T6 is permitted. T3 is available for ACFT MAX 118'/36m. T6 is available for ACFT with MAX 213'/65m.

Simultaneous use of taxi routes T4 and T6 is permitted. T4 is available for ACFT with MAX wingspan of 118'/36m or 213'/65m. T6 is available for ACFT with MAX wingspan of 118'/36m or 213'/65m.

Simultaneous use of taxi routes C1 and C3 is permitted for ACFT with MAX wingspan 118'/36m.

Simultaneous use of taxi routes C1 and C2, C2 and C3, T3 and T4, T4 and T5 or T5 and T6 is PROHIBITED.

Segment of taxi route L3 from taxi routes A1 to A2 are available for ACFT with MAX wingspan 108'/33m.

Taxi routes C1, C3, J1, J2, J3, L6, L7, P4, T3 and T5 are available for ACFT with MAX wingspan 118'/36m.

Taxi route D5 in vicinity of stand 12 is available for ACFT with wingspan 118'/36m. For ACFT with wingspan of more than 118'/36m up to 213'/65m only by Follow-me car.

Taxi route F3 in vicinity of stands 59 thru 60 is available for ACFT with wingspan 138'/42m.

Taxi route F1 is available for ACFT with wingspan 139'/42.5m.

UUEE/SVO
SHEREMETYEVO

12 DEC 25

JEPPESEN
20-1P4

Eff 25 Dec

MOSCOW, RUSSIA
AIRPORT BRIEFING

1. GENERAL

Taxi route D4 is available for ACFT with MAX wingspan 148'/45m.

Taxi routes A1, C2, C5, D1, D2, D3, D5 in vicinity of stands 15 thru 17, F4, segment of taxi route L1 from TWYs S8 thru S9, L5, L8, T1, T2, T4, T6 and segment of taxi route C7 from stand 190 to 201 are available for ACFT with MAX wingspan of 213'/65m.

Taxi route F3 (except segment in vicinity of stands 59 thru 60) is available for ACFT with wingspan 224'/68.4m.

Taxi routes A2, A3, C8, F2, F5, segment of taxi route L1 from TWY S4 thru S8, L4, segment of taxi route C7 from TWY N3 to stand 201 and segment of taxi route L3 from taxi routes A2 to A3 are available for ACFT with MAX wingspan of 263'/80m.

ACFT with wingspan 118'/36m or less taxiing North under assistance of Follow-me car are permitted to turn from route T3 to routes T5 or T6 and from routes T5 or T6 to route T3 abeam stand 131 in accordance with the appropriate marking.

ACFT with wingspan 213'/65m or less taxiing North under assistance of Follow-me car are permitted to turn from route T4 to route T6 and from route T6 to route T4 abeam stand 128 in accordance with the appropriate marking.

Taxiing of AN-124, B747-8/8F and A380 ACFT via MAIN TWY A (from TWY A9 to TWY S13) strictly along centerline at reduced speed with flight crews increased caution.

Stands 42 thru 45 and 62 thru 66 on apron of Terminal F (when ACFT are parked facing the Terminal) are available for successive start of engines followed by setting engines to idle power by Apron controller's clearance.

Apron segment between stands 2, 2A, 3 and the hangar is available for taxiing.

1.4.2. USE OF STANDARD TAXI ROUTES WITHOUT CLEARANCE TO OCCUPY TWY B

Procedure for use of standard taxi routes without obtaining clearance to occupy TWY B is established for arriving ACFT intended to park on stands of Terminals A, B, C.

Standard taxi route designator includes code number of TWY of entry onto the apron (routes N1, N3, N5, N7, N9, N11). TWYs N1 and N11 are used for entry into/exit from the apron, TWYs N2, N6, N8 are used for exit from the apron.

Procedure is not applied, when LVP are implemented at aerodrome.

After landing on RWY 06C/24C or RWY 06R/24L, arriving ACFT intended to park on stands of Terminals A, B, C shall vacate the RWY via the nearest TWY or the TWY assigned by TWR controller.

TWR controller gives instructions to flight crews of arriving ACFT regarding RWY vacating after landing: "AFL 1701, vacate right (left) TWY (...) standard route (N...)" or "AFL 1701 cross RWY 24C (06C), when vacated standard route (N...)"

ACFT CAT	RWY 24C	RWY 24L	RWY 06C	RWY 06R
	TWY/DIST (m)			
Heavy	B2/2745	G2/2798	B6/2700	G4/2798
Medium	B4/1910	G3/1962	B4/1660	G3/1761
Light				

ACFT vacating RWY 06C/24C has priority over ACFT taxiing via TWY B.

After vacating RWY 06R/24L via TWYs G1-G5 flight crew shall standby for TWR controller's clearance to cross the parallel RWY.

After vacating RWY 06C/24C via TWYs B1, B7 flight crew shall proceed along the standard taxi route assigned earlier, take a right/left via TWY B or cross TWY B towards the assigned TWY of entry onto the apron.

UUEE/SVO
SHEREMETYEVO

JEPPESEN
 12 DEC 25

20-1P5

Eff 25 Dec

MOSCOW, RUSSIA
AIRPORT BRIEFING

1. GENERAL

When taxiing via TWY B flight crew shall:

- maintain a listening watch on GND 1 FREQ (or as instructed by the ATS unit) without initiating contact;
- give way to ACFT vacating RWY 06C/24C, signaling intent to give way by turning off taxi lights;
- proceed via TWY B in accordance with the assigned taxi route.

Flight crew of ACFT approaching the assigned TWY shall establish radio communication with Apron 3 or Apron 4 controller and obtain further taxi instructions. The controller monitors movement of ACFT and informs flight crew, if taxi instructions change or conflicting traffic is expected.

If flight crew is not ready to taxi via standard route, they must immediately inform GND 1 controller.

1.5. PARKING INFORMATION

Apron of terminal A:

- Taxiing to the apron shall be executed under assistance of Follow-me car onto stands 85 and 85A thru 85Z.
- ACFT shall be parked into hangar 2 under tow.
- Taxiing of ACFT from stands 85 and 85A thru 85Z and out of hangar 2 shall be executed by towing to start-up positions.
- ACFT are permitted to taxi into stand AE under assistance of the Follow-me car and self-manoeuvre off the stand.

Terminal D stands 15 thru 33, terminal E stands 34 thru 41, terminal F stands 46 thru 60, terminal B stands 113 thru 131 and terminal C stands 132 thru 150 equipped with visual docking guidance system SAFEDOCK.

Stand 1 is designated for maintenance.

Stands 1A, 82 thru 84, 190 and stands T and V available for commercial servicing and maintenance.

ACFT intended to take off in heading 063° MAG shall vacate stand 1A via TWYS2.

When docking guidance system is inoperative, pilot must stop and inform Apron controller about it. Taxiing shall be carried out by the signals of marshaller.

Enter stands 2 and 3 facing stands 7 thru 9 by towing.

Enter stands 4 thru 6 facing stands 10 and 11 by towing.

Enter stands 1, 1A, 42C, 43C, 44C, 68 thru 70, 73B, 74, 74A, 74B, 75, 76, 76A, 76B, 77, 78, 79, 79A, 79B, 80, 81, 81A, 81B, 86, 87, 88, 88B, 89, 89B and 90 by towing.

Enter stands 86A, 89C, 89D, 162 thru 182, 186A, 187A, 190, 201A, 203A, 205A, 207A, 208A, 209A, 211A, 213A, 215A and 220 by push-back.

Stands 89C and 89D available for helicopters.

Exit stands 1 thru 6, 15 thru 33, 34 thru 41, 46 thru 60, 61 thru 63, 67A, 68 thru 70, 73B, 74 thru 76B, 77, 78, 79, 79A, 79B, 80, 81, 81A, 81B, 82, 86 thru 90A, 98, 98A, 99, 100, 100A, 101, 102, 102A, 103, 113 thru 150, 162 thru 182, 184 thru 189 and 220 by towing.

Exit stands 93 thru 97 and 191 thru 216 by push-back.

Enter/exit stands 200C, 200E, 200F under tow.

Stands 200E, 200F are designated for ACFT maintenance in daylight hours.

Exit stands 201A, 203A, 205A, 207A, 209A, 211A, 213A, 215A by towing to start-up position.

Stands 42 thru 45, 61 thru 66 and 68 thru 70 available for de-icing.

UUEE/SVO
SHEREMETYEVO

JEPPESEN

13 FEB 26

20-1P6

Eff 19 Feb

MOSCOW, RUSSIA
AIRPORT BRIEFING

1. GENERAL

Enter stands 191 thru 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 216, 215, V and T by Follow-me car.

Taxiing onto stands and hangar of hangar 1 apron/terminal B shall be carried out by towing.

Taxiing out of hangar and stands 104 thru 104J shall be executed by towing.

ACFT with wingspan exceeding 102'/31m shall stop at start-up area E1 on apron of terminal B, after that ACFT shall be parked by towing.

Enter stands 82 thru 84 after Follow-me car by instructions of Apron 1 controller.

Exit stands 82, 82A, 83, 83A and 84 only by instruction of TWR (GND) controller.

1.6. COMMUNICATION FAILURE PROCEDURE

In case of communication failure, the pilot can:

- use mobile communication
Flight Control Officer (Moscow TMA Control Center)
Tel: +7 495 956 87 33
+7 495 436 25 36
+7 916 043 35 90
Flight Control Officer (Moscow ACC)
Tel: +7 495 956 87 34
+7 495 436 26 62
+7 916 043 36 16
Flight Control Officer (Sheremetyevo AD)
Tel: +7 495 578 03 71
+7 916 249 15 68
- monitor NDB/MKR frequency for ATC information and instructions.

1.7. RWY OPERATIONS

1.7.1. PARALLEL DEPARTURE AND APPROACH OPERATIONS

Information about parallel departure and approach operations at aerodrome must be included in ATIS broadcast using the following phrase: "Parallel departure and approach operations in progress".

Basic RWY operation modes:

- During segregated parallel operations:
RWY 06L/24R is used for landing, RWY 06C/24C and/or RWY 06R/24L is used for take-off. RWY 06C/24C and/or RWY 06R/24L can also be used for simultaneous approach operations.
- During simultaneous independent parallel departure operations:
RWY 06L/24R is used for take-off, RWY 06C/24C and/or RWY 06R/24L is also used for take-off. RWY 06C/24C and/or RWY 06R/24L, and/or RWY 06L/24R can also be used for simultaneous landing operations.
- During simultaneous dependent parallel approach operations:
RWY 06L/24R is used for landing, RWY 06C/24C and/or RWY 06R/24L is also used for landing. RWY 06C/24C and/or RWY 06R/24L can also be used for simultaneous departure operations.

The established minimum horizontal separation interval can be reduced to a value equal to the distance between parallel RWY centerlines or their extensions over the course of parallel departure and approach operations, unless other conditions are required for employment of a specific procedure.

1.7.2. POTENTIAL AIR TRAFFIC CONFLICT SITUATIONS

Potential air traffic conflict situations, which can occur in case an approach procedure is discontinued:

- between two successive approaching ACFT, including cases, when one of the arriving ACFT (proceeding either first or second) has discontinued approach procedure and initiated missed approach;
- between an ACFT that has taken off and an ACFT executing approach, when both ACFT are airborne, and the arriving ACFT intends to execute landing ("departure - approach" procedure) or discontinues approach procedure and initiates missed approach.

UUEE/SVO
SHEREMETYEVO

JEPPESEN

13 FEB 26

20-1P7

Eff 19 Feb

MOSCOW, RUSSIA
AIRPORT BRIEFING

1. GENERAL

The established minimum horizontal separation interval can be reduced for a short-term period to a value of 1.7NM/3.2km, if the specified above situations occur.

1.7.3. SUCCESSIVE DEPARTURES OF ACFT

The procedure is employed, when successive departures are operated by two ACFT either from one RWY (RWY 06C/24C or RWY 06R/24L) or from parallel RWYs (RWY06C/24C and RWY 06R/24L).

Prior to issuing take-off clearance to the second departing ACFT, ATS unit shall assign initial climb altitude restrictions to flight crew of this ACFT. Flight crew must acknowledge receipt and follow these instructions.

The established minimum horizontal separation interval in MOSCOW (Sheremetyevo) CTR can be reduced for a short-term period to a value of 1.7NM/3.2km over the course of ACFT successive departure operations ("departure - departure" procedure).

1.8. OTHER INFORMATION

Birds in vicinity of APT.

2. ARRIVAL

2.1. COMMUNICATION FAILURE PROCEDURES

2.1.1. GENERAL

Continue the flight maintaining the route and flight profile of the cleared basic RNAV STAR to the maximum extent.

Execute approach-to-land according to the established procedure.

In the event of a missed approach follow paragraph 2.1.1. AFTER MISSED APPROACH.

Set transponder to code 7700, if it is necessary to deviate from the specified procedure.

2.1.2. AFTER MISSED APPROACH

Continue maintaining the route and profile of missed approach procedure to the nearest holding area to the maximum extent.

Enter the holding area at the upper published altitude at IAF, burn out fuel, if necessary.

After taking the decision to land at Moscow/Sheremetyevo:

- Execute approach in accordance with the established procedure.

After taking the decision to proceed to the alternate AD in Moscow TMA:

- Proceed to MR DVORDME climbing to transition altitude 10000'.
- Proceed to IAF via the following waypoints:

Moscow/Domodedovo:

BESTA - RUGEL - GEKLA - IMZUP - KUPVE - NIDBE - IZVOK - IPKED - ZOVGO - ODZAG - GUFUZ - ALBOR (IAF).

Moscow/Vnukovo:

GIGUN - ASLEK - BUPOS - ORSIF - MEZER - NALFI - RAMZA - UKABE - FIDOT - RORUK (IAF)

Ramenskoye:

BESTA - RUGEL - MONIK - RAFDA - NIGLI - NDB RT - BW316 - BW317 - BW318 - BW319 - ODLOR (IAF)

- At IAF enter the published, if available, or standard holding area.
- In the holding area descend from transition altitude 10000' to the upper published approach procedure altitude at IAF.
- Execute approach in accordance with the established procedure.

UUEE/SVO
SHEREMETYEVO

JEPPESEN

13 FEB 26

20-1P8

Eff 19 Feb

MOSCOW, RUSSIA
AIRPORT BRIEFING

2. ARRIVAL

After taking the decision to proceed to the alternate AD outside Moscow TMA:

- Execute approach according to the established procedure to IF.
- Proceed from IF to the initiation point of the basic RNAV SID of the same RWY.
- Maintain the route and flight profile of the basic RNAV SID till leaving Moscow TMA to the maximum extent.
- Continue climbing to the FL specially established for flight without radio communication (FL 140, FL 150, FL 240, FL 250) after leaving Moscow TMA.

After taking the decision to proceed to the destination AD:

- Execute approach in accordance with the established procedure to IF.
- Proceed from IF to the initiation point of the basic RNAV SID of the same RWY.
- Maintain flight route and profile of the basic RNAV SID to the maximum extent until leaving Moscow TMA.
- After leaving Moscow TMA, reach flight level indicated in the flight plan.

2.2. EMERGENCY LANDING PROCEDURE

In cases of emergency, requiring immediate landing, during take-off phase from V1 (decision speed) till reaching 1030' (400'), the pilot-in-command can carry out emergency landing depending on take-off conditions having reported about emergency landing to SHEREMETYEVO Tower as follows:

- At 1030' (400') carry out 180-degree turn (right turn when take-off heading is 243° and left turn when take-off heading is 063°) climbing to 1780' (1150') under VFR or 2110' (1480') under IFR and carry out a flight according to approach chart and land.

Execution of continued take-off

If during take-off the emergency situation arises when V1 speed has been reached, pilot must continue take-off, assess the situation and execute the following:

- approach according to published procedure or by vectoring on operational landing direction;
- missed approach procedure;
- flying to the alternate aerodrome, if unable to land at the departure aerodrome due to meteorological conditions.

Pilot must report his decision and about ACFT position relative to RWY to ATS.

2.3. NOISE ABATEMENT PROCEDURES

Maintain STAR routes, in case of deviation join the assigned track immediately. If special meteorological conditions are present in arrival and approach sectors, the flight crew can deviate from STAR route with mandatory report about it to ATC.

Limitations

Immediately prior to the final approach, avoid excessive rates of descent, change configuration and speed according Airplane Flight Manual. During instrument as well as visual approach, it is not allowed to fly below ILS GS. Noise abatement procedures shall not envisage the increasing of indicated rate of descent. A displacement of THR shall not be used as a noise abatement measure. 'AIR GROUND' communication shall be reduced to absolute minimum.

2.4. CAT II/III OPERATIONS

RWY 24L approved for CAT II operations and RWYs 06L, 06R, 24C and 24R approved for CAT II/III operations, special aircrew and ACFT certification required.

UUEE/SVO
SHEREMETYEVO

JEPPESEN

13 FEB 26

20-1P9

Eff 19 Feb

MOSCOW, RUSSIA
AIRPORT BRIEFING

2. ARRIVAL

2.5. REDUCED RADIO COMMUNICATION

- After receiving the instruction "Contact SHEREMETYEVO Tower" from Radar controller, a pilot shall tune the radio station to the mentioned frequency and call for TWR controller having advised his call sign and selected approach procedure: "SHEREMETYEVO Tower, AFL 1713, ILS 24R".
- TWR controller shall confirm establishing radio communication by a phrase indicating the index of RWY for landing: "AFL 1713, 24R".
- The pilot shall confirm: "24R, AFL 1713".
- If the type of approach, chosen by a pilot and advised to ATS unit, differs from the type of approach broadcasted in ATIS message, then a controller shall indicate it on first contact: "AFL 1713, RNAV 24R approach".
- The pilot shall confirm: "RNAV 24R approach, AFL 1713".

2.6. RWY OPERATIONS

2.6.1. MINIMUM RWY OCCUPANCY TIME

After landing arriving ACFT shall vacate the RWY via the nearest TWY, or the TWY assigned TWR controller.

After vacating the RWY via TWY G1-G5, flight crew shall continue taxiing via TWY, hold short of the parallel RWY at the marked holding position (marking lines of LOC critical area of the parallel RWY) and standby for TWR controller's clearance to cross the parallel RWY.

2.6.2. MINIMUM REDUCED SEPARATION ON THE SAME RWY

Reduced RWY separation minima are applied during flight operations to/from RWY 06C/24C, RWY 06R/24L and RWY 06L/24R only in the day-time, within the time period that starts 30 minutes after sunrise and ends 30 minutes before sunset (LT), provided weather conditions at aerodrome comply with the following criteria:

- VIS 5km or above, ceil 1000' AAL or above;
- Tailwind component shall not exceed 3m/sec;
- Measured friction coefficient is 0.36 or above (estimated braking action is "good" or "good to medium").

Information about application of reduced separation minima is included into ATIS.

ATS unit can issue landing clearance to flight crew of an arriving ACFT, provided there is reasonable assurance, that when this ACFT crosses RWY THR:

- The preceding ACFT has landed and passed the point located at a distance of not less than 8202'/2500m from RWY THR is in motion and will vacate RWY without backtracking;
- The preceding departing ACFT is airborne and has passed the point located at a distance of not less than 8202'/2500m from RWY THR.

Landing clearance issued by the ATS unit to flight crew of an arriving ACFT must contain information on type of the preceding departing ACFT or arriving ACFT that has executed landing.

Flight crew must report having the preceding departing ACFT or arriving ACFT that has executed landing in sight and acknowledge obtaining landing clearance at the request of ATS unit.

Pilot-in-command takes the final decision regarding execution of landing. The obtained landing clearance does not entail an obligation to execute landing.

UUEE/SVO
SHEREMETYEVO

JEPPESEN
12 DEC 25 **20-1P10**

Eff 25 Dec

MOSCOW, RUSSIA
AIRPORT BRIEFING

3. DEPARTURE

3.1. DE-ICING

For de-icing positions refer to 20-9 charts.

During de-icing treatment of ACFT with running engines communication between the flight crew and operator of de-icing car shall be maintained on following frequencies:

- 118.900 - on apron of Terminal C (de-icing areas E10, H1, 4), de-icing areas D, 5;
- 118.500 - on aprons of Terminals A, B (de-icing areas on stands 105A, 107A, de-icing area M1, S);
- 118.400 - on aprons of Terminals D, E, F (de-icing area on TWY S1, de-icing areas W, B2);
- 118.200 - on apron of Terminal F (de-icing areas on TWY S8, de-icing area 2 [stands 73 and 73B]), apron of the Cargo Terminal, de-icing area 1.

The flight crew shall notify the appropriate Apron controller of the necessity of de-icing treatment on initial radio contact.

De-icing treatment of ACFT is executed on:

- Engines start-up positions;
- ACFT stands and temporary parking points;
- De-icing areas for ACFT with running engines.

SAFEDOCK Visual Docking Guidance System LED display is used to provide information on position assigned for de-icing treatment of ACFT with running engines.

Simultaneous taxiing and towing on de-icing area 1 and de-icing area 5 is prohibited.

T1, T2, T3 and T4 are engines start-up and de-icing areas.

V1 and V2 are additional stop points and engine start-up positions.

Apron controller coordinates movement on area designated for de-icing treatment of ACFT with running engines.

ACFT shall taxi into the areas designated for de-icing treatment of ACFT with running engines under assistance of the Follow-me car.

Flight crews shall report the relevant Apron controller, controlling them, that de-icing treatment is completed and they are ready to vacate de-icing area with started engines to perform "After De-icing/Anti-icing Checklist" procedures.

It is prohibited to vacate de-icing area to perform "After De-icing/Anti-icing Checklist" procedure from stands of de-icing area 1, de-icing area 5.

After de-icing treatment of ACFT with running engines in areas H1 on route L5, stands 105A and 107A, M1 on route L3, de-icing area 2 (stands 73 and 73B), de-icing area W (stand 9A), E10 on route C5, de-icing area S on route A2, an operator of de-icing treatment informs pilot about completion of de-icing treatment via radio: "ACFT call sign _ all is clear, route is clear, stand by for clear signal at Left (Right)." Pilot confirms obtained information via radio "ACFT call sign clear signal at Left (Right) , all is clear, route is clear."

In de-icing areas in vicinity of TWYs S1, S2, S8, S12, de-icing areas B2, 1, 4, 5, W (7A), D and stand 67A an operator of de-icing treatment informs via radio after completion of de-icing treatment: "Expect clear signal", drives away to a safe distance and transmits a signal: "ACFT call sign _ all is clear, route is clear." Pilot confirms the obtained information via radio: "ACFT call sign_ route is clear."

De-icing treatment of ACFT in engines start-up areas and on stands shall be carried out when engines are shut down.

UUEE/SVO
SHEREMETYEVO

JEPPESEN
12 DEC 25 **20-1P11**

Eff 25 Dec

MOSCOW, RUSSIA
AIRPORT BRIEFING

3. DEPARTURE

3.2. START-UP, PUSH-BACK AND TAXI PROCEDURES

3.2.1. START-UP

A request for ATC departure clearance shall be made to Delivery or Delivery 2. Information about availability of Delivery 2 will be broadcasted via ATIS.

A pilot shall request departure clearance within 5 to 15 minutes before TOBT.

The request must include call sign, destination APT, ACFT stand number and the code letter of the latest ATIS information.

The received clearance must be acknowledged by the following information:

- RWY designation number for take-off, SID designator, SSR squawk and any other information that differs from the information that shall be at pilot's disposal at that moment.

In case of departure in the South direction, a pilot request to change departure route shall be made 20 minutes before TOBT.

The validity period of the departure clearance is not earlier than 15 minutes before and not later than 30 minutes after getting such permission.

When approaching the TWY designated by the controller, flight crew shall report this to GND controller.

When it is necessary to treat the ACFT with de-icing fluid, it is allowed to request the departure clearance before or during the de-icing treatment.

Clearance for towing and start-up shall be requested on the frequency of apron 1, apron 2, apron 3 or apron 4.

The operation of the ACFT transponder in Mode S on the ground:

- The transponder shall be switched on before towing (start-up);
- The transponder shall be switched off after the termination of parking on the ACFT stand.

The ACFT shall start movement within 10 seconds after getting take-off clearance. If the ACFT movement has not begun after 10 seconds, take-off can be prohibited by TWR controller instructing the flight crew to vacate the RWY via the nearest TWY.

When medium and light ACFT take off from TWYs B2, G2, B6, G4, A2 or A8 following a heavy ACFT, a separation minimum of 2 minutes or more is applied in view of wake turbulence; when ACFT take off from TWYs B4, G3 or A5 a separation minimum of 3 minutes or more is applied. If flight crew determines that separation interval needs to be increased, they shall inform TWR controller.

3.2.2. TAXI PROCEDURES

ACFT taxiing on the aprons intending to exit the apron must stop in front of the appropriate TWY and, by the instruction of Apron controller, switch over to communication with Ground controller, report ACFT call sign and position, and obtain clearance to taxi to the RWY holding position and taxi instructions.

The pilot shall request clearance for towing to the position of ACFT treatment with de-icing fluid and engines start-up when the ACFT is completely ready for towing. When submitting the request, the pilot shall advise ACFT position (stand number) and receipt of the latest ATIS information.

For ACFT parked on Terminal D apron clearance for start-up and taxiing is issued by Apron 2 controller.

When the RWY is available only for take-off, TWR controller can issue conditional clearance which is the instruction to the flight crew for self-dependent line-up from the RWY beginning after the preceding ACFT which has started the take-off run.

For example:

"AFL1234, Tower, 24L line-up in sequence". After the start of the take-off run by a preceding ACFT, a pilot shall taxi to line-up position and wait for further instructions.

UUEE/SVO
SHEREMETYEVO

JEPPESEN
26 SEP 25

20-1P12

Eff 2 Oct

MOSCOW, RUSSIA
AIRPORT BRIEFING

3. DEPARTURE

3.2.3. TAXI ROUTES FROM TERMINALS A, B AND C

Assigned by ATC follow TWYs N1, N2, N3, N5, N6, N7, N8, N9 and N11 via TWYB:

- Route B1 - to holding position on TWY B1;
- Route B2 - to holding position on TWY B2;
- Route B4 - to holding position on TWY B4;
- Route B6 - to holding position on TWY B6;
- Route B7 - to holding position on TWY B7;

3.2.4. TAXI ROUTES FROM TERMINALS D, E AND F

Assigned by ATC follow TWYs S1, S2, S3, S4, S5, S6, S7, S8, S9, S10, S11, S12 and stands on de-icing area 1 via MAIN TWY A:

- Route A1 - to holding position on TWY A1;
- Route A2 - to holding position on TWY A2;
- Route A5 - to holding position on TWY A5;
- Route A8 - to holding position on TWY A8;
- Route S13 - to holding position on TWY S13;
- Route A9 - to holding position on TWY A9;
- Route CAT II - to holding position on MAIN TWY A indicated by "24 CAT II" sign;
- Route CAT IIIA - to holding position on MAIN TWY A indicated by "06 CAT III" sign.

3.3. NOISE ABATEMENT PROCEDURES

TAKE-OFF AND CLIMBING PHASE

Noise abatement procedures shall not be executed in case of engine failure during take-off.

Restrictions

Changing of flight direction after take-off is permitted only after reaching 1030' and passing back course MKR, then strictly maintain the published procedures.

Turns from 1030' to 1600' (excluding) shall be executed with a bank angle not exceeding 15°, from 1600' to 3600' (excluding) with a bank angle of not more than 20°, and from 3600' with a bank angle of not more than 25° or with rate of turn 3°/sec.

Noise Abatement Procedures

NADP1 is applied.

3.4. COMMUNICATION FAILURE PROCEDURES

3.4.1. AFTER TAKE-OFF

Maintain the route and profile of the cleared RNAV SID to the maximum extent.

After taking the decision to return to the departure AD:

- Proceed to SID termination fix, and then to the nearest origination point of the shortest basic RNAV STAR of the departure aerodrome.
- Maintain the route and flight profile of the basic RNAV STAR to the maximum extent.
- Execute approach-to-land according to the established procedure.
- In case of missed approach continue the flight maintaining the route and profile of missed approach procedure to the nearest holding area to the maximum extent.
- Follow paragraph 2.1.2. AFTER MISSED APPROACH.

After taking the decision to proceed to the destination AD:

- Continue climbing to the flight level indicated in flight plan after leaving Moscow TMA.

The flight crew must set transponder to code 7700, if it is necessary to deviate from the specified procedure.

UUEE/SVO
SHEREMETYEVO

JEPPESEN

26 SEP 25

20-1P13

Eff 2 Oct

MOSCOW, RUSSIA
AIRPORT BRIEFING

3. DEPARTURE

3.5. RWY OPERATIONS

3.5.1. MINIMUM RWY OCCUPANCY TIME

In all cases while taxiing along MAIN TWY A, pilot must be ready to stop before CAT II/III marking and to obtain further instructions and permissions from TWR controller.

When making decisions, TWR controller is based on the fact that the flight crew of the ACFT, which is at the RWY holding position, is ready for departure without delay. The flight crew must advise if additional time for preparation is required.

The flight crew shall provide take-off without stop on line-up position not later than 30 seconds after receiving ATC clearance at the RWY holding position.

The execution of take-off immediately after lining up can be required on the basis of the air and ground situation. In this case, TWR controller can give the instruction to line up and be ready for the immediate take-off.

If unable to follow this instruction, the flight crew shall report it to TWR controller.

The instruction to line up and take off shall be carried out by the flight crew without delay.

Take-off from RWYs 06C, 06R, 24L, 24C shall be carried out as follows:

- from intersection with TWY G2, B2 - for RWY 06C;
- from intersection with TWY G2, A2 - for RWY 06R;
- from intersection with TWY G4, A8 - for RWY 24L;
- from intersection with TWY G4, B6 - for RWY 24C.

When full RWY distances are required, the flight crew shall advise this to Delivery controller after obtaining departure clearance.

The checks, which must be carried out during the stay on the RWY, must be reduced to a minimum.

After ACFT occupation of the RWY, the flight crew shall provide commencement of ACFT movement for take-off within 10 seconds after obtaining clearance.

After confirmation of the take-off clearance by the flight crew, TWR controller anticipates that the ACFT will commence movement within 10 seconds.

3.5.2. MINIMUM REDUCED SEPARATION ON THE SAME RWY

Reduced RWY separation minima are applied during flight operations to/from RWY 06C/24C, RWY 06R/24L and RWY 06L/24R only in the day-time, within the time period that starts 30 minutes after sunrise and ends 30 minutes before sunset (LT), provided weather conditions at aerodrome comply with the following criteria:

- VIS 5km or above, ceil 1000' AAL or above;
- Tailwind component shall not exceed 3m/sec;
- Measured friction coefficient is 0.36 or above (estimated braking action is "good" or "good to medium").

Information about application of reduced separation minima is included into ATIS.

ATS unit can issue take-off clearance to flight crew of a departing ACFT, provided there is reasonable assurance, that when flight crew starts accelerating this ACFT on the RWY from the line-up position, the preceding departing ACFT is airborne and has already passed the point located at distance of not less than 8202'/2500m from the succeeding departing ACFT.

Take-off clearance issued by the ATS unit to flight crew of a succeeding departing ACFT must contain information on type of the preceding departing ACFT. ATS unit may instruct flight crew to comply with altitude restrictions on initial climb.

Flight crew must report having the preceding departing ACFT in sight and acknowledge obtaining take-off clearance at the request of ATS unit.

Pilot-in-command takes the final decision regarding execution of take-off. The obtained take-off clearance does not entail an obligation for the flight crew to execute take-off.

UUEE/SVO
SHEREMETYEVO

14 MAR 25

JEPPESEN

20-1R

Eff 20 Mar

MOSCOW, RUSSIA

RADAR MINIMUM ALTITUDES

SHEREMETYEVO Radar (TWR)

118.1 120.675

122.7 126.6

135.175

Apt Elev

630

Alt Set: hPa (MM on request)

Trans level: FL110

FL120 when QNH is less than 1013 hPa (760 mm)


FL130 when QNH is less than 977 hPa (733 mm)

Trans alt: 10000 QNH (QFE on request)

1. This chart may only be used for cross-checking of altitudes while under RADAR control.


2. When vectoring is carried out under low-temperature conditions, minimum altitudes must be corrected by altimeter temperature correction.

FEET	METERS	FEET	METERS
QNH	QNH	QNH	QFE
10000	3050	3300	(815)
		3000	(725)
		2800	(665)
		2400	(540)



CHANGES: Sectors revised.

© JEPPESEN, 2021, 2025. ALL RIGHTS RESERVED.




UUUU/SVO
SHEREMETYEVO

CHANGES: DIMGI 3W established.

© JEPPESEN, 2020, 2024. ALL RIGHTS RESERVED.





UUUE/SVO
SHERMETYEVO

5 APR 24 (20-2B)

JEPPESSEN MOSCOW, RUSSIA
RNAV STAR



UUEE/SVO
SHEREMETYEVO

 **JEPPESSEN** MOSCOW, RUSSIA

5 APR 24 (20-2D)


RNAV STAR

UUEE/SVO
SHEREMETYEVO

 **JEPPESSEN** MOSCOW, RUSSIA

5 APR 24 (20-2E)


RNAV STAR



UJEE/SVO
SHEREMETYEVO



UUEE/SVO
SHEREMETYEVO



CHANGES: Track update.

UUEE/SVO
SHEREMETYEVO

FEET	METERS
QNH	(QFE)
4000	(1035)
6000	(1645)
8000	(2250)
10000	(2860)

RILPO
NOT TO SCALE

ARP

3900 **1** Computed for surface air temperature at ARP -31°C

Age Group	Percentage
18-24	54%
25-34	48%
35-44	42%
45-54	36%
55-64	30%
65-74	24%
75-84	18%
85+	1%

SHERMETEVO Delivery 120.875	ans alt: 10000 QNH (QF NAV 1 DME/DME or GNS
--	---

FEET	METERS
QNH	(QFE)
4000	(1035)
6000	(1645)
8000	(2250)
10000	(2860)

RILPO
NOT TO SCALE

EE810
MAX 250 KT

3900 **1** Computed for surface air temperature at ARP -31°C

Age Group	Percentage
18-24	54%
25-34	48%
35-44	42%
45-54	36%
55-64	30%
65-74	24%
75-84	18%
85+	1%

**RILPO 3F [RILP3F]
RNAV DEPARTURE
(RWYS 06C/R)
BY ATC**

LOST COMMS ▼ LOST COMMS
Refer to 20-1P Pages.
LOST COMMS ▼ LOST COMMS

Initial climb clearance 4000

Close-in Obstacles

Max elevation 710 - between 0.4 NM and 1.0 NM from DER, located to the LEFT of take-off heading RWY 06C

Max elevation 689 - between 0.3 NM and 0.5 NM from DER, located to the R of take-off heading RWY 06R.

This SID requires a minimum climb gradient of 3.9% up to 4000, due to airspace structure.


Gnd speed-KT	75	100	150	200	250	300
3.9% V/V (fpm)	296	395	592	790	987	1185

If unable to comply advise SHERMETYEVO Delivery.

3900 1

① Computed for surface air temperature at ARP -31°C

CHANGES: Track update.



UUEE/SVO

SHERMETYEVO

31

23

23

34

39-00

38-30

37-30

56-30

55-30

54-30

53-30

52-30

51-30

50-30

49-30

48-30

47-30

46-30

45-30

44-30

43-30

42-30

41-30

40-30

39-30

38-30

37-30

36-30

35-30

34-30

33-30

32-30

31-30

30-30

29-30

28-30

27-30

26-30

25-30

24-30

23-30

22-30

21-30

20-30

19-30

18-30

17-30

16-30

15-30

14-30

13-30

12-30

11-30

10-30

9-30

8-30

7-30

6-30

5-30

4-30

3-30

2-30

1-30

0-30

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00

34-00

33-00

32-00

31-00

30-00

29-00

28-00

27-00

26-00

25-00

24-00

23-00

22-00

21-00

20-00

19-00

18-00

17-00

16-00

15-00

14-00

13-00

12-00

11-00

10-00

9-00

8-00

7-00

6-00

5-00

4-00

3-00

2-00

1-00

0-00

39-00

38-00

37-00

36-00

35-00


34-00

33-00

32-00


31-00</


SHEREMETYEVO Delivery	Apt Elev 630
120.875	
Trans alt: 10000 QNH (QFE on request)	
RNAV 1 DME/DME or GNSS required	
RILPO 3H [RILP3H] RNAV DEPARTURE (RWYS 24C/L)	




Gnd speed-KT	75	100	150	200	250	300
6.5% V/V (fpm)	494	658	987	1316	1646	1975

If unable to comply advise **SHERMETEVO** Delivery.

















16 FEB 24 (20-3L) Eff 22 Feb

UUEE / SVO
SHEREMETYEVO


MOSCOW, RUSSIA
RNAV SID

FEET	METERS
QNH (QFE)	
1100 (160)	
3000 (735)	
4000 (1040)	
6000 (1650)	
7000 (1955)	
10000 (2870)	

SHERMETYEVO Delivery	Apt Elev
120.875	630

Trans alt: 10000 QNH (QFE on request)
RNAV 1 DME/DME or GNSS required
Turn before DER is prohibited.

KOGOM 3K [KOG03K]
OLMUN 3K [OLMU3K]
RNAV DEPARTURES
(RWY 24R)



NOT TO SCALE

Initial climb clearance 4000

Close-in Obstacles

Max elevation 688 - between 0.2 NM and 0.5 NM

from DER, located to the LEFT and to the RIGHT

of take-off heading RWY 24R

These SIDs require minimum climb gradients

of

4.5% up to 1300, due to obstacles and

5.7% up to 3700, due to airspace structure.


Grd speed-KT


75 100 150 200 250 300

4.5% V/V (fpm) 342 456 684 911 1139 1367

5.7% V/V (fpm) 433 577 866 1154 1443 1732

If unable to comply advise SHERMETYEVO Delivery.








UUE/SVO
SHEREMETYEVO


JEPPESEN


16 FEB 24 **20-3Q** **Eff 22 Feb**

MOSCOW, RUSSIA
RNAV SID














Trans alt: 10000 QNH (QFE on request)
RNAV 1 DME/DME or GNSS required
Turn before DER is PROHIBITED.

LIDRI 3J [LIDR3J]
TOKNU 3J [TOKN3J]
RNAV DEPARTURES
(RWYS 24C/24L)
BY ATC

FEET	METERS
QNH (QFE)	
1200 (180)	
5000 (1335)	
7000 (1945)	
8000 (2230)	
10000 (2860)	

LOST COMMS
Refer to 20-1P Pages.
LOST COMMS


① Computed for surface
air temperature at
ARP -31°C.


Initial climb clearance 4000

These SIDs require minimum climb gradients
of
4.1% up to 1200 due to obstacles,
5.5% up to 5000 due to airspace structure.

Gnd speed-KT	75	100	150	200	250	300
4.1% V/V (fpm)	311	415	623	830	1038	1246
5.5% V/V (fpm)	418	557	835	1114	1392	1671

If unable to comply, advise SHEREMETYEVO Delivery.





UUEE/SVO
SHEREMETYEVO

 **JEPPESSEN**
13 FEB 26 **20-3X3** **Eff 19 Feb**

MOSCOW, RUSSIA
DEPARTURE

Apt Elev 630	Trans alt: 10000 QNH (QFE on request)
------------------------	--

FLIGHT ROUTES BETWEEN AERODROMES WITHIN MOSCOW TMA


1. Departure instructions provide ACFT vectoring to the significant point on the route (the first waypoint in the flight plan);
2. Flights within CTRs shall be carried out via waypoints, separated by letters DCT in the flight plan, to IAF of the destination aerodrome (in accordance with the information published for appropriate departure aerodrome);
3. Approach shall be executed from IAF of the destination aerodrome:
 - Moscow/Sheremetyevo - KEZVU (IAF)
 - Moscow/Domodedovo - ALBOR (IAF)
 - Moscow/Vnukovo - RORUK (IAF)
 - Ramenskoye - ODLOR (IAF).

Departure To	ROUTING
Moscow/ Domodedovo	BESTA - RUGEL - GEKLA - IMZUP - KUPVE - NIDBE - IZVOK - IPKED - ZOVGO - ODZAG - GUFUZ - ALBOR (IAF).
Moscow/ Vnukovo	GIGUN - ASLEK - BUPOS - ORSIF - MEZER - NALFI - RAMZA - UKABE - FIDOT - RORUK (IAF).
Ramenskoye	BESTA - RUGEL - MONIK - RAFDA - NIGLI - RT NDB - BW316 - BW317 - BW318 - BW319 - ODLOR (IAF).

**FUEL CALCULATION ROUTES
BETWEEN AERODROMES WITHIN MOSCOW TMA**

Routes are designated for fuel calculation only and not to be used for navigation.

Departure To	ROUTING
Moscow/ Domodedovo	BESTA - RUGEL - GEKLA - IMZUP - KUPVE - PEFOS - DD362 - ALBOR (IAF).
Moscow/ Vnukovo	GIGUN - ASLEK - BUPOS - ORSIF - MEZER - FIDOT - RORUK (IAF).
Ramenskoye	BESTA - RUGEL - MONIK - RAFDA - NIGLI - BW138 - BW316 - BW319 - ODLOR (IAF).




© JEPPESEN, 2001, 2025. ALL RIGHTS RESERVED.

UUUE/SVO



MOSCOW , RUSSIA
SHEREMETYEVO

INS COORDINATES	
STAND No.	COORDINATES
162, 162A	N55 58.7 E037 24.3
163, 163A	N55 58.6 E037 24.2
163B	N55 58.6 E037 24.3
164, 164A	N55 58.6 E037 24.2
165, 166	N55 58.7 E037 24.3
167, 168	N55 58.7 E037 24.2
169 thru 171	N55 58.7 E037 24.1
172, 173	N55 58.7 E037 24.0
174, 175	N55 58.7 E037 23.9
176	N55 58.6 E037 23.9
177, 177A	N55 58.6 E037 24.1
177B	N55 58.6 E037 24.2
178, 178A	N55 58.6 E037 24.1
179 thru 180A	N55 58.6 E037 24.0
181 thru 182	N55 58.6 E037 23.9
184	N55 58.6 E037 24.3
185 thru 187A	N55 58.6 E037 24.2
188, 189	N55 58.6 E037 24.1
190	N55 58.6 E037 23.8
191	N55 58.5 E037 23.8
192, 193	N55 58.5 E037 23.7
194, 195	N55 58.5 E037 23.6
196	N55 58.5 E037 23.5
197, 198	N55 58.5 E037 23.4
199 thru 200F	N55 58.5 E037 23.3
201 thru 203	N55 58.5 E037 23.8
203A thru 205	N55 58.5 E037 23.7
205A	N55 58.4 E037 23.7
206, 207	N55 58.5 E037 23.6
207A	N55 58.4 E037 23.6
208	N55 58.5 E037 23.6
209	N55 58.4 E037 23.6
209A thru 211A	N55 58.4 E037 23.6
212 thru 215	N55 58.4 E037 23.5
215A, 216	N55 58.4 E037 23.3
217, 217A	N55 58.4 E037 23.2
218 thru 219	N55 58.4 E037 23.1
220	N55 58.4 E037 23.0



CHANGES: De-icing areas, guidance lines.



MOSCOW, RUSSIA
SHEREMETYEVO


27 JUN 25 20-9C Eff 10 Jul

UUUU/SVO

LEGEND

Start-up point & De-icing area

NOT TO SCALE




INS COORDINATES				INS COORDINATES			
STAND No.	COORDINATES	STAND No.	COORDINATES	STAND No.	COORDINATES	STAND No.	COORDINATES
86, 86A	N55 58.9 E037 26.3	104A, 104B	N55 58.9 E037 25.4	112W	N55 58.9 E037 25.2	C01E	N55 58.6 E037 24.5
87 thru 88B	N55 58.9 E037 26.2	104C thru 104J	N55 58.9 E037 25.5	113	N55 58.9 E037 25.1	C01W thru C02W	N55 58.6 E037 24.4
89 thru 89D	N55 58.9 E037 26.1	105A	N55 58.7 E037 25.3	113A thru 117A	N55 58.8 E037 25.1	C03E	N55 58.7 E037 24.4
90, 90A	N55 58.9 E037 26.0	105E	N55 58.7 E037 25.4	118 thru 122	N55 58.7 E037 25.0	C03W	N55 58.6 E037 24.4
93	N55 59.0 E037 25.9	105W thru 106W	N55 58.7 E037 25.3	123 thru 126A	N55 58.7 E037 25.0		
93A thru 93C	N55 58.9 E037 25.9	107A thru 108W	N55 58.8 E037 25.3	127 thru 130A	N55 58.8 E037 25.0		
94 thru 94B	N55 58.9 E037 25.8	109A	N55 58.8 E037 25.2	131	N55 58.8 E037 24.9		
94C	N55 58.9 E037 25.9	109E	N55 58.8 E037 25.3	132 thru 134A	N55 58.8 E037 24.7		
95 thru 95C	N55 58.9 E037 25.8	109W	N55 58.8 E037 25.2	135 thru 136A	N55 58.7 E037 24.7		
96 thru 96C	N55 58.9 E037 25.7	110E	N55 58.8 E037 25.3	137 thru 139	N55 58.7 E037 24.8		
97 thru 97C	N55 58.9 E037 25.6	110W	N55 58.8 E037 25.2	139A	N55 58.6 E037 24.8		
98 thru 99	N55 58.8 E037 25.9	111A	N55 58.9 E037 25.2	140 thru 142A	N55 58.6 E037 24.7		
100 thru 101	N55 58.8 E037 25.8	111E	N55 58.9 E037 25.3	143, 144	N55 58.6 E037 24.6		
102 thru 103	N55 58.8 E037 25.7	111W	N55 58.9 E037 25.2	145 thru 148	N55 58.7 E037 24.6		
104	N55 58.9 E037 25.5	112E	N55 58.9 E037 25.3	149 thru 150	N55 58.8 E037 24.6		

UUEE/SVO

JEPPESEN
13 FEB 26 20-9D Eff 19 Feb

MOSCOW, RUSSIA
SHEREMETYEVO



UUEE/SVO

JEPPesen


MOSCOW, RUSSIA

13 FEB 26

20-9E

Eff 19 Feb

SHEREMETYEVO



UUEE/SVO

JEPPESSEN
27 AUG 21 **20-9S** Eff 9 Sep

EASA AIR OPS
MOSCOW, RUSSIA
SHEREMETYEVO

STRAIGHT-IN RWY		A	B	C	D
06L	CAT 3A ILS	RA50' R200m	RA50' R200m	RA50' R200m	RA50' R200m
	CAT 2 ILS	700' (100') RA102' R300m	700' (100') RA102' R300m	700' (100') RA102' R300m	700' (100') RA102' ① R300m
	ILS FULL TDZ or CL out ALS out	800' (200') R550m ② R550m R1200m	800' (200') R550m ② R550m R1200m	800' (200') R550m ② R550m R1200m	800' (200') R550m ② R550m R1200m
	GLS TDZ or CL out ALS out	800' (200') R550m ② R550m R1200m	800' (200') R550m ② R550m R1200m	800' (200') R550m ② R550m R1200m	800' (200') R550m ② R550m R1200m
	③ LOC	1320' (720') R1500m	1320' (720') R1500m	1320' (720') R2400m	1320' (720') R2400m
	RNP LNAV/VNAV ALS out	1000' (400') R1100m R1500m	1010' (410') R1200m R1500m	1030' (430') R1300m R2000m	1050' (450') R1400m R2100m
	③ RNP LNAV ALS out	1060' (460') R1400m R1500m	1060' (460') R1400m R1500m	1060' (460') R1400m R2100m	1060' (460') R1400m R2100m
	③ VOR with D3.3	1280' (680') R1500m	1280' (680') R1500m	1280' (680') R2400m	1280' (680') R2400m
	③ VOR w/o D3.3	1320' (720') R1500m	1320' (720') R1500m	1320' (720') R2400m	1320' (720') R2400m
	③ NDB with D2.3 ALS out	1130' (530') R1500m R1500m	1130' (530') R1500m R1500m	1130' (530') R1700m R2400m	1130' (530') R1700m R2400m
	③ NDB w/o D2.3	1320' (720') R1500m	1320' (720') R1500m	1320' (720') R2400m	1320' (720') R2400m
06C	ILS FULL ALS out	820' (200') ② R550m R1200m	820' (200') ② R550m R1200m	820' (200') ② R550m R1200m	820' (200') ② R550m R1200m
	GLS ALS out	820' (200') ② R550m R1200m	820' (200') ② R550m R1200m	820' (200') ② R550m R1200m	820' (200') ② R550m R1200m
	③ LOC ALS out	1190' (570') R1500m R1500m	1190' (570') R1500m R1500m	1190' (570') R1900m R2400m	1190' (570') R1900m R2400m
	RNP LNAV/VNAV ALS out	880' (260') R750m R1300m	890' (270') R750m R1300m	900' (280') R750m R1300m	930' (310') R750m R1400m
	③ RNP LNAV ALS out	1140' (520') R1500m R1500m	1140' (520') R1500m R1500m	1140' (520') R1600m R2400m	1140' (520') R1600m R2400m
	③ NDB ALS out	1170' (550') R1500m R1500m	1170' (550') R1500m R1500m	1170' (550') R1800m R2400m	1170' (550') R1800m R2400m

① without autoland: R350m.

② RVR 750m when a Flight Director or Autopilot or HUD to DA is not used.

③ Continuous Descent Final Approach.

UUEE/SVO
 **JEPPesen**
27 AUG 21 **20-9S1** **Eff 9 Sep**
EASA AIR OPS
MOSCOW, RUSSIA
SHEREMETYEVO

STRAIGHT-IN RWY		A	B	C	D
06R	CAT 3A ILS	RA50' R200m	RA50' R200m	RA50' R200m	RA50' R200m
	CAT 2 ILS	719' (100') RA106' R300m	719' (100') RA106' R300m	719' (100') RA106' R300m	719' (100') RA106' ①R300m
	ILS FULL TDZ or CL out ALS out	819' (200') R550m ②R550m R1200m	819' (200') R550m ②R550m R1200m	819' (200') R550m ②R550m R1200m	819' (200') R550m ②R550m R1200m
	GLS TDZ or CL out ALS out	819' (200') R550m ②R550m R1200m	819' (200') R550m ②R550m R1200m	819' (200') R550m ②R550m R1200m	819' (200') R550m ②R550m R1200m
	③ LOC ALS out	1140' (521') R1500m R1500m	1140' (521') R1500m R1500m	1140' (521') R1700m R2400m	1140' (521') R1700m R2400m
	RNP LNAV/VNAV ALS out	989' (370') R1000m R1500m	999' (380') R1000m R1500m	1009' (390') R1100m R1800m	1009' (390') R1100m R1800m
	③ RNP LNAV ALS out	1140' (521') R1500m R1500m	1140' (521') R1500m R1500m	1140' (521') R1700m R2400m	1140' (521') R1700m R2400m
	③ NDB ALS out	1170' (551') R1500m R1500m	1170' (551') R1500m R1500m	1170' (551') R1800m R2400m	1170' (551') R1800m R2400m
24L	CAT 2 ILS	721' (100') RA98' R300m	721' (100') RA98' R300m	721' (100') RA98' R300m	721' (100') RA98' ①R300m
	ILS FULL TDZ or CL out ALS out	821' (200') R550m ②R550m R1200m	821' (200') R550m ②R550m R1200m	821' (200') R550m ②R550m R1200m	821' (200') R550m ②R550m R1200m
	GLS TDZ or CL out ALS out	821' (200') R550m ②R550m R1200m	821' (200') R550m ②R550m R1200m	821' (200') R550m ②R550m R1200m	821' (200') R550m ②R550m R1200m
	③ LOC ALS out	970' (349') R900m R1500m	970' (349') R900m R1500m	970' (349') R900m R1600m	970' (349') R900m R1600m
	RNP LNAV/VNAV ALS out	951' (330') R800m R1500m	961' (340') R800m R1500m	981' (360') R900m R1600m	1001' (380') R1000m R1700m
	③ RNP LNAV ALS out	1060' (439') R1300m R1500m	1060' (439') R1300m R1500m	1060' (439') R1300m R2000m	1060' (439') R1300m R2000m
	③ NDB ALS out	1100' (479') R1500m R1500m	1100' (479') R1500m R1500m	1100' (479') R1500m R2200m	1100' (479') R1500m R2200m

① without autoland: R350m.

② RVR 750m when a Flight Director or Autopilot or HUD to DA is not used.

③ Continuous Descent Final Approach.

UUEE/SVO

JEPPesen
27 AUG 21 **20-9S2** Eff 9 Sep

EASA AIR OPS
MOSCOW, RUSSIA
SHEREMETYEVO

STRAIGHT-IN RWY	A	B	C	D
24C				
CAT 3A ILS	RA50' R200m	RA50' R200m	RA50' R200m	RA50' R200m
CAT 2 ILS	722' (100') RA100' R300m	722' (100') RA100' R300m	722' (100') RA100' R300m	722' (100') RA100' ①R300m
ILS FULL TDZ or CL out ALS out	822' (200') R550m ②R550m R1200m	822' (200') R550m ②R550m R1200m	822' (200') R550m ②R550m R1200m	822' (200') R550m ②R550m R1200m
GLS TDZ or CL out ALS out	822' (200') R550m ②R550m R1200m	822' (200') R550m ②R550m R1200m	822' (200') R550m ②R550m R1200m	822' (200') R550m ②R550m R1200m
③LOC ALS out	970' (348') R900m R1500m	970' (348') R900m R1500m	970' (348') R900m R1600m	970' (348') R900m R1600m
RNP LNAV/VNAV ALS out	892' (270') ④ R750m R1300m	902' (280') ④ R750m R1300m	912' (290') ⑤ R750m R1400m	1002' (380') R1000m R1700m
③ RNP LNAV ALS out	1060' (438') R1300m R1500m	1060' (438') R1300m R1500m	1060' (438') R1300m R2000m	1060' (438') R1300m R2000m
③NDB ALS out	1140' (518') R1500m R1500m	1140' (518') R1500m R1500m	1140' (518') R1600m R2400m	1140' (518') R1600m R2400m
24R				
CAT 3A ILS	RA50' R200m	RA50' R200m	RA50' R200m	RA50' R200m
CAT 2 ILS	689' (100') RA102' R300m	689' (100') RA102' R300m	689' (100') RA102' R300m	689' (100') RA102' ①R300m
ILS FULL TDZ or CL out ALS out	789' (200') R550m ②R550m R1200m	789' (200') R550m ②R550m R1200m	789' (200') R550m ②R550m R1200m	789' (200') R550m ②R550m R1200m
GLS TDZ or CL out ALS out	789' (200') R550m ②R550m R1200m	789' (200') R550m ②R550m R1200m	789' (200') R550m ②R550m R1200m	789' (200') R550m ②R550m R1200m
③LOC ALS out	1150' (561') R1500m R1500m	1150' (561') R1500m R1500m	1150' (561') R1900m R2400m	1150' (561') R1900m R2400m
RNP LNAV/VNAV ALS out	969' (380') R1000m R1500m	989' (400') R1100m R1500m	999' (410') R1200m R1900m	1009' (420') R1200m R1900m
③RNP LNAV ALS out	1060' (471') R1500m R1500m	1060' (471') R1500m R1500m	1060' (471') R1500m R2200m	1060' (471') R1500m R2200m
③VOR with D3.6 ALS out	1080' (491') R1500m R1500m	1080' (491') R1500m R1500m	1080' (491') R1500m R2300m	1080' (491') R1500m R2300m
③VOR w/o D3.6 ALS out	1150' (561') R1500m R1500m	1150' (561') R1500m R1500m	1150' (561') R1900m R2400m	1150' (561') R1900m R2400m

① without autoland: R350m. ② RVR 750m when a Flight Director or Autopilot or HUD to DA is not used. ③ Continuous Descent Final Approach. ④ With TDZ & CL & HUD: RVR 600m. ⑤ With TDZ & CL & HUD: RVR 650m.

UUEE/SVO

JEPPESEN

27 AUG 21

20-9S3

Eff 9 Sep

Standard

MOSCOW, RUSSIA

SHEREMETYEVO

STRAIGHT-IN RWY		A	B	C	D
24R cont'd	③ NDB	1150' (561')	1150' (561')	1150' (561')	1150' (561')
		R1500m	R1500m	R1900m	R1900m
	ALS out	R1500m	R1500m	R2400m	R2400m

③ Continuous Descent Final Approach.



TAKE-OFF								
HIRL & CL (spacing 15m or less) & relevant RVR	RL & CL & relevant RVR	RL & CL	RL & RCLM	RL or CL	RL or RCLM	RL or CL	Adequate Vis Ref	
			DAY	NIGHT	DAY	NIGHT	DAY	NIGHT
TDZ R125m Mid R125m Rollout R125m	TDZ R150m Mid R150m Rollout R150m	R200m	R300m		R/V400m		R/V500m	NA

UUEE/SVO
SHEREMETYEVO

JEPPESSEN
20 DEC 24
Eff 26 Dec
21-1A

MOSCOW, RUSSIA
CAT II/III ILS Rwy 06L

BRIEFING STRIP	ATIS		SHEREMETEVO Radar (TWR)					SHEREMETEVO Tower	Ground 3
	122.075	(Russian) 120.375	118.1	120.675	122.7	126.6	135.175	118.7	122.9
	LOC IMA 108.75	Final Apch Crs 063°	EE612 MANDATORY 3000' (2400')	CAT IIIA ILS Refer to Minimums	CAT II ILS RA 102' DA(H) 700' (100')	Apt Elev 630' Rwy 600'		3900 MSA ARP ①	
	MISSED APCH: Climb STRAIGHT AHEAD to 1200' or above (MAX 210 KT), then turn LEFT to EE018 (MAX 210 KT) on 023° climbing to 3000', then turn LEFT to KEZVU (MANDATORY 220 KT), then according to chart or as directed.								
20	Alt Set: hPa (MM on req)		Rwy Elev: 22 hPa		Trans level: FL110 ②		Trans alt: 10000'		
	RNAV 1 for initial, intermediate and missed approach.		1. Special Aircrew & Acft Certification Required. 2. GNSS or DME/DME required. 3. ILS DME reads zero at rwy 06L threshold.						



Gnd speed-Kts	70	90	100	120	140	160
GS 3.00°	372	478	531	637	743	849

HIALS-II
PAPI

MIN
1200'
↑

210 KT
MAX

EEØ18 on **023°**

LT ↙


STRAIGHT-IN LANDING	
CAT IIIA ILS	CAT II ILS RA 102' DA(H) 700' (100')
R175m	I R300m
I CAT D without autoland: R350m.	

UUEE/SVO
SHEREMETYEVO


JEPPESEN
20 DEC 24 (21-2) Eff 26 Dec

MOSCOW, RUSSIA
LOC Rwy 06L

ATIS		SHEREMETYEVO Radar (TWR)					SHEREMETYEVO Tower	Ground 3
122.075 (Russian 120.375)		118.1	120.675	122.7	126.6	135.175	118.7	122.9
LOC IMA 108.75	Final Apch Crs 063°	EE612 MANDATORY 3000' (2400')	DA/MDA(H) 1320' (720')	Apt Elev 630' Rwy 600'		3900 MSA ARP ①		
MISSED APCH: Climb STRAIGHT AHEAD to 1200' or above to ER NDB, then turn LEFT onto 031° from ER NDB to RATKE (MAX 210 KT) climbing to 3000'. On 004° to KN NDB turn LEFT to intercept 224° from KN NDB to KEZVU (MANDATORY 220 KT), then proceed according to chart or as directed.								
Alt Set: hPa (MM on req)		Rwy Elev: 22 hPa		Trans level: FL110 ②				
RNAV 1 for initial and intermediate apch.			GNSS or DME/DME required.					



MR DME	6.5	5.4	4.3	3.2	2.2	1.1
ALTITUDE	2710'	2370'	2030'	1690'	1350'	1010'



Gnd speed-Kts	70	90	100	120	140	160	HIALS-II		MIN	ER	RATKE	ER
Descent Angle	3.00°	372	478	531	637	743	PAPI		1200'	794	onto	794
EE612 to MAP	7.2	6:10	4:48	4:19	3:36	3:05					LT	031°


Std		STRAIGHT-IN LANDING CDFA	
		1 DA/MDA(H) 1320' (720')	
		ALS out	
A	R1500m		
B			
C	R2400m		
D			
1 VNAV DA(H) in lieu of MDA(H) depends on operator policy.			

CHANGES: P-areas, RATKE fly-over WP.

UUEE/SVO
SHEREMETYEVO

JEPPESEN
13 FEB 26 **(21-3)** **Eff 19 Feb**

MOSCOW, RUSSIA
ILS Rwy 06C





UUEE/SVO
SHEREMETYEVO

JEPPESEN
13 FEB 26 (21-4) Eff 19 Feb

MOSCOW, RUSSIA
LOC Rwy 06C

BRIEFING STRIP™

ATIS		SHEREMETYEVO Radar (TWR)					SHEREMETYEVO Tower	Ground 3
122.075 (Russian 120.375)		118.1	120.675	122.7	126.6	135.175	118.7	122.9
LOC IMR 108.1	Final Apch Crs 063°	EE632 2000' (1380')	DA/MDA(H) 1190' (570')	Apt Elev 630' Rwy 620'		3900 MSA ARP ①		
MISSED APCH: Climb STRAIGHT AHEAD to UMLOL, then turn LEFT onto 356° to KN NDB to EE826 (MAX 210 KT) climbing to 3000', then turn LEFT onto 224° from KN NDB to KEZVU (MANDATORY 220 KT), then according to chart or as directed.								
Alt Set: hPa (MM on req)		Rwy Elev: 22 hPa		Trans level: FL110 ②				
RNAV 1 for initial and intermediate apch.			GNSS or DME/DME required.					



Gnd speed-KT	70	90	100	120	140	160	HIALS PAPI UMLOL
Descent Angle 3.00°	372	478	531	637	743	849	
MAP at LMM							

STRAIGHT-IN LANDING	
CDFA	
① DA/MDA(H) 1190' (570')	
ALS out	
A	R1500m
B	
C	R1900m
D	R2400m
① VNAV DA(H) in lieu of MDA(H) depends on operator policy.	

CHANGES: NDB ident.



© JEPPESEN 2021, 2026. ALL RIGHTS RESERVED.

UUEE/SVO
SHEREMETYEVO

JEPPESEN
13 FEB 26 (21-5) Eff 19 Feb

MOSCOW, RUSSIA
ILS Rwy 06R

BRIEFING STRIP™	ATIS		SHEREMETYEVO Radar (TWR)					SHEREMETYEVO Tower	Ground 3
	122.075 (Russian 120.375)		118.1 120.675 122.7 126.6 135.175					118.7	122.9
	LOC INL 109.1	Final Appch Crs 063°	EE622 2000' (1381')	DA(H) 819' (200')	Apt Elev 630' Rwy 619'		3900 MSA ARP①		
	MISSED APCH: Climb STRAIGHT AHEAD to 1100' or above (MAX 210 KT), then turn RIGHT to EE057 (MAX 220 KT) on 086° climbing to 3000', then turn LEFT to OLZON (MAX 220 KT), then to RIMDE (MAX 220 KT), then to EE078 (MAX 220 KT), then to KEZVU (MANDATORY 220 KT), then according to chart or as directed.								
	Alt Set: hPa (MM on req)		Rwy Elev: 22 hPa		Trans level: FL110 ②				Trans alt: 10000'
	RNAV 1 for initial, intermediate and missed approach.			GNSS or DME/DME required.					



Gnd speed-KT	70	90	100	120	140	160	HIALS-II PAPI	MIN 1100'	210 KT MAX	EE057 on RT 086°
Gs	3.00°	372	478	531	637	743				

STRAIGHT-IN LANDING		
ILS		
DA(H) 819' (200')		
TDZ or CL out		ALS out
A	R550m	R1200m
B	① R550m	
C		
D		
① R750m when a Flight Director or Autopilot or HUD to DA is not used.		

CHANGES: NDB ident.



© JEPPESEN 2020, 2026. ALL RIGHTS RESERVED.

UUEE/SVO
SHEREMETYEVO

JEPPESSEN
13 FEB 26 (21-6) Eff 19 Feb

MOSCOW, RUSSIA
LOC Rwy 06R

ATIS		SHEREMETYEVO Radar (TWR)					SHEREMETYEVO Tower	Ground 3
122.075 (Russian) 120.375		118.1 120.675 122.7 126.6 135.175					118.7	122.9
LOC INL 109.1	Final Apch Crs 063°	EE622 2000' (1381')	DA/MDA(H) 1140' (521')	Apt Elev 630' Rwy 619'				
MISSED APCH: Climb STRAIGHT AHEAD, after passing RWY 24L THR turn RIGHT onto 074° from NL Lctr to EE825/353° KN NDB (MAX 210 KT) climbing to 3000', turn LEFT to intercept 356° to KN NDB to EE826 (MAX 210 KT), turn LEFT onto 224° from KN NDB to KEZVU (MANDATORY 220 KT), then proceed according to chart or as directed.								
Alt Set: hPa (MM on req)		Rwy Elev: 22 hPa		Trans level: FL110 ②		Trans alt: 10000'		
RNAV 1 for initial and intermediate apch.		GNSS or DME/DME required.						



Gnd speed-KT	70	90	100	120	140	160	HIALS-II PAPI	RWY 24L THR	EE825 onto	KN 642 074°	210 KT MAX
Descent Angle 3.00°	372	478	531	637	743	849					
MAP at LMM											

Std

STRAIGHT-IN LANDING

CDFA

1 DA/MDA(H) **1 140'** (521')

ALS out


A	R1500m	
B		
C	R1700m	R2400m
D		

1 VNAV DA(H) in lieu of MDA(H) depends on operator policy.

UUEE/SVO
SHEREMETYEVO

JEPPESSEN
13 FEB 26 (21-7) Eff 19 Feb


MOSCOW, RUSSIA
ILS Rwy 24L



UUEE/SVO
SHEREMETYEVO

JEPPESEN
13 FEB 26 21-7A Eff 19 Feb


MOSCOW, RUSSIA
CAT II ILS Rwy 24L



UUEE/SVO
SHEREMETYEVO

JEPPESSEN
13 FEB 26 (21-8) Eff 19 Feb

MOSCOW, RUSSIA
LOC Rwy 24L



UUEE/SVO
SHEREMETYEVO



JEPPESEN
13 FEB 26 (21-9) Eff 19 Feb

MOSCOW, RUSSIA
ILS Rwy 24C

20

BRIEFING STRIP™

ATIS		SHERMETYEVO Radar (TWR)					SHERMETYEVO Tower	Ground 3
122.075 (Russian 120.375)		118.1	120.675	122.7	126.6	135.175	118.7	122.9
LOC IAD 111.3	Final Apch Crs 243°	EE142 2000' (1378')	DA(H) 822' (200')	Apt Elev 630' Rwy 622'		3900 MSA ARP ①		
MISSED APCH: Climbing to 3000' to AKFOL (MAX 220 KT), then turn RIGHT to DUFAR (MAX 220 KT), then to TIRDE (MAX 220 KT), then to KEZVU (MANDATORY 220 KT), then according to chart or as directed.								
Alt Set: hPa (MM on req)		Rwy Elev: 23 hPa		Trans level: FL110 ②				
RNAV 1 for initial, intermediate and missed approach.				GNSS or DME/DME required.				




Gnd speed-KT	70	90	100	120	140	160	HIALS-II			
GS	3.00°	372	478	531	637	849	PAPI		3000'	AKFOL 210 KT

Std STRAIGHT-IN LANDING		
ILS		
DA(H) 822' (200')		
	TDZ or CL out	ALS out
A		
B	R550m	R1200m
C		
D		
① R750m when a Flight Director or Autopilot or HUD to DA is not used.		

UUEE/SVO
SHEREMETYEVO

JEPPESEN
13 FEB 26
Eff 19 Feb 21-9A


MOSCOW, RUSSIA
CAT II/III ILS Rwy 24C



UUEE/SVO
SHEREMETYEVO

JEPPESEN
13 FEB 26 (21-10) Eff 19 Feb

MOSCOW, RUSSIA
LOC Rwy 24C



UUEE/SVO
SHEREMETYEVO



JEPPESEN
8 NOV 24 (21-11)

MOSCOW, RUSSIA
ILS Rwy 24R

BRIEFING STRIP™

ATIS		SHEREMETYEVO Radar (TWR)					SHEREMETYEVO Tower	Ground 3	
122.075 (Russian)		120.375	118.1	120.675	122.7	126.6	135.175	118.7	122.9
LOC IBR 109.35	Final Apch Crs 243°		EE112 MANDATORY 3000' (2411')		DA(H) 789' (200')		Apt Elev 630' Rwy 589'		3900 MSA ARP ①
MISSED APCH: Climb STRAIGHT AHEAD to 1100' or above (MAX 210 KT), then turn RIGHT on 309° to EE058 (MAX 210 KT) climbing to 3000', then turn RIGHT to KEZVU (MANDATORY 220 KT), then according to chart or as directed.									
Alt Set: hPa (MM on req)		Rwy Elev: 21 hPa		Trans level: FL110 ②			Trans alt: 10000'		
RNAV 1 for initial, intermediate and missed approach.					GNSS or DME/DME required.				

20



STRAIGHT-IN LANDING		
ILS		
DA(H) 789' (200')		
TDZ or CL out		ALS out
A	R550m	R1200m
B		
C		
D		
① R750m when a Flight Director or Autopilot or HUD to DA is not used.		


CHANGES: MKR withdrawn.

© JEPPESEN, 2020, 2024. ALL RIGHTS RESERVED.

UUEE/SVO
SHEREMETYEVO

JEPPESEN
8 NOV 24 (21-11A)


MOSCOW, RUSSIA
CAT II/III ILS Rwy 24R



UUEE/SVO
SHEREMETYEVO

JEPPESEN
20 DEC 24 (21-12) Eff 26 Dec


MOSCOW, RUSSIA
LOC Rwy 24R



UUEE/SVO
SHEREMETYEVO

JEPPESEN
20 DEC 24 **22-2** Eff 26 Dec


MOSCOW, RUSSIA
RNP Rwy 06C



UUEE/SVO
SHEREMETYEVO

JEPPESEN
20 DEC 24 **22-3** Eff 26 Dec

MOSCOW, RUSSIA
RNP Rwy 06R



UUEE/SVO
SHEREMETYEVO

JEPPESEN
20 DEC 24 **(22-4)** Eff 26 Dec

MOSCOW, RUSSIA
RNP Rwy 24L

BRIEFING STRIP™

ATIS 122.075 (Russian) 120.375		SHEREMETYEVO Radar (TWR) 118.1 120.675 122.7 126.6 135.175				SHEREMETYEVO Tower 118.7	Ground 3 122.9
RNAV	Final Apch Crs 243°	EE122 MANDATORY 2000' (1379')	RNAV/VNAV DA(H) Refer to Minimums	Apt Elev 630' Rwy 621'	3900 MSA ARP①		

MISSED APCH: Climb STRAIGHT AHEAD to 1400' or above, then turn LEFT to EE245 (MAX 220 KT) climbing to 3000', then turn RIGHT to AKFOL (MAX 220 KT) to 3000', then to DUFAR (MAX 220 KT), then to TIRDE (MAX 220 KT), then to KEZVU (MANDATORY 220 KT), then according to chart or as directed.

Alt Set: hPa (MM on req) Rwy Elev: 23 hPa Trans level: FL110 ② Trans alt: 10000'

RNP Apch | 1. GNSS or DME/DME required. 2. Baro-VNAV not authorized below -31.0°C.

② FL120 if pressure is less than 1013 hPa (760mm).
FL130 if pressure is less than 977 hPa (733mm).

DIST to RW24L	1.1	2.2	3.2	4.3
ALTITUDE	1010'	1350'	1700'	2000'

Vertical Profile:

- KEZVU MANDATORY 220 KT MAX 7000'
- EE078 MANDATORY 220 KT MAX 5000'
- ARKUD MANDATORY 190 KT MAX 4000'
- KUZUN MANDATORY 180 KT MAX 180 KT
- ZUBHA MANDATORY 180 KT 2500'
- EE122 MANDATORY 160 KT 2000'

Horizontal Profile:

- TIRDE → DUFAR → AKFOL → EE245 → KEZVU → EE078 → ARKUD → KUZUN → ZUBHA → EE122

Obstacle Clearance:

- Obstacle at 1042' cleared by 1045'.
- Obstacle at 1153' cleared by 1152'.
- Obstacle at 1152' cleared by 1152'.
- Obstacle at 1073' cleared by 1073'.
- Obstacle at 1523' cleared by 1523'.

Navigation Data:

- UU(P)-409, UU(P)-408, UU(R)-392, UU(P)-418, UU(R)-317, UU(P)-53, UU(R)-276, UU(P)-424

Legend:

- ① is computed for surface air temperature at apt -31.0°C
- ③ UU(P)-407

Scale:

FEET	METERS
10000	(2860)
7000	(1945)
5000	(1335)
4000	(1030)
3900	(1000)
3000	(725)
2500	(575)
2100	(455)
2000	(420)
1900	(390)
1700	(330)
1400	(240)
1350	(225)
1060	(135)
1010	(120)
1001	(120)
981	(110)
961	(105)
951	(105)

STRAIGHT-IN LANDING:

LNNAV/VNAV DA(H): A: 951' (330') C: 981' (360') B: 961' (340') D: 1001' (380')

LNNAV CDFA: DA/MDA(H) 1060' (439')

Gnd speed-Kts	70	90	100	120	140	160
Descent Angle	3.00°	372	478	531	637	743

PANS OPS:


A	R800m	R1500m	R1300m	R1500m
B				
C				
D				

① VNAV DA(H) in lieu of MDA(H) depends on operator policy.

UUEE/SVO
SHEREMETYEVO

JEPPESEN
5 JUL 24 (22-5) Eff 11 Jul


MOSCOW, RUSSIA
RNP Rwy 24C



UUEE/SVO
SHEREMETYEVO

JEPPESEN
5 JUL 24 (22-6) Eff 11 Jul


MOSCOW, RUSSIA
RNP Rwy 24R



UUEE/SVO
SHEREMETYEVO

JEPPESEN
20 DEC 24 (22-40) Eff 26 Dec


MOSCOW, RUSSIA
GLS Rwy 06L



UUEE/SVO
SHEREMETYEVO

JEPPESEN
20 DEC 24 **(22-41)** Eff 26 Dec

MOSCOW, RUSSIA
GLS Rwy 06C




CHANGES: UU(P)-447 added.

© JEPPESEN 2011, 2024 ALL RIGHTS RESERVED.

UUEE/SVO
SHEREMETYEVO

JEPPESEN
20 DEC 24 (22-42) Eff 26 Dec


MOSCOW, RUSSIA
GLS Rwy 06R



UUEE/SVO
SHEREMETYEVO

JEPPESEN
20 DEC 24 (22-43) Eff 26 Dec


MOSCOW, RUSSIA
GLS Rwy 24L



UUEE/SVO
SHEREMETYEVO

JEPPESSEN
16 FEB 24 **(22-44)** Eff 22 Feb


MOSCOW, RUSSIA
GLS Rwy 24C



UUEE/SVO
SHEREMETYEVO

JEPPESEN
16 FEB 24 (22-45) Eff 22 Feb

MOSCOW, RUSSIA
GLS Rwy 24R




UUEE/SVO
SHEREMETYEVO


JEPPESEN
20 DEC 24 (23-1) Eff 26 Dec

MOSCOW, RUSSIA
VOR Rwy 06L

ATIS		SHEREMETYEVO Radar (TWR)					SHEREMETYEVO Tower	Ground 3
122.075 (Russian 120.375)		118.1	120.675	122.7	126.6	135.175	118.7	122.9
VOR MR 114.35	Final Apch Crs 065°	D7.2 MANDATORY 3000' (2400')	DA/MDA(H) (CONDITIONAL) 1280' (680')		Apt Elev 630' Rwy 600'		3900 MSA ARP ①	
MISSED APCH: Climb STRAIGHT AHEAD to 1200' or above (MAX 210 KT) to ER NDB, then turn LEFT onto R-036 to RATKE (MAX 210 KT) climbing to 3000', then turn LEFT onto 224° from KN NDB to KEZVU (MANDATORY 220 KT), then proceed according to chart or as directed.								
Alt Set: hPa (MM on req)		Rwy Elev: 22 hPa		Trans level: FL110 ②		Trans alt: 10000'		
RNAV 1 for initial and intermediate apch.		1. GNSS or DME/DME required. 2. Final approach track offset by 2° from rwy centerline.						



MR DME	6.5	5.4	4.3	3.2	2.2	1.1
ALTITUDE	2710'	2370'	2030'	1690'	1350'	1010'




Gnd speed-Kts	70	90	100	120	140	160	HIALS-II	MIN 1200'	210 KT MAX	ER 794	RATKE R-036
Descent Angle 3.00°	372	478	531	637	743	849	PAPI				LT
MAP at VOR											

Std		STRAIGHT-IN LANDING	
with D3.3 CDFA		w/o D3.3 CDFA	
1 DA/MDA(H) 1280' (680')		1 DA/MDA(H) 1320' (720')	
ALS out		ALS out	
A	R1500m		R1500m
B			
C	R2400m		R2400m
D			
1 VNAV DA(H) in lieu of MDA(H) depends on operator policy.			

UUEE/SVO
SHEREMETYEVO

JEPPESSEN
20 DEC 24 **23-2** Eff 26 Dec

MOSCOW, RUSSIA
VOR Rwy 24R




UUEE/SVO
SHEREMETYEVO


JEPPESEN
13 FEB 26 (26-1) Eff 19 Feb

MOSCOW, RUSSIA
NDB Rwy 06L

ATIS		SHEREMETYEVO Radar (TWR)					SHEREMETYEVO Tower	Ground 3
122.075 (Russian 120.375)		118.1	120.675	122.7	126.6	135.175	118.7	122.9
NDB ER 794	Final Apch Crs 063°	EE612 3000' (2400')	DA/MDA(H) (CONDITIONAL) 1130' (530')	Apt Elev 630' Rwy 600'		3900 MSA ARP ①		
MISSED APCH: Climb STRAIGHT AHEAD to ER NDB, then turn LEFT onto 031° from ER NDB to RATKE (MAX 210 KT) climbing to 3000'. On 004° to KN NDB turn LEFT onto 224° from KN NDB to KEZVU (MANDATORY 220 KT), then proceed according to chart or as directed.								
Alt Set: hPa (MM on req)		Rwy Elev: 22 hPa		Trans level: FL110 ②				
RNAV 1 for initial and intermediate apch.			GNSS or DME/DME required.					



MR DME	6.5	5.4	4.3	3.2	2.2	1.1
ALTITUDE	2710'	2370'	2030'	1690'	1350'	1010'



Gnd speed-KT	70	90	100	120	140	160	HIALS-II		ER 794	RATKE	ER 794	3000'
Descent Angle	3.00°	372	478	531	637	743	PAPI		↑	LT	031°	↑
EE612 to MAP	7.2	6:10	4:48	4:19	3:36	3:05						


Std			STRAIGHT-IN LANDING			w/o D2.3		
with D2.3 CDFA						CDFA		
1 DA/MDA(H) 1130' (530')						1 DA/MDA(H) 1320' (720')		
ALS out						ALS out		
A	R1500m			R1500m				
B								
C	R1700m			R2400m			R2400m	
D								

1 VNAV DA(H) in lieu of MDA(H) depends on operator policy.

UUEE/SVO
SHEREMETYEVO

JEPPESEN
13 FEB 26 **(26-2)** Eff 19 Feb


MOSCOW, RUSSIA
NDB Rwy 06C



UUEE/SVO
SHEREMETYEVO

JEPPESEN
13 FEB 26 (26-3) Eff 19 Feb

MOSCOW, RUSSIA
NDB Rwy 06R



UUEE/SVO
SHEREMETYEVO



JEPPESEN
13 FEB 26 (26-4) Eff 19 Feb

MOSCOW, RUSSIA
NDB Rwy 24L

BRIEFING STRIP 10M

ATIS		SHEREMETYEVO Radar (TWR)					SHEREMETYEVO Tower	Ground 3
122.075 (Russian 120.375)		118.1	120.675	122.7	126.6	135.175	118.7	122.9
Lctr BW 380	Final Apch Crs 243°	EE122 2000' (1379')	DA/MDA(H) 1100' (479')	Apt Elev 630'		3900 MSA ARP ①		
Rwy 621'								
MISSED APCH: Climb STRAIGHT AHEAD, after passing RWY 06R THR turn LEFT onto 198° from ER NDB to EE245 (MAX 210 KT) climbing to 3000', then turn RIGHT onto 261° to UM NDB (MAX 210 KT), then turn RIGHT onto 321° to AR NDB (MAX 210 KT), turn RIGHT on 047° from AR NDB to KEZVU (MANDATORY 220 KT), then according to chart or as directed.								
Alt Set: hPa (MM on req)		Rwy Elev: 23 hPa		Trans level: FL110 ②		Trans alt: 10000'		
RNAV 1 for initial and intermediate apch.		GNSS or DME/DME required.						

0



Gnd speed-KT	70	90	100	120	140	160	HIALS-II	RWY 06R THR	EE245	ER	210 KT
Descent Angle	3.00°	372	478	531	637	743	849	PAPI	LT	onto 794	MAX
MAP at LMM											

Std STRAIGHT-IN LANDING											
CDFA											
① DA/MDA(H) 1100' (479')											
ALS out											


A	R1500m										
B											
C											
D	R1500m					R2200m					

① VNAV DA(H) in lieu of MDA(H) depends on operator policy.

UUEE/SVO
SHEREMETYEVO

JEPPESEN
13 FEB 26 (26-5) Eff 19 Feb

MOSCOW, RUSSIA
NDB Rwy 24C



UUEE/SVO
SHEREMETYEVO

JEPPESEN
13 FEB 26 (26-6) Eff 19 Feb

MOSCOW, RUSSIA
NDB Rwy 24R

