Appendix IV: Complete Code

All files

1. auth.js (Storage\controllers\auth.js)

```
const mysql = require("mysql")
const jwet = require("jsonwebtoken")
const bcrypt = require("bcryptjs")
const { query } = require("express")


const db = mysql.createConnection({
    host: process.env.MYSQL_HOST,
    user: process.env.MYSQL_USER,
    password: process.env.MYSQL_PASSWORD,
    database: process.env.MYSQL_DATABASE
  })

exports.login = (req, res) => {

    console.log(req.body)
    let account = req.body.account
    let password = req.body.password
    db.query(`SELECT * FROM ap_list`,[account,password], function(error, result) {
        if(error){
            console.log(error)
        }

        if(account || password){
            for(i = 0; i < result.length; i++){
                if(account === result[i].account && password ===
result[i].password){
                    return res.render('home.ejs', {
                    })
                }
            }
            return res.render('login.hbs', {
                message: 'Incorrect password or account'
            })
        }
    })
}
```

```
exports.register = (req, res) => {
    console.log(req.body)
    const {account, password} = req.body

    db.query('SELECT account FROM ap_list WHERE account = ?', [account], async
(error, result) => {
        if(error){
            console.log(error)
        }

        if(result.length > 0){
            return res.render('register.hbs', {
                message: 'The account has been used'
            })
        }
        db.query('INSERT INTO ap_list SET ?', {account: account, password: password},
(error, result) => {
            if(error){
                console.log(error)
            }else{
                console.log(result)
                return res.render('login.hbs', {
                message: 'User registered'
            })
            }
        })
    })
}


exports.history = (req, res) => {
    console.log(req.body)
    const {tipinput} = req.body

    db.query('INSERT INTO history SET ?', {tipinput: tipinput}, (error, result) => {
        if(error){
            console.log(error)
        }else{
            console.log(result)
            return res.render('map.hbs')
        }
    })
}

exports.favourite = (req, res) => {
```

```
    console.log(req.body)
    const {tipinput} = req.body

    db.query('INSERT INTO favourite SET ?', {tipinput: tipinput}, (error, result) =>
{
        if(error){
            console.log(error)
        }else{
            console.log(result)
            return res.render('Recommendation.ejs')
        }
    })
}

exports.edit_sample_data = (request, response) => {
    var idd = request.params.first_name;
    var idd = request.body.first_name;
    var last_name = request.body.last_name;
    var query = `UPDATE history SET tipinput = "${last_name}" WHERE idd = "${idd}"`;

    db.query(query, function(error, data){

        if(error)
        {
            throw error;
        }
        else
        {
            request.flash('success', 'Sample Data Edited');
            response.redirect('/sample_data');
        }
    });
}

exports.add_sample_data = (request, response) => {
    var last_name = request.body.last_name;

    var query = `INSERT INTO history (tipinput) VALUES ("${last_name}")`;

    db.query(query, function(error, data){

        if(error)
        {
            throw error;
```

```
        }
        else
        {
            request.flash('success', 'Sample Data Inserted');
            response.redirect("/sample_data");
        }

    });
}

exports.edit_sample_data_cal = (request, response) => {
    var idd = request.params.first_name;

    var idd = request.body.first_name;

    var last_name = request.body.last_name;


    // var age = request.body.age;

    // var gender = request.body.gender;

    var query = `UPDATE history SET tipinput = "${last_name}" WHERE idd = "${idd}"`;

    db.query(query, function(error, data){

        if(error)
        {
            throw error;
        }
        else
        {
            request.flash('success', 'Sample Data Edited');
            response.redirect('/Favourite');
        }

    });
}

exports.add_sample_data_cal = (request, response) => {
    // var idd = request.body.idd;

    var last_name = request.body.last_name;

    // var age = request.body.age;
```

```
    // var gender = request.body.gender;

    var query = `INSERT INTO favourite (tipinput) VALUES ("${last_name}")`;

    db.query(query, function(error, data){

        if(error)
        {
            throw error;
        }
        else
        {
            request.flash('success', 'Sample Data Inserted');
            response.redirect("/Favourite");
        }

    });
}

exports.travellinghistory = (req, res) => {
    console.log(req.body)
    const {tipinput,tepinput,topinput,twpinput,choice} = req.body

    db.query('INSERT INTO travellinghistory SET ?', {tipinput: tipinput,
tepinput:tepinput, topinput:topinput, twpinput:twpinput, choice:choice}, (error,
result) => {
        if(error){
            console.log(error)
        }else{
            console.log(result)
            return res.render('Bybus.ejs')
        }
    })
}

exports.travellinghistorycal = (req, res) => {
    console.log(req.body)
    const {tipinput,tepinput,topinput,twpinput,choice} = req.body

    db.query('INSERT INTO travellinghistory SET ?', {tipinput: tipinput,
tepinput:tepinput, topinput:topinput, twpinput:twpinput, choice:choice}, (error,
result) => {
        if(error){
```

```
            console.log(error)
        }else{
            console.log(result)
            return res.render('Bybus(cal).ejs')
        }
    })
}

exports.travellinghistorycar = (req, res) => {
    console.log(req.body)
    const {tipinput,tepinput,topinput,twpinput,choice} = req.body

    db.query('INSERT INTO travellinghistory SET ?', {tipinput: tipinput,
tepinput:tepinput, topinput:topinput, twpinput:twpinput, choice:choice}, (error,
result) => {
        if(error){
            console.log(error)
        }else{
            console.log(result)
            return res.render('Bycar.ejs')
        }
    })
}

exports.travellinghistorycarcal = (req, res) => {
    console.log(req.body)
    const {tipinput,tepinput,topinput,twpinput,choice} = req.body

    db.query('INSERT INTO travellinghistory SET ?', {tipinput: tipinput,
tepinput:tepinput, topinput:topinput, twpinput:twpinput, choice:choice}, (error,
result) => {
        if(error){
            console.log(error)
        }else{
            console.log(result)
            return res.render('Bycar(cal).ejs')
        }
    })
}
```

2. auth.js (\Storage\routes\auth.js)

```
var express = require("express")
const authcontroller = require("../controllers/auth.js")
```

```
var router = express.Router()

router.post('/register', authcontroller.register)
router.post('/login', authcontroller.login)
router.post('/history', authcontroller.history)
router.post('/favourite', authcontroller.favourite)
router.post('/edit_sample_data', authcontroller.edit_sample_data)
router.post('/add_sample_data', authcontroller.add_sample_data)
router.post('/edit_sample_data_cal', authcontroller.edit_sample_data_cal)
router.post('/add_sample_data_cal', authcontroller.add_sample_data_cal)
router.post('/travellinghistory', authcontroller.travellinghistory)
router.post('/travellinghistorycal', authcontroller.travellinghistorycal)
router.post('/travellinghistorycar', authcontroller.travellinghistorycar)
router.post('/travellinghistorycarcal', authcontroller.travellinghistorycarcal)

module.exports = router
```

3. pages.js (\Storage\routes\pages.js)

```
const express = require("express")
const authcontroller = require("../controllers/auth.js");
const mysql = require("mysql")
const router = express.Router()

const db = mysql.createConnection({
    host: process.env.MYSQL_HOST,
    user: process.env.MYSQL_USER,
    password: process.env.MYSQL_PASSWORD,
    database: process.env.MYSQL_DATABASE
  })


router.get("/login", (req, res) => {
    res.render("login.hbs")
})
router.get("/register", (req, res) => {
    res.render("register.hbs")
})
router.get("/map", (req, res) => {
    res.render("map.hbs")
})
router.get("/", (req, res) => {
    res.render("initial.ejs")
})
router.get("/map_route", (req, res) => {
```

```
    res.render("map_route.ejs")
})
router.get("/home", (req, res) => {
    res.render("home.ejs")
})
router.get("/StudyMode", (req, res) => {
    res.render("Studymode.ejs")
})
router.get("/CausalMode", (req, res) => {
    res.render("Causalmode.ejs")
})
router.get("/Recommendation", (req, res) => {
    res.render("Recommendation.ejs")
})
router.get("/Traffic", (req, res) => {
    res.render("Traffic.ejs")
})
router.get("/Traffic_cal", (req, res) => {
    res.render("Traffic(cal).ejs")
})
router.get("/Searching", (req, res) => {
    res.render("Searching.ejs")
})
router.get("/Surroundings", (req, res) => {
    res.render("surroundings.ejs")
})
router.get("/SurroundingsCausal", (req, res) => {
    res.render("surroundings(Causal).ejs")
})
router.get("/mapc", (req, res) => {
    res.render("mapc.hbs")
})
router.get("/Bycar", (req, res) => {
    res.render("Bycar.ejs")
})
router.get("/Bycarcal", (req, res) => {
    res.render("Bycar(cal).ejs")
})
router.get("/Bybus", (req, res) => {
    res.render("Bybus.ejs")
})
router.get("/Bybuscal", (req, res) => {
    res.render("Bybus(cal).ejs")
})
```

```
router.get("/onfeet", (req, res) => {
    res.render("Onfeet.ejs")
})
router.get("/locatedip", (req, res) => {
    res.render("locatedip.ejs")
})



router.get("/sample_data", function(request, response, next){

    var query = "SELECT * FROM history";

    db.query(query, function(error, data){

        if(error)
        {
            throw error;
        }
        else
        {
            response.render('sample_data.ejs', {title:'History Searched',
action:'list', sampleData:data, message:request.flash('success')});
        }

    });

});

router.get("/routes/pages.js/add", function(request, response, next){

    response.render("sample_data.ejs", {title:'Insert Data into MySQL',
action:'add'});

});


router.get('/routes/pages.js/edit/:idd', function(request, response, next){

    var idd = request.params.idd;

    db.query(`SELECT * FROM history WHERE idd = "${idd}"`, function(error, data){

        response.render('sample_data.ejs', {title: 'Edit MySQL Table Data',
action:'edit', sampleData:data[0]});
```

```
    });

});


router.get('/routes/pages.js/delete/:idd', function(request, response, next){

    var idd = request.params.idd;

    db.query(`DELETE FROM history WHERE idd = "${idd}"`, function(error, data){

        if(error)
        {
            throw (error);
        }
        else
        {
            request.flash('success', 'Sample Data Deleted');
            response.redirect("/sample_data");
        }

    });

});
// router.get("/views/sample_data", (req, res) => {
//     res.render("sample_data.ejs")
// })
// router.get('/login',authcontroller.isLoggedIn, (req, res) => {
//     res.sendFile("home.ejs", { root: './public/' })
// });

router.get("/Favourite", function(request, response, next){

    var query = "SELECT * FROM favourite";

    db.query(query, function(error, data){

        if(error)
        {
            throw error;
        }
        else
        {
```

```
            response.render('Favourite.ejs', {title:'LIKED DESTINATION',
action:'list', sampleData:data, message:request.flash('success')});
        }

    });

});

router.get('/routes/pages.js/delet/:idd', function(request, response, next){

    var idd = request.params.idd;

    // var query = `DELETE FROM history WHERE idd = "${idd}"`;

    db.query(`DELETE FROM favourite WHERE idd = "${idd}"`, function(error, data){

        if(error)
        {
            throw (error);
        }
        else
        {
            request.flash('success', 'Sample Data Deleted');
            response.redirect("/Favourite");
        }

    });

});

router.get('/routes/pages.js/edi/:idd', function(request, response, next){

    var idd = request.params.idd;

    // var query = `SELECT * FROM history WHERE idd = "${idd}"`;

    db.query(`SELECT * FROM favourite WHERE idd = "${idd}"`, function(error, data){

        response.render('Favourite.ejs', {title: 'Edit MySQL Table Data',
action:'edit', sampleData:data[0]});

    });

});
```

```
router.get("/routes/pages.js/ad", function(request, response, next){

    response.render("Favourite.ejs", {title:'Insert Data into MySQL', action:'add'});

});

router.get("/travellinghistory", function(request, response, next){

    var query = "SELECT * FROM travellinghistory";

    db.query(query, function(error, data){

        if(error)
        {
            throw error;
        }
        else
        {
            response.render('travellinghistory.ejs', {title:'History Traveled',
action:'list', sampleData:data, message:request.flash('success')});
        }

    });

});

module.exports = router
```

4. Bybus.ejs (\Storage\views\Bybus.ejs)

```
<!doctype html>
<html>

<head>
  <meta charset="utf-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="initial-scale=1.0, user-scalable=no, width=device-
width">
  <link rel="icon" type="image/x-icon" href="geek.ico">
  <title>Bus Route</title>
  <style type="text/css">
    html,
    body,
```

```css
#container {
  width: 100%;
  height: 100%;
}

#panel {
  position: fixed;
  background-color: white;
  max-height: 90%;
  overflow-y: auto;
  top: 10px;
  right: 10px;
  width: 280px;
}

#panel .amap-call {
  background-color: #009cf9;
  border-top-left-radius: 4px;
  border-top-right-radius: 4px;
}

#panel .amap-lib-driving {
  border-bottom-left-radius: 4px;
  border-bottom-right-radius: 4px;
  overflow: hidden;
}

#myPageTop {
  position: absolute;
  top: 5px;
  left: 10px;
  background: #fff none repeat scroll 0 0;
  border: 1px solid #ccc;
  margin: 10px auto;
  padding:6px;
  font-family: "Microsoft Yahei", "微软雅黑", "Pinghei";
  font-size: 14px;
}

#myPageTop label {
  margin: 0 20px 0 0;
  color: #666666;
  font-weight: normal;
}
```

```
    #myPageTop input {
      width: 130px;
    }

    #myPageTop .column2{
      padding-left: 25px;
    }
  </style>
  <link rel="stylesheet" href="https://a.amap.com/jsapi_demos/static/demo-
center/css/demo-center.css" />
  <script src="https://a.amap.com/jsapi_demos/static/demo-
center/js/demoutils.js"></script>
  <script type="text/javascript"
src="https://cache.amap.com/lbs/static/addToolbar.js"></script>
</head>

<body>

<form action="/map">
  <button type="submit" style="position: relative; top: 100px; left:
15px;">Back</button>
</form>

<div id="myPageTop">
    <form action="/auth/travellinghistory" method="POST">
      <button type="submit">Record</button>

      <label for="">Begin Lat: </label>
      <input id="tipinput"  value="" name="tipinput">

      <label for="">Begin Log: </label>
      <input id="tepinput"  value="" name="tepinput">

      <label for="">Destination Lat: </label>
      <input id="topinput"  value="" name="topinput">

      <label for="">Destination Log: </label>
      <input id="twpinput"  value="" name="twpinput">

      <label for="">Travelling mode: (LEAST_TIME,LEAST_FEE,NO_SUBWAY)</label>
      <input id="choice"  value="" name="choice">
    </form>
    <button onclick="conductSearch()">Forward</button>
```

```
</div>



<script type="text/javascript">
        window._AMapSecurityConfig = {
          securityJsCode: "f6b242cd04daebb47685da20c645bd53",
        };
</script>
<script type="text/javascript"
src="https://webapi.amap.com/maps?v=2.0&key=c3f65892c3589481fd26d92b375055e0&plugin=
AMap.Transfer"></script>

<div id="container"></div>
<div id="panel"></div>


<script type="text/javascript">

function conductSearch(){

    var value1 = document.getElementById('tipinput').value;
    var value2 = document.getElementById('tepinput').value;
    var value3 = document.getElementById('topinput').value;
    var value4 = document.getElementById('twpinput').value;
    var value5 = document.getElementById('choice').value;
    alert(value1+ "," + value2 + "," + value3 + "," + value4 + "\n*" + "The
travelling mode is " + value5);

    var map = new AMap.Map("container", {
      resizeEnable: true,
      center: [116.397428, 39.90923],
      zoom: 13 //Display zoom level
    });
    var transOptions = {
      map: map,
      city: '佛山市',
      panel: 'panel',
      //cityd:'',
      policy: AMap.TransferPolicy.value5,
    };
    //Construct bus transfer class
    var transfer = new AMap.Transfer(transOptions);
    //Construct route according to the starting point and destination point
```

```
    transfer.search(new AMap.LngLat(value1, value2), new AMap.LngLat(value3, value4),
function (status, result) {
      // result is the type of data  https://lbs.amap.com/api/javascript-
api/reference/route-search#m_TransferResult
      if (status === 'complete') {
        map.setCenter([value1, value2])
        log.success('successfully create bus route')
      } else {
        log.error('Fail to create the bus route' + result)
      }
    });
}

  </script>
</body>

</html>
```

5. Bycar.ejs (\Storage\views\Bycar.ejs)

```
<!doctype html>
<html>

<head>
  <meta charset="utf-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="initial-scale=1.0, user-scalable=no, width=device-
width">
  <link rel="icon" type="image/x-icon" href="geek.ico">
  <title>Car Route</title>
  <style type="text/css">
    html,
    body,
    #container {
      width: 100%;
      height: 100%;
    }

    #panel {
      position: fixed;
      background-color: white;
      max-height: 90%;
      overflow-y: auto;
      top: 10px;
```

```
    right: 10px;
    width: 280px;
  }

  #panel .amap-call {
    background-color: #009cf9;
    border-top-left-radius: 4px;
    border-top-right-radius: 4px;
  }

  #panel .amap-lib-driving {
    border-bottom-left-radius: 4px;
    border-bottom-right-radius: 4px;
    overflow: hidden;
  }

  #myPageTop {
    position: absolute;
    top: 5px;
    left: 10px;
    background: #fff none repeat scroll 0 0;
    border: 1px solid #ccc;
    margin: 10px auto;
    padding:6px;
    font-family: "Microsoft Yahei", "微软雅黑", "Pinghei";
    font-size: 14px;
  }

  #myPageTop label {
    margin: 0 20px 0 0;
    color: #666666;
    font-weight: normal;
  }

  #myPageTop input {
    width: 130px;
  }

  #myPageTop .column2{
    padding-left: 25px;
  }

</style>
```

```
  <link rel="stylesheet" href="https://a.amap.com/jsapi_demos/static/demo-
center/css/demo-center.css" />
  <script src="https://a.amap.com/jsapi_demos/static/demo-
center/js/demoutils.js"></script>

  <script type="text/javascript"
src="https://cache.amap.com/lbs/static/addToolbar.js"></script>
</head>

<body>

  <form action="/map">
    <button type="submit" style="position: relative; top: 100px; left:
15px;">Back</button>
  </form>


  <div id="container"></div>
  <div id="panel"></div>
  <script type="text/javascript">
  window._AMapSecurityConfig = {
    securityJsCode: "f6b242cd04daebb47685da20c645bd53",
  };
  </script>
  <script type="text/javascript"
src="https://webapi.amap.com/maps?v=2.0&key=c3f65892c3589481fd26d92b375055e0&plugin=
AMap.Driving"></script>

<div id="myPageTop">
    <form action="/auth/travellinghistorycar" method="POST">
      <button type="submit">Record</button>

      <label for="">Begin Lat: </label>
      <input id="tipinput"  value="" name="tipinput">

      <label for="">Begin Log: </label>
      <input id="tepinput"  value="" name="tepinput">

      <label >Destination Lat: </label>
      <input id="topinput"  value=""name="topinput">

      <label >Destination Log: </label>
      <input id="twpinput"  value="" name="twpinput">

      <label >Travelling mode: (0[fatest], 1[cheapest], 4[avoid traffic])</label>
```

```
      <input id="choice"  value="" name="choice">
    </form>
    <button onclick="conductSearch()">Forward</button>
</div>

<script>
</script>


<script type="text/javascript">


function conductSearch() {

    var value1 = document.getElementById('tipinput').value;
    var value2 = document.getElementById('tepinput').value;
    var value3 = document.getElementById('topinput').value;
    var value4 = document.getElementById('twpinput').value;
    var value5 = document.getElementById('choice').value;
    alert(value1+ "," + value2 + "," + value3 + "," + value4 + "," + value5);

    //Basic map loading
    var map = new AMap.Map("container", {
      resizeEnable: true,
      center: [116.397428, 39.90923],//map center
      zoom: 13 //Display zoom level
    });



    //construct navigation-route class
    var driving = new AMap.Driving({
      map: map,
      panel: "panel",
      policy: value5,
    });


      driving.search(new AMap.LngLat(value1,value2), new AMap.LngLat(value3,value4),
function (status, result) {
      // https://lbs.amap.com/api/javascript-api/reference/route-
search#m_DrivingResult
        if (status === 'complete') {
        // log.success(autoOptions)
          log.success('successfully create car route')
```

```
          map.setCenter([value1, value2])
        } else {
          log.error('Fail to obtain the car route' + result)
        }
      });
}

  </script>
</body>

</html>
```

6. Causalmode.ejs (\Storage\views\Causalmode.ejs)

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>CausalMode</title>
    <link rel="stylesheet"
href="https://maxcdn.bootstrapcdn.com/bootstrap/3.4.1/css/bootstrap.min.css">
    <script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.7.1/jquery.min.js"></script>
    <script
src="https://maxcdn.bootstrapcdn.com/bootstrap/3.4.1/js/bootstrap.min.js"></script>
    <link rel="icon" type="image/x-icon" href="geek.ico">
</head>
<body>

    <div class="container">
        <h1>CausalMode</h1>
        <form action="/mapc" method="get">
            <button type="submit" class="btn btn-info">Jump to map</button>
        </form>
    </div>

    <div class="container">
        <form action="/home" method="get">
            <button type="submit" class="btn btn-info" style="position: relative;
top: 20px;">Back</button>
        <form>
    </div>
```

```
</body>
</html>
```

7. Favourite.ejs (\Storage\views\Favourite.ejs)

```
<!doctype html>
<html lang="en">
    <head>
        <!-- Required meta tags -->
        <meta charset="utf-8">
        <meta name="viewport" content="width=device-width, initial-scale=1">

        <!-- Bootstrap CSS -->
        <link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstrap.min.css"
rel="stylesheet" integrity="sha384-
EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65VohhpuuCOmLASjC"
crossorigin="anonymous">
        <link rel="icon" type="image/x-icon" href="geek.ico">

        <title></title>
    </head>
    <body>
        <div class="container">
            <h1 class="text-center mt-3 mb-3"><%= title %></h1>

            <% if(action == 'add') { %>

            <div class="card">
                <div class="card-header">Sample Form</div>
                <div class="card-body">
                    <form method="POST" action="/auth/add_sample_data_cal">
                        <div class="row">
                            <div class="col-md-6">
                                <div class="mb-3">
                                    <label>id</label>
                                    <input type="text" name="first_name"
id="first_name" class="form-control" />
                                </div>
                            </div>
                            <div class="col-md-6">
                                <div class="mb-3">
                                    <label>Add destination</label>
```

```
                                    <input type="text" name="last_name"
id="last_name" class="form-control" />
                                </div>
                            </div>
                        </div>
                        <!-- <div class="row">
                            <div class="col-md-6">
                                <div class="mb-3">
                                    <label>Time</label>
                                    <input type="number" name="age" id="age"
class="form-control" />
                                </div>
                            </div>
                            <div class="col-md-6">
                                <div class="mb-3">
                                    <label>Gender</label>
                                    <select name="gender" class="form-control">
                                        <option value="Male">Male</option>
                                        <option value="Female">Female</option>
                                    </select>
                                </div>
                            </div> -->
                        </div>
                        <div class="mb-3">
                            <input type="submit" name="submit_button" class="btn
btn-primary" value="Add" />
                        </div>
                    </form>
                </div>
            </div>

            <% } else if(action == 'edit') { %>
            <div class="card">
                <div class="card-header">Sample Form</div>
                <div class="card-body">
                    <form method="POST" action="/auth/edit_sample_data_cal">
                        <div class="row">
                            <div class="col-md-6">
                                <div class="mb-3">
                                    <label>id</label>
                                    <input type="text" name="first_name"
id="first_name" class="form-control" value="<%= sampleData.first_name %>" />
                                </div>
                            </div>
```

```
                            <div class="col-md-6">
                                <div class="mb-3">
                                    <label>Searched destination</label>
                                    <input type="text" name="last_name"
id="last_name" class="form-control" value="<%= sampleData.last_name %>" />
                                </div>
                            </div>
                        </div>
                        <div class="row">
                            <div class="col-md-6">
                                <div class="mb-3">
                                    <label>Age</label>
                                    <input type="number" name="age" id="age"
class="form-control" value="<%= sampleData.age %>" />
                                </div>
                            </div>
                            <div class="col-md-6">
                                <div class="mb-3">
                                    <label>Gender</label>
                                    <select name="gender" id="gender" class="form-
control">
                                        <option value="Male">Male</option>
                                        <option value="Female">Female</option>
                                    </select>
                                </div>
                            </div>
                        </div>
                        <div class="mb-3">
                            <input type="submit" name="submit_button" class="btn
btn-primary" value="Edit" />
                        </div>
                    </form>
                    <script>
                    document.getElementById('gender').value="<%=
sampleData.gender %>";
                    </script>
                </div>
            </div>
            <% } else { %>
                <% if(message.length > 0) { %>
                <div class="alert alert-success">
                    <%= message %>
                </div>
                <% } %>
```

```
            <div class="card">
                <div class="card-header">
                    <div class="row">
                        <div class="col">Sample Data</div>
                        <div class="col">
                            <a href="/routes/pages.js/ad" class="btn btn-success
btn-sm float-end">Add</a>
                            <a href="/home" class="btn btn-success btn-sm float-end"
style="position: relative; right: 30px;">Back</a>
                        </div>
                    </div>
                </div>
                <div class="card-body">
                    <div class="table-responsive">
                        <table class="table table-bordered">
                            <tr>
                                <th>id</th>
                                <th>Recorded destination</th>
                                <th>Time</th>
                                <th>Action</th>
                            </tr>
                            <%
                            if(sampleData.length > 0)
                            {
                                sampleData.forEach(function(data){
                            %>
                            <tr>
                                <td><%= data.idd %></td>
                                <td><%= data.tipinput %></td>
                                <td><%= data.time %></td>
                                <td>
                                    <a href="/routes/pages.js/edi/<%= data.idd %>"
class="btn btn-primary btn-sm">Edit</a>
                                    <a href="/routes/pages.js/delet/<%= data.idd %>"
class="btn btn-danger btn-sm">Delete</a>
                                </td>
                            </tr>
                            <%
                                });
                            }
                            else
                            {
                            %>
                            <tr>
```

```
                            <td colspan="5">No Data Found</td>
                        </tr>
                        <%
                        }
                        %>
                    </table>
                </div>
            </div>
        </div>

        <% } %>

    </div>

    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.bundle.min.js"
integrity="sha384-MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/tWtIaxVXM"
crossorigin="anonymous"></script>
</body>
</html>
```

8. home.ejs (\Storage\views\home.ejs)

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta http-equiv="X-UA-Compitable" content="IE=edge">
    <!-- <meta http-equiv="refresh" content="1" > -->
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <!-- <link rel="/stylesheet" href="style.css"> -->
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link rel="stylesheet"
href="https://fonts.googleapis.com/css2?family=Noto+Sans:wght@400;600&display=swap">
    <link rel="stylesheet"
href="https://cdn.jsdelivr.net/npm/bootstrap@4.6.2/dist/css/bootstrap.min.css">
    <link rel="icon" type="image/x-icon" href="geek.ico">
    <script
src="https://cdn.jsdelivr.net/npm/jquery@3.7.1/dist/jquery.slim.min.js"></script>
    <script
src="https://cdn.jsdelivr.net/npm/popper.js@1.16.1/dist/umd/popper.min.js"></script>
```

```
    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@4.6.2/dist/js/bootstrap.bundle.min.js"><
/script>
    <link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.1.3/dist/css/bootstrap.min.css"
rel="stylesheet"
        integrity="sha384-
1BmE4kWBq78iYhFldvKuhfTAU6auU8tT94WrHftjDbrCEXSU1oBoqyl2QvZ6jIW3"
crossorigin="anonymous">
    <title>Home</title>
    <style>
        * {
            font-family: 'Poppins', sans-serif;
        }
        body{
            font-family: 'Poppins', sans-serif;
            background: url('/Mode3.jpg') no-repeat;
            background-size: 120pc;
        }
        /* .background {
            background: url('/Mode3.jpg');
            background-position: bottom;
            background-repeat: no-repeat;
            background-size: cover;
            height: 91vh;
        } */
        /* .blur {
            background: rgba(255, 255, 255, 0.2);
            background-size: auto;
            backdrop-filter: blur(1px);
            height: 91vh;
        } */
        .wrapper{
            text-align: center;
        }
        .wrapper h1{
            font-size: 70px;
            margin-top: 10px;
        }
        .wrapper .btn{
            /* position: relative;
            top: 150px;
            right: 250px; */
            font-size: 23px;
```

```
    border-radius: 25px;
    border-width: 5px;
    border-color: black;
    margin-top: 10px;
}
.btn:hover{
    background-color: grey;
    color: white;
}
.btnLabel {
    font-family: Arial, Helvetica, sans-serif;
    /* text-align: start; */
    margin-right: 80px;
    position: relative;
    left: 200px;
    font-weight: bold;
}

.wrapper .atn{
    position: relative;
    top: 150px;
    display: inline;
    width: 30%;
    border-width: 2px;
    border-radius: 10px;
    font-size: 15px;
    font-weight: 60;
    transition-duration: 0.4s;
}
.atn:hover {
    background-color: black;
    color: white;
}
span {
    display: inline-block;
    text-align: left;
}
td {
    width: 40em;
}
table {
    margin-left: 450px;
}
```

```
    </style>

</head>
<body>


    <div class="background">
        <div class="blur">
            <div class="wrapper">
                <h1>Home</h1>
                <div class="">
                    <form action="/StudyMode">
                        <button type="submit" class="btn" style="margin-right:
500px"><b>StudyMode</b></button>
                        <br>
                        <br>
                        <table>
                            <tr>
                                <td>
                                    <span class="btnLabel">Studymode is mainly focus
on the day of studying. It provides a routine from your location to destination.
According to your choice, the route will recommend different passing store to you
like library, education, etc ...</span>
                                </td>
                            </tr>
                        </table>
                    </form>
                        <form action="/CausalMode">
                        <button type="submit" class="btn" style="margin-right:
490px"><b>CausalMode</b></button>
                        <br>
                        <br>
                        <table>
                            <tr>
                                <td>
                                    <span class="btnLabel">Causalmode is mainly
focus on the day of relaxing. It provides a routine from your location to
destination. According to your choice, the route will recommend different passing
store to you like gym, park, KTV, etc ...</span>
                                </td>
                            </tr>
                        </table>
                    </form>
                </div>
```

```
                <div>
                    <form action="/sample_data">
                        <button type="submit" class="atn">History</button>
                    </form>
                    <br>
                    <form action="/Favourite">
                        <button type="submit" class="atn">Favourite</button>
                    </form>
                    <br>
                    <form action="/Recommendation">
                        <button type="submit" class="atn">Recommendation</button>
                    </form>
                    <br>
                    <form action="/travellinghistory">
                        <button type="submit" class="atn">Traveling History</button>
                    </form>
                    <br>
                    <form action="/login">
                        <button type="submit" class="atn">Log out</button>
                    </form>
                </div>
            </div>
        </div>
    </div>

    <script
src="https://cdn.jsdelivr.net/npm/@popperjs/core@2.11.8/dist/umd/popper.min.js"
integrity="sha384-I7E8VVD/ismYTF4hNIPjVp/Zjvgyol6VFvRkX/vR+Vc4jQkC+hVqc2pM8ODewa9r"
crossorigin="anonymous"></script>
    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.min.js"
integrity="sha384-0pUGZvbkm6XF6gxjEnlmuGrJXVbNuzT9qBBavbLwCsOGabYfZo0T0to5eqruptLy"
crossorigin="anonymous"></script>

</body>
</html>
```

9. initial.ejs (\Storage\views\initial.ejs)

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
```

```
    <meta http-equiv="X-UA-Compitable" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <link rel="stylesheet" href="/style.css">
    <link rel="icon" type="image/x-icon" href="geek.ico">
    <title>Map System</title>
    <style>
        button {
        width: 300px;
        font-size: 20px;
        padding: 7px;
        border-radius: 40px;
        color: black;
        cursor: pointer;
        margin: 20px;
        }
        #container{
            position: fixed;
            top: 20%;
            left: 40%;
        }
    </style>
</head>
<body>

    <h1 style="position: relative; left: 35%; padding: 10px;">Welcome</h1>

    <p style="position: relative; left: 200px;"><%= Date() %></p>

    <style>
        body {
            background-image: url('Mode.jpg');
        }
        </style>
    <div id = "container">
        <form action="/login">
            <button id="container" type= "submit">Start Your Journey!😳</button>
          </form>
    </div>

</body>
</html>
```

10. locatedip.ejs (\Storage\views\locatedip.ejs)

```
<!doctype html>
<html>
<head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="initial-scale=1.0, user-scalable=no,
width=device-width">
    <title>Location</title>
      <link rel="stylesheet" href="https://a.amap.com/jsapi_demos/static/demo-
center/css/demo-center.css" />
      <link rel="icon" type="image/x-icon" href="geek.ico">
    <style>
        html,body,#container{
            height:100%;
        }
        .info{
            width:26rem;
        }
    </style>
</head>
<body>

<div id="tap" class='info' style='min-width:18rem;'></div>

<div id="container">
    <input type="text" id="tipinput" placeholder="Enter your location for
weather...">
    <input id='stationKeyWord' type="text" value='' placeholder="Bus stop..." >
    <button id="tip" onclick="dealSearch()" type="submit">Search</button>
    <button onclick="history.back()">Back</button>
</div>


<div class="info">
    <h4 id="status"></h4><hr>
    <p id="result"></p><hr>
    <p >Notice: https will be more accurate!</p>
</div>
<script type="text/javascript">
    window._AMapSecurityConfig = {
      securityJsCode: "f6b242cd04daebb47685da20c645bd53",
    };
</script>
```

```
<script type="text/javascript"
src="https://webapi.amap.com/maps?v=2.0&key=c3f65892c3589481fd26d92b375055e0"></scri
pt>
<script type="text/javascript"
src="https://webapi.amap.com/maps?v=2.0&key=c3f65892c3589481fd26d92b375055e0&plugin=
AMap.StationSearch"></script>

<script type="text/javascript">

function dealSearch(){

    var value6 = document.getElementById('tipinput').value;
    var value7 = document.getElementById('stationKeyWord').value;
    alert("Your position is " + value6 + "\n" + "The bus stop is around " + value7);

    var map = new AMap.Map('container', {
        resizeEnable: true
    });
    AMap.plugin('AMap.Geolocation', function() {
        var geolocation = new AMap.Geolocation({
            enableHighAccuracy: true,//high accuracy located
            timeout: 10000,          //exceeding 10s will be considered as failure
            position:'RB',    //location of the located button
            offset: [10, 20], //location button and the top left corner
            zoomToAccuracy: true,   //zoom to the location located

        });
        map.addControl(geolocation);
        geolocation.getCurrentPosition(function(status,result){
            if(status=='complete'){
                onComplete(result)
            }else{
                onError(result)
            }
        });
    });


    //Analysis of the location results
    function onComplete(data) {

        document.getElementById('status').innerHTML='Successfully located'
        var str = [];
        str.push('Located result: ' + data.position);
        str.push('Located types: ' + data.location_type);
```

```
        if(data.accuracy){
             str.push('Accuracy: ' + data.accuracy + ' meters');
        }//If IP is accurate, no need for accuracy
        str.push('Shift or not: ' + (data.isConverted ? 'Yes' : 'No'));
        document.getElementById('result').innerHTML = str.join('<br>');

        AMap.plugin('AMap.Weather', function() {
        var weather = new AMap.Weather();
        //Inquire of real-time weather, the city/district name is optional
        weather.getLive(value6, function(err, data) {
            if (!err) {
                var str = [];
                str.push('<h4 >Real-time weather: ' + '</h4><hr>');
                str.push('<p>City/District: ' + data.city + '</p>');
                str.push('<p>Weather: ' + data.weather + '</p>');
                str.push('<p>Temperature: ' + data.temperature + '℃</p>');
                str.push('<p>Wind direction: ' + data.windDirection + '</p>');
                str.push('<p>Wind Strength: ' + data.windPower + ' Level</p>');
                str.push('<p>Humidity: ' + data.humidity + '</p>');
                str.push('<p>Released time: ' + data.reportTime + '</p>');
                var marker = new AMap.Marker({map: map, position: map.getCenter()});
                var infoWin = new AMap.InfoWindow({
                    content: '<div class="info" style="position:inherit;margin-
bottom:0;">'+str.join('')+'</div><div class="sharp"></div>',
                    isCustom:true,
                    offset: new AMap.Pixel(0, -37)
                });
                infoWin.open(map, marker.getPosition());
                marker.on('mouseover', function() {
                    infoWin.open(map, marker.getPosition());
                });
            }
        });
    });
    }

    //Analysis of the location failure
    function onError(data) {
        document.getElementById('status').innerHTML='Fail to locate'
        document.getElementById('result').innerHTML = 'Reasons of
failure:'+data.message+'</br>Callback information from browser: '+data.originMessage;
    }


    var markers = [];
```

```
    stationSearch();

    //bus stop searching
    function stationSearch() {

        // Remove all the Marker
        map.remove(markers);

        markers = [];
        var stationKeyWord  = document.getElementById('stationKeyWord').value
        if(!stationKeyWord) return

        //Instantiate the bus stop query class
        var station = new AMap.StationSearch({
            pageIndex: 1, //page number
            pageSize: 60, //display the number of results per page
            city: ''   //ensure the search is within the city
        });

        station.search(stationKeyWord, function(status, result) {

            if (status === 'complete' && result.info === 'OK') {
                stationSearch_CallBack(result);
            } else {
                document.getElementById('tap').innerHTML = JSON.stringify(result);
            }
        });

    }


    //analysis of the search results of bus stop
    function stationSearch_CallBack(searchResult) {

        var stationArr = searchResult.stationInfo;
        var searchNum = stationArr.length;

        if (searchNum > 0) {
            document.getElementById('tap').innerHTML = 'Inquire results: ' +
searchNum + 'related bus stops';
            for (var i = 0; i < searchNum; i++) {

                var marker = new AMap.Marker({
                    icon:new AMap.Icon({
                       image:'//a.amap.com/jsapi_demos/static/resource/img/pin.png',
```

```
                    size:new AMap.Size(32,32),
                    imageSize:new AMap.Size(32,32)
                }),

                offset:new AMap.Pixel(-16,-32),
                position: stationArr[i].location,
                map: map,
                title: stationArr[i].name
            });

            marker.info = new AMap.InfoWindow({
                content: stationArr[i].name,
                offset: new AMap.Pixel(0, -30)
            });

            marker.on('mouseover', function(e) {
                e.target.info.open(map, e.target.getPosition())
            })

            markers.push(marker);
        }

        map.setFitView();
    }
}

document.getElementById('tip').onclick = stationSearch;
}



</script>
</body>
</html>
```

11. login.ejs (\Storage\views\login.ejs)

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta http-equiv="X-UA-Compitable" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
```

```
    <link rel="stylesheet"
href="https://fonts.googleapis.com/css2?family=Noto+Sans:wght@400;600&display=swap">
    <link rel="stylesheet"
href="https://cdn.jsdelivr.net/npm/bootstrap@4.6.2/dist/css/bootstrap.min.css">
    <script
src="https://cdn.jsdelivr.net/npm/jquery@3.7.1/dist/jquery.slim.min.js"></script>
    <script
src="https://cdn.jsdelivr.net/npm/popper.js@1.16.1/dist/umd/popper.min.js"></script>
    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@4.6.2/dist/js/bootstrap.bundle.min.js"><
/script>
    <link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.1.3/dist/css/bootstrap.min.css"
rel="stylesheet"
        integrity="sha384-
1BmE4kWBq78iYhFldvKuhfTAU6auU8tT94WrHftjDbrCEXSU1oBoqyl2QvZ6jIW3"
crossorigin="anonymous">
    <link rel="icon" type="image/x-icon" href="geek.ico">
    <title>Login</title>
    <style>
        * {
            margin: 0;
            padding: 0;
            box-sizing: border-box;
            font-family: 'Poppins', sans-serif;
        }
        body{
            color: #ffffff;
            display: flex;
            align-items: center;
            justify-content: center;
            min-height: 100vh;
            background: url('/Mode2.jpg') no-repeat;
            background-size: cover;
            background-position: center;
        }
        /* button {
        width: 150px;
        font-size: 20px;
        padding: 5px;
        border-radius: 10px;
        color: black;
        cursor: pointer;
        margin: 20px;
```

```
} */
#container{
    position: fixed;
    top: 54%;
    right: 65%;;
}
#container2{
    position: fixed;
    top: 54%;
    right: 53%;
}
.dontainer{
    max-width: 700px;
    padding: 0 15px;
    margin: auto;
}
.wrapper .field-holder{
    position: relative;
    margin-bottom: 1.25em;
}
.field-holder input{
    width: 100%;
}
input{
    border: 0;
    border-bottom: 3px solid #dfdfdf;
    outline: none;
    background: transparent;
    color: #dfdfdf;
}
label{
    position: absolute;
    top: 0;
    left: 0;
    font-size: 1em;
    color: #ffffff;
    display: flex;
    align-items: center;
    cursor: text;
    transition: 0.2s ease-in-out;
}
input,label{
    font-size: 1em;
    width: 60%;
```

```
    height: 55px;
    background: transparent;
}
input:focus + label,
input:valid + label{
    color: #424242;
    font-size: .75em;
    top: -25px;
    pointer-events: none;
}
input:focus
input:valid{
    border-bottom: 3px solid #424242;
}
.wrapper{
    width: 500px;
    background: transparent;
    color: #ffffff;
    border-radius: 10px;
    padding: 30px 40px;
    border: 2px solid rgba(255, 255, 255, 0.2);
    backdrop-filter: blur(20px);
}
.wrapper h1{
    font-size: 36px;
    text-align: center;
}
.wrapper .btn{
    width: 100%;
    height: 45px;
    background: #ffffff;
    border: none;
    outline: none;
    border-radius: 40px;
    cursor: pointer;
    font-size: 16px;
    font-weight: 600;
}
.wrapper .register-link{
    font-size: 14.5px;
    text-align: center;
    margin: 20px 0 15px;
}
.register-link p a {
```

```
            color: #ffffff;
            text-decoration: none;
            font-weight: 60 ;
        }
        .register-link p a:hover{
            text-decoration: underline;
        }

    </style>
</head>
<body>

    <div class="wrapper">
        <div class="dontainer">
            <h1>Login</h1>
            <form action="/auth/login" method="POST">
                <div class="field-holder">
                    <input type="text" id ="account" name="account" required>
                    <label for="account">Account</label>
                 </div>

                <div class="field-holder">
                    <input type="password" id="password" name="password" required>
                    <label for="password">Password</label>
                </div>

                <form>
                    <button type= "submit" class="btn">Login</button>
                </form>
                <div class="register-link">
                    <p>Don't have an account? <a href="/register">Register</a></p>
                </div>
            </form>
        </div>
        {{#if message}}
            <h4 class="alert alert-danger mt-4">{{message}}</h4>
        {{/if}}
    </div>

    <script
src="https://cdn.jsdelivr.net/npm/@popperjs/core@2.11.8/dist/umd/popper.min.js"
integrity="sha384-I7E8VVD/ismYTF4hNIPjVp/Zjvgyol6VFvRkX/vR+Vc4jQkC+hVqc2pM8ODewa9r"
crossorigin="anonymous"></script>
```

```
    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.min.js"
integrity="sha384-0pUGZvbkm6XF6gxjEnlmuGrJXVbNuzT9qBBavbLwCsOGabYfZo0T0to5eqruptLy"
crossorigin="anonymous"></script>

</body>
</html>
```

12. map.hbs (\Storage\views\map.hbs)

```
<!doctype html>
<html>
<head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="initial-scale=1.0, user-scalable=no,
width=device-width">
    <title>Map System</title>
    <script src='https://a.amap.com/jsapi_demos/static/citys.js'></script>
    <link rel="stylesheet" href="https://a.amap.com/jsapi_demos/static/demo-
center/css/demo-center.css"/>
    <link rel="icon" type="image/x-icon" href="geek.ico">
</head>
<style>
    html, body {
    margin: 0;
    height: 100%;
    width: 100%;
    position: absolute;
    z-index: 0;
}

#container {
    z-index: 0;
    position: fixed;
    top: 0;
    left: 0;
    right: 0;
    bottom: 0;
    width: 100%;
    height: 100%;
}

.button-group {
```

```
    position: absolute;
    bottom: 20px;
    right: 20px;
    font-size: 12px;
    padding: 10px;
}

.button-group .button {
    height: 28px;
    line-height: 28px;
    background-color: #0D9BF2;
    color: #FFF;
    border: 0;
    outline: none;
    padding-left: 5px;
    padding-right: 5px;
    border-radius: 3px;
    margin-bottom: 4px;
    cursor: pointer;
}
.button-group .inputtext {
    height: 26px;
    line-height: 26px;
    border: 1px;
    outline: none;
    padding-left: 5px;
    padding-right: 5px;
    border-radius: 3px;
    margin-bottom: 4px;
    cursor: pointer;
}
 /*
.tip {
    position: absolute;
    bottom: 30px;
    right: 10px;
    background-color: #FFF;
    text-align: center;
    border: 1px solid #ccc;
    line-height: 30px;
    border-radius: 3px;
    padding: 0 5px;
    font-size: 12px;
}
```

```
*/
#tip {
    background-color: #fff;
    padding-left: 10px;
    padding-right: 10px;
    position: absolute;
    font-size: 12px;
    right: 10px;
    top: 20px;
    border-radius: 3px;
    border: 1px solid #ccc;
    line-height: 30px;
}

/*
#tip input[type='button'] {
    margin-top: 10px;
    margin-bottom: 10px;
    background-color: #0D9BF2;
    height: 30px;
    text-align: center;
    line-height: 30px;
    color: #fff;
    font-size: 12px;
    border-radius: 3px;
    outline: none;
    border: 0;
}
*/
.amap-info-content {
    font-size: 12px;
}

#myPageTop {
    position: absolute;
    top: 5px;
    right: 10px;
    background: #fff none repeat scroll 0 0;
    border: 1px solid #ccc;
    margin: 10px auto;
    padding:6px;
    font-family: "Microsoft Yahei", "微软雅黑", "Pinghei";
    font-size: 14px;
}
```

```
#myPageTop label {
    margin: 0 20px 0 0;
    color: #666666;
    font-weight: normal;
}
#myPageTop input {
    width: 170px;
}
#myPageTop .column2{
    padding-left: 25px;
}

</style>
<body>

    <form action="/Traffic" method="get">
        <button type= "submit" class="btn" style="position:relative; margin-right:
500px; z-index: 1;"><b>Check the traffic</b></button>
    </form>

    <form action="/Searching" method="get">
        <button type= "submit" class="btn" style="position:relative; margin-right:
500px; z-index: 1;"><b>Lat / Log</b></button>
    </form>

    <form action="/Bycar" method="get">
        <button type= "submit" class="btn" style="position:relative; margin-right:
500px; z-index: 1;"><b>By Car</b></button>
    </form>

    <form action="/Bybus" method="get">
        <button type= "submit" class="btn" style="position:relative; margin-right:
500px; z-index: 1;"><b>By Bus</b></button>
    </form>

    <form action="/onfeet" method="get">
        <button type= "submit" class="btn" style="position:relative; margin-right:
500px; z-index: 1;"><b>On feet</b></button>
    </form>

    <form action="/Surroundings" method="get">
        <button type= "submit" class="btn" style="position:relative; margin-right:
500px; z-index: 1;"><b>Surround</b></button>
    </form>
```

```
    <form action="/Searching" method="get">
        <button type= "submit" class="btn" style="position:relative; margin-right:
500px; z-index: 1;"><b>Searching</b></button>
    </form>

    <form action="/locatedip" method="get">
        <button type= "submit" class="btn" style="position:relative; margin-right:
500px; z-index: 1;"><b>IP</b></button>
    </form>

    <form action="/home" method="get">
        <button type= "submit" class="btn" style="position:relative; margin-right:
500px; z-index: 1;"><b>Back</b></button>
    </form>



<div id="container"></div>

<div id="myPageTop">
    <form action="/auth/history" method="POST">
        <label for="tipinput">Please Enter:</label>
        <input id="tipinput" placeholder="Destination..." name="tipinput"
class="tipinput">
        <button type="submit">Forward</button>
    </form>
</div>

<script type="text/javascript">
    window._AMapSecurityConfig = {
      securityJsCode: "f6b242cd04daebb47685da20c645bd53",
    };
  </script>
<script type="text/javascript"
src="https://webapi.amap.com/maps?v=2.0&key=c3f65892c3589481fd26d92b375055e0&plugin=
AMap.Geocoder"></script>
<script type="text/javascript">
    //Load the map
    var map = new AMap.Map("container", {
        resizeEnable: true,
        zoom: 13
    });
    //Enter POI
    var autoOptions = {
```

```
        input: "tipinput"
    };

    AMap.plugin(['AMap.PlaceSearch','AMap.AutoComplete'], function(){
        var auto = new AMap.AutoComplete(autoOptions);
        var placeSearch = new AMap.PlaceSearch({
            map: map
        });  //Construct the pleace search method class
        auto.on("select", select);//Listen to the event, when a record is selected,
it will trigger
        function select(e) {
            placeSearch.setCity(e.poi.adcode);
            placeSearch.search(e.poi.name);  //Keyword search
        }
    });

    var trafficLayer = new AMap.TileLayer.Traffic({
        zIndex: 11
    });

    var roadNetLayer = new AMap.TileLayer.RoadNet({
        zIndex: 10
    });

    var layerGroup = new AMap.LayerGroup([trafficLayer, roadNetLayer]);
    layerGroup.setMap(map);

</script>
</body>
</html>
```

13. Onfeet.ejs (\Storage\views\Onfeet.ejs)

```
<!doctype html>
<html>
<head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="initial-scale=1.0, user-scalable=no,
width=device-width">
    <link rel="icon" type="image/x-icon" href="geek.ico">
    <title>Walking Route</title>
    <style type="text/css">
```

```
html,
body,
#container {
    width: 100%;
    height: 100%;
}
#panel {
    position: fixed;
    background-color: white;
    max-height: 90%;
    overflow-y: auto;
    top: 10px;
    right: 10px;
    width: 280px;
}
#panel .amap-call {
    background-color: #009cf9;
    border-top-left-radius: 4px;
    border-top-right-radius: 4px;
}
#panel .amap-lib-walking {
    border-bottom-left-radius: 4px;
    border-bottom-right-radius: 4px;
    overflow: hidden;
}
#myPageTop {
    position: absolute;
    top: 5px;
    left: 10px;
    background: #fff none repeat scroll 0 0;
    border: 1px solid #ccc;
    margin: 10px auto;
    padding:6px;
    font-family: "Microsoft Yahei", "微软雅黑", "Pinghei";
    font-size: 14px;
}

#myPageTop label {
    margin: 0 20px 0 0;
    color: #666666;
    font-weight: normal;
}

#myPageTop input {
```

```
            width: 170px;
        }

        #myPageTop .column2{
            padding-left: 25px;
        }
    </style>
    <link rel="stylesheet" href="https://a.amap.com/jsapi_demos/static/demo-center/css/demo-center.css" />
    <script type="text/javascript">
        window._AMapSecurityConfig = {
          securityJsCode: "f6b242cd04daebb47685da20c645bd53",
        };
    </script>
    <script type="text/javascript" src="https://webapi.amap.com/maps?v=2.0&key=c3f65892c3589481fd26d92b375055e0&plugin=AMap.Walking"></script>
    <script src="https://a.amap.com/jsapi_demos/static/demo-center/js/demoutils.js"></script>
    <script type="text/javascript" src="https://cache.amap.com/lbs/static/addToolbar.js"></script>
</head>
<body>

<form action="/map">
    <button type="submit" style="position: relative; top: 80px; left: 15px;" onclick="history.back()">Back</button>
</form>

<div id="container"></div>
<div id="panel"></div>

<div id="myPageTop">
    <button onclick="conductSearch()"  type="submit">Forward</button>
    <label for="">Begin Lat: </label>
    <input id="tipinput"  value="">
    <label for="">Begin Log: </label>
    <input id="tepinput"  value="">
    <label >Destination Lat: </label>
    <input id="topinput"  value="">
    <label >Destination Log: </label>
    <input id="twpinput"  value="">
</div>
```

```
<script type="text/javascript">

function conductSearch(){

    var value1 = document.getElementById('tipinput').value;
    var value2 = document.getElementById('tepinput').value;
    var value3 = document.getElementById('topinput').value;
    var value4 = document.getElementById('twpinput').value;
    alert(value1+ "," + value2 + "," + value3 + "," + value4);

    var map = new AMap.Map("container", {
        resizeEnable: true,
        center: [value1, value2],//map center
        zoom: 13 //display the zoom level
    });

    //navigation of walking route
    var walking = new AMap.Walking({
        map: map,
        panel: "panel"
    });
    //Plan walking route according to the given coordinates
    walking.search([value1, value2], [value3, value4], function(status, result) {
        // result is the relevant data  https://lbs.amap.com/api/javascript-
api/reference/route-search#m_WalkingResult
        if (status === 'complete') {
            log.success('Successfully create walking route')
        } else {
            log.error('Fail to construct the walking route' + result)
        }
    });
}

</script>
</body>
</html>
```

14. Recommendation.ejs (\Storage\views\Recommendation.ejs)

```
<!DOCTYPE html>
<html lang="zh">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
    <!-- <meta http-equiv="refresh" content="2"> -->
    <title>Recommendation of famous scenic spots</title>
    <link rel="stylesheet"
href="https://maxcdn.bootstrapcdn.com/bootstrap/3.4.1/css/bootstrap.min.css">
    <link rel="icon" type="image/x-icon" href="geek.ico">
    <script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.7.1/jquery.min.js"></script>
    <script
src="https://maxcdn.bootstrapcdn.com/bootstrap/3.4.1/js/bootstrap.min.js"></script>
    <style>
        body {
            font-family: Arial, sans-serif;
            margin: 0;
            padding: 0;
            background-color: #f0f0f0;
        }
        header {
            z-index: 0;
            background-color: #2c3e50;
            color: white;
            text-align: center;
            padding: 20px;
        }
        section {
            padding: 20px;
        }
        h2 {
            color: #2c3e50;
        }
        .destination {
            background-color: white;
            margin: 10px 0;
            padding: 15px;
            border-radius: 8px;
            box-shadow: 0 0 10px rgba(0, 0, 0, 0.1);
        }
        .destination img {
            width: 100%;
            border-radius: 8px;
        }
        .destination p {
            font-size: 1rem;
            color: #555;
        }
```

```css
footer {
    background-color: #2c3e50;
    color: white;
    text-align: center;
    padding: 10px;
    position: fixed;
    bottom: 0;
    width: 100%;
}
.pagination {
    text-align: center;
    padding: 10px 0;
}
.pagination a {
    text-decoration: none;
    color: #2c3e50;
    padding: 10px 20px;
    margin: 0 5px;
    border: 1px solid #2c3e50;
    border-radius: 5px;
    transition: background-color 0.3s ease, color 0.3s ease;
}
.pagination a:hover {
    background-color: #34495e;
    color: white;
    cursor: pointer;
}
.pagination a:active {
    background-color: #2c3e50;
}
.more-link {
    text-decoration: none;
    color: #3498db;
    font-weight: bold;
}
.more-link:hover {
    text-decoration: underline;
}
.button {
    display: inline-block;
    padding: 5px 10px;
    font-size: 16px;
    cursor: pointer;
    text-align: center;
```

```
            text-decoration: none;
            outline: none;
            color: #fff;
            background-color: #04AA6D;
            border: none;
            /* box-shadow: 0 9px #999; */
            position: relative;
            left: 85%;
            top: 6px;
        }
        /* .button:active {
            background-color: #3e8e41;
            box-shadow: 0 5px #666;
            transform: translateY(4px);
        } */
        .button:hover {background-color: #3e8e41}

        #myPageTop {
            position: absolute;
            top: 5px;
            right: 10px;
            background: #fff none repeat scroll 0 0;
            border: 1px solid #ccc;
            margin: 10px auto;
            padding:6px;
            font-family: "Microsoft Yahei", "微软雅黑", "Pinghei";
            font-size: 14px;
        }
        #myPageTop label {
            margin: 0 20px 0 0;
            color: #666666;
            font-weight: normal;
        }
        #myPageTop input {
            width: 170px;
        }
        #myPageTop .column2{
            padding-left: 25px;
        }
    </style>
</head>
<body>

    <header>
```

```
        <h1>Recommended Famouns Scenic Spots</h1>
    </header>

    <form action="/auth/favourite" method="post">
        <input id="tipinput" name="tipinput" class="tipinput" type="text"
placeholder="Record you favourite..." style="position: relative; left: 86%; top:6px;
padding: 4px;">
        <button type="submit" class="button">Store</button>
    </form>

    <form action="/home" method="get">
        <button type="submit" class="btn btn-info" style="position:relative; bottom:
26px; left: 10px; ">Back</button>
    </form>


    <section id="page1">
        <!-- Page 1 -->
        <div class="destination">
            <h2>长城</h2>
            <img src="https://p1.ssl.qhmsg.com/t01de281851cb09666d.jpg" alt="长城">
            <a href="https://zh.wikipedia.org/wiki/%E9%95%BF%E5%9F%8E" class="more-
link">更多</a>
        </div>
        <div class="destination">
            <h2>故宫</h2>
            <img src="https://ts1.tc.mm.bing.net/th/id/R-
C.246e71aad3772cb31c96ffad3bfe0d17?rik=c9Jua%2bJlpltMKA&riu=http%3a%2f%2fn.sinaimg.c
n%2fsinakd20210218ac%2f120%2fw1440h1080%2f20210218%2f5dd5-
kkciesr2099875.jpg&ehk=w3nsnS%2biBN59FiI%2fFFaoGR8LwiyER4JormACP8zGsxw%3d&risl=&pid=
ImgRaw&r=0" alt="故宫">
            <a href="https://zh.wikipedia.org/wiki/%E6%95%85%E5%AE%AB" class="more-
link">更多</a>
        </div>

        <div class="destination">
            <h2>北京博物馆</h2>
            <img src="https://n.sinaimg.cn/sinakd10111/135/w1110h625/20210401/b06b-
knaqvqp0181373.jpg" alt="北京博物馆">
            <a href="https://www.chnmuseum.cn/" class="more-link">更多</a>
        </div>

        <div class="pagination">
            <a href="#" class="next" data-target="page2">下一页</a>
```

```
        </div>
    </section>

    <section id="page2" style="display:none;">
        <!-- Page 2 -->
        <div class="destination">
            <h2>黄山</h2>
            <img src="https://youimg1.c-
ctrip.com/target/0104a120008ah3n3q93E0_D_10000_1200.jpg?proc=autoorient" alt="黄山">
            <a href="https://zh.wikipedia.org/wiki/%E9%BB%84%E5%B1%B1" class="more-
link">更多</a>
        </div>
        <div class="destination">
            <h2>西湖</h2>
            <img src="https://ts1.tc.mm.bing.net/th/id/R-
C.17b13dabedf3612be20ce643bdd36973?rik=wR9nHAhK01ly%2fQ&riu=http%3a%2f%2fimg.pconlin
e.com.cn%2fimages%2fupload%2fupc%2ftx%2fphotoblog%2f1208%2f24%2fc5%2f13180459_131804
59_1345797688052.jpg&ehk=bQ%2b8S%2b%2bbvuV%2bKerPzQMA%2fUoSAzBhIK63EMjKarMPaio%3d&ri
sl=&pid=ImgRaw&r=0" alt="西湖">
            <a href="https://zh.wikipedia.org/wiki/%E8%A5%BF%E6%B9%96" class="more-
link">更多</a>
        </div>

        <div class="pagination">
            <a href="#" class="prev" data-target="page1">上一页</a>
            <a href="#" class="next" data-target="page3">下一页</a>
        </div>
    </section>

    <section id="page3" style="display:none;">
        <!-- Page 3 -->
        <div class="destination">
            <h2>泰山</h2>
            <img
src="https://p6.itc.cn/images01/20210303/59cad55318f34cce8ce2fe86285d9440.jpeg"
alt="泰山">
            <a href="https://zh.wikipedia.org/wiki/%E6%B3%B0%E5%B1%B1" class="more-
link">更多</a>
        </div>
        <div class="destination">
            <h2>丽江古城</h2>
            <img src="https://dynamic-media-cdn.tripadvisor.com/media/photo-
o/0f/16/fe/c6/lijiang-old-town.jpg?w=1200&h=1200&s=1" alt="丽江古城">
```

```
            <a
href="https://zh.wikipedia.org/wiki/%E4%B8%BD%E6%B1%9F%E5%8F%A4%E5%9F%8E"
class="more-link">更多</a>
        </div>

        <div class="pagination">
            <a href="#" class="prev" data-target="page2">上一页</a>
        </div>
    </section>

    <script>
        const pageLinks = document.querySelectorAll('.pagination a');

        pageLinks.forEach(link => {
            link.addEventListener('click', (event) => {
                event.preventDefault();

                const targetPage = link.getAttribute('data-target');
                const currentPage = link.closest('section');

                currentPage.style.display = 'none';

                document.getElementById(targetPage).style.display = 'block';
            });
        });
        document.getElementById('page1').style.display = 'block';
    </script>
</body>
</html>
```

15. register.hbs (\Storage\views\register.hbs)

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta http-equiv="X-UA-Compitable" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link rel="stylesheet"
href="https://fonts.googleapis.com/css2?family=Noto+Sans:wght@400;600&display=swap">
```

```
    <link rel="stylesheet"
href="https://cdn.jsdelivr.net/npm/bootstrap@4.6.2/dist/css/bootstrap.min.css">
    <link rel="icon" type="image/x-icon" href="geek.ico">
    <script
src="https://cdn.jsdelivr.net/npm/jquery@3.7.1/dist/jquery.slim.min.js"></script>
    <script
src="https://cdn.jsdelivr.net/npm/popper.js@1.16.1/dist/umd/popper.min.js"></script>
    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@4.6.2/dist/js/bootstrap.bundle.min.js"><
/script>
    <link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.1.3/dist/css/bootstrap.min.css"
rel="stylesheet"
        integrity="sha384-
1BmE4kWBq78iYhFldvKuhfTAU6auU8tT94WrHftjDbrCEXSU1oBoqyl2QvZ6jIW3"
crossorigin="anonymous">
    <title>Map System</title>
    <style>
        * {
            margin: 0;
            padding: 0;
            box-sizing: border-box;
            font-family: 'Poppins', sans-serif;
        }
        body{
            color: #ffffff;
            display: flex;
            align-items: center;
            justify-content: center;
            min-height: 100vh;
            background: url('/Mode2.jpg') no-repeat;
            background-size: cover;
            background-position: center;
        }
        .dontainer{
            max-width: 700px;
            padding: 0 15px;
            margin: auto;
        }
        .wrapper .field-holder{
            position: relative;
            margin-bottom: 1.25em;
        }
        .field-holder input{
```

```
    width: 100%;
}
input{
    border: 0;
    border-bottom: 3px solid #dfdfdf;
    outline: none;
    background: transparent;
    color: #dfdfdf;
}
label{
    position: absolute;
    top: 0;
    left: 0;
    font-size: 1em;
    color: #ffffff;
    display: flex;
    align-items: center;
    cursor: text;
    transition: 0.2s ease-in-out;
}
input,label{
    font-size: 1em;
    width: 60%;
    height: 55px;
    background: transparent;
}
input:focus + label,
input:valid + label{
    color: #424242;
    font-size: .75em;
    top: -25px;
    pointer-events: none;
}
input:focus
input:valid{
    border-bottom: 3px solid #424242;
}
.wrapper{
    width: 500px;
    background: transparent;
    color: #ffffff;
    border-radius: 10px;
    padding: 30px 40px;
    border: 2px solid rgba(255, 255, 255, 0.2);
```

```
            backdrop-filter: blur(20px);
        }
        .wrapper h1{
            font-size: 36px;
            text-align: center;
        }
        .wrapper .btn{
            width: 100%;
            height: 45px;
            background: #ffffff;
            border: none;
            outline: none;
            border-radius: 40px;
            cursor: pointer;
            font-size: 16px;
            font-weight: 60;
        }



    </style>
</head>
<body>


    <div class="wrapper">
        <div class="dontainer">
            <h1>Register</h1>
            <form action="/auth/register" method="POST">
                <div class="field-holder">
                    <input type="text" name="account" id ="account" required>
                    <label for="account">Account</label>
                 </div>

                <div class="field-holder">
                    <input type="password" name="password" id="password" required>
                    <label for="password">Password</label>
                </div>

                <form>
                    <button type= "submit" class="btn">Register</button>
                </form>
            </form>
        </div>
```

```
        {{#if message}}
            <h4 class="alert alert-danger mt-4">{{message}}</h4>
        {{/if}}
    </div>


    <script
src="https://cdn.jsdelivr.net/npm/@popperjs/core@2.11.8/dist/umd/popper.min.js"
integrity="sha384-I7E8VVD/ismYTF4hNIPjVp/Zjvgyol6VFvRkX/vR+Vc4jQkC+hVqc2pM8ODewa9r"
crossorigin="anonymous"></script>
    <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.min.js"
integrity="sha384-0pUGZvbkm6XF6gxjEnlmuGrJXVbNuzT9qBBavbLwCsOGabYfZo0T0to5eqruptLy"
crossorigin="anonymous"></script>


</body>
</html>
```

16. Searching.ejs (\Storage\views\Searching.ejs)

```
<!doctype html>
<html>
<head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="initial-scale=1.0, user-scalable=no,
width=device-width">
    <title>Geographical Code</title>
    <link rel="stylesheet" href="https://a.amap.com/jsapi_demos/static/demo-
center/css/demo-center.css"/>
    <link rel="icon" type="image/x-icon" href="geek.ico">
    <style>
        html,body,#container{
            height:100%;
            width:100%;
        }
        .btn{
            width:10rem;
            margin-left:6.8rem;
        }
    </style>
</head>
<body>
<div id="container"></div>
```

```
<div class="input-card" style='width:28rem;'>
    <label style='color:grey'>Through POI search lattitude and longitude</label>
    <div class="input-item">
            <div class="input-item-prepend"><span class="input-item-
text" >location</span></div>
            <input id='address' type="text" value='' >
    </div>
    <div class="input-item">
            <div class="input-item-prepend"><span class="input-item-text">lat &
log</span></div>
            <input id='lnglat' disabled type="text">
    </div>
    <input id="geo" type="button" class="btn" value="location -> lat & log" />
    <button onclick="history.back()" class="btn">Back</button>
</div>
<script src="https://a.amap.com/jsapi_demos/static/demo-
center/js/demoutils.js"></script>
<script type="text/javascript">
    window._AMapSecurityConfig = {
      securityJsCode: "f6b242cd04daebb47685da20c645bd53",
    };
  </script>
<script type="text/javascript"
src="https://webapi.amap.com/maps?v=2.0&key=c3f65892c3589481fd26d92b375055e0&plugin=
AMap.Geocoder"></script>
<script type="text/javascript">
    var map = new AMap.Map("container", {
        resizeEnable: true
    });

    var geocoder = new AMap.Geocoder({
        city: "",
    });

    var marker = new AMap.Marker();
    function geoCode() {
        var address  = document.getElementById('address').value;
        geocoder.getLocation(address, function(status, result) {
            if (status === 'complete'&&result.geocodes.length) {
                var lnglat = result.geocodes[0].location
                document.getElementById('lnglat').value = lnglat;
                marker.setPosition(lnglat);
                map.add(marker);
                map.setFitView(marker);
```

```
            }else{
                log.error('Failed to get the location information');
            }
        });
    }
    document.getElementById("geo").onclick = geoCode;
    document.getElementById('address').onkeydown = function(e) {
        if (e.keyCode === 13) {
            geoCode();
            return false;
        }
        return true;
    };

</script>
</body>
</html>
```

17. surroundings.ejs (\Storage\views\surroundings.ejs)

```
<!doctype html>
<html>
<head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="initial-scale=1.0, user-scalable=no,
width=device-width">
    <title>Surrounded Places</title>
    <link rel="stylesheet" href="https://cache.amap.com/lbs/static/main1119.css"/>
    <link rel="stylesheet"
href="https://maxcdn.bootstrapcdn.com/bootstrap/3.4.1/css/bootstrap.min.css">
    <link rel="icon" type="image/x-icon" href="geek.ico">
    <script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.7.1/jquery.min.js"></script>
    <script
src="https://maxcdn.bootstrapcdn.com/bootstrap/3.4.1/js/bootstrap.min.js"></script>
    <style type="text/css">
        #panel {
            position: fixed;
            z-index: 1;
            background-color: white;
            max-height: 90%;
            overflow-y: auto;
            top: 10px;
```

```
            right: 10px;
            width: 280px;
            border-bottom: solid 1px silver;
        }
        #myPageTop {
            position: absolute;
            top: 5px;
            left: 10px;
            background: #fff none repeat scroll 0 0;
            border: 1px solid #ccc;
            margin: 10px auto;
            padding:6px;
            font-family: "Microsoft Yahei", "微软雅黑", "Pinghei";
            font-size: 14px;
        }
        #myPageTop label {
            margin: 0 20px 0 0;
            color: #666666;
            font-weight: normal;
        }
        #myPageTop input {
            width: 170px;
        }
        #myPageTop .column2{
            padding-left: 25px;
        }
    </style>

<script type="text/javascript">
    window._AMapSecurityConfig = {
      securityJsCode: "f6b242cd04daebb47685da20c645bd53",
    };
  </script>
<script type="text/javascript"
src="https://webapi.amap.com/maps?v=2.0&key=c3f65892c3589481fd26d92b375055e0&plugin=
AMap.Geocoder"></script>
    <script type="text/javascript"
src="https://cache.amap.com/lbs/static/addToolbar.js"></script>
</head>
<body>



<div id="myPageTop">
```

```
    <button onclick="searchfunction()">Submit</button>
    <label>Preferences:</label>
    <input id="praferences" value="">
    <label>Preferences Lat:</label>
    <input id="preferences" value="">
    <label>Preferences Lng:</label>
    <input id="proferences" value="">
    <label>Type of Preferences: 科教文化服务, 交通设施服务, 汽车服务</label>

</div>

<form action="/map" method  ="get">
    <button type="submit" class="btn btn-info" style="position: relative; top: 60px;
left: 10px; z-index: 1;">Back</button>
</form>

<div id="container"></div>
<div id="panel"></div>
<script type="text/javascript">
function searchfunction(){

    var value0 = document.getElementById('praferences').value;
    var value1 = document.getElementById('preferences').value;
    var value2 = document.getElementById('proferences').value;
    alert("Your Preference:" + value0 + " "+ value1 + " " + value2);

    var map = new AMap.Map("container", {
        resizeEnable: true
    });
    AMap.plugin(["AMap.PlaceSearch"], function() {
        //Construct a location query class
        var placeSearch = new AMap.PlaceSearch({
            type: value0, // Point of interest categories
            pageSize: 5, // Number of results displayed per page
            pageIndex: 1, // pagenumber
            city: "060", // Points of Interest Cities
            citylimit: true,  //Whether to restrict searches to the specified city
            map: map, // Map example showing the results
            panel: "panel", // The result list will be displayed in this container.
            autoFitView: true // Whether to automatically adjust the map view so
that all drawn. Marker points are within the visible range of the viewport
        });
```

```
        var cpoint = [value1,value2]; //Center point
        placeSearch.searchNearBy('', cpoint, 500, function(status, result) {

        });
    });
}
</script>
</body>
</html>
```

18. Traffic.ejs (\Storage\views\Traffic.ejs)

```
<!doctype html>
<html>
<head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="initial-scale=1.0, user-scalable=no,
width=device-width">
    <title>Check Your Traffic Condition</title>
    <link rel="stylesheet" href="https://a.amap.com/jsapi_demos/static/demo-
center/css/demo-center.css">
    <link rel="icon" type="image/x-icon" href="geek.ico">
    <script type="text/javascript">
        window._AMapSecurityConfig = {
          securityJsCode: "f6b242cd04daebb47685da20c645bd53",
        };
      </script>
    <script
src="https://webapi.amap.com/maps?v=2.0&key=c3f65892c3589481fd26d92b375055e0"></scri
pt>
    <script src='https://a.amap.com/jsapi_demos/static/citys.js'></script>
    <style>
        html,
        body,
        #container {
            margin: 0;
            padding: 0;
            width: 100%;
            height: 100%;
        }
    </style>
</head>
<body>
```

```
<div id="container"></div>
<div class="input-card" style="width: auto;">
    <div class="input-item">
        <button class="btn" onclick="layerGroup.hide()">Hide</button>
    </div>
    <div class="input-item">
        <button class="btn" onclick="layerGroup.show()">Show</button>
    </div>
    <div class="input-item">
        <button class="btn" onclick="layerGroup.setOptions({ opacity:
Math.random() })">Transparency</button>
    </div>
    <div class="input-item">
        <button class="btn" onclick="layerGroup.reload()">Reload</button>
    </div>
    <div class="input-item">
        <form action="/map" method="get">
            <button class="btn">Back</button>
        </form>
    </div>

</div>
<script language="javascript">
    var map = new AMap.Map('container', {
        center: [116.40, 39.91],
        zoom: 13
    });

    var trafficLayer = new AMap.TileLayer.Traffic({
        zIndex: 11
    });

    var roadNetLayer = new AMap.TileLayer.RoadNet({
        zIndex: 10
    });


    var layerGroup = new AMap.LayerGroup([trafficLayer, roadNetLayer]);
    layerGroup.setMap(map);
</script>
</body>
</html>
```

19. travellinghistory.ejs (\Storage\views\travellinghistory.ejs)

```
<!doctype html>
<html lang="en">
    <head>
        <!-- Required meta tags -->
        <meta charset="utf-8">
        <meta name="viewport" content="width=device-width, initial-scale=1">

        <!-- Bootstrap CSS -->
        <link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstrap.min.css"
rel="stylesheet" integrity="sha384-
EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65VohhpuuCOmLASjC"
crossorigin="anonymous">
        <link rel="icon" type="image/x-icon" href="geek.ico">

        <title></title>
    </head>
    <body>
        <div class="container">
            <h1 class="text-center mt-3 mb-3"><%= title %></h1>

            <% if(action == 'add') { %>

            <div class="card">
                <div class="card-header">Sample Form</div>
                <div class="card-body">
                    <form method="POST" action="/auth/add_sample_data">
                        <div class="row">
                            <div class="col-md-6">
                                <div class="mb-3">
                                    <label>Searched destination</label>
                                    <input type="text" name="last_name"
id="last_name" class="form-control" />
                                </div>
                            </div>
                        </div>
                        </div>
                        <div class="mb-3">
                            <input type="submit" name="submit_button" class="btn
btn-primary" value="Add" />
                        </div>
                    </form>
                </div>
```

```
            </div>

            <% } else if(action == 'edit') { %>
            <div class="card">
                <div class="card-header">Sample Form</div>
                <div class="card-body">
                    <form method="POST" action="/auth/edit_sample_data">
                        <div class="row">
                            <div class="col-md-6">
                                <div class="mb-3">
                                    <label>id</label>
                                    <input type="text" name="first_name"
id="first_name" class="form-control" value="<%= sampleData.first_name %>" />
                                </div>
                            </div>
                            <div class="col-md-6">
                                <div class="mb-3">
                                    <label>Changed destination</label>
                                    <input type="text" name="last_name"
id="last_name" class="form-control" value="<%= sampleData.last_name %>" />
                                </div>
                            </div>
                        </div>
                        </div>
                        <div class="mb-3">
                            <input type="submit" name="submit_button" class="btn
btn-primary" value="Edit" style="position: relative; left: 20px;">
                        </div>
                    </form>
                </div>
            </div>
            <% } else { %>
                <% if(message.length > 0) { %>
                <div class="alert alert-success">
                    <%= message %>
                </div>
                <% } %>
            <div class="card">
                <div class="card-header">
                    <div class="row">
                        <div class="col">Sample Data</div>
                        <div class="col">
                            <!-- <a href="/routes/pages.js/add" class="btn btn-
success btn-sm float-end">Add</a> -->
```

```
                        <a href="/home" class="btn btn-success btn-sm float-end"
style="position: relative; right: 30px;">Back</a>
                    </div>
                </div>
            </div>
            <div class="card-body">
                <div class="table-responsive">
                    <table class="table table-bordered">
                        <tr>
                            <th>id</th>
                            <th>start lattitude</th>
                            <th>start longitude</th>
                            <th>end lattitude</th>
                            <th>end longitude</th>
                            <th>Travelling mode</th>
                            <th>Time</th>
                            <!-- <th>Action</th> -->
                        </tr>
                        <%
                        if(sampleData.length > 0)
                        {
                            sampleData.forEach(function(data){
                        %>
                        <tr>
                            <td><%= data.idd %></td>
                            <td><%= data.tipinput %></td>
                            <td><%= data.tepinput %></td>
                            <td><%= data.topinput %></td>
                            <td><%= data.twpinput %></td>
                            <td><%= data.choice %></td>
                            <td><%= data.time %></td>
                            <!-- <td>
                                <a href="/routes/pages.js/edit/<%= data.idd %>"
class="btn btn-primary btn-sm">Edit</a>
                                <a href="/routes/pages.js/delete/<%=
data.idd %>" class="btn btn-danger btn-sm">Delete</a>
                            </td> -->
                        </tr>
                        <%
                            });
                        }
                        else
                        {
                        %>
```

```
                            <tr>
                                <td colspan="5">No Data Found</td>
                            </tr>
                            <%
                            }
                            %>
                        </table>
                    </div>
                </div>
            </div>

            <% } %>

        </div>

        <script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.bundle.min.js"
integrity="sha384-MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/tWtIaxVXM"
crossorigin="anonymous"></script>
    </body>
</html>
```

20. .env (\Storage\.env)

```
MYSQL_HOST='127.0.0.1'
MYSQL_USER='root'
MYSQL_PASSWORD=''
MYSQL_DATABASE='ap'
```

21. server.js (\Storage\server.js)

```
const express = require("express");
const app = express()
const mysql = require("mysql")
const dotenv = require("dotenv")
const path = require("path")
dotenv.config({path: "./.env"})

var cookieParser = require('cookie-parser');
var flash = require('connect-flash');
var session = require('express-session');


const db = mysql.createConnection({
  host: process.env.MYSQL_HOST,
```

```
  user: process.env.MYSQL_USER,
  password: process.env.MYSQL_PASSWORD,
  database: process.env.MYSQL_DATABASE
})

db.connect((error) =>{
  if(error){
    console.log(error)
  }else{
    console.log("Database connected...")
  }
})


app.use(session({
  secret : 'webslesson',
  cookie : {maxAge : 60000},
  saveUninitialized : false,
  resave : false
}));

app.set("view engine", "ejs")
app.engine('ejs', require('ejs').__express)
app.use(express.static("public"))
app.set("view engine", "hbs")
app.engine('hbs', require('hbs').__express)


//define routes
app.use(express.urlencoded({extended: false}))
app.use(express.json())
app.use(cookieParser());
app.use(flash());

app.use("/", require("./routes/pages"))
app.use("/auth", require("./routes/auth"))
app.use("/js", express.static(__dirname + " /public/js"))
app.use("/css", express.static(__dirname + " /public/css"))


const publicDirectory = path.join(__dirname, "./public")
app.use(express.static(publicDirectory))


app.use(function(err, req, res, next) {
```

```
  // set locals, only providing error in development
  res.locals.message = err.message;
  res.locals.error = req.app.get('env') === 'development' ? err : {};

  // render the error page
  res.status(err.status || 500);
  res.render('error');
});



const port = 3000;
app.listen(port, () => {
    console.log(`Listening at http://localhost:${port}`)
})
```