

SJTU-JiaoJiao

SJTU JiaoJiao backend API document

Auth

Auth - GetAuth

Redirect to OAuth url

GET

http://localhost:8080/v1/auth

权限: none

参数

字段	类型	描述
code	可选 string	OAuth code callback, DO NOT call it by yourself

No param - Redirect 301

字段	类型	描述
url	Redirect	Redirect to OAuth url

With param - Success 200

字段	类型	描述
Response	--	see Auth service [#api-Service-auth_Auth_Auth]

Error 500

名称	描述
AuthServiceDown	Auth service down

User

User - AddUser

Add user, use default value.

PUT

http://localhost:8080/v1/user

权限: admin

参数

字段	类型	描述
Param	--	see User Service [#api-Service-user_User_Create]

Success 200

字段	类型	描述
response	Response	see User Service [#api-Service-user_User_Create]

Error 500

名称	描述
UserServiceDown	User service down

User - FindUser

Find user

GET

http://localhost:8080/v1/user

权限: none/admin

参数

字段	类型	描述
Param	--	see User Service [#api-Service-user_User_Find] No param need admin permission!

Success 200

字段	类型	描述
response	Response	see User Service [#api-Service-user_User_Find] None - studentId: hidden None - studentName: hidden

Error 500

名称	描述
UserServiceDown	User service down

User - GetUserInfo

Get user info

GET

http://localhost:8080/v1/user/:userId

权限: none/self

参数

字段	类型	描述
Param	--	see User Service [#api-Service-user_User_Query]

None - Success 200

字段	类型	描述
response	Response	see User Service [#api-Service-user_User_Query] studentId: hidden studentName: hidden

Self - Success 200

字段	类型	描述
response	Response	see User Service [#api-Service-user_User_Query]

Error 500

名称	描述
UserServiceDown	User service down

User - UpdateUser

Update user

POST

http://localhost:8080/v1/user

权限: self/admin

参数

字段	类型	描述
Param	--	see User Service [#api-Service-user_User_Update]

Success 200

字段	类型	描述
response	Response	see User Service [#api-Service-user_User_Update]

Error 500

名称	描述
UserServiceDown	User service down

SellInfo

SellInfo - AddContent

Add sell info content

PUT

http://localhost:8080/v1/content

权限: user/admin

参数

字段	类型	描述
Param	--	see SellInfo Service [#api-Service-sellinfo_Content_Create]

Success 200

字段	类型	描述
response	Response	see SellInfo Service [#api-Service-sellinfo_Content_Create]

Error 500

名称	描述
SellInfoServiceDown	SellInfo service down

SellInfo - AddSellInfo

Add sell info

PUT

http://localhost:8080/v1/sellInfo

权限: self/admin

参数

字段	类型	描述
Param	--	see SellInfo Service [#api-Service-sellinfo_SellInfo_Create]

Success 200

字段	类型	描述
response	Response	see SellInfo Service [#api-Service-sellinfo_SellInfo_Create]

Error 500

名称	描述
SellInfoServiceDown	SellInfo service down

SellInfo - FindSellInfo

Find sell info

GET

http://localhost:8080/v1/sellInfo

权限: none

参数

字段	类型	描述
Param	--	see SellInfo Service [#api-Service-sellinfo_SellInfo_Find]

Success 200

字段	类型	描述
response	Response	see SellInfo Service [#api-Service-sellinfo_SellInfo_Find]

Error 500

名称	描述
SellInfoServiceDown	SellInfo service down

SellInfo - GetSellInfo

Get sell info

GET

http://localhost:8080/v1/sellInfo/:sellInfoId

权限: none

参数

字段	类型	描述
Param	--	see SellInfo Service [#api-Service-sellinfo_SellInfo_Query]

Success 200

字段	类型	描述
response	Response	see SellInfo Service [#api-Service-sellinfo_SellInfo_Query]

Error 500

名称	描述
SellInfoServiceDown	SellInfo service down

Service

Service - auth.Auth.Auth

Check OAuth code.

RPC

http://localhost:8080/v1/rpc

参数

字段	类型	描述
code	string	OAuth code.

Success 200

字段	类型	描述
status	int32	-1 for invalid param 1 for success 2 for invalid code
token	string	verified token when status=1

Error 500

名称	描述
OAuthServerDown	can't connect to OAuth server

Service - sellinfo.Content.Create

create sell info content

RPC

http://localhost:8080/v1/rpc

参数

字段	类型	描述
contentId 可选	string	24 bytes content id, left empty for first upload
contentToken 可选	string	content token, left empty for first upload
content	bytes	binary content
type	int32	1 for picture 2 for video

Success 200

字段	类型	描述
status	int32	-1 for invalid param 1 for success 2 for invalid token

字段	类型	描述
contentId	string	24 bytes contentId
contentToken	string	random uuid content token

Error 500

名称	描述
DBServerDown	can't connect to database server

Service - sellinfo.SellInfo.Create

create sell info

RPC

http://localhost:8080/v1/rpc

参数

字段	类型	描述
userId	int32	sellinfo userid
validTime	int64	valid timestamp
goodName	string	good name
description	<small>可选</small> string	description for good
price	<small>可选</small> double	good price
contentId	<small>可选</small> string	content id of good
contentToken	<small>可选</small> string	content token

Success 200

字段	类型	描述
status	int32	-1 for invalid param 1 for success 2 for invalid token
sellInfoId	int32	created sellInfoId

Error 500

名称	描述
DBServerDown	can't connect to database server

Service - sellinfo.SellInfo.Find

Find SellInfo.

RPC

http://localhost:8080/v1/rpc

参数

字段		类型	描述
userId	可选	int32	userId
limit		uint32	row limit 默认值: 100
offset		uint32	row offset 默认值: 0

Success 200

字段	类型	描述
sellInfo	list	see SellInfo Service [#api-Service-sellinfo_SellInfo_Query]

Error 500

名称	描述
DBServerDown	can't connect to database server

Service - sellinfo.SellInfo.Query

Query sell info

RPC

http://localhost:8080/v1/rpc

参数

字段	类型	描述
sellInfoId	int32	sellInfo id.

Success 200

字段	类型	描述
sellInfoId	int32	sellInfoId
sellInfoState	int32	1 for selling 2 for reserved 3 for done 4 for expired

字段	类型	描述
releaseTime	int64	sellInfo release time
validTime	int64	sellInfo validate time
goodName	string	good name
price	double	good price
description	string	good description
contentId	string	multimedia data
userId	int32	userId

Error 500

名称	描述
DBServerDown	can't connect to database server

Service - user.AdminUser.Create

Create new admin user.

RPC

http://localhost:8080/v1/rpc

参数

字段	类型	描述
studentId	string	student id.

Success 200

字段	类型	描述
status	int32	-1 for invalid param 1 for success 2 for exist user
adminId	int32	created or existed adminId

Error 500

名称	描述
DBServerDown	can't connect to database server

Service - user.AdminUser.Find

Find admin user.

RPC

http://localhost:8080/v1/rpc

参数

字段	类型	描述
studentId	string	student id.

Success 200

字段	类型	描述
status	int32	-1 for invalid param 1 for success 2 for not found
adminId	int32	

Error 500

名称	描述
DBServerDown	can't connect to database server

Service - user.User.Create

Create new user.

RPC

http://localhost:8080/v1/rpc

参数

字段	类型	描述
studentId	string	student id.
studentName	string	student name.

Success 200

字段	类型	描述
status	int32	-1 for invalid param 1 for success 2 for exist user
userId	int32	created or existed userid

Error 500

名称	描述
----	----

名称	描述
DBServerDown	can't connect to database server

Service - user.User.Find

Find user(fuzzy).

RPC

http://localhost:8080/v1/rpc

参数

字段	类型	描述
userName 可选	string	username
limit	uint32	row limit 默认值: 100
offset	uint32	row offset 默认值: 0

Success 200

字段	类型	描述
user	list	see User Service [#api-Service-user_User_Query]

Error 500

名称	描述
DBServerDown	can't connect to database server

Service - user.User.Query

Query user info.

RPC

http://localhost:8080/v1/rpc

参数

字段	类型	描述
userId	int32	user id

Success 200

字段	类型	描述
----	----	----

字段	类型	描述
userId	int32	user id
userName	string	user name
avatarId	string	user avatar id
telephone	string	user telephone
studentId	string	student id
studentName	string	student name
status	int32	user status, 1 for normal 2 for frozen

Error 500

名称	描述
DBServerDown	can't connect to database server

Service - user.User.Update

Update user info, only update provided field. If clearEmpty=1 and param support allow clear, clear the field when not provided.

RPC

http://localhost:8080/v1/rpc

参数

字段		类型	描述
userId		int32	user id
userName	可选	string	user name
avatarId	可选	string	user avatar id
telephone	可选	string	user telephone, allow clear
studentId	可选	string	student id
studentName	可选	string	student name
status		int32	user status, 1 for normal 2 for frozen

字段	类型	描述
clearEmpty	bool	clear the empty field 默认值: 0

Success 200

字段	类型	描述
status	int32	-1 for invalid param 1 for success 2 for user not found

Error 500

名称	描述
DBServerDown	can't connect to database server

基于 apidoc [http://apidocjs.com] 0.17.7 - 2019-07-15T01:03:58.442Z