

```
@Component
@Getter
@PropertySource(value="classpath:/db.properties")
public class DataBaseProperties {
    @NonNull
    @Value("${db.username}")
    private String username;
    @NonNull
    @Value("${db.password}")
    private String password;
    @NonNull
    @Value("${db.driverClassName}")
    private String driverClassName;
    @NonNull
    @Value("${db.url}")
    private String url;
    @NonNull
    @Value("${db.initialSize}")
    private Integer initialSize;
    @NonNull
    @Value("${db.maxTotal}")
    private Integer maxTotal;
    @NonNull
    @Value("${db.maxIdle}")
    private Integer maxIdle;
    @NonNull
    @Value("${db.minIdle}")
    private Integer minIdle;
    @NonNull
    @Value("${db.maxWaitMillis}")
    private Integer maxWaitMillis;
    @NonNull
    @Value("${db.validationQuery}")
    private String validationQuery;
    @NonNull
    @Value("${db.testOnBorrow}")
    private String testOnBorrow;

    public boolean isTestOnBorrow() {
        return testOnBorrow.equals("true");
    }
}
```

```
@EnableJpaRepositories(basePackageClasses = RepositoryBase.class)
@Configuration
```

```

public class JpaConfig {
    @Bean
    LocalContainerEntityManagerFactoryBean entityManagerFactory(DataSource
dataSource){
    LocalContainerEntityManagerFactoryBean emf = new
LocalContainerEntityManagerFactoryBean();
    emf.setDataSource(dataSource);

    emf.setPackagesToScan("com.nhnacademy.springboard.spirngmvcboard.entity");
    emf.setJpaVendorAdapter(jpaVendorAdapter());
    emf.setJpaProperties(jpaProperties());
    return emf;
}
private JpaVendorAdapter jpaVendorAdapter(){
    HibernateJpaVendorAdapter hibernateJpaVendorAdapter = new
HibernateJpaVendorAdapter();
    hibernateJpaVendorAdapter.setDatabase(Database.MYSQL);
    return hibernateJpaVendorAdapter;
}
private Properties jpaProperties(){
    Properties jpaProperties= new Properties();
    jpaProperties.setProperty("hibernate.show_sql", "true");
    jpaProperties.setProperty("hibernate.format_sql", "true");
    jpaProperties.setProperty("hibernate.use_sql_comments", "true");
    jpaProperties.setProperty("hibernate.globally_quoted_identifiers",
"true");
    jpaProperties.setProperty("hibernate.temp.use_jdbc_metadata_defaults",
"false");

    return jpaProperties;
}
    @Bean
    public PlatformTransactionManager
transactionManager(EntityManagerFactory entityManagerFactory){
        JpaTransactionManager jpaTransactionManager = new
JpaTransactionManager();
        jpaTransactionManager.setEntityManagerFactory(entityManagerFactory);
        return jpaTransactionManager;
    }
}

```

- service
- com/nhnacademy/springboard/spirngmvcboard/service/BoardService.java
- com/nhnacademy/springboard/spirngmvcboard/service/PostService.java
- com/nhnacademy/springboard/spirngmvcboard/service/UserService.java

```

public interface UserService {
    User createUser(User user);
    User getUser(String email);
}

```

```
User modifyUser(User user);
}
```

```
public interface PostService {
    Post createPost(Post post);
    Post getPost(String postId);
    Post modifyPost(Post post);
    List<Post> findByUserId(String userId);
    List<Post> findByBoardId(String boardId);
}
```

```
public interface BoardService {
    Board createBoard(Board board);
    Board getBoard(String boardId);
    Board modifyBoard(Board board);
    List<Board> findAll();

}
```

- service.impl
- com/nhnacademy/springboard/spirngmvcboard/service/impl/BoardServiceImpl.java
- com/nhnacademy/springboard/spirngmvcboard/service/impl/PostServiceImpl.java
- com/nhnacademy/springboard/spirngmvcboard/service/impl/UserServiceImpl.java

```
@Service
@RequiredArgsConstructor
public class BoardServiceImpl implements BoardService {
    private final BoardRepository boardRepository;

    @Override
    public Board createBoard(Board board) {
        return boardRepository.save(board);
    }

    @Override
    public Board getBoard(String boardId) {
        Optional<Board> boardOptional = boardRepository.findById(boardId);
        return boardOptional.orElse(null);
    }

    @Override
    public Board modifyBoard(Board board) {
        Optional<Board> boardOptional =
```

```
boardRepository.findById(String.valueOf(board.getBoardId()));
    if (boardOptional.isPresent()) {
        Board existingBoard = boardOptional.get();
        existingBoard.setBoardName(board.getBoardName());
        existingBoard.setDescription(board.getDescription());
        return boardRepository.save(existingBoard);
    } else {
        return null;
    }
}

@Override
public List<Board> findAll() {
    return boardRepository.findAll();
}
}
```

```
@Service
@RequiredArgsConstructor
@Transactional
public class PostServiceImpl implements PostService {
    private final PostRepository postRepository;

    @Override
    public Post createPost(Post post) {
        return postRepository.save(post);
    }

    @Override
    public Post getPost(String postId) {
        Optional<Post> postOptional = postRepository.findById(postId);
        return postOptional.orElse(null);
    }

    @Override
    public Post modifyPost(Post post) {
        Optional<Post> postOptional =
postRepository.findById(post.getPk().toString());
        if (postOptional.isPresent()) {
            Post existingPost = postOptional.get();
            existingPost.setTitle(post.getTitle());
            existingPost.setContent(post.getContent());
            return postRepository.save(existingPost);
        } else {
            return null;
        }
    }

    @Override
```

```
public List<Post> findByPkUserId(String userId) {
    List<Post> allPosts = postRepository.findAll();
    return allPosts.stream()
        .filter(post -> post.getPk().getAuthorId().equals(userId))
        .collect(Collectors.toList()); }

@Override
public List<Post> findByPkBoardId(String boardId) {
    List<Post> allPosts = postRepository.findAll();
    return allPosts.stream()
        .filter(post -> post.getPk().getBoardId().equals(boardId))
        .collect(Collectors.toList()); }
}
```

```
@Service
@RequiredArgsConstructor
public class UserServiceImpl implements UserService {

    private final UserRepository userRepository;

    @Override
    public User createUser(User user) {
        return userRepository.save(user);
    }

    @Override
    public User getUserById(String id) {
        return userRepository.findById(id).orElse(null);
    }

    @Override
    public User getUserByEmail(String email) {
        List<User> allUsers = userRepository.findAll();
        Optional<User> userByEmail = allUsers.stream()
            .filter(user -> user.getEmail().equals(email))
            .findFirst();
        return userByEmail.orElse(null);
    }

    @Override
    public User modifyUser(User user) {
        Optional<User> existingUser =
            userRepository.findById(String.valueOf(user.getUserId()));

        if (existingUser.isPresent()) {
            User modifiedUser = existingUser.get();
            modifiedUser.setEmail(user.getEmail());
            modifiedUser.setUsername(user.getUsername());
            modifiedUser.setPassword(user.getPassword());
        }
    }
}
```

```

        // 추가적으로 수정하고자 하는 필드들이 있다면 여기에서 수정하세요.

        return userRepository.save(modifiedUser);
    } else {
        return null;
    }
}

@Override
public List<User> findAll() {
    return userRepository.findAll();
}
}

```

```

@Getter
@Setter
public class FindPasswordRequest {
    private String email;
    private String password;
}

```

```

@Getter
@Setter
public class LoginRequest {
    @NotBlank(message="이메일을 입력하세요")
    private String email;
    @NotBlank(message="비밀번호를 입력하세요")
    private String pwd;

    @Getter
    @Setter
    public static class FindIdRequest {
        private String email;

        // 생성자, getter, setter
    }
}

```

```

@Slf4j
@Service
@RequiredArgsConstructor
public class LoginService {
    private final UserMapper userMapper;
}

```

```

    public boolean isValid(LoginRequest loginRequest) {
        User user = userMapper.findByUseremail(loginRequest.getEmail());
        boolean result = user != null &&
        user.getPassword().equals(loginRequest.getPwd());
        log.info("isValid : {}", result);
        return result;
    }
}

```

- com/nhnacademy/springboard/spirngmvcboard/thymeleaf
- com/nhnacademy/springboard/spirngmvcboard/thymeleaf/CustomTagDialect.java
- com/nhnacademy/springboard/spirngmvcboard/thymeleaf/TagUtils.java

```

//todo#15 CustomTagDialect 생성 , 커스텀 함수를 사용하기위해서 IDialect 확장한
IExpressionObjectDialect 구현.
public class CustomTagDialect extends AbstractDialect implements
IExpressionObjectDialect {

    public CustomTagDialect() {
        super("nhnacademy");
    }

    @Override
    public IExpressionObjectFactory getExpressionObjectFactory() {
        return new SpringStandardExpressionObjectFactory(){
            @Override
            public Set<String> getAllExpressionObjectNames() {
                return Collections.singleton("nhnacademy");
            }

            @Override
            public Object buildObject(IExpressionContext context, String
expressionObjectName) {
                super.buildObject(context, expressionObjectName);
                //todo#15 미리 만들어 뒀던 TagUtils 객체;
                return new TagUtils();
            }

            @Override
            public boolean isCacheable(String expressionObjectName) {
                return true;
            }
        };
    }
}

```

```

public class TagUtils {
    public String gender(Gender gender){
        if(gender.name().equals("M")){
            return "남성";
        } else if (gender.name().equals("F")) {
            return "여성";
        }else {
            return "";
        }
    }
}

```

```

public interface BoardRepository extends JpaRepository<Board, String> {

}

@Repository
public interface PostRepository extends JpaRepository<Post, String> {

    List<Post> findByPkUserId(String userId);

    List<Post> findByPkBoardId(String boardId);
}

public interface RepositoryBase {

}

public interface UserRepository extends JpaRepository<User, String> {

}

```

## html

---

- src/main/webapp/WEB-INF
- src/main/webapp/WEB-INF/views
- src/main/webapp/WEB-INF/views/board
- src/main/webapp/WEB-INF/views/board/edit.html
- src/main/webapp/WEB-INF/views/board/post.html
- src/main/webapp/WEB-INF/views/board/posts.html
- src/main/webapp/WEB-INF/views/board/write.html
- src/main/webapp/WEB-INF/views/category
- src/main/webapp/WEB-INF/views/category/category.html
- src/main/webapp/WEB-INF/views/login
- src/main/webapp/WEB-INF/views/login/loginForm.html
- src/main/webapp/WEB-INF/views/user
- src/main/webapp/WEB-INF/views/user/find-id.html



- src/main/webapp/WEB-INF/views/user/find-id-result.html
- src/main/webapp/WEB-INF/views/user/find-password.html
- src/main/webapp/WEB-INF/views/user/find-password-result.html
- src/main/webapp/WEB-INF/views/loginInfo.html
- src/main/webapp/WEB-INF/views/main.html
- src/main/webapp/WEB-INF/views/managementUser.html
- src/main/webapp/WEB-INF/views/userRegist.html
- src/main/webapp/WEB-INF/views/userUpdate.html

```
/*공통 스타일*/
body {
    font-family: Arial, sans-serif;
    background-color: #f8f9fa;
    margin: 0;
}

.container {
    background-color: #ffffff;
    padding: 30px;
    border-radius: 5px;
    box-shadow: 0px 0px 5px 0px rgba(0, 0, 0, 0.1);
    max-width: 800px;
    margin: 50px auto;
}

.link, .auth-links a, .user-info a, .user-table a {
    text-decoration: none;
    color: #3498db;
    font-size: 14px;
}

.link:hover, .auth-links a:hover, .user-info a:hover, .user-table a:hover
{
    text-decoration: underline;
}

.auth-links {
    display: flex;
    justify-content: center;
    gap: 20px;
}

/*로그인 정보 스타일*/
.login-info {
    display: flex;
    justify-content: space-between;
    align-items: center;
    flex-wrap: wrap;
    margin-bottom: 20px;
}
```

```
.login-info ul {
  list-style: none;
  padding: 0;
  margin: 0;
  display: flex;
  gap: 10px;
}

.login-info li {
  display: inline;
}

/*메인 페이지 스타일*/
.main-title {
  text-align: center;
  margin-bottom: 30px;
}

.welcome-message {
  font-weight: bold;
  margin-bottom: 10px;
}

.user-id {
  font-weight: bold;
}

.link.user-list, .link.logout {
  display: inline-block;
  margin-right: 10px;
}

/*유저 리스트 페이지 스타일*/
.user-row:hover {
  background-color: #f8f9fa;
}

.link.update, .link.delete {
  font-weight: bold;
}

.table {
  margin-bottom: 30px;
}

.user-info {
  text-align: center;
}

.user-info a {
  margin-left: 15px;
}

/*로그인 및 회원가입 페이지 스타일*/
.form {
```

```
width: 300px;
margin: 50px auto;
}

.form input {
display: block;
width: 100%;
padding: 10px;
margin-bottom: 10px;
border-radius: 5px;
border: 1px solid #ccc;
}

.form label {
font-size: 14px;
font-weight: bold;
margin-bottom: 5px;
display: block;
}

.form button {
width: 100%;
display: block;
margin-top: 10px;
}

/*유저 리스트 페이지 스타일*/
.user-list-title {
text-align: center;
margin-bottom: 30px;
}

.user-table {
width: 100%;
margin-bottom: 30px;
border-collapse: collapse;
}

.user-table th, .user-table td {
padding: 10px;
text-align: left;
border: 1px solid #ccc;
}

.user-table th {
background-color: #3498db;
color: #fff;
}

/*추가 및 수정된 스타일 코드*/
#wrapper {
display: flex;
flex-direction: column;
align-items: center;
```

```
    justify-content: center;
    min-height: 100vh;
}

.home-link {
    position: absolute;
    top: 20px;
    left: 20px;
    font-size: 16px;
    font-weight: bold;
    background-color: #3498db;
    color: #fff;
    padding: 10px 20px;
    border-radius: 5px;
    text-decoration: none;
}

.link.home:hover {
    background-color: #2980b9;
}

.form {
    background-color: #fff;
    padding: 30px;
    border-radius: 5px;
    box-shadow: 0px 0px 5px 0px rgba(0, 0, 0, 0.1);
}

.form .input-group {
    margin-bottom: 15px;
}

.form .input-group label {
    display: block;
    font-size: 14px;
    font-weight: bold;
    margin-bottom: 5px;
}

.form .input-group input {
    display: block;
    width: 100%;
    padding: 10px;
    border-radius: 5px;
    border: 1px solid #ccc;
}

.form button {
    background-color: #3498db;
    color: #fff;
    padding: 10px;
    border-radius: 5px;
    font-size: 16px;
    font-weight: bold;
}
```

```

border: none;
cursor: pointer;
transition: background-color 0.3s;
}

.form button:hover {
background-color: #2980b9;
}

.form button:active {
transform: translateY(2px);
}
/*게시판 목록 스타일*/
.board-list {
display: flex;
flex-direction: column;
gap: 10px;
}

.board-list a {
font-size: 16px;
font-weight: bold;
color: #3498db;
}

.board-list a:hover {
text-decoration: underline;
}

```

## post.html

---

```

<!DOCTYPE html>
<html xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <title>게시물 상세보기</title>
</head>
<body>
<h1>게시물 상세보기</h1>
<table>
  <tr>
    <th>게시물 ID</th>
    <td th:text="${post.id}"></td>
  </tr>
  <tr>
    <th>게시판 ID</th>
    <td th:text="${post.board.name}"></td>
  </tr>
  <tr>
    <th>제목</th>

```

```

        <td th:text="${post.title}"></td>
    </tr>
    <tr>
        <th>작성자</th>
        <td th:text="${post.author.username}"></td>
    </tr>
    <tr>
        <th>내용</th>
        <td th:text="${post.content}"></td>
    </tr>
    <tr>
        <th>작성일시</th>
        <td th:text="${post.createdAt}"></td>
    </tr>
</table>
<a class="link" th:href="@{/board/{boardId}(boardId=${board.id})}"
th:text="돌아가기"></a>

<!-- 현재 로그인한 유저가 작성한 글인 경우에만 수정/삭제 버튼을 보여줌 -->
<div th:if="${session.user != null and session.user.id ==
post.author.id}">
    <a th:href="@{/board/{boardId}/post/{postId}/edit(boardId=${board.id},
postId=${post.id})}">
        <button>수정</button>
    </a>

    <form th:action="@{/board/{boardId}/deletePost(postId=${post.id},
boardId=${board.id})}" method="POST">
        <button type="submit">삭제</button>
    </form>
</div>

</body>
</html>

```

## posts.html

```

<!DOCTYPE html>
<html lang="ko" xmlns:th="http://www.thymeleaf.org">
<head>
    <meta charset="UTF-8">
    <link rel="stylesheet" th:href="@{/resources/style.css}" type="text/css"
/>
    <title>게시물 목록</title>
</head>
<body>
<div id="wrapper">
    <a href="/" class="home-link">홈으로</a>

```

```

<div class="container">
  <h1 class="main-title">게시물 목록</h1>

  <!-- 로그인 유저 정보 -->
  <div th:replace="loginInfo :: userinfo"></div>

  <table class="post-table">
    <thead>
      <tr>
        <th>글번호</th>
        <th>제목</th>
        <th>작성자</th>
        <th>작성일</th>
      </tr>
    </thead>
    <tbody>
      <tr th:each="post : ${posts}">
        <td th:text="${post.id}"></td>
        <td>
          <a class="post-link" th:if="${post.board != null}"
th:href="@{/board/{boardId}/post/{postId}"
(boardId=${post.board.id},postId=${post.id})" th:text="${post.title}">
</a>
        </td>
        <td th:text="${post.author.username}"></td>
        <td th:text="${#temporals.format(post.createdAt, 'yyyy-MM-dd
HH:mm:ss')}"></td>
      </tr>
    </tbody>
  </table>
</div>
<div th:if="${session.user != null}">
  <a th:href="@{/board/{boardId}/write(boardId=${board.id})}" class="btn
write-btn">글쓰기</a>
</div>

</div>
</body>
</html>

```

## write.html

```

<!DOCTYPE html>
<html lang="ko" xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <title>글쓰기 폼</title>
  <link rel="stylesheet" th:href="@{/resources/style.css}" type="text/css"
/>
</head>

```

```

<body>
<div id="wrapper">
  <a href="/" class="home-link">홈으로</a>
  <div th:with="boardId=${board.id}">

    <form th:method="POST"
th:action="@{/board/{boardId}/write(boardId=${boardId})}"
th:object="${post}" class="post-form">
      <div class="input-group">
        <label for="input-title" class="input-label">제목 :</label>
        <input name="title" type="text" placeholder="제목을 입력하세요."
required id="input-title">
      </div>
      <div class="input-group">
        <label for="input-content" class="input-label">내용 :</label>
        <textarea name="content" rows="10" placeholder="내용을 입력하세요."
required id="input-content"></textarea>
      </div>
      <input name="authorId" type="hidden" th:value="${session.user.id}">
      <input name="board.id" type="hidden" th:value="${board.id}">
      <button type="submit" id="submit-btn">글쓰기</button>
    </form>

  </div>
  <!-- 에러 메시지 출력 부분 -->
  <div th:if="${errorMessage}" class="alert alert-danger mt-3"
role="alert">
    <span th:text="${errorMessage}">Error message goes here</span>
  </div>

</div>
</body>
</html>

```

## edit.html

```

<!DOCTYPE html>
<html lang="ko" xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <title>게시물 수정</title>
  <link rel="stylesheet" th:href="@{/resources/style.css}" type="text/css"
/>
</head>
<body>
<div id="wrapper">
  <h1>게시물 수정</h1>
  <form
th:action="@{/board/{boardId}/post/{postId}/edit(boardId=${post.board.id},
postId=${post.id})}" method="post">

```



```

<div class="input-group">
  <label for="input-title" class="input-label">제목 :</label>
  <input name="title" type="text" th:value="${post.title}"
placeholder="제목을 입력하세요." required id="input-title">
</div>

<div class="input-group">
  <label for="input-content" class="input-label">내용 :</label>
  <textarea name="content" rows="10" placeholder="내용을 입력하세요."
required id="input-content" th:text="${post.content}"></textarea>
</div>

<button type="submit" id="submit-btn">수정</button>
</form>

<!-- 에러 메시지 출력 부분 -->
<div th:if="${errorMessage}" class="alert alert-danger mt-3"
role="alert">
  <span th:text="${errorMessage}">Error message goes here</span>
</div>
</div>
</body>
</html>

```

## category.html

```

<!DOCTYPE html>
<html lang="ko" xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <link rel="stylesheet" th:href="@{/resources/style.css}" type="text/css"
/>
  <title>Title</title>
</head>
<body>
<div id="wrapper">
  <a href="/" class="home-link">홈으로</a>
  <div class="container" th:fragment="category">
    <h1 class="main-title">게시판</h1>
    <div class="board-list" th:each="board: ${boards}" >
      <a class="link" th:href="@{/board/{boardId}(boardId=${board.id})}"
th:text="${board.name}"></a>
    </div>
  </div>
</div>
</body>
</html>

```

## loginForm.html

---

```
<!DOCTYPE html>
<html lang="ko" xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <link rel="stylesheet" th:href="@{/resources/style.css}" type="text/css"
/>
  <title>Title</title>
</head>
<body>
<div id="wrapper">
  <a href="/" class="home-link">홈으로</a>
  <div class="container" th:fragment="category">
    <h1 class="main-title">게시판</h1>
    <div class="board-list" th:each="board: ${boards}" >
      <a class="link" th:href="@{/board/{boardId}(boardId=${board.id})}"
th:text="${board.name}"></a>
    </div>
  </div>
</div>
</body>
</html>
```

## find-id.html

---

```
<!DOCTYPE html>
<html lang="ko" xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <link rel="stylesheet" th:href="@{/resources/style.css}" type="text/css"
/>
  <title>Title</title>
</head>
<body>
<div id="wrapper">
  <a href="/" class="home-link">홈으로</a>
  <div class="container" th:fragment="category">
    <h1 class="main-title">게시판</h1>
    <div class="board-list" th:each="board: ${boards}" >
      <a class="link" th:href="@{/board/{boardId}(boardId=${board.id})}"
th:text="${board.name}"></a>
    </div>
  </div>
</div>
</body>
```

```
</html>
```

## find-id-result.html

---

```
<!DOCTYPE html>
<html lang="ko" xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <title>아이디 찾기 결과</title>
  <link rel="stylesheet" th:href="@{/resources/style.css}" type="text/css"
/>
</head>
<body>
<div id="wrapper">
  <a href="/" class="home-link">홈</a>

  <div class="message">
    <span th:text="${message}"></span>
  </div>

  <!-- 에러 메시지 출력 부분 -->
  <div th:if="${errorMessage}" class="alert alert-danger mt-3"
role="alert">
    <span th:text="${errorMessage}">Error message goes here</span>
  </div>
</div>
</body>
</html>
```

## find-password.html

---

```
<!DOCTYPE html>
<html lang="ko" xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <title>비밀번호 찾기</title>
  <link rel="stylesheet" th:href="@{/resources/style.css}" type="text/css"
/>
</head>
<body>
<div id="wrapper">
  <a href="/" class="home-link">홈</a>

  <form th:method="POST" th:action="@{/find-password}">
```

```

th:object="${FindPasswordRequest}" class="find-form">
  <div class="input-group">
    <label for="input-email" class="input-label">이메일 :</label>
    <input name="email" type="email" placeholder="example@gmail.com"
required id="input-email">
  </div>

  <button type="submit" id="submit-btn">비밀번호 찾기</button>
</form>

<!-- 에러 메시지 출력 부분 -->
<div th:if="${errorMessage}" class="alert alert-danger mt-3"
role="alert">
  <span th:text="${errorMessage}">Error message goes here</span>
</div>

</div>
</body>
</html>

```

## find-password-result

```

<!DOCTYPE html>
<html lang="ko" xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <title>비밀번호 찾기 결과</title>
  <link rel="stylesheet" th:href="@{/resources/style.css}" type="text/css"
/>
</head>
<body>
<div id="wrapper">
  <a href="/" class="home-link">홈</a>

  <div th:if="${message}" class="alert alert-success mt-3" role="alert">
    <span th:text="${message}">Success message goes here</span>
  </div>

  <div th:if="${errorMessage}" class="alert alert-danger mt-3"
role="alert">
    <span th:text="${errorMessage}">Error message goes here</span>
  </div>

</div>
</body>
</html>

```

## login-info.html

```

<html lang="ko" xmlns:th="http://www.thymeleaf.org">
<body>
<div th:fragment="userinfo">
    <div class="login-info">
        <ul>
            <li><span th:text="${#messages.msg('info.id')}" /> : <span
th:text="${user?.id}" ></span></li>
            <li><span th:text="${#messages.msg('info.name')}" /> : <span
th:text="${user?.username}" ></span></li>
            <li>
                <button type="button" onclick="location.href=location.pathname +
'?locale=ko' ">한국어</button>
            </li>
            <li>
                <button type="button" onclick="location.href=location.pathname +
'?locale=en' ">영어</button>
            </li>
        </ul>
    </div>
</div>
</body>
</html>

```

## main.html

```

<!DOCTYPE html>
<html lang="ko" xmlns:th="http://www.thymeleaf.org">
<head>
    <meta charset="UTF-8">
    <title>Login</title>
    <link rel="stylesheet" th:href="@{/resources/style.css}" type="text/css"
/>
</head>
<body>
<div id="wrapper">
    <div class="container">
        <h1 id="main-title">MAIN</h1>
        <th:block th:insert=~{loginInfo :: userinfo}" ></th:block>

        <div th:if="${user != null}" class="user-info">
            <p class="welcome-message">환영합니다. <span th:text="${user.username}"
class="user-id"></span></p>
            <a href="/usermanage/list" class="user-list-link">유저리스트</a>
            <a href="/board" class="board-link">게시판</a>
            <a href="/logout" class="logout-link">로그아웃</a>
        </div>
    </div>
</div>

```

```

<div th:if="${user == null}" class="auth-links">
  <a href="/login" class="login-link">로그인</a>
  <a href="/regist" class="register-link">회원가입</a>
</div>

<script>
  var user = [[${user != null} ? ${user} : 'null']];
  console.log(user);
</script>

</div>
</div>
</body>
</html>

```

## managementUser.html

```

<!DOCTYPE html>
<html xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <title>User List</title>
  <link rel="stylesheet" th:href="@{/resources/style.css}" type="text/css" />
</head>
<body>
<th:block th:insert="~{loginInfo :: userinfo}" ></th:block>

<a href="/" class="home-link">홈</a>

<div class="container">
  <h1 class="mt-5 mb-5 user-list-title">User List</h1>
  <table class="table table-bordered table-striped user-list-table">
    <thead>
      <tr>
        <th>ID</th>
        <th>Name</th>
        <th>Email</th>
        <th>Birth Date</th>
        <th>Created At</th>
        <th>Update</th>
        <th>Delete</th>
      </tr>
    </thead>
    <tbody>
      <tr th:each="user : ${userlist}" class="user-row">
        <td th:text="${user.id}" class="user-id"></td>
        <td th:text="${user.username}" class="user-name"></td>
        <td th:text="${user.email}" class="user-email"></td>
        <td th:text="${user.birthDate}" class="user-birthDate"></td>

```

```

        <td th:text="${user.createdAt}" class="user-createdAt"></td>
        <td>
            <a th:href="@{/usermanage/update/{id}(id=${user.id})}"
class="update-link">Update</a>
        </td>
        <td>
            <a th:href="@{/usermanage/delete/{id}(id=${user.id})}"
            onclick="return confirm('정말로 삭제하시겠습니까?')" class="delete-
link">Delete</a>
        </td>
    </tr>
</tbody>
</table>
</div>
<script src="https://code.jquery.com/jquery-3.5.1.slim.min.js"></script>
<script
src="https://cdn.jsdelivr.net/npm/@popperjs/core@2.9.3/dist/umd/popper.min
.js"></script>
<script
src="https://maxcdn.bootstrapcdn.com/bootstrap/4.5.2/js/bootstrap.min.js">
</script>
</body>
</html>

```

## userRegist.html

```

<!DOCTYPE html>
<html lang="ko" xmlns:th="http://www.thymeleaf.org">
<head>
    <meta charset="UTF-8">
    <title>REGIST</title>
    <link rel="stylesheet" th:href="@{/resources/style.css}" type="text/css"
/>
</head>
<body>
<div id="wrapper">
    <th:block th:insert="~{loginInfo :: userinfo}" ></th:block>

    <div class="container">
        <form th:method="POST" th:action="@{/regist/}" class="registration-
form">
            <a href="/" class="home-link">홈</a>

            <p class="name-label">이름 :</p>
            <input name="username" type="text" placeholder="이름" required
class="name-input">

            <p class="email-label">이메일 :</p>
            <input name="email" type="text" placeholder="example@example.com"

```

```

required class="email-input">
  <div th:if="${error}" class="error-message">
    <span th:text="${error}"></span>
  </div>
  <p class="pwd-label">비밀번호 :</p>
  <input name="password" type="password" placeholder="1234" required
class="pwd-input">

  <p class="birth-date-label">생년월일 :</p>
  <input name="birthDate" type="date" required class="birth-date-
input">

  <button type="submit" class="submit-button">회원 가입</button>
</form>
</div>
</div>
</body>
</html>

```

## userUpdate.html

```

<!DOCTYPE html>
<html lang="ko" xmlns:th="http://www.thymeleaf.org">
<head>
  <meta charset="UTF-8">
  <title>Title</title>
  <link rel="stylesheet" th:href="@{/resources/style.css}" type="text/css"
/>
</head>
<body>
<div id="wrapper">
  <th:block th:insert="~{loginInfo :: userinfo}" ></th:block>

  <div class="container">
    <a href="/" class="home-link">홈</a>

    <h1 class="mt-5 mb-5 update-title">User List</h1>
    <table class="table table-bordered table-striped user-table">
      <thead>
        <tr>
          <th>ID</th>
          <th>Password</th>
          <th>Name</th>
        </tr>
      </thead>
      <tbody>
        <tr>
          <td th:text="${user.id}" class="user-id"></td>
          <td th:text="${user.pwd}" class="user-pwd"></td>

```



```
        <td th:text="${user.name}" class="user-name"></td>
    </tr>
</tbody>
</table>

<form th:method="post" th:action="@{/usermanage/update/${user.id}}"
class="update-form">
    <p class="name-label">이름 :</p>
    <input name="name" type="text" placeholder="이름" required
class="name-input">
    <input name="id" style="display: none" th:value="${user.id}"
class="hidden-id"/>

    <p class="pwd-label">비밀번호 :</p>
    <input name="pwd" type="password" placeholder="1234" required
class="pwd-input">
    <button type="submit" class="submit-button">수정</button>
</form>
</div>
</div>
</body>
</html>
```