

```

import javax.sql.DataSource;

@Configuration
@ComponentScan(basePackageClasses = Base.class,
    excludeFilters = @ComponentScan.Filter(Controller.class))
public class RootConfig {
    @Bean
    public DataSource dataSource() {
        BasicDataSource dataSource = new BasicDataSource();
        dataSource.setDriverClassName("org.h2.Driver");

        // 데이터베이스 접속 정보 설정
        dataSource.setUrl("jdbc:h2:~/spring-jpa;DATABASE_TO_UPPER=false;"
            + "INIT=RUNSCRIPT FROM 'classpath:/script/schema.sql'");
        dataSource.setUsername("sa");
        dataSource.setPassword("");

        // 초기 커넥션 풀 크기 설정
        dataSource.setInitialSize(10);

        // 최대 커넥션 풀 크기 설정
        dataSource.setMaxTotal(10);

        // 최소 유휴 커넥션 개수 설정
        dataSource.setMinIdle(10);

        // 최대 유휴 커넥션 개수 설정
        dataSource.setMaxIdle(10);

        // 커넥션 풀이 바쁠 때 대기 시간 설정 (밀리초)
        dataSource.setMaxWaitMillis(1000);

        // 커넥션 풀에서 커넥션을 가져올 때 살아있는지 확인
        dataSource.setTestOnBorrow(true);

        // 사용이 끝난 커넥션을 다시 풀에 반환할 때 해당 커넥션이 사용 가능한지 확인
        dataSource.setTestOnReturn(true);

        // 주기적으로 유휴 상태인 커넥션들을 검사하여 살아있는지 확인 (약간의 성능 저하가 있을 수 있음)
        dataSource.setTestWhileIdle(true);

        return dataSource;
    }
    @Bean
    //플랫폼 트랜잭션 매니저
    //트랜잭션 추상화를 위한 중심 API
    // jdbc를 쓰지만 다른걸 쓰면 DataSource가아니라 다르게 들어갈수도있음
    public PlatformTransactionManager transactionManager() {
        return new DataSourceTransactionManager(dataSource());
    }
}

```

```
}
```

- 두개의 유저정보를 미리 넣어둠

```
CREATE TABLE IF NOT EXISTS `Users` (  
  `user_id`  VARCHAR(50) NOT NULL,  
  `password` VARCHAR(50) NOT NULL,  
  
  PRIMARY KEY(`user_id`)  
);  
  
MERGE INTO `Users` KEY ( `user_id` ) VALUES ( 'admin', '12345' );  
MERGE INTO `Users` KEY ( `user_id` ) VALUES ( 'dongmyo', '67890' );
```

```
@RestController  
@RequestMapping("/users/{userId}")  
public class UserRestController {  
    private final UserRepository userRepository;  
  
    public UserRestController(UserRepository userRepository) {  
        this.userRepository = userRepository;  
    }  
  
    @ModelAttribute(value = "user", binding = false)  
    public User getUser(@PathVariable("userId") String userId) {  
        User user = userRepository.getUser(userId);  
        if (Objects.isNull(user)) {  
            throw new UserNotFoundException();  
        }  
  
        return user;  
    }  
  
    @GetMapping  
    public User getUser(@ModelAttribute("user") User user) {  
        return user;  
    }  
  
    @PutMapping  
    public User modifyUser(@ModelAttribute("user") User user,  
                           @Valid @RequestBody UserModifyRequest request,  
                           BindingResult bindingResult) {  
        if (bindingResult.hasErrors()) {  
            throw new ValidationFailedException(bindingResult);  
        }  
  
        if (!userRepository.modifyUser(user.getId(),
```

```
request.getPassword())) {  
    throw new UserModifyFailedException();  
}  
  
    return userRepository.getUser(user.getId());  
}  
  
}
```

```
package com.nhnacademy.springjpa.repository;  
  
import com.nhnacademy.springjpa.domain.User;  
import com.nhnacademy.springjpa.domain.UserRowMapper;  
import org.springframework.jdbc.core.JdbcTemplate;  
import org.springframework.stereotype.Repository;  
  
import javax.sql.DataSource;  
import java.util.Objects;  
  
@Repository("userRepository")  
public class UserRepositoryImpl implements UserRepository {  
    private final JdbcTemplate jdbcTemplate;  
  
    public UserRepositoryImpl(DataSource dataSource) {  
        this.jdbcTemplate = new JdbcTemplate(dataSource);  
    }  
  
    @Override  
    public boolean exists(String id) {  
        Integer count = jdbcTemplate.queryForObject("SELECT count(*) FROM  
Users WHERE user_id = ?1", Integer.class, id);  
        return count != null && count == 1;  
    }  
  
    @Override  
    public boolean matches(String id, String password) {  
        User user = jdbcTemplate.queryForObject("SELECT user_id, password  
FROM Users WHERE user_id = ?1 AND password = ?2",  
        User.class, id, password);  
  
        return Objects.nonNull(user) && user.getId().equals(id);  
    }  
  
    @Override  
    public User getUser(String id) {  
        return jdbcTemplate.queryForObject("SELECT user_id, password FROM  
Users where user_id = ?1", new UserRowMapper(), id);  
    }  
  
    @Override
```

```
    public boolean addUser(String id, String password) {
        int result = jdbcTemplate.update("INSERT INTO Users (`user_id`,
`password`) VALUES (?, ?)",
            id,
            password);

        return result == 1;
    }

    @Override
    public boolean modifyUser(String id, String password) {
        int result = jdbcTemplate.update("UPDATE Users set password = ?1
WHERE user_id = ?2",
            password,
            id);

        return result == 1;
    }
}
```

```
GET /users/admin
Host: localhost:8080
Content-Type: application/json
```

```
###
```

```
POST /users HTTP/1.1
Host: localhost:8080
Content-Type: application/json
```

```
{
  "id": "nhn",
  "password": "academy"
}
```

```
###
```

```
GET /users/nhn
Host: localhost:8080
Content-Type: application/json
```

```
###
```

```
PUT /users/nhn
Host: localhost:8080
Content-Type: application/json
```

```
{  
  "password": "hahaha"  
}
```

```
// Component 스캔과 비슷한 기능을 한다.  
// SPRING에서 jpa 쓰려면 이게 필요하다.  
@EnableJpaRepositories(basePackageClasses = RepositoryBase.class)  
@Configuration  
public class JpaConfig {  
    @Bean  
    public LocalContainerEntityManagerFactoryBean  
entityManagerFactory(DataSource dataSource) {  
        LocalContainerEntityManagerFactoryBean emf = new  
LocalContainerEntityManagerFactoryBean();  
        emf.setDataSource(dataSource);  
        emf.setPackagesToScan("com.nhnacademy.springjpa.entity");  
        emf.setJpaVendorAdapter(jpaVendorAdapters());  
        emf.setJpaProperties(jpaProperties());  
  
        return emf;  
    }  
  
    private JpaVendorAdapter jpaVendorAdapters() {  
        HibernateJpaVendorAdapter hibernateJpaVendorAdapter = new  
HibernateJpaVendorAdapter();  
        hibernateJpaVendorAdapter.setDatabase(Database.H2);  
  
        return hibernateJpaVendorAdapter;  
    }  
  
    private Properties jpaProperties() {  
        Properties jpaProperties = new Properties();  
        jpaProperties.setProperty("hibernate.show_sql", "true");  
        jpaProperties.setProperty("hibernate.format_sql", "true");  
        jpaProperties.setProperty("hibernate.use_sql_comments", "true");  
        jpaProperties.setProperty("hibernate.globally_quoted_identifiers",  
"true");  
  
        jpaProperties.setProperty("hibernate.temp.use_jdbc_metadata_defaults",  
"false");  
  
        return jpaProperties;  
    }  
  
    @Bean  
    public PlatformTransactionManager  
transactionManager(EntityManagerFactory entityManagerFactory) {  
        JpaTransactionManager transactionManager = new  
JpaTransactionManager();  
        transactionManager.setEntityManagerFactory(entityManagerFactory);  
    }  
}
```

```
        return transactionManager;  
    }  
  
}
```