

【华工包打听说明】

此答案由某位学生提供，包打整理无偿分享给大家，禁止用于资料买卖或他用

答案仅供参考，不保证正确。

更多资料欢迎大家关注包打听（QQ 号、微信号或公众号）

校园资讯，问题答疑，感情树洞
万事皆可找包包

进入华工社群，探索华园更多玩法
黑市，学习群，二手交易，考试资料...
你能想到的，我们都愿意帮你实现

我们是华工包打听，由校内学生组建而成的校园自媒体
立志成为陪伴华园学子度过漫长岁月的一盏灯



SCUT包打听（新）



华工包打听



华工卫星站



包打听公众号



包打听QQ

由于华工包打听、华工卫星站好友人数已满，请加SCUT包打听或包打听QQ

更多资料、资讯，可加包打听公众号获取！

诚信应考,考试作弊将带来严重后果!

华南理工大学期末考试

《 Data Structure 》 试卷 B

- 注意事项: 1. 考前请将密封线内填写清楚;
2. 所有答案请答在答题纸上;
3. 考试形式: 闭卷;
4. 本试卷共十大题, 满分 100 分, 考试时间 120 分钟。

题号	一	二	三	四	五	六	七	八	九	十	总分
得分											
评卷人											

1. Select the correct choice. (30 scores, each 2 scores)

(1) If a data element requires 4 bytes and a pointer requires 2 bytes, then a linked list representation will be more space efficient than a standard array representation when the fraction of non-zero elements is less than about: (A)

(A) 2/3 (B) 3/4 (C) 1/3 (D) 1/2

(2) Assume array A contains a random permutation of the values from 0 to n - 1, the time cost of the following code fragment is: (B)

```
sum = 0;
for (i=0; i<n; i++)
    for (j=0; A[j]!=i; j++)
        sum++;
```

(A) $\Theta(n)$ (B) $\Theta(n^2)$ (C) $\Theta(n \log n)$ (D) $\Theta(\log n)$

(3) Which statement is **not** correct among the following four: (D)

(A) In a BST, the left child of any node is less than the right child, but in a heap, the left child of any node could be less than or greater than the right child.

(B) The number of empty subtrees in a non-empty binary tree is one more than the number of nodes in the tree.

(C) A general tree can be transferred to a binary tree with the root having only left child.

(D) A heap must be a full binary tree.

(4) An algorithm must be or do all of the following EXCEPT: (B)

(A) Correct (B) Ambiguous (C) Concrete step (D) terminable

(5) In the following sorting algorithms, which is the best one to find the first 10 biggest elements in the 1000 unsorted elements? (C)

(A) Insert sort. (B) Quicksort.


(C) Heap sort. (D) Shell sort.

(6) Which of the following is the max-heap constructed by a sequence of key (48, 76,

- 54, 32, 40, 85) ? (B)
- (A) 76, 85, 54, 32, 48, 40 (B) 85, 76, 54, 32, 40, 48
(C) 85, 54, 76, 48, 32, 40 (D) 85, 76, 54, 32, 40, 48
- (7) If there is 1MB working memory, 4KB each block, and yield 256 blocks for working memory. By the multi-way merge in external sorting, the average run size and the sorted size in one pass of multi-way merge on average respectively are : (C)
- (A) 1MB, 256 MB (B) 1MB, 512 MB
(C) 2MB, 512 MB (D) 2MB, 1024MB
- (8) The golden rule of a disk-based program design is to: (A)
- (A) Minimize the number of disk accesses. (B) Eliminate the recursive calls.
(C) Improve the basic operations. (D) Reduce main memory use.
- (9) The time cost of Quicksort in the worst case is (D).
- (A) $O(n)$ (B) $O(\log_2 n)$ (C) $O(n \log_2 n)$ (D) $O(n^2)$
- (10) The function of replacement selection sort is (B).
- (A) Select the maximal element. (B) Generate the initial sorted merge files.
(C) Merge the sorted file. (D) Replace some record.
- (11) Tree indexing methods are meant to overcome what deficiency in hashing?
(D)
- (A) Inability to handle range queries.
(B) Inability to handle largest key value queries.
(C) Inability to handle queries in key order
(D) All above.
- (12) Which statement is not correct among the following four: (A)
- (A) The worst case for my algorithm is n becoming larger and larger because that is the slowest.
(B) A cluster is the smallest unit of allocation for a file, so all files occupy a multiple of the cluster size.
(C) The selection sort is an unstable sorting algorithm.
(D) The number of leaves in a non-empty full binary tree is one more than the number of internal node.
- (13) Assume that we have eight records, with key values A to H, and that they are initially placed in alphabetical order. Now, consider the result of applying the following access pattern: F D F G G F A D F G, if the list is organized by frequency count (count will store the records in the order of frequency that has actually occurred so far), then the final list will be (A).
- (A) A B F G D C E H (B) E G F D A B C H
(C) A G F D B C E H (D) F E G D A B C H
- (14) In the hash function, collision refers to (B).
- (A) Two elements have the same sequence number.
(B) Different keys are mapped to the same address of hash table.

(C) Two records have the same key. (D) Data elements are too much.

(15) For the following graph, one of results of Depth-first traversal is: (C)



A. acbdieghf B. abighfcde C. abdeighcf D. abcdefghi


2. Arrange the following expressions by growth rate from slowest to fastest. (4 scores)

$3n^2$ $\log_3 n$ $n!$ $10n$ $2n$ 20 $\log_2 n$ $8n^{2/3}$

Answer: $20 < \log_3 n < \log_2 n < 8n^{2/3} < 10n < 3n^2 < 2n < n!$

3. Draw the general tree represented by the following sequential representation for general trees: RAC)M)PL)V)))NW)J))) (6 scores)

Answer:



4. Please apply Quicksort Algorithm to sort the array in ascending order: 265, 301, 751, 129, 937, 863, 742, 694, 076, 438. Note that the pivot value is selected based on the following function, Parameters i and j define the start and end indices of the Array A , respectively. (10 scores)


```
template <typename E>
inline int findpivot(E A[], int i, int j)
{ return A[i]; }
```

Answer:

Initial: [265 301 751 129 937 863 742 694 076 438]
 1st pass: [076 129] 265 [751 937 863 742 694 301 438]
 2nd pass: 076 [129] 265 [438 301 694 742] 751 [863 937]
 3rd pass: 076 129 265 [301] 438 [694 742] 751 863 [937]
 4th pass: 076 129 265 301 438 694 [742] 751 863 937
 5th pass: 076 129 265 301 438 694 742 751 863 937


5. Please draw pictures to show the heaps that results from (6 scores)

- 1) add 38 to the following heap;
- 2) then delete 42 from the result heap of 1);




Answer:

1)




2)



6. Please give the Huffman codes for the letters of the following table, draw pictures to show how to obtain the Huffman tree step by step, and compute the expected bit-length per letter. What's the advantage of Huffman code scheme. (8 scores)

Letter	a	b	c	d	e	f	g	h
Frequency	55	34	17	6	70	11	17	22

Answer:



2) expected bit-length

$$[(6 + 11) \times 5 + 17 \times 4 + (34 + 17 + 22) \times 3 + (70 + 55) \times 2] \div 222 \approx 2.8$$

3) advantage

Huffman code scheme saves text length in most cases.

7. Given a hash table of size 11, assume that $H_1(k) = (2k + 1) \bmod 11$ and

$H_2(k) = (3k \bmod 10) + 1$ are two hash functions, where H_1 is used to get home

position and H_2 is used to resolve collision for method double hashing. Please insert

keys 9, 17, 63, 55, 22, 27, 88, 41 into the hash table in order. (10 scores)

Answer:

$H_1(9)=8$, $H_1(17)=2$, $H_1(63)=6$, $H_1(55)=1$, no conflict

When $H_1(22)=1$, $H_2(22)=7$ $(1+2*7) \% 11=4$, so 22 enters the 4 slot (pass by 1,8);


$H_1(27)=0$ so 27 enters the 0 slot;

$H_1(88)=1$, $H_2(88)=5$ $(1+3*5)\%11=5$ so 88 enters 5 (pass by 1, 6, 0);

$H_1(41)=6$, $H_2(41)=4$ $(6+1*4)\%11=10$ so 41 enters 10(pass by 6)


27	55	17		22	88	63		9		41
0	1	2	3	4	5	6	7	8	9	10

8. Please insert 18, 58, 8 into the following 2-3 tree. Inserting a key, draw a picture for the resulted 2-3 tree. Thus you should draw 3 pictures. (10 scores)




Answer:


1)



2)



3)



9. Complete the insert, remove functions of the Link-based List class. (6 scores)

```

template <class Elem> class LList: public List<Elem> {
private:
    Link<Elem>* head;//Point to list header
    Link<Elem>* tail;//Pointer to last Elem
    Link<Elem>* fence;//Last element on left
    int leftcnt; //Size of left
    int rightcnt; //Size of right
public:
    bool LList<Elem>::insert(const Elem& item) { }
    template <class Elem> bool LList<Elem>::remove(Elem& it) { }

```

Solution:

// Insert at front of right partition

template <class Elem>

**bool LList<Elem>::insert(const Elem& item) {fence->next =
 new Link<Elem>(item, fence->next);
 if (tail == fence) tail = fence->next; rightcnt++;
 return true;}**

// Remove and return first Elem in right

// partition

**template <class Elem> bool LList<Elem>::remove(Elem& it) {
 if (fence->next == NULL) return false;
 it = fence->next->element; //Remember val
 // Remember link node
 Link<Elem>* ltemp = fence->next;
 fence->next = ltemp->next; // Remove
 if (tail == ltemp) // Reset tail
 tail = fence;
 delete ltemp; // Reclaim space
 rightcnt--;
 return true;**

}

10. Assume a disk drive is configured as follows. The total storage is approximately 1.5G divided among 15 surfaces. Each surface has 512 tracks; there are 256 sectors/track, 1024 byte/sector, and 32 sectors/cluster. The disk turns at 7200rpm (8.33 ms/r). The track-to-track seek time is 3 ms, and the average seek time is 10 ms. Now how long does it take to read all of the data in a 960 KB file on the disk? Assume that the file's clusters are spread randomly across the disk. A seek must be performed each time the I/O reader moves to a new track. Show your calculations. (The process of your solution is required!!!) (8 scores)

Solution:

The first question is how many clusters the file requires?

A cluster holds $32 \times 1K = 32K$. Thus, the file requires $960K/32K=30$ clusters


The time to read a cluster is seek time to the cluster+ latency time + (rotation time).

Average seek time is defined to be 10 ms. Latency time is 0.5×8.33 ms ($60/7200 \approx 8.33$ ms), and cluster rotation time is $(32/256) \times 8.33$.

Seek time for the total file read time is

$30 \times (10 + 0.5 \times 8.33 + (32/256) \times 8.33) \approx 456$ ms

11. The following graph is a communication network in some area, whose edge presents the channel between two cities with the weight as the channel's cost. How to choose the cheapest path from A to other cities? And how to get cheapest paths connecting all cities? You can draw all choices if there is more than one path. (10 scores)



Solution:

- a. Get the shortest paths from A to other cities

(6 scores)

	A	B	C	D	E	F	G
Process A		12	5	4	∞	∞	∞
Process D		D:10	5		∞	D: 13	D:15
Process C					∞	C: 11	
Process B					B:12		
Process F							
Process E							E:14
Process G		D:10	A:5	A:4	B:12	C: 11	E:14

A to D: 4 (A,D); A to C: 5(A,C); A to B: 10(A,D,B); A to E: 12(A,D,B,E); A to F: 11(A,C,F); A to G:14(A,D,B,E,G)

b. Draw the MST

(4 scores)

