

63266-5007WO
P3925WO1

What is claimed is:

1. A method of controlling an electronic device with a touch-sensitive display, comprising:

5 detecting contact with the touch-sensitive display while the device is in a user-interface lock state;

moving an image corresponding to a user-interface unlock state of the device in accordance with the contact;

10 transitioning the device to the user-interface unlock state if the detected contact corresponds to a predefined gesture; and

maintaining the device in the user-interface lock state if the detected contact does not correspond to the predefined gesture.

2. The method of claim 1, further comprising, while the device is in the user-interface lock state, preventing the device from performing a predefined set of actions in response to
15 detecting any contact with the touch-sensitive display that does not correspond to the predefined gesture.

3. The method of claim 1, further comprising, while the device is in the user-interface lock state, displaying on the touch-sensitive display one or more visual cues of the predefined gesture.

20 4. A method of controlling a device comprising a touch-sensitive display, comprising: displaying an image on the touch-sensitive display while the device is in a user-interface lock state,

detecting contact with the touch-sensitive display;

25 transitioning the device to a user-interface unlock state if the detected contact corresponds to moving the image to a predefined location on the touch-sensitive display; and maintaining the device in the user-interface lock state if the detected contact does not correspond to moving the image to the predefined location.

5. The method of claim 4, further comprising, while the device is in the user-interface lock state, preventing the device from performing a predefined set of actions in response to

63266-5007WO
P3925WO1

detecting any contact with the touch-sensitive display that does not correspond to moving the image to the predefined location.

6. The method of claim 4, further comprising, while the device is in the user-interface lock state, displaying on the touch-sensitive display one or more visual cues of the predefined location.

7. A method of controlling a device comprising a touch-sensitive display, comprising:
displaying an image on the touch-sensitive display while the device is in a user-interface lock state;

detecting contact with the touch-sensitive display; and

transitioning the device to a user-interface unlock state if the detected contact corresponds to moving the image on the touch-sensitive display according to a predefined path on the touch-sensitive display; and

maintaining the device in the user-interface lock state if the detected contact does not correspond to moving the image according to the predefined path.

8. The method of claim 7, further comprising, while the device is in a user-interface lock state, preventing the device from performing a predefined set of actions in response to detecting any contact with the touch-sensitive display that does not correspond to moving the image according to the predefined path.

9. The method of claim 7, wherein the detected contact corresponding to moving the image according the predefined path comprises contact corresponding to moving the image to an endpoint of the predefined path.

10. The method of claim 7, further comprising, while the device is in the user-interface lock state, displaying on the touch-sensitive display one or more visual cues of the predefined path.

11. A method of controlling a device comprising a touch-sensitive display, comprising:
displaying first and second images on the touch-sensitive display while the device is in a user-interface lock state;

detecting contact with the touch-sensitive display;

transitioning the device to a first active state corresponding to the first image if the

detected contact corresponds to a predefined gesture with respect to the first image; and

63266-5007WO
P3925WO1

transitioning the device to a second active state distinct from the first active state if the detected contact corresponds to a predefined gesture with respect to the second image.

12. A portable electronic device, comprising:

a touch-sensitive display;

5 memory;

one or more processors; and

one or more modules stored in the memory and configured for execution by the one or more processors, the one or more modules including instructions:

to set the device to a user-interface lock state;

10 to display at least one image on the touch-sensitive display while the device is in the user-interface lock state;

to detect contact with the touch-sensitive display; and,

to transition the device to a user-interface unlock state if the detected contact corresponds to a predefined gesture with respect to the image.

15 13. A portable electronic device, comprising:

a touch-sensitive display;

memory;

one or more processors; and

20 one or more modules stored in the memory and configured for execution by the one or more processors, the one or more modules including instructions:

to set the device to a user-interface lock state;

to display at least one image on the touch-sensitive display while the device is in the user-interface lock state;

to detect contact with the touch-sensitive display; and

25 to transition the device to a user-interface unlock state if the detected contact corresponds to moving the image to a predefined location on the touch-sensitive display.

14. A portable electronic device, comprising:

a touch-sensitive display;

memory;

30 one or more processors; and

one or more modules stored in the memory and configured for execution by the one or more processors, the one or more modules including instructions:

63266-5007WO
P3925WO1

to set the device to a user-interface lock state;
to display at least one image on the touch-sensitive display while the device is
in the user-interface lock state;
to detect contact with the touch-sensitive display; and
5 to transition the device to a user-interface unlock state if the detected contact
corresponds to moving the image on the touch-sensitive display according to a predefined
path on the touch-sensitive display.

15. A portable electronic device, comprising:

a touch sensitive display;

10 memory;

one or more processors;

one or more modules stored in the memory and configured for execution by the one or
more processors, the one or more processors including instructions:

to set the device to a user-interface lock state;

15 to display first and second images on the touch-sensitive display;

to detect contact with the touch-sensitive display;

to transition the device to a first active state corresponding to the first image if
the detected contact corresponds to a predefined gesture with respect to the first image; and

20 to transition the device to a second active state distinct from the first active
state if the detected contact corresponds to a predefined gesture with respect to the second
image.

16. A portable electronic device, comprising:

a touch-sensitive display;

25 means for detecting contact with the touch-sensitive display while the device is in a
user-interface lock state;

means for moving an image corresponding to a user-interface unlock state of the
device in accordance with the contact;

means for transitioning the device to the user-interface unlock state if the detected
contact corresponds to a predefined gesture; and

30 means for maintaining the device in the user-interface lock state if the detected
contact does not correspond to the predefined gesture.

63266-5007WO
P3925WO1

17. A portable electronic device, comprising:
a touch-sensitive display;
means for displaying an image on the touch-sensitive display while the device is in a
user-interface lock state,

5 means for detecting contact with the touch-sensitive display;
means for transitioning the device to a user-interface unlock state if the detected
contact corresponds to moving the image to a predefined location on the touch-sensitive
display; and
means for maintaining the device in the user-interface lock state if the detected
10 contact does not correspond to moving the image to the predefined location.

18. A portable electronic device, comprising:
a touch-sensitive display;
means for displaying an image on the touch-sensitive display while the device is in a
user-interface lock state;

15 means for detecting contact with the touch-sensitive display; and
means for transitioning the device to a user-interface unlock state if the detected
contact corresponds to moving the image on the touch-sensitive display according to a
predefined path on the touch-sensitive display; and
means for maintaining the device in the user-interface lock state if the detected
20 contact does not correspond to moving the image according to the predefined path.

19. A portable electronic device, comprising:
a touch-sensitive display;
means for displaying first and second images on the touch-sensitive display while the
device is in a user-interface lock state;

25 means for detecting contact with the touch-sensitive display;
means for transitioning the device to a first active state corresponding to the first
image if the detected contact corresponds to a predefined gesture with respect to the first
image; and
means for transitioning the device to a second active state distinct from the first active
30 state if the detected contact corresponds to a predefined gesture with respect to the second
image.

63266-5007WO
P3925WO1

20. A computer program product for use in conjunction with a portable electronic device comprising a touch-sensitive display, the computer program product comprising a computer readable storage medium and a computer program mechanism embedded therein, the computer program mechanism comprising instructions for:

5 detecting contact with the touch-sensitive display while the device is in a user-interface lock state;

moving an image corresponding to a user-interface unlock state of the device in accordance with the contact;

10 transitioning the device to the user-interface unlock state if the detected contact corresponds to a predefined gesture; and

maintaining the device in the user-interface lock state if the detected contact does not correspond to the predefined gesture.

21. A computer program product for use in conjunction with a portable electronic device comprising a touch-sensitive display, the computer program product comprising a computer readable storage medium and a computer program mechanism embedded therein, the computer program mechanism comprising instructions for:

15 displaying an image on the touch-sensitive display while the device is in a user-interface lock state,

20 detecting contact with the touch-sensitive display;

transitioning the device to a user-interface unlock state if the detected contact corresponds to moving the image to a predefined location on the touch-sensitive display; and

maintaining the device in the user-interface lock state if the detected contact does not correspond to moving the image to the predefined location.

22. A computer program product for use in conjunction with a portable electronic device comprising a touch-sensitive display, the computer program product comprising a computer readable storage medium and a computer program mechanism embedded therein, the computer program mechanism comprising instructions for:

25 displaying an image on the touch-sensitive display while the device is in a user-interface lock state;

30 detecting contact with the touch-sensitive display; and

63266-5007WO
P3925WO1

transitioning the device to a user-interface unlock state if the detected contact corresponds to moving the image on the touch-sensitive display according to a predefined path on the touch-sensitive display; and

5 maintaining the device in the user-interface lock state if the detected contact does not correspond to moving the image according to the predefined path.

23. A computer program product for use in conjunction with a portable electronic device comprising a touch-sensitive display, the computer program product comprising a computer readable storage medium and a computer program mechanism embedded therein, the computer program mechanism comprising instructions for:

10 displaying first and second images on the touch-sensitive display while the device is in a user-interface lock state;

detecting contact with the touch-sensitive display;

transitioning the device to a first active state corresponding to the first image if the detected contact corresponds to a predefined gesture with respect to the first image; and

15 transitioning the device to a second active state distinct from the first active state if the detected contact corresponds to a predefined gesture with respect to the second image.