

## SECOND AUXILIARY REQUEST

### CLAIMS

1. A computer-implemented method, comprising:

while an electronic device (400/700) having a touch-sensitive display (714) is in a first user-interface state, detecting progress towards ~~satisfaction of a user input condition~~ completion of a gesture input on the touch-sensitive display needed to transition to a second user-interface state;

characterised in that:

the gesture input includes dragging an image (702) to a predefined location on the touch-sensitive display (714), and in that the method further comprises:

while the device (400/700) is in the first user-interface state,

indicating (604) progress ~~towards satisfaction of the condition~~ of the gesture input by transitioning an optical intensity of one or more user interface objects (708) ~~associated with the second user interface state without being associated with the first user interface state,~~

wherein at least one of the one or more user interface objects (708) associated with the second user interface state (214) is not displayed prior to detecting progress towards ~~satisfaction of the user input condition~~ completion of the gesture input and,

wherein transitioning the optical intensity includes the one or more user interface objects (708) associated with the second user interface state appearing and increasing in optical intensity; and

transitioning (606) the device (400/700) to the second user-interface state if the ~~condition is satisfied~~ gesture input is completed.

2. ~~The method of claim 1, wherein the device comprises a touch sensitive display, and wherein satisfying the condition comprises detecting contact with the touch sensitive display that corresponds to a predefined gesture.~~

32. The method of claim 1, ~~wherein the device comprises a touch sensitive display, and wherein satisfying the condition~~ the method further comprises:

displaying ~~an the~~ image on the touch-sensitive display; and

detecting contact with the touch-sensitive display that corresponds to a ~~predefined gesture~~ the gesture input with respect to the image.

~~43. The method of claim 1, wherein the device comprises a touch sensitive display, and wherein satisfying the condition~~completion of the gesture input ~~comprises:~~  
~~— displaying an image on the touch sensitive display; and~~  
~~— detecting contact with the touch sensitive display that corresponds to moving the image to a predefined location on the touch sensitive display.~~

~~53. The method of claim 1, wherein the device comprises a touch sensitive display, and wherein~~ completion of the gesture input~~satisfying the condition~~ comprises:  
displaying ~~an~~ the image on the touch-sensitive display; and  
detecting contact with the touch-sensitive display that corresponds to moving the image along a predefined path on the touch-sensitive display.

~~64. A portable electronic device (100700), comprising:~~  
a touch-sensitive display (~~126~~714);  
memory (102);  
one or more processors (106); and  
one or more modules stored in memory and configured for execution by the one or more processors (106), the one or more modules including instructions for:

while the device (~~100~~700) is in a first user-interface state, detecting progress towards ~~satisfaction of a user input condition~~completion of a gesture input needed to transition to a second user-interface state;

~~—~~ characterised in that

~~—~~ the gesture input includes dragging an image (702) to a predefined location on the touch-sensitive display (714), and in that the one or more modules further include instructions for:

while the device (~~100~~700) is in the first user-interface state, indicating (604) progress ~~towards satisfaction of the condition~~of the gesture input by transitioning an optical intensity of one or more user interface objects (~~708~~) ~~associated with the second user interface state without being associated with the first user interface state~~, wherein at least one of the one or more user interface objects (~~708~~) ~~associated with the second user interface state~~ is not displayed prior to detecting progress towards ~~satisfaction of the user input condition~~completion of the gesture input and,

\_\_\_\_\_ wherein transitioning of the optical intensity includes the one or more user interface objects (708) ~~associated with the second user interface state~~ appearing and increasing in optical intensity; and

transitioning (606) the device (100700) to the second user-interface state if the ~~condition is satisfied~~ gesture input is completed.

~~7. The device of claim 6, wherein satisfying the condition comprises detecting contact with the touch sensitive display that corresponds to a predefined gesture.~~

85. The device of claim 64, wherein the one or more modules further include instructions for satisfying the condition comprises:

displaying ~~an~~ the image on the touch-sensitive display; and

detecting contact with the touch-sensitive display that corresponds to ~~a predefined gesture~~ the gesture input with respect to the image.

~~97. The device of claim 65, wherein completion of the gesture input satisfying the condition comprises:-~~

~~—displaying an image on the touch sensitive display; and~~

~~—detecting contact with the touch sensitive display that corresponds to moving the image to a predefined location on the touch sensitive display.~~

106. The device of claim 64, wherein completion of the gesture input satisfying the condition comprises:

displaying ~~an~~ the image on the touch-sensitive display; and

detecting contact with the touch-sensitive display that corresponds to moving the image along a predefined path on the touch-sensitive display.

117. A computer readable storage medium having stored therein executable instructions, which when executed by an electronic device (100700) having a touch-sensitive display (714), cause the device (100700) to:

while the device (100700) is in a first user-interface state, detect progress towards ~~satisfaction of a user input condition~~ completion of a gesture input on the touch-sensitive display (714) needed to transition to a second user-interface state;

\_\_\_\_\_ characterised in that

~~the gesture input includes dragging an image (702) to a predefined location on the touch-sensitive display (714), and in that said executable instructions, when executed by the electronic device (100), further cause the device (100) to:~~

~~while the device (100) is in the first user-interface state, indicate (604) progress towards satisfaction of the condition of the gesture input by transitioning an optical intensity of one or more user interface objects (708) associated with the second user interface state without being associated with the first user interface state, wherein at least one of the one or more user interface objects (708) associated with the second user interface state is not displayed prior to detecting progress towards satisfaction of the user input completion of the gesture input condition and, wherein transitioning the optical intensity includes the one or more user interface objects (708) associated with the second user interface state appearing and increasing in optical intensity; and~~

~~transition (606) the device (100) to the second user-interface state if the condition is satisfied gesture input is completed.~~

~~12. The computer readable storage medium of claim 11, wherein the device comprises a touch sensitive display, and wherein detecting progress towards satisfaction of the condition includes detecting contact with the touch sensitive display corresponding to a predefined gesture.~~

~~13. The computer readable storage medium of claim 11, wherein the device comprises a touch sensitive display, and wherein the executable instructions further cause the device to detecting progress towards satisfaction of the condition includes:~~

~~displaying an the image on the touch-sensitive display; and~~

~~detecting contact with the touch-sensitive display corresponding to a predefined gesture the gesture input with respect to the image.~~

~~14. The computer readable storage medium of claim 11, wherein the device comprises a touch sensitive display, and wherein detecting progress towards completion of the gesture inputsatisfaction of the condition includes:~~

~~displaying an image on the touch sensitive display; and~~

~~detecting contact with the touch sensitive display corresponding to moving the image to a predefined location on the touch sensitive display.~~

159. The computer readable storage medium of claim 117, ~~wherein the device comprises a touch sensitive display, and wherein detecting progress towards~~ completion of the gesture ~~inputsatisfaction of the condition~~ includes:

displaying ~~an~~ the image on the touch-sensitive display; and

detecting contact with the touch-sensitive display corresponding to moving the image along a predefined path on the touch-sensitive display.