Público (Cliente)

Next.js Route Handler / ReservationService

PostgreSQL (Transação ACID)

NotificationService (Resend)

Atendente (Balcão)

1 POST /api/portal/reservas (sessionId, seatIds, buyer)

2 Valida antecedência (>= 60 min) e ordena seatIds

3 BEGIN TRANSACTION

4 SELECT * FROM session_seats WHERE id IN (...) FOR UPDATE

**alt** [Algum assento não está AVAILABLE (e não expirado JIT)]

5 Retorna status != AVAILABLE

6 ROLLBACK

7 HTTP 409 Conflict (Poltrona indisponível)

**[Todos os assentos disponíveis]**

8 INSERT INTO reservations (code: CD-XXXX, status: PENDING, expiresAt)

9 UPDATE session_seats SET status = 'RESERVED', reservation_id = id

10 COMMIT

11 sendReservationVoucher(reservationId)

12 UPDATE reservations SET email_sent_at = NOW()

13 HTTP 201 Created (Voucher CD-XXXX)

Espectador comparece à bilheteria até 60 min antes da sessão

14 POST /api/bilheteria/reservas/confirmar (code: CD-XXXX)

15 BEGIN TRANSACTION + SELECT reservation FOR UPDATE

16 Verifica se NOW() <= expiresAt (Regra JIT 60 min)

17 UPDATE reservations SET status = 'CONFIRMED', confirmed_at = NOW()

18 UPDATE session_seats SET status = 'SOLD'

19 INSERT INTO tickets (status: 'SOLD', operator_id)

20 COMMIT

21 HTTP 200 OK (Ingressos Emitidos)