


Neuronify: a new tool for creating simple neural networks

Simen Tennøe,
Svenn-Arne Dragly,
Andreas V. Solbrå,
Milad H. Mobarhan

CINPLA - University of Oslo
Wednesday 29th April, 2015




In this lecture we will introduce Neuronify, a new tool for creating neural networks



Integrate and fire neurons




Neuronify




Exercises


We do not need all information in the action potential for a neuron in a network and can create an approximation




We do not need all information in the action potential for a neuron in a network and can create an approximation



We do not need all information in the action potential for a neuron in a network and can create an approximation



We do not need all information in the action potential for a neuron in a network and can create an approximation



The integrate and fire neuron is much faster to evaluate than the Hodgkin-Huxley neuron

Hodgkin-Huxley

The integrate and fire neuron is much faster to evaluate than the Hodgkin-Huxley neuron

Hodgkin-Huxley

$$\begin{aligned}C \frac{dV}{dt} &= I_{inj} - \bar{g}_{Na} m^3 h (V - V_{Na}) - \bar{g}_K n^4 (V - V_K) - g_L (V - V_L) \\ \frac{dn}{dt} &= \alpha_n(V)(1 - n) - \beta_n(V)n \quad \frac{dm}{dt} = \alpha_m(V)(1 - m) - \beta_m(V)m \\ \frac{dh}{dt} &= \alpha_h(V)(1 - h) - \beta_h(V)h \quad \alpha_n(V) = \frac{0.01(V + 55)}{1 - \exp[-(V + 55)/10]} \\ \beta_n(V) &= 1.125 \exp[-(V + 65)/80] \quad \alpha_m(V) = \frac{0.1(V + 40)}{1 - \exp[-(V + 40)/10]} \\ \beta_m(V) &= 4 \exp[-(V + 65)/18] \quad \alpha_h(V) = 0.07 \exp[-(V + 65)/20] \\ \beta_h(V) &= \frac{1}{1 + \exp[-(V + 35)/10]}\end{aligned}$$

The integrate and fire neuron is much faster to evaluate than the Hodgkin-Huxley neuron

Hodgkin-Huxley

$$\begin{aligned}C \frac{dV}{dt} &= I_{inj} - \bar{g}_{Na} m^3 h (V - V_{Na}) - \bar{g}_K n^4 (V - V_K) - g_L (V - V_L) \\ \frac{dn}{dt} &= \alpha_n(V)(1 - n) - \beta_n(V)n \quad \frac{dm}{dt} = \alpha_m(V)(1 - m) - \beta_m(V)m \\ \frac{dh}{dt} &= \alpha_h(V)(1 - h) - \beta_h(V)h \quad \alpha_n(V) = \frac{0.01(V + 55)}{1 - \exp[-(V + 55)/10]} \\ \beta_n(V) &= 1.125 \exp[-(V + 65)/80] \quad \alpha_m(V) = \frac{0.1(V + 40)}{1 - \exp[-(V + 40)/10]} \\ \beta_m(V) &= 4 \exp[-(V + 65)/18] \quad \alpha_h(V) = 0.07 \exp[-(V + 65)/20] \\ \beta_h(V) &= \frac{1}{1 + \exp[-(V + 35)/10]}\end{aligned}$$

Integrate and fire

The integrate and fire neuron is much faster to evaluate than the Hodgkin-Huxley neuron


Hodgkin-Huxley

$$\begin{aligned}C \frac{dV}{dt} &= I_{inj} - \bar{g}_{Na} m^3 h (V - V_{Na}) - \bar{g}_K n^4 (V - V_K) - g_L (V - V_L) \\ \frac{dn}{dt} &= \alpha_n(V)(1 - n) - \beta_n(V)n \quad \frac{dm}{dt} = \alpha_m(V)(1 - m) - \beta_m(V)m \\ \frac{dh}{dt} &= \alpha_h(V)(1 - h) - \beta_h(V)h \quad \alpha_n(V) = \frac{0.01(V + 55)}{1 - \exp[-(V + 55)/10]} \\ \beta_n(V) &= 1.125 \exp[-(V + 65)/80] \quad \alpha_m(V) = \frac{0.1(V + 40)}{1 - \exp[-(V + 40)/10]} \\ \beta_m(V) &= 4 \exp[-(V + 65)/18] \quad \alpha_h(V) = 0.07 \exp[-(V + 65)/20] \\ \beta_h(V) &= \frac{1}{1 + \exp[-(V + 35)/10]}\end{aligned}$$


Integrate and fire

$$C_m \frac{dV(t)}{dt} = - \frac{V(t) - E_m}{R_m} + I$$


Example: learning in mice (Vasilaki et. al., 2009)



Example: learning in mice (Vasilaki et. al., 2009)



Example: learning in mice (Vasilaki et. al., 2009)




Neuronify is a new tool for creating neural networks



Download:

<http://cinpla.org/neuronify/>

Exercises



Exercises:

<http://cinpla.org/neuronify/>