




UWMM-Baseline: A Python Package for Supervised Classification of Underwater Military Munitions Using Multi-Modal Data

Taqi Hamoda¹, Hayat Rajani¹, Arthur Gleason², and Nuno Gracias¹

¹ University of Girona, Spain  ² University of Miami, USA

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

The presence of underwater military munitions (UWMM) in coastal and marine environments poses significant environmental and safety risks. Accurate detection and classification of UWMM are critical for remediation efforts, requiring robust methods to process multi-modal data, such as optical imagery and 3D reconstructions. UWMM detection leverages computer vision, machine learning, and 3D modeling to identify munitions against complex seabed backgrounds. Existing approaches, such as those only using image features (2D), often suffer from high false positive rates, necessitating the integration of geometric data (3D) to improve accuracy.

UWMM-Baseline is an open-source Python package designed for the supervised classification of UWMMs using multi-modal data, including optical imagery and depth-maps derived from 3D reconstructions of the scene. Building on the methodology of Gleason et al. (2015), the package implements a modular pipeline for dataset creation, feature extraction, classification, and evaluation. Key features include:

- **Dataset Creation:** Automated tile extraction and labeling from underwater imagery and depth-maps.
- **Feature Extraction:** Extraction of 2D-derived (color, texture) and 3D-derived (curvature, rugosity) features, which can be combined into a hybrid 2.5D feature set.
- **Classification:** Support for binary (UWMM vs. background) and multi-class (UWMM type) classification using Support Vector Machines (SVM).
- **Inference and Evaluation:** A complete inference pipeline to generate prediction masks on new data and quantitative evaluation using mean Intersection over Union (mIoU).
- **Modularity:** A flexible, configuration-driven framework allowing integration of new features, models, and data modalities.

UWMM-Baseline is designed for researchers, oceanographers, and environmental engineers working on UWMM detection, as well as educators teaching computer vision or marine science. It integrates with popular scientific Python libraries and supports workflows for both research and practical applications, such as seabed surveys and environmental monitoring. This package provides a modern implementation of Gleason et al. (2015) as a baseline benchmark for evaluating semantic segmentation performance on UWMMs.

Statement of Need

UWMM detection is a pressing challenge in marine environments, where legacy munitions from military activities contaminate coastlines and pose risks to ecosystems and human safety. Traditional detection methods, such as acoustic or optical imagery, are often limited by

40 resolution or seabed complexity. Optical imagery, combined with depth-maps, offers high-
41 resolution data for precise UWMM identification, as demonstrated by Gleason et al. (2015).
42 However, existing software tools for UWMM detection are either proprietary, domain-specific,
43 or lack the flexibility to handle multi-modal data in a unified framework.

44 UWMM-Baseline addresses this gap by providing a free, open-source, and modern implementation
45 of Gleason et al. (2015), an established UWMM classification model for semantic segmentation.
46 This package serves as a baseline benchmark for evaluating the performance of machine learning
47 UWMM classifiers. It provides a reliable benchmark against which the performance gains of
48 novel algorithms can be accurately measured and validated.

49 The package's modularity enables researchers to experiment with new features, classifiers, or
50 data sources (e.g., sonar, stereo vision), while its accessibility supports educational use in
51 courses on machine learning, oceanography, or environmental science. By providing a full
52 pipeline from data ingestion to evaluation, UWMM-Baseline lowers barriers to entry for UWMM
53 detection research, fostering innovation in environmental monitoring and remediation.

54 Background



Figure 1: Inference output of the UWMM baseline model. The leftmost image represents the output of the model trained exclusively on 2D-derived features, the central image shows the output of the model trained exclusively on 3D-derived features, and the rightmost image illustrates the output of the model trained on 2.5D extracted features.

55 The detection of UWMM in underwater environments involves processing optical imagery
56 to identify munitions against varied seabed backgrounds (e.g., coral reefs, seagrass). The
57 core challenge lies in distinguishing human-made objects from similarly shaped or textured
58 natural features. It was demonstrated that while 2D-derived features (color, texture) achieve
59 moderate accuracy (>80% for binary classification), they suffer from high false positives
60 due to background complexity (Gleason et al., 2015). Incorporating 3D-derived features
61 (e.g. curvature, rugosity) from depth-maps significantly improves accuracy (89-95%) and
62 reduces false positives, as these features capture the distinct geometric properties of munitions.
63 This combined, hybrid approach is referred to as the 2.5D approach.

64 The methodology is broken down into a multi-stage pipeline. First, large survey images are
65 processed into smaller, manageable tiles. This approach allows the model to learn local,
66 high-resolution features and creates a large, diverse dataset suitable for training supervised
67 machine learning models. The general workflow is as follows:

- 68 1. **Dataset Creation:** Optical images, depth maps, and ground-truth masks are used to
69 generate a labeled dataset of image tiles.
- 70 2. **Feature Extraction:** A comprehensive set of 2D-derived and 3D-derived features is
71 extracted from each tile.
- 72 3. **Model Training:** A classifier, such as an SVM, is trained on the extracted features.

- 73 4. **Inference:** The trained model is used to predict the locations of UWMM in new, unseen
74 images.
75 5. **Evaluation:** The model's predictions are compared against ground-truth data to assess
76 performance quantitatively.
- 77 This project implements this entire workflow in a configurable and automated pipeline, building
78 on the foundational work of Gleason et al. (2015). to provide an accessible software tool.

79 **Methodology**



Figure 2: The implemented classification framework is depicted in the above flowchart. The left section outlines the primary stages of the pipeline, while the right section details the specific components and features utilized in each stage.

80 The UWMM-Baseline pipeline processes underwater images, depth-maps, and masks to generate
81 a labeled dataset of uniformly sized tiles for training and testing. It identifies potential UWMM
82 and background locations using masks, extracting corresponding square tiles from image and
83 depth data. To address class imbalance, a fixed number of background tiles are sampled per
84 image, and only a subset of available UWMM pixels are used as tile centers. Data augmentation
85 is applied by rotating UWMM tiles at multiple angles.

86 From the processed tiles, 2D-derived and 3D-derived features are extracted, extending the
87 feature set proposed by Shihavuddin et al. (2014) and Gleason et al. (2015):

- 88 ■ **2D-derived Features (from optical images):**
- 89 – **Color Histograms:** HSV color distributions to capture seabed and UWMM appear-
90 ance (Shihavuddin et al., 2013).
 - 91 – **Local Binary Patterns (LBP):** Texture descriptors robust to illumination changes
92 (Ojala et al., 1994).
 - 93 – **Gray Level Co-occurrence Matrix (GLCM):** Texture metrics (e.g., contrast, dissim-
94 ilarity) for seabed characterization (Haralick et al., 1973).

- **Gabor Filters:** Edge and texture detection across multiple scales and orientations (Granlund, 1978).
- **3D-derived Features (from depth maps):**
 - **Principal Plane Features:** Statistics of depth values, polynomial coefficients from a fitted surface, and rugosity (ratio of surface area to planar area).
 - **Curvatures and Normals:** Mean and Gaussian curvatures, shape index, curvedness, and surface normal vector statistics.
 - **Symmetry Features:** Gabor filters applied to depth maps to capture structural symmetry.

The classifier is implemented using a SVM (Cortes & Vapnik, 1995) with a radial basis function (RBF) kernel, approximated via the Nystroem method (Williams & Seeger, 2000). The model supports training on 2D-derived, 3D-derived, or combined 2.5D feature sets. Prior to inference, superpixel segmentation (Achanta et al., 2012) identifies homogeneous regions in the input image. For each identified superpixel, a sliding window centered on its centroid is used to extract a series of overlapping tiles. These tiles are individually processed through the trained model to predict class labels. A neighborhood pool determines UWMM presence by evaluating whether the number of positive tile predictions within a region exceeds a predefined threshold. The final output is a segmentation mask indicating detected UWMM locations (see Figure 1).

This implementation leverages standard Python libraries, including NumPy (Harris et al., 2020), OpenCV (Bradski, 2000), scikit-learn (Pedregosa et al., 2011), scikit-image (Walt et al., 2014), and SciPy (Virtanen et al., 2020) for feature extraction, model training, and data processing.

Model Training and 3D-derived Feature Extraction

The classification pipeline in UWMM-Baseline relies on feature extraction and SVM-based classification. For a tile $x \in \mathbb{R}^{m \times n}$ (image) and corresponding depth-map $d \in \mathbb{R}^{m \times n}$, the feature vector $f_{2.5D}$ combines 2D-derived and 3D-derived features:

$$f_{2.5D} = [f_{2D}, f_{3D}]$$

The 3D-derived features, f_{3D} , are extracted from the depth-map of each tile. This process involves several calculations to describe the geometry of the surface.

A 2D-derived polynomial surface of the third degree is fitted to the depth-map of a tile to model its shape (Shihavuddin et al., 2014). The equation for this surface is:

$$f(x, y) = p_1 + p_2x + p_3y + p_4x^2 + p_5xy + p_6y^2 + p_7x^2y + p_8xy^2 + p_9y^3$$

The nine coefficients of this polynomial (p_1, \dots, p_9) are extracted through least-squares fitting and used as features (Shihavuddin et al., 2014).

Additional statistical features are calculated from the depth values (z_i) within a tile, including the standard deviation, skewness, and kurtosis (Shihavuddin et al., 2014). With z_m as the mean depth, S as the standard deviation, and N as the number of data points, the skewness and kurtosis are calculated as:

$$\text{Skewness} = \frac{\sum (z_i - z_m)^3}{(N - 1)S^3}$$

$$\text{Kurtosis} = \frac{\sum_{i=1}^N (z_i - z_m)^4}{(N - 1)S^4}$$

With regards to surface curvature, the Gaussian (G) and mean (M) surface curvatures are first calculated from the partial derivatives of the depth map where the two principal curvatures, k_1 and k_2 , can then be derived (Shihavuddin et al., 2014):

$$k_1 = M + \sqrt{M^2 - G}$$

$$k_2 = M - \sqrt{M^2 - G}$$

These principal curvatures are then used to calculate a shape index (S) and a curvedness index (C):

$$S = \frac{2}{\pi} \arctan \left(\frac{k_2 + k_1}{k_2 - k_1} \right), \quad C = \sqrt{\frac{k_1^2 + k_2^2}{2}}$$

Finally, rugosity (r) is computed to characterize the roughness of the seafloor habitat (Shihavuddin et al., 2014). It is calculated by dividing the contoured surface area of the tile (A_s) by the area of its orthogonal projection onto the principal plane (A_p):

$$r = \frac{A_s}{A_p}$$

Once the full feature vector is assembled, the SVM classifier solves the following optimization problem:

$$\min_{\mathbf{w}, b, \xi} \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_{i=1}^N \xi_i$$

subject to:

$$y_i(\mathbf{w}^T \phi(\mathbf{f}_i) + b) \geq 1 - \xi_i, \quad \xi_i \geq 0, \quad i = 1, \dots, N$$

where \mathbf{w} is the weight vector, b is the bias, ξ_i are slack variables, C is the regularization parameter, ϕ is the kernel mapping (RBF), and y_i are the class labels (Cortes & Vapnik, 1995).

Acknowledgements

This work was supported by the SERDP project MR23-3821, titled “Optically Derived 3D Models for Munitions Location and Identification”, funded by the DoD, DOE and EPA.

References

- Achanta, R., Shaji, A., Smith, K., Lucchi, A., Fua, P., & Süsstrunk, S. (2012). SLIC superpixels compared to state-of-the-art superpixel methods. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 34(11), 2274–2282. <https://doi.org/10.1109/TPAMI.2012.120>
- Bradski, G. (2000). The OpenCV Library. *Dr. Dobb's Journal of Software Tools*.
- Cortes, C., & Vapnik, V. (1995). Support-vector networks. *Machine Learning*, 20(3), 273–297. <https://doi.org/10.1007/BF00994018>

- 153 Gleason, A. C. R., Shihavuddin, A., Gracias, N., Schultz, G., & Gintert, B. E. (2015).
154 Improved supervised classification of underwater military munitions using height features
155 derived from optical imagery. *OCEANS 2015 - MTS/IEEE Washington*, 1–5. <https://doi.org/10.23919/OCEANS.2015.7404580>
156
- 157 Granlund, G. H. (1978). In search of a general picture processing operator. *Computer Graphics*
158 *and Image Processing*, 8(2), 155–173. [https://doi.org/10.1016/0146-664X\(78\)90047-3](https://doi.org/10.1016/0146-664X(78)90047-3)
- 159 Haralick, R. M., Shanmugam, K., & Dinstein, I. (1973). Textural features for image clas-
160 sification. *IEEE Transactions on Systems, Man, and Cybernetics*, SMC-3(6), 610–621.
161 <https://doi.org/10.1109/TSMC.1973.4309314>
- 162 Harris, C. R., Millman, K. J., Walt, S. J. van der, Gommers, R., Virtanen, P., Cournapeau, D.,
163 Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., Kerkwijk,
164 M. H. van, Brett, M., Haldane, A., Río, J. F. del, Wiebe, M., Peterson, P., ... Oliphant,
165 T. E. (2020). Array programming with NumPy. *Nature*, 585(7825), 357–362. <https://doi.org/10.1038/s41586-020-2649-2>
166
- 167 Ojala, T., Pietikainen, M., & Harwood, D. (1994). Performance evaluation of texture measures
168 with classification based on kullback discrimination of distributions. *Proceedings of 12th*
169 *International Conference on Pattern Recognition*, 1, 582–585 vol.1. <https://doi.org/10.1109/ICPR.1994.576366>
170
- 171 Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M.,
172 Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D.,
173 Brucher, M., Perrot, M., & Duchesnay, E. (2011). Scikit-learn: Machine learning in Python.
174 *Journal of Machine Learning Research*, 12, 2825–2830.
- 175 Shihavuddin, A. S. M., Gracias, N., Garcia, R., Campos, R., Gleason, A. C. R., & Gintert,
176 B. (2014). Automated detection of underwater military munitions using fusion of 2D and
177 2.5D features from optical imagery. *Marine Technology Society Journal*, 48(4), 61–71.
178 <https://doi.org/doi:10.4031/MTSJ.48.4.7>
- 179 Shihavuddin, A. S. M., Gracias, N., Garcia, R., Gleason, A. C. R., & Gintert, B. (2013). Image-
180 based coral reef classification and thematic mapping. *Remote Sensing*, 5(4), 1809–1841.
181 <https://doi.org/10.3390/rs5041809>
- 182 Virtanen, P., Gommers, R., Oliphant, T. E., Haberland, M., Reddy, T., Cournapeau, D.,
183 Burovski, E., Peterson, P., Weckesser, W., Bright, J., van der Walt, S. J., Brett, M., Wilson,
184 J., Millman, K. J., Mayorov, N., Nelson, A. R. J., Jones, E., Kern, R., Larson, E., ... SciPy
185 1.0 Contributors. (2020). SciPy 1.0: Fundamental Algorithms for Scientific Computing in
186 Python. *Nature Methods*, 17, 261–272. <https://doi.org/10.1038/s41592-019-0686-2>
- 187 Walt, S. van der, Schönberger, J. L., Nunez-Iglesias, J., Boulogne, F., Warner, J. D., Yager,
188 N., Gouillart, E., Yu, T., & contributors, the scikit-image. (2014). Scikit-image: Image
189 processing in Python. *PeerJ*, 2, e453. <https://doi.org/10.7717/peerj.453>
- 190 Williams, C. K. I., & Seeger, M. (2000). Using the nyström method to speed up kernel machines.
191 *Proceedings of the 14th International Conference on Neural Information Processing Systems*,
192 661–667.