

Geist

A multimodal data transformation, query, and reporting language

Meng Li, Timothy McPhillips, Bertram Ludäscher

Copyright © 2023-2025, CIRSS

Table of contents

| | |
|-----------------------------------|----|
| 1. Welcome to Geist documentation | 3 |
| 1.1 Features | 3 |
| 1.2 Demo for SciPy 2024 | 3 |
| 2. Setup | 4 |
| 3. Geist Templates | 5 |
| 3.1 Geist Templates | 5 |
| 3.2 Tags | 9 |
| 4. CLI | 21 |
| 4.1 Command report | 21 |
| 4.2 Command create | 23 |
| 4.3 Command destroy | 25 |
| 4.4 Command export | 26 |
| 4.5 Command graph | 27 |
| 4.6 Command load | 28 |
| 4.7 Command query | 29 |
| 5. Python API | 31 |
| 5.1 Class Connection | 31 |
| 5.2 Functions | 42 |
| 6. Changelog | 51 |

1. Welcome to Geist documentation

Geist is a new templating language for declarative data manipulation, query, and report generation. Building on the [Jinja2](#) template engine, Geist is designed to support diverse data backends and query engines via predefined tags and filters, and may be extended with custom tags. A single Geist template may include multiple queries expressed in different languages, e.g. SQL and SPARQL, to leverage the strengths of each for clarity and ease of maintenance. Because Geist both can generate reports in diverse formats and perform inserts and updates on new or existing databases during template expansion, Geist templates may orchestrate data extraction, transformation, and load operations spanning multiple tools and data storage systems. The Geist Python package can be installed easily and accessed via the command line. If your dataset is stored in DuckDB and SPARQL queries are more suitable for your problem, then Geist might be for you! Check out our [Poster](#) for [SciPy 2024](#)!

At the moment, Geist supports [DuckDB](#) and [RDFLib](#). More types of data backends will be available in the near future.

1.1 Features

Both CLI and Python API provide the following features:

- [report](#) feature: expand a report using dataset(s)
- [create](#) feature: create a new dataset
- [destroy](#) feature: delete a dataset
- [export](#) feature: export a graph
- [graph](#) feature: visualize a dataset
- [load](#) feature: import data into a dataset
- [query](#) feature: perform a query on a dataset

1.2 Demo for SciPy 2024

A Geist report that employs two different query languages. We demonstrate how Geist can be used to extract triples from a relational database, store them as a RDF dataset, and perform SPARQL queries on it. Instead of purely in-memory operations, Geist can be used to migrate data. With the hamming numbers dataset stored in DuckDB as an input, we generate a [report](#) to describe the original dataset and the subgraph extracted via SQL and SPARQL queries using a single [Geist script](#).

2. Setup

Before installing Geist, please make sure [Graphviz](#) is installed.

Example: GitHub Codespaces

```
sudo apt-get update && sudo apt-get install -y graphviz graphviz-dev
```

Example: Google Colab (Jupyter Notebook)

```
apt install libgraphviz-dev
```

Install Geist:

```
pip install geist-p
```

To check Geist is working, run `geist` in the command line. You should get the following output:

```
Usage: geist [OPTIONS] COMMAND [ARGS]...

Options:
  --help  Show this message and exit.

Commands:
  create  Create a new dataset
  destroy Delete a dataset
  export  Export a dataset
  graph   Visualize a dataset
  load    Import data into a dataset
  query   Perform a query on a dataset
  report  Expand a report using dataset(s)
```

3. Geist Templates

3.1 Geist Templates

3.1.1 What is a Geist template?

A Geist template is a text file without a specific extension requirement although adding a `.geist` extension is recommended. It is an extension of a [Jinja template](#), therefore it follows the default Jinja delimiters:

- `{% ... %}` for Statements
- `{{ ... }}` for Expressions to print to the template output
- `{# ... #}` for Comments not included in the template output

3.1.2 How to write a Geist template?

A Geist template relies on tags and filters.

Tags

Tags are used within the statements, i.e., `{% ... %}`. There are two types of tags, `StandaloneTag` and `ContainerTag`. While the `StandaloneTag` does not require a closing tag, the `ContainerTag` does. Besides the Jinja [predefined tags](#) (e.g., `for`), Geist supports the following tags:

`StandaloneTag` :

- `destroy`
- `graph`
- `graph2`
- `use`

`ContainerTag` :

- `create`
- `load`
- `query`
- `component`
- `map`
- `html`
- `img`
- `table`

Custom tags can be defined through files with the `use` tag.

Filters

Filters are used to modify variables. Each filter can only take one variable as input. Multiple filters can be applied to a single variable in sequence. For example, `{{ var|filter1|filter2|filter3 }}` denotes the variable `var` will be processed through `filter1` first, then `filter2`, and `filter3` at the end.

Besides the Jinja [predefined filters](#), Geist supports the following filters:

- **head**: extract the first 5 rows of a Pandas data frame
- **csv2df**: convert a CSV string to a Pandas data frame
- **dict2df**: convert a dictionary to a Pandas data frame
- **json2df**: convert a JSON string to a Pandas data frame
- **json2dict**: convert a JSON string to a dictionary
- **df2json**: convert a Pandas data frame to a JSON string
- **df2htmltable**: convert a Pandas data frame to an HTML table
- **escape_quotes**: escape both double and single quotation marks
- **process_str_for_html**: preprocess a string to be displayed within an HTML document, e.g., replace `<` with `<`

3.1.3 How to execute (expand) a Geist template?

CLI

report command can expand a report (Geist template) using dataset(s).

Here are options of the *report* command:

```
Usage: geist report [OPTIONS]

Expand a report using dataset(s)

Options:
  -ifile, --inputfile FILENAME  Path of the file containing the report
                                template to expand [required]
  -oroot, --outputroot TEXT     Path of the directory to store the
                                report (default: current directory)
  -so, --suppressoutput BOOLEAN Suppress output or not (default: False)
  -a, --args <TEXT TEXT>...    Arguments to be passed to the report
                                template, e.g., (arg, value)

indicates that                  {{ arg }} in the report template will
be                               replaced by value
--help                          Show this message and exit.
```

Example 1: expand a report from stdin

```
geist report << END_TEMPLATE

{% create "test", datastore="rdflib", inputformat="nt",
isfilepath=False %}
<http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-
syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
<http://example.com/drewp> <http://example.com/says> "Hello
World" .
{% endcreate %}

{% query "test", datastore="rdflib", isfilepath=False as
all_triples %}
SELECT ?s ?p ?o
WHERE {
  ?s ?p ?o
}
ORDER BY ?s ?p ?o
{% endquery %}

{% for _, row in all_triples.iterrows() %}
  Subject: {{ row["s"] }}, Predicate: {{ row["p"] }}, Object:
  {{ row["o"] }}.
{% endfor %}

{% destroy "test", datastore="rdflib" %}

END_TEMPLATE
```

Example 2: expand a report from a file

```
geist report --inputfile report.geist

{% create "test", datastore="rdflib", inputformat="nt",
isfilepath=False %}
<http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-
syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
<http://example.com/drewp> <http://example.com/says> "Hello
World" .
{% endcreate %}

{% query "test", datastore="rdflib", isfilepath=False as
all_triples %}
SELECT ?s ?p ?o
WHERE {
    ?s ?p ?o
}
ORDER BY ?s ?p ?o
{% endquery %}

{% for _, row in all_triples.iterrows() %}
    Subject: {{ row["s"] }}, Predicate: {{ row["p"] }}, Object:
    {{ row["o"] }}.
{% endfor %}

{% destroy "test", datastore="rdflib" %}
```

Example 3: expand a report from a file with external arguments

```
geist report --inputfile report.geist --args sentence "Hello
World" --args feeling Happy

{% create "test", datastore="rdflib", inputformat="nt",
isfilepath=False %}
<http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-
syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
<http://example.com/drewp> <http://example.com/says>
"{{ sentence }}" .
<http://example.com/drewp> <http://example.com/feels>
"{{ feeling }}" .
{% endcreate %}

{% query "test", datastore="rdflib", isfilepath=False as
all_triples %}
SELECT ?s ?p ?o
WHERE {
    ?s ?p ?o
}
ORDER BY ?s ?p ?o
{% endquery %}

{% for _, row in all_triples.iterrows() %}
    Subject: {{ row["s"] }}, Predicate: {{ row["p"] }}, Object:
    {{ row["o"] }}.
{% endfor %}

{% destroy "test", datastore="rdflib" %}
```

Python API

report function can expand a report (Geist template) using dataset(s).

Parameters description for *report()*:

| Name | Description |
|----------------|---|
| inputfile | String. A report to be expanded ([required]) |
| isinputpath | Bool. <code>True</code> if the inputfile is the file path, otherwise the inputfile is the content (by default, <code>False</code>) |
| outputroot | String. Path of the directory to store the expanded report (by default, current directory, i.e., <code>./</code>) |
| suppressoutput | Bool. <code>True</code> to suppress output (by default, <code>True</code>) |
| args | Dict. External arguments, e.g., <code>{"arg1": "value1", "arg2": "value2"}</code> denotes that <code>{{ arg1 }}</code> and <code>{{ arg2 }}</code> in the report template will be replaced by <code>value1</code> and <code>value2</code> respectively (by default, <code>{}</code>) |

Example 1: expand a report from a string

```
import geist

report = """

{% create "test", datastore="rdflib", inputformat="nt",
isfilepath=False %}
<http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-
syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
<http://example.com/drewp> <http://example.com/says> "Hello
World" .
{% endcreate %}

{% query "test", datastore="rdflib", isfilepath=False as
all_triples %}
SELECT ?s ?p ?o
WHERE {
    ?s ?p ?o
}
ORDER BY ?s ?p ?o
{% endquery %}

{% for _, row in all_triples.iterrows() %}
    Subject: {{ row["s"] }}, Predicate: {{ row["p"] }}, Object:
    {{ row["o"] }}.
{% endfor %}

{% destroy "test", datastore="rdflib" %}

"""

# Return the expanded report as a string variable named
expanded_report
expanded_report = geist.report(inputfile=report)
```

Example 2: expand a report from a file

```
import geist

# Return the expanded report as a string variable named
expanded_report
expanded_report = geist.report(inputfile='report.geist',
                              isinputpath=True)
```

Here is the report.geist file:

```
{% create "test", datastore="rdflib", inputformat="nt",
isfilepath=False %}
<http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-
syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
<http://example.com/drewp> <http://example.com/says> "Hello
World" .
{% endcreate %}

{% query "test", datastore="rdflib", isfilepath=False as
all_triples %}
SELECT ?s ?p ?o
WHERE {
    ?s ?p ?o
}
ORDER BY ?s ?p ?o
{% endquery %}

{% for _, row in all_triples.iterrows() %}
    Subject: {{ row["s"] }}, Predicate: {{ row["p"] }}, Object:
    {{ row["o"] }}.
{% endfor %}

{% destroy "test", datastore="rdflib" %}
```

Example 3: expand a report from a file with external arguments

```
import geist

# Return the expanded report as a string variable named
expanded_report
expanded_report = geist.report(
    inputfile='report.geist',
    isinputpath=True,
    args={
        "sentence": "Hello World",
        "feeling": "Happy"
    }
)
```

Here is the report.geist file:

```
{% create "test", datastore="rdflib", inputformat="nt",
isfilepath=False %}
<http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-
syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
<http://example.com/drewp> <http://example.com/says>
"{{ sentence }}" .
<http://example.com/drewp> <http://example.com/feels>
"{{ feeling }}" .
{% endcreate %}

{% query "test", datastore="rdflib", isfilepath=False as
all_triples %}
SELECT ?s ?p ?o
WHERE {
    ?s ?p ?o
}
ORDER BY ?s ?p ?o
{% endquery %}

{% for _, row in all_triples.iterrows() %}
    Subject: {{ row["s"] }}, Predicate: {{ row["p"] }}, Object:
    {{ row["o"] }}.
{% endfor %}

{% destroy "test", datastore="rdflib" %}
```


3.2 Tags

3.2.1 Tag create

The `create` tag creates a dataset based on the given string. By default, the given string is a file path. However, it can be updated by setting the `isfilepath` field to `False`. Here are parameters of the `create` tag:

| Name | Description |
|--------------------------|--|
| <code>dataset</code> | Name of RDF dataset to create (by default, <code>kb</code>) |
| <code>datastore</code> | Data backend. <code>duckdb</code> and <code>rdflib</code> are available for now. (by default, <code>rdflib</code>) |
| <code>inputformat</code> | Format of the file to be loaded as triples (by default, <code>json-ld</code>). It has to be one of { <code>xml</code> , <code>n3</code> , <code>turtle</code> , <code>nt</code> , <code>pretty-xml</code> , <code>trix</code> , <code>trig</code> , <code>nquads</code> , <code>json-ld</code> , <code>hext</code> , <code>csv</code> } |
| <code>infer</code> | Inference to perform on update choosing from { <code>none</code> , <code>rdfs</code> , <code>owl</code> , <code>rdfs_owl</code> } (by default, <code>none</code>). Please check OWL-RL document for detailed information. |
| <code>isfilepath</code> | A bool value to denote if the given data is a file path or not (by default: <code>True</code> , which denotes the given data is a file path) |
| <code>table</code> | Table name. Available for <code>duckdb</code> data backend only. |
| <code>colnames</code> | Column names of triples with the format of <code>[[subject1, predicate1, object1], [subject2, predicate2, object2], ...]</code> when the input format is <code>csv</code> (by default, <code>None</code>). Available for <code>rdflib</code> data backend only. |

Example 1: the given string is not a file path

```
{% create "test", datastore="rdflib", inputformat="nt",
isfilepath=False %}
<http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
<http://example.com/drewp> <http://example.com/says> "Hello World" .
{% endcreate %}
```

Example 2: the given string is a file path

Here is the `test.nt` file:

```
<http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
<http://example.com/drewp> <http://example.com/says> "Hello World" .
```

Code:

```
{% create "test", datastore="rdflib", inputformat="nt",
isfilepath=True %} test.nt {% endcreate %}
```

3.2.2 Tag destroy

The `destroy` tag deletes a dataset. Here are parameters of the `destroy` tag:

| Name | Description |
|------------------------|---|
| <code>dataset</code> | Name of RDF dataset to be removed (default <code>kb</code>) |
| <code>datastore</code> | Data backend. <code>duckdb</code> and <code>rdflib</code> are available for now. (by default, <code>rdflib</code>) |
| <code>quiet</code> | Suppress error messages if the provided dataset does not exist |

Example: delete the `test` dataset

```
{% destroy dataset="test" %}
```

OR

```
{% destroy "test" %}
```

The `.geistdata/test.pkl` file will be removed after this operation. By default, you will get an error message if the provided dataset (in this case, it is the `test` dataset) does not exist. To suppress this error message, you can add the `quiet` parameter:

```
{% destroy "test", quiet=True %}
```

3.2.3 Tag graph

The `graph` tag visualizes a dataset. Here are parameters of the `graph` tag:

| Name | Description |
|------------------------|--|
| <code>dataset</code> | Name of RDF dataset to be visualized (default <code>kb</code>) |
| <code>datastore</code> | Data backend. <code>duckdb</code> and <code>rdflib</code> are available for now. (by default, <code>rdflib</code>) |
| <code>rankdir</code> | Direction of the graph (default <code>TB</code>): <code>TB</code> or <code>BT</code> or <code>LR</code> or <code>RL</code> |
| <code>mappings</code> | File of the mappings to shorten text (str): path of a JSON file, where the key is the original text and the value is the shorter text. |
| <code>on</code> | Column(s) to be mapped (default <code>None</code> , which means all columns will be mapped) |
| <code>samecolor</code> | A bool value to denote if all edges are filled with the same color (default: <code>True</code>) |

Example: visualize the `test` dataset

```
{% graph "test", datastore="rdflib" %}
```

3.2.4 Tag graph2

The `graph2` tag visualizes a dataset. It does not rely on the `PyGraphviz` package, which makes it more flexible compared to the `graph` tag. Here are parameters of the `graph2` tag:

| Name | Description |
|-----------------------|--|
| <code>dataset</code> | Name of RDF dataset to be visualized (default <code>kb</code>) |
| <code>rankdir</code> | Direction of the graph (default <code>TB</code>): <code>TB</code> or <code>BT</code> or <code>LR</code> or <code>RL</code> |
| <code>mappings</code> | File of the mappings to shorten text (str): path of a JSON file, where the key is the original text and the value is the shorter text. |
| <code>on</code> | Column(s) to be mapped (default <code>None</code> , which means all columns will be mapped) |
| <code>...</code> | Graph attributes of Graphviz |

Example: visualize the `test` dataset

```
{% graph2 dataset="test" %}
```

3.2.5 Tag load

The `load` tag imports data into a dataset. Here are parameters of the `load` tag:

| Name | Description |
|--------------------------|--|
| <code>dataset</code> | Name of RDF dataset to be removed (default <code>kb</code>) |
| <code>datastore</code> | Data backend. <code>duckdb</code> and <code>rdflib</code> are available for now. (by default, <code>rdflib</code>) |
| <code>inputformat</code> | Format of the file to be loaded as triples (default <code>json-ld</code>) |
| <code>isfilepath</code> | A bool value to denote if the given data is a file path or not (default <code>True</code> , which denotes the given data is a file path) |
| <code>table</code> | Table name to be loaded. Available for <code>duckdb</code> data backend only. |
| <code>colnames</code> | Column names of triples with the format of <code>[[subject1, predicate1, object1], [subject2, predicate2, object2], ...]</code> when the input format is csv. Available for <code>rdflib</code> data backend only. |

Example: load a file into the `test` dataset

```
{% load "test", datastore="rdflib" %} test_add.jsonld {% endload %}
```

3.2.6 Tag query

The `query` tag performs a query on a dataset and returns a Pandas DataFrame. Here are parameters of the `query` tag:

| Name | Description |
|-------------------------|--|
| <code>dataset</code> | Name of a dataset to query (default <code>kb</code>) |
| <code>datastore</code> | Data backend. <code>duckdb</code> and <code>rdflib</code> are available for now. (by default, <code>rdflib</code>) |
| <code>isfilepath</code> | A bool value to denote if the given data is a file path or not (default <code>True</code> , which denotes the given data is a file path) |

Example 1: the given string is not a file path

```
{% query "test", datastore="rdflib", isfilepath=False %}
SELECT ?s ?p ?o
WHERE {
    ?s ?p ?o
}
ORDER BY ?s ?p ?o
{% endquery %}
```

Example 2: the given string is a file path

```
{% query "test", datastore="rdflib", isfilepath=True %} query_file {%
endquery %}
```

Here is the `query_file`'s content:

```
SELECT ?s ?p ?o
WHERE {
    ?s ?p ?o
}
ORDER BY ?s ?p ?o
```

3.2.7 Tag component

The `component` tag finds connected components in a graph. It will return a dict where the key is the index of a component (e.g., 0, 1, 2, ...) and the value is a connected component. By default, the given string is a file path.

However, it can be updated by setting the `isfilepath` field to False. Here are parameters of the `component` tag:

| Name | Description |
|-------------------------|---|
| <code>isfilepath</code> | A bool value to denote if the given data is a file path or not (by default: <code>True</code> , which denotes the given data is a file path) |
| <code>edges</code> | A list of list. <code>[[start_node1, end_node1], [start_node2, end_node2], ...]</code> or <code>[[start_node1, end_node1, label1], [start_node2, end_node2, label2], ...]</code> where these items are column names |

3.2.8 Tag map

The `map` replaces the original string (JSON string) on selected columns (if provides) with the shorter ones based on the given mappings. By default, the given string is a file path. However, it can be updated by setting the `isfilepath` field to `False`. A Pandas DataFrame will be returned. Here are parameters of the `map` tag:

| Name | Description |
|-------------------------|--|
| <code>isfilepath</code> | A bool value to denote if the given data is a file path or not (by default: <code>True</code> , which denotes the given data is a file path) |
| <code>mappings</code> | File of the mappings to shorten text (str): path of a JSON file, where the key is the original text and the value is the shorter text. |
| <code>on</code> | A column or a list of selected columns. All columns will be selected by default (<code>None</code>) |

data.json

```
{
  "v1": {"0":"test_a1","1":"test_b1","2":"test_c1"},
  "v2": {"0":"test_a2","1":"test_b2","2":"test_c2"},
  "v3": {"0":"test_a3","1":"test_b3","3":"test_c3"}
}
```

mapping.json

```
{"test_": ""}
```

Example 1: replace all columns

```
{%- map mappings="mappings.json" as res %} data.json {% endmap %}
{{ res }}
```

Expected output:

```
v1,v2,v3
a1,a2,a3
b1,b2,b3
c1,c2,c3
```

Example 2: replace selected columns

```
{% map mappings="mappings.json", on=["v1","v2"] as res %} data.json {%
endmap %}
{{ res }}
```

Expected output:

```
v1,v2,v3
a1,a2,test_a3
b1,b2,test_b3
c1,c2,test_c3
```

If only "v1" column need to be replaced, you can replace `on=["v1", "v2"]` with `on="v1"`.

3.2.9 Tag html

The `html` tag formats and saves the string as a HTML file.
Here is a parameter of the `html` tag:

| Name | Description |
|-------------------|---|
| <code>path</code> | Path of the HTML file to be saved. By default, <code>report.html</code> |

Save the Hello World! string as a file

```
{% html %}Hello World!{% endhtml %}
```

Expected content of the `report.html` file:

```
<!DOCTYPE html>
<html>
Hello World!
</html>
```

3.2.10 Tag img

The `img` tag renders Graphviz code as an image and embeds it into HTML. Here are parameters of the `img` tag:

| Name | Description |
|------|--|
| src | Path of the rendered image to be saved. Various extensions are supported. Check PyGraphviz Docs for the whole list. Note: <code>dot</code> or <code>gv</code> will show code directly. |
| ... | Attributes of the HTML or the HTML tag |

Example 1: render as svg

```
{% img src="test.svg" %}digraph test_graph { node1 -> node2 }{% endingimg %}
```

A file named `test.svg` will be created and the Geist template will be updated as:

```

```

Example 2: render as gv

```
{% img src="test.gv" %}digraph test_graph { node1 -> node2 }{% endingimg %}
```

A file named `test.gv` will be created and the Geist template will be updated as:

```
<pre><code>digraph test_graph { node1 -> node2 }</code></pre>
```

3.2.11 Tag table

The `table` tag embeds query results to HTML as a table. Please make sure the stdin is a JSON string. Here are parameters of the `table` tag:

| Name | Description |
|-----------------------|--|
| <code>mappings</code> | File of the mappings to shorten text (str): path of a JSON file, where the key is the original text and the value is the shorter text. |
| <code>on</code> | A column or a list of selected columns. All columns will be selected by default (<code>None</code>) |

Example: embed query results as a table

```
{% table %}
{%- query isfilepath=False as query_results %}
  SELECT ?s ?p ?o
  WHERE {
    ?s ?p ?o
  }
  ORDER BY ?s ?p ?o
{% endquery %}
{{ query_results | df2json }}
{% endtable %}
```

It can also be done with the `df2htmltable` filter:

```
{%- query isfilepath=False as query_results %}
  SELECT ?s ?p ?o
  WHERE {
    ?s ?p ?o
  }
  ORDER BY ?s ?p ?o
{% endquery %}
{{ query_results | df2htmltable }}
```

3.2.12 Tag use

The `use` tag can be used to define custom tags. Here is a parameter of the `use` tag:

| Name | Description |
|-----------------------|--------------------------------------|
| <code>filepath</code> | Path of a file to define custom tags |

Here is the structure of tags to be defined within the file at the path `filepath`:

```
{% template TAG_NAME PARAM1 PARAM2 %}  
CONTENT  
{% endtemplate %}
```

You need to update `TAG_NAME`, `PARAM1`, `PARAM2`, and `CONTENT` based on your use case. `TAG_NAME` must be unique, which means you cannot define multiple tags with the same name. You can have any number of parameters, which means `{% template TAG_NAME %}` and `{% template TAG_NAME PARAM1 PARAM2 PARAM3 %}` are also valid. Nested tags are also supported, which means you can put another tag within the `CONTENT` part.

 **Example: define predicate_term and format_output tags**

- Write `{% use "templates.geist" %}` at the beginning of a Geist template, where you want to use the custom tags, i.e., `predicate_term` and `format_output` tags.
- Define custom tags in file with the path of `"templates.geist"`:

```
{% template predicate_term %}says{% endtemplate %}  
  
{% template format_output person sent %}  
  {{ person }} {% predicate_term %} {{sent}}  
{% endtemplate %}
```
- Use custom tags in the Geist template as other predefined tags (e.g., `create`)

```
{% use "templates.geist" %}  
  
{%- create inputformat="nt", isfilepath=False %}  
  <http://example.com/test1> <http://example.com/p1> "Hello World".  
  <http://example.com/test2> <http://example.com/p2> "What a Nice Day".  
{% endcreate %}  
  
{%- query "kb1", isfilepath=False as res %}  
  SELECT ?s ?o  
  WHERE {  
    ?s ?p ?o  
  }  
  ORDER BY ?s ?o  
{% endquery %}  
{% set all_triples = res | json2df %}  
  
{% for _, row in all_triples.iterrows() %}  
  {% format_output row["s"], row["o"] %}.  
{%- endfor %}  
  
{%- destroy %}
```
- Expected output:

```
<http://example.com/test1> says Hello World.  
<http://example.com/test2> says What a Nice Day.
```

4. CLI

4.1 Command report

report command can expand a report (Geist template) using dataset(s).

Here are options of the *report* command:

```
Usage: geist report [OPTIONS]

Expand a report using dataset(s)

Options:
  -ifile, --inputfile FILENAME  Path of the file containing the report
                                template to expand [required]
  -oroot, --outputroot TEXT      Path of the directory to store the expanded
                                report (default: current directory)
  -so, --suppressoutput BOOLEAN  Suppress output or not (default: False)
  -a, --args <TEXT TEXT>...     Arguments to be passed to the report
                                template, e.g., (arg, value) indicates that
                                {{ arg }} in the report template will be
                                replaced by value
  --help                        Show this message and exit.
```

Example 1: expand a report from stdin

```
geist report << END_TEMPLATE

{% create "test", datastore="rdflib", inputformat="nt", isfilepath=False %}
  <http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
  <http://example.com/drewp> <http://example.com/says> "Hello World" .
{% endcreate %}

{% query "test", datastore="rdflib", isfilepath=False as all_triples %}
  SELECT ?s ?p ?o
  WHERE {
    ?s ?p ?o
  }
  ORDER BY ?s ?p ?o
{% endquery %}

{% for _, row in all_triples.iterrows() %}
  Subject: {{ row["s"] }}, Predicate: {{ row["p"] }}, Object: {{ row["o"] }}.
{% endfor %}

{% destroy "test", datastore="rdflib" %}

END_TEMPLATE
```

Example 2: expand a report from a file

```
geist report --inputfile report.geist
```

Here is the report.geist file:

```
{% create "test", datastore="rdflib", inputformat="nt", isfilepath=False %}
  <http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
  <http://example.com/drewp> <http://example.com/says> "Hello World" .
{% endcreate %}

{% query "test", datastore="rdflib", isfilepath=False as all_triples %}
  SELECT ?s ?p ?o
  WHERE {
    ?s ?p ?o
  }
  ORDER BY ?s ?p ?o
{% endquery %}

{% for _, row in all_triples.iterrows() %}
  Subject: {{ row["s"] }}, Predicate: {{ row["p"] }}, Object: {{ row["o"] }}.
{% endfor %}

{% destroy "test", datastore="rdflib" %}
```

Example 3: expand a report from a file with external arguments

```
geist report --inputfile report.geist --args sentence "Hello World" --args feeling Happy
```

Here is the report.geist file:

```
{% create "test", datastore="rdflib", inputformat="nt", isfilepath=False %}  
  <http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .  
  <http://example.com/drewp> <http://example.com/says> "{{ sentence }}" .  
  <http://example.com/drewp> <http://example.com/feels> "{{ feeling }}" .  
{% endcreate %}  
  
{% query "test", datastore="rdflib", isfilepath=False as all_triples %}  
  SELECT ?s ?p ?o  
  WHERE {  
    ?s ?p ?o  
  }  
  ORDER BY ?s ?p ?o  
{% endquery %}  
  
{% for _, row in all_triples.iterrows() %}  
  Subject: {{ row["s"] }}, Predicate: {{ row["p"] }}, Object: {{ row["o"] }}.  
{% endfor %}  
  
{% destroy "test", datastore="rdflib" %}
```

4.2 Command create

The *create* command has two subcommands, both of which create a new dataset on disk. The dataset name `:memory:` is a reserved value for datasets that exist only in memory and is not allowed in the CLI.

```
Usage: geist create [OPTIONS] COMMAND [ARGS]...

Create a new dataset

Options:
  --help  Show this message and exit.

Commands:
  duckdb  Create a new SQL dataset using DuckDB
  rdflib  Create a new RDF dataset using RDFLib
```

geist create duckdb [OPTIONS]

```
Usage: geist create duckdb [OPTIONS]

Create a new SQL dataset using DuckDB

Options:
  -d, --dataset TEXT          Name of SQL dataset to create (default "kb")
  -ifile, --inputfile FILENAME Path of the file to be loaded as a Pandas
                              DataFrame [required]
  -iformat, --inputformat [csv|json]
                              Format of the file to be loaded as a Pandas
                              DataFrame (default csv)
  -t, --table TEXT           Name of the table to be created (default
                              "df")
  --help                     Show this message and exit.
```

Example 1: create a test SQL dataset from stdin

```
geist create duckdb --dataset test --inputformat csv --table df << __END_INPUT__
v1,v2,v3
1,2,3
4,5,6
7,8,9
__END_INPUT__
```

Example 2: create a test dataset from a file

Here is the `test.csv` file:

```
v1,v2,v3
1,2,3
4,5,6
7,8,9
```

Code:

```
geist create duckdb --dataset test --inputfile test.csv --inputformat csv --table df
```

geist create rdflib [OPTIONS]

Usage: geist create rdflib [OPTIONS]

Create a new RDF dataset

Options:

-d, --dataset TEXT Name of RDF dataset to create (default "kb")
 -ifile, --inputfile FILENAME Path of the file to be loaded as triples
 [required]
 -iformat, --inputformat [xml|n3|turtle|nt|pretty-xml|trix|trig|nquads|json-ld|hext|csv] Format of the file to be loaded as triples
 (default json-ld)
 --colnames TEXT Column names of triples with the format of
 [[subject1, predicate1, object1], [subject2,
 predicate2, object2], ...] when the input
 format is csv
 --infer [none|rdfs|owl|rdfs_owl] Inference to perform on update [none, rdfs,
 owl, rdfs_owl] (default "none")
 --help Show this message and exit.

Example 1: create a test RDF dataset from stdin

```
geist create rdflib --dataset test --inputformat nt --infer none << __END_INPUT__

<http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
<http://example.com/drewp> <http://example.com/says> "Hello World" .

__END_INPUT__
```

Example 2: create a test dataset from a file

Here is the `test.nt` file:

```
<http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
<http://example.com/drewp> <http://example.com/says> "Hello World" .
```

Code:

```
geist create rdflib --dataset test --inputfile test.nt --inputformat nt --infer none
```


4.3 Command destroy

`destroy` command can delete a dataset. The `.duckdb` or the `.pkl` file of the corresponding dataset will be discarded.

There are two subcommands for `destroy`:

```
Usage: geist destroy [OPTIONS] COMMAND [ARGS]...

Delete a dataset

Options:
  --help  Show this message and exit.

Commands:
  duckdb  Delete a SQL dataset
  rdflib  Delete an RDF dataset
```

geist destroy duckdb [OPTIONS]

```
Usage: geist destroy duckdb [OPTIONS]

Delete a SQL dataset

Options:
  -d, --dataset TEXT  Name of SQL dataset to be removed (default "kb")
  -q, --quiet          Suppress error messages if the provided dataset does not
                      exist
  --help              Show this message and exit.
```

Example: delete the test dataset

```
geist destroy duckdb --dataset test
```

The `.geistdata/duckdb/test.duckdb` file will be removed after this operation. By default, you will get an error message if the provided dataset (in this case, it is the `test` dataset) does not exist. To suppress this error message, you can add `--quiet` :

```
geist destroy duckdb --dataset test --quiet
```

geist destroy rdflib [OPTIONS]

```
Usage: geist destroy rdflib [OPTIONS]

Delete an RDF dataset

Options:
  -d, --dataset TEXT  Name of RDF dataset to be removed (default "kb")
  -q, --quiet          Suppress error messages if the provided dataset does not
                      exist
  --help              Show this message and exit.
```

Example: delete the test dataset

```
geist destroy rdflib --dataset test
```

The `.geistdata/rdflib/test.pkl` file will be removed after this operation. By default, you will get an error message if the provided dataset (in this case, it is the `test` dataset) does not exist. To suppress this error message, you can add `--quiet` :

```
geist destroy rdflib --dataset test --quiet
```

4.4 Command export

export command can export a dataset.

There are two subcommands for *export*:

```
Usage: geist export [OPTIONS] COMMAND [ARGS]...

Export a dataset

Options:
  --help  Show this message and exit.

Commands:
  duckdb  Export a SQL dataset
  rdflib  Export an RDF dataset
```

geist export duckdb [OPTIONS]

```
Usage: geist export duckdb [OPTIONS]

Export a SQL dataset

Options:
  -d, --dataset TEXT          Name of SQL dataset to be exported (default "kb")
  -oroot, --outputroot TEXT    Path of the directory to store the exported table (default: current directory). If the given path (i.e., --outputfile) is None or a relative path, it will be ignored.
  -ofile, --outputfile TEXT    Path of the file to store the exported table (default: None)
  -ofmt, --outputformat [csv|json]
                                Format of the exported table (default csv)
  -t, --table TEXT            Name of the table to be exported (default "df")
  --help                      Show this message and exit.
```

Example: export the df table in test dataset

By default, the exported table will be printed in terminal:

```
geist export duckdb --dataset test --table df
```

geist export rdflib [OPTIONS]

```
Usage: geist export rdflib [OPTIONS]

Export an RDF dataset

Options:
  -d, --dataset TEXT          Name of RDF dataset to be exported (default "kb")
  -oroot, --outputroot TEXT    Path of the directory to store these exported triples (default: current directory). If the given path (i.e., --outputfile) is None or a relative path, it will be ignored.
  -ofile, --outputfile TEXT    Path of the file to store these exported triples (default: None)
  -ofmt, --outputformat [json-ld|n3|nquads|nt|hext|pretty-xml|trig|trix|turtle|longturtle|xml]
                                Format of the exported triples (default nt)
  --help                      Show this message and exit.
```

Example: export the test dataset

By default, the exported triples will be printed in terminal:

```
geist export rdflib --dataset test
```

4.5 Command graph

`graph` command can visualize a dataset. Only `rdflib` is supported for now.

```
Usage: geist graph [OPTIONS] COMMAND [ARGS]...
```

Visualize a dataset

Options:

--help Show this message and exit.

geist graph rdflib [OPTIONS]

```
Usage: geist graph rdflib [OPTIONS]
```

Visualize an RDF dataset

Options:

| | |
|--|---|
| <code>-d, --dataset TEXT</code> | Name of RDF dataset to be visualized (default "kb") |
| <code>-r, --rankdir [TB BT LR RL]</code> | Direction of the graph (default TB): TB or BT or LR or RL |
| <code>-m, --mappings TEXT</code> | File of the mappings to shorten text (str): path of a JSON file, where the key is the original text and the value is the shorter text. |
| <code>-on, --on TEXT</code> | Column(s) to be mapped. |
| <code>-sc, --samecolor</code> | Use the same color for same edges. |
| <code>-oroot, --outputroot TEXT</code> | Path of the directory to store the graph (default: current directory). If the given path (i.e., --outputfile) is a relative path, it will be ignored. |
| <code>-ofile, --outputfile TEXT</code> | Path of the file without extension to store the graph (default: res) |
| <code>-ofomat, --outputformat [none svg png gv]</code> | Format of the graph (default: none): none or svg or png or gv |
| <code>--help</code> | Show this message and exit. |

Example: visualize the test dataset

```
geist graph rdflib --dataset test --outputformat svg
```

4.6 Command load

load command can import data into an existing dataset.

There are two subcommands for *load*:

```
Usage: geist load [OPTIONS] COMMAND [ARGS]...

Import data into a dataset

Options:
  --help  Show this message and exit.

Commands:
  duckdb  Import data into a SQL dataset
  rdflib  Import data into a RDF dataset
```

geist load duckdb [OPTIONS]

```
Usage: geist load duckdb [OPTIONS]

Import data into a SQL dataset

Options:
  -d, --dataset TEXT          Name of SQL dataset to load a file (default
                              "kb")
  -ifile, --inputfile FILENAME Path of the file to be loaded as a table
                              [required]
  -ifformat, --inputformat [csv|json]
                              Format of the file to be loaded as a table
                              (default csv)
  -t, --table TEXT           Name of the table to be created [required]
  --help                     Show this message and exit.
```

Example: load a file into the test dataset

```
geist load duckdb --dataset test --inputfile test_add.csv --inputformat csv --table df
```

geist load rdflib [OPTIONS]

Here are options of the *load* command:

```
Usage: geist load rdflib [OPTIONS]

Import data into a RDF dataset

Options:
  -d, --dataset TEXT          Name of RDF dataset to load a file (default
                              "kb")
  -ifile, --inputfile FILENAME Path of the file to be loaded as triples
                              [required]
  -ifformat, --inputformat [xml|n3|turtle|nt|pretty-xml|trix|trig|nquads|json-ld|hext|csv]
                              Format of the file to be loaded as triples
                              (default json-ld)
  --colnames TEXT           Column names of triples with the format of
                              [[subject1, predicate1, object1], [subject2,
                              predicate2, object2], ...] when the input
                              format is csv
  --help                     Show this message and exit.
```

Example: load a file into the test dataset

```
geist load rdflib --dataset test --inputfile test_add.jsonld
```

4.7 Command query

`query` command can perform a query on a dataset.

There are two subcommands for `query`:

```
Usage: geist query [OPTIONS] COMMAND [ARGS]...

    Perform a query on a dataset

Options:
  --help  Show this message and exit.

Commands:
  duckdb  Perform a SQL query on a dataset
  rdflib  Perform a SPARQL query on a dataset
```

geist query duckdb [OPTIONS]

```
Usage: geist query duckdb [OPTIONS]

    Perform a SQL query on a dataset

Options:
  -d, --dataset TEXT          Name of RDF dataset to be queried (default
                              "kb")
  -ifile, --inputfile FILENAME Specify either the path of the file containing
                              the SQL query to execute or provide the SQL
                              query itself via stdin [required]
  -oroot, --outputroot TEXT   Path of the directory to store the query
                              results (default: current directory). If the
                              given path (i.e., --outputfile) is None or a
                              relative path, it will be ignored.
  -ofile, --outputfile TEXT   Path of the file to store the query results
                              (default: None)
  --help                      Show this message and exit.
```

Example 1: all rows of the `df` table in `test` dataset from stdin

```
geist query duckdb --dataset test << __END_QUERY__

SELECT * FROM df

__END_QUERY__
```

Example 2: all rows of the `test` dataset from a query file

```
geist query duckdb --dataset test --inputfile query_file
```

Here is the `query_file`'s content:

```
SELECT * FROM df
```

geist query rdflib [OPTIONS]

Usage: geist query rdflib [OPTIONS]

Perform a SPARQL query on a dataset

Options:

| | |
|------------------------------|---|
| -d, --dataset TEXT | Name of RDF dataset to be queried (default "kb") |
| -ifile, --inputfile FILENAME | Specify either the path of the file containing the SPARQL query to execute or provide the SPARQL query itself via stdin [required] |
| -oroot, --outputroot TEXT | Path of the directory to store the query results (default: current directory). If the given path (i.e., --outputfile) is None or a relative path, it will be ignored. |
| -ofile, --outputfile TEXT | Path of the file to store the query results (default: None) |
| --help | Show this message and exit. |

Example 1: all triples of the test dataset from stdin

```
geist query rdflib --dataset test << __END_QUERY__
```

```
SELECT ?s ?p ?o
WHERE {
  ?s ?p ?o
}
ORDER BY ?s ?p ?o
__END_QUERY__
```

Example 2: all triples of the test dataset from a query file

```
geist query rdflib --dataset test --inputfile query_file
```

Here is the query_file's content:

```
SELECT ?s ?p ?o
WHERE {
  ?s ?p ?o
}
ORDER BY ?s ?p ?o
```

5. Python API

5.1 Class Connection

Connection class can interact with a dataset with `create`, `close`, `destroy`, `export`, `graph`, `load`, and `query` methods.

5.1.1 What is a *Connection* class?

A *Connection* class has three attributes:


| Name | Description |
|-----------|---|
| datastore | String. A backend datastore, i.e., 'rdflib' or 'duckdb' ([required]) |
| dataset | String. Name of the dataset. Note that ':memory:' is a reserved value for datasets that exist only in memory ([required]) |
| conn | DuckPyConnection object OR GeistGraph object (by default, None) |

5.1.2 How to instantiate a *Connection* class?

If the dataset exists, the *Connection* class can be instantiated using its **connect** method:

```
# create a Connection object to an existing dataset named test
connection = geist.Connection.connect(datastore='duckdb',
dataset='test')
```

If the dataset does not exist, there are two approaches to create and connect:

 **Approach 1: use the create function, then initialize the Connection class**

create function

create function can create a new dataset on disk or in memory.

Parameters description for *create()*:

| Name | Description |
|-------------|---|
| datastore | String. A backend datastore, i.e., 'rdflib' or 'duckdb' ([required]) |
| dataset | String. Name of the dataset to be created. Note that ':memory:' is a reserved value for datasets that exist only in memory ([required]) |
| inputfile | String. A file to be loaded ([required]) |
| inputformat | String. Format of the file to be loaded ([required]) |
| isinputpath | Bool. <code>True</code> if the inputfile is the file path, otherwise the inputfile is the content ([required]) |
| config | Dict. A dictionary with configurations for certain backend store. See below for detailed information |

Description for the *config* parameter:

datastore: duckdb

| Key | Description |
|-------|---|
| table | String. Name of the table to be created (by default, 'df') |

datastore: rdflib

| Key | Description |
|----------|--|
| colnames | String. Column names of triples with the format of <code>[[subject1, predicate1, object1], [subject2, predicate2, object2], ...]</code> ([required] when <code>inputformat='csv'</code>) |
| infer | String. Inference to perform on update, i.e., 'none', 'rdfs', 'owl', or 'rdfs_owl' (by default, 'none') |

Example 1: create a test SQL dataset on disk from a string

The `.geistdata/duckdb/test.duckdb` file is created and a `DuckDBPyConnection` object is returned.

```
import geist

csv_str = """
v1,v2,v3
1,2,3
4,5,6
7,8,9
"""

# Create a DuckPyConnection object
conn = geist.create(datastore='duckdb', dataset='test',
inputfile=csv_str, inputformat='csv', isinputpath=False,
config={"table": "df"})
```

Example 2: create a test SQL dataset on disk from a file

The `.geistdata/duckdb/test.duckdb` file is created and a `DuckDBPyConnection` object is returned.

Here is the `test.csv` file:

```
v1,v2,v3
1,2,3
4,5,6
7,8,9
```

Code:

```
import geist

# Create a DuckPyConnection object
conn = geist.create(datastore='duckdb', dataset='test',
inputfile="test.csv", inputformat='csv', isinputpath=True,
config={"table": "df"})
```

Example 3: create a SQL dataset in memory from a string

A `DuckDBPyConnection` object is returned.

```
import geist

csv_str = """
v1,v2,v3
1,2,3
4,5,6
7,8,9
"""

# Create a DuckPyConnection object
conn = geist.create(datastore='duckdb', dataset=':memory:',
inputfile=csv_str, inputformat="csv", isinputpath=False,
config={"table": "df"})
```

Example 4: create a SQL dataset in memory from a file

A `DuckDBPyConnection` object is returned.

Here is the `test.csv` file:

```
v1,v2,v3
1,2,3
4,5,6
7,8,9
```

Code:

```
import geist

# Create a DuckPyConnection object
conn = geist.create(datastore='duckdb', dataset=':memory:',
inputfile="test.csv", inputformat="csv", isinputpath=True,
config={"table": "df"})
```

```
import geist

csv_str = """
v1,v2,v3
1,2,3
7,8,9
"""

# create a Connection object
conn = geist.create(datastore='duckdb', dataset=':memory:',
inputfile=csv_str, inputformat="csv", isinputpath=False,
config={"table": "df"})
connection = geist.Connection(datastore='duckdb', dataset=':memory:',
conn=conn)
```

Approach 2: use the create method of the Connection class

create method of the Connection class

create method of the *Connection* class creates a new dataset on disk or in memory. It is very similar to the `create()` function. The only difference is that the `datastore` and the `dataset` parameters do not need to be passed as they have already been specified while initializing the *Connection* class.

Parameters description for *create* method of the *Connection* class:

| Name | Description |
|-------------|--|
| inputfile | String. A file to be loaded ([required]) |
| inputformat | String. Format of the file to be loaded ([required]) |
| isinputpath | Bool. <code>True</code> if the inputfile is the file path, otherwise the inputfile is the content ([required]) |
| config | Dict. A dictionary with configurations for certain backend store. See below for detailed information |

Description for the *config* parameter:

datastore: duckdb

| Key | Description |
|-------|---|
| table | String. Name of the table to be created (by default, 'df') |

datastore: rdflib

| Key | Description |
|----------|--|
| colnames | String. Column names of triples with the format of <code>[[subject1, predicate1, object1], [subject2, predicate2, object2], ...]</code> . ([required] when <code>inputformat='csv'</code>) |
| infer | String. Inference to perform on update, i.e., <code>'none'</code> , <code>'rdfs'</code> , <code>'owl'</code> , or <code>'rdfs_owl'</code> (by default, <code>'none'</code>) |

Example 1: create a test SQL dataset from a string

The `.geistdata/duckdb/test.duckdb` file is created and a `Connection` instance is returned.

```
import geist

csv_str = """
v1,v2,v3
1,2,3
4,5,6
7,8,9
"""

# Create a Connection instance
connection = geist.Connection(datastore='duckdb',
dataset='test')
connection.create(inputfile=csv_str, inputformat="csv",
isinputpath=False, config={"table": "df"})
```

Example 2: create a test SQL dataset from a file

The `.geistdata/duckdb/test.duckdb` file is created and a `Connection` instance is returned.

Here is the `test.csv` file:

```
v1,v2,v3
1,2,3
4,5,6
7,8,9
```

Code:

```
import geist

# Create a Connection instance
connection = geist.Connection(datastore='duckdb',
dataset='test')
connection.create(inputfile="test.csv", inputformat="csv",
isinputpath=True, config={"table": "df"})
```

Example 3: create a SQL dataset in memory from a string

A `Connection` instance is returned.

```
import geist

csv_str = """
v1,v2,v3
1,2,3
4,5,6
7,8,9
"""

# Create a Connection instance
connection = geist.Connection(datastore='duckdb',
                              dataset=':memory:')
connection.create(inputfile=csv_str, inputformat="csv",
                  isinputpath=False, config={"table": "df"})
```

Example 4: create a SQL dataset in memory from a file

A `Connection` instance is returned.

Here is the `test.csv` file:

```
v1,v2,v3
1,2,3
4,5,6
7,8,9
```

Code:

```
import geist

# Create a Connection instance
connection = geist.Connection(datastore='duckdb',
                              dataset=':memory:')
connection.create(inputfile="test.csv", inputformat="csv",
                  isinputpath=True, config={"table": "df"})
```

```
import geist

csv_str = """
v1,v2,v3
1,2,3
4,5,6
7,8,9
"""

# create a Connection object
connection = geist.Connection(datastore='duckdb', dataset=':memory:')
connection.create(inputfile=csv_str, inputformat="csv",
                  isinputpath=False, config={"table": "df"})
```

close method

close method of the *Connection* class is to close the dataset connection, i.e., reset all attributes to None. No parameters are required.

Example: close the connection

Suppose `connection` is the instance of the *Connection* class.

```
# Close the connection
connection.close()
```

destroy method

destroy method of the *Connection* class is to delete the dataset and close the dataset connection.

Example: delete the dataset and close the connection

Suppose `connection` is the instance of the *Connection* class for a DuckDB dataset named `test` stored on disk. The following code will delete the `.geistdata/duckdb/test.duckdb` file.

```
# Delete the dataset and close the connection
connection.destroy()
```

5.1.3 How to interact with a *Connection* class?

Once a *Connection* class is instantiated, we can interact with it using `close`, `destroy`, `export`, `graph`, `load`, and `query` methods.

export method

export method of the *Connection* class exports a dataset. It is very similar to the `export()` function. The only difference is that the `datastore` and the `dataset` parameters do not need to be passed as they have already been specified while initializing the *Connection* class.

Parameters description for *export* method of the *Connection* class:

| Name | Description |
|-----------|--|
| hasoutput | Bool. <code>True</code> to export as a file or print it out ([required]) |
| config | Dict. A dictionary with configurations for certain backend store. See below for detailed information |

Description for the *config* parameter:

datastore: duckdb

| Key | Description |
|--------------|---|
| outputroot | String. Path of the directory to store the exported table (by default, <code>'./'</code>) |
| outputfile | String. Path of the file to store the exported table (by default, <code>None</code>) |
| outputformat | String. Format of the exported table, i.e., <code>'csv'</code> or <code>'json'</code> (by default, <code>'csv'</code>) |
| table | String. Name of the table to be exported (by default, <code>'df'</code>) |

datastore: rdflib

| Key | Description |
|--------------|--|
| outputroot | String. Path of the directory to store these exported triples (by default, <code>'./'</code>) |
| outputfile | String. Path of the file to store these exported triples (by default, <code>None</code>) |
| outputformat | String. Format of the exported triples, i.e., <code>'json-ld'</code> , <code>'n3'</code> , <code>'nquads'</code> , <code>'nt'</code> , <code>'hex'</code> , <code>'pretty-xml'</code> , <code>'trig'</code> , <code>'trix'</code> , <code>'turtle'</code> , <code>'longturtle'</code> , or <code>'xml'</code> (by default, <code>'nt'</code>) |

Example 1: export all rows of the `df` table in `test` dataset on disk

There exist a file with the path of `.geistdata/duckdb/test.duckdb`. The following code returns a Pandas data frame named `data`.

```
import geist

# Create a Connection instance
connection = geist.Connection.connect(datastore='duckdb',
dataset='test')
# Export the df table of the test dataset
data = connection.export(hasoutput=False, config={'table': 'df'})
```

Example 2: export all rows of the `df` table in `test` dataset in memory

Suppose `conn` is a `DuckPyConnection` object points to a DuckDB dataset in memory. The following code returns a Pandas data frame named `data`.

```
import geist

# Create a Connection instance
connection = geist.Connection(datastore='duckdb',
dataset=':memory:', conn=conn)
# Export the df table of the test dataset
data = connection.export( hasoutput=False, config={'table':
'df'})
```

graph method

graph method of the *Connection* class exports a dataset. Only `rdflib` is supported for now. It is very similar to the `graph()` function. The only difference is that the `datastore` and the `dataset` parameters do not need to be passed as they have already been specified while initializing the *Connection* class.

Parameters description for *graph* method of the *Connection* class:

| Name | Description |
|------------------------|--|
| <code>datastore</code> | String. A backend datastore, i.e., <code>'rdflib'</code> or <code>'duckdb'</code> ([required]) |
| <code>dataset</code> | String OR <code>GeistGraph</code> object. Dataset to load an object: (1) A string indicates the name of the dataset stored on disk OR (2) a <code>GeistGraph</code> object for dataset in memory ([required]) |
| <code>hasoutput</code> | Bool. <code>True</code> to export as a file or print it out ([required]) |
| <code>config</code> | Dict. A dictionary with configurations for certain backend store. See below for detailed information |

Description for the *config* parameter:

datastore: rdflib

| Key | Description |
|----------------------------|--|
| <code>rankdir</code> | String. Direction of the graph: <code>'TB'</code> or <code>'BT'</code> or <code>'LR'</code> or <code>'RL'</code> (by default, <code>'TB'</code>) |
| <code>mappings</code> | String. File of the mappings to shorten text (str): path of a JSON file, where the key is the original text and the value is the shorter text (by default, <code>None</code>) |
| <code>on</code> | String. Column(s) to be mapped (by default, <code>None</code>) |
| <code>samecolor</code> | Bool. <code>True</code> to use the same color for same edges (by default, <code>True</code>) |
| <code>outputroot</code> | String. Path of the directory to store the graph (by default, <code>'./'</code>) |
| <code>outputfile</code> | String. Path of the file without extension to store the graph (by default, <code>'res'</code>) |
| <code>outputformats</code> | List. Format of the graph: <code>'none'</code> or <code>'svg'</code> or <code>'png'</code> or <code>'gv'</code> (by default, <code>['none']</code>) |

Example 1: visualize the test dataset on disk

There exist a file with the path of `.geistdata/duckdb/test.duckdb`. The following code visualizes the test dataset as a graph and saves it as the `res.svg` file.

```
import geist

# Create a Connection instance
connection = geist.Connection.connect(datastore='duckdb',
dataset='test')
# Visualize the test dataset
connection.graph(hasoutput=True, config={'outputformats':
['svg']})
```

Example 2: visualize the test dataset in memory

Suppose `conn` is a `DuckPyConnection` object points to a DuckDB dataset in memory. The following code visualizes the test dataset as a graph and saves it as the `res.svg` file.

```
import Geist

# Create a Connection instance
connection = Geist.Connection(datastore='duckdb',
                             dataset='.memory:', conn=conn)
# Visualize the test dataset
connection.graph(hasoutput=True, config={'outputformats':
['svg']})
```

load method

load method of the *Connection* class imports data into an existing dataset on disk or in memory. It is very similar to the `load()` function. The only difference is that `datastore`, `dataset`, and `inmemory` parameters do not need to be passed as they have already been specified while initializing the *Connection* class.

Parameters description for *load* method of the *Connection* class:

| Name | Description |
|-------------|--|
| inputfile | String. A file to be loaded ([required]) |
| inputformat | String. Format of the file to be loaded ([required]) |
| isinputpath | Bool. <code>True</code> if the inputfile is the file path, otherwise the inputfile is the content ([required]) |
| config | Dict. A dictionary with configurations for certain backend store. See below for detailed information |

Description for the *config* parameter:

datastore: duckdb

| Key | Description |
|-------|---|
| table | String. Name of the table to be loaded ([required]) |

datastore: rdflib

| Key | Description |
|----------|---|
| colnames | String. Column names of triples with the format of <code>[[subject1, predicate1, object1], [subject2, predicate2, object2], ...]</code> ([required] when <code>inputformat='csv'</code>) |

Example: load a table into the test dataset

There exist a file with the path of `.geistdata/duckdb/test.duckdb`. The `csv_str` will be imported into the `df` table. Note that the order of table columns should be consistent with the imported data.

```
import geist

csv_str = """
v1,v2,v3
1,1,1
2,2,2
3,3,3
"""

# Create a Connection instance
connection = geist.Connection.connect(datastore='duckdb',
dataset='test')
# Load csv_str to the df table of the test dataset
connection.load(inputfile=csv_str, inputformat='csv',
isinputpath=False, config={'table': 'df'})
```

query method

query method of the *Connection* class can query a dataset stored on disk or in memory. It is very similar to the `query()` function. The only difference is that the `datastore` and the `dataset` parameters do not need to be passed as they have already been specified while initialize the *Connection* class.

Parameters description for *query* method of the *Connection* class:

| Name | Description |
|-------------|--|
| inputfile | String. File containing the query ([required]) |
| isinputpath | Bool. <code>True</code> if the inputfile is the file path, otherwise the inputfile is the content ([required]) |
| hasoutput | Bool. <code>True</code> to store the query results as a CSV file or print them out ([required]) |
| config | Dict. A dictionary with configurations when <code>hasoutput=True</code> . See below for detailed information |

Description for the *config* parameter:

| Key | Description |
|------------|---|
| outputroot | String. Path of the directory to store the query results (by default, <code>'./'</code>) |
| outputfile | String. Path of the file to store the query results (by default, <code>None</code>) |

Example 1: all rows of the df table in test dataset on disk (query from a string)

There exist a file with the path of `.geistdata/duckdb/test.duckdb`. The following code returns a Pandas data frame named `res` with query results.

```
import geist

# Create a Connection instance
connection = geist.Connection.connect(datastore='duckdb',
dataset='test')
# Query the df table of the test dataset
res = connection.query(inputfile="SELECT * FROM df;",
isinputpath=False, hasoutput=False)
```


Example 2: all rows of the df table in test dataset on disk (query from a file)

There exist a file with the path of `.geistdata/duckdb/test.duckdb`. The following code returns a Pandas data frame named `res` with query results.

Here is the `query.txt` file:

```
SELECT * FROM df;
```

Code:

```
import geist

# Create a Connection instance
connection = geist.Connection.connect(datastore='duckdb',
dataset='test')
# Query the df table of the test dataset
res = connection.query(inputfile="query.txt", isinputpath=True,
hasoutput=False)
```

Example 3: all rows of the df table in test dataset in memory (query from a string)

Suppose `conn` is a `DuckPyConnection` object points to a DuckDB dataset in memory. The following code returns a Pandas data frame named `res` with query results.

```
import geist

# Create a Connection instance
connection = geist.Connection(datastore='duckdb',
dataset=':memory:', conn=conn)
# Query the df table of the test dataset
res = connection.query(inputfile="SELECT * FROM df;",
isinputpath=False, hasoutput=False)
```

Example 4: all rows of the df table in test dataset in memory (query from a file)

Suppose `conn` is a `DuckPyConnection` object points to a DuckDB dataset in memory. The following code returns a Pandas data frame named `res` with query results.

Here is the `query.txt` file:

```
SELECT * FROM df;
```

Code:

```
import geist

# Create a Connection instance
connection = geist.Connection(datastore='duckdb',
dataset=':memory:', conn=conn)
# Query the df table of the test dataset
res = connection.query(inputfile="query.txt", isinputpath=True,
hasoutput=False)
```

5.2 Functions

5.2.1 Function report

report function can expand a report (Geist template) using dataset(s).

Parameters description for *report()*:

| Name | Description |
|----------------|---|
| inputfile | String. A report to be expanded ([required]) |
| isinputpath | Bool. True if the inputfile is the file path, otherwise the inputfile is the content (by default, False) |
| outputroot | String. Path of the directory to store the expanded report (by default, current directory, i.e., ./) |
| suppressoutput | Bool. True to suppress output (by default, True) |
| args | Dict. External arguments, e.g., <code>{"arg1": "value1", "arg2": "value2"}</code> denotes that <code>{{ arg1 }}</code> and <code>{{ arg2 }}</code> in the report template will be replaced by <code>value1</code> and <code>value2</code> respectively (by default, <code>{}</code>) |

Example 1: expand a report from a string

```
import geist

report = ""

{% create "test", datastore="rdflib", inputformat="nt",
isfilepath=False %}
<http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-
syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
<http://example.com/drewp> <http://example.com/says> "Hello
World" .
{% endcreate %}

{% query "test", datastore="rdflib", isfilepath=False as all_triples
%}
SELECT ?s ?p ?o
WHERE {
  ?s ?p ?o
}
ORDER BY ?s ?p ?o
{% endquery %}

{% for _, row in all_triples.iterrows() %}
  Subject: {{ row["s"] }}, Predicate: {{ row["p"] }}, Object:
  {{ row["o"] }}.
{% endfor %}

{% destroy "test", datastore="rdflib" %}

"""

# Return the expanded report as a string variable named
expanded_report
expanded_report = geist.report(inputfile=report)
```

Example 2: expand a report from a file

```
import geist

# Return the expanded report as a string variable named
expanded_report
expanded_report = geist.report(inputfile='report.geist',
isinputpath=True)
```

Here is the `report.geist` file:

```
{% create "test", datastore="rdflib", inputformat="nt",
isfilepath=False %}
<http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-
syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
<http://example.com/drewp> <http://example.com/says> "Hello
World" .
{% endcreate %}

{% query "test", datastore="rdflib", isfilepath=False as all_triples
%}
SELECT ?s ?p ?o
WHERE {
  ?s ?p ?o
}
ORDER BY ?s ?p ?o
{% endquery %}

{% for _, row in all_triples.iterrows() %}
  Subject: {{ row["s"] }}, Predicate: {{ row["p"] }}, Object:
  {{ row["o"] }}.
{% endfor %}

{% destroy "test", datastore="rdflib" %}
```

Example 3: expand a report from a file with external arguments

```
import geist

# Return the expanded report as a string variable named
expanded_report
expanded_report = geist.report(
    inputfile='report.geist',
    isinputpath=True,
    args={
        "sentence": "Hello World",
        "feeling": "Happy"
    }
)
```

Here is the report.geist file:

```
{% create "test", datastore="rdflib", inputformat="nt",
isfilepath=False %}
  <http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-
syntax-ns#type> <http://xmlns.com/foaf/0.1/Person> .
  <http://example.com/drewp> <http://example.com/says>
"{{ sentence }}" .
  <http://example.com/drewp> <http://example.com/feels>
"{{ feeling }}" .
{% endcreate %}

{% query "test", datastore="rdflib", isfilepath=False as all_triples
%}
  SELECT ?s ?p ?o
  WHERE {
    ?s ?p ?o
  }
  ORDER BY ?s ?p ?o
{% endquery %}

{% for _, row in all_triples.iterrows() %}
  Subject: {{ row["s"] }}, Predicate: {{ row["p"] }}, Object:
  {{ row["o"] }}.
{% endfor %}

{% destroy "test", datastore="rdflib" %}
```

5.2.2 Function create

create function can create a new dataset on disk or in memory.

Parameters description for *create()*:

| Name | Description |
|-------------|--|
| datastore | String. A backend datastore, i.e., <code>'rdflib'</code> or <code>'duckdb'</code> ([required]) |
| dataset | String. Name of the dataset to be created. Note that <code>':memory:'</code> is a reserved value for datasets that exist only in memory ([required]) |
| inputfile | String. A file to be loaded ([required]) |
| inputformat | String. Format of the file to be loaded ([required]) |
| isinputpath | Bool. <code>True</code> if the inputfile is the file path, otherwise the inputfile is the content ([required]) |
| config | Dict. A dictionary with configurations for certain backend store. See below for detailed information |

Description for the *config* parameter:

| datastore: duckdb | |
|-------------------|--|
| Key | Description |
| table | String. Name of the table to be created (by default, <code>'df'</code>) |

i datastore: rdflib

| Key | Description |
|----------|--|
| colnames | String. Column names of triples with the format of <code>[[subject1, predicate1, object1], [subject2, predicate2, object2], ...]</code> ([required] when <code>inputformat='csv'</code>) |
| infer | String. Inference to perform on update, i.e., <code>'none'</code> , <code>'rdfs'</code> , <code>'owl'</code> , or <code>'rdfs_owl'</code> (by default, <code>'none'</code>) |

Example 1: create a test SQL dataset on disk from a string

The `.geistdata/duckdb/test.duckdb` file is created and a `DuckDBPyConnection` object is returned.

```
import geist

csv_str = """
v1,v2,v3
1,2,3
4,5,6
7,8,9
"""

# Create a DuckPyConnection object
conn = geist.create(datastore='duckdb', dataset='test',
inputfile=csv_str, inputformat="csv", isinputpath=False,
config={"table": "df"})
```

Example 2: create a test SQL dataset on disk from a file

The `.geistdata/duckdb/test.duckdb` file is created and a `DuckDBPyConnection` object is returned.

Here is the `test.csv` file:

```
v1,v2,v3
1,2,3
4,5,6
7,8,9
```

Code:

```
import geist

# Create a DuckPyConnection object
conn = geist.create(datastore='duckdb', dataset='test',
inputfile="test.csv", inputformat="csv", isinputpath=True,
config={"table": "df"})
```

Example 3: create a SQL dataset in memory from a string

A `DuckDBPyConnection` object is returned.

```
import geist

csv_str = """
v1,v2,v3
1,2,3
4,5,6
7,8,9
"""

# Create a DuckPyConnection object
conn = geist.create(datastore='duckdb', dataset=':memory:',
inputfile=csv_str, inputformat='csv', isinputpath=False,
config={"table": "df"})
```

Example 4: create a SQL dataset in memory from a file

A `DuckDBPyConnection` object is returned.

Here is the `test.csv` file:

```
v1,v2,v3
1,2,3
4,5,6
7,8,9
```

Code:

```
import geist

# Create a DuckPyConnection object
conn = geist.create(datastore='duckdb', dataset=':memory:',
inputfile="test.csv", inputformat="csv", isinputpath=True,
config={"table": "df"})
```

5.2.3 Function destroy

destroy function can delete a dataset.

Parameters description for *destroy()*:

| Name | Description |
|-----------|---|
| datastore | String. A backend datastore, i.e., <code>'rdflib'</code> or <code>'duckdb'</code> ([required]) |
| dataset | String. Name of the dataset to be removed ([required]) |
| quiet | Bool. <code>True</code> to suppress error messages if the provided dataset does not exist (by default, <code>False</code>) |

Example: delete the `test` dataset

```
import geist
geist.destroy(datastore='rdflib', dataset='test')
```

The `.geistdata/rdflib/test.pkl` file will be removed after this operation. By default, you will get an error message if the provided dataset (in this case, it is the `test` dataset) does not exist. To suppress this error message, you can set `quiet=True`:

```
import geist
geist.destroy(datastore='rdflib', dataset='test', quiet=True)
```

5.2.4 Function export

export function can export a dataset.

Parameters description for *export()*:

| Name | Description |
|-----------|---|
| datastore | String. A backend datastore, i.e., <code>'rdflib'</code> or <code>'duckdb'</code> ([required]) |
| dataset | String OR <code>DuckPyConnection</code> object OR <code>GeistGraph</code> object. Dataset to load an object: (1) A string indicates the name of the dataset stored on disk OR (2) a <code>DuckPyConnection</code> object OR a <code>GeistGraph</code> object for dataset in memory ([required]) |
| hasoutput | Bool. <code>True</code> to export as a file or print it out ([required]) |
| config | Dict. A dictionary with configurations for certain backend store. See below for detailed information |

Description for the *config* parameter:

| datastore: duckdb | |
|-------------------|---|
| Key | Description |
| outputroot | String. Path of the directory to store the exported table (by default, <code>'.'</code>) |
| outputfile | String. Path of the file to store the exported table (by default, <code>None</code>) |
| outputformat | String. Format of the exported table, i.e., <code>csv</code> or <code>json</code> (by default, <code>'csv'</code>) |
| table | String. Name of the table to be exported (by default, <code>'df'</code>) |

i datastore: rdflib

| Key | Description |
|--------------|---|
| outputroot | String. Path of the directory to store these exported triples (by default, <code>'.'</code>) |
| outputfile | String. Path of the file to store these exported triples (by default, <code>None</code>) |
| outputformat | String. Format of the exported triples, i.e., <code>'json-ld'</code> , <code>'n3'</code> , <code>'nquads'</code> , <code>'nt'</code> , <code>'hext'</code> , <code>'pretty-xml'</code> , <code>'trig'</code> , <code>'trix'</code> , <code>'turtle'</code> , <code>'longturtle'</code> , or <code>'xml'</code> (by default, <code>'nt'</code>) |

Example 1: export all rows of the df table in test dataset on disk

There exist a file with the path of `.geistdata/duckdb/test.duckdb`. The following code returns a Pandas data frame named `data` and the `DuckPyConnection` object `conn`.

```
import geist

# Export the df table of the test dataset
(data, conn) = geist.export(datastore='duckdb', dataset='test',
                             hasoutput=False, config={'table': 'df'})
```

Example 2: export all rows of the df table in test dataset in memory

Suppose `conn` is a `DuckPyConnection` object points to a DuckDB dataset in memory. The following code returns a Pandas data frame named `data` and the same `DuckPyConnection` object `conn`.

```
import geist

# Export the df table of the test dataset
(data, conn) = geist.export(datastore='duckdb', dataset=conn,
                             hasoutput=False, config={'table': 'df'})
```

5.2.5 Function graph

graph function can visualize a dataset. Only `rdflib` is supported for now.

Parameters description for `export()`:

| Name | Description |
|-----------|---|
| datastore | String. A backend datastore, i.e., <code>'rdflib'</code> or <code>'duckdb'</code> ([required]) |
| dataset | String OR <code>GeistGraph</code> object. Dataset to load an object: (1) A string indicates the name of the dataset stored on disk OR (2) a <code>GeistGraph</code> object for dataset in memory ([required]) |
| hasoutput | Bool. <code>True</code> to export as a file or print it out ([required]) |
| config | Dict. A dictionary with configurations for certain backend store. See below for detailed information |

Description for the `config` parameter:

| i datastore: rdflib | |
|----------------------------|--|
| Key | Description |
| rankdir | String. Direction of the graph: <code>'TB'</code> or <code>'BT'</code> or <code>'LR'</code> or <code>'RL'</code> |
| mappings | String. File of the mappings to shorten text (str): path of a JSON file, where the key is the original text and the value is the shorter text (by default, <code>None</code>) |
| on | String. Column(s) to be mapped (by default, <code>None</code>) |
| samecolor | Bool. <code>True</code> to use the same color for same edges (by default, <code>True</code>) |
| outputroot | String. Path of the directory to store the graph (by default, <code>'./'</code>) |
| outputfile | String. Path of the file without extension to store the graph (by default, <code>'res'</code>) |
| outputformats | List. Format of the graph: <code>'none'</code> or <code>'svg'</code> or <code>'png'</code> or <code>'gv'</code> (by default, <code>['none']</code>) |

Example: visualize the test dataset

```
import geist

# Visualize the test dataset as a graph and save it as the res.svg file
geist.graph(datastore='rdflib', dataset='test', hasoutput=True,
            config={'outputformats': ['svg']})
```


5.2.6 Function load

load function can import data into an existing dataset.

Parameters description for *query()*:

| Name | Description |
|-------------|---|
| datastore | String. A backend datastore, i.e., 'rdflib' or 'duckdb' ([required]) |
| dataset | String OR <code>DuckPyConnection</code> object OR <code>GeistGraph</code> object. Dataset to load an object: (1) A string indicates the name of the dataset stored on disk OR (2) a <code>DuckPyConnection</code> object OR a <code>GeistGraph</code> object for dataset in memory ([required]) |
| inputfile | String. File to be loaded ([required]) |
| inputformat | String. Format of the file to be loaded ([required]) |
| isinputpath | Bool. <code>True</code> if the inputfile is the file path, otherwise the inputfile is the content ([required]) |
| config | Dict. A dictionary with configurations for certain backend store. See below for detailed information |

Description for the *config* parameter:

datastore: duckdb

| Key | Description |
|-------|---|
| table | String. Name of the table to be loaded ([required]) |

datastore: rdflib

| Key | Description |
|----------|--|
| inmemory | Bool. <code>True</code> if the new dataset (after loading data) is stored in memory only, otherwise it is stored on disk (by default, <code>False</code>) |
| colnames | String. Column names of triples with the format of <code>[[subject1, predicate1, object1], [subject2, predicate2, object2], ...]</code> ([required] when <code>inputformat='csv'</code>) |

Example: load a table into the test dataset

There exist a file with the path of `.geistdata/duckdb/test.duckdb`. The `csv_str` will be imported into the `df` table. Note that the order of table columns should be consistent with the imported data.

```
import geist

csv_str = """
v1,v2,v3
1,1,1
2,2,2
3,3,3
"""

# Load csv_str to the df table of the test dataset
geist.load(datastore='duckdb', dataset='test', inputfile=csv_str,
inputformat='csv', isinputpath=False, config={'table': 'df'})
```

5.2.7 Function query

query function can perform a query on a dataset.

Parameters description for *query()*:

| Name | Description |
|-------------|--|
| datastore | String. A backend datastore, i.e., 'rdflib' or 'duckdb' ([required]) |
| dataset | String OR <code>DuckPyConnection</code> object OR <code>GeistGraph</code> object: (1) A string indicates the name of the dataset stored on disk OR (2) a <code>DuckPyConnection</code> object OR a <code>GeistGraph</code> object for dataset in memory ([required]) |
| inputfile | String. File containing the query ([required]) |
| isinputpath | Bool |
| hasoutput | Bool |
| config | Dict |

Description for the *config* parameter:

| Key | Description |
|------------|---|
| outputroot | String. Path of the directory to store the query results (by default, <code>'./'</code>) |
| outputfile | String. Path of the file to store the query results (by default, <code>None</code>) |

Example 1: all rows of the df table in test dataset on disk (query from a string)

There exist a file with the path of `.geistdata/duckdb/test.duckdb`. The following code returns a Pandas data frame named `res` with query results, and a `DuckPyConnection` object.

```
import geist

# Query the df table of the test dataset
(res, conn) = geist.query(datastore='duckdb', dataset='test',
inputfile="SELECT * FROM df;", isinputpath=False, hasoutput=False)
```

Example 2: all rows of the df table in test dataset on disk (query from a file)

There exist a file with the path of `.geistdata/duckdb/test.duckdb`. The following code returns a Pandas data frame named `res` with query results, and a `DuckPyConnection` object.

Here is the `query.txt` file:

```
SELECT * FROM df;
```

Code:

```
import geist

# Query the df table of the test dataset
(res, conn) = geist.query(datastore='duckdb', dataset='test',
inputfile="query.txt", isinputpath=True, hasoutput=False)
```

Example 3: all rows of the df table in test dataset in memory (query from a string)

Suppose `conn` is a `DuckPyConnection` object points to a DuckDB dataset in memory. The following code returns a Pandas data frame named `res` with query results, and the same `DuckPyConnection` object.

```
import geist

# Query the df table of the test dataset
(res, conn) = geist.query(datastore='duckdb', dataset=conn,
inputfile="SELECT * FROM df;", isinputpath=False, hasoutput=False)
```

Example 4: all rows of the df table in test dataset in memory (query from a file)

Suppose `conn` is a `DuckPyConnection` object points to a DuckDB dataset in memory. The following code returns a Pandas data frame named `res` with query results, and the same `DuckPyConnection` object.

Here is the `query.txt` file:

```
SELECT * FROM df;
```

Code:

```
import geist

# Query the df table of the test dataset
(res, conn) = geist.query(datastore='duckdb', dataset=conn,
inputfile="query.txt", isinputpath=True, hasoutput=False)
```

6. Changelog

v0.3.1 (2025-01-06)

- Fix minor bug of the report feature: update TAGS and filters
- Add external arguments for the report feature: `{{ arg }}` will be replaced by `value` in the report template

v0.3.0 (2024-12-26)

- Code refactoring: `datastore` -> `api` -> commands (e.g., code under the `api` folder is based on code under the `datastore` folder)
- Add Python API: (1) Connection class with `create`, `close`, `destroy`, `export`, `graph`, `load`, and `query` methods; and (2) `create`, `destroy`, `export`, `graph`, `load`, `query`, and `report` functions
- Update CLI of report and query commands: replace `--file` with `--inputfile`
- Update the documentation

v0.2.1 (2024-08-17)

- Add the Geist Poster for [SciPy 2024](#)
- Update the documentation: add descriptions for the demo of SciPy 2024

v0.2.0 (2024-03-15)

- SQL queries are supported by GEIST based on [duckdb](#)
- Update ContainerTag: return objects of any type, not just strings

v0.1.0 (2024-03-04)

- Add [documentation](#)
- Add the component tag to extract connected components of a given graph
- Add the `process_str_for_html` filter
- Make the map tag more flexible: make it possible to map selected columns
- Fix the quotes bug: keep the cell's original format

v0.0.1 (2023-09-21)

- The first version of GEIST with `create`, `load`, `query`, `destroy`, `graph`, `graph2`, `map`, `use`, `html`, `img`, and `table` tags
- SPARQL queries are supported by GEIST based on [RDFLib](#)