

API Documentation

API Documentation

March 14, 2013

Contents

Contents	1
1 Package fabio	6
1.1 Modules	6
1.2 Variables	7
2 Module fabio.GEimage	8
2.1 Functions	8
2.2 Variables	8
2.3 Class GEimage	8
2.3.1 Methods	8
2.3.2 Properties	9
3 Module fabio.GEimage_old	10
3.1 Variables	10
3.2 Class GEimage	10
3.2.1 Methods	11
3.2.2 Properties	11
4 Module fabio.HiPiCimage	12
4.1 Variables	12
4.2 Class HiPiCimage	12
4.2.1 Methods	12
4.2.2 Properties	13
5 Module fabio.OXDimage	14
5.1 Variables	14
5.2 Class OXDimage	14
5.2.1 Methods	15
5.2.2 Properties	15
5.3 Class Section	16
5.3.1 Methods	16
5.3.2 Properties	17
6 Module fabio.TiffIO	18
6.1 Variables	18
6.2 Class TiffIO	19
6.2.1 Methods	19

6.2.2	Properties	19
7	Module fabio.adscimage	21
7.1	Functions	21
7.2	Variables	21
7.3	Class adscimage	21
7.3.1	Methods	22
7.3.2	Properties	22
8	Module fabio.binaryimage	23
8.1	Variables	23
8.2	Class binaryimage	23
8.2.1	Methods	24
8.2.2	Properties	24
9	Module fabio.brucker100image	26
9.1	Variables	26
9.2	Class brucker100image	26
9.2.1	Methods	26
9.2.2	Properties	27
9.2.3	Class Variables	27
10	Module fabio.bruckerimage	28
10.1	Functions	28
10.2	Variables	28
10.3	Class bruckerimage	28
10.3.1	Methods	29
10.3.2	Properties	29
10.3.3	Class Variables	29
11	Module fabio.byte_offset	31
11.1	Variables	31
12	Module fabio.cbimage	32
12.1	Variables	32
12.2	Class cbimage	32
12.2.1	Methods	33
12.2.2	Properties	34
12.3	Class CIF	34
12.3.1	Methods	34
12.3.2	Properties	38
12.3.3	Class Variables	38
13	Module fabio.cf_io	39
13.1	Functions	39
13.2	Variables	39
14	Module fabio.compression	40
14.1	Functions	40
14.2	Variables	42
14.3	Class str	42
14.3.1	Methods	43
14.3.2	Properties	52

15 Module fabio.converters	53
15.1 Functions	53
15.2 Variables	53
16 Module fabio.datIO	54
16.1 Variables	54
16.2 Class fabiodata	54
16.2.1 Methods	54
16.2.2 Properties	55
16.3 Class columnfile	55
16.3.1 Methods	55
16.3.2 Properties	55
17 Module fabio.dm3image	56
17.1 Variables	56
17.2 Class dm3image	56
17.2.1 Methods	56
17.2.2 Properties	57
18 Module fabio.edfimage	58
18.1 Variables	58
18.2 Class Frame	58
18.2.1 Methods	59
18.2.2 Properties	60
18.3 Class edfimage	60
18.3.1 Methods	61
18.3.2 Properties	65
19 Module fabio.fabioimage	66
19.1 Functions	66
19.2 Variables	66
19.3 Class fabioimage	66
19.3.1 Methods	67
19.3.2 Properties	69
20 Module fabio.fabioutils	70
20.1 Functions	70
20.2 Variables	71
20.3 Class filename_object	72
20.3.1 Methods	72
20.4 Class StringIO	72
20.4.1 Methods	72
20.4.2 Properties	72
20.5 Class File	73
20.5.1 Methods	74
20.5.2 Properties	74
20.6 Class UnknownCompressedFile	75
20.6.1 Methods	76
20.6.2 Properties	76
20.7 Class GzipFile	77
20.7.1 Methods	77
20.7.2 Properties	78

20.7.3 Class Variables	78
20.8 Class BZ2File	79
20.8.1 Methods	79
20.8.2 Properties	80
21 Module fabio.file_series	81
21.1 Functions	81
21.2 Variables	82
21.3 Class file_series	82
21.3.1 Methods	83
21.3.2 Properties	85
21.3.3 Class Variables	85
21.4 Class numbered_file_series	85
21.4.1 Methods	86
21.4.2 Properties	86
21.4.3 Class Variables	86
21.5 Class filename_series	87
21.5.1 Methods	87
22 Module fabio.fit2dmaskimage	89
22.1 Variables	89
22.2 Class fit2dmaskimage	89
22.2.1 Methods	89
22.2.2 Properties	90
23 Module fabio.fit2ds spreadsheetimage	91
23.1 Variables	91
23.2 Class fit2ds spreadsheetimage	91
23.2.1 Methods	91
23.2.2 Properties	92
24 Module fabio.kcdimage	93
24.1 Variables	93
24.2 Class kcdimage	93
24.2.1 Methods	93
24.2.2 Properties	94
25 Module fabio.mar345_IO	95
25.1 Variables	95
26 Module fabio.mar345image	96
26.1 Variables	96
26.2 Class mar345image	96
26.2.1 Methods	96
26.2.2 Properties	97
27 Module fabio.marccdimage	98
27.1 Functions	98
27.2 Variables	98
27.3 Class marccdimage	99
27.3.1 Methods	99
27.3.2 Properties	99

28 Module fabio.openimage	100
28.1 Functions	100
28.2 Variables	100
29 Module fabio.pilatusimage	101
29.1 Variables	101
29.2 Class pilatusimage	101
29.2.1 Methods	101
29.2.2 Properties	102
30 Module fabio.pnmimage	103
30.1 Variables	103
30.2 Class pnmimage	103
30.2.1 Methods	103
30.2.2 Properties	105
31 Module fabio.readbytestream	106
31.1 Functions	106
31.2 Variables	106
32 Module fabio.tifimage	107
32.1 Variables	107
32.2 Class tifimage	108
32.2.1 Methods	108
32.2.2 Properties	109
32.3 Class Tiff_header	109
32.3.1 Methods	109
32.3.2 Properties	109
32.4 Class Image_File_Directory	109
32.4.1 Methods	110
32.4.2 Properties	110
32.5 Class Image_File_Directory_entry	110
32.5.1 Methods	110
32.5.2 Properties	111
33 Module fabio.xsdimage	112
33.1 Variables	112
33.2 Class xsdimage	112
33.2.1 Methods	112
33.2.2 Properties	113
Index	114

1 Package *fabio*

1.1 Modules

- **GEimage** (*Section 2, p. 8*)
- **GEimage_old**: Reads the header from a GE a-Si Angio Detector (*Section 3, p. 10*)
- **HiPiCimage**: Authors: Henning O. (*Section 4, p. 12*)
- **OXDimage**: Reads Oxford Diffraction Sapphire 3 images (*Section 5, p. 14*)
- **TiffIO** (*Section 6, p. 18*)
- **adscimage**:
Authors: Henning O. (*Section 7, p. 21*)
- **binaryimage**: Authors: Gael Goret, Jerome Kieffer, ESRF, France Emails: gael.goret@esrf.fr, jerome.kieffer@esrf.fr (*Section 8, p. 23*)
- **bruker100image** (*Section 9, p. 26*)
- **brukerimage**:
Authors: Henning O. (*Section 10, p. 28*)
- **byte_offset**: Authors: Jerome Kieffer, ESRF Email: jerome.kieffer@esrf.eu (*Section 11, p. 31*)
- **cbfimage**: Authors: Jérôme Kieffer, ESRF email:jerome.kieffer@esrf.fr (*Section 12, p. 32*)
- **cf.io** (*Section 13, p. 39*)
- **compression**: Authors: Jérôme Kieffer, ESRF email:jerome.kieffer@esrf.fr (*Section 14, p. 40*)
- **converters**: Converter module. (*Section 15, p. 53*)
- **datIO**: Authors: Henning O. (*Section 16, p. 54*)
- **dm3image**: Authors: Henning O. (*Section 17, p. 56*)
- **edfimage**:
License: GPLv2+ (*Section 18, p. 58*)
- **fabioimage**:
Authors: Henning O. (*Section 19, p. 66*)
- **fabioutils**: General purpose utilities functions for *fabio* (*Section 20, p. 70*)
- **file_series**:
Authors: Henning O. (*Section 21, p. 81*)
- **fit2dmaskimage**: Author: Andy Hammersley, ESRF Translation into python/fabio: Jon Wright, ESRF (*Section 22, p. 89*)
- **fit2dspreadsheetimage**: Read the fit2d ascii image output... (*Section 23, p. 91*)
- **kcdimage**: Authors: Jerome Kieffer, ESRF email:jerome.kieffer@esrf.fr

- (Section 24, p. 93)
- **mar345_IO**: New Cython version of mar345.io for preparing the migration to Python3
(Section 25, p. 95)
 - **mar345image**:
Authors: Henning O.
(Section 26, p. 96)
 - **marccdimage**:
Authors: Henning O.
(Section 27, p. 98)
 - **openimage**:
Authors: Henning O.
(Section 28, p. 100)
 - **pilatusimage**:
Authors: Henning O.
(Section 29, p. 101)
 - **pnmimage**:
Authors: Henning O.
(Section 30, p. 103)
 - **readbytestream**: Reads a bytestream
(Section 31, p. 106)
 - **tifimage**: FabIO class for dealing with TIFF images.
(Section 32, p. 107)
 - **xsdimage**: Authors: Jérôme Kieffer, ESRF email:jerome.kieffer@esrf.fr
(Section 33, p. 112)

1.2 Variables

Name	Description
version	Value: '0.1.1'
__package__	Value: 'fabio'

2 Module fabio.GEimage


2.1 Functions

demo()

2.2 Variables

Name	Description
logger	Value: logging.getLogger("GEimage")
GE_HEADER_INFO	Value: [('ImageFormat', 10, None), ('VersionOfStandardHeader', 2...]
__package__	Value: 'fabio'

2.3 Class GEimage



2.3.1 Methods

read(*self*, *fname*, *frame*=None)

Read in header into self.header and the data into self.data

Overrides: fabio.fabioimage.fabioimage.read

write(*self*, *fname*, *force_type*=<type 'numpy.uint16'>)

Not yet implemented

Overrides: fabio.fabioimage.fabioimage.write

getframe(*self*, *num*)

Returns a frame as a new fabioimage object

Overrides: fabio.fabioimage.fabioimage.getframe

next(*self*)

Get the next image in a series as a fabio image

Overrides: fabio.fabioimage.fabioimage.next

previous (<i>self</i>)

Get the previous image in a series as a fabio image

Overrides: fabio.fabioimage.fabioimage.previous

Inherited from fabio.fabioimage.fabioimage (Section 19.3)

`__init__()`, `add()`, `checkData()`, `checkHeader()`, `convert()`, `getclassname()`, `getheader()`,
`getmax()`, `getmean()`, `getmin()`, `getstddev()`, `integrate_area()`, `load()`, `make_slice()`,
`readROI()`, `readheader()`, `rebin()`, `resetvals()`, `save()`, `toPIL16()`, `update_header()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`,
`__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

2.3.2 Properties

Name	Description
<i>Inherited from fabio.fabioimage.fabioimage (Section 19.3)</i>	
classname	
<i>Inherited from object</i>	
__class__	

3 Module fabio.GEimage_old

Reads the header from a GE a-Si Angio Detector

Authors: Henning O. Sorensen & Erik Knudsen
 Center for Fundamental Research: Metal Structures in Four Dimensions
 Risoe National Laboratory
 Frederiksborgvej 399
 DK-4000 Roskilde
 email:erik.knudsen@risoe.dk

+ Jon Wright, ESRF

The header information has been taken from the script read.GEaSi_data.py
 by
 Antonino Miceli
 Thu Jan 4 13:46:31 CST 2007

3.1 Variables

Name	Description
<code>--package--</code>	Value: 'fabio'

3.2 Class GEimage



3.2.1 Methods

read (<i>self</i> , <i>fname</i> , <i>frame</i> =None)
--

Read in header into <code>self.header</code> and the data into <code>self.data</code>
--

Overrides: <code>fabio.fabioimage.fabioimage.read</code>
--

Inherited from fabio.fabioimage.fabioimage (Section 19.3)

`__init__()`, `add()`, `checkData()`, `checkHeader()`, `convert()`, `getclassname()`, `getframe()`, `getheader()`, `getmax()`, `getmean()`, `getmin()`, `getstddev()`, `integrate_area()`, `load()`, `make_slice()`, `next()`, `previous()`, `readROI()`, `readheader()`, `rebin()`, `resetvals()`, `save()`, `toPIL16()`, `update_header()`, `write()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattribute__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

3.2.2 Properties

Name	Description
<i>Inherited from fabio.fabioimage.fabioimage (Section 19.3)</i>	
<code>classname</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

4 Module fabio.HiPiCimage

Authors: Henning O. Sorensen & Erik Knudsen

Center for Fundamental Research: Metal Structures in Four Dimensions

Risoe National Laboratory

Frederiksborgvej 399

DK-4000 Roskilde

email:erik.knudsen@risoe.dk

+ Jon Wright, ESRF

Information about the file format from Masakatzu Kobayashi is highly appreciated

4.1 Variables

Name	Description
logger	Value: logging.getLogger("HiPiCimage")
__package__	Value: 'fabio'

4.2 Class HiPiCimage

object └

fabio.fabioimage.fabioimage └

fabio.HiPiCimage.HiPiCimage

Read HiPic images e.g. collected with a Hamamatsu CCD camera

4.2.1 Methods

read(*self*, *fname*, *frame*=None)

Read in header into self.header and
the data into self.data

Overrides: fabio.fabioimage.fabioimage.read

Inherited from fabio.fabioimage.fabioimage(Section 19.3)

`__init__()`, `add()`, `checkData()`, `checkHeader()`, `convert()`, `getclassname()`, `getframe()`, `getheader()`, `getmax()`, `getmean()`, `getmin()`, `getstddev()`, `integrate_area()`, `load()`, `make_slice()`, `next()`, `previous()`, `readROI()`, `readheader()`, `rebin()`, `resetvals()`, `save()`, `toPIL16()`, `update_header()`, `write()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

4.2.2 Properties

Name	Description
<i>Inherited from fabio.fabioimage.fabioimage (Section 19.3)</i>	
<code>classname</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

5 Module *fabio.OXDimage*

Reads Oxford Diffraction Sapphire 3 images

Authors: Henning O. Sorensen & Erik Knudsen

Center for Fundamental Research: Metal Structures in Four Dimensions

Risoe National Laboratory

Frederiksborgvej 399

DK-4000 Roskilde

email:erik.knudsen@risoe.dk

+ Jon Wright, ESRF

+ Gaël Goret, ESRF

+ Jérôme Kieffer, ESRF

5.1 Variables

Name	Description
<code>__doc__</code>	Value: "..."
<code>logger</code>	Value: <code>logging.getLogger("OXDimage")</code>
<code>rad2deg</code>	Value: <code><ufunc 'rad2deg'></code>
<code>deg2rad</code>	Value: <code><ufunc 'deg2rad'></code>
<code>DETECTOR_TYPES</code>	Value: <code>{0: 'Sapphire/KM4CCD (1x1: 0.06mm, 2x2: 0.12mm)', 1: 'Sap...</code>
<code>DEFAULT_HEADERS</code>	Value: <code>{'ASCII Section size in Byte': 256, 'Compression': 'TY1', ...</code>
<code>__package__</code>	Value: <code>'fabio'</code>

5.2 Class *OXDimage*

object

fabio.fabioimage.fabioimage

fabio.OXDimage.OXDimage

Oxford Diffraction Sapphire 3 images reader/writer class

5.2.1 Methods

read(*self*, *fname*, *frame*=None)

Read in header into `self.header` and
the data into `self.data`

Overrides: `fabio.fabioimage.fabioimage.read`

write(*self*, *fname*)

Write Oxford diffraction images: this is still beta

Parameters

fname: output filename

Overrides: `fabio.fabioimage.fabioimage.write`

getCompressionRatio(*self*)

calculate the compression factor obtained vs raw data

checkData(*data*=None)

Empty for `fabioimage` but may be populated by others classes, especially for
format accepting only integers

Overrides: `fabio.fabioimage.fabioimage.checkData` extit(inherited
documentation)

Inherited from `fabio.fabioimage.fabioimage` (Section 19.3)

`__init__()`, `add()`, `checkHeader()`, `convert()`, `getclassname()`, `getframe()`, `getheader()`,
`getmax()`, `getmean()`, `getmin()`, `getstddev()`, `integrate_area()`, `load()`, `make_slice()`,
`next()`, `previous()`, `readROI()`, `readheader()`, `rebin()`, `resetvals()`, `save()`, `toPIL16()`,
`update_header()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`,
`__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

5.2.2 Properties

Name	Description
<i>Inherited from <code>fabio.fabioimage.fabioimage</code> (Section 19.3)</i>	

continued on next page

Name	Description
classname	
<i>Inherited from object</i>	
__class__	

5.3 Class Section



Small helper class for writing binary headers

5.3.1 Methods

__init__(*self*, *size*, *dictHeader*)

x.__init__(...) initializes x; see x.__class__.__doc__ for signature

Parameters

size: size of the header section in bytes

dictHeader: headers of the image

Overrides: object.__init__

__repr__(*self*)

repr(x)

Overrides: object.__repr__ `exitit`(inherited documentation)

getSize(*self*, *dtype*)

setData(*self*, *key*, *offset*, *dtype*, *default=None*)

Parameters

offset: int, starting position in the section

key: name of the header key

dtype: type of the data to insert (defines the size!)

Inherited from object

`__delattr__()`, `__format__()`, `__getattribute__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

5.3.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

6 Module *fabio.TiffIO*

Author: V.A. Sole - ESRF Data Analysis

6.1 Variables

Name	Description
<code>__revision__</code>	Value: 1501
<code>DEBUG</code>	Value: 0
<code>ALLOW_MULTIPLE_STRIPS</code>	Value: False
<code>TAG_ID</code>	Value: {256: 'NumberOfColumns', 257: 'NumberOfRows', 258: 'BitsP...
<code>TAG_NUMBER_OF_COLUMNS</code>	Value: 256
<code>TAG_NUMBER_OF_ROWS</code>	Value: 257
<code>TAG_BITS_PER_SAMPLE</code>	Value: 258
<code>TAG_PHOTOMETRIC_INTERPRETATION</code>	Value: 262
<code>TAG_COMPRESSION</code>	Value: 259
<code>TAG_IMAGE_DESCRIPTION</code>	Value: 270
<code>TAG_STRIP_OFFSETS</code>	Value: 273
<code>TAG_ROWS_PER_STRIP</code>	Value: 278
<code>TAG_STRIP_BYTE_COUNTS</code>	Value: 279
<code>TAG_SOFTWARE</code>	Value: 305
<code>TAG_DATE</code>	Value: 306
<code>TAG_COLORMAP</code>	Value: 320
<code>TAG_SAMPLE_FORMAT</code>	Value: 339
<code>FIELD_TYPE</code>	Value: {1: ('BYTE', 'B'), 2: ('ASCII', 's'), 3: ('SHORT', 'H'), ...
<code>FIELD_TYPE_OUT</code>	Value: {'B': 1, 'H': 3, 'I': 4, 'II': 5, 'b': 6, 'd': 12, 'f': 1...
<code>SAMPLE_FORMAT_UINT</code>	Value: 1
<code>SAMPLE_FORMAT_INT</code>	Value: 2
<code>SAMPLE_FORMAT_FLOAT</code>	Value: 3

continued on next page

Name	Description
SAMPLE_FORMAT_VOID	Value: 4
SAMPLE_FORMAT_COMPLEXINT	Value: 5
SAMPLE_FORMAT_COMPLEXIEEEFP	Value: 6
<code>--package--</code>	Value: 'fabio'

6.2 Class *TiffIO*



6.2.1 Methods

```
__init__(self, filename, mode=None, cache_length=20, mono_output=False)
```

x.**__init__**(...) initializes x; see x.**__class__**.**__doc__** for signature

Overrides: object.**__init__** extit(inherited documentation)

```
getNumberOfImages(self)
```

```
getImageFileDirectories(self, fd=None)
```

```
getData(self, nImage, **kw)
```

```
getImage(self, nImage)
```

```
getInfo(self, nImage, **kw)
```

```
writeImage(self, image0, info=None, software=None, date=None)
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(),
__repr__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()
```

6.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>--class--</code>	

7 Module *fabio.adscimage*

Authors: Henning O. Sorensen & Erik Knudsen
 Center for Fundamental Research: Metal Structures in Four Dimensions
 Risoe National Laboratory
 Frederiksborgvej 399
 DK-4000 Roskilde
 email:erik.knudsen@risoe.dk

+ mods for fabio by JPW

7.1 Functions

test()
testcase

7.2 Variables

Name	Description
logger	Value: logging.getLogger("adscimage")
__package__	Value: 'fabio'

7.3 Class *adscimage*

object └─

fabio.fabioimage.fabioimage └─

fabio.adscimage.adscimage

Read an image in ADSC format (quite similar to edf?)

7.3.1 Methods

`--init--(self, *args, **kwargs)`

Set up initial values

Overrides: `object.__init__` `exitit`(inherited documentation)

`read(self, fname, frame=None)`

read in the file

Overrides: `fabio.fabioimage.fabioimage.read`

`write(self, fname)`

Write adsc format

Overrides: `fabio.fabioimage.fabioimage.write`

Inherited from `fabio.fabioimage.fabioimage` (Section 19.3)

`add()`, `checkData()`, `checkHeader()`, `convert()`, `getclassname()`, `getframe()`, `getheader()`, `getmax()`, `getmean()`, `getmin()`, `getstddev()`, `integrate_area()`, `load()`, `make_slice()`, `next()`, `previous()`, `readROI()`, `readheader()`, `rebin()`, `resetvals()`, `save()`, `toPIL16()`, `update_header()`

Inherited from `object`

`--delattr--()`, `--format--()`, `--getattr--()`, `--hash--()`, `--new--()`, `--reduce--()`, `--reduce_ex--()`, `--repr--()`, `--setattr--()`, `--sizeof--()`, `--str--()`, `--subclasshook--()`

7.3.2 Properties

Name	Description
<i>Inherited from <code>fabio.fabioimage.fabioimage</code> (Section 19.3)</i>	
<code>classname</code>	
<i>Inherited from <code>object</code></i>	
<code>--class--</code>	

8 Module **fabio.binaryimage**

Authors: Gael Goret, Jerome Kieffer, ESRF, France Emails: gael.goret@esrf.fr, jerome.kieffer@esrf.fr

Binary files images are simple none-compressed 2D images only defined by their : data-type, dimensions, byte order and offset

This simple library has been made for manipulating exotic/unknown files format.

Version: 17 Apr 2012

Authors: Gael Goret, Jerome Kieffer

Contact: gael.goret@esrf.fr

Copyright: European Synchrotron Radiation Facility, Grenoble, France

License: GPLv3+

8.1 Variables

Name	Description
<code>__doc__</code>	Value: ...
<code>logger</code>	Value: <code>logging.getLogger("binaryimage")</code>
<code>__package__</code>	Value: 'fabio'

8.2 Class **binaryimage**



This simple library has been made for manipulating exotic/unknown files format.

Binary files images are simple none-compressed 2D images only defined by their : data-type, dimensions, byte order and offset

8.2.1 Methods

`__init__(self, *args, **kwargs)`

Set up initial values

Overrides: `object.__init__` `exitit`(inherited documentation)

`swap_needed(endian)`

Decide if we need to byteswap

`read(self, fname, dim1, dim2, offset=0, bytecode='int32', endian='<')`

Read a binary image Parameters : fname, dim1, dim2, offset, bytecode, endian
fname : file name :

str dim1,dim2 : image dimensions : int offset : size of the : int bytecode among :
"int8", "int16", "int32", "int64", "uint8", "uint16", "uint32", "uint64", "float32", "float64", ...
endian among short or long endian ("<" or ">")

Overrides: `fabio.fabioimage.fabioimage.read`

`estimate_offset_value(self, fname, dim1, dim2, bytecode='int32')`

Estimates the size of a file

`write(self, fname)`

To be overwritten - write the file

Overrides: `fabio.fabioimage.fabioimage.write` `exitit`(inherited documentation)

Inherited from `fabio.fabioimage.fabioimage` (Section 19.3)

`add()`, `checkData()`, `checkHeader()`, `convert()`, `getclassname()`, `getframe()`, `getheader()`, `getmax()`, `getmean()`, `getmin()`, `getstddev()`, `integrate_area()`, `load()`, `make_slice()`, `next()`, `previous()`, `readROI()`, `readheader()`, `rebin()`, `resetvals()`, `save()`, `toPIL16()`, `update_header()`

Inherited from `object`

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

8.2.2 Properties

Name	Description
<i>Inherited from <code>fabio.fabioimage.fabioimage</code> (Section 19.3)</i>	

continued on next page


Name	Description
classname	
<i>Inherited from object</i>	
__class__	

9 Module *fabio.bruker100image*

9.1 Variables

Name	Description
logger	Value: logging.getLogger("bruker100image")
__package__	Value: 'fabio'

9.2 Class *bruker100image*



9.2.1 Methods

toPIL16(*self*, *filename*=None)

Convert to Python Imaging Library 16 bit greyscale image

FIXME - this should be handled by the libraries now

Overrides: *fabio.fabioimage.fabioimage.toPIL16* extit(inherited documentation)

read(*self*, *fname*, *frame*=None)

Read in and unpack the pixels (including overflow table

Overrides: *fabio.fabioimage.fabioimage.read* extit(inherited documentation)

*Inherited from **fabio.brukerimage.brukerimage**(Section 10.3)*

write(), *write2()*

*Inherited from **fabio.fabioimage.fabioimage**(Section 19.3)*

__init__(), *add()*, *checkData()*, *checkHeader()*, *convert()*, *getclassname()*, *getframe()*, *getheader()*, *getmax()*, *getmean()*, *getmin()*, *getstddev()*, *integrate_area()*, *load()*,

`make_slice()`, `next()`, `previous()`, `readROI()`, `readheader()`, `rebin()`, `resetvals()`, `save()`,
`update_header()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`,
`__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

9.2.2 Properties

Name	Description
<i>Inherited from <code>fabio.fabioimage.fabioimage</code> (Section 19.3)</i>	
<code>classname</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

9.2.3 Class Variables

Name	Description
<i>Inherited from <code>fabio.brukerimage.brukerimage</code> (Section 10.3)</i>	
<code>__headerstring__</code>	

10 Module *fabio.brukerimage*

Authors: Henning O. Sorensen & Erik Knudsen

Center for Fundamental Research: Metal Structures in Four Dimensions

Risoe National Laboratory

Frederiksborgvej 399

DK-4000 Roskilde

email:erik.knudsen@risoe.dk

Based on: `openbruker`, `readbruker`, `readbrukerheader` functions in the `opendata` module of `ImageD11` written by Jon Wright, ESRF, Grenoble, France

10.1 Functions

test()
a testcase

10.2 Variables

Name	Description
<code>logger</code>	Value: <code>logging.getLogger("brukerimage")</code>
<code>--package--</code>	Value: <code>'fabio'</code>

10.3 Class *brukerimage*



Known Subclasses: `fabio.bruker100image.bruker100image`

Read and eventually write ID11 bruker (eg smart6500) images

10.3.1 Methods

read (<i>self</i> , <i>fname</i> , <i>frame</i> =None)
--

Read in and unpack the pixels (including overflow table)
--

Overrides: <i>fabio.fabioimage.fabioimage.read</i>
--

write (<i>self</i> , <i>fname</i>)

Writes the image as EDF

FIXME - this should call <i>edfimage.write</i> if that is wanted?

eg: <i>obj</i> = <i>edfimage</i> (<i>data</i> = <i>self.data</i> , <i>header</i> = <i>self.header</i>)
<i>obj.write</i> (<i>fname</i>)
or maybe something like: <i>edfimage.write</i> (<i>self</i> , <i>fname</i>)

Overrides: <i>fabio.fabioimage.fabioimage.write</i>

write2 (<i>self</i> , <i>fname</i>)
--

FIXME: what is this?

*Inherited from **fabio.fabioimage.fabioimage** (Section 19.3)*

__init__(), *add*(), *checkData*(), *checkHeader*(), *convert*(), *getclassname*(), *getframe*(), *getheader*(), *getmax*(), *getmean*(), *getmin*(), *getstddev*(), *integrate_area*(), *load*(), *make_slice*(), *next*(), *previous*(), *readROI*(), *readheader*(), *rebin*(), *resetvals*(), *save*(), *toPIL16*(), *update_header*()

Inherited from object

__delattr__(), *__format__*(), *__getattr__*(), *__hash__*(), *__new__*(), *__reduce__*(), *__reduce_ex__*(), *__repr__*(), *__setattr__*(), *__sizeof__*(), *__str__*(), *__subclasshook__*()

10.3.2 Properties

Name	Description
<i>Inherited from fabio.fabioimage.fabioimage (Section 19.3)</i>	
<i>classname</i>	
<i>Inherited from object</i>	
<i>__class__</i>	

10.3.3 Class Variables

Name	Description
<code>__headerstring__</code>	Value: ' '

11 Module `fabio.byte_offset`

Authors: Jerome Kieffer, ESRF Email: jerome.kieffer@esrf.eu

Cif Binary Files images are 2D images written by the Pilatus detector and others. They use a modified (simplified) byte-offset algorithm. This file contains the decompression function from a string to an int64 numpy array.

This is Cython: convert it to pure C then compile it with `gcc $(cython byte_offset.pyx)`

Author: Jérôme Kieffer

Contact: jerome.kieffer@esrf.eu

Copyright: 2010, European Synchrotron Radiation Facility, Grenoble, France

License: GPLv3+

11.1 Variables

Name	Description
<code>--package--</code>	Value: <code>'fabio'</code>
<code>--test--</code>	Value: <code>{}</code>

12 Module *fabio.cbfimage*

Authors: Jérôme Kieffer, ESRF
 email:jerome.kieffer@esrf.fr

Cif Binary Files images are 2D images written by the Pilatus detector and others. They use a modified (simplified) byte-offset algorithm.

CIF is a library for manipulating Crystallographic information files and tries to conform to the specification of the IUCR

Author: Jérôme Kieffer

Contact: jerome.kieffer@esrf.eu


Copyright: European Synchrotron Radiation Facility, Grenoble, France

License: GPLv3+

12.1 Variables

Name	Description
logger	Value: logging.getLogger("cbfimage")
DATA_TYPES	Value: {'signed 16-bit integer': <type 'numpy.int16'>, 'signed 3...
MINIMUM_KEYS	Value: ['X-Binary-Size-Fastest-Dimension', 'ByteOrder', 'Data ty...
STARTER	Value: '\x0c\x1a\x04\xd5'
PADDING	Value: 512
__package__	Value: 'fabio'

12.2 Class *cbfimage*



Read the Cif Binary File data format

12.2.1 Methods

`__init__(self, data=None, header=None, fname=None)`

Constructor of the class CIF Binary File reader.

Parameters

`_strFilename`: the name of the file to open
(type=string)

Overrides: `object.__init__`

`checkData(data=None)`

Empty for `fabioimage` but may be populated by others classes, especially for format accepting only integers

Overrides: `fabio.fabioimage.fabioimage.checkData` extit(inherited documentation)

`read(self, fname, frame=None)`

Read in header into `self.header` and
the data into `self.data`

Overrides: `fabio.fabioimage.fabioimage.read`

`write(self, fname)`

write the file in CBF format

Parameters

`fname`: name of the file

Overrides: `fabio.fabioimage.fabioimage.write`

Inherited from `fabio.fabioimage.fabioimage` (Section 19.3)

`add()`, `checkHeader()`, `convert()`, `getclassname()`, `getframe()`, `getheader()`, `getmax()`, `getmean()`, `getmin()`, `getstddev()`, `integrate_area()`, `load()`, `make_slice()`, `next()`, `previous()`, `readROI()`, `readheader()`, `rebin()`, `resetvals()`, `save()`, `toPIL16()`, `update_header()`

Inherited from `object`

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

12.2.2 Properties

Name	Description
<i>Inherited from fabio.fabioimage.fabioimage (Section 19.3)</i> classname	
<i>Inherited from object</i> __class__	

12.3 Class CIF



This is the CIF class, it represents the CIF dictionary; and as a python dictionary thus inherits from the dict built in class.

12.3.1 Methods

<code>__init__(self, _strFilename=None)</code>
Constructor of the class.
Parameters
<code>_strFilename</code> : the name of the file to open <i>(type=filename (str) or file object)</i>
Return Value
new empty dictionary
Overrides: <code>object.__init__</code>

<code>__setitem__(self, key, value)</code>
<code>x[i]=y</code>
Overrides: <code>dict.__setitem__</code> <code>extit</code> (inherited documentation)

pop(*self*, *key*)

If key is not found, d is returned if given, otherwise KeyError is raised

Return Value

v, remove specified key and return the corresponding value

Overrides: dict.pop exitit(inherited documentation)

popitem(*self*, *key*)

2-tuple; but raise KeyError if D is empty.

Return Value

(k, v), remove and return some (key, value) pair as a

Overrides: dict.popitem exitit(inherited documentation)

loadCIF(*self*, *_strFilename*, *_bKeepComment=False*)

Load the CIF file and populates the CIF dictionary into the object

Parameters

_strFilename: the name of the file to open
(*type=string*)

_strFilename: the name of the file to open
(*type=string*)

Return Value

None

readCIF(*self*, *_strFilename*, *_bKeepComment=False*)

Load the CIF file and populates the CIF dictionary into the object

Parameters

_strFilename: the name of the file to open
(*type=string*)

_strFilename: the name of the file to open
(*type=string*)

Return Value

None

isAscii(*_strIn*)

Check if all characters in a string are ascii,

Parameters

_strIn: input string
(type=python string)

Return Value

boolean
(type=boolean)

saveCIF(*self*, *_strFilename*=`'test.cif'`, *linesep*=`'\n'`, *binary*=`False`)

Transforms the CIF object in string then write it into the given file

Parameters

_strFilename: the of the file to be written
linesep: line separation used (to force compatibility with windows/unix)
binary: Shall we write the data as binary (True only for imageCIF/CBF)
param: *(type=string)*

tostring(*self*, *_strFilename*=`None`, *linesep*=`'\n'`)

converts a cif dictionary to a string according to the CIF syntax

Parameters

_strFilename: the name of the filename to be appended in the header of the CIF file
(type=string @return : a sting that corresponds to the content of the CIF - file.)

Return Value

string

exists(*self*, *sKey*)

Check if the key exists in the CIF and is non empty.

Parameters

sKey: CIF key
 (*type=string*)
cif: CIF dictionary

Return Value

True if the key exists in the CIF dictionary and is non empty
 (*type=boolean*)

existsInLoop(*self*, *sKey*)

Check if the key exists in the CIF dictionary.

Parameters

sKey: CIF key
 (*type=string*)
cif: CIF dictionary

Return Value

True if the key exists in the CIF dictionary and is non empty
 (*type=boolean*)

loadCHIPLOT(*self*, *_strFilename*)

Load the powder diffraction CHIPLOT file and returns the pd.CIF dictionary in the object

Parameters

_strFilename: the name of the file to open
 (*type=string*)

Return Value

the CIF object corresponding to the powder diffraction
 (*type=dictionary*)

LoopHasKey(*loop*, *key*)

Returns True if the key (string) exist in the array called loop

Inherited from dict

`--cmp--()`, `--contains--()`, `--delitem--()`, `--eq--()`, `--ge--()`, `--getattribute--()`, `--getitem--()`,
`--gt--()`, `--iter--()`, `--le--()`, `--len--()`, `--lt--()`, `--ne--()`, `--new--()`, `--repr--()`, `--sizeof--()`,

clear(), copy(), fromkeys(), get(), has_key(), items(), iteritems(), iterkeys(), iter-values(), keys(), setdefault(), update(), values()

Inherited from object

__delattr__(), __format__(), __reduce__(), __reduce_ex__(), __setattr__(), __str__(), __subclasshook__()

12.3.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

12.3.3 Class Variables

Name	Description
EOL	Value: ['\r', '\n', '\r\n', '\n\r']
BLANK	Value: [' ', '\t', '\r', '\n', '\r\n', '\n\r']
START_COMMENT	Value: ['"', '\']
BINARY_MARKER	Value: '--CIF-BINARY-FORMAT-SECTION--'
<i>Inherited from dict</i>	
__hash__	

13 Module *fabio.cf_io*

13.1 Functions

read(...)

call the c-columnfile reading interface. The mode keyword argument is either: "a" for ascii (the default) "b" for binary

13.2 Variables

Name	Description
<code>__package__</code>	Value: None

14 Module *fabio.compression*

Authors: Jérôme Kieffer, ESRF
 email:jerome.kieffer@esrf.fr

FabIO library containing compression and decompression algorithm for various

Author: Jérôme Kieffer

Contact: jerome.kieffer@esrf.eu

Copyright: European Synchrotron Radiation Facility, Grenoble, France

License: GPLv3+

14.1 Functions

md5sum (<i>blob</i>)

returns the md5sum of an object...

endianness ()

decGzip (<i>stream</i>)

decBzip2 (<i>stream</i>)

decompress a chunk of data using the bzip2 algorithm
--

decZlib (<i>stream</i>)

decompress a chunk of data using the zlib algorithm

decByteOffset_python (<i>stream</i> , <i>size</i>)

Analyze a stream of char with any length of exception (2,4, or 8 bytes integers)
--

Parameters

stream: string representing the compressed data
--

size: the size of the output array (of longInts) @return :NArrays
--


```
@return list of NPararrays
```

```
@return list of NPararrays
```

```
@return list of NArrays
```

```
numpy.array([0,1,2,127,0,1,2,128,0,1,2,32767,0,1,2,32768,0,1,2,2147483647,0,1,2,2147483648,0,1,2,
```

raw_8, raw_16, raw_32: strings containing raw data with integer of the given size @return numpy.ndarray

decKM4CCD(*raw_8*, *raw_16*=None, *raw_32*=None)

Modified byte offset decompressor used in Oxford Diffraction images

Parameters

raw_8, *raw_16*, *raw_32*: strings containing raw data with integer of the given size @return numpy.ndarray

compTY1(*data*)

Modified byte offset compressor used in Oxford Diffraction images

@param data numpy.ndarray

decPCK(*stream*, *dim1*=None, *dim2*=None, *overflowPix*=None)

Modified CCP4 pck decompressor used in MAR345 images

Parameters

stream: string or file @return numpy.ndarray (square array)

compPCK(*data*)


Modified CCP4 pck compressor used in MAR345 images

@param data numpy.ndarray (square array) @return compressed stream

14.2 Variables

Name	Description
logger	Value: logging.getLogger("compression")
__package__	Value: 'fabio'

14.3 Class str



str(object) -> string

Return a nice string representation of the object. If the argument is a string, the return value is the same object.

14.3.1 Methods

`--add--`(*x*, *y*)

`x+y`

`--contains--`(*x*, *y*)

`y in x`

`--eq--`(*x*, *y*)

`x==y`

`--format--`(*S*, *format_spec*)

default object formatter

Return Value

string

Overrides: `object.__format__`

`--ge--`(*x*, *y*)

`x>=y`

`--getattr--`(...)

`x.__getattr__('name') <==> x.name`

Overrides: `object.__getattr__`

`--getitem--`(*x*, *y*)

`x[y]`

`--getnewargs--`(...)

`--getslice--`(*x*, *i*, *j*)

`x[i:j]`

Use of negative indices is not supported.

`--gt--`(*x*, *y*)

`x>y`

__hash__(*x*)

hash(*x*)

Overrides: object.__hash__

__le__(*x*, *y*)

x ≤ *y*

__len__(*x*)

len(*x*)

__lt__(*x*, *y*)

x < *y*

__mod__(*x*, *y*)

x % *y*

__mul__(*x*, *n*)

x * *n*

__ne__(*x*, *y*)

x != *y*

__new__(*T*, *S*, ...)

Return Value

a new object with type *S*, a subtype of *T*

Overrides: object.__new__

__repr__(*x*)

repr(*x*)

Overrides: object.__repr__

__rmod__(*x*, *y*)

y % *x*

__rmul__(*x*, *n*)

n * *x*

__sizeof__(*S*)**Return Value**size of *S* in memory, in bytesOverrides: `object.__sizeof__`**__str__**(*x*)`str(x)`Overrides: `object.__str__`**capitalize**(*S*)Return a copy of the string *S* with only its first character capitalized.**Return Value**

string

center(*S*, *width*, *fillchar*=...)Return *S* centered in a string of length *width*. Padding is done using the specified fill character (default is a space)**Return Value**

string

count(*S*, *sub*, *start*=..., *end*=...)Return the number of non-overlapping occurrences of substring *sub* in string *S*[*start*:*end*]. Optional arguments *start* and *end* are interpreted as in slice notation.**Return Value**

int

decode(*S*, *encoding*=..., *errors*=...)

Decodes *S* using the codec registered for encoding. *encoding* defaults to the default encoding. *errors* may be given to set a different error handling scheme. Default is 'strict' meaning that encoding errors raise a `UnicodeDecodeError`. Other possible values are 'ignore' and 'replace' as well as any other name registered with `codecs.register_error` that is able to handle `UnicodeDecodeErrors`.

Return Value

object

encode(*S*, *encoding*=..., *errors*=...)

Encodes *S* using the codec registered for encoding. *encoding* defaults to the default encoding. *errors* may be given to set a different error handling scheme. Default is 'strict' meaning that encoding errors raise a `UnicodeEncodeError`. Other possible values are 'ignore', 'replace' and 'xmlcharrefreplace' as well as any other name registered with `codecs.register_error` that is able to handle `UnicodeEncodeErrors`.

Return Value

object

endswith(*S*, *suffix*, *start*=..., *end*=...)

Return True if *S* ends with the specified suffix, False otherwise. With optional *start*, test *S* beginning at that position. With optional *end*, stop comparing *S* at that position. *suffix* can also be a tuple of strings to try.

Return Value

bool

expandtabs(*S*, *tabsize*=...)

Return a copy of *S* where all tab characters are expanded using spaces. If *tabsize* is not given, a tab size of 8 characters is assumed.

Return Value

string

find(*S*, *sub*, *start*=..., *end*=...)

Return the lowest index in *S* where substring *sub* is found, such that *sub* is contained within *s*[*start*:*end*]. Optional arguments *start* and *end* are interpreted as in slice notation.

Return -1 on failure.

Return Value

int

format(*S*, **args*, ***kwargs*)**Return Value**

string

index(*S*, *sub*, *start*=... , *end*=...)

Like *S.find()* but raise *ValueError* when the substring is not found.**Return Value**

int

isalnum(*S*)

Return True if all characters in *S* are alphanumeric and there is at least one character in *S*, False otherwise.**Return Value**

bool

isalpha(*S*)

Return True if all characters in *S* are alphabetic and there is at least one character in *S*, False otherwise.**Return Value**

bool

isdigit(*S*)

Return True if all characters in *S* are digits and there is at least one character in *S*, False otherwise.**Return Value**

bool

islower(*S*)

Return True if all cased characters in *S* are lowercase and there is at least one cased character in *S*, False otherwise.**Return Value**

bool

isspace(*S*)

Return True if all characters in *S* are whitespace and there is at least one character in *S*, False otherwise.**Return Value**

bool

istitle(*S*)

Return True if *S* is a titlecased string and there is at least one character in *S*, i.e. uppercase characters may only follow uncased characters and lowercase characters only cased ones. Return False otherwise.

Return Value

bool

isupper(*S*)

Return True if all cased characters in *S* are uppercase and there is at least one cased character in *S*, False otherwise.

Return Value

bool

join(*S*, *iterable*)

Return a string which is the concatenation of the strings in the iterable. The separator between elements is *S*.

Return Value

string

ljust(*S*, *width*, *fillchar*=...)

Return *S* left-justified in a string of length *width*. Padding is done using the specified fill character (default is a space).

Return Value

string

lower(*S*)

Return a copy of the string *S* converted to lowercase.

Return Value

string

lstrip(*S*, *chars*=...)

Return a copy of the string *S* with leading whitespace removed. If *chars* is given and not None, remove characters in *chars* instead. If *chars* is unicode, *S* will be converted to unicode before stripping

Return Value

string or unicode

partition(*S*, *sep*)

Search for the separator *sep* in *S*, and return the part before it, the separator itself, and the part after it. If the separator is not found, return *S* and two empty strings.

Return Value

(head, sep, tail)

replace(*S*, *old*, *new*, *count*=...)

Return a copy of string *S* with all occurrences of substring *old* replaced by *new*. If the optional argument *count* is given, only the first *count* occurrences are replaced.

Return Value

string

rfind(*S*, *sub*, *start*=... , *end*=...)

Return the highest index in *S* where substring *sub* is found, such that *sub* is contained within *s*[*start*:*end*]. Optional arguments *start* and *end* are interpreted as in slice notation.

Return -1 on failure.

Return Value

int

rindex(*S*, *sub*, *start*=... , *end*=...)

Like *S*.*rfind*() but raise *ValueError* when the substring is not found.

Return Value

int

rjust(*S*, *width*, *fillchar*=...)

Return *S* right-justified in a string of length *width*. Padding is done using the specified fill character (default is a space)

Return Value

string

rpartition(*S*, *sep*)

Search for the separator *sep* in *S*, starting at the end of *S*, and return the part before it, the separator itself, and the part after it. If the separator is not found, return two empty strings and *S*.

Return Value

(head, sep, tail)

rsplit(*S*, *sep*=... , *maxsplit*=...)

Return a list of the words in the string *S*, using *sep* as the delimiter string, starting at the end of the string and working to the front. If *maxsplit* is given, at most *maxsplit* splits are done. If *sep* is not specified or is *None*, any whitespace string is a separator.

Return Value

list of strings

rstrip(*S*, *chars*=...)

Return a copy of the string *S* with trailing whitespace removed. If *chars* is given and not *None*, remove characters in *chars* instead. If *chars* is unicode, *S* will be converted to unicode before stripping

Return Value

string or unicode

split(*S*, *sep*=... , *maxsplit*=...)

Return a list of the words in the string *S*, using *sep* as the delimiter string. If *maxsplit* is given, at most *maxsplit* splits are done. If *sep* is not specified or is *None*, any whitespace string is a separator and empty strings are removed from the result.

Return Value

list of strings

splitlines(*S*, *keepends*=...)

Return a list of the lines in *S*, breaking at line boundaries. Line breaks are not included in the resulting list unless *keepends* is given and true.

Return Value

list of strings

startswith(*S*, *prefix*, *start*=..., *end*=...)

Return True if *S* starts with the specified prefix, False otherwise. With optional *start*, test *S* beginning at that position. With optional *end*, stop comparing *S* at that position. *prefix* can also be a tuple of strings to try.

Return Value

bool

strip(*S*, *chars*=...)

Return a copy of the string *S* with leading and trailing whitespace removed. If *chars* is given and not None, remove characters in *chars* instead. If *chars* is unicode, *S* will be converted to unicode before stripping

Return Value

string or unicode

swapcase(*S*)

Return a copy of the string *S* with uppercase characters converted to lowercase and vice versa.

Return Value

string

title(*S*)

Return a titlecased version of *S*, i.e. words start with uppercase characters, all remaining cased characters have lowercase.

Return Value

string

translate(*S*, *table*, *deletechars*=...)

Return a copy of the string *S*, where all characters occurring in the optional argument *deletechars* are removed, and the remaining characters have been mapped through the given translation table, which must be a string of length 256.

Return Value

string

upper(*S*)

Return a copy of the string *S* converted to uppercase.

Return Value

string

zfill (<i>S</i> , <i>width</i>)
--

Pad a numeric string <i>S</i> with zeros on the left, to fill a field of the specified width. The string <i>S</i> is never truncated.

Return Value string

Inherited from object

`--delattr--()`, `--init--()`, `--reduce--()`, `--reduce_ex--()`, `--setattr--()`, `--subclasshook--()`

14.3.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>--class--</code>	

15 Module *fabio.converters*

Converter module. This is for the moment empty (populated only with almost pass through anonymous functions) but aims to be populated with more sophisticated translators ...

Author: Jérôme Kieffer

Contact: jerome.kieffer@esrf.eu

Copyright: European Synchrotron Radiation Facility, Grenoble, France

License: GPLv3+

15.1 Functions

convert_data_integer (<i>data</i>)
convert data to integer

convert_data (<i>inp, outp, data</i>)
Return data converted to the output format ... over-simplistic implementation for the moment ...
Parameters
<i>inp, outp</i> : input/output format like "cbfimage"
<i>data</i> (ndarray): the actual dataset to be transformed

convert_header (<i>inp, outp, header</i>)
return header converted to the output format
Parameters
<i>inp, outp</i> : input/output format like "cbfimage"
<i>header</i> (dict): the actual set of headers to be transformed

15.2 Variables

Name	Description
logger	Value: logging.getLogger("converter")
CONVERSION_HEADER	Value: {'edfimage', 'edfimage': <function <lambda> at 0x21960c8>}
CONVERSION_DATA	Value: {'edfimage', 'OXDimage': <function convert_data_integer...>}
--package--	Value: 'fabio'

16 Module *fabio.datIO*

Authors: Henning O. Sorensen & Erik Knudsen

Center for Fundamental Research: Metal Structures in Four Dimensions

Risoe National Laboratory

Frederiksborgvej 399

DK-4000 Roskilde

email:erik.knudsen@risoe.dk

and Jon Wright, ESRF

16.1 Variables

Name	Description
<code>__package__</code>	Value: None

16.2 Class *fabiodata*

object └─ **fabio.datIO.fabiodata**

Known Subclasses: *fabio.datIO.columnfile*

A common class for dataIO in fable Contains a 2d numpy array for keeping data, and two lists (clabels and rlabels) containing labels for columns and rows respectively

16.2.1 Methods

<code>__init__(self, data=None, clabels=None, rlabels=None, fname=None)</code>

set up initial values

Overrides: object.__init__

<code>read(self, fname=None, frame=None)</code>
--

To be overridden by format specific subclasses

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`,

`__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

16.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

16.3 Class *columnfile*



Concrete *fabiodata* class

16.3.1 Methods

`read(self, fname, frame=None)`

To be overridden by format specific subclasses

Overrides: `fabio.datIO.fabiodata.read` `exitit`(inherited documentation)

Inherited from `fabio.datIO.fabiodata`(Section 16.2)

`__init__()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`,
`__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

16.3.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

17 Module *fabio.dm3image*

Authors: Henning O. Sorensen & Erik Knudsen

Center for Fundamental Research: Metal Structures in Four Dimensions

Risoe National Laboratory

Frederiksborgvej 399

DK-4000 Roskilde

email:erik.knudsen@risoe.dk

+ Jon Wright, ESRF

17.1 Variables

Name	Description
logger	Value: logging.getLogger("dm3image")
DATA_TYPES	Value: {2: <type 'numpy.int16'>, 3: <type 'numpy.int32'>, 4: <ty...
DATA_BYTES	Value: {2: 2, 3: 4, 4: 2, 5: 4, 6: 4, 7: 8, 8: 1, 9: None, 10: N...
__package__	Value: 'fabio'

17.2 Class *dm3image*

object └

fabio.fabioimage.fabioimage └

fabio.dm3image.dm3image

Read and try to write the dm3 data format

17.2.1 Methods

__init__(*self*, **args*, ***kwargs*)

Set up initial values

Overrides: object.__init__ extit(inherited documentation)


```
read(self, fname, frame=None)
```

To be overridden - fill in *self.header* and *self.data*

Overrides: *fabio.fabioimage.fabioimage.read* *exitit*(inherited documentation)

```
readbytes(self, bytes_to_read, format, swap=True)
```

```
read_tag_group(self)
```

```
read_tag_entry(self)
```

```
read_tag_type(self)
```

```
read_data(self)
```

Inherited from *fabio.fabioimage.fabioimage* (Section 19.3)

add(), *checkData*(), *checkHeader*(), *convert*(), *getclassname*(), *getframe*(), *getheader*(), *getmax*(), *getmean*(), *getmin*(), *getstddev*(), *integrate_area*(), *load*(), *make_slice*(), *next*(), *previous*(), *readROI*(), *readheader*(), *rebin*(), *resetvals*(), *save*(), *toPIL16*(), *update_header*(), *write*()

Inherited from object

__delattr__(), *__format__*(), *__getattr__*(), *__hash__*(), *__new__*(), *__reduce__*(), *__reduce_ex__*(), *__repr__*(), *__setattr__*(), *__sizeof__*(), *__str__*(), *__subclasshook__*()

17.2.2 Properties

Name	Description
<i>Inherited from <i>fabio.fabioimage.fabioimage</i> (Section 19.3)</i>	
<i>classname</i>	
<i>Inherited from object</i>	
<i>__class__</i>	

18 Module *fabio.edfimage*

License: GPLv2+

Authors: Henning O. Sorensen & Erik Knudsen

Center for Fundamental Research: Metal Structures in Four Dimensions

Risoe National Laboratory

Frederiksborgvej 399

DK-4000 Roskilde

email:erik.knudsen@risoe.dk

+ Jon Wright, ESRF

2011-02-11: Mostly rewritten by Jérôme Kieffer (Jerome.Kieffer@esrf.eu)

European Synchrotron Radiation Facility

Grenoble (France)

2012-08-20: laisy read of data in EDF

18.1 Variables

Name	Description
logger	Value: <code>logging.getLogger("edfimage")</code>
BLOCKSIZE	Value: 512
DATA_TYPES	Value: {'Double': <type 'numpy.float64'>, 'DoubleIEEE128': <type...
NUMPY_EDF_DTYPE	Value: {'float128': 'QuadrupleValue', 'float32': 'FloatValue', '...
MINIMUM_KEYS	Value: ['HEADERID', 'IMAGE', 'BYTEORDER', 'DATATYPE', 'DIM_1', '...
DEFAULT_VALUES	Value: {}
__package__	Value: 'fabio'

18.2 Class Frame

object └─
 fabio.edfimage.Frame

A class representing a single frame in an EDF file

18.2.1 Methods

`__init__(self, data=None, header=None, header_keys=None, number=None)`

`x.__init__(...)` initializes `x`; see `x.__class__.__doc__` for signature

Overrides: `object.__init__` `extit`(inherited documentation)

`parseheader(self, block)`

Parse the header in some EDF format from an already open file

Parameters

`block`: string representing the header block
(type=string, should be full ascii)

Return Value

size of the binary blob

`swap_needed(self)`

Decide if we need to byteswap

`getData(self)`

Unpack a binary blob according to the specification given in the header

Return Value

dataset as `numpy.ndarray`

`setData(self, npa=None)`

Setter for data in edf frame

`getByteCode(self)`

`setByteCode(self, _iVal)`

```
getEdfBlock(self, force_type=None, fit2dMode=False)
```

Parameters

force_type: type of the dataset to be enforced like "float64" or "uint16"
(type=string or numpy.dtype)

fit2dMode: enforce compatibility with fit2d and starts counting number of images at 1
(type=boolean)

Return Value

ascii header block
(type=python string with the concatenation of the ascii header and the binary data block)

Inherited from object

```
--delattr--(), --format--(), --getattrattribute--(), --hash--(), --new--(), --reduce--(), --reduce_ex--(),  
--repr--(), --setattr--(), --sizeof--(), --str--(), --subclasshook--()
```

18.2.2 Properties

Name	Description
data	Unpack a binary blob according to the specification given in the header
bytecode	
<i>Inherited from object</i>	
__class__	

18.3 Class edfimage

```
object └─
fabio.fabioimage.fabioimage └─
                                fabio.edfimage.edfimage
```

Read and try to write the ESRF edf data format

18.3.1 Methods

`__init__(self, data=None, header=None, header_keys=None, frames=None)`

Set up initial values

Overrides: `object.__init__` `exitit`(inherited documentation)

`checkHeader(header=None)`

Empty for `fabioimage` but may be populated by others classes

Overrides: `fabio.fabioimage.fabioimage.checkHeader`

`read(self, fname, frame=None)`

Read in header into `self.header` and
the data into `self.data`

Overrides: `fabio.fabioimage.fabioimage.read`

`swap_needed(self)`

Decide if we need to byteswap

`unpack(self)`

Unpack a binary blob according to the specification given in the header and return the dataset

Return Value

dataset as `numpy.ndarray`

`getframe(self, num)`

returns the file numbered 'num' in the series as a `fabioimage`

Overrides: `fabio.fabioimage.fabioimage.getframe`

`previous(self)`

returns the previous file in the series as a `fabioimage`

Overrides: `fabio.fabioimage.fabioimage.previous`

next(*self*)

 returns the next file in the series as a *fabioimage*

 Overrides: *fabio.fabioimage.fabioimage.next*

write(*self*, *fname*, *force_type=None*, *fit2dMode=False*)

 Try to write a file check we can write zipped also mimics that *fabian* was writing *uint16* (we sometimes want floats)

Parameters

force_type: can be *numpy.uint16* or simply "float"

Return Value

None

 Overrides: *fabio.fabioimage.fabioimage.write*

appendFrame(*self*, *frame=None*, *data=None*, *header=None*)

 Method used add a frame to an EDF file

Parameters

frame: frame to append to edf image

(*type=instance of Frame*)

Return Value

None

deleteFrame(*self*, *frameNb=None*)

 Method used to remove a frame from an EDF image. by default the last one is removed.

Parameters

frameNb: frame number to remove, by default the last.

(*type=integer*)

Return Value

None

fastReadData(*self*, *filename=None*)

 This is a special method that will read and return the data from another file ... The aim is performances, ... but only supports uncompressed files.

Return Value

data from another file using positions from current *edfimage*

fastReadROI(*self*, *filename*, *coords*=None)

Method reading Region of Interest of another file based on metadata available in current edfimage. The aim is performances, ... but only supports uncompressed files.

Return Value

ROI-data from another file using positions from current edfimage
(*type=numpy 2darray*)

getNbFrames(*self*)

Getter for number of frames

setNbFrames(*self*, *val*)

Setter for number of frames ... should do nothing. Here just to avoid bugs

getHeader(*self*)

Getter for the headers. used by the property header,

setHeader(*self*, *_dictHeader*)

Enforces the propagation of the header to the list of frames

delHeader(*self*)

Deleter for edf header

getHeaderKeys(*self*)

Getter for edf header_keys

setHeaderKeys(*self*, *_listtHeader*)

Enforces the propagation of the header_keys to the list of frames

Parameters

_listtHeader: list of the (ordered) keys in the header
(*type=python list*)

delHeaderKeys(*self*)

Deleter for edf header_keys

getData(self)

getter for edf Data

Return Value

data for current frame

*(type=numpy.ndarray)***setData(self, _data)**

Enforces the propagation of the data to the list of frames

Parameters**_data:** numpy array representing data**delData(self)**

deleter for edf Data

getCapsHeader(self)

getter for edf headers keys in upper case

Return Value

data for current frame

*(type=dict)***setCapsHeader(self, _data)**

Enforces the propagation of the header keys to the list of frames

Parameters**_data:** numpy array representing data**delCapsHeader(self)**

deleter for edf capsHeader

getDim1(self)**setDim1(self, _iVal)****getDim2(self)****setDim2(self, _iVal)****getDims(self)**

<code>getByteCode(self)</code>

<code>setByteCode(self, _iVal)</code>

<code>getBpp(self)</code>

<code>setBpp(self, _iVal)</code>

Inherited from fabio.fabioimage.fabioimage (Section 19.3)

add(), checkData(), convert(), getclassname(), getheader(), getmax(), getmean(),
getmin(), getstddev(), integrate_area(), load(), make_slice(), readROI(), readheader(),
rebin(), resetvals(), save(), toPIL16(), update_header()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(),
__repr__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()

18.3.2 Properties

Name	Description
nframes	Getter for number of frames
header	property: header of EDF file
header_keys	property: header_keys of EDF file
data	property: data of EDF file
capsHeader	property: capsHeader of EDF file, i.e. the keys of the header in UPPER case.
dim1	
dim2	
dims	
bytecode	
bpp	
<i>Inherited from fabio.fabioimage.fabioimage (Section 19.3)</i>	
classname	
<i>Inherited from object</i>	
__class__	

19 Module *fabio.fabioimage*

Authors: Henning O. Sorensen & Erik Knudsen
 Center for Fundamental Research: Metal Structures in Four Dimensions
 Risoe National Laboratory
 Frederiksborgvej 399
 DK-4000 Roskilde
 email:erik.knudsen@risoe.dk

and Jon Wright, Jerome Kieffer: ESRF

19.1 Functions

test()
check some basic fabioimage functionality

19.2 Variables

Name	Description
logger	Value: <code>logging.getLogger("fabioimage")</code>
<code>--package--</code>	Value: <code>'fabio'</code>

19.3 Class *fabioimage*

object —
fabio.fabioimage.fabioimage

Known Subclasses: *fabio.fit2dmaskimage.fit2dmaskimage*, *fabio.tifimage.tifimage*, *fabio.kcdimage.kcdimage*, *fabio.bruckerimage.bruckerimage*, *fabio.cbimage.cbimage*, *fabio.edfimage.edfimage*, *fabio.GEimage.GEimage*, *fabio.xsimage.xsimage*, *fabio.binaryimage.binaryimage*, *fabio.OXDimage.OXDimage*, *fabio.mar345image.mar345image*, *fabio.dm3image.dm3image*, *fabio.adscimage.adscimage*, *fabio.GEimage_old.GEimage*, *fabio.pnmimage.pnmimage*, *fabio.fit2dspearsheetimage.fit2dspearsheetimage*, *fabio.HiPiCimage.HiPiCimage*

A common object for images in fable Contains a numpy array (`.data`) and dict of meta data (`.header`)

19.3.1 Methods

`__init__(self, data=None, header=None)`

Set up initial values

Overrides: `object.__init__`

`checkHeader(header=None)`

Empty for *fabioimage* but may be populated by others classes

`checkData(data=None)`

Empty for *fabioimage* but may be populated by others classes, especially for format accepting only integers

`getclassname(self)`

Retrieves the name of the class

Return Value

the name of the class

`getframe(self, num)`

returns the file numbered 'num' in the series as a *fabioimage*

`previous(self)`

returns the previous file in the series as a *fabioimage*

`next(self)`

returns the next file in the series as a *fabioimage*

`toPIL16(self, filename=None)`

Convert to Python Imaging Library 16 bit greyscale image

FIXME - this should be handled by the libraries now

`getheader(self)`

returns `self.header`

`getmax(self)`

Find max value in `self.data`, caching for the future

getmin(*self*)

Find min value in self.data, caching for the future

make_slice(*self*, *coords*)

Convert a len(4) set of coords into a len(2) tuple (pair) of slice objects the latter are immutable, meaning the roi can be cached

integrate_area(*self*, *coords*)

Sums up a region of interest if len(coords) == 4 -> convert coords to slices if len(coords) == 2 -> use as slices floor -> ? removed as unused in the function.

getmean(*self*)

return the mean

getstddev(*self*)

return the standard deviation

add(*self*, *other*)

Add another Image - warning, does not clip to 16 bit images by default

resetvals(*self*)

Reset cache - call on changing data

rebin(*self*, *x_rebin_fact*, *y_rebin_fact*, *keep_I=True*)

Rebin the data and adjust dims

Parameters**x_rebin_fact**: x binning factor*(type=int)***y_rebin_fact**: y binning factor*(type=int)***keep_I**: shall the signal increase ?*(type=boolean)***write**(*self*, *fname*)

To be overwritten - write the file

save (<i>self</i> , <i>fname</i>)
--

wrapper for write

readheader (<i>self</i> , <i>filename</i>)

Call the <code>_readheader</code> function...

update_header (<i>self</i> , **kws)

update the header entries by default pass in a dict of key, values.

read (<i>self</i> , <i>filename</i> , <i>frame</i> =None)

To be overridden - fill in <code>self.header</code> and <code>self.data</code>
--

load (<i>self</i> , * <i>arg</i> , **karg)
--

Wrapper for read

readROI (<i>self</i> , <i>filename</i> , <i>frame</i> =None, <i>coords</i> =None)

Method reading Region of Interest. This implementation is the trivial one, just doing read and crop

convert (<i>self</i> , <i>dest</i>)
--

Convert a <i>fabioimage</i> object into another <i>fabioimage</i> object (with possible conversions)
--

Parameters

dest : destination type "EDF", "edfimage" or the class itself
--

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

19.3.2 Properties

Name	Description
<code>classname</code>	Retrieves the name of the class
<i>Inherited from object</i>	
<code>__class__</code>	

20 Module *fabio.fabioutils*

General purpose utilities functions for *fabio*

20.1 Functions

getnum(*name*)

try to figure out a file number # guess it starts at the back

numstem(*name*)

cant see how to do without reversing strings Match 1 or more digits going backwards from the end of the string

deconstruct_filename(*filename*)

Break up a filename to get image type and number

construct_filename(*filename*, *frame*)

Try to construct the filename for a given frame

next_filename(*name*, *padding*=True)

increment number

previous_filename(*name*, *padding*=True)

decrement number

jump_filename(*name*, *num*, *padding*=True)

jump to number

extract_filename(*name*)

extract file number

isAscii(*name*, *listExcluded*=None)

Parameters

name: string to check
listExcluded: list of char or string excluded.

Return Value

True or False whether name is pure ascii or not

toAscii(*name*, *excluded*=None)

Parameters

name: string to check
excluded: tuple of char or string excluded (not list: they are mutable).

Return Value

the name with all non valid char removed

nice_int(*s*)

Workaround that int('1.0') raises an exception

Parameters

s: string to be converted to integer

20.2 Variables

Name	Description
logger	Value: logging.getLogger("fabioutils")
FILETYPES	Value: {'cbf': ['cbf'], 'cbf.bz2': ['cbf'], 'cbf.gz': ['cbf'], ...}
COMPRESSORS	Value: {'bz2': 'bzip2 -dc ', 'gz': 'gzip -dc '}
dictAscii	Value: {None: [' ', '!', '"', '#', '\$', '%', '&', '\\', '(', ')'] ...}
lines	Value: 'bzip2, a block-sorting file compressor. Version 1.0.5, ...
__package__	Value: 'fabio'
i	Value: 126
key	Value: 'cbf'

20.3 Class `filename_object`

The 'meaning' of a filename

20.3.1 Methods

```
__init__(self, stem, num=None, directory=None, format=None,
extension=None, postnum=None, digits=4)
```

```
str(self)
```

Return a string representation

```
tostring(self)
```

convert yourself to a string

20.4 Class `StringIO`

StringIO.StringIO —
fabio.fabioutils.StringIO

just an interface providing the name and mode property to a StringIO

BugFix for MacOSX mainly

20.4.1 Methods

```
__init__(self, data, fname=None, mode='r')
```

Overrides: StringIO.StringIO.__init__

```
getSize(self)
```

```
setSize(self, size)
```

Inherited from StringIO.StringIO

`_iter_()`, `close()`, `flush()`, `getvalue()`, `isatty()`, `next()`, `read()`, `readline()`, `readlines()`,
`seek()`, `tell()`, `truncate()`, `write()`, `writelines()`

20.4.2 Properties

Name	Description
size	

20.5 Class File



Known Subclasses: `fabio.fabioutils.UnknownCompressedFile`

wrapper for "file" with locking

20.5.1 Methods

`__init__(name, mode=..., buffering=...)`

Open a file. The mode can be 'r', 'w' or 'a' for reading (default), writing or appending. The file will be created if it doesn't exist when opened for writing or appending; it will be truncated when opened for writing. Add a 'b' to the mode for binary files. Add a '+' to the mode to allow simultaneous reading and writing. If the buffering argument is given, 0 means unbuffered, 1 means line buffered, and larger numbers specify the buffer size. The preferred way to open a file is with the builtin `open()` function. Add a 'U' to mode to open the file for input with universal newline support. Any line ending in the input file will be seen as a ' ', in Python. Also, a file so opened gains the attribute 'newlines'; the value for this attribute is one of None (no newline read yet), ' ', or a tuple containing all the newline types seen. 'U' cannot be combined with 'w' or '+' mode.

Return Value

file object

Overrides: `object.__init__`

`getSize(self)`

`setSize(self, size)`

Inherited from file

`__delattr__()`, `__enter__()`, `__exit__()`, `__getattr__()`, `__iter__()`, `__new__()`, `__repr__()`, `__setattr__()`, `close()`, `fileno()`, `flush()`, `isatty()`, `next()`, `read()`, `readinto()`, `readline()`, `readlines()`, `seek()`, `tell()`, `truncate()`, `write()`, `writelines()`, `xreadlines()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce__()`, `__reduce_ex__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

20.5.2 Properties

Name	Description
<code>size</code>	
<i>Inherited from file</i>	
<code>closed, encoding, errors, mode, name, newlines, softspace</code>	
<i>Inherited from object</i>	
<code>--class--</code>	

20.6 Class `UnknownCompressedFile`



20.6.1 Methods

```

__init__(self, name, mode='rb', buffering=0)

    Open a file. The mode can be 'r', 'w' or 'a' for reading (default),
    writing or appending. The file will be created if it doesn't exist
    when opened for writing or appending; it will be truncated when
    opened for writing. Add a 'b' to the mode for binary files.
    Add a '+' to the mode to allow simultaneous reading and writing.
    If the buffering argument is given, 0 means unbuffered, 1 means line
    buffered, and larger numbers specify the buffer size. The preferred way
    to open a file is with the builtin open() function.
    Add a 'U' to mode to open the file for input with universal newline
    support. Any line ending in the input file will be seen as a '
    ,
    in Python. Also, a file so opened gains the attribute 'newlines';
    the value for this attribute is one of None (no newline read yet),
    ,
    , ,
    , ,
    ' or a tuple containing all the newline types seen.

    'U' cannot be combined with 'w' or '+' mode.

Return Value
    file object

    Overrides: object.__init__ exitit(inherited documentation)

```

*Inherited from **fabio.fabioutils.File**(Section 20.5)*

getSize(), setSize()

*Inherited from **file***

__delattr__(), __enter__(), __exit__(), __getattr__(), __iter__(), __new__(), __repr__(),
 __setattr__(), close(), fileno(), flush(), isatty(), next(), read(), readinto(), readline(),
 readlines(), seek(), tell(), truncate(), write(), writelines(), xreadlines()

*Inherited from **object***

__format__(), __hash__(), __reduce__(), __reduce_ex__(), __sizeof__(), __str__(), __subclasshook__()

20.6.2 Properties

Name	Description
<i>Inherited from <code>fabio.fabioutils.File</code> (Section 20.5)</i>	
<code>size</code>	
<i>Inherited from <code>file</code></i>	
<code>closed</code> , <code>encoding</code> , <code>errors</code> , <code>mode</code> , <code>name</code> , <code>newlines</code> , <code>softspace</code>	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

20.7 Class GzipFile

`gzip.GzipFile` —
`fabio.fabioutils.GzipFile`

Just a wrapper for `gzip.GzipFile` providing the correct seek capabilities for python 2.5

20.7.1 Methods

<code>__init__(self, filename=None, mode=None, compresslevel=9, fileobj=None)</code>
<p>Wrapper with locking for constructor for the <code>GzipFile</code> class.</p> <p>At least one of <code>fileobj</code> and <code>filename</code> must be given a non-trivial value.</p> <p>The new class instance is based on <code>fileobj</code>, which can be a regular file, a <code>StringIO</code> object, or any other object which simulates a file. It defaults to <code>None</code>, in which case <code>filename</code> is opened to provide a file object.</p> <p>When <code>fileobj</code> is not <code>None</code>, the <code>filename</code> argument is only used to be included in the gzip file header, which may includes the original filename of the uncompressed file. It defaults to the filename of <code>fileobj</code>, if discernible; otherwise, it defaults to the empty string, and in this case the original filename is not included in the header.</p> <p>The <code>mode</code> argument can be any of <code>'r'</code>, <code>'rb'</code>, <code>'a'</code>, <code>'ab'</code>, <code>'w'</code>, or <code>'wb'</code>, depending on whether the file will be read or written. The default is the mode of <code>fileobj</code> if discernible; otherwise, the default is <code>'rb'</code>. Be aware that only the <code>'rb'</code>, <code>'ab'</code>, and <code>'wb'</code> values should be used for cross-platform portability.</p> <p>The <code>compresslevel</code> argument is an integer from 1 to 9 controlling the level of compression; 1 is fastest and produces the least compression, and 9 is slowest and produces the most compression. The default is 9.</p> <p>Overrides: <code>gzip.GzipFile.__init__</code></p>

getSize (<i>self</i>)

setSize (<i>self</i> , <i>value</i>)

seek (<i>self</i> , <i>offset</i> , <i>whence</i> =0)

Move to new file position.

Argument offset is a byte count. Optional argument whence defaults to 0 (offset from start of file, offset should be ≥ 0); other values are 1 (move relative to current position, positive or negative), and 2 (move relative to end of file, usually negative, although many platforms allow seeking beyond the end of a file). If the file is opened in text mode, only offsets returned by tell() are legal. Use of other offsets causes undefined behavior.

This is a wrapper for seek to ensure compatibility with old python 2.5

Overrides: gzip.GzipFile.seek

Inherited from gzip.GzipFile

`__del__()`, `__iter__()`, `__repr__()`, `close()`, `fileno()`, `flush()`, `isatty()`, `next()`, `read()`, `readline()`, `readlines()`, `rewind()`, `tell()`, `write()`, `writelines()`

20.7.2 Properties

Name	Description
size	
closed	
<i>Inherited from gzip.GzipFile</i>	
filename	

20.7.3 Class Variables

Name	Description
<i>Inherited from gzip.GzipFile</i>	
max_read_chunk, myfileobj	

20.8 Class BZ2File



Wrapper with lock

20.8.1 Methods

`__init__(name, mode='r', buffering=0, compresslevel=9)`

Open a bz2 file. The mode can be 'r' or 'w', for reading (default) or writing. When opened for writing, the file will be created if it doesn't exist, and truncated otherwise. If the buffering argument is given, 0 means unbuffered, and larger numbers specify the buffer size. If compresslevel is given, must be a number between 1 and 9.

Add a 'U' to mode to open the file for input with universal newline support. Any line ending in the input file will be seen as a '

' in

Python. Also, a file so opened gains the attribute 'newlines'; the value for this attribute is one of None (no newline read yet), '

', ,
, ,
, ,

,

' or a tuple containing all the newline types seen. Universal newlines are available only when reading.

Return Value

file object

Overrides: `object.__init__`

`getSize(self)`

`setSize(self, value)`

Inherited from bz2.BZ2File

`__delattr__()`, `__getattr__()`, `__iter__()`, `__new__()`, `__setattr__()`, `close()`, `next()`, `read()`, `readline()`, `readlines()`, `seek()`, `tell()`, `write()`, `writelines()`, `xreadlines()`

Inherited from object

`__format__()`, `__hash__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__sizeof__()`, `__str__()`,
`__subclasshook__()`

20.8.2 Properties

Name	Description
size	
<i>Inherited from bz2.BZ2File</i>	
closed, mode, name, newlines, softspace	
<i>Inherited from object</i>	
__class__	

21 Module *fabio.file_series*

Authors: Henning O. Sorensen & Erik Knudsen
Center for Fundamental Research: Metal Structures in Four Dimensions
Risoe National Laboratory
Frederiksborgvej 399
DK-4000 Roskilde
email:erik.knudsen@risoe.dk

+ Jon Wright, ESRF

21.1 Functions

<code>new_file_series0(<i>first_object</i>, <i>first</i>=None, <i>last</i>=None, <i>step</i>=1)</code>
--

Created from a fabio image first and last are file numbers
--

```
new_file_series(first_object, nimages=0, step=1, traceback=False)
```

A generator function that creates a file series starting from a *fabioimage*. Iterates through all images in a file (if more than 1), then proceeds to the next file as determined by *fabio.next_filename*.

first_object: the starting *fabioimage*, which will be the first one yielded in the sequence

nimages: the maximum number of images to consider

step: step size, will yield the first and every *step*'th image until *nimages* is reached. (e.g. *nimages* = 5, *step* = 2 will yield 3 images (0, 2, 4))

traceback: if True causes it to print a traceback in the event of an exception (missing image, etc.). Otherwise the calling routine can handle the exception as it chooses

yields: the next *fabioimage* in the series.

In the event there is an exception, it yields the *sys.exec_info* for the exception instead. *sys.exec_info* is a tuple:

```
( exceptionType, exceptionValue, exceptionTraceback )
```

from which all the exception information can be obtained.

Suggested usage:

```
for obj in new_file_series( ... ):
    if not isinstance( obj, fabio.fabioimage.fabioimage ):
        # deal with errors like missing images, non readable files, etc
        # e.g.
        traceback.print_exception(obj[0], obj[1], obj[2])
```

21.2 Variables

Name	Description
<i>logger</i>	Value: <i>logging.getLogger("fileseries")</i>
<i>--package--</i>	Value: 'fabio'

21.3 Class *file_series*



Known Subclasses: *fabio.file_series.numbered_file_series*

represents a series of files to iterate
 has an idea of a current position to do next and prev

You also get from the list python superclass:

```
append
count
extend
insert
pop
remove
reverse
sort
```

21.3.1 Methods

`__init__(self, list_of_strings)`

arg should be a list of strings which are filenames

Return Value

new empty list

Overrides: `object.__init__`

`first(self)`

first image in series

`last(self)`

last in series

`previous(self)`

prev in a sequence

`current(self)`

current position in a sequence

`next(self)`

next in a sequence

jump(*self*, *num*)

goto a position in sequence

len(*self*)

number of files

first_image(*self*)

first image in a sequence

last_image(*self*)

last image in a sequence

next_image(*self*)

Return the next image

previous_image(*self*)

Return the previous image

jump_image(*self*, *num*)

jump to and read image

current_image(*self*)

current image in sequence

first_object(*self*)

first image in a sequence

last_object(*self*)

last image in a sequence

next_object(*self*)

Return the next image

previous_object(*self*)

Return the previous image

jump_object (<i>self</i> , <i>num</i>)

jump to and read image

current_object (<i>self</i>)

current image in sequence

Inherited from list

```
__add__(), __contains__(), __delitem__(), __delslice__(), __eq__(), __ge__(), __getattr__(),
__getitem__(), __getslice__(), __gt__(), __iadd__(), __imul__(), __iter__(), __le__(), __len__(),
__lt__(), __mul__(), __ne__(), __new__(), __repr__(), __reversed__(), __rmul__(), __setitem__(),
__setslice__(), __sizeof__(), append(), count(), extend(), index(), insert(), pop(), re-
move(), reverse(), sort()
```

Inherited from object

```
__delattr__(), __format__(), __reduce__(), __reduce_ex__(), __setattr__(), __str__(), __subclasshook__()
```

21.3.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

21.3.3 Class Variables

Name	Description
<i>Inherited from list</i>	
<code>__hash__</code>	

21.4 Class `numbered_file_series`

```

object ┌
      │
      └─ list ┌
            │
            └─ fabio.file_series.file_series ┌
                                                  └─ fabio.file_series.numbered_file_series
```

```
mydata0001.edf = "mydata" + 0001 + ".edf" mydata0002.edf = "mydata" + 0002 + ".edf"
mydata0003.edf = "mydata" + 0003 + ".edf"
```

21.4.1 Methods

```
__init__(self, stem, first, last, extension, digits=4, padding='Y', step=1)
```

stem - first part of the name
step - in case of every nth file
padding - possibility for specifying that numbers are not padded
 with zeroes up to digits

Return Value
new empty list

Overrides: `object.__init__`

Inherited from `fabio.file_series.file_series` (Section 21.3)

`current()`, `current_image()`, `current_object()`, `first()`, `first_image()`, `first_object()`,
`jump()`, `jump_image()`, `jump_object()`, `last()`, `last_image()`, `last_object()`, `len()`, `next()`,
`next_image()`, `next_object()`, `previous()`, `previous_image()`, `previous_object()`

Inherited from `list`

`__add__()`, `__contains__()`, `__delitem__()`, `__delslice__()`, `__eq__()`, `__ge__()`, `__getattr__()`,
`__getitem__()`, `__getslice__()`, `__gt__()`, `__iadd__()`, `__imul__()`, `__iter__()`, `__le__()`, `__len__()`,
`__lt__()`, `__mul__()`, `__ne__()`, `__new__()`, `__repr__()`, `__reversed__()`, `__rmul__()`, `__setitem__()`,
`__setslice__()`, `__sizeof__()`, `append()`, `count()`, `extend()`, `index()`, `insert()`, `pop()`, `re-`
`move()`, `reverse()`, `sort()`

Inherited from `object`

`__delattr__()`, `__format__()`, `__reduce__()`, `__reduce_ex__()`, `__setattr__()`, `__str__()`, `__subclasshook__()`

21.4.2 Properties

Name	Description
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

21.4.3 Class Variables

Name	Description
<i>Inherited from <code>list</code></i>	
<code>__hash__</code>	

21.5 Class `filename_series`

Much like the others, but created from a string filename

21.5.1 Methods

<code>__init__</code> (<i>self</i> , <i>filename</i>)
--

create from a filename (String)

<code>next</code> (<i>self</i>)
--

increment number

<code>previous</code> (<i>self</i>)
--

decrement number

<code>current</code> (<i>self</i>)

return current filename string

<code>jump</code> (<i>self</i> , <i>num</i>)

jump to a specific number

<code>next_image</code> (<i>self</i>)
--

returns the next image as a <code>fabioimage</code>

<code>prev_image</code> (<i>self</i>)
--

returns the previos image as a <code>fabioimage</code>
--

<code>current_image</code> (<i>self</i>)

returns the current image as a <code>fabioimage</code>
--

<code>jump_image</code> (<i>self</i> , <i>num</i>)

returns the image number as a <code>fabioimage</code>

<code>next_object</code> (<i>self</i>)

returns the next filename as a <code>fabio.filename_object</code>

previous_object(*self*)returns the previous filename as a `fabio.filename_object`**current_object**(*self*)returns the current filename as a `fabio.filename_object`**jump_object**(*self*, *num*)returns the filename num as a `fabio.filename_object`

22 Module *fabio.fit2dmaskimage*

Author: Andy Hammersley, ESRF Translation into python/fabio: Jon Wright, ESRF

22.1 Variables

Name	Description
<code>--package--</code>	Value: 'fabio'

22.2 Class *fit2dmaskimage*



Read and try to write Andy Hammersley's mask format

22.2.1 Methods

read(*self*, *fname*, *frame*=None)

Read in header into `self.header` and
the data into `self.data`

Overrides: `fabio.fabioimage.fabioimage.read`

write(*self*, *fname*)

Try to write a file check we can write zipped also mimics that fabian was
writing uint16 (we sometimes want floats)

Overrides: `fabio.fabioimage.fabioimage.write`

checkData(*data=None*)

Empty for fabioimage but may be populated by others classes, especially for format accepting only integers

Overrides: `fabio.fabioimage.fabioimage.checkData` extit(inherited documentation)

Inherited from `fabio.fabioimage.fabioimage` (Section 19.3)

`__init__()`, `add()`, `checkHeader()`, `convert()`, `getclassname()`, `getframe()`, `getheader()`, `getmax()`, `getmean()`, `getmin()`, `getstddev()`, `integrate_area()`, `load()`, `make_slice()`, `next()`, `previous()`, `readROI()`, `readheader()`, `rebin()`, `resetvals()`, `save()`, `toPIL16()`, `update_header()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

22.2.2 Properties

Name	Description
<i>Inherited from <code>fabio.fabioimage.fabioimage</code> (Section 19.3)</i>	
<code>classname</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

23 Module *fabio.fit2dspreadsheetimage*

Read the fit2d ascii image output
+ Jon Wright, ESRF

23.1 Variables

Name	Description
<code>--package--</code>	Value: 'fabio'

23.2 Class *fit2dspreadsheetimage*

object └─
fabio.fabioimage.fabioimage └─
fabio.fit2dspreadsheetimage.fit2dspreadsheetimage

Read a fit2d ascii format

23.2.1 Methods

<code>read(self, fname, frame=None)</code> Read in header into <code>self.header</code> and the data into <code>self.data</code> Overrides: <code>fabio.fabioimage.fabioimage.read</code>

Inherited from `fabio.fabioimage.fabioimage` (Section 19.3)

`__init__()`, `add()`, `checkData()`, `checkHeader()`, `convert()`, `getclassname()`, `getframe()`,
`getheader()`, `getmax()`, `getmean()`, `getmin()`, `getstddev()`, `integrate_area()`, `load()`,
`make_slice()`, `next()`, `previous()`, `readROI()`, `readheader()`, `rebin()`, `resetvals()`, `save()`,
`toPIL16()`, `update_header()`, `write()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`,
`__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

23.2.2 Properties

Name	Description
<i>Inherited from <code>fabio.fabioimage.fabioimage</code> (Section 19.3)</i>	
<code>classname</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

24 Module *fabio.kcdimage*


Authors: Jerome Kieffer, ESRF
 email:jerome.kieffer@esrf.fr

kcd images are 2D images written by the old KappaCCD diffractometer built by Nonius in t
 Based on the edfimage.py parser.

24.1 Variables

Name	Description
logger	Value: logging.getLogger("kcdimage")
DATA_TYPES	Value: {'u16': <type 'numpy.uint16'>}
MINIMUM_KEYS	Value: ['ByteOrder', 'Data type', 'X dimension', 'Y dimension', ...]
DEFAULT_VALUES	Value: {'Data type': 'u16'}
__package__	Value: 'fabio'

24.2 Class *kcdimage*



Read the Nonius kcd data format

24.2.1 Methods

read (<i>self</i> , <i>fname</i> , <i>frame</i> =None) Read in header into self.header and the data into self.data Overrides: fabio.fabioimage.fabioimage.read

checkData(*data=None*)

Empty for *fabioimage* but may be populated by others classes, especially for format accepting only integers

Overrides: *fabio.fabioimage.fabioimage.checkData* extit(inherited documentation)

Inherited from *fabio.fabioimage.fabioimage* (Section 19.3)

__init__(), *add*(), *checkHeader*(), *convert*(), *getclassname*(), *getframe*(), *getheader*(), *getmax*(), *getmean*(), *getmin*(), *getstddev*(), *integrate_area*(), *load*(), *make_slice*(), *next*(), *previous*(), *readROI*(), *readheader*(), *rebin*(), *resetvals*(), *save*(), *toPIL16*(), *update_header*(), *write*()

Inherited from object

__delattr__(), *__format__*(), *__getattr__*(), *__hash__*(), *__new__*(), *__reduce__*(), *__reduce_ex__*(), *__repr__*(), *__setattr__*(), *__sizeof__*(), *__str__*(), *__subclasshook__*()

24.2.2 Properties

Name	Description
<i>Inherited from <i>fabio.fabioimage.fabioimage</i> (Section 19.3)</i>	
<i>classname</i>	
<i>Inherited from object</i>	
<i>__class__</i>	

25 Module *fabio.mar345_IO*

New Cython version of *mar345_io* for preparing the migration to Python3

Compressor & decompressor for "pack" algorithm by JPA, binding to CCP4 libraries

Warning: decompressor is just a cython porting of *mar345_io*, but in cython so (soon) pyth

Future: make those algorithm actually generate strings not go via files;
it will allow a broader use of the algorithm.

Authors: Jerome Kieffer, Gael Goret

Contact: jerome.kieffer@esrf.eu

Copyright: 2012, European Synchrotron Radiation Facility, Grenoble, France

License: LGPLv3+

25.1 Variables

Name	Description
<code>__package__</code>	Value: 'fabio'
<code>__test__</code>	Value: {}


26 Module *fabio.mar345image*

Authors: Henning O. Sorensen & Erik Knudsen
 Center for Fundamental Research: Metal Structures in Four Dimensions
 Risoe National Laboratory
 Frederiksborgvej 399
 DK-4000 Roskilde
 email:erik.knudsen@risoe.dk
 +
 Jon Wright, Jerome Kieffer, Gael Goret ESRF, France

26.1 Variables

Name	Description
<code>__doc__</code>	Value: ...
<code>logger</code>	Value: <code>logging.getLogger("mar345image")</code>
<code>__package__</code>	Value: 'fabio'

26.2 Class *mar345image*



26.2.1 Methods

`__init__(self, *args, **kwargs)`

Set up initial values

Overrides: `object.__init__` `exitit`(inherited documentation)

`read(self, fname, frame=None)`

Read a mar345 image

Overrides: `fabio.fabioimage.fabioimage.read`

write(*self*, *fname*)

Try to write mar345 file. This is still in beta version. It uses CCP4 (LGPL) PCK1 algo from JPA

Overrides: `fabio.fabioimage.fabioimage.write`

nb_overflow_pixels(*self*)

checkData(*data=None*)

Empty for fabioimage but may be populated by others classes, especially for format accepting only integers

Overrides: `fabio.fabioimage.fabioimage.checkData` `exitit`(inherited documentation)

Inherited from `fabio.fabioimage.fabioimage` (Section 19.3)

`add()`, `checkHeader()`, `convert()`, `getclassname()`, `getframe()`, `getheader()`, `getmax()`, `getmean()`, `getmin()`, `getstddev()`, `integrate_area()`, `load()`, `make_slice()`, `next()`, `previous()`, `readROI()`, `readheader()`, `rebin()`, `resetvals()`, `save()`, `toPIL16()`, `update_header()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

26.2.2 Properties

Name	Description
<i>Inherited from <code>fabio.fabioimage.fabioimage</code> (Section 19.3)</i>	
<code>classname</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

Name	Description
<code>--package--</code>	Value: 'fabio'

27.3 Class *marccdimage*



Read in data in mar ccd format, also MarMosaic images, including header info

27.3.1 Methods

*Inherited from **fabio.tifimage.tifimage** (Section 32.2)*

`--init--()`, `read()`, `write()`

*Inherited from **fabio.fabioimage.fabioimage** (Section 19.3)*

`add()`, `checkData()`, `checkHeader()`, `convert()`, `getclassname()`, `getframe()`, `getheader()`, `getmax()`, `getmean()`, `getmin()`, `getstddev()`, `integrate_area()`, `load()`, `make_slice()`, `next()`, `previous()`, `readROI()`, `readheader()`, `rebin()`, `resetvals()`, `save()`, `toPIL16()`, `update_header()`

*Inherited from **object***

`--delattr--()`, `--format--()`, `--getattr--()`, `--hash--()`, `--new--()`, `--reduce--()`, `--reduce_ex--()`, `--repr--()`, `--setattr--()`, `--sizeof--()`, `--str--()`, `--subclasshook--()`

27.3.2 Properties

Name	Description
<i>Inherited from fabio.fabioimage.fabioimage (Section 19.3)</i>	
<code>classname</code>	
<i>Inherited from object</i>	
<code>--class--</code>	

28 Module *fabio.openimage*

Authors: Henning O. Sorensen & Erik Knudsen
 Center for Fundamental Research: Metal Structures in Four Dimensions
 Risoe National Laboratory
 Frederiksborgvej 399
 DK-4000 Roskilde
 email:henning.sorensen@risoe.dk

mods for fabio by JPW

28.1 Functions

do_magic (<i>byts</i>)

Try to interpret the bytes starting the file as a magic number
--

openimage (<i>filename</i> , <i>frame=None</i>)
--

Try to open an image

openheader (<i>filename</i>)

return only the header

28.2 Variables

Name	Description
logger	Value: <code>logging.getLogger("openimage")</code>
MAGIC_NUMBERS	Value: <code>[('FORMAT : 86', 'bruker'), ('MM\x00*', 'tif'), ('...</code>
<code>__package__</code>	Value: <code>'fabio'</code>

29 Module *fabio.pilatusimage*

Authors: Henning O. Sorensen & Erik Knudsen
 Center for Fundamental Research: Metal Structures in Four Dimensions
 Risoe National Laboratory
 Frederiksborgvej 399
 DK-4000 Roskilde
 email:henning.sorensen@risoe.dk


+ (mods for fabio) Jon Wright, ESRF
 marccdimage can read MarCCD and MarMosaic images including header info.

JPW : Use a parser in case of typos (sorry?)

29.1 Variables

Name	Description
<code>--package--</code>	Value: 'fabio'

29.2 Class *pilatusimage*



Read in Pilatus format, also pilatus images, including header info

29.2.1 Methods

Inherited from `fabio.tifimage.tifimage` (Section 32.2)

`__init__()`, `read()`, `write()`

Inherited from `fabio.fabioimage.fabioimage` (Section 19.3)

add(), checkData(), checkHeader(), convert(), getclassname(), getframe(), getheader(), getmax(), getmean(), getmin(), getstddev(), integrate_area(), load(), make_slice(), next(), previous(), readROI(), readheader(), rebin(), resetvals(), save(), toPIL16(), update_header()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()

29.2.2 Properties

Name	Description
<i>Inherited from fabio.fabioimage.fabioimage (Section 19.3)</i>	
classname	
<i>Inherited from object</i>	
__class__	

30 Module *fabio.pnmimage*

Authors: Henning O. Sorensen & Erik Knudsen

Center for Fundamental Research: Metal Structures in Four Dimensions

Risoe National Laboratory

Frederiksborgvej 399


DK-4000 Roskilde

email:henning.sorensen@risoe.dk

30.1 Variables

Name	Description
logger	Value: <code>logging.getLogger("pnmimage")</code>
SUBFORMATS	Value: ['P1', 'P2', 'P3', 'P4', 'P5', 'P6', 'P7']
HEADERITEMS	Value: ['SUBFORMAT', 'DIMENSIONS', 'MAXVAL']
P7HEADERITEMS	Value: ['WIDTH', 'HEIGHT', 'DEPTH', 'MAXVAL', 'TUPLTYPE', 'ENDHDR']
<code>__package__</code>	Value: 'fabio'

30.2 Class *pnmimage*



30.2.1 Methods

```
__init__(self, *arg, **kwargs)
```

Set up initial values

Overrides: `object.__init__` extit(inherited documentation)

read(*self*, *fname*, *frame*=None)

try to read PNM images

Parameters

fname: name of the file

frame: not relevant here! PNM is always single framed

Overrides: *fabio.fabioimage.fabioimage.read*

P1dec(*buf*, *bytecode*)

P4dec(*buf*, *bytecode*)

P2dec(*buf*, *bytecode*)

P5dec(*buf*, *bytecode*)

P3dec(*buf*, *bytecode*)

P6dec(*buf*, *bytecode*)

P7dec(*buf*, *bytecode*)

write(*self*, *filename*)

To be overwritten - write the file

Overrides: *fabio.fabioimage.fabioimage.write* *exitit*(inherited documentation)

checkData(*data*=None)

Empty for *fabioimage* but may be populated by others classes, especially for format accepting only integers

Overrides: *fabio.fabioimage.fabioimage.checkData* *exitit*(inherited documentation)

Inherited from *fabio.fabioimage.fabioimage* (Section 19.3)

add(), *checkHeader*(), *convert*(), *getclassname*(), *getframe*(), *getheader*(), *getmax*(), *getmean*(), *getmin*(), *getstddev*(), *integrate_area*(), *load*(), *make_slice*(), *next*(), *previous*(), *readROI*(), *readheader*(), *rebin*(), *resetvals*(), *save*(), *toPIL16*(), *update_header*()

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`,
`__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

30.2.2 Properties

Name	Description
<i>Inherited from <code>fabio.fabioimage.fabioimage</code> (Section 19.3)</i>	
<code>classname</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

31 Module *fabio.readbytestream*

Reads a bytestream

Authors: Jon Wright Henning O. Sorensen & Erik Knudsen
 ESRF Risoe National Laboratory

31.1 Functions

```
readbytestream(fil, offset, x, y, nbytespp, datatype='int', signed='n',  

swap='n', typeout=<type 'numpy.uint16'>)
```

Reads in a bytestream from a file (which may be a string indicating a filename, or an already opened file (should be "rb")) offset is the position (in bytes) where the pixel data start *nbytespp* = number of bytes per pixel type can be int or float (4 bytes pp) or double (8 bytes pp) signed: normally signed data 'y', but 'n' to try to get back the right numbers when unsigned data are converted to signed (python once had no unsigned numeric types.) swap, normally do not bother, but 'y' to swap bytes typeout is the numpy type to output, normally uint16, but more if overflows occurred *x* and *y* are the pixel dimensions

TODO : Read in regions of interest

PLEASE LEAVE THE STRANGE INTERFACE ALONE - IT IS USEFUL FOR THE BRUKER FORMAT

31.2 Variables

Name	Description
logger	Value: logging.getLogger("readbytestream")
DATATYPES	Value: {('double', 'y', 4): <type 'numpy.float64'>, ('float', 'y...
--package--	Value: 'fabio'

32 Module *fabio.tifimage*

FabIO class for dealing with TIFF images.

In facts wraps TiffIO from Armando (available in PyMca) or falls back to PIL

Authors: Jérôme Kieffer (jerome.kieffer@esrf.fr)

Henning O. Sorensen & Erik Knudsen

Center for Fundamental Research: Metal Structures in Four Dimensions

Risoe National Laboratory

Frederiksborgvej 399

DK-4000 Roskilde

email:henning.sorensen@risoe.dk

License: GPLv3+

Date: 11/07/2011

Authors: Jérôme Kieffer, Henning O. Sorensen, Erik Knudsen


Copyright: ESRF, Grenoble & Risoe National Laboratory

License: GPLv3+

32.1 Variables

Name	Description
logger	Value: logging.getLogger("tifimage")
PIL_TO_NUMPY	Value: {'1': <type 'bool'>, 'F': <type 'numpy.float32'>, 'I': <t...
LITTLE_ENDIAN	Value: 1234
BIG_ENDIAN	Value: 3412
TYPES	Value: {0: 'invalid', 1: 'byte', 2: 'ascii', 3: 'short', 4: 'lon...
TYPESIZES	Value: {0: 0, 1: 1, 2: 1, 3: 2, 4: 4, 5: 8, 6: 1, 7: 1, 8: 2, 9:...
baseline_tiff_tags	Value: {256: 'ImageWidth', 257: 'ImageLength', 258: 'BitsPerSamp...
__package__	Value: 'fabio'

32.2 Class *tifimage*



Known Subclasses: *fabio.marccdimage.marccdimage*, *fabio.pilatusimage.pilatusimage*

Images in TIF format Wraps TiffIO

32.2.1 Methods

`__init__(self, *args, **kwargs)`

Tifimage constructor adds an nbits member attribute

Overrides: *object.__init__*

`read(self, fname, frame=None)`

Wrapper for TiffIO.

Overrides: *fabio.fabioimage.fabioimage.read*

`write(self, fname)`

Overrides the *fabioimage.write* method and provides a simple TIFF image writer.

Parameters

`fname`: name of the file to save the image to

Overrides: *fabio.fabioimage.fabioimage.write*

Inherited from *fabio.fabioimage.fabioimage* (Section 19.3)

add(), *checkData()*, *checkHeader()*, *convert()*, *getclassname()*, *getframe()*, *getheader()*, *getmax()*, *getmean()*, *getmin()*, *getstddev()*, *integrate_area()*, *load()*, *make_slice()*, *next()*, *previous()*, *readROI()*, *readheader()*, *rebin()*, *resetvals()*, *save()*, *toPIL16()*, *update_header()*

Inherited from *object*

__delattr__(), *__format__()*, *__getattr__()*, *__hash__()*, *__new__()*, *__reduce__()*, *__reduce_ex__()*, *__repr__()*, *__setattr__()*, *__sizeof__()*, *__str__()*, *__subclasshook__()*

32.2.2 Properties

Name	Description
<i>Inherited from <code>fabio.fabioimage.fabioimage</code> (Section 19.3)</i>	
<code>classname</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

32.3 Class `Tiff_header`**32.3.1 Methods**

```

__init__(self, string)

x.__init__(...) initializes x; see x.__class__.__doc__ for signature
Overrides: object.__init__ exitit(inherited documentation)

```

Inherited from object

```

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(),
__repr__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()

```

32.3.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

32.4 Class `Image_File_Directory`

32.4.1 Methods

```
__init__(self, instring=None, offset=-1)

x.__init__(...) initializes x; see x.__class__...__doc__ for signature
Overrides: object.__init__ extit(inherited documentation)
```

```
unpack(self, instring, offset=-1)
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(),
__repr__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()
```

32.4.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

32.5 Class *Image_File_Directory_entry*



32.5.1 Methods

```
__init__(self, tag=0, tag_type=0, count=0, offset=0)

x.__init__(...) initializes x; see x.__class__...__doc__ for signature
Overrides: object.__init__ extit(inherited documentation)
```

```
unpack(self, strInput)
```

```
extract_data(self, full_string)
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(),
__repr__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()
```

32.5.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>--class--</code>	

33 Module fabio.xsdimage

Authors: Jérôme Kieffer, ESRF
email:jerome.kieffer@esrf.fr

XSDimage are XML files containing numpy arrays

Author: Jérôme Kieffer

Contact: jerome.kieffer@esrf.eu


Copyright: European Synchrotron Radiation Facility, Grenoble, France

License: GPLv3+

33.1 Variables

Name	Description
logger	Value: logging.getLogger("xsdimage")
__package__	Value: 'fabio'

33.2 Class xsdimage



Read the XSDataImage XML File data format

33.2.1 Methods

__init__ (self, data=None, header=None, fname=None)
Constructor of the class XSDataImage.
Parameters
_strFilename: the name of the file to open (type=string)
Overrides: object.__init__


```
read(self, fname, frame=None)
```

To be overridden - fill in self.header and self.data

Overrides: fabio.fabioimage.fabioimage.read

Inherited from fabio.fabioimage.fabioimage (Section 19.3)

add(), checkData(), checkHeader(), convert(), getclassname(), getframe(), getheader(), getmax(), getmean(), getmin(), getstddev(), integrate_area(), load(), make_slice(), next(), previous(), readROI(), readheader(), rebin(), resetvals(), save(), toPIL16(), update_header(), write()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()

33.2.2 Properties

Name	Description
<i>Inherited from fabio.fabioimage.fabioimage (Section 19.3)</i>	
classname	
<i>Inherited from object</i>	
__class__	

Index

- fabio (*package*), 6–7
 - fabio.adscimage (*module*), 21–22
 - fabio.adscimage.adscimage (*class*), 21–22
 - fabio.adscimage.test (*function*), 21
 - fabio.binaryimage (*module*), 23–25
 - fabio.binaryimage.binaryimage (*class*), 23–25
 - fabio.bruker100image (*module*), 26–27
 - fabio.bruker100image.bruker100image (*class*), 26–27
 - fabio.brukerimage (*module*), 28–30
 - fabio.brukerimage.brukerimage (*class*), 28–30
 - fabio.brukerimage.test (*function*), 28
 - fabio.byte_offset (*module*), 31
 - fabio.cbimage (*module*), 32–38
 - fabio.cbimage.cbimage (*class*), 32–34
 - fabio.cbimage.CIF (*class*), 34–38
 - fabio.cf_io (*module*), 39
 - fabio.cf_io.read (*function*), 39
 - fabio.compression (*module*), 40–52
 - fabio.compression.compByteOffset_numpy (*function*), 41
 - fabio.compression.compPCK (*function*), 42
 - fabio.compression.compTY1 (*function*), 42
 - fabio.compression.decByteOffset_cython (*function*), 41
 - fabio.compression.decByteOffset_numpy (*function*), 41
 - fabio.compression.decByteOffset_python (*function*), 40
 - fabio.compression.decByteOffset_weave (*function*), 40
 - fabio.compression.decBzip2 (*function*), 40
 - fabio.compression.decGzip (*function*), 40
 - fabio.compression.decPCK (*function*), 42
 - fabio.compression.decTY1 (*function*), 41
 - fabio.compression.decZlib (*function*), 40
 - fabio.compression.endianness (*function*), 40
 - fabio.compression.md5sum (*function*), 40
 - fabio.converters (*module*), 53–54
 - fabio.converters.convert_data (*function*), 53
 - fabio.converters.convert_data_integer (*function*), 53
 - fabio.converters.convert_header (*function*), 53
 - fabio.datIO (*module*), 54–55
 - fabio.datIO.columnfile (*class*), 55
 - fabio.datIO.fabiodata (*class*), 54–55
 - fabio.dm3image (*module*), 56–57
 - fabio.dm3image.dm3image (*class*), 56–57
 - fabio.edfimage (*module*), 58–65
 - fabio.edfimage.edfimage (*class*), 60–65
 - fabio.edfimage.Frame (*class*), 58–60
 - fabio.fabioimage (*module*), 66–69
 - fabio.fabioimage.fabioimage (*class*), 66–69
 - fabio.fabioimage.test (*function*), 66
 - fabio.fabioutils (*module*), 70–80
 - fabio.fabioutils.BZ2File (*class*), 78–80
 - fabio.fabioutils.construct_filename (*function*), 70
 - fabio.fabioutils.deconstruct_filename (*function*), 70
 - fabio.fabioutils.extract_filename (*function*), 70
 - fabio.fabioutils.File (*class*), 73–75
 - fabio.fabioutils.filename_object (*class*), 71–72
 - fabio.fabioutils.getnum (*function*), 70
 - fabio.fabioutils.GzipFile (*class*), 77–78
 - fabio.fabioutils.isAscii (*function*), 70
 - fabio.fabioutils.jump_filename (*function*), 70
 - fabio.fabioutils.next_filename (*function*), 70
 - fabio.fabioutils.nice_int (*function*), 71

- fabio.fabioutils.numstem (*function*), 70
- fabio.fabioutils.previous_filename (*function*), 70
- fabio.fabioutils.StringIO (*class*), 72–73
- fabio.fabioutils.toAscii (*function*), 71
- fabio.fabioutils.UnknownCompressedFile (*class*), 75–77
- fabio.file_series (*module*), 81–88
 - fabio.file_series.file_series (*class*), 82–85
 - fabio.file_series.filename_series (*class*), 86–88
 - fabio.file_series.new_file_series (*function*), 81
 - fabio.file_series.new_file_series0 (*function*), 81
 - fabio.file_series.numbered_file_series (*class*), 85–86
- fabio.fit2dmaskimage (*module*), 89–90
 - fabio.fit2dmaskimage.fit2dmaskimage (*class*), 89–90
- fabio.fit2dspreadsheetimage (*module*), 91–92
 - fabio.fit2dspreadsheetimage.fit2dspreadsheetimage (*class*), 91–92
- fabio.GEimage (*module*), 8–9
 - fabio.GEimage.demo (*function*), 8
 - fabio.GEimage.GEimage (*class*), 8–9
- fabio.GEimage_old (*module*), 10–11
 - fabio.GEimage_old.GEimage (*class*), 10–11
- fabio.HiPiCimage (*module*), 12–13
 - fabio.HiPiCimage.HiPiCimage (*class*), 12–13
- fabio.kcdimage (*module*), 93–94
 - fabio.kcdimage.kcdimage (*class*), 93–94
- fabio.mar345_IO (*module*), 95
- fabio.mar345image (*module*), 96–97
 - fabio.mar345image.mar345image (*class*), 96–97
- fabio.marccdimage (*module*), 98–99
 - fabio.marccdimage.interpret_header (*function*), 98
 - fabio.marccdimage.make_format (*function*), 98
- fabio.marccdimage.marccdimage (*class*), 99
- fabio.openimage (*module*), 100
 - fabio.openimage.do_magic (*function*), 100
 - fabio.openimage.openheader (*function*), 100
 - fabio.openimage.openimage (*function*), 100
- fabio.OXDimage (*module*), 14–17
 - fabio.OXDimage.OXDimage (*class*), 14–16
 - fabio.OXDimage.Section (*class*), 16–17
- fabio.pilatusimage (*module*), 101–102
 - fabio.pilatusimage.pilatusimage (*class*), 101–102
- fabio.pnmimage (*module*), 103–105
 - fabio.pnmimage.pnmimage (*class*), 103–105
- fabio.readbytestream (*module*), 106
 - fabio.readbytestream.readbytestream (*function*), 106
- fabio.TiffIO (*module*), 18–20
 - fabio.TiffIO.TiffIO (*class*), 19–20
- fabio.tifimage (*module*), 107–111
 - fabio.tifimage.Image_File_Directory (*class*), 109–110
 - fabio.tifimage.Image_File_Directory_entry (*class*), 110–111
 - fabio.tifimage.Tiff_header (*class*), 109
 - fabio.tifimage.tifimage (*class*), 107–109
- fabio.xsdimage (*module*), 112–113
 - fabio.xsdimage.xsdimage (*class*), 112–113
- str (*class*), 42–52
 - str.__add__ (*function*), 43
 - str.__contains__ (*function*), 43
 - str.__eq__ (*function*), 43
 - str.__ge__ (*function*), 43
 - str.__getitem__ (*function*), 43
 - str.__getnewargs__ (*function*), 43
 - str.__getslice__ (*function*), 43
 - str.__gt__ (*function*), 43
 - str.__le__ (*function*), 44
 - str.__len__ (*function*), 44

str.__lt__ (function), 44
str.__mod__ (function), 44
str.__mul__ (function), 44
str.__ne__ (function), 44
str.__rmod__ (function), 44
str.__rmul__ (function), 44
str.capitalize (function), 45
str.center (function), 45
str.count (function), 45
str.decode (function), 45
str.encode (function), 45
str.endswith (function), 46
str.expandtabs (function), 46
str.find (function), 46
str.format (function), 46
str.index (function), 46
str.isalnum (function), 47
str.isalpha (function), 47
str.isdigit (function), 47
str.islower (function), 47
str.isspace (function), 47
str.istitle (function), 47
str.isupper (function), 48
str.join (function), 48
str.ljust (function), 48
str.lower (function), 48
str.lstrip (function), 48
str.partition (function), 48
str.replace (function), 49
str.rfind (function), 49
str.rindex (function), 49
str.rjust (function), 49
str.rpartition (function), 49
str.rsplit (function), 50
str.rstrip (function), 50
str.split (function), 50
str.splitlines (function), 50
str.startswith (function), 50
str.strip (function), 51
str.swapcase (function), 51
str.title (function), 51
str.translate (function), 51
str.upper (function), 51
str.zfill (function), 51