



My Basic Network Scan

Report generated by Tenable Nessus™

Mon, 10 Mar 2025 07:19:58 EDT

TABLE OF CONTENTS

Vulnerabilities by Host

• 172.16.16.131.....	4
----------------------	---

Nessus Essentials

Vulnerabilities by Host

172.16.16.131

2

CRITICAL

2

HIGH

8

MEDIUM

4

LOW

73

INFO

Scan Information

Start time: Mon Mar 10 07:06:51 2025

End time: Mon Mar 10 07:19:58 2025

Host Information

Netbios Name: UBUNTU

IP: 172.16.16.131

OS: Linux Kernel 3.13 on Ubuntu 14.04 (trusty)

Vulnerabilities

92626 - Drupal Coder Module Deserialization RCE

Synopsis

A PHP application running on the remote web server is affected by a remote code execution vulnerability.

Description

The version of Drupal running on the remote web server is affected by a remote code execution vulnerability in the Coder module, specifically in file `coder_upgrade.run.php`, due to improper validation of user-supplied input to the `unserialize()` function. An unauthenticated, remote attacker can exploit this, via a specially crafted request, to execute arbitrary PHP code.

See Also

<https://www.drupal.org/node/2765575>

<https://www.drupal.org/project/coder>

Solution

Upgrade the Coder module to version 7.x-1.3 / 7.x-2.6 or later.

Alternatively, remove the entire Coder module directory from any publicly accessible website.

Risk Factor

Critical

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:ND)

References

XREF EDB-ID:40149

Plugin Information

Published: 2016/07/29, Modified: 2022/04/11

Plugin Output

tcp/80/www

Nessus was able to exploit the issue using the following request :

`http://172.16.16.131/drupal/sites/all/modules/coder/coder_upgrade/scripts/coder_upgrade.run.php`

This produced the following truncated output (limited to 10 lines) :

```
----- snip -----  
file parameter is not setNo path to parameter file  
----- snip -----
```

84215 - ProFTPD mod_copy Information Disclosure

Synopsis

The remote host is running a ProFTPD module that is affected by an information disclosure vulnerability.

Description

The remote host is running a version of ProFTPD that is affected by an information disclosure vulnerability in the mod_copy module due to the SITE CPFR and SITE CPTO commands being available to unauthenticated clients. An unauthenticated, remote attacker can exploit this flaw to read and write to arbitrary files on any web accessible path on the host.

See Also

http://bugs.proftpd.org/show_bug.cgi?id=4169

Solution

Upgrade to ProFTPD 1.3.5a / 1.3.6rc1 or later.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.1 (CVSS:3.0/E:F/RL:O/RC:C)

VPR Score

7.4

EPSS Score

0.9679

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	74238
CVE	CVE-2015-3306
XREF	EDB-ID:36742
XREF	EDB-ID:36803

Exploitable With

CANVAS (true) Metasploit (true)

Plugin Information

Published: 2015/06/16, Modified: 2024/01/16

Plugin Output

tcp/21/ftp

```
Nessus received a 350 response from sending the following unauthenticated request :  
SITE CPFR /etc/passwd
```

78515 - Drupal Database Abstraction API SQLi

Synopsis

The remote web server is running a PHP application that is affected by a SQL injection vulnerability.

Description

The remote web server is running a version of Drupal that is affected by a SQL injection vulnerability due to a flaw in the Drupal database abstraction API, which allows a remote attacker to use specially crafted requests that can result in arbitrary SQL execution. This may lead to privilege escalation, arbitrary PHP execution, or remote code execution.

See Also

<https://www.drupal.org/SA-CORE-2014-005>

<https://www.drupal.org/project/drupal/releases/7.32>

Solution

Upgrade to version 7.32 or later.

Risk Factor

High

VPR Score

7.4

EPSS Score

0.9738

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.2 (CVSS2#E:F/RL:OF/RC:C)

References

BID	70595
CVE	CVE-2014-3704
XREF	EDB-ID:34984
XREF	EDB-ID:34992

XREF EDB-ID:34993
XREF EDB-ID:35150

Exploitable With

CANVAS (true) Core Impact (true) (true) Metasploit (true)

Plugin Information

Published: 2014/10/16, Modified: 2022/04/11

Plugin Output

tcp/80/www

Nessus was able to exploit the issue using the following request :

```
POST /drupal/?q=node&destination=node HTTP/1.1
Host: 172.16.16.131
Accept-Charset: iso-8859-1,utf-8;q=0.9,*;q=0.1
Accept-Language: en
Content-Type: application/x-www-form-urlencoded
Connection: Keep-Alive
Content-Length: 117
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Pragma: no-cache
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
name[0];SELECT
+@@version;#]=0;&name[0]=nessus&pass=nessus&test2=test&form_build_id=&form_id=user_login_block&op=Log
+in
```

This produced the following truncated output (limited to 5 lines) :

```
----- snip -----
>Warning</em>: mb_strlen() expects parameter 1 to be string, array given in <em
  class="placeholder">drupal_strlen()</em> (line <em class="placeholder">441</em> of <em
  class="placeholder">/var/www/html/drupal/includes/unicode.inc</em>).</li>
<li><em class="placeholder">Warning</em>: addcslashes() expects parameter 1 to be string,
  array given in <em class="placeholder">DatabaseConnection-&gt;escapeLike()</em> (line <em
  class="placeholder">965</em> of <em class="placeholder">/var/www/html/drupal/includes/database/
  database.inc</em>).</li>
<li>Sorry, unrecognized username or password. <a href="/drupal/?q=user/password">Have you forgotten
  your password?</a></li>
</ul>
</div>
[...]
```

----- snip -----

42873 - SSL Medium Strength Cipher Suites Supported (SWEET32)

Synopsis

The remote service supports the use of medium strength SSL ciphers.

Description

The remote host supports the use of SSL ciphers that offer medium strength encryption. Nessus regards medium strength as any encryption that uses key lengths at least 64 bits and less than 112 bits, or else that uses the 3DES encryption suite.

Note that it is considerably easier to circumvent medium strength encryption if the attacker is on the same physical network.

See Also

<http://www.nessus.org/u?df5555f5>

<https://sweet32.info>

Solution

Reconfigure the affected application if possible to avoid use of medium strength ciphers.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

VPR Score

5.1

EPSS Score

0.0398

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

References

CVE CVE-2016-2183

Plugin Information

Published: 2009/11/23, Modified: 2025/02/12

Plugin Output

tcp/631/www

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	
SHA1					

The fields above are :

{Tenable ciphername}

{Cipher ID code}

Kex={key exchange}

Auth={authentication}

Encrypt={symmetric encryption method}

MAC={message authentication code}

{export flag}

10704 - Apache Multiviews Arbitrary Directory Listing

Synopsis

The remote web server is affected by an information disclosure vulnerability.

Description

The Apache web server running on the remote host is affected by an information disclosure vulnerability. An unauthenticated, remote attacker can exploit this, by sending a crafted request, to display a listing of a remote directory, even if a valid index file exists in the directory.

For Apache web server later than 1.3.22, review listing directory configuration to avoid disclosing sensitive information

See Also

<http://www.nessus.org/u?f39e976b>

<http://www.nessus.org/u?a96611bc>

<http://www.nessus.org/u?c1c382bc>

Solution

Upgrade to Apache version 1.3.22 or later. Alternatively, as a workaround, disable Multiviews.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.8 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

2.2

EPSS Score

0.858

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	3009
CVE	CVE-2001-0731
XREF	OWASP:OWASP-CM-004
XREF	EDB-ID:21002

Plugin Information

Published: 2016/02/16, Modified: 2020/10/21

Plugin Output

tcp/80/www

Nessus was able to exploit the issue using the following request :

`http://172.16.16.131/?M=A`

This produced the following truncated output (limited to 10 lines) :

```
----- snip -----
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN">
<html>
<head>
<title>Index of </title>
</head>
<body>
<h1>Index of </h1>
<table>
<tr><th valign="top"></th><th><a href="?C=N;O=D">Name</a></th>
<th><a href="?C=M;O=A">Last modified</a></th><th><a href="?C=S;O=A">Size</a></th><th><a href="?C=D;O=A">Description</a></th></tr>
<tr><th colspan="5"><hr></th></tr>
[...]
```

----- snip -----

57608 - SMB Signing not required

Synopsis

Signing is not required on the remote SMB server.

Description

Signing is not required on the remote SMB server. An unauthenticated, remote attacker can exploit this to conduct man-in-the-middle attacks against the SMB server.

See Also

<http://www.nessus.org/u?df39b8b3>

<http://technet.microsoft.com/en-us/library/cc731957.aspx>

<http://www.nessus.org/u?74b80723>

<https://www.samba.org/samba/docs/current/man-html/smb.conf.5.html>

<http://www.nessus.org/u?a3cac4ea>

Solution

Enforce message signing in the host's configuration. On Windows, this is found in the policy setting 'Microsoft network server: Digitally sign communications (always)'. On Samba, the setting is called 'server signing'. See the 'see also' links for further details.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

Plugin Information

Published: 2012/01/19, Modified: 2022/10/05

Plugin Output

tcp/445/cifs

187315 - SSH Terrapin Prefix Truncation Weakness (CVE-2023-48795)

Synopsis

The remote SSH server is vulnerable to a mitm prefix truncation attack.

Description

The remote SSH server is vulnerable to a man-in-the-middle prefix truncation weakness known as Terrapin. This can allow a remote, man-in-the-middle attacker to bypass integrity checks and downgrade the connection's security.

Note that this plugin only checks for remote SSH servers that support either ChaCha20-Poly1305 or CBC with Encrypt-then-MAC and do not support the strict key exchange countermeasures. It does not check for vulnerable software versions.

See Also

<https://terrapin-attack.com/>

Solution

Contact the vendor for an update with the strict key exchange countermeasures or disable the affected algorithms.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

5.3 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.1

EPSS Score

0.9547

CVSS v2.0 Base Score

5.4 (CVSS2#AV:N/AC:H/Au:N/C:N/I:C/A:N)

CVSS v2.0 Temporal Score

4.2 (CVSS2#E:POC/RL:OF/RC:C)

References

CVE CVE-2023-48795

Plugin Information

Published: 2023/12/27, Modified: 2024/01/29

Plugin Output

tcp/22/ssh

```
Supports following CBC Client to Server algorithm : cast128-cbc
Supports following CBC Client to Server algorithm : aes192-cbc
Supports following CBC Client to Server algorithm : aes256-cbc
Supports following CBC Client to Server algorithm : rijndael-cbc@lysator.liu.se
Supports following CBC Client to Server algorithm : blowfish-cbc
Supports following CBC Client to Server algorithm : 3des-cbc
Supports following CBC Client to Server algorithm : aes128-cbc
Supports following ChaCha20-Poly1305 Client to Server algorithm : chacha20-poly1305@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm : hmac-md5-etm@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm : hmac-sha1-etm@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm : hmac-md5-96-etm@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm : hmac-sha1-96-etm@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm : hmac-ripemd160-etm@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm : hmac-sha2-512-etm@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm : hmac-sha2-256-etm@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm : umac-128-etm@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm : umac-64-etm@openssh.com
Supports following CBC Server to Client algorithm : cast128-cbc
Supports following CBC Server to Client algorithm : aes192-cbc
Supports following CBC Server to Client algorithm : aes256-cbc
Supports following CBC Server to Client algorithm : rijndael-cbc@lysator.liu.se
Supports following CBC Server to Client algorithm : blowfish-cbc
Supports following CBC Server to Client algorithm : 3des-cbc
Supports following CBC Server to Client algorithm : aes128-c [...]
```

90317 - SSH Weak Algorithms Supported

Synopsis

The remote SSH server is configured to allow weak encryption algorithms or no algorithm at all.

Description

Nessus has detected that the remote SSH server is configured to use the Arcfour stream cipher or no cipher at all. RFC 4253 advises against using Arcfour due to an issue with weak keys.

See Also

<https://tools.ietf.org/html/rfc4253#section-6.3>

Solution

Contact the vendor or consult product documentation to remove the weak ciphers.

Risk Factor

Medium

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2016/04/04, Modified: 2016/12/14

Plugin Output

tcp/22/ssh

The following weak server-to-client encryption algorithms are supported :

```
arcfour
arcfour128
arcfour256
```

The following weak client-to-server encryption algorithms are supported :

```
arcfour
arcfour128
arcfour256
```

51192 - SSL Certificate Cannot Be Trusted

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2010/12/15, Modified: 2020/04/27

Plugin Output

tcp/631/www

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

```
| -Subject : CN=ubuntu  
| -Issuer  : CN=ubuntu
```

57582 - SSL Self-Signed Certificate

Synopsis

The SSL certificate chain for this service ends in an unrecognized self-signed certificate.

Description

The X.509 certificate chain for this service is not signed by a recognized certificate authority. If the remote host is a public host in production, this nullifies the use of SSL as anyone could establish a man-in-the-middle attack against the remote host.

Note that this plugin does not check for certificate chains that end in a certificate that is not self-signed, but is signed by an unrecognized certificate authority.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2012/01/17, Modified: 2022/06/14

Plugin Output

tcp/631/www

The following certificate was found at the top of the certificate chain sent by the remote host, but is self-signed and was not found in the list of known certificate authorities :

| -Subject : CN=ubuntu

104743 - TLS Version 1.0 Protocol Detection

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.0. TLS 1.0 has a number of cryptographic design flaws. Modern implementations of TLS 1.0 mitigate these problems, but newer versions of TLS like 1.2 and 1.3 are designed against these flaws and should be used whenever possible.

As of March 31, 2020, Endpoints that aren't enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

PCI DSS v3.2 requires that TLS 1.0 be disabled entirely by June 30, 2018, except for POS POI terminals (and the SSL/TLS termination points to which they connect) that can be verified as not being susceptible to any known exploits.

See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

Solution

Enable support for TLS 1.2 and 1.3, and disable support for TLS 1.0.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

CVSS v2.0 Base Score

6.1 (CVSS2#AV:N/AC:H/Au:N/C:C/I:P/A:N)

References

XREF CWE:327

Plugin Information

Published: 2017/11/22, Modified: 2023/04/19

Plugin Output

tcp/631/www

TLSv1 is enabled and the server supports at least one cipher.

157288 - TLS Version 1.1 Deprecated Protocol

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.1. TLS 1.1 lacks support for current and recommended cipher suites. Ciphers that support encryption before MAC computation, and authenticated encryption modes such as GCM cannot be used with TLS 1.1

As of March 31, 2020, Endpoints that are not enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

See Also

<https://datatracker.ietf.org/doc/html/rfc8996>

<http://www.nessus.org/u?c8ae820d>

Solution

Enable support for TLS 1.2 and/or 1.3, and disable support for TLS 1.1.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

CVSS v2.0 Base Score

6.1 (CVSS2#AV:N/AC:H/Au:N/C:C/I:P/A:N)

References

XREF CWE:327

Plugin Information

Published: 2022/04/04, Modified: 2024/05/14

Plugin Output

tcp/631/www

TLSv1.1 is enabled and the server supports at least one cipher.

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

VPR Score

2.2

EPSS Score

0.8939

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

The remote clock is synchronized with the local clock.

70658 - SSH Server CBC Mode Ciphers Enabled

Synopsis

The SSH server is configured to use Cipher Block Chaining.

Description

The SSH server is configured to support Cipher Block Chaining (CBC) encryption. This may allow an attacker to recover the plaintext message from the ciphertext.

Note that this plugin only checks for the options of the SSH server and does not check for vulnerable software versions.

Solution

Contact the vendor or consult product documentation to disable CBC mode cipher encryption, and enable CTR or GCM cipher mode encryption.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

VPR Score

6.5

EPSS Score

0.6016

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	32319
CVE	CVE-2008-5161
XREF	CERT:958563
XREF	CWE:200

Plugin Information

Published: 2013/10/28, Modified: 2023/10/27

Plugin Output

tcp/22/ssh

The following client-to-server Cipher Block Chaining (CBC) algorithms are supported :

```
3des-cbc
aes128-cbc
aes192-cbc
aes256-cbc
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

The following server-to-client Cipher Block Chaining (CBC) algorithms are supported :

```
3des-cbc
aes128-cbc
aes192-cbc
aes256-cbc
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

153953 - SSH Weak Key Exchange Algorithms Enabled

Synopsis

The remote SSH server is configured to allow weak key exchange algorithms.

Description

The remote SSH server is configured to allow key exchange algorithms which are considered weak.

This is based on the IETF draft document Key Exchange (KEX) Method Updates and Recommendations for Secure Shell (SSH) RFC9142. Section 4 lists guidance on key exchange algorithms that SHOULD NOT and MUST NOT be enabled. This includes:

diffie-hellman-group-exchange-sha1

diffie-hellman-group1-sha1

gss-gex-sha1-*

gss-group1-sha1-*

gss-group14-sha1-*

rsa1024-sha1

Note that this plugin only checks for the options of the SSH server, and it does not check for vulnerable software versions.

See Also

<https://datatracker.ietf.org/doc/html/rfc9142>

Solution

Contact the vendor or consult product documentation to disable the weak algorithms.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2021/10/13, Modified: 2024/03/22

Plugin Output

tcp/22/ssh

The following weak key exchange algorithms are enabled :

diffie-hellman-group-exchange-sha1
diffie-hellman-group1-sha1

71049 - SSH Weak MAC Algorithms Enabled

Synopsis

The remote SSH server is configured to allow MD5 and 96-bit MAC algorithms.

Description

The remote SSH server is configured to allow either MD5 or 96-bit MAC algorithms, both of which are considered weak.

Note that this plugin only checks for the options of the SSH server, and it does not check for vulnerable software versions.

Solution

Contact the vendor or consult product documentation to disable MD5 and 96-bit MAC algorithms.

Risk Factor

Low

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2013/11/22, Modified: 2016/12/14

Plugin Output

tcp/22/ssh

```
The following client-to-server Message Authentication Code (MAC) algorithms
are supported :
```

```
  hmac-md5
  hmac-md5-96
  hmac-md5-96-etm@openssh.com
  hmac-md5-etm@openssh.com
  hmac-sha1-96
  hmac-sha1-96-etm@openssh.com
```

```
The following server-to-client Message Authentication Code (MAC) algorithms
are supported :
```

```
  hmac-md5
  hmac-md5-96
  hmac-md5-96-etm@openssh.com
  hmac-md5-etm@openssh.com
  hmac-sha1-96
  hmac-sha1-96-etm@openssh.com
```


18261 - Apache Banner Linux Distribution Disclosure

Synopsis

The name of the Linux distribution running on the remote host was found in the banner of the web server.

Description

Nessus was able to extract the banner of the Apache web server and determine which Linux distribution the remote host is running.

Solution

If you do not wish to display this information, edit 'httpd.conf' and set the directive 'ServerTokens Prod' and restart Apache.

Risk Factor

None

Plugin Information

Published: 2005/05/15, Modified: 2022/03/21

Plugin Output

tcp/0

```
The Linux distribution detected was :  
- Ubuntu 14.04 (trusty)
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2023/08/17

Plugin Output

tcp/80/www

```
URL      : http://172.16.16.131/
Version  : 2.4.99
Source   : Server: Apache/2.4.7 (Ubuntu)
backported : 1
os       : ConvertedUbuntu
```

39519 - Backported Security Patch Detection (FTP)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote FTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2015/07/07

Plugin Output

tcp/21/ftp

Give Nessus credentials to perform local checks.

39520 - Backported Security Patch Detection (SSH)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote SSH server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2015/07/07

Plugin Output

tcp/22/ssh

Give Nessus credentials to perform local checks.

39521 - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2015/07/07

Plugin Output

tcp/80/www

Give Nessus credentials to perform local checks.

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2025/02/12

Plugin Output

tcp/0

The remote operating system matched the following CPE :

cpe:/o:canonical:ubuntu_linux:14.04 -> Canonical Ubuntu Linux

Following application CPE's matched on the remote system :

cpe:/a:apache:http_server:2.4.7 -> Apache Software Foundation Apache HTTP Server
cpe:/a:apache:http_server:2.4.99 -> Apache Software Foundation Apache HTTP Server
cpe:/a:drupal:drupal:7.5 -> Drupal
cpe:/a:eclipse:jetty:8.1.7 -> Eclipse Jetty
cpe:/a:mysql:mysql -> MySQL MySQL
cpe:/a:openbsd:openssh:6.6 -> OpenBSD OpenSSH
cpe:/a:openbsd:openssh:6.6.1p1 -> OpenBSD OpenSSH
cpe:/a:samba:samba -> Samba Samba
cpe:/a:samba:samba:4.3.11 -> Samba Samba

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2022/09/09

Plugin Output

tcp/0

```
Remote device type : general-purpose  
Confidence level : 95
```

Synopsis

A content management system is running on the remote web server.

Description

Drupal, an open source content management system written in PHP, is running on the remote web server.

See Also

<https://www.drupal.org/>

Solution

Ensure that the use of this software aligns with your organization's security and acceptable use policies.

Risk Factor

None

References

XREF IAVT:0001-T-0586

Plugin Information

Published: 2005/07/07, Modified: 2023/05/24

Plugin Output

tcp/80/www

```
URL      : http://172.16.16.131/drupal
Version  : 7.5
```

194915 - Eclipse Jetty Web Server Detection

Synopsis

The Eclipse Jetty web server was detected on the remote host.

Description

The Eclipse Jetty web server was detected on the remote host.

See Also

<https://eclipse.dev/jetty/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/05/02, Modified: 2025/02/12

Plugin Output

tcp/0

```
URL      : http://172.16.16.131:8080/  
Version  : 8.1.7  
Source   : Server: Jetty(8.1.7.v20120910)
```

19689 - Embedded Web Server Detection

Synopsis

The remote web server is embedded.

Description

The remote web server cannot host user-supplied CGIs. CGI scanning will be disabled on this server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/09/14, Modified: 2019/11/22

Plugin Output

tcp/631/www

10092 - FTP Server Detection

Synopsis

An FTP server is listening on a remote port.

Description

It is possible to obtain the banner of the remote FTP server by connecting to a remote port.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0030

XREF IAVT:0001-T-0943

Plugin Information

Published: 1999/10/12, Modified: 2023/08/17

Plugin Output

tcp/21/ftp

The remote FTP banner is :

220 ProFTPD 1.3.5 Server (ProFTPD Default Installation) [172.16.16.131]

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/80/www

Based on the response to an OPTIONS request :

- HTTP methods GET HEAD OPTIONS POST are allowed on :

/

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/631/www

Based on the response to an OPTIONS request :

- HTTP methods HEAD OPTIONS POST PUT GET are allowed on :

/

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :  
Apache/2.4.7 (Ubuntu)
```

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/631/www

```
The remote web server type is :  
CUPS/1.7 IPP/2.1
```

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/3500/www

```
The remote web server type is :  
WEBrick/1.3.1 (Ruby/2.3.8/2018-10-18)
```

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/8080/www

```
The remote web server type is :  
Jetty(8.1.7.v20120910)
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

Date: Mon, 10 Mar 2025 11:12:06 GMT

Server: Apache/2.4.7 (Ubuntu)

Vary: Accept-Encoding

Content-Length: 1351

Keep-Alive: timeout=5, max=100

Connection: Keep-Alive

Content-Type: text/html; charset=UTF-8

Response Body :

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN">

<html>

<head>

<title>Index of </title>

</head>

<body>

<h1>Index of </h1>

```

<table>
  <tr><th valign="top"></th><th><a href="?C=N;O=D">Name</a></th><th><a href="?C=M;O=A">Last modified</a></th><th><a href="?C=S;O=A">Size</a></th><th><a href="?C=D;O=A">Description</a></th></tr>
  <tr><th colspan="5"><hr></th></tr>
  <tr><td valign="top"></td><td><a href="chat/">chat</a></td><td align="right">2020-10-29 20:01 </td><td align="right"> - </td><td>&nbsp;</td></tr>
  <tr><td valign="top"></td><td><a href="drupal/">drupal</a></td><td align="right">2011-07-27 20:17 </td><td align="right"> - </td><td>&nbsp;</td></tr>
  <tr><td valign="top"></td><td><a href="payroll_app.php">payroll_app.php</a></td><td align="right">2020-10-29 20:01 </td><td align="right">1.7K</td><td>&nbsp;</td></tr>
  <tr><td valign="top"></td><td><a href="phpmyadmin/">phpmyadmin</a></td><td align="right">2013-04-08 12:06 </td><td align="right"> - </td><td>&nbsp;</td></tr>
  <tr><th colspan="5"><hr></th></tr>
</table>
<address>Apache/2.4.7 (Ubuntu) Server at 172.16.16.131 Port 80</address>
</body></html>

```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/3500/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : GET, HEAD, POST, OPTIONS

Headers :

X-Frame-Options: SAMEORIGIN

X-Xss-Protection: 1; mode=block

X-Content-Type-Options: nosniff

Content-Type: text/html; charset=utf-8

Etag: W/"b56dd5f9363ed0f7bd4d11c36d9471dd"

Cache-Control: max-age=0, private, must-revalidate

X-Request-Id: 440001ab-d1ef-4da9-9f77-2abb4dde2496

X-Runtime: 0.002176

Server: WEBrick/1.3.1 (Ruby/2.3.8/2018-10-18)

Date: Mon, 10 Mar 2025 11:12:06 GMT

Content-Length: 14935

Connection: Keep-Alive

Response Body :

```
<!DOCTYPE html>
<html>
```

```

<head>
  <title>Ruby on Rails: Welcome aboard</title>
  <style media="screen">
    body {
      margin: 0;
      margin-bottom: 25px;
      padding: 0;
      background-color: #f0f0f0;
      font-family: "Lucida Grande", "Bitstream Vera Sans", "Verdana";
      font-size: 13px;
      color: #333;
    }

    h1 {
      font-size: 28px;
      color: #000;
    }

    a {color: #03c}

    a:hover {
      background-color: #03c;
      color: white;
      text-decoration: none;
    }

    #page {
      background-color: #f0f0f0;
      width: 750px;
      margin: 0;
      margin-left: auto;
      margin-right: auto;
    }

    #content {
      float: left;
      background-color: white;
      border: 3px solid #aaa;
      border-top: none;
      padding: 25px;
      width: 500px;
    }

    #sidebar {
      float: right;
      width: 175px;
    }

    #footer {
      clear: both;
    }

    #header, #about, #getting-started {
      padding-left: 75px;
      padding-right: 30px;
    }

    #header {
      background-image: url(
t5Sr9aur16q00l3Z9/DEoJh18gZQGAUXPHIyQHH7eioZ8bjnAFHZ0RndNxxRBhGcUbxoKIHBkTEcUYREIHIGpKQjUDS6 [...])

```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/8080/www

Response Code : HTTP/1.1 404 Not Found

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : no

Options allowed : (Not implemented)

Headers :

Date: Mon, 10 Mar 2025 11:12:06 GMT

Content-Type: text/html

Content-Length: 795

Connection: close

Server: Jetty(8.1.7.v20120910)

Response Body :

42410 - Microsoft Windows NTLMSSP Authentication Request Remote Network Name Disclosure

Synopsis

It is possible to obtain the network name of the remote host.

Description

The remote host listens on tcp port 445 and replies to SMB requests.

By sending an NTLMSSP authentication request it is possible to obtain the name of the remote system and the name of its domain.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/11/06, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

The following 2 NetBIOS names have been gathered :

UBUNTU	= Computer name
UBUNTU	= Workgroup / Domain name

17651 - Microsoft Windows SMB : Obtains the Password Policy

Synopsis

It is possible to retrieve the remote host's password policy using the supplied credentials.

Description

Using the supplied credentials it was possible to extract the password policy for the remote Windows host. The password policy must conform to the Informational System Policy.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/03/30, Modified: 2015/01/12

Plugin Output

tcp/445/cifs

The following password policy is defined on the remote host:

```
Minimum password len: 5
Password history len: 0
Maximum password age (d): No limit
Password must meet complexity requirements: Disabled
Minimum password age (d): 0
Forced logoff time (s): Not set
Locked account time (s): 1800
Time between failed logon (s): 1800
Number of invalid logon before locked out (s): 0
```

10859 - Microsoft Windows SMB LsaQueryInformationPolicy Function SID Enumeration

Synopsis

It is possible to obtain the host SID for the remote host.

Description

By emulating the call to LsaQueryInformationPolicy(), it was possible to obtain the host SID (Security Identifier).

The host SID can then be used to get the list of local users.

See Also

<http://technet.microsoft.com/en-us/library/bb418944.aspx>

Solution

You can prevent anonymous lookups of the host SID by setting the 'RestrictAnonymous' registry setting to an appropriate value.

Refer to the 'See also' section for guidance.

Risk Factor

None

Plugin Information

Published: 2002/02/13, Modified: 2024/01/31

Plugin Output

tcp/445/cifs

```
The remote host SID value is : S-1-5-21-3226904217-2194950160-3952231666
```

```
The value of 'RestrictAnonymous' setting is : unknown
```

Synopsis

It was possible to obtain information about the remote operating system.

Description

Nessus was able to obtain the remote operating system name and version (Windows and/or Samba) by sending an authentication request to port 139 or 445. Note that this plugin requires SMB to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/10/17, Modified: 2021/09/20

Plugin Output

tcp/445/cifs

```
The remote Operating System is : Windows 6.1
The remote native LAN manager is : Samba 4.3.11-Ubuntu
The remote SMB Domain Name is : UBUNTU
```

11011 - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

tcp/445/cifs

```
A CIFS server is running on this port.
```

60119 - Microsoft Windows SMB Share Permissions Enumeration

Synopsis

It was possible to enumerate the permissions of remote network shares.

Description

By using the supplied credentials, Nessus was able to enumerate the permissions of network shares. User permissions are enumerated for each network share that has a list of access control entries (ACEs).

See Also

<https://technet.microsoft.com/en-us/library/bb456988.aspx>

<https://technet.microsoft.com/en-us/library/cc783530.aspx>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2012/07/25, Modified: 2022/08/11

Plugin Output

tcp/445/cifs

```
Share path : \\UBUNTU\print$
Local path : C:\var\lib\samba\printers
Comment : Printer Drivers
[*] Allow ACE for Everyone (S-1-1-0): 0x001f01ff
    FILE_GENERIC_READ:      YES
    FILE_GENERIC_WRITE:     YES
    FILE_GENERIC_EXECUTE:   YES

Share path : \\UBUNTU\public
Local path : C:\var\www\html\
Comment : WWW
[*] Allow ACE for Everyone (S-1-1-0): 0x001f01ff
    FILE_GENERIC_READ:      YES
    FILE_GENERIC_WRITE:     YES
    FILE_GENERIC_EXECUTE:   YES

Share path : \\UBUNTU\IPC$
Local path : C:\tmp
Comment : IPC Service (ubuntu server (Samba, Ubuntu))
[*] Allow ACE for Everyone (S-1-1-0): 0x001f01ff
    FILE_GENERIC_READ:      YES
```

FILE_GENERIC_WRITE:	YES
FILE_GENERIC_EXECUTE:	YES

10395 - Microsoft Windows SMB Shares Enumeration

Synopsis

It is possible to enumerate remote network shares.

Description

By connecting to the remote host, Nessus was able to enumerate the network share names.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2000/05/09, Modified: 2022/02/01

Plugin Output

tcp/445/cifs

Here are the SMB shares available on the remote host :

- print\$
- public
- IPC\$

100871 - Microsoft Windows SMB Versions Supported (remote check)

Synopsis

It was possible to obtain information about the version of SMB running on the remote host.

Description

Nessus was able to obtain the version of SMB running on the remote host by sending an authentication request to port 139 or 445.

Note that this plugin is a remote check and does not work on agents.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/06/19, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The remote host supports the following versions of SMB :  
SMBv1  
SMBv2
```

106716 - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check)

Synopsis

It was possible to obtain information about the dialects of SMB2 and SMB3 available on the remote host.

Description

Nessus was able to obtain the set of SMB2 and SMB3 dialects running on the remote host by sending an authentication request to port 139 or 445.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/02/09, Modified: 2020/03/11

Plugin Output

tcp/445/cifs

```
The remote host supports the following SMB dialects :
_version_  _introduced in windows version_
2.0.2      Windows 2008
2.1        Windows 7
2.2.2      Windows 8 Beta
2.2.4      Windows 8 Beta
3.0        Windows 8
3.0.2      Windows 8.1
3.1        Windows 10
3.1.1      Windows 10
```

10719 - MySQL Server Detection

Synopsis

A database server is listening on the remote port.

Description

The remote host is running MySQL, an open source database server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0802

Plugin Information

Published: 2001/08/13, Modified: 2022/10/12

Plugin Output

tcp/3306/mysql

The remote database access is restricted and configured to reject access from unauthorized IPs. Therefore it was not possible to extract its version number.

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/02/12

Plugin Output

tcp/21/ftp

```
Port 21/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/02/12

Plugin Output

tcp/22/ssh

```
Port 22/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/02/12

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/02/12

Plugin Output

tcp/445/cifs

```
Port 445/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/02/12

Plugin Output

tcp/631/www

Port 631/tcp was found to be open

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/02/12

Plugin Output

tcp/3306/mysql

```
Port 3306/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/02/12

Plugin Output

tcp/3500/www

```
Port 3500/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/02/12

Plugin Output

tcp/8080/www

```
Port 8080/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2024/12/31

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.8.3
Nessus build : 20010
Plugin feed version : 202503091240
Scanner edition used : Nessus Home
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```

```
Scan policy used : Basic Network Scan
Scanner IP : 172.17.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 24.936 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : no
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2025/3/10 7:07 EDT (UTC -04:00)
Scan duration : 776 sec
Scan for malware : no
```

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : CentOS Linux 7 Linux Kernel 3.10
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 3.13 on Ubuntu 14.04 (trusty)
Confidence level : 95
Method : SSH
Type : general-purpose
Fingerprint : SSH:SSH-2.0-OpenSSH_6.6.1p1 Ubuntu-2ubuntu2.13

Remote operating system : Linux Kernel 3.13 on Ubuntu 14.04 (trusty)
Confidence level : 95
Method : HTTP
Type : general-purpose
Fingerprint : unknown

Following fingerprints could not be used to determine OS :

SinFP:!!
P1:B10113:F0x12:W29200:00204ffff:M1460:
P2:B10113:F0x12:W28960:00204ffff0402080affffff4445414401030307:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191003_7_p=8080R
SSLCert:!:i/CN:ubuntus/CN:ubuntu
2d697f035500a5069a452eca7f1f9795ff43c941



11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2024/10/14

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 3.13 on Ubuntu 14.04 (trusty)
Confidence level : 95
Method : HTTP
```

Not all fingerprints could give a match. If you think that these signatures would help us improve OS fingerprinting, please submit them by visiting <https://www.tenable.com/research/submitsignatures>.

```
SSH:SSH-2.0-OpenSSH_6.6.1p1 Ubuntu-2ubuntu2.13
```

```
SinFP:!!
```

```
P1:B10113:F0x12:W29200:00204ffff:M1460:
```

```
P2:B10113:F0x12:W28960:00204ffff0402080affffff4445414401030307:M1460:
```

```
P3:B00000:F0x00:W0:00:M0
```

```
P4:191003_7_p=8080R
```

```
SSLcert:!:i/CN:ubuntu/CN:ubuntu
```

```
2d697f035500a5069a452eca7f1f9795ff43c941
```

The remote host is running Linux Kernel 3.13 on Ubuntu 14.04 (trusty)

117886 - OS Security Patch Assessment Not Available

Synopsis

OS Security Patch Assessment is not available.

Description

OS Security Patch Assessment is not available on the remote host.

This does not necessarily indicate a problem with the scan.

Credentials may not have been provided, OS security patch assessment may not be supported for the target, the target may not have been identified, or another issue may have occurred that prevented OS security patch assessment from being available. See plugin output for details.

This plugin reports non-failure information impacting the availability of OS Security Patch Assessment. Failure information is reported by plugin 21745 : 'OS Security Patch Assessment failed'. If a target host is not supported for OS Security Patch Assessment, plugin 110695 : 'OS Security Patch Assessment Checks Not Supported' will report concurrently with this plugin.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0515

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

tcp/0

The following issues were reported :

```
- Plugin      : no_local_checks_credentials.nasl
  Plugin ID   : 110723
  Plugin Name : Target Credential Status by Authentication Protocol - No Credentials Provided
  Message     :
  Credentials were not provided for detected SSH service.
```

181418 - OpenSSH Detection

Synopsis

An OpenSSH-based SSH server was detected on the remote host.

Description

An OpenSSH-based SSH server was detected on the remote host.

See Also

<https://www.openssh.com/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/09/14, Modified: 2025/03/06

Plugin Output

tcp/22/ssh

```
Service : ssh
Version : 6.6.1p1
Banner  : SSH-2.0-OpenSSH_6.6.1p1 Ubuntu-2ubuntu2.13
```

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2025/02/12

Plugin Output

tcp/0

```
. You need to take the following 2 actions :
```

```
[ ProFTPD mod_copy Information Disclosure (84215) ]
```

```
+ Action to take : Upgrade to ProFTPD 1.3.5a / 1.3.6rc1 or later.
```

```
[ SSH Terrapin Prefix Truncation Weakness (CVE-2023-48795) (187315) ]
```

```
+ Action to take : Contact the vendor for an update with the strict key exchange countermeasures or  
disable the affected algorithms.
```

10860 - SMB Use Host SID to Enumerate Local Users

Synopsis

Nessus was able to enumerate local users.

Description

Using the host security identifier (SID), Nessus was able to enumerate local users on the remote Windows system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/02/13, Modified: 2023/02/28

Plugin Output

tcp/445/cifs

- nobody (id 501, Guest account)
- chewbacca (id 1000)

Note that, in addition to the Administrator, Guest, and Kerberos accounts, Nessus has enumerated local users with IDs between 1000 and 1200. To use a different range, edit the scan policy and change the 'Enumerate Local Users: Start UID' and/or 'End UID' preferences under 'Assessment->Windows' and re-run the scan. Only UIDs between 1 and 2147483647 are allowed for this range.

70657 - SSH Algorithms and Languages Supported

Synopsis

An SSH server is listening on this port.

Description

This script detects which algorithms and languages are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/28, Modified: 2025/01/20

Plugin Output

tcp/22/ssh

```
Nessus negotiated the following encryption algorithm(s) with the server :
```

```
Client to Server: aes256-ctr
Server to Client: aes256-ctr
```

```
The server supports the following options for compression_algorithms_server_to_client :
```

```
none
zlib@openssh.com
```

```
The server supports the following options for mac_algorithms_client_to_server :
```

```
hmac-md5
hmac-md5-96
hmac-md5-96-etm@openssh.com
hmac-md5-etm@openssh.com
hmac-ripemd160
hmac-ripemd160-etm@openssh.com
hmac-ripemd160@openssh.com
hmac-sha1
hmac-sha1-96
hmac-sha1-96-etm@openssh.com
hmac-sha1-etm@openssh.com
hmac-sha2-256
hmac-sha2-256-etm@openssh.com
hmac-sha2-512
hmac-sha2-512-etm@openssh.com
umac-128-etm@openssh.com
umac-128@openssh.com
```

```
umac-64-etm@openssh.com
umac-64@openssh.com
```

The server supports the following options for `server_host_key_algorithms` :

```
ecdsa-sha2-nistp256
ssh-dss
ssh-ed25519
ssh-rsa
```

The server supports the following options for `encryption_algorithms_client_to_server` :

```
3des-cbc
aes128-cbc
aes128-ctr
aes128-gcm@openssh.com
aes192-cbc
aes192-ctr
aes256-cbc
aes256-ctr
aes256-gcm@openssh.com
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
chacha20-poly1305@openssh.com
rijndael-cbc@lysator.liu.se
```

The server supports the following options for `mac_algorithms_server_to_client` :

```
hmac-md5
hmac-md5-96
hmac-md5-96-etm@openssh.com
hmac-md5-etm@openssh.com
hmac-ripemd160
hmac-ripemd160-etm@openssh.com
hmac-ripemd160@openssh.com
hmac-sha1
hmac-sha1-96
hmac-sha1-96-etm@openssh.com
hmac-sha1-etm@openssh.com
hmac-sha2-256
hmac-sha2-256-etm@openssh.com
hmac-sha2-512
hmac-sha2-512-etm@openssh.com
umac-128-etm@openssh.com
umac-128@openssh.com
umac-64-etm@openssh.com
umac-64@openssh.com
```

The server supports the following options for `kex_algorithms` :

```
curve25519-sha256@libssh.org
diffie-hellman-group-exchange-sha1
diffie-hellman-group-exchange-sha256
diffie-hellman-group1-sha1
diffie-hellman-group14-sha1
ecdh-sha2-nistp256
[...]
```

149334 - SSH Password Authentication Accepted

Synopsis

The SSH server on the remote host accepts password authentication.

Description

The SSH server on the remote host accepts password authentication.

See Also

<https://tools.ietf.org/html/rfc4252#section-8>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/05/07, Modified: 2021/05/07

Plugin Output

tcp/22/ssh

10881 - SSH Protocol Versions Supported

Synopsis

A SSH server is running on the remote host.

Description

This plugin determines the versions of the SSH protocol supported by the remote SSH daemon.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/03/06, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

The remote SSH daemon supports the following versions of the SSH protocol :

- 1.99
- 2.0

153588 - SSH SHA-1 HMAC Algorithms Enabled

Synopsis

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Description

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Although NIST has formally deprecated use of SHA-1 for digital signatures, SHA-1 is still considered secure for HMAC as the security of HMAC does not rely on the underlying hash function being resistant to collisions.

Note that this plugin only checks for the options of the remote SSH server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/09/23, Modified: 2022/04/05

Plugin Output

tcp/22/ssh

The following client-to-server SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :

```
hmac-sha1
hmac-sha1-96
hmac-sha1-96-etm@openssh.com
hmac-sha1-etm@openssh.com
```

The following server-to-client SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :

```
hmac-sha1
hmac-sha1-96
hmac-sha1-96-etm@openssh.com
hmac-sha1-etm@openssh.com
```

10267 - SSH Server Type and Version Information

Synopsis

An SSH server is listening on this port.

Description

It is possible to obtain information about the remote SSH server by sending an empty authentication request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0933

Plugin Information

Published: 1999/10/12, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

```
SSH version : SSH-2.0-OpenSSH_6.6.1p1 Ubuntu-2ubuntu2.13
SSH supported authentication : publickey,password
```

56984 - SSL / TLS Versions Supported

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/01, Modified: 2023/07/10

Plugin Output

tcp/631/www

This port supports TLSv1.0/TLSv1.1/TLSv1.2.

10863 - SSL Certificate Information

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

Plugin Output

tcp/631/www

Subject Name:

Common Name: ubuntu

Issuer Name:

Common Name: ubuntu

Serial Number: 00 9B 8C 3D A8 5E DB F4 73

Version: 3

Signature Algorithm: SHA-256 With RSA Encryption

Not Valid Before: Oct 29 19:51:36 2020 GMT

Not Valid After: Oct 27 19:51:36 2030 GMT

Public Key Info:

Algorithm: RSA Encryption

Key Length: 2048 bits

Public Key: 00 AF D3 2A 68 22 FC C3 E7 A0 80 71 60 14 54 D8 56 98 66 2B
B0 CA 9A 44 FE 3C 02 F7 5B 0E CA 7A 59 AC 73 52 FB FF A8 5D
99 EF 99 CC 90 51 B4 AD 93 F7 67 21 9B 25 B8 F1 EB 14 53 4B
D8 04 0A 3E 1D 1F 95 4D EE AC E5 03 02 E8 B4 F1 A1 CD F5 2E
EC C9 7A 9D 10 25 E5 62 E9 02 40 47 88 F5 77 69 90 6E 20 DD
D8 B1 E6 13 29 68 03 8C 83 8E F3 1B A5 9B 4F 9E 1E D4 84 D7
96 E0 27 15 19 60 DC 18 64 96 E0 E9 F8 AA FA 02 4E 9D 1E C7
69 BF F1 6C BA 92 38 0F B6 23 F3 66 07 98 C4 6C 6C E2 97 F6
29 96 86 76 AE B8 8F FA E2 3D 02 17 E7 B1 0D 35 9A F0 14 91
AD A4 C6 F1 BA 93 02 64 3B 10 31 3E 11 57 29 BD C9 D6 38 54
5B 44 AC 06 7C 51 AE 46 44 DD 73 D8 9F 91 6E B0 97 62 5A 1B

```
D8 97 F2 3E 85 0C 9B 0E C5 FC D0 22 EF 72 8D E2 D3 D9 05 AF
C4 11 00 14 7C CF 5F 90 0A 8C 89 63 8C FC 79 C5 79
Exponent: 01 00 01
```

Signature Length: 256 bytes / 2048 bits

```
Signature: 00 3E 6D 9B F1 0A B1 94 8C 8D 98 CB 2F 03 86 93 70 AD 12 01
2E AB BB 85 B7 38 A4 20 0F 3F 48 E9 86 E6 77 70 11 23 D5 D6
14 EF BB 5D 24 8F AA 3B 82 04 C2 38 BC B1 F7 92 23 6B 42 49
4F 0E 33 88 86 F4 9A 6A DD 85 60 EE 4F B2 0A 9D 47 01 27 CB
74 6A 2A B9 DC 11 10 14 DF D0 E5 B8 B0 77 C8 DF 5A 7B 5E 6B
31 6D A7 69 A3 19 99 D7 16 61 0A 89 E4 BE F5 55 A7 6C F2 2B
80 4A B9 92 DD C7 76 F9 58 15 D7 80 EF C8 30 C0 35 92 C6 88
AA 91 E9 94 DC 1F 15 B8 28 EE AA 2B 4D 5F 62 2F CB D0 C1 3B
E4 FA C5 A7 39 47 08 52 83 FC 64 4E A6 8B E2 99 A5 BE 59 D1
E9 E4 11 51 93 58 E1 78 25 7F B3 9E 57 DB 61 22 A2 06 19 [...]
```

70544 - SSL Cipher Block Chaining Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Cipher Block Chaining ciphers, which combine previous blocks with subsequent ones.

Description

The remote host supports the use of SSL ciphers that operate in Cipher Block Chaining (CBC) mode. These cipher suites offer additional security over Electronic Codebook (ECB) mode, but have the potential to leak information if used improperly.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

<http://www.nessus.org/u?cc4a822a>

<https://www.openssl.org/~bodo/tls-cbc.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/22, Modified: 2021/02/03

Plugin Output

tcp/631/www

Here is the list of SSL CBC ciphers supported by the remote server :

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)	
AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC(256)	

CAMELLIA128-SHA SHA1	0x00, 0x41	RSA	RSA	Camellia-CBC(128)
CAMELLIA256-SHA SHA1	0x00, 0x84	RSA	RSA	Camellia-CBC(256)
RSA-AES128-SHA256 SHA256	0x00, 0x3C	RSA	RSA	AES-CBC(128)
RSA-AES256-SHA256 SHA256	0x00, 0x3D	RSA	RSA	AES-CBC(256)

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

21643 - SSL Cipher Suites Supported

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffced>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/06/05, Modified: 2024/09/11

Plugin Output

tcp/631/www

Here is the list of SSL ciphers supported by the remote server :
Each group is reported per SSL Version.

SSL Version : TLSv12

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	

SHA1

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)	
AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC(256)	
CAMELLIA128-SHA	0x00, 0x41	RSA	RSA	Camellia-CBC(128)	
CAMELLIA256-SHA	0x00, 0x84	RSA	RSA	Camellia-CBC(256)	

SHA1

RSA-AES128-SHA256 SHA256	0x00, 0x3C	RSA	RSA	AES-CBC(128)
RSA-AES256-SHA256 SHA256	0x00, 0x3D	RSA	RSA	AES-CBC(256)

SSL Version : TLSv11

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DES-CBC3-SHA SHA1	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
AES128-SHA	0x00, 0x2F	RSA [...]			

156899 - SSL/TLS Recommended Cipher Suites

Synopsis

The remote host advertises discouraged SSL/TLS ciphers.

Description

The remote host has open SSL/TLS ports which advertise discouraged cipher suites. It is recommended to only enable support for the following cipher suites:

TLSv1.3:

- 0x13,0x01 TLS13_AES_128_GCM_SHA256
- 0x13,0x02 TLS13_AES_256_GCM_SHA384
- 0x13,0x03 TLS13_CHACHA20_POLY1305_SHA256

TLSv1.2:

- 0xC0,0x2B ECDHE-ECDSA-AES128-GCM-SHA256
- 0xC0,0x2F ECDHE-RSA-AES128-GCM-SHA256
- 0xC0,0x2C ECDHE-ECDSA-AES256-GCM-SHA384
- 0xC0,0x30 ECDHE-RSA-AES256-GCM-SHA384
- 0xCC,0xA9 ECDHE-ECDSA-CHACHA20-POLY1305
- 0xCC,0xA8 ECDHE-RSA-CHACHA20-POLY1305

This is the recommended configuration for the vast majority of services, as it is highly secure and compatible with nearly every client released in the last five (or more) years.

See Also

https://wiki.mozilla.org/Security/Server_Side_TLS

<https://ssl-config.mozilla.org/>

Solution

Only enable support for recommended cipher suites.

Risk Factor

None

Plugin Information

Published: 2022/01/20, Modified: 2024/02/12

Plugin Output

tcp/631/www

The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)	
SHA1					
AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC(256)	
SHA1					
CAMELLIA128-SHA	0x00, 0x41	RSA	RSA	Camellia-CBC(128)	
SHA1					
CAMELLIA256-SHA	0x00, 0x84	RSA	RSA	Camellia-CBC(256)	
SHA1					
RSA-AES128-SHA256	0x00, 0x3C	RSA	RSA	AES-CBC(128)	
SHA256					
RSA-AES256-SHA256	0x00, 0x3D	RSA	RSA	AES-CBC(256)	
SHA256					

The fields above are :

{Tenable ciphertype}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

25240 - Samba Server Detection

Synopsis

An SMB server is running on the remote host.

Description

The remote host is running Samba, a CIFS/SMB server for Linux and Unix.

See Also

<https://www.samba.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2022/10/12

Plugin Output

tcp/445/cifs

The remote host tries to hide its SMB server type by changing the MAC address and the LAN manager name.

However by sending several valid and invalid RPC requests it was possible to fingerprint the remote SMB server as Samba.

104887 - Samba Version

Synopsis

It was possible to obtain the samba version from the remote operating system.

Description

Nessus was able to obtain the samba version from the remote operating by sending an authentication request to port 139 or 445. Note that this plugin requires SMB1 to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/11/30, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The remote Samba Version is : Samba 4.3.11-Ubuntu
```

96982 - Server Message Block (SMB) Protocol Version 1 Enabled (uncredentialed check)

Synopsis

The remote Windows host supports the SMBv1 protocol.

Description

The remote Windows host supports Server Message Block Protocol version 1 (SMBv1). Microsoft recommends that users discontinue the use of SMBv1 due to the lack of security features that were included in later SMB versions. Additionally, the Shadow Brokers group reportedly has an exploit that affects SMB; however, it is unknown if the exploit affects SMBv1 or another version. In response to this, US-CERT recommends that users disable SMBv1 per SMB best practices to mitigate these potential issues.

See Also

<https://blogs.technet.microsoft.com/filecab/2016/09/16/stop-using-smb1/>

<https://support.microsoft.com/en-us/help/2696547/how-to-detect-enable-and-disable-smbv1-smbv2-and-smbv3-in-windows-and>

<http://www.nessus.org/u?8dcab5e4>

<http://www.nessus.org/u?234f8ef8>

<http://www.nessus.org/u?4c7e0cf3>

Solution

Disable SMBv1 according to the vendor instructions in Microsoft KB2696547. Additionally, block SMB directly by blocking TCP port 445 on all network boundary devices. For SMB over the NetBIOS API, block TCP ports 137 / 139 and UDP ports 137 / 138 on all network boundary devices.

Risk Factor

None

References

XREF IAVT:0001-T-0710

Plugin Information

Published: 2017/02/03, Modified: 2020/09/22

Plugin Output

tcp/445/cifs

The remote host supports SMBv1.

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

tcp/21/ftp

```
An FTP server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

tcp/22/ssh

```
An SSH server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

tcp/80/www

A web server is running on this port.

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

tcp/631/www

A TLSv1 server answered on this port.

tcp/631/www

A web server is running on this port through TLSv1.

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

tcp/3306/mysql

A MySQL server is running on this port.

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

tcp/8080/www

A web server is running on this port.

11153 - Service Detection (HELP Request)

Synopsis

The remote service could be identified.

Description

It was possible to identify the remote service by its banner or by looking at the error message it sends when it receives a 'HELP' request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/11/18, Modified: 2024/11/19

Plugin Output

tcp/3500/www

A web server seems to be running on this port.

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

121010 - TLS Version 1.1 Protocol Detection

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.1.

TLS 1.1 lacks support for current and recommended cipher suites.

Ciphers that support encryption before MAC computation, and authenticated encryption modes such as GCM cannot be used with TLS 1.1

As of March 31, 2020, Endpoints that are not enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

<http://www.nessus.org/u?c8ae820d>

Solution

Enable support for TLS 1.2 and/or 1.3, and disable support for TLS 1.1.

Risk Factor

None

References

XREF CWE:327

Plugin Information

Published: 2019/01/08, Modified: 2023/04/19

Plugin Output

tcp/631/www

```
TLSv1.1 is enabled and the server supports at least one cipher.
```

110723 - Target Credential Status by Authentication Protocol - No Credentials Provided

Synopsis

Nessus was able to find common ports used for local checks, however, no credentials were provided in the scan policy.

Description

Nessus was not able to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials. There may have been a protocol failure that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may be invalid. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.
- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0504

Plugin Information

Published: 2018/06/27, Modified: 2024/04/19

Plugin Output

tcp/0

```
SSH was detected on port 22 but no credentials were provided.  
SSH local checks were not enabled.
```


10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2023/12/04

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.17.0.2 to 172.16.16.131 :  
172.17.0.2  
172.17.0.1  
172.16.16.131
```

```
Hop Count: 2
```

135860 - WMI Not Available

Synopsis

WMI queries could not be made against the remote host.

Description

WMI (Windows Management Instrumentation) is not available on the remote host over DCOM. WMI queries are used to gather information about the remote host, such as its current state, network interface configuration, etc.

Without this information Nessus may not be able to identify installed software or security vulnerabilities that exist on the remote host.

See Also

<https://docs.microsoft.com/en-us/windows/win32/wmisdk/wmi-start-page>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2020/04/21, Modified: 2025/02/12

Plugin Output

tcp/445/cifs

```
Can't connect to the 'root\CIMV2' WMI namespace.
```

Synopsis

The remote web server contains a graphic image that is prone to information disclosure.

Description

The 'favicon.ico' file found on the remote web server belongs to a popular web server. This may be used to fingerprint the web server.

Solution

Remove the 'favicon.ico' file or create a custom one for your site.

Risk Factor

None

Plugin Information

Published: 2005/10/28, Modified: 2020/06/12

Plugin Output

tcp/8080/www

```
MD5 fingerprint : ed7d5c39c69262f4ba95418d4f909b10
Web server      : jetty 5.1.14
```

10150 - Windows NetBIOS / SMB Remote Host Information Disclosure

Synopsis

It was possible to obtain the network name of the remote host.

Description

The remote host is listening on UDP port 137 or TCP port 445, and replies to NetBIOS nbtscan or SMB requests.

Note that this plugin gathers information to be used in other plugins, but does not itself generate a report.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2021/02/10

Plugin Output

tcp/445/cifs

The following 2 NetBIOS names have been gathered :

UBUNTU	= Computer name
UBUNTU	= Workgroup / Domain name