

General_plotting

October 3, 2019

1 Making publication ready plots with Matplotlib

Matplotlib makes it easy to make quick plots in python, unfortunately the default style is very ugly and is not publication ready. The good news is it has become much easier to customize in the past few years.

1.1 Packages being used

- matplotlib: all the plotting is done here
- astropy: has an override for the histogram function for finding bin widths

1.2 Relevant documentation

- matplotlib: http://matplotlib.org/3.1.1/api/pyplot_summary.html,
<http://matplotlib.org/users/customizing.html>, <http://matplotlib.org/gallery.html>,
http://matplotlib.org/examples/color/colormaps_reference.html
- astropy: <http://docs.astropy.org/en/stable/visualization/histogram.html>

```
[1]: import matplotlib as mpl
from matplotlib import pyplot as plt
import numpy as np
from astropy.visualization import hist
%matplotlib inline

mpl.style.use('classic')
```

1.3 Make some test data to plot

To test out various plots lets create some fake data sets.

1.3.1 1D data set

```
[2]: # generate some complicated data
rng = np.random.RandomState(0)
one_d = np.concatenate([-5 + 1.8 * rng.standard_cauchy(500),
                        -4 + 0.8 * rng.standard_cauchy(2000),
                        -1 + 0.3 * rng.standard_cauchy(500),
```

```

                2 + 0.8 * rng.standard_cauchy(1000),
                4 + 1.5 * rng.standard_cauchy(1000)])

# truncate to a reasonable range
one_d = one_d[(one_d > -15) & (one_d < 15)]

```

1.3.2 2D image

```

[3]: x_img = np.arange(0, np.pi, 0.1)
     y_img = np.arange(0, 2*np.pi, 0.1)
     X_img, Y_img = np.meshgrid(x_img, y_img)
     image = np.cos(X_img) * np.sin(Y_img) * 10

```

1.3.3 2D line

```

[4]: x = np.arange(10)
     y = np.zeros(10)

```

1.3.4 2D scatter

```

[5]: n = 100000
     x_scatter = np.random.standard_normal(n)
     y_scatter = 2 + 3 * x_scatter + 4 * np.random.standard_normal(n)

```

2 The Old Defaults (and why they are bad)

Lets take a look at matplotlib's default styles for these types of plots


2.1 Histograms

This example also shows how to create subplots using GridSpec (see <http://matplotlib.org/users/gridspec.html>), change the figure size, and how to use latex in your labels.

```

[6]: plt.figure(1, figsize=(8, 5))
     ax1 = plt.subplot2grid((1, 2), (0, 0))
     ax1.hist(one_d, bins=10, density=True)
     ax1.set_xlabel(r'$\sigma$')
     ax1.set_ylabel(r'$P(\sigma)$')
     ax2 = plt.subplot2grid((1, 2), (0, 1))
     ax2.hist(one_d, bins=200, density=True)
     ax2.set_xlabel(r'$\sigma$')
     ax2.set_ylabel(r'$P(\sigma)$')
     # make sure subplots don't overlap
     plt.tight_layout();

```




2.1.1 Issues

- bins size needs to be set “by eye”
- each bin is drawn as a filled rectangle
- font size is small
- tick size is small
- lines are too thin

2.2 Images

```
[7]: plt.figure(2)
plt.imshow(image)
plt.xlabel('x')
plt.ylabel('y')
cbar = plt.colorbar()
cbar.set_label('z');
```




2.2.1 issues

- color map is about as bad as it gets (e.g. <https://eagereyes.org/basics/rainbow-color-map>, <http://bids.github.io/colormap/>)
- font size is small
- tick size is small
- lines are too thin

2.3 Line plots

For this example we will show a set of horizontal lines that are all labeled.

```
[10]: plt.figure(3)
      for i in range(7):
          plt.plot(x, y + i, label='{0}'.format(i))
      plt.xlabel('x')
      plt.ylabel('y')
      plt.ylim(-1, 7)
      plt.legend();
```




2.3.1 issues

- colors are harsh on the eyes
- font size is small
- tick size is small
- lines are too thin
- legend could be formatted better

2.4 2D scatter plots

```
[11]: plt.figure(4)
plt.plot(x_scatter, y_scatter, 'o')
plt.xlabel('x')
plt.ylabel('y');
```



2.4.1 issues

- there is no useful information contained in the high density regions
- font size is small
- tick size is small
- lines are too thin

3 Doing things better


The easiest way to make consistent plots is to define a new `matplotlib` style in its own `.py` file and import it every time you want to plot some data. Included in with these notebooks is an example style file `mpl_style.py` that increases line widths, increases font sizes, uses a better color cycle, formats ticks and axes larger, and sets to default colormap to something reasonable (`magma`, `plasma`, `inferno`, and `viridis` are all color blind friendly and convert to black and white without issue).

```
[12]: mpl.style.use('default')
import mpl_style
plt.style.use(mpl_style.style1)
```

3.1 Histograms


`astropy.visualization` has a wrapper for the default `hist` function that will automatically pick the bin width based on the data. Additionally we will add some keywords to make the histogram look better.

```
[14]: plt.figure(5, figsize=(10, 5))
ax1 = plt.subplot2grid((1, 2), (0, 0))
hist(one_d, bins='scott', ax=ax1, density=True, histtype='step', lw=1.5)
ax1.set_title("bins='scott'")
ax1.set_xlabel(r'$\sigma$')
ax1.set_ylabel(r'$P(\sigma)$')
ax2 = plt.subplot2grid((1, 2), (0, 1))
hist(one_d, bins='blocks', ax=ax2, density=True, histtype='step', lw=1.5)
ax2.set_title("bins='blocks'")
ax2.set_xlabel(r'$\sigma$')
ax2.set_ylabel(r'$P(\sigma)$')
# make sure subplots don't overlap
plt.tight_layout()
```




3.2 Images

```
[15]: plt.figure(6, figsize=(3, 6))
plt.imshow(image)
plt.xlabel('x')
plt.ylabel('y')
cbar = plt.colorbar()
cbar.set_label('z')
```



Since this image is symmetrical about 0, it would be best if we use a diverging colorbar (**note** if the data was not symmetric you can use the `vmin` and `vmax` keywords to make the color scale symmetric.):


```
[16]: plt.figure(7, figsize=(3, 6))
plt.imshow(image, cmap=plt.cm.RdBu, vmin=-10, vmax=10)
plt.xlabel('x')
plt.ylabel('y')
cbar = plt.colorbar()
cbar.set_label('z')
```

3.3 Line plots

Adding a few more keywords to the legend and slightly adjusting the plot range we can make it look much better:


```
[17]: plt.figure(8, figsize=(10, 6))
      for i in range(10):
          plt.plot(x, y + i, label='{0}'.format(i))
      plt.xlabel('x')
      plt.ylabel('y')
      plt.ylim(-3.5, 10)
      plt.legend(loc='lower center', ncol=5);
```



3.4 2D scatter plots

Since the goal of this plot is to show density we should plot it as a 2D-histogram instead of scatter points. To avoid various binning issues I recommend using hexbin and a colormap that is white at 0:

```
[18]: plt.figure(9)
plt.hexbin(x_scatter, y_scatter, gridsize=50, mincnt=1, cmap=plt.cm.Blues,
           zorder=-1)
plt.xlabel('x')
plt.ylabel('y')
cbar = plt.colorbar()
cbar.set_label('Count');
```



Note If you want to make a density plot that keeps the outliers as scatter points check out the matplotlib extension I wrote: <https://github.com/CKrawczyk/densityplot>

4 Saving a figure

To save the current figure using the `plt.savefig(<filename>)` command. For data analysis .png are fine, for publication .pdf will be needed. **Note** if you have a large number of objects drawn (e.g. scatter points) in a figure the .pdf will be slow to open since everything is saved in vector format. In these cases I would recommend rasterizing as many of the objects as you can (e.g. the scatter points) but leaving the axes as vectors. This can be done by setting the axes rasterization zorder via `plt.gca().set_rasterization_zorder(1)`, any object with `zorder<1` will be rasterized, and all other object (including the axes) will be vectorized.

Rasterization can also be used to “trick” .eps and .ps file formats to using transparency: <https://osxastrotricks.wordpress.com/2014/01/19/rasterized-graphics-with-matplotlib-to-preserve-plot-transparencies-for-apj-figures/>

5 Tips and tricks

- whenever possible don’t put plotting commands inside a loop, each time a new command is called the entire figure is redrawn, meaning each pass through the loop will take longer

than the previous pass. Instead you can pass the plot function 2D arrays and each *column* will be plotted as a different line.

- change marker face colors and marker edge colors with the `mfc` and `mec` keywords
- change the line style and line width with the `ls` and `lw` keywords
- use the `alpha` keyword to set transparency
- use the `zorder` keyword to control what objects are plotted on top
- turn on minor tick marks with `plt.minorticks_on()`
- set custom tick positions and labels using `plt.xticks()` and `plt.yticks()`
- use interactive mode with `plt.ion()` (the `plt.show()` command is not input blocking, **note** currently dose not work on macs)
- get the current figure object with `plt.gcf()`
- get the current axes object with `plt.gca()`
- clear the current figure with `plt.clf()`
- reverse an axis with `plt.gca().invert_xaxis()` or `plt.gca().invert_yaxis()`
- make log plots with `plt.semilogx()`, `plt.semilogy()`, or `plt.loglog()`
- plot error bars with `plt.errorbar()`
- get ideas and examples from the matplotlib gallery: <http://matplotlib.org/gallery.html>
- get a list of all the available plot functions: https://matplotlib.org/3.1.1/api/pyplot_summary.html
- get a list of all available colormaps: http://matplotlib.org/examples/color/colormaps_reference.html

[]: