

ECE 5725 Embedded Operating Systems Lecture 11

Prof. Joseph F. Skovira



Lab 2 Week 1

Homework 2

Lab 1 Report

Debug...



print

input

Convert to str

Convert to int

Concatenate strings



Performance Monitoring with Linux Perf

Two Subsystems


SYSCALL

User space tools

Perf installed in kernel

Only need to install perf executable







Event number	Event mnemonic	PMUEVENTx[24:0] bus ^{ex}	PMU event bus (to trace)**	Event name	
SW_INCR			[0]	Instruction architecturally executed (condition check pass) - Software increment	
0x01	L1I_CACHE_REFILL	[0]	[1]	Level 1 instruction cache refill	
0x02	L11_TLB_REFILL	[1]	[2]	Level 1 instruction TLB refill	
0x03	L1D_CACHE_REFILL	[2]	[3]	Level 1 data cache refill	
0x04	L1D_CACHE		[5:4]	Level 1 data cache access	
0x05	L1D_TLB_REFILL	-	[7:6]	Level 1 data TLB refill	
0x08	INST_RETIRED	[6:3]	[11:8]	Instruction architecturally executed	
0x09	EXC_TAKEN	[7]	[12]	Exception taken	
0×0A	EXC_RETURN	[8]	[13]	Instruction architecturally executed (condition check pass) - Exception return	
0x0B	CID_WRITE_RETIRED	-	[14]	Instruction architecturally executed (condition check pass) - Write to CONTEXTIDR	
0x10	BR_MIS_PRED	[9]	[15]	Mispredicted or not predicted branch speculatively executed	
0x11	CPU_CYCLES	-	[16]	Cycle	
0x12	BR_PRED	[10]	[17]	Predictable branch speculatively executed	
0x13	MEM_ACCESS	- 1	[19:18]	Data memory access	
0x14	L11_CACHE	[11]	[20]	Level 1 instruction cache access	
0x15	L1D_CACHE_WB	[12]	[21]	Level 1 data cache Write-Back	
0x16	L2D_CACHE	-7	[23:22]	Level 2 data cache access	
0x17	L2D_CACHE_REFILL	[13]	[24]	Level 2 data cache refill	
0x18	L2D_CACHE_WB	[14]	[25]	Level 2 data cache Write-Back	
0x19	BUS_ACCESS		[27:26]	Bus access	
0x1A	MEMORY_ERROR	- 1	[28]	Local memory error	
0x1B	INST_SPEC	-	[30:29]	Operation speculatively executed	

Joseph Skovira, 2021



Performance Monitoring with Linux Perf

stat

record


report

top



GPIO

GPIO#	2nd func	pin#		pin#	2nd func	GPIO#		
N/A	+3V3	1		2	+5V	N/A		
GPIO2	SDA1 (I2C)	3		4	+5V	N/A		
GPIO3	SCL1 (I2C)	5		6	GND	N/A		
GPIO4	GCLK	7		8	TXD0 (UART)	GPIO14		
N/A	GND	9		10	RXD0 (UART)	GPIO15		
GPIO17	GEN0	11		12	GEN1	GPIO18		
GPIO27	GEN2	13		14	GND	N/A		
GPIO22	GEN3	15		16	GEN4	GPIO23		
N/A	+3V3	17		18	GEN5	GPIO24		
GPIO10	MOSI (SPI)	19		20	GND	N/A		
GPIO9	MISO (SPI)	21		22	GEN6	GPIO25		
GPIO11	SCLK (SPI)	23		24	CE0_N (SPI)	GPIO8		
N/A	GND	25		26	CE1_N (SPI)	GPIO7		
(Models A and B stop here)								
EEPRO M	ID_SD	27		28	ID_SC	EEPRO M		
GPIO5	N/A	29		30	GND	N/A		
GPIO6	N/A	31		32	-	GPIO12		
GPIO13	N/A	33		34	GND	N/A		
GPIO19	N/A	35		36	N/A	GPIO16		
GPIO26	N/A	37		38	Digital IN	GPIO20		
N/A	GND	39		40	Digital OUT	GPIO21		





GPIO Events

Polling on GPIO events

Interrupt on GPIO event
GPIO Edge Detection
Trigger python on an event



```
import RPi.GPIO as GPIO
GPIO.setmode(GPIO.BCM)

GPIO.setup(26, GPIO.IN, pull_up_down=GPIO.PUD_UP)

Try:
    print "Waiting for falling edge on port 26"
    GPIO.wait_for_edge(26, GPIO.FALLING)
    print "Falling edge detected on port 26"

except KeyboardInterrupt:
    GPIO.cleanup() # clean up GPIO on CTRL+C exit

GPIO.cleanup() # clean up GPIO on normal exit
```



GPIO threaded callback interrupt

Initialize GPIO

Setup a callback routine

Connect callback to GPIO



```
import RPi.GPIO as GPIO
GPIO.setmode(GPIO.BCM)
GPIO.setup(19, GPIO.IN, pull up down=GPIO.PUD UP)
def GPIO19_callback(channel):
  print "falling edge detected on 19"
# " main" part of the program
GPIO.add_event_detect(19, GPIO.FALLING, callback=GPIO19_callback)
# Continue on with main processing
    Background code goes here...
#
                   # clean up GPIO on normal exit
GPIO.cleanup()
```



GPIO threaded callback interrupt

More than one interrupt?

Multiple threaded callbacks



```
import RPi.GPIO as GPIO
Import subprocess
GPIO.setmode(GPIO.BCM)
GPIO.setup(19, GPIO.IN, pull up down=GPIO.PUD UP)
GPIO.setup(13, GPIO.IN, pull up down=GPIO.PUD UP)
def GPIO19 callback(channel):
  print "falling edge detected on 19"
def GPIO13 callback(channel):
 cmd = 'echo "pause" '
 subprocess.check output(cmd, shell=True)
# " main" part of the program
GPIO.add event detect(19, GPIO.FALLING, callback=GPIO19 callback)
GPIO.add event detect(13, GPIO.FALLING, callback=GPIO13 callback)
# Continue on with main processing – Background code....
GPIO.cleanup()
                    # clean up GPIO on normal exit
```



```
import RPi.GPIO as GPIO
Import subprocess
GPIO.setmode(GPIO.BCM)
GPIO.setup(19, GPIO.IN, pull up down=GPIO.PUD UP)
GPIO.setup(13, GPIO.IN, pull up down=GPIO.PUD UP)
GPIO.setup(26, GPIO.IN, pull up down=GPIO.PUD UP)
def GPIO19 callback(channel):
  print "falling edge detected on 19"
def GPIO13 callback(channel):
 cmd = 'echo "pause" '
 subprocess.check output(cmd, shell=True)
# " main" part of the program
GPIO.add event detect(19, GPIO.FALLING, callback=GPIO19 callback, bouncetime=300)
GPIO.add event detect(13, GPIO.FALLING, callback=GPIO13 callback, bouncetime=300)
Try:
   print "Waiting for falling edge on port 26"
   GPIO.wait for edge(26, GPIO.FALLING)
   print "Falling edge detected on port 26"
 except KeyboardInterrupt:
   GPIO.cleanup() # clean up GPIO on CTRL+C exit
                     # clean up GPIO on normal exit
GPIO.cleanup()
```