CS22510 Assignment 1 Runners and Riders "Out and About"

Chris Savill chs17@aber.ac.uk
March 20, 2013

Contents

1	Description of three programs 1.1 Event Creation Program	3 3 3
2	Code for the Event Creation Program2.1 Header files2.2 Cpp files	3 3
3	Clean build and compilation of Event Creation Program	17
4	Run through of Event Creation Program	18
5	Files created by execution of Event Creation Program	22
6	Code for Checkpoint Manager Program	22
7	Clean build and compilation of Checkpoint Program	50
8	Run through of Checkpoint Manager Program	51
9	Files created by execution of Checkpoint Manager Program	54
10	Clean build and compilation of Event Manager Program	56
11	Run through of Event Manager Program	58
12	Results list produced at the end of an event 12.1 Results of successful competitors	73 73 76
13	Log file contents	77

1 Description of three programs

- 1.1 Event Creation Program
- 1.2 Checkpoint Manager Program
- 1.3 Event Manager Program
- 2 Code for the Event Creation Program
- 2.1 Header files

Listing 1: Header file for non-class specific functions.

```
* Author: Chris Savill, chs17@aber.ac.uk
3
    * File Name: creator.h
    * Description: Header file for the starter function declarations.
4
    * First Created: 11/03/2013
5
6
    * Last Modified: 14/03/2013
7
8
9
   #ifndef CREATOR_H
10
   #define CREATOR_H
11
12
   #include <memory>
   #include "event.h"
13
14
15
   bool get_acceptance(); //Function to get the user's input for accepting or
      rejecting their inputs.
   bool checkCourseExists(char letter, Event *event); //Member function that
16
      checks if the letter given be the user matches any of the course letters.
   void ecp_menu(Event *event); //Function that launches the event creation
17
      program menu.
19 #endif /* CREATOR_H */
```

Listing 2: Header file Event class.

```
2
    * Author: Chris Savill, chs17@aber.ac.uk
    * File Name: event.h
 3
    * Description: Header file for the Event class.
4
 5
    * First Created: 11/03/2013
 6
    * Last Modified: 14/03/2013
 7
8
   #ifndef EVENT_H
9
10
   #define EVENT_H
11
12
   #include <memory>
   #include "competitor.h"
13
   #include "course.h"
14
   #include <vector>
15
16
   #include <cstdlib>
   #include <iostream>
17
18
19
   #define MAX_EVENT_NAME_LENGTH 79
20
   #define MAX_DATE_LENGTH 19
21
```

```
class Competitor;
22
23
   class Course;
24
25
   class Event {
26
   private:
27
       std::string name; //Name of the event.
28
       std::string date; //Date of the event.
29
       std::string start_time; //Start time of the event.
30
       std::vector<Competitor*> *competitors; //Array of competitors to take
          part in the event.
31
       std::vector<Course*> *courses; //Array of courses that are part of an
           event.
32
33
       void set_name(); //Member function to get the user to input the events
       void set_date(); //Member function to get the user to input the date of
34
           the event.
35
       void set_start_time(); //Member function to get the user to input the
          start time of the event.
36
37
   public:
38
       Event();
39
       ~Event();
40
       std::vector<Course*>* getCourses(); //Member function that returns a
          pointer to the vector of courses.
       void add_competitor(); //Member function that will handle adding a
41
           competitor to the event.
42
       void add_course(); //Member function that will handle adding a course to
            the event.
43
       void export_event(); //Member function that will handle exporting the
          name, date and start\_time of the event to a '.txt' file.
       void export_competitors(); //Member function that will handle the
44
           exporting of the array of competitors to a '.txt' file.
       void export_courses(); //Member function that will handle the exporting
45
           of the array of courses to a '.txt' file.
46
   };
47
48 | #endif /* EVENT_H */
```

Listing 3: Header file for Course class.

```
1
 2
    * Author: Chris Savill, chs17@aber.ac.uk
 3
    * File Name: course.h
 4
    * Description: Header file for the Course class.
    * First Created: 11/03/2013
 5
 6
    * Last Modified: 14/03/2013
 7
    */
 8
9
   #ifndef COURSE_H
10
   #define COURSE_H
11
12
   #include <memory>
13
   #include <vector>
14
15
   class Event;
16
17
   class Course {
   private:
18
       char letter; //The courses unique identification letter for an event.
19
20
       int number_of_nodes; // The number of nodes the course contains.
21
       std::vector<int> *nodes; //An array of nodes that are contained in the
```

```
course.
22
       std::vector<int> *nodes_available; //An array of nodes that are
           available to select from, read in from the 'nodes.txt' file.
23
       void set_letter(Event *event); //Member function that will set the
24
           letter of the course.
       void set_number_of_nodes(); //Member function that will set the number
25
           of nodes of the course.
26
       bool read_nodes_available(); //Member function that reads in the nodes
          from the 'nodes.txt' file and adds them to the nodes available array.
27
       void add_node(); //Member function that adds a new node to the course.
28
       bool duplicated_last_node(int number); //Member function to check if the
            new node being selected matches the last node added.
       bool check_node_exists(int number); //Member function that checks that
29
           the node being added exists in the array of nodes available.
30
31
   public:
32
       char get_letter(); //Member function to return a course's letter.
33
       int get_number_of_nodes(); //Member function to return a course's number
            of nodes.
       int get_node(int index); //Member function to return a node from the
34
           course's vector of nodes.
35
       Course(Event *event);
       ~Course();
36
   };
37
38
39 | #endif /* COURSE_H */
```

Listing 4: Header file for Competitor class.

```
1
 2
    * Author: Chris Savill, chs17@aber.ac.uk
 3
    * File Name: competitor.h
    * Description: Header file for the Competitor class.
 4
    * First Created: 11/03/2013
 5
    * Last Modified: 14/03/2013
 6
 7
    */
 8
 9
   #ifndef COMPETITOR_H
   #define COMPETITOR_H
10
11
12
   #include <memory>
13
   #include <string>
14
   #define MAX_COMPETITOR_NAME_LENGTH 51 //Includes null terminator \0.
15
16
17
   class Event;
18
19
   class Competitor {
20
   private:
21
       int number; // The competitor's unique identification number for an event
22
       std::string name; //The competitor's name.
23
       char course; //The course letter the competitor is entering in for.
24
25
       void set_number(int number); //Member function that will set the number
           of the competitor.
       void set_name(); //Member function that will set the name of the
26
           competitor.
       void set_course(Event *event); //Member function that will set the
27
           course letter for the competitor.
28
```

```
public:
    int get_number(); //Member function to return a competitor's number.
    std::string get_name(); //Member function to return a competitor's name.
    char get_course(); //Member function to return a competitor's course.
    Competitor(int number, Event *event);
};

#endif /* COMPETITOR_H */
```

2.2 Cpp files

Listing 5: Main method and menu file.

```
1 ||
2
    * Author: Chris Savill, chs17@aber.ac.uk
3
    * File Name: main.cpp
    * Description: cpp file that contains function definitions for the start-up
4
        of the event creation program.
    * First Created: 11/03/2013
5
6
    * Last Modified: 14/03/2013
7
8
   #include "creator.h"
9
   #include <iostream>
10
11
   #include <cstdlib>
   #include <limits>
12
13
14
   using namespace std;
15
16
   /* Main function that just calls a function that takes over. */
   int main(int argc, char** argv) {
17
18
       Event *event = new Event();
19
       ecp_menu(event);
20
21
       return 0;
22
   }
23
24
   /* Function to get the user's input for accepting or rejecting their inputs.
25
   bool get_acceptance() {
26
       char option;
27
28
       do {
           cout << "If yes press 'y' then 'Enter'" << endl << "If no press 'n'</pre>
29
              then 'Enter'" << endl;
30
           cin.clear();
31
           option = cin.get();
32
           cin.ignore(numeric_limits < streamsize >:: max(), '\n');
33
           if (option == 'y') return true;
34
35
           else if (option == 'n') return false;
36
           else cout << "Invalid option selected" << endl;</pre>
37
       } while (option != 'y' && option != 'n');
38
39
   \slash * Function that displays the main menu for the event creation program. */
40
41
   void ecp_menu(Event *event) {
42
       int option; //Field to store the user's option input.
43
44
       do {
           45
              << endl;
```

```
46
          cout << "* Runners and Riders Event Creation Program Main Menu *"</pre>
              << end1;
           47
             << endl;
           cout << "*
                                 1. Add Competitor to Event
48
             << endl;
49
           cout << "*
                                  2. Add Course to Event
                                                                         * "
             << end1;
           cout << "*
                                 3. Export Event to File
50
             << endl;
           cout << "*
                                 4. Export Competitors to File
                                                                         * "
51
             << endl;
52
           cout << "*
                                 5. Export Courses to File
             << end1;
53
           cout << "*
                                 6. Exit Event Creation Program
             << endl;
           54
             << endl << endl;
55
          cout << "Please enter in an option from the above an press 'Enter':</pre>
56
57
          cin.clear();
58
          cin >> option;
59
          cin.ignore();
60
61
           switch (option) {
62
              case 1:
63
                  event->add_competitor();
64
                  break;
65
              case 2:
66
                  event ->add_course();
67
                  break;
68
              case 3:
69
                  event -> export_event();
70
                  break;
71
              case 4:
72
                  event->export_competitors();
73
                  break;
74
              case 5:
75
                  event -> export_courses();
76
                  break;
77
              case 6:
78
                  delete(event);
79
                  cout << "Exiting program..." << endl << endl;</pre>
80
81
              default:
82
                  cout << "Please enter in a valid option." << endl << endl;</pre>
83
84
       } while (option != 6);
85 || }
```

Listing 6: Cpp file for Event class.

```
1  /*
2  * Author: Chris Savill, chs17@aber.ac.uk
3  * File Name: event.cpp
4  * Description: cpp file that contains member function definitions for the event class.
5  * First Created: 11/03/2013
6  * Last Modified: 14/03/2013
7  */
8
```

```
9 # #include "event.h"
10
   #include "creator.h"
11
   #include <iostream>
12
   #include <stdlib.h>
   #include <fstream>
13
14
   #include <sstream>
15
   #include <limits>
16
17
   using namespace std;
18
19
   /* Member function that returns a pointer to the vector of courses. */
20
   vector < Course * > * Event :: getCourses() {
21
       return courses;
22
   }
23
24
   /st Member function to get the user to input the events name. st/
25
   void Event::set_name() {
26
       bool name_chosen = false;
27
       string name;
28
29
       do {
30
            do {
31
                cout << "Please enter in the name for the event (no more than 79</pre>
                    characters): ";
32
                cin.clear();
33
                getline(cin, name);
34
            } while (name.length() > MAX_EVENT_NAME_LENGTH);
35
            cout << endl << "Are you happy with the name: '" << name <<
36
               "'?" << endl;
37
            name_chosen = get_acceptance();
38
       } while (name_chosen == false);
39
40
       this->name = name;
41
   }
42
   /* Member function to get the user to input the date of the event. */
43
44
   void Event::set_date() {
45
       bool date_chosen = false;
46
       string date;
47
       do {
48
49
            do {
                cout << endl << "Please enter in the date for the event</pre>
50
                   (no more than 19 characters): ";
                cin.clear();
51
                getline(cin, date);
52
53
            } while (date.length() > MAX_DATE_LENGTH);
54
            cout << endl << "Are you happy with the date: '" << date <<
55
               "'?" << endl;
            date_chosen = get_acceptance();
56
57
       } while (date_chosen == false);
58
59
       this->date = date;
60
   }
61
62
   /* Member function to get the user to input the start time of the event. */
63
   void Event::set_start_time() {
64
       bool start_time_chosen = false;
65
       bool valid_hours = false;
66
       bool valid_minutes = false;
67
       char input[3];
```

```
68
        int hours;
69
        int minutes;
70
        string start_time;
71
        string string_hours;
72
        string string_minutes;
73
74
        do {
75
            do {
76
                 cout << endl << endl << "Please enter in the start time for the</pre>
                    event with the 24 hour format 'HH: MM', hours first: ";
77
                 cin.clear();
78
                 cin >> input;
79
                 cin.ignore(numeric_limits < streamsize >:: max(), '\n');
                 cout << endl;</pre>
80
81
82
                 if (isdigit(input[0]) && isdigit(input[1])) { //Ensures the
                    input has 2 digits.
83
                     hours = atoi(input); //Converts the digits into an int and
                         stores it in hours.
84
                     if (hours <= 23 && hours >= 00) { //Makes sure that the
85
                        hours are in 24-hour format.
86
                         cout << "Valid hours entered." << endl << endl;</pre>
87
                         valid_hours = true;
                     }
88
89
                 } else cout << "Invalid hours entered, please enter in a value
                    between 00 and 23 inclusive." << endl << endl;
90
            } while (valid_hours == false);
91
92
93
                 cout << endl << "Please now enter in the minutes: ";</pre>
94
                 cin.clear();
95
                 cin >> input;
96
                 cin.ignore(numeric_limits < streamsize >:: max(), '\n');
97
                 cout << endl;</pre>
98
                 if (isdigit(input[0]) && isdigit(input[1])) {
99
100
                     minutes = atoi(input);
101
102
                     if (minutes <= 59 && minutes >= 00) { //Makes sure minutes
                         are valid.
103
                         cout << "Valid minutes entered." << endl << endl;</pre>
104
                         valid_minutes = true;
105
                     }
106
                 } else cout << "Invalid minutes entered, please enter in a value
                     between 00 and 59 inclusive." << endl << endl;
107
            } while (valid_minutes == false);
108
109
             cout << endl << endl << "Are you happy with the start time: '" <<</pre>
                hours << ":" << minutes << "'?" << endl;
             start_time_chosen = get_acceptance();
110
        } while (start_time_chosen == false);
111
112
113
        ostringstream string_retriever; //Converts into strings.
114
        string_retriever << hours;</pre>
115
        string_hours = string_retriever.str();
116
        string_retriever.str(""); //Clears the string stream.
117
        string_retriever << minutes;</pre>
118
        string_minutes = string_retriever.str();
119
120
        start_time = string_hours + ":" + string_minutes; //Concatenates the
            final time into HH:MM format.
121
        this->start_time = start_time;
```

```
122 || }
123
124
    /* Member function that will handle adding a competitor to the event.
125
     * Oparam number The current competitor number.
126
     */
127
    void Event::add_competitor() {
128
        if (courses->empty()) cout << "No courses exist for competitor course
            selection. Please create a course first." << endl << endl;</pre>
129
        else {
            Competitor *competitor = new Competitor((competitors->size() + 1),
130
131
             competitors ->push_back(competitor);
132
             cout << "New competitor added to event." << endl << endl;</pre>
             cout << "Competitor number: " << competitors -> back() -> get_number();
133
134
             cout << "Competitor name: " << competitors -> back() -> get_name() <<</pre>
                endl;
135
             cout << "Course: " << competitors->back()->get_course() << endl;</pre>
136
        }
137
138
139
    /* Member function that will handle adding a course to the event. */
140
    void Event::add_course() {
141
        Course *course = new Course(this);
142
        courses ->push_back(course);
143
        cout << "New course added to event." << endl << endl;</pre>
        cout << "Course letter: " << courses->back()->get_letter() << endl;</pre>
144
        cout << "Number of course nodes: " << courses->back()->
145
            get_number_of_nodes() << endl;</pre>
        cout << "Nodes: " << courses->back()->get_node(0);
146
147
148
        for (int counter = 1; counter < courses->back()->get_number_of_nodes();
            counter++) {
             cout << ", " << courses->back()->get_node(counter);
149
150
        }
151
152
        cout << endl << endl;</pre>
153
154
155
    /st Member function that will handle exporting the name, date and start_time
        of the event to a '.txt' file. */
156
    void Event::export_event() {
157
        ofstream competitors_file;
158
        competitors_file.open("name.txt", ios::out);
159
160
        if (competitors_file.is_open()) {
             competitors_file << this->name << "\n" << this->date << "\n" << this
161
                ->start_time;
162
             competitors_file.close();
163
             cout << "Event successfully exported to 'name.txt'." << endl << endl</pre>
164
        } else cout << "File 'name.txt' could not be written." << endl;</pre>
165
166
167
    /* Member function that will handle the exporting of the array of
        competitors to a '.txt' file. */
    void Event::export_competitors() {
168
169
        if (competitors -> empty()) cout << "No competitors to export. Exporting
            cancelled." << endl << endl;</pre>
170
        else {
171
             ofstream competitors_file;
172
             competitors_file.open("entrants.txt", ios::out);
173
174
             if (competitors_file.is_open()) {
```

```
175
                 for (int counter = 0; counter < this->competitors->size();
                    counter++) {
176
                     competitors_file << this->competitors->at(counter)->
                         get_number() << " " << this->competitors->at(counter)->
                         get_course()
                              << " " << this->competitors->at(counter)->get_name()
177
                                   << "\n";
                 }
178
179
180
                 competitors_file.close();
181
                 cout << "Competitors successfully exported to 'entrants.txt'."</pre>
                     << endl << endl:
182
             } else cout << "File 'entrants.txt' could not be written." << endl;</pre>
        }
183
184
185
186
    /* Member function that will handle the exporting of the array of courses to
        a '. txt' file. */
    void Event::export_courses() {
187
        if (courses->empty()) cout << "No courses to export. Exporting cancelled
188
            ." << endl << endl;
        else {
189
190
            ofstream courses_file;
191
             courses_file.open("courses.txt", ios::out);
192
193
             if (courses_file.is_open()) {
194
                 for (int counter = 0; counter < this->courses->size(); counter
                     ++) {
195
                      courses_file << this->courses->at(counter)->get_letter() <<</pre>
                         " " << this->courses->at(counter)->get_number_of_nodes();
196
197
                     for (int counter2 = 0; counter2 < this->courses->at(counter)
                         ->get_number_of_nodes(); counter2++) {
198
                          courses_file << " " << this->courses->at(counter)->
                             get_node(counter2);
199
                     }
200
                     courses_file << "\n";</pre>
201
                 }
202
203
                 courses_file.close();
204
                 cout << "Courses successfully exported to 'courses.txt'." <<</pre>
                     endl << endl;</pre>
205
             } else cout << "File 'courses.txt' could not be written." << endl;</pre>
206
        }
207
208
209
    /* Constructor for Event class. */
210
    Event::Event() {
211
        competitors = new vector < Competitor* > ();
212
        courses = new vector < Course * > ();
213
        set_name();
214
        set_date();
215
        set_start_time();
216
217
        cout << "Event name: " << this->name << endl;</pre>
        cout << "Event date: " << this->date << endl;</pre>
218
219
        cout << "Event start time: " << this->start_time << endl << endl;</pre>
220
221
222 \parallel /* Destructor for Event class. */
223
    Event::~Event() {
224
        delete(competitors);
225
        delete(courses);
```

Listing 7: Cpp file for Course class.

```
1
 2
    * Author: Chris Savill, chs17@aber.ac.uk
 3
    * File Name: course.cpp
    * Description: cpp file that contains member function definitions for the
 4
        course class.
    * First Created: 11/03/2013
 5
 6
    * Last Modified: 14/03/2013
 7
8
   #include "course.h"
9
10
   #include "creator.h"
11
   #include <iostream>
12
   #include <fstream>
   #include <sstream>
13
14
   #include <limits>
15
16
   using namespace std;
17
18
   /* Member function to return a course's letter. */
19
   char Course::get_letter() {
20
       return this->letter;
21
22
23
   /* Member function to return a course's number of nodes. */
24
   int Course::get_number_of_nodes() {
25
       return this->number_of_nodes;
26
27
28
   /* Member function to return a node from the course's vector of nodes. */
29
   int Course::get_node(int index) {
30
       return this->nodes->at(index);
31
   }
32
33
   /* Member function that checks if the letter given be the user matches any
      of the course letters. */
34
   bool checkCourseExists(char letter, Event *event) {
35
       for (int counter = 0; counter < event->getCourses()->size(); counter++)
36
            if (letter == event->getCourses()->at(counter)->get_letter()) return
                true; //Checks if letter matches any of the course letters.
       }
37
38
39
       return false; //Return false if no match found.
40
41
42
   /* Member function that will set the letter of the course. */
43
   void Course::set_letter(Event *event) {
       bool valid_letter = false;
44
45
       bool letter_chosen = false;
46
       char letter;
47
       do {
48
49
            do {
                cout << endl << endl << "Please enter in the course letter for</pre>
50
                   the course: ";
51
                cin.clear();
                letter = cin.get();
53
                cin.ignore(numeric_limits < streamsize >:: max(), '\n');
```

```
54
55
                if (isalpha(letter) && !checkCourseExists(letter, event))
                    valid_letter = true; //Checks that character entered is a
                    letter and that it does not match any course letters.
56
                 else {
57
                     cout << "Please enter in a valid course letter that does not</pre>
                         already exist in this event, a-z or A-Z." << endl <<
                        end1:
                     valid_letter = false;
58
                }
59
60
            } while (valid_letter == false);
61
62
            cout << endl << "Are you happy with the course letter: '" << letter
                << "'?" << endl;
63
            letter_chosen = get_acceptance();
64
        } while (letter_chosen == false);
65
66
        this->letter = letter;
67
    }
68
    /* Member function that will set the number of nodes of the course. */
69
70
    void Course::set_number_of_nodes() {
71
        bool number_chosen = false;
72
        int number;
73
74
        do {
75
            cout << endl << "Please enter in the number of nodes for</pre>
                this course: ";
76
            cin.clear();
77
            cin >> number;
78
            cin.ignore(numeric_limits < streamsize >:: max(), '\n');
79
80
            cout << endl << "Are you happy with the number of nodes: '"</pre>
                << number << "'?" << endl;
81
            number_chosen = get_acceptance();
82
        } while (number_chosen == false && number > 0);
83
        this->number_of_nodes = number;
84
85
    }
86
87
    /* Member function that reads in the nodes from the 'nodes.txt' file and
       adds them to the nodes available array. */
88
    bool Course::read_nodes_available() {
89
        ifstream nodes_file;
90
        string input;
91
        int node_number;
92
93
        nodes_file.open("nodes.txt", ios::in);
94
95
        if (nodes_file.is_open()) {
96
            while (getline(nodes_file, input)) { //Keep reading until EOF
                reached.
97
                 stringstream int_retriever(input); //Retrieves int from the
                    string stream.
98
                int_retriever >> node_number; //Stores the int in node_number.
99
                this->nodes_available->push_back(node_number);
100
            }
101
102
            nodes_file.close();
            cout << "Nodes from 'nodes.txt' read in successfully." << endl;</pre>
103
104
            cout << "Nodes read in: " << nodes_available->at(0);
105
            for (int counter = 1; counter < nodes_available -> size(); counter++)
                cout << ", " << nodes_available ->at(counter);
```

```
106
            cout << endl << endl;</pre>
107
        } else cout << "File 'nodes.txt' could not be opened. Please check file
            is in correct directory and permissions." << endl;
108 || }
109
110
    /* Member function that adds a new node to the course. */
    void Course::add_node() {
111
112
        bool number_chosen = false;
113
        string input;
114
        int number = 0;
115
116
        do {
117
            do {
                 cout << "Please enter in the node number you wish to add to the
118
                    course: ";
119
                 getline(cin, input);
120
                 stringstream int_retriever(input);
121
                 int_retriever >> number;
122
            } while (duplicated_last_node(number) || !check_node_exists(number))
                ; //Makes sure that the number entered doesn't match the last
                number entered and that it does exist.
123
            cout << endl << endl << "Are you happy with the node number: '" <<</pre>
124
                number << "'?" << endl;</pre>
125
            number_chosen = get_acceptance();
126
        } while (number_chosen == false);
127
128
        this->nodes->push_back(number);
129
130
    \slash* Member function to check if the new node being selected matches the last
131
       node added. */
132
    bool Course::duplicated_last_node(int number) {
133
        if (!nodes->empty()) { //Only checks if there are nodes present.
134
             if (number == nodes->back()) {
                 cout << "Node matches last node. Please choose a different node</pre>
135
                    number to add." << endl;</pre>
136
                 return true;
137
            }
        }
138
139
        return false; //Returns false if the number entered and the last number
140
            entered don't match.
141
    }
142
143
    /* Member function that checks that the node being added exists in the array
        of node available. */
144
    bool Course::check_node_exists(int number) {
145
        for (int counter = 0; counter < this->nodes_available->size(); counter
            ++) {
            if (number == this->nodes_available->at(counter)) return true;
146
147
148
        cout << "Node does not exist, please choose a different node number to</pre>
149
           add." << endl;</pre>
        return false; //Returns false if the number entered does not exist in
150
           the vector of nodes available.
151
152
153
    /* Constructor for Course class. */
154
    Course::Course(Event *event) {
155
        this->nodes = new vector<int>();
156
        this->nodes_available = new vector<int>();
```

```
157
158
        if (read_nodes_available()) {
159
             set_letter(event);
160
             set_number_of_nodes();
161
162
            for (int counter = 0; counter < number_of_nodes - 1; counter++) {</pre>
163
                 add_node();
164
165
            nodes -> push_back(nodes -> front()); //Adds the last node, matching the
166
                 first node to the course.
        } else cout << "Nodes could not be read in from 'nodes.txt' file. Course
167
             creation cancelled." << endl << endl;</pre>
168
169
170
    /* Destructor for Course class. */
171
   Course::~Course() {
172
        delete(nodes);
173
        delete(nodes_available);
174 | }
```

Listing 8: Cpp file for Competitor class.

```
1 ||
 2
    * Author: Chris Savill, chs17@aber.ac.uk
 3
    * File Name: competitor.cpp
 4
    * Description: cpp file that contains member function definitions for the
        competitor class.
    * First Created: 11/03/2013
 5
 6
    * Last Modified: 14/03/2013
7
8
9
   #include "competitor.h"
   #include "creator.h"
10
   #include <ctype.h>
11
12
   #include <iostream>
13
   #include <limits>
14
15
   using namespace std;
16
17
   /* Member function to return a competitor's number. */
18
   int Competitor::get_number() {
19
       return this->number;
20
   }
21
22
   /* Member function to return a competitor's name. */
23
   string Competitor::get_name() {
       return this->name;
24
25
   }
26
27
   /* Member function to return a competitor's course. */
28
   char Competitor::get_course() {
29
       return this->course;
30
   }
31
32
   /* Member function that will set the number of the competitor.
33
   * @param number The number for the competitor.
34
35
   void Competitor::set_number(int number) {
36
       this->number = number;
37
   }
38 ||
```

```
39
   /* Member function that will set the name of the competitor. */
40
   void Competitor::set_name() {
41
       bool name_chosen = false;
42
       string name;
43
44
       do {
           do {
45
46
                cout << endl << "Please enter in the name for the</pre>
                   competitor (no more than 50 characters): ";
47
                getline(cin, name);
48
           } while (name.length() > MAX_COMPETITOR_NAME_LENGTH);
49
            cout << endl << "Are you happy with the name: '" << name <<
50
               "'?" << endl;
51
52
           name_chosen = get_acceptance();
53
54
       } while (name_chosen == false);
55
56
       this->name = name;
57
   }
58
   /* Member function that will set the course letter for the competitor. */
59
60
   void Competitor::set_course(Event *event) {
61
       bool valid_letter = false;
62
       bool letter_chosen = false;
63
       char letter;
64
65
       do {
66
            do {
                cout << endl << "List of courses available for the</pre>
67
                   competitor to enter on: " << event->getCourses()->front()->
                   get_letter();
68
69
                if (event->getCourses()->size() > 1) { //Only prints out other
                   courses if the size of the vector > 1.
70
                    for (int counter = 1; counter < event->getCourses()->size();
                        counter++)
                        cout << ", " << event->getCourses()->at(counter)->
71
                            get_letter();
                }
72
73
                cout << endl << endl << "Please enter in the letter of the</pre>
74
                   course that the competitor is entering: ";
75
                cin.clear(); //Resets the input stream flags.
76
                letter = cin.get(); //Gets a single character.
77
                cin.ignore(numeric_limits < streamsize > :: max(), '\n'); //Clears
                   the input stream.
78
79
                if (isalpha(letter) && checkCourseExists(letter, event))
                   valid_letter = true; //Makes sure character is a letter and
                   that it corresponds to a course that exists.
80
                else {
81
                    cout << "Please enter in a valid course letter." << endl <<</pre>
                       endl;
82
                    valid_letter = false;
                }
83
84
           } while (valid_letter == false);
85
            cout << endl << "Are you happy with the course letter: '" << letter</pre>
86
               << "'' << endl;
87
            letter_chosen = get_acceptance();
88
       } while (letter_chosen == false);
```

```
89
90
        this->course = letter;
91
    }
92
93
    /* Constructor for Competitor class.
94
     * Oparam number The number for the new competitor.
95
96
    Competitor::Competitor(int number, Event *event) {
97
        set_number(number);
        cout << "Competitor number: " << this->number << endl;</pre>
98
99
        set_name();
        cout << "Competitor name: " << this->name << endl;</pre>
100
101
        set_course(event);
        cout << "Competitor course:" << this-> course << endl;</pre>
102
103 || }
```

3 Clean build and compilation of Event Creation Program

```
"/usr/bin/make" -f nbproject/Makefile-Debug.mk QMAKE= SUBPROJECTS= .clean-
make[1]: Entering directory '/home/clsavill/GitHub/Runners_and_Riders_3_Part
   /Event_Creation_Program'
rm -f -r build/Debug
rm -f dist/Debug/GNU-Linux-x86/event_creation_program
make[1]: Leaving directory '/home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Event_Creation_Program'
CLEAN SUCCESSFUL (total time: 217ms)
"/usr/bin/make" -f nbproject/Makefile-Debug.mk QMAKE= SUBPROJECTS= .build-
   conf
make[1]: Entering directory '/home/clsavill/GitHub/Runners_and_Riders_3_Part
   /Event_Creation_Program'
"/usr/bin/make" -f nbproject/Makefile-Debug.mk dist/Debug/GNU-Linux-x86/
   event_creation_program
make[2]: Entering directory '/home/clsavill/GitHub/Runners_and_Riders_3_Part
   /Event_Creation_Program'
mkdir -p build/Debug/GNU-Linux-x86
rm -f build/Debug/GNU-Linux-x86/main.o.d
     -c -g -MMD -MP -MF build/Debug/GNU-Linux-x86/main.o.d -o build/Debug/
   GNU-Linux-x86/main.o main.cpp
mkdir -p build/Debug/GNU-Linux-x86
rm -f build/Debug/GNU-Linux-x86/course.o.d
g++
      -c -g -MMD -MP -MF build/Debug/GNU-Linux-x86/course.o.d -o build/
   Debug/GNU-Linux-x86/course.o course.cpp
mkdir -p build/Debug/GNU-Linux-x86
rm -f build/Debug/GNU-Linux-x86/event.o.d
      -c -g -MMD -MP -MF build/Debug/GNU-Linux-x86/event.o.d -o build/Debug
   /GNU-Linux-x86/event.o event.cpp
mkdir -p build/Debug/GNU-Linux-x86
rm -f build/Debug/GNU-Linux-x86/competitor.o.d
       -c -g -MMD -MP -MF build/Debug/GNU-Linux-x86/competitor.o.d -o build/
   Debug/GNU-Linux-x86/competitor.o competitor.cpp
mkdir -p dist/Debug/GNU-Linux-x86
        -o dist/Debug/GNU-Linux-x86/event_creation_program build/Debug/GNU-
   Linux-x86/main.o build/Debug/GNU-Linux-x86/course.o build/Debug/GNU-Linux
   -x86/event.o build/Debug/GNU-Linux-x86/competitor.o
make[2]: Leaving directory '/home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Event_Creation_Program'
```

```
make[1]: Leaving directory '/home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Event_Creation_Program'
BUILD SUCCESSFUL (total time: 5s)
    Run through of Event Creation Program
Please enter in the name for the event (no more than 79 characters): Horse
   Trekkers 21st Anniversary
Are you happy with the name: 'Horse Trekkers 21st Anniversary'?
If yes press 'y' then 'Enter'
If no press 'n' then 'Enter'
Please enter in the date for the event (no more than 19 characters): 3rd May
    2013
Are you happy with the date: '3rd May 2013'?
If yes press 'y' then 'Enter'
If no press 'n' then 'Enter'
У
Please enter in the start time for the event with the 24 hour format 'HH:MM
   ', hours first: 13
Valid hours entered.
Please now enter in the minutes: 37
Valid minutes entered.
Are you happy with the start time: '13:37'?
If yes press 'y' then 'Enter'
If no press 'n' then 'Enter'
Event name: Horse Trekkers 21st Anniversary
Event date: 3rd May 2013
Event start time: 13:37
********************
* Runners and Riders Event Creation Program Main Menu *
********************
              1. Add Competitor to Event
              2. Add Course to Event
              3. Export Event to File
              4. Export Competitors to File
              5. Export Courses to File
              6. Exit Event Creation Program
```

Please enter in an option from the above an press 'Enter': 1 No courses exist for competitor course selection. Please create a course

first.

```
*********************
  Runners and Riders Event Creation Program Main Menu *
*******************
              1. Add Competitor to Event
              2. Add Course to Event
              3. Export Event to File
              4. Export Competitors to File
              5. Export Courses to File
              6. Exit Event Creation Program
********************
Please enter in an option from the above an press 'Enter': 2
Nodes from 'nodes.txt' read in successfully.
Nodes read in: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18
Please enter in the course letter for the course: A
Are you happy with the course letter: 'A'?
If yes press 'y' then 'Enter'
If no press 'n' then 'Enter'
Please enter in the number of nodes for this course: 5
Are you happy with the number of nodes: '5'?
If yes press 'y' then 'Enter'
If no press 'n' then 'Enter'
Please enter in the node number you wish to add to the course: 1
Are you happy with the node number: '1'?
If yes press 'y' then 'Enter'
If no press 'n' then 'Enter'
Please enter in the node number you wish to add to the course: 3
Are you happy with the node number: '3'?
If yes press 'y' then 'Enter'
If no press 'n' then 'Enter'
Please enter in the node number you wish to add to the course: 12
Are you happy with the node number: '12'?
If yes press 'y' then 'Enter'
If no press 'n' then 'Enter'
Please enter in the node number you wish to add to the course: 20
Node does not exist, please choose a different node number to add.
Please enter in the node number you wish to add to the course: 8
Are you happy with the node number: '8'?
If yes press 'y' then 'Enter'
```

If no press 'n' then 'Enter'

```
New course added to event.
Course letter: A
Number of course nodes: 5
Nodes: 1, 3, 12, 8, 1
********************
* Runners and Riders Event Creation Program Main Menu *
******************
             1. Add Competitor to Event
             2. Add Course to Event
             3. Export Event to File
             4. Export Competitors to File
             5. Export Courses to File
             6. Exit Event Creation Program
*********************
Please enter in an option from the above an press 'Enter': 1
Competitor number: 1
Please enter in the name for the competitor (no more than 50 characters):
  Julius Munching
Are you happy with the name: 'Julius Munching'?
If yes press 'y' then 'Enter'
If no press 'n' then 'Enter'
Competitor name: Julius Munching
List of courses available for the competitor to enter on: A
Please enter in the letter of the course that the competitor is entering: a
Please enter in a valid course letter.
List of courses available for the competitor to enter on: A
Please enter in the letter of the course that the competitor is entering: A
Are you happy with the course letter: 'A'?
If yes press 'y' then 'Enter'
If no press 'n' then 'Enter'
Competitor course: A
New competitor added to event.
Competitor number: 1Competitor name: Julius Munching
Course: A
*******************
* Runners and Riders Event Creation Program Main Menu *
********************
             1. Add Competitor to Event
             2. Add Course to Event
             3. Export Event to File
             4. Export Competitors to File
             5. Export Courses to File
             6. Exit Event Creation Program
********************
```

```
Please enter in an option from the above an press 'Enter': 1
Competitor number: 2
Please enter in the name for the competitor (no more than 50 characters):
Are you happy with the name: 'Helen Boon'?
If yes press 'y' then 'Enter'
If no press 'n' then 'Enter'
Competitor name: Helen Boon
List of courses available for the competitor to enter on: A
Please enter in the letter of the course that the competitor is entering: A
Are you happy with the course letter: 'A'?
If yes press 'y' then 'Enter'
If no press 'n' then 'Enter'
{\tt Competitor\ course:A}
New competitor added to event.
Competitor number: 2Competitor name: Helen Boon
Course: A
********************
st Runners and Riders Event Creation Program Main Menu st
******************
            1. Add Competitor to Event
            2. Add Course to Event
            3. Export Event to File
            4. Export Competitors to File
            5. Export Courses to File
            6. Exit Event Creation Program
*********************
Please enter in an option from the above an press 'Enter': 3
Event successfully exported to 'name.txt'.
*********************
* Runners and Riders Event Creation Program Main Menu *
*********************
            1. Add Competitor to Event
            2. Add Course to Event
            3. Export Event to File
            4. Export Competitors to File
            5. Export Courses to File
            6. Exit Event Creation Program
********************
Please enter in an option from the above an press 'Enter': 4
Competitors successfully exported to 'entrants.txt'.
******************
* Runners and Riders Event Creation Program Main Menu *
********************
            1. Add Competitor to Event
            2. Add Course to Event
                                                *
            3. Export Event to File
```

```
4. Export Competitors to File
            5. Export Courses to File
            6. Exit Event Creation Program
Please enter in an option from the above an press 'Enter': 5
Courses successfully exported to 'courses.txt'.
*******************
 Runners and Riders Event Creation Program Main Menu
********************
            1. Add Competitor to Event
            2. Add Course to Event
            3. Export Event to File
            4. Export Competitors to File
            5. Export Courses to File
            6. Exit Event Creation Program
*********************
Please enter in an option from the above an press 'Enter': 6
Exiting program...
RUN SUCCESSFUL (total time: 2m 46s)
```

5 Files created by execution of Event Creation Program

```
Listing 9: Event 'name.txt' file

Horse Trekkers 21st Anniversary
3rd May 2013
13:37

Listing 10: Event 'courses.txt' file

A 5 1 3 12 8 1

Listing 11: Event 'entrants.txt' file

1 A Julius Munching
2 A Helen Boon
```

6 Code for Checkpoint Manager Program

Listing 12: Launcher class.

```
1 \parallel /* File Name: Launcher.java
    * Description: Launcher class which handles the initial launching of the
 2
        Checkpoint Manager Program.
    * First Created: 15/03/2013
3
    * Last Modified: 19/03/2013
 4
 5
 6
   package Data_Structures;
7
8 | import GUI. TypeWindow;
   import java.io.IOException;
   import javax.swing.JOptionPane;
10
11
12
    * @author Chris Savill, chs17@aber.ac.uk
13
14
    */
15 public class Launcher {
```

```
16
        /**
17
18
         st Main method that checks that the right number of arguments were
         st and calls methods to load the file required and launch the GUI.
19
20
21
         * Oparam args String array of arguments, should be a list of file names
22
         */
23
       public static void main(String[] args) throws IOException {
24
            if (args.length < 4) {</pre>
25
                JOptionPane.showMessageDialog(null, "Invalid number of file
                   names supplied required for program to run.\n\"
                        + "File names required for:\nFile containing nodes\nFile
26
                             containing courses\nFile containing entrants\n"
27
                        + "File to retrieve time records and write time records
                            to.\n\n"
28
                        + "Now exiting program.");
29
30
                Event event = new Event(args);
31
32
                if (event.loadCycle(args)) {
33
                    JOptionPane.showMessageDialog(null, "Data files loaded
                        successfully.");
                    TypeWindow typeWindow = new TypeWindow(event);
34
35
36
                    System.out.print("Exiting Program...\n");
37
            }
38
39
       }
40 ||
   }
```

Listing 13: Event class.

```
1
   /* File Name: Manager.java
 2
    st Description: Event class which stores all members and functions
        pertaining to an event.
 3
    * First Created: 15/03/2013
 4
    * Last Modified: 18/03/2013
    */
 5
   package Data_Structures;
 6
 7
8
   import File_Handling.FileHandler;
9
   import java.io.IOException;
10
   import java.util.ArrayList;
11
   import java.util.Date;
12
13
    * @author Chris Savill, chs17@aber.ac.uk
14
15
   public class Event {
16
17
18
       private ArrayList < Competitor > competitors; //Array list of competitors
           in an event.
19
       private ArrayList < Node > nodes; //Array list of nodes in an event.
20
       private ArrayList < Node > checkpoints; //Array list of nodes that are of
           type "CP" or "MC".
21
       private ArrayList <Course > courses; //Array list of courses in an event.
22
       private ArrayList < Record > records; //Array list of records logged.
23
       private int lastLineRead;
24
       private Date lastRecordedTime;
25
       private boolean timeFileExists;
```

```
26
       private String[] fileNames;
27
28
        /**
29
         * Method to return array list of competitors.
30
31
         * Oreturn The array list of competitors.
32
33
       public ArrayList < Competitor > getCompetitors() {
34
           return competitors;
35
       }
36
37
        /**
38
         * Method to return array list of nodes.
39
40
         * Oreturn The array list of nodes.
41
         */
       public ArrayList < Node > getNodes() {
42
43
           return nodes;
44
45
        /**
46
         * Method to return array list of checkpoints.
47
48
49
         * Oreturn The array list of checkpoints (non-junction nodes).
50
51
       public ArrayList < Node > getCheckpoints() {
            return checkpoints;
52
53
       }
54
55
        /**
         * Method to return array list of courses.
56
57
58
         * Oreturn The array list of courses.
59
60
       public ArrayList < Course > getCourses() {
61
            return courses;
62
       }
63
64
        /**
65
         * Method to return array list of records.
66
         * Oreturn The array list of records.
67
68
         */
69
        public ArrayList < Record > getRecords() {
70
            return records;
71
72
        /**
73
74
         * Method to get the last line read number.
75
76
         * Oreturn The line read from the times file.
77
         */
78
       public int getLastLineRead() {
79
            return lastLineRead;
80
       }
81
82
83
         * Method to return the array of file names.
84
         * Oreturn The string array of file names.
85
86
         */
87
        public String[] getFileNames() {
            return fileNames;
88
```

```
89
        }
90
91
        /**
         * Method to set the last line read number.
92
93
94
         * @param lineNumber The line read from the times file.
95
96
        public void setLastLineRead(int lineNumber) {
97
            this.lastLineRead = lineNumber;
98
        }
99
100
        /**
101
         * Method to set the last time recorded.
102
103
         * Oparam time The last time recorded.
104
         */
105
        public void setLastRecordedTime(Date time) {
106
            this.lastRecordedTime = time;
107
108
109
110
         * Method to call a series of methods to load in the data required by
             the
111
         * program.
112
113
         st Oparam args The list of filenames to load the required data into the
114
         * system.
115
         * Oreturn Successful/Unsuccessful.
116
         */
117
        public boolean loadCycle(String[] fileNames) throws IOException {
            this.fileNames = fileNames;
118
119
120
            FileHandler fileReader = new FileHandler();
121
122
            if (fileReader.readNodes(fileNames[0], this)) {
123
                 if (fileReader.readCourses(fileNames[1], this)) {
124
                     if (fileReader.readCompetitors(fileNames[2], this)) {
125
                         return true;
126
                     } else {
127
                         System.out.print("Failed to load competitors. Program
                             Exiting.\n");
128
                     }
129
                 } else {
130
                     System.out.print("Failed to load courses. Program Exiting.\n
                        ");
                 }
131
132
            } else {
133
                 System.out.print("Failed to load nodes. Program Exiting.\n");
134
            }
135
136
            return false;
        }
137
138
139
140
         * Method that checks if the node number passed in exists in the array
             list
141
         * of nodes loaded in.
142
143
         * @param number The number to be compared with.
144
         * Oreturn True if node exists else false.
145
146
        public boolean checkNodeExists(int number) {
147
            for (int counter = 0; counter < nodes.size(); counter++) {</pre>
```

```
148
                 if (number == nodes.get(counter).getNumber()) {
149
                     return true;
150
                 } //Nodes exists.
            }
151
152
153
            return false; //Returns false if the node number passed in does not
                exist in the array list of nodes.
154
        }
155
156
        /**
157
         * Method that checks if the course letter passed in exists in the array
158
         * list of courses loaded in.
159
         * @param letter The letter to be compared with.
160
161
         * Oreturn True if course exists else false.
162
         */
163
        public boolean checkCourseExists(char letter) {
164
            for (int counter = 0; counter < courses.size(); counter++) {</pre>
165
                 if (letter == courses.get(counter).getLetter()) {
166
                     return true;
167
                 } //Course exists.
            }
168
169
170
            return false; //Returns false if the course letter passed in does
                not exist in the array list of courses.
171
        }
172
173
        /**
174
         * Method to let the know event instance know that a time file does now
175
         * exist.
176
177
178
        public void setTimesFilesExistsTrue() {
179
            timeFileExists = true;
180
181
182
183
         * Method to find a competitor and return it.
184
185
         * @param competitorNumber The number of the competitor being looked for
186
         * @return The competitor matched.
187
         */
188
        public Competitor retrieveCompetitor(int competitorNumber) {
189
            for (Competitor competitor: competitors) {
190
                 if (competitor.getNumber() == competitorNumber) {
191
                     return competitor;
192
                 }
193
            }
194
            return null;
195
        }
196
197
198
         * Method to find a course and return it.
199
200
         * Oparam courseLetter The course being looked for.
201
         * @return The course matched.
202
         */
203
        public Course retrieveCourse(char courseLetter) {
204
             for (Course course : courses) {
205
                 if (course.getLetter() == courseLetter) {
206
                     return course;
                 }
207
```

```
208
            }
209
            return null;
210
        }
211
212
        /**
213
         * Method to retrieve the checkpoint number.
214
215
         st Oparam type The type of the checkpoint.
216
         st Oparam listIndex The index of the list element.
         st Oparam number Of Elements The size of the list.
217
218
         * @return The checkpoint number being looked for.
219
         */
220
        public int retrieveCheckpointNumber(String type, int listIndex, int
           numberOfElements) {
221
            int[] checkpointArray = new int[numberOfElements];
222
            int arrayIndex = 0;
223
224
            for (int counter = 0; counter < checkpoints.size(); counter++) {</pre>
225
                 if (checkpoints.get(counter).getType().equals(type)) {
226
                     checkpointArray[arrayIndex++] = checkpoints.get(counter).
                        getNumber();
227
                }
            }
228
229
230
            return checkpointArray[listIndex];
231
        }
232
233
        /**
234
         * Method to check if the new record is valid.
235
236
         * Oparam checkpoint The checkpoint number.
237
         * Oparam status The status.
238
         * @param competitorNumber The competitor's number.
239
         * Oparam time The time of the record.
240
         * Oreturn True is record is valid, else false.
241
         */
242
        public boolean checkNewRecord(int checkpoint, int status, int
           competitorNumber, Date time) {
243
            Competitor competitor = retrieveCompetitor(competitorNumber);
244
245
            if (timeFileExists != false) {
246
                 if (time.before(lastRecordedTime)) {
247
                     System.out.println("\nInvalid time.");
248
                     return false;
249
                 } else if (competitor.getCheckpointIndex() == competitor.
                    getCheckpoints().length) {
                     System.out.println("\nCompetitor already finished.");
250
251
                     return false;
252
                }
253
            }
254
255
            if (competitor.getStatus() == 'I' || competitor.getStatus() == 'E')
256
257
                System.out.println("\nCompetitor already excluded.");
258
                return false; //Should not be updated as competitor already
                    excluded.
259
            } else if (status == 2 || status == 3) {
260
                 if (competitor.getStatus() != 'A') {
261
                     System.out.println("\nCompetitor hasn't arrived at a medical
                         checkpoint yet.");
262
                     return false; //Competitor cannot be departing or be exclude
                         from a medical checkpoint they haven't arrived at.
```

```
263
                 } else {
264
                     return true;
265
                 }
266
            } else if (status == 0) {
267
                 if (competitor.getStatus() != 'A') {
268
                     return true;
269
                 } else {
270
                     System.out.println("\nCompetitor is still being examined at
                        a medical checkpoint.");
271
                     return false; //Competitor cannot be at a time checkpoint
                        when should be at a medical checkpoint being examined.
272
273
            } else if (status == 1) {
274
                 return true;
275
276
277
            return false;
278
        }
279
        /**
280
281
         * Method to determine the final status to be written to the time record
              file.
282
         * Oparam checkpoint The checkpoint number.
283
         * Oparam status The status.
284
         * @param competitorNumber The competitor's number.
285
         * Oreturn The final status for the record.
286
         */
287
        public char determineFinalStatus(int checkpoint, int status, int
            competitorNumber) {
288
            Competitor competitor = retrieveCompetitor(competitorNumber);
289
290
            if (competitor.getStatus() == 'N') {
291
                 if (checkpoint != competitor.getCheckpoints()[competitor.
                    getCheckpointIndex()]) {
292
                     return 'I';
293
                 } else if (status == 0) {
294
                     return 'T';
295
                 } else if (status == 1) {
296
                     return 'A';
297
298
            } else if (competitor.getStatus() == 'A') {
299
                 if (status == 2) {
300
                     return 'D';
301
                 } else if (status == 3) {
302
                     return 'E';
303
                 }
304
             } else if (checkpoint != competitor.getCheckpoints()[competitor.
                getCheckpointIndex() + 1]) {
305
                 return 'I';
306
            } else {
307
                 if (status == 0) {
308
                     return 'T';
309
                 } else if (status == 1) {
310
                     return 'A';
311
                 } else if (status == 2) {
312
                     return 'D';
313
                 } else if (status == 3) {
314
                     return 'E';
315
                 }
316
            }
317
318
             System.out.print("\n\nInvalid final status, returning 'I'.\n");
319
             return 'I';
```

```
320
         }
321
322
         /**
          st Constructor to initialise the event.
323
324
          */
325
         public Event(String[] fileNames) {
326
             competitors = new ArrayList < Competitor > ();
327
             nodes = new ArrayList < Node > ();
328
             checkpoints = new ArrayList < Node > ();
329
             courses = new ArrayList < Course > ();
330
             records = new ArrayList < Record > ();
331
             lastLineRead = 0;
332
             timeFileExists = false;
333
         }
334 || }
```

Listing 14: Node class.

```
/* File Name: Node.java
    * Description: Node class which stores all members and functions pertaining
         to a node.
3
    * First Created: 15/03/2013
    * Last Modified: 15/03/2013
 4
 5
 6
   package Data_Structures;
7
8
   /**
9
    * @author Chris Savill, chs17@aber.ac.uk
10
   public class Node {
11
12
       private int number;
13
14
       private String type;
15
16
17
         * Constructor to initialise Node.
18
19
         * Oparam number The number of the node.
20
         * Oparam type The type of the node.
21
         */
22
       public Node(int number, String type) {
23
            this.number = number;
24
            this.type = type;
25
       }
26
27
        /**
28
         * Method to return the node's number.
29
30
         * @return The node number.
31
32
       public int getNumber() {
33
            return number;
34
       }
35
36
37
         * Method to return the node's type.
38
         * Oreturn The type of the node.
39
40
       public String getType() {
41
            return type;
42
43
```

```
/* File Name: Couse.java
 2
    * Description: Course class which stores all members and functions
        pertaining to a course.
    * First Created: 15/03/2013
 3
 4
    * Last Modified: 17/03/2013
 5
 6
   package Data_Structures;
 7
8
9
    * @author Chris Savill, chs17@aber.ac.uk
10
11
   public class Course {
12
13
       private char letter;
       private int numberOfNodes;
14
       private int[] nodes;
15
16
17
        /**
        * Constructor to initialise course.
18
19
20
         * Oparam letter The course letter identifier.
21
         st Oparam numberOfNodes The number of nodes the course contains.
22
         * Oparam nodes The array of nodes the course contains.
23
         */
24
       public Course(char letter, int numberOfNodes, int[] nodes) {
            this.letter = letter;
25
26
            this.numberOfNodes = numberOfNodes;
27
            this.nodes = nodes;
28
       }
29
        /**
30
31
         * Method to return the course letter.
32
33
       public char getLetter() {
34
           return letter;
35
       }
36
37
38
         * Method to return the number of nodes the course contains.
39
40
       public int getNumberOfNodes() {
            return numberOfNodes;
41
42
43
44
45
         * Method to return the array of nodes the course contains.
46
47
       public int[] getNodes() {
48
           return nodes;
49
       }
50 || }
```

Listing 16: Competitor class.

```
6 | package Data_Structures;
7
8
   import java.util.ArrayList;
9
   /**
10
    * Qauthor Chris Savill, chs17Qaber.ac.uk
11
12
   public class Competitor {
13
14
15
       private String name;
16
       private int number;
17
       private char course;
18
       private char status;
       private int[] checkpoints;
19
20
       private int checkpointIndex;
21
22
23
         * Constructor to initialise competitor.
24
25
         st Oparam number The competitor's number.
26
         * Oparam course The competitor's course.
27
         * Oparam name The competitor's name.
28
29
       public Competitor(int number, char course, String name, Event event) {
30
           this.number = number;
31
            this.course = course;
            this.name = name;
32
            this.checkpoints = setCheckpoints(event);
33
            this.checkpointIndex = 0;
34
35
            this.status = 'N'; //Not started yet.
36
       }
37
38
       /**
39
         * Method to return the competitor's number.
40
         * Oreturn The number of the competitor.
41
42
43
       public int getNumber() {
44
           return number;
45
       }
46
47
48
         * Method to return the course the competitor is entered on.
49
50
         * Oreturn The course the competitor entered in on.
51
        */
52
       public char getCourse() {
53
            return course;
54
       }
55
56
         * Method to return the competitor's name.
57
58
59
         * Oreturn The name of the competitor.
60
         */
61
       public String getName() {
62
            return name;
       }
63
64
65
66
         * Method to return the competitor's status.
67
68
         * Oreturn The status of the competitor.
```

```
69
         */
70
        public char getStatus() {
71
            return status;
72
73
74
         * Method to return the index of the last checkpoint the competitor
75
             arrived
76
         * at.
77
78
          * Oreturn The index of the last checkpoint the competitor arrived at.
79
         */
80
        public int getCheckpointIndex() {
81
            return checkpointIndex;
82
83
84
        /**
85
         * Method to return the int array of checkpoints.
86
87
         * Oreturn The int array of checkpoints.
88
89
        public int[] getCheckpoints() {
90
            return checkpoints;
91
        }
92
93
        /**
          * Method to get the nodes which are recordable checkpoints (non-
94
             junction
95
         * nodes).
96
97
         * Oparam event The event instance.
98
          * Oreturn The int array of checkpoints.
99
         */
100
        private int[] setCheckpoints(Event event) {
101
             ArrayList < Integer > checkpointsList = new ArrayList < Integer > ();
102
            Course courseReference = event.retrieveCourse(course);
103
104
             for (int counter = 0; counter < courseReference.getNumberOfNodes();</pre>
                counter++) {
105
                 for (int counter2 = 0; counter2 < event.getNodes().size();</pre>
                    counter2++) {
                     if ((!event.getNodes().get(counter2).getType().equals("JN"))
106
107
                              && (event.getNodes().get(counter2).getNumber() ==
                                  courseReference.getNodes()[counter])) {
108
                          checkpointsList.add(event.getNodes().get(counter2).
                             getNumber());
109
                          break;
110
                     }
111
                 }
112
            }
113
114
            int[] intList = new int[checkpointsList.size()];
115
            for (int counter = 0; counter < checkpointsList.size(); counter++) {</pre>
116
117
                 intList[counter] = checkpointsList.get(counter).intValue();
            }
118
119
120
            return intList;
        }
121
122
123
124
         * Method to set the status of the competitor.
125
```

```
126
          * Oparam status The current status of the competitor.
127
128
        public void setStatus(char status) {
129
             this.status = status;
130
131
132
133
         * Method to increment the checkpoint index by 1.
134
135
        public void incrementCheckpointIndex() {
136
             checkpointIndex++;
137
        }
138 || }
```

Listing 17: Record class.

```
/* File Name: Record.java
 2
    * Description: Record class which stores all members and functions
       pertaining to checking a competitor in at a checkpoint.
 3
    * First Created: 15/03/2013
    * Last Modified: 17/03/2013
 4
 5
 6
   package Data_Structures;
 7
8
   import java.util.Date;
9
10
    * @author Chris Savill, chs17@aber.ac.uk
11
12
13
   public class Record {
14
15
       private Event event;
16
       private char competitorStatus;
17
       private int checkpoint;
18
       private int competitorNumber;
19
       private Date time;
20
21
       /**
22
        * Constructor to initialise record data when read in from file.
23
        st Oparam checkpoint The number of the checkpoint.
24
25
         * Oparam competitorNumber The number of the competitor.
26
        * Oparam time The time of the record.
27
28
       public Record(char status, int checkpoint, int competitorNumber, Date
29
           this.competitorStatus = status;
30
           this.checkpoint = checkpoint;
31
           this.competitorNumber = competitorNumber;
32
           this.time = time;
33
       }
34
35
       /**
36
        * Constructor to initialise record data when recorded through GUI.
37
         st Oparam checkpoint The number of the checkpoint.
38
39
         * @param competitorNumber The number of the competitor.
40
        * Oparam time The time of the record.
41
42
       public Record(int checkpoint, char status, int competitorNumber, Date
43
           this.competitorStatus = status;
```

```
44
            this.checkpoint = checkpoint;
45
            this.competitorNumber = competitorNumber;
46
            this.time = time;
       }
47
48
49
        /**
50
         * Method to return the status of the competitor as marked by the
51
         * checkpoint.
52
53
         * Oreturn The status of the competitor.
54
55
       public char getCompetitorStatus() {
56
            return competitorStatus;
57
       }
58
59
        /**
60
         * Method to return the checkpoint number being recorded.
61
62
         * Oreturn The checkpoint number.
63
         */
64
       public int getCheckpointNumber() {
65
           return checkpoint;
66
67
        /**
68
69
         * Method to return the competitor number being recorded.
70
71
         * @return The competitor number.
72
         */
73
       public int getCompetitorNumber() {
74
            return competitorNumber;
75
       }
76
77
78
         * Method to return the time being recorded.
79
80
         * @return The time of the record.
81
82
       public Date getTime() {
83
            return time;
       }
84
85 || }
```

Listing 18: FileHandler class.

```
/* File Name: FileHandler.java
 2
    * Description: FileHandler class which stores methods to handle the reading
         of files.
    * First Created: 15/03/2013
 3
 4
    * Last Modified: 18/03/2013
 5
    */
 6
   package File_Handling;
 7
8
   import Data_Structures.Competitor;
   import Data_Structures.Course;
9
   import Data_Structures.Event;
10
11
   import Data_Structures.Node;
12
   import Data_Structures.Record;
   import java.io.BufferedReader;
13
14 | import java.io.FileNotFoundException;
15 | import java.io.FileReader;
16 | import java.io.FileWriter;
```

```
17
   import java.io.IOException;
18
   import java.io.RandomAccessFile;
19
   import java.nio.channels.FileChannel;
20
   import java.nio.channels.FileLock;
21
   import java.text.ParseException;
22
   import java.text.SimpleDateFormat;
23
   import java.util.Date;
24
   import java.util.logging.Level;
25
   import java.util.logging.Logger;
26
27
28
    * @author Chris Savill, chs17@aber.ac.uk
29
30
   public class FileHandler {
31
32
       /**
33
        * Method to read in all the details for the nodes pertaining to an
            event.
34
        st Oparam fileName The file name required to access the file needed.
35
36
         * Oparam event The event instance.
37
         * Oreturn True if file loaded successfully, else false if it fails at
            any
         * point.
38
39
         */
40
       public boolean readNodes(String fileName, Event event) throws
           IOException {
           String input;
41
42
           int nodeNumber;
43
            String nodeType;
           String[] subStrings;
44
           String pattern = "(\d+\s+([A-Z]{2}))"; //Regular expression for
45
               nodes file.
46
47
           try {
                BufferedReader reader = new BufferedReader(new FileReader(
48
                   fileName));
49
50
                while ((input = reader.readLine()) != null) {
                    if (input.matches(pattern)) { //Checks to make sure the line
51
                        is in the right format.
                        subStrings = input.split("\\s+"); //Gets rid of
52
                           whitespace and separates the two sides into two
                           substrings.
53
                        nodeNumber = Integer.parseInt(subStrings[0]); //
                           Retrieves the node number by parsing the string into
                           an int.
                        nodeType = subStrings[1]; //Retrieves the node type.
54
55
56
                        Node node = new Node(nodeNumber, nodeType); //Creates
                           new node with parameters read in.
                        event.getNodes().add(node); //Adds new node to array
57
                           list of nodes.
58
59
                        if (node.getType().equals("CP") || node.getType().equals
                           ("MC")) {
60
                            event.getCheckpoints().add(node); //Adds new node to
                                 array list of checkpoints if the node is of type
                                 "CP or "MC".
                        }
61
62
                    } else {
63
                        System.out.print("Invalid line format. Cancelling
                           loading of nodes.\n\n");
```

```
64
                         reader.close();
65
                         return false;
66
                     }
                }
67
68
69
                 if (!event.getNodes().isEmpty()) {
70
                     System.out.print("Loading in of nodes successful.\n\n");
71
                     reader.close();
72
                     return true;
                } else {
73
74
                     System.out.print("Loading in of nodes unsuccessful. No nodes
                         in file.\n\n");
75
                     reader.close();
76
                     return false;
77
78
            } catch (FileNotFoundException ex) {
79
                Logger.getLogger(FileHandler.class.getName()).log(Level.SEVERE,
                    null, ex);
80
            }
81
82
            System.out.print("Could not open file that contains nodes.\n\n");
83
            return false;
84
        }
85
        /**
86
         * Method to read in all the details for the courses pertaining to an
87
             event.
88
89
         st Oparam fileName The file name required to access the file needed.
90
         * Oparam event The event instance.
91
         * Oreturn True if file loaded successfully, else false if it fails at
             any
92
         * point.
93
94
        public boolean readCourses(String fileName, Event event) throws
           IOException {
95
            String input;
96
            char courseLetter;
97
            int numberOfNodes;
98
            int[] nodes;
99
            String[] subStrings;
            String pattern = "(([A-Za-z]+)((\s+\d+)+)*)"; //Regular expression
100
                 for courses file.
101
102
            try {
                 BufferedReader reader = new BufferedReader(new FileReader(
103
                    fileName));
104
105
                 while ((input = reader.readLine()) != null) {
106
                     if (input.matches(pattern)) { //Checks to make sure the line
                         is in the right format.
                         subStrings = input.split("\\s+"); //Gets rid of
107
                            whitespace and separates the strings into substrings.
108
                         courseLetter = subStrings[0].charAt(0); //Retrieves the
                            course letter.
109
                         numberOfNodes = Integer.parseInt(subStrings[1]);
110
                         nodes = new int[numberOfNodes];
111
112
                         for (int counter = 0; counter < numberOfNodes; counter</pre>
                            ++) {
                             if (event.checkNodeExists(Integer.parseInt(
113
                                 subStrings[counter + 2]))) {
114
                                 nodes[counter] = Integer.parseInt(subStrings[
```

```
counter + 2]);
115
                             } else {
116
                                  System.out.print("Invalid node in course file
                                     found. Cancelling loading of courses\n\n");
117
                                  reader.close();
118
                                  return false;
119
                             }
                         }
120
121
122
                         Course course = new Course(courseLetter, numberOfNodes,
                            nodes); //Creates new course with parameters read in.
123
                         event.getCourses().add(course); //Adds new course to
                             array list of courses.
124
                     } else {
125
                         System.out.print("Invalid line format. Cancelling
                            loading of courses\n\n");
126
                         reader.close();
127
                         return false;
128
                     }
                }
129
130
131
                 if (!event.getCourses().isEmpty()) {
132
                     System.out.print("Loading in of courses successful.\n\n");
133
                     reader.close();
134
                     return true;
135
                 } else {
136
                     System.out.print("Loading in of courses unsuccessful. No
                        courses in file.\n\n");
137
                     reader.close();
138
                     return false;
139
140
            } catch (FileNotFoundException ex) {
141
                 Logger.getLogger(FileHandler.class.getName()).log(Level.SEVERE,
                    null, ex);
            }
142
143
            System.out.print("Could not open file that contains courses.\n\n");
144
145
            return false;
146
        }
147
        /**
148
         * Method to read in all the details for the competitors pertaining to
149
             an
150
         * event.
151
152
         st Oparam fileName The file name required to access the file needed.
153
         * Oparam event The event instance.
154
         * Oreturn True if file loaded successfully, else false if it fails at
             any
155
         * point.
156
        public boolean readCompetitors(String fileName, Event event) throws
157
           IOException {
            String input;
158
159
            int competitorNumber;
            char courseLetter;
160
161
            String[] subStrings;
162
            String competitorName;
            String pattern = "(\d+\s+[A-Za-z]((\s+[A-Za-z]{1}[a-z]+)+))"; //
163
                Regular expression for competitors file.
164
165
            try {
166
                 BufferedReader reader = new BufferedReader(new FileReader(
```

```
fileName));
167
168
                while ((input = reader.readLine()) != null) {
                     if (input.matches(pattern)) { //Checks to make sure the line
169
                         is in the right format.
                         subStrings = input.split("\\s+"); //Gets rid of
170
                            whitespace and separates the strings into substrings.
171
                         competitorNumber = Integer.parseInt(subStrings[0]); //
                            Retrieves the competitor number by parsing the string
                             into an int.
172
                         if (event.checkCourseExists(subStrings[1].charAt(0))) {
173
174
                             courseLetter = subStrings[1].charAt(0); //Retrieves
                                 the course the competitor is entering in on.
175
176
                             System.out.print("Invalid course in competitor file
                                 found. Cancelling loading of competitors.\n\n");
177
                             reader.close();
178
                             return false;
179
                         }
180
181
                         competitorName = subStrings[2];
182
183
                         if (subStrings.length > 3) {
184
                             for (int counter = 3; counter < subStrings.length;</pre>
                                 counter++) {
                                 competitorName += " " + subStrings[counter]; //
185
                                     Concatanates name substrings together.
186
                             }
187
                         }
188
189
                         Competitor competitor = new Competitor(competitorNumber,
                             courseLetter, competitorName, event); //Creates new
                             competitor with parameters read in.
190
                         event.getCompetitors().add(competitor); //Adds new
                            competitor to array list of competitors.
191
                     } else {
192
                         System.out.print("Invalid line format. Cancelling
                            loading of competitors.\n\n");
193
                         reader.close();
194
                         return false;
195
                     }
                }
196
197
198
                 if (!event.getCompetitors().isEmpty()) {
                     System.out.print("Loading in of competitors successful.\n\n"
199
                        );
200
                     reader.close();
201
                     return true;
202
                } else {
203
                     System.out.print("Loading in of competitors unsuccessful. No
                         competitors in file.\n\n");
204
                     reader.close();
205
                     return false;
206
                }
207
            } catch (FileNotFoundException ex) {
208
                Logger.getLogger(FileHandler.class
209
                         .getName()).log(Level.SEVERE, null, ex);
210
            }
211
212
            System.out.print("Could not open file that contains competitors.\n\n
                ");
213
            return false;
```

```
214
        }
215
216
        /**
217
         * Method to read in all the details for the checkpoint times pertaining
218
         * an event.
219
220
         st @param fileName The file name required to access the file needed.
221
         * Oparam event The event instance.
222
         * Oreturn True if file loaded successfully, else false if it fails at
223
         * point.
224
         */
225
        public boolean readTimes(String fileName, Event event) throws
           IOException, ParseException {
226
            String input;
227
            int currentLineNumber = 0;
228
            int lastLineNumber = event.getLastLineRead();
229
            char competitorStatus;
230
            int competitorNumber;
231
            int nodeNumber;
232
            String[] subStrings;
233
            String pattern = "([A-Z{1}]((\s+\d+){2})\s
               +[0-2\{1\}][0-9\{1\}]:[0-5\{1\}][0-9\{1\}]$)"; //Regular expression for
                times file.
234
            SimpleDateFormat formatter = new SimpleDateFormat("HH:mm");
235
            Date time:
236
237
            event.getRecords().clear(); //Empties array list.
238
239
            try {
                FileChannel channel = new RandomAccessFile(fileName, "rw").
240
                    getChannel(); //Creates a channel for the file.
241
                FileLock lock = channel.lock(); //Blocks/Halts thread until lock
                     aquired.
242
243
                BufferedReader reader = new BufferedReader(new FileReader("
                    cp_times.txt"));
244
245
                while ((input = reader.readLine()) != null) {
246
                     currentLineNumber++;
247
                     if (currentLineNumber > lastLineNumber) {
                         if (input.matches(pattern)) { //Checks to make sure the
248
                            line is in the right format.
249
                             subStrings = input.split("[\\s+]"); //Gets rid of
                                whitespace and separates the strings into
                                substrings.
250
                             competitorStatus = subStrings[0].charAt(0); //
                                Retrieves competitor status.
251
                             nodeNumber = Integer.parseInt(subStrings[1]); //
                                Retrieves the node number by parsing the string
                                into an int.
252
                             competitorNumber = Integer.parseInt(subStrings[2]);
                                //Retrieves the competitor number by parsing the
                                string into an int.
253
                             time = formatter.parse(subStrings[3]); //Retrieves
                                the time being recorded and formats it into 24
                                hour HH: MM.
254
255
                             Competitor competitor = event.retrieveCompetitor(
                                competitorNumber);
256
                             if (competitor.getStatus() == 'T') {
257
                                 competitor.incrementCheckpointIndex(); //
```

```
Increments the competitor's checkpoint intdex
                                      by 1.
258
                             }
259
260
                             Record record = new Record(competitorStatus,
                                nodeNumber, competitorNumber, time); //Creates
                                 new record with parameters read in.
261
                             event.getRecords().add(record); //Adds new record to
                                  array list of records.
262
                             competitor.setStatus(competitorStatus); //Updates
                                 competitor's status.
263
264
                             event.setLastLineRead(currentLineNumber);
265
                             event.setLastRecordedTime(time);
266
267
                             System.out.print("Invalid line format. Cancelling
                                loading of times.\n\n");
268
                             reader.close();
269
                             lock.release();
270
                             channel.close();
271
                             return false;
272
                         }
273
                    }
274
                }
275
276
                 event.setTimesFilesExistsTrue(); //Lets the event instance know
                    that an event does exist.
277
                reader.close(); //Closes reader.
278
                lock.release(); //Releases file lock.
279
                 channel.close(); //Closes channel ensuring lock release and
                    release of resources.
280
                return true;
281
            } catch (FileNotFoundException ex) {
282
                 System.out.print("Could not open file that contains times.\n\n")
283
            }
284
            return false;
285
        }
286
287
        /**
288
         * Method to write a record on a line in the time records file.
289
290
         * Oparam fileName The file name required to access the file needed.
         * @param record The record to be written.
291
292
         * @return True if file written to successfully, else false if it fails
             at
293
         * any point.
294
         */
295
        public boolean appendTimeRecord(String fileName, Record record) {
296
            SimpleDateFormat formatter = new SimpleDateFormat("HH:mm");
297
298
            try {
299
                FileChannel channel = new RandomAccessFile(fileName, "rw").
                    getChannel(); //Creates a channel for the file.
300
                FileLock lock = channel.lock();
301
302
                FileWriter writer = new FileWriter(fileName, true); //True sets
                    append mode.
                writer.write(record.getCompetitorStatus() + " " + record.
303
                    getCheckpointNumber()
                         + " " + record.getCompetitorNumber() + " " + formatter.
304
                            format(record.getTime()) + "\n");
305
                writer.close();
```

```
306
                 lock.release();
307
                 channel.close();
308
                 return true;
309
             } catch (IOException ex) {
310
                 System.out.print("\nCould not open file for writing.\n\n");
311
312
             return false;
313
        }
314 || }
```

Listing 19: TypeWindow class.

```
/* File Name: TypeWindow.java
 1
    *\ \textit{Description: TypeWindow GUI class using swing.}
 2
 3
    * First Created: 17/03/2013
    * Last Modified: 18/03/2013
 4
 5
    */
 6
   package GUI;
 7
8
   import Data_Structures.Event;
   import java.awt.BorderLayout;
9
10
   import java.awt.Dimension;
11
   import java.awt.event.ActionEvent;
12
   import java.awt.event.ActionListener;
   import javax.swing.ButtonGroup;
13
14
   import javax.swing.ImageIcon;
15
   import javax.swing.JButton;
16
   import javax.swing.JFrame;
   import javax.swing.JLabel;
17
18
   import javax.swing.JPanel;
19
   import javax.swing.JRadioButton;
20
   import javax.swing.border.EmptyBorder;
21
22
   /**
23
    * @author Chris Savill, chs17@aber.ac.uk
24
25
   public class TypeWindow extends JFrame implements ActionListener {
26
27
       private Event event;
28
       private boolean medicalSelected;
29
       private JFrame typeFrame;
30
       private JPanel typePanel, bottomPanel;
31
       private JLabel typeLabel;
32
       private JRadioButton time, medical;
33
       private ButtonGroup typeGroup;
34
       private JButton next;
35
36
37
         * Constructor for TypeWindow GUI class that sets up and launches GUI.
38
39
         * Oparam event The event instance.
40
41
       public TypeWindow(Event event) {
42
            this.event = event;
43
            medicalSelected = false;
44
45
            //Setup frame:
            typeFrame = new JFrame("Checkpoint Type Selection");
46
47
            typeFrame.setPreferredSize(new Dimension(300, 200));
48
            typeFrame.setLocation(400, 200);
49
            typeFrame.setLayout(new BorderLayout());
            typeFrame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE); //Sets the
50
```

```
default close operation
51
          typeFrame.setIconImage(new ImageIcon("horse.jpg").getImage()); //
             Loads an image and sets it as the frame icon
52
          53
54
          //Setup panels:
          typePanel = new JPanel(new BorderLayout()); //Creates new JPanel.
55
56
          typePanel.setBorder(new EmptyBorder(25, 25, 25, 25));
             invisible border to simulate a padding effect
          typeFrame.add(typePanel, BorderLayout.NORTH); //Adds panel to frame
57
             and places it in NORTH container.
58
          bottomPanel = new JPanel();
          typeFrame.add(bottomPanel, BorderLayout.SOUTH); //Adds panel to
59
             frame and places it in SOUTH container.
60
          61
62
          //Setup checkpoint panel components:
63
          typeLabel = new JLabel("Select Checkpoint Type Below: ");
64
          typePanel.add(typeLabel, BorderLayout.NORTH);
65
          time = new JRadioButton("Time Checkpoint");
66
67
          time.setActionCommand("time");
68
          time.addActionListener(this);
69
          time.setSelected(true); //Defaults this button to be selected.
          typePanel.add(time, BorderLayout.CENTER);
70
71
          medical = new JRadioButton("Medical Checkpoint");
72
          medical.setActionCommand("medical");
73
          medical.addActionListener(this);
74
          medical.setSelected(false);
75
          typePanel.add(medical, BorderLayout.SOUTH);
76
77
          typeGroup = new ButtonGroup(); //Creates a group for the radio
             buttons to prevent both from being selected.
78
          typeGroup.add(time);
79
          typeGroup.add(medical);
          80
81
82
          //Setup bottom panel components:
83
          next = new JButton("Next");
84
          next.setPreferredSize(new Dimension(100, 50));
85
          bottomPanel.add(next);
86
          next.addActionListener(this);
          87
88
89
          //Finialise frame setup:
90
          typeFrame.pack();
91
          typeFrame.setVisible(true); //Makes the frame visible
          92
93
       }
94
95
96
        * Method to handle actions performed.
97
98
        * Oparam evt The event triggered.
99
        */
100
       @Override
       public void actionPerformed(ActionEvent evt) {
101
102
          String actionCommand = evt.getActionCommand();
103
104
          switch (actionCommand) {
105
              case "Next":
                  if (medicalSelected == true) {
106
                     typeFrame.setVisible(false);
107
```

```
108
                          SelectionWindow selectionWindow = new SelectionWindow(
                              event, "MC", typeFrame);
109
                      } else {
110
                          typeFrame.setVisible(false);
                          SelectionWindow selectionWindow = new SelectionWindow(
111
                             event, "CP", typeFrame);
112
                      }
113
114
                      typeFrame.dispose();
115
                      this.dispose();
116
                     break;
117
                 case "time":
118
                     medicalSelected = false;
119
                     break;
120
                 case "medical":
                      medicalSelected = true;
121
122
                     break;
123
             }
124
        }
125 || }
```

Listing 20: SelectionWindow class.

```
1 \parallel /* File Name: SelectionWindow.java
    * Description: SelectionWindow GUI class using swing.
 2
    * First Created: 16/03/2013
 3
 4
    * Last Modified: 17/03/2013
 5
    */
 6
   package GUI;
 7
   import Data_Structures.Competitor;
9
   import Data_Structures.Event;
10
   import Data_Structures.Node;
11
   import java.awt.BorderLayout;
12
   import java.awt.Color;
13
   import java.awt.Dimension;
   import java.awt.event.ActionEvent;
14
15
   import java.awt.event.ActionListener;
16
   import javax.swing.DefaultListModel;
   import javax.swing.ImageIcon;
17
   import javax.swing.JButton;
18
19
   import javax.swing.JFrame;
20
   import javax.swing.JLabel;
21
   import javax.swing.JList;
22
   import javax.swing.JOptionPane;
   import javax.swing.JPanel;
   import javax.swing.JScrollPane;
   import javax.swing.ScrollPaneConstants;
25
26
   import javax.swing.border.EmptyBorder;
27
   import javax.swing.border.LineBorder;
28
   import javax.swing.event.ListSelectionEvent;
29
   import javax.swing.event.ListSelectionListener;
30
31
32
   * @author Chris Savill, chs17@aber.ac.uk
33
34
   public class SelectionWindow extends JFrame implements ActionListener,
      ListSelectionListener {
35
36
       private Event event;
37
       private int checkpoint;
38
       private String type;
```

```
39
       private int competitor;
40
       private boolean checkpointSelected = false;
41
       private boolean competitorSelected = false;
42
       private JFrame selectionFrame, typeFrame;
       private JPanel checkpointPanel, competitorPanel, bottomPanel;
43
44
       private JLabel checkpointLabel, competitorLabel;
       private DefaultListModel checkpointListModel, competitorListModel;
45
       private JList checkpointList, competitorList;
46
       private JScrollPane checkpointListScrollBar, competitorListScrollBar;
47
48
       private JButton next;
49
50
       /**
        * Constructor for SelectionWindow GUI class, sets up and runs GUI.
51
        * Oparam event The event instance.
52
53
        * Oparam type The type of the checkpoint.
54
        * Oparam typeFrame The JFrame this transitioned from.
55
56
       public SelectionWindow(Event event, String type, JFrame typeFrame) {
57
           typeFrame.dispose();
           this.typeFrame = typeFrame;
58
           this.event = event;
59
60
           this.type = type;
61
62
           //Setup frame:
           selectionFrame = new JFrame("Checkpoint and Competitor Selection");
63
64
           selectionFrame.setLocation(400, 200);
65
           selectionFrame.setLayout(new BorderLayout());
66
           selectionFrame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE); //
              Sets the default close operation
67
           selectionFrame.setIconImage(new ImageIcon("horse.jpg").getImage());
              //Loads an image and sets it as the frame icon
           68
69
70
           //Setup panels:
           checkpointPanel = new JPanel(new BorderLayout()); //Creates new
71
              JPanel.
           checkpointPanel.setBorder(new EmptyBorder(10, 25, 10, 25));
72
              an invisible border to simulate a padding effect
73
           selectionFrame.add(checkpointPanel, BorderLayout.WEST); //Adds panel
               to frame and places it in WEST container.
74
           competitorPanel = new JPanel(new BorderLayout());
           competitorPanel.setBorder(new EmptyBorder(10, 25, 10, 25));
75
           selectionFrame.add(competitorPanel, BorderLayout.EAST); //Adds panel
76
               to frame and places it in EASTcontainer.
           bottomPanel = new JPanel();
           selectionFrame.add(bottomPanel, BorderLayout.SOUTH); //Adds panel to
78
               frame and places it in SOUTH container.
           79
80
81
           //Setup checkpoint panel components:
82
           checkpointLabel = new JLabel("Select Checkpoint Below: ");
           checkpointPanel.add(checkpointLabel, BorderLayout.NORTH);
83
84
85
           checkpointListModel = new DefaultListModel();
86
           checkpointList = new JList(checkpointListModel);
           checkpointList.setBorder(new LineBorder(Color.BLACK));
87
88
           checkpointPanel.add(checkpointList, BorderLayout.CENTER);
89
           checkpointList.addListSelectionListener(this);
90
91
           checkpointListScrollBar = new JScrollPane(checkpointList);
92
           checkpointListScrollBar.setPreferredSize(new Dimension(50, 100));
93
           checkpointListScrollBar.setVerticalScrollBarPolicy(
              ScrollPaneConstants.VERTICAL_SCROLLBAR_AS_NEEDED); //Adds
```

```
vertical scrollbar to JList
94
           checkpointListScrollBar.setHorizontalScrollBarPolicy(
              ScrollPaneConstants.HORIZONTAL_SCROLLBAR_AS_NEEDED); //Adds
              horizontal scrollbar to JList
95
           checkpointPanel.add(checkpointListScrollBar);
96
           97
98
           //Setup competitor panel components:
99
           competitorLabel = new JLabel("Select Competitor Below: ");
100
           competitorPanel.add(competitorLabel, BorderLayout.NORTH);
101
102
           competitorListModel = new DefaultListModel();
103
           competitorList = new JList(competitorListModel);
104
           competitorList.setBorder(new LineBorder(Color.BLACK));
105
           competitorPanel.add(competitorList, BorderLayout.CENTER);
106
           competitorList.addListSelectionListener(this);
107
108
           competitorListScrollBar = new JScrollPane(competitorList);
109
           competitorListScrollBar.setPreferredSize(new Dimension(400, 300));
110
           competitorListScrollBar.setVerticalScrollBarPolicy(
              ScrollPaneConstants.VERTICAL_SCROLLBAR_AS_NEEDED); //Adds
              vertical scrollbar to JList
111
           competitorListScrollBar.setHorizontalScrollBarPolicy(
              ScrollPaneConstants.HORIZONTAL_SCROLLBAR_AS_NEEDED); //Adds
              horizontal scrollbar to JList
112
           competitorPanel.add(competitorListScrollBar);
113
           114
115
           //Setup bottom panel components:
116
           next = new JButton("Next");
117
           next.setPreferredSize(new Dimension(100, 50));
           bottomPanel.add(next);
118
119
           next.addActionListener(this);
120
           121
122
           //Finialise frame setup:
123
           addCheckpoints();
124
           addCompetitors();
125
           selectionFrame.pack();
126
           selectionFrame.setVisible(true); //Makes the frame visible
127
           }
128
129
130
       /**
131
        * Method that adds the checkpoint checkpoints to the checkpoint JList
132
133
       public void addCheckpoints() {
           checkpointListModel.removeAllElements();
134
135
136
           for (Node currentCheckpoint : event.getCheckpoints()) {
137
               if (currentCheckpoint.getType().equals(type)) {
138
                  checkpointListModel.addElement(currentCheckpoint.getNumber()
                      + ": " + currentCheckpoint.getType());
139
              }
140
           }
       }
141
142
143
144
        st Method that adds the competitors to the competitor JList
145
146
       public void addCompetitors() {
147
           competitorListModel.removeAllElements();
148
```

```
149
            for (Competitor currentCompetitor : event.getCompetitors()) {
                 competitorListModel.addElement("Competitor: " +
150
                    currentCompetitor.getNumber()
                              Course: " + currentCompetitor.getCourse() + "
151
                            Name: " + currentCompetitor.getName());
            }
152
153
        }
154
155
        /**
156
         * Method to handle actions performed.
157
         * Oparam evt The event triggered.
158
         */
        @Override
159
160
        public void actionPerformed(ActionEvent evt) {
161
            String actionCommand = evt.getActionCommand();
162
163
            if (actionCommand.equals("Next")) {
                 if (checkpointSelected == true && competitorSelected == true) {
164
165
                     selectionFrame.setVisible(false);
166
                     TimeWindow timeWindow = new TimeWindow(event, checkpoint,
                        type, competitor, selectionFrame, typeFrame);
167
                     selectionFrame.dispose();
168
                     this.dispose();
169
                } else {
                     JOptionPane.showMessageDialog(selectionFrame, "Please select
170
                         both a checkpoint and competitor.");
                }
171
172
            }
173
        }
174
175
        /**
176
         * Method to handle values changing in a JList.
177
         * Oparam evt The event triggered.
178
         */
179
        @Override
180
        public void valueChanged(ListSelectionEvent evt) {
181
182
            if (!evt.getValueIsAdjusting()) {
                 JList list = (JList) evt.getSource();
183
184
185
                 if (list.equals(checkpointList)) {
186
                     checkpoint = event.retrieveCheckpointNumber(type, list.
                        getSelectedIndex(), list.getModel().getSize());
187
                     checkpointSelected = true;
188
                 } else if (list.equals(competitorList)) {
                     competitor = event.getCompetitors().get(list.
189
                        getSelectedIndex()).getNumber();
190
                     competitorSelected = true;
191
                }
192
            }
193
        }
194 || }
```

Listing 21: TimeWindow class.

```
import Data_Structures.Event;
8
9
   import Data_Structures.Record;
10 | import File_Handling.FileHandler;
11 | import java.awt.BorderLayout;
   import java.awt.Dimension;
12
13
   import java.awt.event.ActionEvent;
   import java.awt.event.ActionListener;
14
   import java.io.IOException;
15
16
   import java.text.ParseException;
17
   import java.util.Calendar;
18
   import java.util.Date;
19
   import java.util.logging.Level;
20
   import java.util.logging.Logger;
21
   import javax.swing.ImageIcon;
22
   import javax.swing.JButton;
23
   import javax.swing.JFrame;
24
   import javax.swing.JLabel;
25
   import javax.swing.JOptionPane;
26
   import javax.swing.JPanel;
27
   import javax.swing.JSpinner;
28
   import javax.swing.SpinnerDateModel;
29
   import javax.swing.border.EmptyBorder;
30
31
   /**
32
    * @author Chris Savill, chs17@aber.ac.uk
33
34
   public class TimeWindow extends JFrame implements ActionListener {
35
36
       private Event event;
37
       private FileHandler fileHandler;
38
       private int checkpoint;
39
       private String type;
40
       private int competitor;
41
       private int status;
42
       private JFrame timeFrame, typeFrame;
       private JPanel timePanel, bottomPanel;
43
44
       private JLabel timeLabel;
45
       private JButton submit;
46
       private Date date;
47
       private SpinnerDateModel spinnerModel;
48
       private JSpinner spinner;
49
       private JSpinner.DateEditor dateEditor;
50
       /**
51
52
         st Constructor for TimeWindow GUI class that sets up and launches the
53
54
        * Oparam event The event instance.
55
         * Oparam checkpoint The checkpoint number.
56
        * Oparam type The checkpoint type.
57
         * @param competitor The competitor number.
         * Oparam selectionFrame The JFrame this transitioned from.
58
59
         * @param typeFrame The JFrame that is reopened after this JFrame closes
60
         */
       public TimeWindow(Event event, int checkpoint, String type, int
61
           competitor, JFrame selectionFrame, JFrame typeFrame) {
62
           selectionFrame.dispose();
63
64
            this.typeFrame = typeFrame;
65
            this.event = event;
66
            this.checkpoint = checkpoint;
67
            this.type = type;
```

```
68
          this.competitor = competitor;
69
          fileHandler = new FileHandler();
70
71
          //Setup frame:
          timeFrame = new JFrame("Time Of Record");
72
73
74
          if (type.equals("MC")) {
75
              status = getMedicalOptions();
76
          } else {
77
              status = 0; //Comeptitor status not a medical related status.
78
          }
79
          timeFrame.setLocation(400, 200);
80
81
          timeFrame.setLayout(new BorderLayout());
          timeFrame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE); //Sets the
82
              default close operation
          timeFrame.setIconImage(new ImageIcon("horse.jpg").getImage()); //
83
             Loads an image and sets it as the frame icon
84
          85
86
          //Setup panels:
87
          timePanel = new JPanel(new BorderLayout()); //Creates new JPanel.
88
          timePanel.setBorder(new EmptyBorder(10, 25, 10, 25));
             invisible border to simulate a padding effect
          timeFrame.add(timePanel, BorderLayout.WEST); //Adds panel to frame
89
             and places it in WEST container.
90
          bottomPanel = new JPanel();
          timeFrame.add(bottomPanel, BorderLayout.SOUTH); //Adds panel to
91
             frame and places it in SOUTH container.
92
          93
          //Setup checkpoint panel components:
94
95
          timeLabel = new JLabel("Select Time Below: ");
96
          timePanel.add(timeLabel, BorderLayout.NORTH);
97
98
          date = new Date();
99
          spinnerModel = new SpinnerDateModel(date, null, null, Calendar.
             HOUR_OF_DAY);
100
          spinner = new JSpinner(spinnerModel);
101
          dateEditor = new JSpinner.DateEditor(spinner, "HH:mm"); //24-hour
102
          spinner.setEditor(dateEditor);
103
          timePanel.add(spinner, BorderLayout.CENTER);
          104
105
106
          //Setup bottom panel components:
107
          submit = new JButton("Submit Checkpoint Record");
108
          submit.setPreferredSize(new Dimension(225, 30));
109
          bottomPanel.add(submit);
110
          submit.addActionListener(this);
          111
112
113
          //Finialise frame setup:
114
          timeFrame.pack();
115
          timeFrame.setVisible(true); //Makes the frame visible
116
          117
       }
118
       /**
119
120
        * Method to handle actions performed.
121
122
        * Oparam evt The event triggered.
123
```

```
124
        @Override
125
        public void actionPerformed(ActionEvent evt) {
126
            String actionCommand = evt.getActionCommand();
127
128
            if (actionCommand.equals("Submit Checkpoint Record")) {
129
                try {
130
                    if (!fileHandler.readTimes(event.getFileNames()[3], event))
131
                         JOptionPane.showMessageDialog(timeFrame, "Failed to load
                             time records from file.");
132
                } catch (IOException | ParseException ex) {
133
134
                    Logger.getLogger(TimeWindow.class.getName()).log(Level.
                        SEVERE, null, ex);
135
                }
136
137
                if (event.checkNewRecord(checkpoint, status, competitor, (Date)
                    spinner.getValue())) {
138
                    char finalStatus = event.determineFinalStatus(checkpoint,
                        status, competitor);
139
                    Record record = new Record(checkpoint, finalStatus,
140
                        competitor, (Date) spinner.getValue());
141
                    event.getRecords().add(record);
142
143
                    fileHandler.appendTimeRecord(event.getFileNames()[3], record
144
                     JOptionPane.showMessageDialog(timeFrame, "Time record
                        successfully added.");
145
                     JOptionPane.showMessageDialog(timeFrame, "Non-valid record.
146
                        Record will not added.");
                }
147
148
149
                timeFrame.dispose(); //Closes frame and releases resourses.
                this.dispose(); //Releases resources.
150
                TypeWindow typeFrame = new TypeWindow(event);
151
152
153
            }
        }
154
155
156
157
         * Method to get the user to select the status of the competitor at the
158
         * medical checkpoint.
159
160
         * Greturn The status of the competitor at the medical checkpoint.
161
162
        public int getMedicalOptions() {
163
            String[] options = new String[]{"Arriving", "Departing", "Excluded"
               };
164
165
            int selection = JOptionPane.showOptionDialog(timeFrame, "Is the
               competitor being marked as 'Arriving',"
                    + " 'Departing' or as 'Excluded' on medical grounds?", "
166
                        Medical Marking", JOptionPane.DEFAULT_OPTION,
167
                     JOptionPane.PLAIN_MESSAGE, null, options, options[0]);
168
            if (selection == 0) {
169
                return 1; //Competitor status to be set to arriving at medical
170
                    checkpoint.
171
            } else if (selection == 1) {
172
                return 2; //Competitor status to be set to departing medical
                    checkpoint.
```

7 Clean build and compilation of Checkpoint Program

```
ant -f /home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Checkpoint_Manager_Program clean jar
init:
deps-clean:
Updating property file: /home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Checkpoint_Manager_Program/build/built-clean.properties
Deleting directory /home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Checkpoint_Manager_Program/build
clean:
init:
deps-jar:
Created dir: /home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Checkpoint_Manager_Program/build
Updating property file: /home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Checkpoint_Manager_Program/build/built-jar.properties
Created dir: /home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Checkpoint_Manager_Program/build/classes
Created dir: /home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Checkpoint_Manager_Program/build/empty
Created dir: /home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Checkpoint_Manager_Program/build/generated-sources/ap-source-output
Compiling 10 source files to /home/clsavill/GitHub/Runners_and_Riders_3_Part
   /Checkpoint_Manager_Program/build/classes
Note: /home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Checkpoint_Manager_Program/src/GUI/SelectionWindow.java uses unchecked or
    unsafe operations.
Note: Recompile with -Xlint:unchecked for details.
compile:
Created dir: /home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Checkpoint_Manager_Program/dist
Copying 1 file to /home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Checkpoint_Manager_Program/build
Nothing to copy.
Building jar: /home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Checkpoint_Manager_Program/dist/Checkpoint_Manager_Program.jar
To run this application from the command line without Ant, try:
java -jar "/home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Checkpoint_Manager_Program/dist/Checkpoint_Manager_Program.jar"
BUILD SUCCESSFUL (total time: 2 seconds)
```

8 Run through of Checkpoint Manager Program




Figure 1: Start up of GUI letting user know data file loaded successfully (if they did) else the program would close.




Figure 2: Checkpoint type selection window showing the time checkpoint type selected.




Figure 3: Message that pops up when both a checkpoint and competitor are not selected.




Figure 4: Time checkpoint 17 selection and competitor 3 selected within selection window.




Figure 5: Time window where the user has to input the time for the new record.



Figure 6: Message stating that the new record was successfully added and written to the time records file.



Figure 7: Checkpoint type selection window showing the medical checkpoint type selected.




Figure 8: Medical checkpoint 14 selection and competitor 17 selected within the selection window.



Figure 9: Prompt asking the user the status of the competitor at the chosen medical checkpoint.




Figure 10: Time window with a valid time entered (a time after the last record time.



Figure 11: Message stating that the new record was successfully added and written to the time records file.




Figure 12: The same record as above time window with an invalid time entered (a time before the last record time.



Figure 13: Message stating that the new record attempted to be added was invalid (either the time was before the last record, or the system determined that the status given cannot be correct due to the current status of the competitor.

9 Files created by execution of Checkpoint Manager Program

Listing 22: Copy of cp_times_1.txt file from event_3 that was read into the program plus 2 new records appended.

```
T 1 1 07:30
  1 3 07:33
 1 4 07:37
T 1 5 07:40
Т
 1 6 07:43
T 1 7 07:46
Т
 1 8 07:49
Т
 1 9 07:52
Τ
  1 10 07:55
    11 07:58
Т
 1 12 08:01
T 1 13 08:04
T 1 14 08:07
T 1 16 08:10
Т
 4 3 08:11
Т
  9 1 08:12
Τ
  1 17 08:13
  4 4 08:15
Т
 1 18 08:16
T 1 19 08:20
T 4 7 08:22
T 9 5 08:22
T 1 20 08:23
Т
 5 3 08:24
  4 6 08:25
  1 22 08:26
T 4 9 08:28
 1 23 08:29
T 5 4 08:30
T 1 24 08:32
T 4 10 08:32
```

- T 5 7 08:34
- T 9 8 08:34
- T 1 26 08:35
- T 4 12 08:36
- T 1 27 08:38
- T 5 6 08:38
- T 4 11 08:39
- T 4 13 08:40
- T 1 28 08:41
- T 5 9 08:42
- T 7 3 08:42
- T 4 14 08:43
- T 1 30 08:45
- T 5 10 08:47
- T 1 31 08:48
- T 4 17 08:49
- T 5 12 08:49
- T 13 1 08:50
- T 7 4 08:50
- T 1 32 08:51
- T 5 11 08:52
- - - - -
- T 7 7 08:52
- T 9 16 08:53
- T 1 34 08:54
- T 4 18 08:55
- T 5 13 08:55
- T 1 35 08:57
- T 4 19 08:57
- T 5 14 08:57
- T 13 5 08:59
- T 13 8 08:59
- T 1 36 09:00
- T 1 38 09:03
- T 4 20 09:03
- T 5 17 09:04
- T 4 23 09:05
- T 9 6 09:05
- T 1 39 09:06
- T 7 10 09:06
- T 4 22 09:07
- T 9 9 09:07
- T 7 12 09:08
- T 1 40 09:09
- T 5 18 09:10
- T 7 11 09:10
- T 5 19 09:11 T 1 41 09:12
- T 4 24 09:14
- T 1 42 09:15
- T 7 13 09:15
- T 5 20 09:16
- T 7 14 09:16
- T 13 16 09:17
- T 5 23 09:17
- T 1 44 09:18
- T 4 28 09:18
- T 5 22 09:19
- T 9 26 09:19
- T 9 27 09:19
- T 4 30 09:20 T 1 45 09:21
- A 14 3 09:22
- T 7 17 09:22

```
D 14 3 09:25
T 1 46 09:25
T 13 4 09:26
T 4 32 09:26
A 14 7 09:28
T 17 3 12:07
A 14 17 12:13
```

10 Clean build and compilation of Event Manager Program

```
"/usr/bin/make" -f nbproject/Makefile-Debug.mk QMAKE= SUBPROJECTS= .clean-
make[1]: Entering directory '/home/clsavill/GitHub/Runners_and_Riders_3_Part
   /Event_Manager_Program'
rm -f -r build/Debug
rm -f dist/Debug/GNU-Linux-x86/event_manager_program
make[1]: Leaving directory '/home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Event_Manager_Program '
CLEAN SUCCESSFUL (total time: 57ms)
"/usr/bin/make" -f nbproject/Makefile-Debug.mk QMAKE= SUBPROJECTS= .build-
make[1]: Entering directory '/home/clsavill/GitHub/Runners_and_Riders_3_Part
   /Event_Manager_Program'
"/usr/bin/make" -f nbproject/Makefile-Debug.mk dist/Debug/GNU-Linux-x86/
   event_manager_program
make[2]: Entering directory '/home/clsavill/GitHub/Runners_and_Riders_3_Part
   /Event_Manager_Program'
mkdir -p build/Debug/GNU-Linux-x86
rm -f build/Debug/GNU-Linux-x86/loader.o.d
     -c -g -MMD -MP -MF build/Debug/GNU-Linux-x86/loader.o.d -o build/
   Debug/GNU-Linux-x86/loader.o loader.c
mkdir -p build/Debug/GNU-Linux-x86
rm -f build/Debug/GNU-Linux-x86/logger.o.d
      -c -g -MMD -MP -MF build/Debug/GNU-Linux-x86/logger.o.d -o build/
   Debug/GNU-Linux-x86/logger.o logger.c
mkdir -p build/Debug/GNU-Linux-x86
rm -f build/Debug/GNU-Linux-x86/updater.o.d
      -c -g -MMD -MP -MF build/Debug/GNU-Linux-x86/updater.o.d -o build/
   Debug/GNU-Linux-x86/updater.o updater.c
mkdir -p build/Debug/GNU-Linux-x86
rm -f build/Debug/GNU-Linux-x86/courses.o.d
      -c -g -MMD -MP -MF build/Debug/GNU-Linux-x86/courses.o.d -o build/
& C C
   Debug/GNU-Linux-x86/courses.o courses.c
mkdir -p build/Debug/GNU-Linux-x86
rm -f build/Debug/GNU-Linux-x86/competitors.o.d
      -c -g -MMD -MP -MF build/Debug/GNU-Linux-x86/competitors.o.d -o build
gcc
   /Debug/GNU-Linux-x86/competitors.o competitors.c
mkdir -p build/Debug/GNU-Linux-x86
rm -f build/Debug/GNU-Linux-x86/nodes.o.d
      -c -g -MMD -MP -MF build/Debug/GNU-Linux-x86/nodes.o.d -o build/Debug
   /GNU-Linux-x86/nodes.o nodes.c
mkdir -p build/Debug/GNU-Linux-x86
rm -f build/Debug/GNU-Linux-x86/main.o.d
    -c -g -MMD -MP -MF build/Debug/GNU-Linux-x86/main.o.d -o build/Debug/
   {\tt GNU-Linux-x86/main.o} main.c
mkdir -p build/Debug/GNU-Linux-x86
rm -f build/Debug/GNU-Linux-x86/event.o.d
```

```
gcc -c -g -MMD -MP -MF build/Debug/GNU-Linux-x86/event.o.d -o build/Debug
  /GNU-Linux-x86/event.o event.c
mkdir -p build/Debug/GNU-Linux-x86
rm -f build/Debug/GNU-Linux-x86/tracks.o.d
gcc -c -g -MMD -MP -MF build/Debug/GNU-Linux-x86/tracks.o.d -o build/
  Debug/GNU-Linux-x86/tracks.o tracks.c
mkdir -p dist/Debug/GNU-Linux-x86
      -o dist/Debug/GNU-Linux-x86/event_manager_program build/Debug/GNU-
  Linux-x86/loader.o build/Debug/GNU-Linux-x86/logger.o build/Debug/GNU-
  Linux-x86/updater.o build/Debug/GNU-Linux-x86/courses.o build/Debug/GNU-
   Linux-x86/competitors.o build/Debug/GNU-Linux-x86/nodes.o build/Debug/GNU
   -Linux-x86/main.o build/Debug/GNU-Linux-x86/event.o build/Debug/GNU-Linux
   -x86/tracks.o
make[2]: Leaving directory '/home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Event_Manager_Program '
make[1]: Leaving directory '/home/clsavill/GitHub/Runners_and_Riders_3_Part/
   Event_Manager_Program '
```

BUILD SUCCESSFUL (total time: 857ms)

11 Run through of Event Manager Program

Event Monitoring Program Launching... Please enter in the file path and name of the event file: Mission_Files/event_3/name.txt Endurance Horse Race - The Main Event 27th June 2012 07:30 Event file loaded in successfully. Event loading finished. Please enter in the file path and name of the nodes file: Mission_Files/event_3/nodes.txt Head Node: Number: 1, Type: 0 = CP Node: Number: 2, Type: 1 = JN Node: Number: 3, Type: 1 = JN Node: Number: 4, Type: 0 = CP Node: Number: 5, Type: 0 = CP Node: Number: 6, Type: 1 = JN Node: Number: 7, Type: 0 = CP Node: Number: 8, Type: 1 = JN Node: Number: 9, Type: 0 = CP Node: Number: 10, Type: 1 = JN Node: Number: 11, Type: 1 = JN Node: Number: 12, Type: 1 = JN Node: Number: 13, Type: 0 = CP Node: Number: 14, Type: -13 = MCNode: Number: 15, Type: 1 = JN Node: Number: 16, Type: 1 = JN Node: Number: 17, Type: 0 = CP Node: Number: 18, Type: 1 = JN Nodes file loaded in successfully. Node loading finished.

Please enter in the file path and name of the tracks file: Mission_Files/event_3/tracks.txt

Track: Number: 2, Start: 2, End: 3, Max Time: 10 Track: Number: 3, Start: 3, End: 4, Max Time: 11 Track: Number: 4, Start: 4, End: 5, Max Time: 15 Track: Number: 5, Start: 5, End: 6, Max Time: 12 Track: Number: 6, Start: 6, End: 8, Max Time: 10 Track: Number: 7, Start: 6, End: 7, Max Time: 8 Track: Number: 8, Start: 7, End: 10, Max Time: 12 Track: Number: 9, Start: 8, End: 10, Max Time: 10 Track: Number: 10, Start: 8, End: 9, Max Time: 5 Track: Number: 11, Start: 3, End: 9, Max Time: 18 Track: Number: 12, Start: 9, End: 12, Max Time: 20 Track: Number: 13, Start: 2, End: 13, Max Time: 30 Track: Number: 14, Start: 12, End: 13, Max Time: 5 Track: Number: 15, Start: 10, End: 11, Max Time: 15 Track: Number: 16, Start: 11, End: 12, Max Time: 5 Track: Number: 17, Start: 11, End: 14, Max Time: 12 Track: Number: 18, Start: 14, End: 15, Max Time: 15 Track: Number: 19, Start: 15, End: 16, Max Time: 8 Track: Number: 20, Start: 16, End: 17, Max Time: 8 Track: Number: 21, Start: 17, End: 18, Max Time: 7 Track: Number: 22, Start: 15, End: 18, Max Time: 5 Tracks file loaded in successfully. Track loading finished. Please enter in the file path and name of the courses file: Mission_Files/event_3/courses.txt Head Course: ID: A, Number of Nodes: 21, Nodes: [1,2,3,4,5,6,7,10,11,14,15,16,17,18,15,14,11,12,13,2,1] Course: ID: B, Number of Nodes: 15, Nodes: [1,2,3,4,5,6,7,10,11,14,11,12,13,2,1] Course: ID: C, Number of Nodes: 13, Nodes: [1,2,3,4,5,6,7,10,11,12,13,2,1] Course: ID: D, Number of Nodes: 11, Nodes: [1,2,3,4,5,6,8,9,3,2,1] Course: ID: E, Number of Nodes: 11, Nodes: [1,2,3,9,8,10,11,12,13,2,1] Course: ID: F, Number of Nodes: 8, Nodes: [1,2,3,9,12,13,2,1]

Head Track: Number: 1, Start: 1, End: 2, Max Time: 20

Courses file loaded in successfully. Course loading finished.

```
Please enter in the file path and name of the competitors file: Mission_Files/event_3/entrants.txt
Head Competitor: Number: 1, Course: E, Name: Ace Abbey
Competitor: Number: 3, Course: A, Name: Ace Fudge
Competitor: Number: 4, Course: C, Name: Amber Abbey
Competitor: Number: 5, Course: E, Name: Amber Fudge
Competitor: Number: 6, Course: D, Name: April Abbey
Competitor: Number: 7, Course: B, Name: April Fudge
Competitor: Number: 8, Course: F, Name: Ash Abbey
Competitor: Number: 9, Course: D, Name: Ash Fudge
Competitor: Number: 10, Course: A, Name: Asti Abbey
Competitor: Number: 11, Course: A, Name: Asti Fudge
Competitor: Number: 12, Course: C, Name: Autumn Abbey
Competitor: Number: 13, Course: B, Name: Autumn Fudge
Competitor: Number: 14, Course: A, Name: Barfields Marco Abbey
Competitor: Number: 16, Course: F, Name: Barfields Marco Fudge
Competitor: Number: 17, Course: B, Name: Basil Abbey
Competitor: Number: 18, Course: A, Name: Basil Fudge
Competitor: Number: 19, Course: C, Name: Beatrice Abbey
Competitor: Number: 20, Course: A, Name: Beatrice Fudge
Competitor: Number: 22, Course: D, Name: Beau Abbey
Competitor: Number: 23, Course: C, Name: Beau Fudge
Competitor: Number: 24, Course: B, Name: Bella Abbey
Competitor: Number: 26, Course: F, Name: Bella Fudge
Competitor: Number: 27, Course: F, Name: Black Jack Abbey
Competitor: Number: 28, Course: A, Name: Black Jack Fudge
Competitor: Number: 30, Course: B, Name: Blue Abbey
Competitor: Number: 31, Course: B, Name: Blue Fudge
Competitor: Number: 32, Course: A, Name: Bobby Abbey
Competitor: Number: 34, Course: E, Name: Bobby Fudge
Competitor: Number: 35, Course: C, Name: Bubbles Abbey
Competitor: Number: 36, Course: D, Name: Bubbles Fudge
Competitor: Number: 38, Course: A, Name: Captain Abbey
Competitor: Number: 39, Course: B, Name: Captain Fudge
Competitor: Number: 40, Course: D, Name: Chalkie Abbey
Competitor: Number: 41, Course: F, Name: Chalkie Fudge
```

```
Competitor: Number: 42, Course: E, Name: Copper Abbey
Competitor: Number: 44, Course: B, Name: Copper Fudge
Competitor: Number: 45, Course: C, Name: Diamond Abbey
Competitor: Number: 46, Course: B, Name: Diamond Fudge
Competitor: Number: 47, Course: E, Name: Dinky Abbey
Competitor: Number: 48, Course: F, Name: Dinky Fudge
Competitor: Number: 49, Course: B, Name: Ebony Abbey
Competitor: Number: 50, Course: C, Name: Ebony Fudge
Competitor: Number: 51, Course: C, Name: Ginger Abbey
Competitor: Number: 52, Course: F, Name: Ginger Fudge
Competitor: Number: 53, Course: A, Name: Goldie Abbey
Competitor: Number: 55, Course: E, Name: Goldie Fudge
Competitor: Number: 56, Course: F, Name: Honey Abbey
Competitor: Number: 57, Course: C, Name: Honey Fudge
Competitor: Number: 58, Course: A, Name: Izzy Abbey
Competitor: Number: 59, Course: A, Name: Izzy Fudge
Competitor: Number: 60, Course: A, Name: Jasmine Abbey
Competitor: Number: 61, Course: F, Name: Jasmine Fudge
Competitor: Number: 62, Course: D, Name: Lady Abbey
Competitor: Number: 64, Course: B, Name: Lady Fudge
Competitor: Number: 65, Course: C, Name: Lady Tara Abbey
Competitor: Number: 66, Course: B, Name: Lady Tara Fudge
Competitor: Number: 67, Course: B, Name: Lemon Abbey
Competitor: Number: 68, Course: E, Name: Lemon Fudge
Competitor: Number: 69, Course: F, Name: Lord Abbey
Competitor: Number: 70, Course: E, Name: Lord Fudge
Competitor: Number: 71, Course: A, Name: Lucky Abbey
Competitor: Number: 74, Course: E, Name: Lucky Fudge
Competitor: Number: 76, Course: D, Name: Lord Abbey
Competitor: Number: 77, Course: B, Name: Lord Fudge
Competitor: Number: 78, Course: F, Name: Maddy Abbey
Competitor: Number: 79, Course: A, Name: Maddy Fudge
Competitor: Number: 80, Course: D, Name: Magic Abbey
Competitor: Number: 81, Course: D, Name: Magic Fudge
Competitor: Number: 83, Course: A, Name: Major Abbey
Competitor: Number: 85, Course: A, Name: Major Fudge
Competitor: Number: 86, Course: B, Name: Mattie Abbey
Competitor: Number: 87, Course: A, Name: Mattie Fudge
Competitor: Number: 89, Course: B, Name: Prince Abbey
Competitor: Number: 90, Course: A, Name: Prince Fudge
```

```
Competitor: Number: 91, Course: B, Name: Princess Abbey
Competitor: Number: 92, Course: B, Name: Princess Fudge
Competitor: Number: 93, Course: D, Name: Rosie Abbey
Competitor: Number: 94, Course: B, Name: Rosie Fudge
Competitor: Number: 95, Course: F, Name: Ruby Abbey
Competitor: Number: 97, Course: C, Name: Ruby Fudge
Competitor: Number: 98, Course: C, Name: Sapphire Abbey
Competitor: Number: 100, Course: F, Name: Sapphire Fudge
Competitor: Number: 101, Course: C, Name: Scarlet Abbey
Competitor: Number: 102, Course: F, Name: Scarlet Fudge
Competitor: Number: 103, Course: D, Name: sienna Abbey
Competitor: Number: 106, Course: B, Name: sienna Fudge
Competitor: Number: 107, Course: F, Name: Silver Abbey
Competitor: Number: 108, Course: A, Name: Silver Fudge
Competitor: Number: 109, Course: A, Name: Smokey Abbey
Competitor: Number: 110, Course: D, Name: Smokey Fudge
Competitor: Number: 111, Course: E, Name: Snowy Abbey
Competitor: Number: 113, Course: C, Name: Snowy Fudge
Competitor: Number: 114, Course: A, Name: sonic Abbey
Competitor: Number: 115, Course: D, Name: sonic Fudge
Competitor: Number: 117, Course: A, Name: Summer Abbey
Competitor: Number: 118, Course: E, Name: Summer Fudge
Competitor: Number: 121, Course: B, Name: Tango Abbey
Competitor: Number: 122, Course: A, Name: Tango Fudge
Competitor: Number: 123, Course: B, Name: Topaz Abbey
Competitor: Number: 124, Course: F, Name: Topaz Fudge
Competitor: Number: 126, Course: D, Name: Zizou Abbey
Competitor: Number: 127, Course: F, Name: Zizou Fudge
Competitors file loaded in successfully.
Competitor loading finished.
Loading Cycle Finished.
Press enter to continue.
```

| I : Query competitor for current location/status. | I : Display how many competitors have not started yet. | I : Display how many competitors are out on the courses.

```
| 4: Display how many competitors have completed their course successfully.
| 5: Read in a file of times at which competitors have reached time checkpoints.
| 6: Display the result times for the successfully completed.
| 7: Display the competitors who have been excluded.
| 8: Exit program.
Please select from one of the options above (number): 5
Please enter in the file path and name of the time record file: Mission_Files/event_3/cp_times_1.txt
End of file reached.
Loading of times files complete.
Time record loading finished.
Press enter to continue.
| 1: Query competitor for current location/status.
| 2: Display how many competitors have not started yet.
| 3: Display how many competitors are out on the courses.
| 4: Display how many competitors have completed their course successfully.
| 5: Read in a file of times at which competitors have reached time checkpoints.
| 6: Display the result times for the successfully completed.
| 7: Display the competitors who have been excluded.
| 8: Exit program.
Please select from one of the options above (number): 3
Printing competitors that are out on a course...
Number
                                                      | Course | Last Recorded Checkpoint | Presumed Location |
                              Name
______
   001 | Ace Abbey
                                                                                          TN - 01
```

1	003	Ace Fudge	l A	1	14	TN - 18
- 1	004	Amber Abbey	l C	1	13	TC - 13
- 1	005	Amber Fudge	l E	1	13	TN - 13
- 1		April Abbey	l D	1	09	TN - 02
- 1	007	April Fudge	I В	1	14	A - 14
1	008	Ash Abbey	l F	1	13	TN - 13
- 1	009	Ash Fudge	l D	1	09	TN - 02
1	010	Asti Abbey	l A	1	07	TN - 15
1	011	Asti Fudge	l A	1	07	TN - 15
1	012	Autumn Abbey	l C		07	TN - 15
1	013	Autumn Fudge	l В		07	TN - 08
1	014	Barfields Marco Abbey	l A		07	TN - 08
1	016	Barfields Marco Fudge	l F		13	TN - 13
1	017	Basil Abbey	l В		07	TN - 08
1	018	Basil Fudge	l A		05	TN - 07
- 1	019	Beatrice Abbey	l C		05	TN - 07
1	020	Beatrice Fudge	l A	1	05	TN - 05
1	022	Beau Abbey	l D	1	05	TN - 05
- 1	023	Beau Fudge	l C	1	05	TN - 05
- 1	024	Bella Abbey	l В	1	04	TN - 04
	026	Bella Fudge	l F		09	TN - 12
- 1	027	Black Jack Abbey	l F	1	09	TN - 12
- 1	028	Black Jack Fudge	l A	1	04	TN - 04
- 1	030	Blue Abbey	l В	1	04	TN - 04
- 1	031	Blue Fudge	I В		01	TN - 03
-	032	Bobby Abbey	l A		04	TC - 04
1	034	Bobby Fudge	l E		01	TN - 11
1	035	Bubbles Abbey	l C		01	TN - 02
1	036	Bubbles Fudge	l D		01	TN - 02
1	038	Captain Abbey	l A		01	TN - 02
I	039	Captain Fudge	l В		01	TN - 01
I	040	Chalkie Abbey	l D		01	TN - 01
I	041	Chalkie Fudge	l F		01	TN - 01
I	042	Copper Abbey	l E		01	TN - 01
	044	Copper Fudge	I В		01	TN - 01
	045	Diamond Abbey	l C		01	TN - 01
I	046	Diamond Fudge	l В	1	01	TN - 01
===	=======		======	========		

 $\mbox{Key: NS = Not Started, TC = Time Checkpoint, TN = Track Number, } \\$

```
A = Medical Checkpoint, D = Departed Medical Checkpoint.
Number of Competitors out on course: 38 out of 102
Current Event Time: 9:26.
Press enter to continue.
| 1: Query competitor for current location/status.
| 2: Display how many competitors have not started yet.
| 3: Display how many competitors are out on the courses.
| 4: Display how many competitors have completed their course successfully.
| 5: Read in a file of times at which competitors have reached time checkpoints.
| 6: Display the result times for the successfully completed.
| 7: Display the competitors who have been excluded.
| 8: Exit program.
Please select from one of the options above (number): 5
Please enter in the file path and name of the time record file: Mission_Files/event_3/cp_times_2.txt
End of file reached.
Loading of times files complete.
Time record loading finished.
Press enter to continue.
| 1: Query competitor for current location/status.
| 2: Display how many competitors have not started yet.
| 3: Display how many competitors are out on the courses.
| 4: Display how many competitors have completed their course successfully.
| 5: Read in a file of times at which competitors have reached time checkpoints.
```

```
| 6: Display the result times for the successfully completed.
| 7: Display the competitors who have been excluded.
| 8: Exit program.
Please select from one of the options above (number): 5
Please enter in the file path and name of the time record file: Mission_Files/event_3/cp_times_3.txt
End of file reached.
Loading of times files complete.
Time record loading finished.
Press enter to continue.
| 1: Query competitor for current location/status.
| 2: Display how many competitors have not started yet.
| 3: Display how many competitors are out on the courses.
| 4: Display how many competitors have completed their course successfully.
| 5: Read in a file of times at which competitors have reached time checkpoints.
| 6: Display the result times for the successfully completed.
| 7: Display the competitors who have been excluded.
| 8: Exit program.
Please select from one of the options above (number): 2
Printing competitors that have not yet started...
                                                          | Course | Location |
| Number |
   095 | Ruby Abbey
   097
       | Ruby Fudge
   098
       | Sapphire Abbey
```

1	100	- 1	Sapphire Fudge	1	F	1	NS	1
1	101	- 1	Scarlet Abbey		C	1	NS	1
1	102	- 1	Scarlet Fudge		F		NS	1
1	103	- 1	sienna Abbey		D	1	NS	1
1	106	- 1	sienna Fudge		В		NS	1
1	107	- [Silver Abbey	1	F	1	NS	
	108	- 1	Silver Fudge		Α	1	NS	
	109	- 1	Smokey Abbey		Α	1	NS	-
	110	- 1	Smokey Fudge		D	1	NS	-
	111	- 1	Snowy Abbey		E	1	NS	
	113	- 1	Snowy Fudge		C	1	NS	
	114	- 1	sonic Abbey		Α	1	NS	
	115	- 1	sonic Fudge		D	1	NS	
	117	- 1	Summer Abbey		Α	1	NS	
	118	- 1	Summer Fudge		E	1	NS	
	121	- 1	Tango Abbey		В	1	NS	
	122	- 1	Tango Fudge		Α	1	NS	
	123	- 1	Topaz Abbey		В	1	NS	
	124	- 1	Topaz Fudge		F	1	NS	
	126	- 1	Zizou Abbey		D	1	NS	
	127	- 1	Zizou Fudge		F		NS	
===	=====	==		====	=====	====	======	==

Key: NS = Not Started.

Number of Competitors not started yet: 24 out of 102

Current Event Time: 11:39.

Press enter to continue.

| I: Query competitor for current location/status. | I: Display how many competitors have not started yet. | I: Display how many competitors are out on the courses. | I: Display how many competitors have completed their course successfully.

 \mid 5: Read in a file of times at which competitors have reached time checkpoints.

 \mid 6: Display the result times for the successfully completed.

```
| 7: Display the competitors who have been excluded.
| 8: Exit program.
```

Please select from one of the options above (number): 3

Printing competitors that are out on a course...

==:		===		=======		=======================================
1	Number	١	Name	Course	Last Recorded Checkpoint	Presumed Location
==:	======	===				
!	010		Asti Abbey	I A	13	TN - 01
!	011		Asti Fudge	I A	13	TN - 01
- !	014	- !	Barfields Marco Abbey	I A	13	TN - 13
-	018		Basil Fudge	l A	13	TN - 13
	020	١	Beatrice Fudge	l A	13	TN - 13
-	028		Black Jack Fudge	l A	14	TN - 20
-	032	- 1	Bobby Abbey	l A	14	TN - 17
	038	- 1	Captain Abbey	l A	17	TN - 22
-	039	- 1	Captain Fudge	I В	13	TN - 13
	044	- 1	Copper Fudge	l В	14	TN - 14
-	045	- 1	Diamond Abbey	l C	13	TN - 01
1	049	- 1	Ebony Abbey	I В	14	TN - 17
-	050	- 1	Ebony Fudge	l C	13	TN - 13
-	051	- 1	Ginger Abbey	l C	13	TN - 13
- 1	052	- 1	Ginger Fudge	l F	13	TN - 01
- 1	055	- 1	Goldie Fudge	l E	13	TN - 13
1	056	- 1	Honey Abbey	l F	13	TN - 01
-	057	- 1	Honey Fudge	l C	07	TN - 16
- 1	058	- 1	Izzy Abbey	l A	07	TN - 17
- 1	060	- 1	Jasmine Abbey	l A	07	TN - 15
- 1	061	- 1	Jasmine Fudge	l F	13	TN - 13
-	062	- 1	Lady Abbey	l D	l 09	TN - 11
- 1	064	- 1	Lady Fudge	I В	07	TN - 08
- 1	065	- 1	Lady Tara Abbey	l C	07	TN - 08
- 1	066	- 1	Lady Tara Fudge	l В	07	TN - 08
-	067	- 1	Lemon Abbey	l В	07	TN - 08
1	068	١	Lemon Fudge	l E	09	TN - 15
- 1	069	- 1	Lord Abbey	l F	13	TN - 13

	070	Lord Fudge		E	1	09	1	TN - 15	1
	071	Lucky Abbey		Α	1	05	1	TN - 05	
	074	Lucky Fudge	1	E	1	09	1	TN - 09	
	076	Lord Abbey		D	1	05	1	TC - 05	1
	077	Lord Fudge		В	1	04	1	TN - 04	1
	078	Maddy Abbey		F	1	09	1	TN - 12	- 1
	079	Maddy Fudge		Α	1	04	1	TN - 04	1
	080	Magic Abbey		D	1	01	1	TN - 03	1
	081	Magic Fudge		D	1	01	1	TN - 03	1
	083	Major Abbey		Α	1	01	1	TN - 03	- 1
- 1	085	Major Fudge	1	Α	1	01	1	TN - 02	1
	086	Mattie Abbey		В	1	01	1	TN - 02	- 1
- 1	087	Mattie Fudge	1	Α	1	01	1	TN - 02	1
- 1	089	Prince Abbey	1	В	1	01	1	TN - 01	1
- 1	090	Prince Fudge	1	Α	1	01	1	TN - 01	1
- 1	091	Princess Abbey	1	В	1	01	1	TN - 01	1
	092	Princess Fudge		В	1	01	1	TN - 01	1
-	093	Rosie Abbey		D	1	01	1	TN - 01	- 1
-	094	Rosie Fudge		В	1	01	1	TN - 01	- 1
==	:	- ====================================			====			=========	====

```
Key: NS = Not Started, TC = Time Checkpoint, TN = Track Number, A = Medical Checkpoint, D = Departed Medical Checkpoint.
```

Number of Competitors out on course: 47 out of 102

Current Event Time: 11:39.

Press enter to continue.

```
| 1: Query competitor for current location/status. | 2: Display how many competitors have not started yet. | 3: Display how many competitors are out on the courses. | 4: Display how many competitors have completed their course successfully. | 5: Read in a file of times at which competitors have reached time checkpoints. | 6: Display the result times for the successfully completed. | 7: Display the competitors who have been excluded.
```

```
| 8: Exit program.
```

Please select from one of the options above (number): 4

Printing competitors that have finished...

=												
-	Number	-	Name	Course	Location							
=	======	==		=======								
	001		Ace Abbey	l E	l CC l							
	003	ı	Ace Fudge	l A	l CC l							
	004		Amber Abbey	l C	l CC l							
	005		Amber Fudge	l E	l CC l							
	006	- 1	April Abbey	l D	CC I							
-	007	-	April Fudge	l В	l CC l							
	800	- 1	Ash Abbey	l F	CC I							
-	009	- 1	Ash Fudge	l D	l CC l							
	012	- 1	Autumn Abbey	l C	l CC l							
	013	- 1	Autumn Fudge	l В	l CC l							
	016	- 1	Barfields Marco Fudge	l F	l CC l							
	017	- 1	Basil Abbey	l В	l CC l							
	019	- 1	Beatrice Abbey	l C	l CC l							
	022	- 1	Beau Abbey	l D	l CC l							
	024	- 1	Bella Abbey	l В	l CC l							
	026	- 1	Bella Fudge	l F	l CC l							
-	027	- 1	Black Jack Abbey	l F	l CC l							
-	030	- 1	Blue Abbey	l В	l CC l							
-	031	- 1	Blue Fudge	l В	l CC l							
	034	- 1	Bobby Fudge	l E	l CC l							
	035	- 1	Bubbles Abbey	l C	l CC l							
-	040	- 1	Chalkie Abbey	l D	l CC l							
	042	- 1	Copper Abbey	l E	l CC l							
	047	- 1	Dinky Abbey	l E	l CC l							
I	048	I	Dinky Fudge	l F	CC I							
=		==		=====								

Number of Competitors completed course successfully: 25 out of 102

Current Event Time: 11:39.

Press enter to continue.

| 1: Query competitor for current location/status. | 2: Display how many competitors have not started yet. | 3: Display how many competitors are out on the courses. | 4: Display how many competitors have completed their course successfully. | 5: Read in a file of times at which competitors have reached time checkpoints. | 6: Display the result times for the successfully completed. | 7: Display the competitors who have been excluded. | 8: Exit program. |

Please select from one of the options above (number): 6

Printing results...

_							
Ī	Number		Name	Status	1	Time	1
=	. = = = = = =	==	=======================================				
	001		Ace Abbey	l cc		02:04	ı
	003		Ace Fudge	l CC		03:52	
-	004	- 1	Amber Abbey	l CC	1	02:37	
-	005	-	Amber Fudge	l CC	1	02:11	
-	006		April Abbey	l CC	1	02:03	
-	007	- 1	April Fudge	l CC	1	02:46	
-	800	-	Ash Abbey	l CC	1	01:56	
-	009	-	Ash Fudge	l CC	1	01:58	
-	012	- 1	Autumn Abbey	l CC	1	02:30	
-	013		Autumn Fudge	l CC	1	02:53	
-	016		Barfields Marco Fudge	l CC	1	01:55	
-	017		Basil Abbey	l CC	1	02:49	
-	019		Beatrice Abbey	l CC	1	02:27	
-	022	-	Beau Abbey	l CC	1	02:02	
- 1	024	- 1	Bella Abbev	l CC	1	02:54	- 1

I	026	ı	Bella Fudge	1	CC	ı	01:49	ı
1	027		Black Jack Abbey		CC		01:49	
1	030	-1	Blue Abbey	1	CC	1	02:43	
1	031	-	Blue Fudge		CC		02:44	
1	034	- [Bobby Fudge		CC		02:03	
1	035	- 1	Bubbles Abbey		CC		02:32	
1	040		Chalkie Abbey		CC		02:03	
1	042		Copper Abbey		CC		02:05	
1	047		Dinky Abbey		CC		02:10	
1	048	- 1	Dinky Fudge		CC		01:54	
===	=====	==:		====		====		==
Num	ber of	C	ompetitors completed course successfully: 25 out of	102				
Cur	rent E	vei	nt Time: 11:39.					
Pre	ss ent	er	to continue.					

Please select from one of the options above (number): 7

Printing excluded...

==	======	=======================================	.==========	=========	======			==
1	Number	I	Name	I	Status	I	At Time	I
	023	Beau Fudge			EI		09:49	==

```
| Bubbles Fudge
                                                                      09:57
   036
   041
        | Chalkie Fudge
                                                                      11:05
        | Diamond Fudge
                                                                      11:13
   046
   059
        | Izzy Fudge
                                                                      11:10
Number of Competitors excluded: 5 out of 102
Key: EI = Excluded for taking an Incorrect Route, EM = Excluded for Medical Safety Reasons.
Current Event Time: 11:39.
Press enter to continue.
| 1: Query competitor for current location/status.
| 2: Display how many competitors have not started yet.
| 3: Display how many competitors are out on the courses.
| 4: Display how many competitors have completed their course successfully.
| 5: Read in a file of times at which competitors have reached time checkpoints.
| 6: Display the result times for the successfully completed.
| 7: Display the competitors who have been excluded.
| 8: Exit program.
Please select from one of the options above (number): 8
Exiting Program...
RUN SUCCESSFUL (total time: 2m 5s)
```

12 Results list produced at the end of an event

12.1 Results of successful competitors

lumber	Name	Status	Time
001	Ace Abbey		02:04
003	Ace Fudge	I CC I	03:52
004	Amber Abbey	l CC l	02:37
005	Amber Fudge	l CC l	02:11
006	April Abbey	l CC l	02:03
007	April Fudge	i cc i	02:46
008	Ash Abbey	i cc i	01:56
009	Ash Fudge	i cc i	01:58
010	Asti Abbey	l CC l	03:49
011	Asti Fudge	l cc l	03:51
012	Autumn Abbey	l cc l	02:30
	Autumn Fudge	l CC l	02:53
	Barfields Marco Abbey	l cc l	03:49
	Barfields Marco Fudge	i cc i	01:55
017	Basil Abbey	I CC I	02:49
018	Basil Fudge	l CC l	03:50
019	Beatrice Abbey	l CC l	02:27
020	Beatrice Fudge	l cc l	03:50
022	Beau Abbey	l cc l	02:02
024	Bella Abbey	l CC l	02:54
026	Bella Fudge	l CC l	01:49
027	Black Jack Abbey	l CC l	01:49
030	Blue Abbey	l cc l	02:43
031	Blue Fudge	l cc l	02:44
032	Bobby Abbey	l cc l	03:52
034	Bobby Fudge	l cc l	02:03
035	Bubbles Abbey	l cc l	02:32
038	Captain Abbey	l CC l	03:52
039	Captain Fudge	l CC l	02:51
040	Chalkie Abbey	l CC l	02:03
042	Copper Abbey	l CC l	02:05
045	Diamond Abbey	l CC l	02:29
047	Dinky Abbey	l CC l	02:10
048	Dinky Fudge	l CC l	01:54
049	Ebony Abbey	l CC l	03:04
050	Ebony Fudge	l cc l	02:35
051	Ginger Abbey	l CC l	02:32

1	052	Ginger Fudge	l CC	01:58
1	055	Goldie Fudge	l CC	02:12
	056	Honey Abbey	l CC	01:54
	057	Honey Fudge	l CC	02:36
	058	Izzy Abbey	l CC	03:53
	060 l	Jasmine Abbey	l CC	03:50
- 1	061	Jasmine Fudge	l CC	01:55
- 1	064 l	Lady Fudge	l CC	02:59
- 1	065 l	Lady Tara Abbey	l CC	02:29
- 1	066 l	Lady Tara Fudge	l CC	02:50
- 1	067 l	Lemon Abbey	l CC	03:02
- 1	069 l	Lord Abbey	l CC	01:54
-	070 l	Lord Fudge	l CC	02:14
-	074 l	Lucky Fudge	l CC	02:12
-	076 l	Lord Abbey	l CC	02:03
-	077	Lord Fudge	l CC	02:56
- 1	079	Maddy Fudge	l CC	03:54
- 1	080 l	Magic Abbey	l CC	02:04
- 1	081	Magic Fudge	l CC	02:02
-	083	Major Abbey	l CC	03:43
-	086	Mattie Abbey	l CC	02:52
-	087	Mattie Fudge	l CC	03:52
- 1	089	Prince Abbey	l CC	02:59
- 1	090 l	Prince Fudge	l CC	04:00
-	091	Princess Abbey	l CC	03:01
- 1	092	Princess Fudge	l CC	03:02
- 1	093	Rosie Abbey	l CC	01:59
- 1	094	Rosie Fudge	l CC	02:45
- 1	095	Ruby Abbey	l CC	01:59
- 1	097	Ruby Fudge	l CC	02:36
- 1	098	Sapphire Abbey	l CC	02:30
- 1	100 l	Sapphire Fudge	l CC	01:57
- 1	101 I	Scarlet Abbey	l CC	02:35
- 1	102	Scarlet Fudge	l CC	01:56
1	103	sienna Abbey	l CC	02:02
-	107 l	Silver Abbey	l CC	01:56
- 1	108	Silver Fudge	l CC	03:43
- 1	109	Smokey Abbey	l CC	03:55
- 1	110 l	Smokey Fudge	l CC	02:03
- 1	113	Snowy Fudge	l CC	02:28

	114	sonic Abbey	l CC	1	03:47	1
1	115	sonic Fudge	l CC		02:03	1
1	117	Summer Abbey	l CC		03:58	1
	118	Summer Fudge	l CC	- 1	02:10	-
	121	Tango Abbey	l CC	- 1	02:57	-
	122	Tango Fudge	l CC	- 1	04:02	-
	123	Topaz Abbey	l CC		02:54	-
	124	Topaz Fudge	l CC		01:53	-
	126	Zizou Abbey	l CC		02:03	-
1	127	Zizou Fudge	l CC	1	01:55	1
===	=====			====		==

Number of Competitors completed course successfully: 87 out of 102

Current Event Time: 16:48.

12.2 Table of excluded competitors

Number	Name	1	Status	I	At Time	l
023	======================================	 	EI	=== 	09:49	<u>-</u>
028	Black Jack Fudge	ĺ	ΕI	Ī	11:46	ı
l 036	Bubbles Fudge	1	ΕI	-	09:57	ı
041	Chalkie Fudge	1	ΕI	-	11:05	ı
044	Copper Fudge	1	ΕI		11:47	ı
1 046	Diamond Fudge	1	ΕI		11:13	ı
053	Goldie Abbey	1	ΕI		12:57	ı
059	Izzy Fudge	1	ΕI		11:10	l
062	Lady Abbey	1	ΕI		13:01	l
l 068	Lemon Fudge	1	ΕI		12:54	ı
071	Lucky Abbey	1	ΕI	-	13:56	l
078	Maddy Abbey	1	ΕI	-	12:55	l
l 085	Major Fudge	1	ΕI	-	14:23	l
106	sienna Fudge	1	ΕI	-	14:53	l
111	Snowy Abbey	1	EI	1	13:36	

Number of Competitors excluded: 15 out of 102

Key: EI = Excluded for taking an Incorrect Route, EM = Excluded for Medical Safety Reasons.

Current Event Time: 16:48.

13 Log file contents

```
Action: Read in a time records file, Date: Tue Mar 19 17:07:56 2013
Action: Viewed results of competitors that completed their course successfully, Date: Tue Mar 19 17:07:56 2013
Action: Queried competitor, Date: Tue Mar 19 17:08:25 2013
Action: Viewed results of competitors that completed their course successfully, Date: Tue Mar 19 17:08:30 2013
Action: Quit Program, Date: Tue Mar 19 17:08:32 2013
Action: Read in a time records file, Date: Tue Mar 19 17:15:06 2013
Action: Viewed list of competitors out on course, Date: Tue Mar 19 17:15:13 2013
Action: Read in a time records file, Date: Tue Mar 19 17:15:38 2013
Action: Read in a time records file, Date: Tue Mar 19 17:15:56 2013
Action: Viewed list of competitors not started, Date: Tue Mar 19 17:16:03 2013
Action: Viewed list of competitors out on course, Date: Tue Mar 19 17:16:08 2013
Action: Viewed list of competitors that have finished, Date: Tue Mar 19 17:16:13 2013
Action: Viewed results of competitors that completed their course successfully, Date: Tue Mar 19 17:16:17 2013
Action: Viewed results of competitors that were excluded, Date: Tue Mar 19 17:16:19 2013
Action: Quit Program, Date: Tue Mar 19 17:16:27 2013
Action: Read in a time records file, Date: Wed Mar 20 11:19:11 2013
Action: Read in a time records file, Date: Wed Mar 20 11:19:25 2013
Action: Read in a time records file, Date: Wed Mar 20 11:19:31 2013
Action: Read in a time records file, Date: Wed Mar 20 11:19:38 2013
Action: Read in a time records file, Date: Wed Mar 20 11:19:43 2013
Action: Viewed results of competitors that completed their course successfully, Date: Wed Mar 20 11:19:56 2013
Action: Viewed results of competitors that were excluded, Date: Wed Mar 20 11:20:00 2013
```