

MixedComplementarityProblems.jl: A Fast, Batched, Open-Source Interior-Point Solver for Mixed Complementarity Problems

David Fridovich-Keil

Department of Aerospace Engineering and Engineering Mechanics
The University of Texas at Austin
Austin, TX, USA
dfk@utexas.edu

Abstract—Mixed complementarity problems (MCPs) arise as the first-order optimality conditions of nonlinear programs and noncooperative games, and give a natural formulation for the multi-agent trajectory optimization problems that appear throughout robotics. The dominant solver for problems of this form is `PATH`, a mature but closed-source package. We present `MixedComplementarityProblems.jl`, an open-source, pure Julia implementation of an interior-point method for parametric MCPs that (i) matches `PATH`’s reliability on standard benchmarks and (ii) natively supports batched solving, in which many parameter instances are solved simultaneously and in parallel, either across CPU threads or on an NVIDIA GPU, behind a single solver implementation. On a multi-agent lane-change trajectory game representative of robotics planning problems, our CPU-multithreaded batched solver clears a batch of parametric instances 60–80 $\times$ faster than sequential calls to `PATH`, and our GPU backend clears the same batches roughly 20 $\times$ faster than `PATH` **[TODO: finalize the GPU-vs-CPU comparison for the trajectory game once the latest benchmark numbers are in—earlier runs showed GPU trailing CPU here, but that may no longer hold]**. We describe the solver’s interior-point formulation, the abstraction that lets a single solver implementation run unmodified across dense, batched-sparse, and single-large linear-algebra backends, and report benchmarks against `PATH` on both randomly generated quadratic programs and trajectory games.

I. INTRODUCTION

Multi-agent trajectory planning problems in robotics, ranging from autonomous driving to human-robot interaction, are naturally posed as noncooperative dynamic games, in which each agent optimizes its own trajectory subject to the others’ choices. The first-order necessary conditions of optimality for each agent in the game take the form of a mixed complementarity problem (MCP). Solving MCPs rapidly, therefore, becomes a core computational burden for real-time decision-making in multi-agent robotics applications.

The dominant solver for this class of problems is `PATH` [1]. `PATH` is mature, reliable, and widely used; but, it is closed-source, solves one problem instance at a time, and was not designed to support automatic differentiation of solutions with respect to problem parameters. All three pose serious, practical limitations for use in robotics: (i) developers must have access to solver internals in order to customize to the problem at hand, (ii) scenario- and contingency-based planning (e.g., [2], [3]) requires solving a *batch* of identically-structured but differently *parameterized* problems, and (iii) modern machine learning pipelines often embed optimization problem solvers as “layers” [4], and end-to-end differentiability requires us to

be able to differentiate a solver’s output with respect to its input parameters.

We present `MixedComplementarityProblems.jl`, an open-source, pure Julia solver for parametric MCPs that addresses all of these practical challenges. Concretely, we contribute:

- A simple and easily-customized interior-point method for parametric MCPs that matches `PATH`’s reliability on standard benchmarks, while supporting automatic differentiation of solutions with respect to problem parameters.
- A native *batched* solve mode, in which many parameter instances sharing one MCP structure are solved simultaneously, parallelized across CPU threads or an NVIDIA GPU behind a single solver implementation.
- An abstraction boundary defined by a small verb set that separates the interior-point loop and its linear algebra backend, which lets a single solver implementation run unmodified across dense, batched-sparse, and single-large-instance regimes, so that supporting a new device or linear-algebra strategy never requires touching the solver loop itself.

As Figure 1 previews and Section V quantifies, on a multi-agent lane-change trajectory game representative of robotics planning problems, clearing a batch of parametric instances with our batched solver takes a small fraction of the wall-clock time required to clear the same batch with sequential calls to `PATH`. **[TODO: replace with the top-line numerical speedup results when they are finalized]**

II. BACKGROUND: MIXED COMPLEMENTARITY PROBLEMS

A. Problem definition

A mixed complementarity problem is specified by a map $F : \mathbb{R}^n \rightarrow \mathbb{R}^n$ and bounds $\ell, u \in (\mathbb{R} \cup \{\pm\infty\})^n$; a solution is a vector $z \in \mathbb{R}^n$ satisfying, for every coordinate dimension i ,

$$\begin{aligned} \ell_i < z_i < u_i &\implies F_i(z) = 0, \\ z_i = \ell_i &\implies F_i(z) \geq 0, \\ z_i = u_i &\implies F_i(z) \leq 0. \end{aligned} \tag{1}$$

Readers are referred to [5] for a complete introduction to MCPs and related problems.

[TODO: replace with rendered lane-change trajectory game schematic, showing the two vehicles' solved trajectories overlaid with a faint fan of trajectories from other initial conditions in the same batch]

(a) One multi-agent trajectory game is one instance out of a batch of parametrically related MCPs, solved simultaneously.

[TODO: replace with wall-clock-vs-batch-size plot: PATH (serial), CPU-batched, and GPU-batched, log-scaled y-axis]

(b) Clearing that batch: sequential PATH calls versus our batched CPU and GPU solves.

Fig. 1. [TODO: finalize caption once the real figure is in] Solving a batch of parametric trajectory-game instances (a) with `MixedComplementarityProblems.jl`'s batched interior-point solver is substantially faster than solving the same batch with sequential calls to `PATH` (b).

B. MCPs from KKT conditions

Consider a parametric nonlinear program

$$\min_x f(x; \theta) \quad \text{s.t.} \quad g(x; \theta) = 0, \quad h(x; \theta) \geq 0, \quad (2)$$

with primal variables $x \in \mathbb{R}^{n_x}$, parameters θ , and Lagrange multipliers $\lambda \in \mathbb{R}^{n_\lambda}$ associated with the equality constraint g and $\mu \in \mathbb{R}_{\geq 0}^{n_\mu}$ associated with the inequality constraint h . The first order necessary (i.e. Karush-Kuhn-Tucker, KKT) conditions of optimality for problem (2) are

$$0 = \begin{bmatrix} \overbrace{\nabla_x f(x; \theta) - \nabla_x g(x; \theta)^\top \lambda - \nabla_x h(x; \theta)^\top \mu}^{G(x, \lambda, \mu; \theta)} \\ g(x; \theta) \end{bmatrix} \quad (3a)$$

$$0 \leq \underbrace{h(x; \theta)}_{H(x, \lambda, \mu; \theta)} \perp \mu \geq 0. \quad (3b)$$

Problem (3) can be converted into the form (1) by taking $z = (x, \lambda, \mu)$, $F = (G, H)$, $u_i = \infty$ ($\forall i$), $\ell_i = -\infty$ ($\forall i \in \{1, 2, \dots, n_x + n_\lambda\}$), and $\ell_i = 0$ ($\forall i > n_x + n_\lambda$). Because of the natural connection between KKT conditions (e.g., arising from trajectory optimization problems in robotics) and this *primal-dual* form of the MCP, it is the only form `MixedComplementarityProblems.jl` exposes.

C. MCPs from noncooperative games

The construction in Section II-B extends from one decision maker to many. Consider N agents, where agent i solves

$$\forall i \begin{cases} \min_{x_i} f_i(x_i, x_{-i}; \theta) \\ \text{s.t.} \quad g_i(x_i, x_{-i}; \theta) = 0, \quad h_i(x_i, x_{-i}; \theta) \geq 0 \end{cases} \quad (4a)$$

$$\text{s.t.} \quad g_{\text{sh}}(x; \theta) = 0, \quad h_{\text{sh}}(x; \theta) \geq 0, \quad (4b)$$

subject to its own equality and inequality constraints (g_i and h_i , respectively) and to constraints $g_{\text{sh}}, h_{\text{sh}}$ shared across

agents (e.g., pairwise collision avoidance). Each agent i 's decision variable is $x_i \in \mathbb{R}^{n_{x_i}}$, and x_{-i} denotes the other agents' decisions so that $x = (x_i, x_{-i}) = (x_1, \dots, x_N)$. Writing out each agent's KKT conditions as in (3) and concatenating them—with the shared constraints $g_{\text{sh}}, h_{\text{sh}}$ coupling agents through shared multipliers $\lambda_{\text{sh}}, \mu_{\text{sh}}$ —yields a single primal-dual MCP whose solution is a generalized Nash equilibrium: a strategy profile from which no agent can unilaterally improve its own objective [5].

Concretely, concatenate the agents' primal variables as $x = (x_1, \dots, x_N)$ and their private multipliers as $\lambda_{\text{priv}} = (\lambda_1, \dots, \lambda_N)$, $\mu_{\text{priv}} = (\mu_1, \dots, \mu_N)$, and append a single pair of shared multipliers $\lambda_{\text{sh}}, \mu_{\text{sh}}$ —common to *every* agent's stationarity condition, rather than duplicated per agent, as is standard when seeking a variational (normalized) equilibrium [5]—so that agent i 's Lagrangian is $L_i := f_i - \lambda_i^\top g_i - \mu_i^\top h_i - \lambda_{\text{sh}}^\top g_{\text{sh}} - \mu_{\text{sh}}^\top h_{\text{sh}}$. The concatenated system is again an instance of (3), with

$$\begin{aligned} G &:= (\nabla_{x_1} L_1, \dots, \nabla_{x_N} L_N, g_1, \dots, g_N, g_{\text{sh}}), \\ H &:= (h_1, \dots, h_N, h_{\text{sh}}), \end{aligned} \quad (5)$$

with G and H each a function of the full concatenated primal and dual variables and θ . Every agent's stationarity block $\nabla_{x_i} L_i$ depends on the shared multipliers $\lambda_{\text{sh}}, \mu_{\text{sh}}$ in addition to its own λ_i, μ_i , which is exactly what couples the agents' otherwise-separate KKT systems into one game.

III. SOLVER DESIGN

TODO

IV. BATCHED AND GPU-PARALLEL SOLVING

TODO

V. EXPERIMENTS

TODO

VI. DISCUSSION AND FUTURE WORK

TODO

REFERENCES

- [1] S. P. Dirkse and M. C. Ferris, “The path solver: a nonmonotone stabilization scheme for mixed complementarity problems,” *Optimization methods and software*, vol. 5, no. 2, pp. 123–156, 1995.
- [2] J. Li, C. Y. Chiu, L. Peters, F. Palafox, M. Karabag, J. Alonso-Mora, S. Sojoudi, C. Tomlin, and D. Fridovich-Keil, “Scenario-game admm: A parallelized scenario-based solver for stochastic noncooperative games,” in *62nd IEEE Conference on Decision and Control, CDC 2023*. IEEE, 2023, pp. 8093–8099.
- [3] L. Peters, A. Bajcsy, C.-Y. Chiu, D. Fridovich-Keil, F. Laine, L. Ferranti, and J. Alonso-Mora, “Contingency games for multi-agent interaction,” *IEEE Robotics and Automation Letters*, vol. 9, no. 3, pp. 2208–2215, 2024.
- [4] B. Amos and J. Z. Kolter, “Optnet: differentiable optimization as a layer in neural networks,” in *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, 2017, pp. 136–145.
- [5] F. Facchinei and J.-S. Pang, *Finite-dimensional variational inequalities and complementarity problems*. Springer, 2003.