


Chapter 13

Randomized Algorithms



Slides by Kevin Wayne.
Copyright © 2005 Pearson-Addison Wesley.
All rights reserved.

Randomization

Algorithmic design patterns.

- Greed.
- Divide-and-conquer.
- Dynamic programming.
- Network flow.
- **Randomization.**

Randomization. Allow fair coin flip in unit time.

Why randomize? Can lead to simplest, fastest, or only known algorithm for a particular problem.

Ex. Symmetry breaking protocols, graph algorithms, quicksort, hashing, load balancing, cryptography.


13.1 Contention Resolution

Contention Resolution in a Distributed System

Contention resolution. Given n processes P_1, \dots, P_n , each competing for access to a shared database. If two or more processes access the database simultaneously, all processes are locked out. Devise protocol to ensure all processes get through on a regular basis.

Restriction. Processes can't communicate.

Challenge. Need **symmetry-breaking** paradigm.



Contention Resolution: Randomized Protocol

Protocol. Each process requests access to the database at time t with probability $p = 1/n$.

Claim. Let $S[i, t]$ = event that process i succeeds in accessing the database at time t . Then $1/(e \cdot n) \leq \Pr[S(i, t)] \leq 1/(2n)$.

Pf. By independence, $\Pr[S(i, t)] = p (1-p)^{n-1}$.

process i requests access \nearrow \nwarrow none of remaining $n-1$ processes request access

- Setting $p = 1/n$, we have $\Pr[S(i, t)] = 1/n \underbrace{(1 - 1/n)^{n-1}}_{\text{value that maximizes } \Pr[S(i, t)] \text{ between } 1/e \text{ and } 1/2}$. ▪

Useful facts from calculus. As n increases from 2, the function:

- $(1 - 1/n)^n$ converges monotonically from $1/4$ up to $1/e$
- $(1 - 1/n)^{n-1}$ converges monotonically from $1/2$ down to $1/e$.

Contention Resolution: Randomized Protocol

Claim. The probability that process i fails to access the database in en rounds is at most $1/e$. After $e \cdot n(c \ln n)$ rounds, the probability is at most n^{-c} .

Pf. Let $F[i, t]$ = event that process i fails to access database in rounds 1 through t . By independence and previous claim, we have $\Pr[F(i, t)] \leq (1 - 1/(en))^t$.

- Choose $t = \lceil e \cdot n \rceil$: $\Pr[F(i, t)] \leq \left(1 - \frac{1}{en}\right)^{\lceil en \rceil} \leq \left(1 - \frac{1}{en}\right)^{en} \leq \frac{1}{e}$
- Choose $t = \lceil e \cdot n \rceil \lceil c \ln n \rceil$: $\Pr[F(i, t)] \leq \left(\frac{1}{e}\right)^{c \ln n} = n^{-c}$

Contention Resolution: Randomized Protocol

Claim. The probability that **all** processes succeed within $2e \cdot n \ln n$ rounds is at least $1 - 1/n$.

Pf. Let $F[t]$ = event that at least one of the n processes fails to access database in any of the rounds 1 through t .

$$\Pr[F[t]] = \Pr\left[\bigcup_{i=1}^n F[i, t]\right] \leq \sum_{i=1}^n \Pr[F[i, t]] \leq n\left(1 - \frac{1}{en}\right)^t$$

union bound previous slide

- Choosing $t = 2 \lceil en \rceil \lceil c \ln n \rceil$ yields $\Pr[F[t]] \leq n \cdot n^{-2} = 1/n$. ▪

Union bound. Given events E_1, \dots, E_n , $\Pr\left[\bigcup_{i=1}^n E_i\right] \leq \sum_{i=1}^n \Pr[E_i]$

13.3 Linearity of Expectation

Expectation

Expectation. Given a discrete random variables X , its expectation $E[X]$ is defined by:

$$E[X] = \sum_{j=0}^{\infty} j \Pr[X = j]$$

Waiting for a first success. Coin is heads with probability p and tails with probability $1-p$. How many independent flips X until first heads?

$$E[X] = \sum_{j=0}^{\infty} j \cdot \Pr[X = j] = \sum_{j=0}^{\infty} j \underset{\substack{\uparrow \\ \text{j-1 tails}}}{(1-p)^{j-1}} \underset{\substack{\uparrow \\ \text{1 head}}}{p} = \frac{p}{1-p} \sum_{j=0}^{\infty} j (1-p)^j = \frac{p}{1-p} \cdot \frac{1-p}{p^2} = \frac{1}{p}$$

Expectation: Two Properties

Useful property. If X is a 0/1 random variable, $E[X] = \Pr[X = 1]$.

Pf.
$$E[X] = \sum_{j=0}^{\infty} j \cdot \Pr[X = j] = \sum_{j=0}^1 j \cdot \Pr[X = j] = \Pr[X = 1]$$

Linearity of expectation. Given two random variables X and Y defined over the same probability space, $E[X + Y] = E[X] + E[Y]$.

Decouples a complex calculation into simpler pieces.

Guessing Cards

Game. Shuffle a deck of n cards; turn them over one at a time; try to guess each card.

Memoryless guessing. No psychic abilities; can't even remember what's been turned over already. Guess a card from full deck uniformly at random.

Claim. The expected number of correct guesses is 1.

Pf.

- Let $X_i = 1$ if i^{th} prediction is correct and 0 otherwise.
- Let $X =$ number of correct guesses $= X_1 + \dots + X_n$.
- $E[X_i] = \Pr[X_i = 1] = 1/n$.
- $E[X] = E[X_1] + \dots + E[X_n] = 1/n + \dots + 1/n = 1$. ▪

↑
linearity of expectation

Guessing Cards

Game. Shuffle a deck of n cards; turn them over one at a time; try to guess each card.

Guessing with memory. Guess a card uniformly at random from cards not yet seen.

Claim. The expected number of correct guesses is $\Theta(\log n)$.

Pf.

- Let $X_i = 1$ if i^{th} prediction is correct and 0 otherwise.
- Let $X =$ number of correct guesses $= X_1 + \dots + X_n$.
- $E[X_i] = \Pr[X_i = 1] = 1 / (n - i - 1)$.
- $E[X] = E[X_1] + \dots + E[X_n] = 1/n + \dots + 1/2 + 1/1 = \Theta(\log n)$. ▪

↑
linearity of expectation

13.4 MAX 3-SAT

Maximum 3-Satisfiability

↙ exactly 3 distinct literals per clause

MAX-3SAT. Given 3-SAT formula, find a truth assignment that satisfies as many clauses as possible.

$$\begin{aligned}C_1 &= x_2 \vee \overline{x_3} \vee \overline{x_4} \\C_2 &= x_2 \vee x_3 \vee \overline{x_4} \\C_3 &= \overline{x_1} \vee x_2 \vee x_4 \\C_4 &= \overline{x_1} \vee \overline{x_2} \vee x_3 \\C_5 &= x_1 \vee \overline{x_2} \vee \overline{x_4}\end{aligned}$$

Remark. NP-hard search problem.

Simple idea. Flip a coin, and set each variable true with probability $\frac{1}{2}$, independently for each variable.

Maximum 3-Satisfiability: Analysis

Claim. Given a 3-SAT formula with k clauses, the **expected number** of clauses satisfied by a random assignment is $7k/8$.

Pf. Consider random variable $Z_j = \begin{cases} 1 & \text{if clause } C_j \text{ is satisfied} \\ 0 & \text{otherwise.} \end{cases}$

- Let Z = number of clauses satisfied by random assignment.

$$\begin{aligned} E[Z] &= \sum_{j=1}^k E[Z_j] \\ \text{linearity of expectation} \quad &\nearrow \\ &= \sum_{j=1}^k \Pr[\text{clause } C_j \text{ is satisfied}] \\ &= \frac{7}{8}k \end{aligned}$$

The Probabilistic Method

Corollary. For any instance of 3-SAT, **there exists** a truth assignment that satisfies at least a $7/8$ fraction of all clauses.

Pf. Random variable is at least its expectation some of the time. ■

Maximum 3-Satisfiability: Analysis

Q. Can we turn this idea into a $7/8$ -approximation algorithm?

Lemma. The probability that a random assignment satisfies $\geq 7k/8$ clauses is at least $1/(8k)$.

Pf. Let p_j be probability that exactly j clauses are satisfied; let p be probability that $\geq 7k/8$ clauses are satisfied.

$$\begin{aligned}\frac{7}{8}k &= E[Z] = \sum_{j \geq 0} j p_j \\ &= \sum_{j < 7k/8} j p_j + \sum_{j \geq 7k/8} j p_j \\ &\leq \left(\frac{7k}{8} - \frac{1}{8}\right) \sum_{j < 7k/8} p_j + k \sum_{j \geq 7k/8} p_j \\ &\leq \left(\frac{7}{8}k - \frac{1}{8}\right) \cdot 1 + k p\end{aligned}$$

Rearranging terms yields $p \geq 1 / (8k)$. ■

Maximum 3-Satisfiability: Analysis

Johnson's algorithm. Repeatedly generate random truth assignments until one of them satisfies $\geq 7k/8$ clauses.

Theorem. Johnson's algorithm is a $7/8$ -approximation algorithm.

Pf. By previous lemma, each iteration succeeds with probability at least $1/(8k)$. By the waiting-time bound, the expected number of trials to find the satisfying assignment is at most $8k$. ■

Maximum Satisfiability

Extensions.

- Allow one, two, or more literals per clause.
- Find max **weighted** set of satisfied clauses.

Theorem. [Asano-Williamson 2000] There exists a 0.784-approximation algorithm for MAX-SAT.

Theorem. [Karloff-Zwick 1997, Zwick+computer 2002] There exists a $7/8$ -approximation algorithm for version of MAX-3SAT where each clause has **at most** 3 literals.

Theorem. [Håstad 1997] Unless $P = NP$, no ρ -approximation algorithm for MAX-3SAT (and hence MAX-SAT) for any $\rho > 7/8$.

↑
very unlikely to improve over simple randomized
algorithm for MAX-3SAT

13.9 Chernoff Bounds

Chernoff Bounds

Theorem. Suppose X_1, \dots, X_n are independent 0-1 random variables. Let $X = X_1 + \dots + X_n$. Then for any $\mu \geq E[X]$ and for any $\delta > 0$, we have

$$\Pr[X > (1 + \delta)\mu] < \left[\frac{e^\delta}{(1 + \delta)^{1+\delta}} \right]^\mu$$

Theorem. Suppose X_1, \dots, X_n are independent 0-1 random variables. Let $X = X_1 + \dots + X_n$. Then for any $\mu \leq E[X]$ and for any $0 < \delta < 1$, we have

$$\Pr[X < (1 - \delta)\mu] < e^{-\delta^2 \mu / 2}$$

13.10 Load Balancing

Load Balancing

Load balancing. System in which m jobs arrive in a stream and need to be processed immediately on n identical processors. Find an assignment that balances the workload across processors.

Centralized controller. Assign jobs in round-robin manner. Each processor receives at most $\lceil m/n \rceil$ jobs.

Decentralized controller. Assign jobs to processors uniformly at random. How likely is it that some processor is assigned "too many" jobs?

Load Balancing

Analysis.

- Let X_i = number of jobs assigned to processor i .
- Let $Y_{ij} = 1$ if job j assigned to processor i , and 0 otherwise.
- We have $E[Y_{ij}] = 1/n$
- Thus, $X_i = \sum_j Y_{ij}$, and $\mu = E[X_i] = 1$.
- Applying Chernoff bounds with $\delta = c - 1$ yields $\Pr[X_i > c] < \frac{e^{c-1}}{c^c}$
- Let $\gamma(n)$ be number x such that $x^x = n$, and choose $c = e^{\gamma(n)}$.

$$\Pr[X_i > c] < \frac{e^{c-1}}{c^c} < \left(\frac{e}{c}\right)^c = \left(\frac{1}{\gamma(n)}\right)^{e\gamma(n)} < \left(\frac{1}{\gamma(n)}\right)^{2\gamma(n)} = \frac{1}{n^2}$$

- Union bound \Rightarrow with probability $\geq 1 - 1/n$ no processor receives more than $e^{\gamma(n)} = \Theta(\log n / \log \log n)$ jobs.