

Import required library

```
In [1]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
import keras
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import to_categorical, pad_sequences
from keras.callbacks import EarlyStopping
%matplotlib inline
```

Read dataset and do pre-processing

```
In [2]: df = pd.read_csv('spam.csv', delimiter=',', encoding='latin-1')
df.head()
```

```
Out[2]:
```

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4
0	ham	Go until jurong point, crazy.. Available only ...	NaN	NaN	NaN
1	ham	Ok lar... Joking wif u oni...	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...	NaN	NaN	NaN
3	ham	U dun say so early hor... U c already then say...	NaN	NaN	NaN
4	ham	Nah I don't think he goes to usf, he lives aro...	NaN	NaN	NaN


```
In [3]: df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'], axis=1, inplace=True)
```

```
In [4]: df.shape
```

```
Out[4]: (5572, 2)
```

```
In [5]: #plot the ham and spam messages to understand the distribution
df['v1'].value_counts().plot(kind='bar')
plt.xlabel('Label')
plt.title('Number of ham and spam messages')
```

```
Out[5]: Text(0.5, 1.0, 'Number of ham and spam messages')
```



```
In [6]: X = df.v2
Y = df.v1
#label encoding for Y
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)
```

```
In [7]: #split into train and test sets
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.20)
```

Tokenizer

```
In [8]: max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = keras.utils.pad_sequences(sequences,maxlen=max_len)
```

Add Layers(LSTM, Dense-(Hidden Layers), Output)

```
In [9]: inputs = Input(name='inputs',shape=[max_len])
layer = Embedding(max_words,50,input_length=max_len)(inputs)
layer = LSTM(64)(layer)
layer = Dense(256,name='FC1')(layer)
layer = Activation('relu')(layer)
layer = Dropout(0.5)(layer)
layer = Dense(1,name='out_layer')(layer)
layer = Activation('sigmoid')(layer)
```

Create Model

```
In [10]: model = Model(inputs=inputs,outputs=layer)
```

Compile the Model

```
In [11]: model.summary()  
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accu
```

Model: "model"

Layer (type)	Output Shape	Param #
inputs (InputLayer)	[(None, 150)]	0
embedding (Embedding)	(None, 150, 50)	50000
lstm (LSTM)	(None, 64)	29440
FC1 (Dense)	(None, 256)	16640
activation (Activation)	(None, 256)	0
dropout (Dropout)	(None, 256)	0
out_layer (Dense)	(None, 1)	257
activation_1 (Activation)	(None, 1)	0

=====
Total params: 96,337
Trainable params: 96,337
Non-trainable params: 0
=====

Fit the Model

```
In [12]: model.fit(sequences_matrix,Y_train,batch_size=128,epochs=10,validation_split
```

```
Epoch 1/10  
28/28 [=====] - 11s 261ms/step - loss: 0.3656 - ac  
curacy: 0.8572 - val_loss: 0.1512 - val_accuracy: 0.9529  
Epoch 2/10  
28/28 [=====] - 8s 281ms/step - loss: 0.1064 - acc  
uracy: 0.9708 - val_loss: 0.0537 - val_accuracy: 0.9798  
<keras.callbacks.History at 0x7f94b6d2e150>
```

Out[12]:

Save the Model

```
In [13]: model.save('spam_lstm_model.h5')
```

Test the Model

```
In [14]: #processing test data  
test_sequences = tok.texts_to_sequences(X_test)  
test_sequences_matrix = keras.utils.pad_sequences(test_sequences,maxlen=max_
```

```
In [15]: #evaluation of our model  
accr = model.evaluate(test_sequences_matrix,Y_test)
```

```
print('Test set\n Loss: {:.3f}\n Accuracy: {:.3f}'.format(accr[0],accr[1])
35/35 [=====] - 1s 34ms/step - loss: 0.0760 - accu
racy: 0.9758
Test set
Loss: 0.076
Accuracy: 0.976
```

In []: