


# Naive Bayes Classifier



## Table Of Contents

1. Why do we need Naive Bayes
2. Concept of how it works
3. Mathematical Intuition of Naive Bayes
4. Solving an Example on Naive Bayes
5. Other Bayes Classifiers
  - Gaussian Naive Bayes Classifier
  - Multinomial Naive Bayes Classifier
  - Bernoulli Naive Bayes Classifier

## ① Naive Bayes classifier

→ If we have a dataset, where relationship with one single feature may effect the output/label, then we cannot generalize about all the features at a time!!

Eg:-

1) The food I ordered is good.

2) The food I ordered is bad.

Here only the last word signifies about the sentiment or statement.

② This is where Naive Bayes steps in.

→ Naive Bayes will not try to generalize complete features at a time and instead tries to build a independent relationship each & every input feature with output label, so that we get a better idea.

## ③ How it works?

→ Naive Bayes is not a single algorithm, but a family of algorithms where all of them share a common principle, i.e. they are based on Bayes.

→ Bayes' Theorem finds the probability of an event occurring given the probability of another event that has already occurred.  
mathematically,

$$P(A/B) = \frac{P(B/A) \cdot P(A)}{P(B)}$$

where A & B are events &  $P(B) \neq 0$

→ Basically we are trying to find the Probability of A, given the event B is true. Event B is also termed as evidence.

→  $P(A)$  is the Prior of A, that is the probability of event before evidence is seen (Prior Probability).

→  $P(A/B)$  is the posterior probability, that is the probability of event after evidence is seen.   
 (Here, event B occurrence)

eg let's take a dataset of Playing golf based on climate.

S. No	outlook	Temperature	Humidity	windy	Play Golf
0	Rainy	Hot	High	False	No
1	Rainy	Hot	High	True	No
2	overcast	Hot	High	False	Yes
3	Sunny	Mild	High	False	Yes
4	Sunny	cool	Normal	False	Yes
5	Sunny	cool	Normal	True	No
6	overcast	cool	Normal	True	Yes
7	Rainy	mild	High	False	No
8	Rainy	cool	Normal	False	Yes
9	Sunny	mild	Normal	False	Yes
10	Rainy	mild	Normal	True	Yes
11	overcast	mild	High	True	Yes
12	overcast	Hot	Normal	False	Yes
13	Sunny	mild	High	True	No



→ Here we can say that if it's sunny, mostly likely person wouldn't go for game.  
similar case if it's too windy / too rainy.

→ so we can clearly see that a single feature will effect the label directly.  
Hence, we will build model using independent relationship of each feature with output label by leveraging Naive Bayes.

→ But before we apply Naive Bayes, we should make sure it follows the assumptions.

★ ① the fundamental Naive Bayes Assumption is that each feature makes an independent, and equal contribution to the outcome.

→ And we can clearly say no pair of features are dependent, Eg - the temperature being hot has nothing to do with humidity / being rainy.  
Hence, features are independent.

→ knowing only temperature & humidity alone can't predict the outcome, hence assumed all features contribute equally to outcome.

we have, Bayes' Theorem as

$$P(y/x) = \frac{P(x|y) \cdot P(y)}{P(x)}$$

y - class variable

x - dependent feature

→ And by taking naive assumption to Bayes theorem, which is independence among the features, we get  $P(A, B) = P(A) \cdot P(B)$

$$P(y | (x_1, x_2, \dots, x_n)) = \frac{P((x_1, x_2, \dots, x_n) | y) \cdot P(y)}{P(x_1, x_2, \dots, x_n)}$$

Based on Naive assumption of independence,

$$= \frac{[P(x_1 | y) \cdot P(x_2 | y) \dots P(x_n | y)] \cdot P(y)}{P(x_1) \cdot P(x_2) \dots P(x_n)}$$

$$= \frac{P(y) \cdot \prod_{i=1}^n P(x_i | y)}{\prod_{i=1}^n P(x_i)}$$

constant for any class variable in a class.

→ Now, to make a classifier model, we find the probability of a given set of inputs for all possible values of the class variable  $y$  and pick up the output with maximum probability.

$$\therefore y = \operatorname{argmax}_y P(y) \prod_{i=1}^n P(x_i | y)$$

→ so, to solve this problem we need to calculate  $P(y)$  &  $P(x_i | y)$  → class probability, Conditional Probability.

→ so now we calculate  $P(\text{sunny} | \text{yes})$ ,  $P(\text{overcast} | \text{yes})$ ,  $P(\text{rainy} | \text{yes})$ ,  $P(\text{sunny} | \text{no})$ ,  $P(\text{overcast} | \text{no})$ ,  $P(\text{rainy} | \text{no})$ , similarly for each feature.  $P(x_i | y_j)$

~~✗~~



we get,

outlook feature

	Y	N	P(Y)	P(N)
Sunny	3	2	3/9	2/5
overcast	4	0	4/9	0/5
Rainy	2	3	2/9	3/5
Total	9	5	100%	100%

temperature feature

	Y	N	P(Y)	P(N)
Hot	2	2	2/9	2/5
mild	4	2	4/9	2/5
cold	3	1	3/9	1/5
Total	9	5	100%	100%

Humidity feature

	Y	N	P(Y)	P(N)
High	3	4	3/9	4/5
Normal	6	1	6/9	1/5
Total	9	5	100%	100%

wind feature

	Y	N	P(Y)	P(N)
False	6	2	6/9	2/5
True	3	3	3/9	3/5
Total	9	5	100%	100%

play	P(yes) / P(no)	
yes	9	9/14
No	5	5/14
Total	14	100%

→ Here we calculated  $P(n_i | y_j)$  for each  $n_i$  &  $y_j$ , And also  $P(y_j)$  for each class variable  $y_j$ .

### Prediction

→ now, if we have a new datapoint as

(Sunny, Hot, Normal, False) = today climate.

$$P(y | \text{today climate}) = P(\text{Sunny} | y) \cdot P(\text{Hot} | y) \cdot$$

$$P(\text{Normal} | y) \cdot P(\text{False} | y) \cdot P(y)$$

$$P(\text{today})$$

$$P(y | \text{today}) \propto \frac{3}{9} \cdot \frac{2}{9} \cdot \frac{6}{9} \cdot \frac{6}{9} \cdot \frac{9}{14} \approx 0.0211$$

$$P(N|today) \propto \frac{2}{5} \cdot \frac{2}{5} \cdot \frac{1}{5} \cdot \frac{2}{5} \cdot \frac{5}{11} \approx 0.1142$$

However, we know,

$$P(Y|today) + P(N|today) = 1$$

Apply reciprocal,

$$1 = \frac{1}{P(Y|today) + P(N|today)} \quad \therefore \text{multiply } P(Y|today)$$

$$P(Y|today) \geq \frac{P(Y|today)}{P(Y|today) + P(N|today)}$$

$$P(Y|today) = \frac{0.024}{0.024 + 0.1142} = \frac{0.024}{0.1382} \approx 0.155$$

$$P(N|today) = \frac{0.1142}{0.024 + 0.1142} = \frac{0.1142}{0.1382} \approx 0.844$$

So, clearly  $P(N|today) > P(Y|today)$

Hence, play golf  $\rightarrow$  No for today's climate.

$\rightarrow$  However, this above method is for the categorical data.

$\rightarrow$  And in case of continuous data we need to make assumptions regarding the distribution & values of each feature.

$\rightarrow$  The different Naive Bayes classifier differ mainly by the assumptions we make regarding the distribution of  $P(X_i|y)$



## ① Gaussian Naive Bayes classifier —

→ If the feature variables are a continuous variables, then we cannot use the Naive Bayes, and instead we should be using Gaussian Naive Bayes Classifier.

→ In Gaussian Naive Bayes, continuous values associated with each feature are assumed to be distributed according to a Gaussian distribution, also called 'Normal' distribution.

→ The likelihood of the features is assumed to be Gaussian, hence conditional probability is,

$$P(x_i | y) = \frac{1}{\sqrt{2\pi}\sigma_y} \exp\left(-\frac{(x_i - \mu_y)^2}{2\sigma_y^2}\right)$$

Other popular Naive Bayes classifiers are —

① Multinomial Naive Bayes: Feature vectors represent the frequencies with which certain events have been generated by multinomial distribution. This is typically used for document classification.

② Bernoulli Naive Bayes: Assumes that the features are binary or categorical. It is particularly useful for document classification like MNBC, and where binary term occurrence features are used rather than term frequencies.