

# Package ‘RAINLINK’

April 18, 2016

**Type** Package

**Title** Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network.

**Version** 1.1

**Date** 2016-04-13

**Author** Aart Overeem & Hidde Leijnse

**Maintainer** Aart Overeem <overeem@knmi.nl>

**Description** The RAINLINK software enables to obtain rainfall maps from microwave links in a cellular telecommunication network.

**Suggests** sp, gstat, ggplot2, ggmap, maps, mapproj, labeling, rgdal, ncdf4

**License** This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

**RoxygenNote** 5.0.1

**Installation** To install this R package run: `install.packages("RAINLINK_1.1.tar.gz", repos=NULL, type = "source")`. To install it in a specified directory, add `"", path"`, where path is the name of the folder where the package needs to be installed, e.g. `"Rlibraries"` (use quotation marks).

**Available at** <https://github.com/overeem11/RAINLINK>

**Additional information** see `"ManualRAINLINK.pdf"`

## R topics documented:

ClimVarParam . . . . .	2
CorrectMinMaxRSL . . . . .	3
IDW . . . . .	4
Interpolation . . . . .	4
IntpPathToPoint . . . . .	6
Linkdata . . . . .	7
MinMaxRSLToMeanR . . . . .	8
OrdinaryKriging . . . . .	9
OutlierFilterMinMaxRSL . . . . .	10
PlotLinkLocations . . . . .	11
Polygons . . . . .	13
PreprocessingMinMaxRSL . . . . .	14
RainMapsLinksDaily . . . . .	15

RainMapsLinksTimeStep . . . . .	20
RainMapsRadarsDaily . . . . .	25
RainMapsRadarsTimeStep . . . . .	29
RainRetrievalMinMaxRSL . . . . .	34
ReadRainLocation . . . . .	35
RefLevelMinMaxRSL . . . . .	36
ToPolygonsRain . . . . .	37
WetDryNearbyLinkApMinMaxRSL . . . . .	37

<b>Index</b>	<b>39</b>
--------------	-----------

---

ClimVarParam	<i>Subfunction for obtaining climatological values of sill, range, and nugget of spherical variogram model for RAINLINK.</i>
--------------	--

---

## Description

Subfunction for obtaining climatological values of sill, range, and nugget of spherical variogram model. This is based on a climatological variogram based on 30-year automatic rain gauge data sets from The Netherlands. Spherical variograms have been modelled as function of the day number and duration in Van de Beek et al. (2012). They use durations of 1 - 24 h. In this function the relationships can be extrapolated to, e.g. 15-min, data.

## Usage

```
ClimVarParam(DateStr, TimeScaleHours)
```

## Arguments

DateStr	The end date of the chosen daily period
TimeScaleHours	Rainfall aggregation interval in hours

## Value

Data frame with values of sill, range and nugget

## Author(s)

Aart Overeem & Hidde Leijnse

## References

”ManualRAINLINK.pdf”

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

Van de Beek, C. Z., Leijnse, H., Torfs, P. J. J. F., and Uijlenhoet, R.: Seasonal semi-variance of Dutch rainfall at hourly to daily scales, Adv. Water Resour., 45, 76-85, doi:10.1016/j.advwatres.2012.03.023, 2012.

## Examples

```
ClimVarParam(DateStr="20110911",TimeScaleHours=TimeScaleHours)
```

---

CorrectMinMaxRSL	<i>Function for correcting minimum and maximum received signal powers.</i>
------------------	--

---

## Description

Function for correcting minimum and maximum received signal powers. For a rainy time interval the corrected minimum received signal power becomes equal to the minimum received signal power if this is below the reference signal level. Otherwise the corrected minimum received signal power becomes equal to the reference signal level. The corrected maximum received signal power becomes equal to the maximum received signal power if both the maximum received signal power and the corrected minimum received signal power are below the reference signal level.

Works for a sampling strategy where minimum and maximum received signal powers are provided, and the transmitted power levels are constant.

## Usage

```
CorrectMinMaxRSL(Data, Dry = NULL, Pref)
```

## Arguments

Data	Data frame with microwave link data
Dry	Data frame: Should interval be considered dry for reference level determination? (0 = wet; 1 = dry)
Pref	Reference level (dB)

## Value

Data frame with corrected minimum and maximum received powers (dB)

## Author(s)

Aart Overeem & Hidde Leijnse

## References

"ManualRAINLINK.pdf"

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

## Examples

```
CorrectMinMaxRSL(Data=DataOutlierFiltered,Dry=WetDry$Dry,Pref=Pref)
```

---

IDW

---

*Subfunction for inverse distance weighted interpolation on point data.*


---

### Description

Subfunction for inverse distance weighted interpolation on point data.

### Usage

```
IDW(idp, rain.grid, Rainlink)
```

### Arguments

idp	The inverse distance weighting power
rain.grid	Interpolation grid in Azimuthal Equidistant Cartesian coordinate system
Rainlink	Coordinates of links in Azimuthal Equidistant Cartesian coordinate system and rainfall intensity (latitude in km, longitude in km, intensity in $\text{mm h}^{-1}$ )

### Value

Interpolated field of rainfall intensities

### Author(s)

Aart Overeem & Hidde Leijnse

### References

"ManualRAINLINK.pdf"

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

### Examples

```
IDW(idp=idp, rain.grid=rain.grid, Rainlink=Rainlink)
```

---

Interpolation

---

*Interpolation of link-based path-averaged rainfall estimates.*


---

## Description

Interpolation of link-based path-averaged rainfall estimates. The type of interpolation has to be specified. The following types are available: 1) Inverse distance weighted interpolation on data (subfunction IDW); 2) Ordinary kriging with spherical variogram model. Its parameter values nugget, sill, and range, can be defined by the user; 3) Ordinary kriging with spherical variogram model with climatological parameter values based on a 30-year rain gauge data set. These are computed for the day of year as obtained from the file name, thus taking into account seasonality in spatial rainfall correlation. The subfunction ClimVarParam computes these parameter values.

Ordinary kriging is performed by subfunction OrdinaryKriging. Note that this interpolation algorithm is developed for interpolation of link-based rainfall estimates, which are path averages. The subfunction IntpPathToPoint computes the path-averaged rainfall intensities for unique link paths. And it assigns path-averaged intensity to the point at the middle of the link path.

## Usage

```
Interpolation(Data, CoordSystemInputData = NULL, idp = 2,
  IntpMethod = "OK", nmax = 50, NUGGET, RANGE, RainGrid, Rmean, SILL,
  Variogram, OutputDir = NULL)
```

## Arguments

Data	Data frame with microwave link data Use "Manual" for spherical variogram model with nugget, sill, and range values supplied as function arguments.
CoordSystemInputData	Define coordinate system of input data (in case of WGS84 provide NULL)
idp	The inverse distance weighting power
IntpMethod	Interpolation method: Ordinary kriging ("OK") or inverse distance weighted interpolation ("IDW")
nmax	The number of nearest observations that should be used for a kriging prediction or simulation, where nearest is defined in terms of the space of the spatial locations
NUGGET	Nugget of spherical variogram model (mm)
RANGE	Range of spherical variogram model (km)
RainGrid	Data frame containing information on the points in space where rainfall needs to be estimated, is assumed to be in the same coordinate system as the original link data.
Rmean	Vector of link-derived rainfall intensities ( $\text{mm h}^{-1}$ ) with length equal to Data
SILL	Sill of spherical variogram model ( $\text{mm}^2$ )
Variogram	For OK: which variogram to use? Use "Climvdbek" for climatological spherical variogram model. Use "Manual" for spherical variogram model with NUGGET, SILL, and RANGE values supplied as function arguments.
OutputDir	If supplied (not NULL), files with resulting interpolated rainfall fields will be written to this directory. If not supplied, the interpolated fields will be returned.

## Value

Interpolated field of rainfall intensities ( $\text{mm h}^{-1}$ )

**Author(s)**

Aart Overeem & Hidde Leijnse

**References**

"ManualRAINLINK.pdf"

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review..

**Examples**

```
Interpolation(Data=DataPreprocessed,CoorSystemInputData=NULL,idp=2.0,
IntpMethod="OK",nmax=50,NUGGET=0.37,RANGE=18.7,RainGrid=RainGrid,
Rmean=Rmean,SILL=3.7,Variogram="ClimVar",OutputDir="RainMapsLinks15min")
```

---

IntpPathToPoint

*Subfunction for computing path-averaged rainfall intensities for unique link paths. A path-averaged rainfall intensity is assigned to a point at the middle of the link path.*

---

**Description**

Subfunction for computing path-averaged rainfall intensities for unique link paths. The link-based, e.g. a 15-minute path-averaged rainfall accumulation is converted to a path-averaged rainfall intensity, and subsequently assigned to a point at the middle of the link path. Path-averaged rainfall intensities are obtained, so data from full-duplex links are averaged.

**Usage**

```
IntpPathToPoint(ID, Rmean, XEnd, XStart, YEnd, YStart)
```

**Arguments**

ID	Link identifier
Rmean	Data frame with mean path-averaged rainfall intensities ( $\text{mm h}^{-1}$ )
XEnd	Easting of end of links (km)
XStart	Easting of start of links (km)
YEnd	Northing of end of links (km)
YStart	Northing of start of links (km)

**Value**

Coordinates of links in Azimuthal Equidistant Cartesian coordinate system (latitude, longitude) and rainfall intensity ( $\text{mm h}^{-1}$ )

**Author(s)**

Aart Overeem & Hidde Leijnse

## References

”ManualRAINLINK.pdf”

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

## Examples

```
IntpPathToPoint(ID,Rmean,Xend,XStart,YEnd,YStart)
```

---

Linkdata	<i>Microwave link dataset from which path-averaged rainfall intensities can be computed. Received signal powers were obtained from Nokia microwave links in one of the national cellular communication networks in The Netherlands, operated by T-Mobile NL. The minimum and maximum received powers over 15-min intervals were provided, based on 10-Hz sampling. The transmitted power was almost constant. Here the data have a resolution of 1 dB, and the majority of these Nokia links used vertically polarised signals.</i>
----------	---

---

## Description

Data were obtained from September 9, 0800 UTC - September 11, 0800 UTC (2011). The data set contains data from 2613 microwave links.

## Usage

```
data(Linkdata)
```

## Format

A data frame with link data from a commercial cellular communication network

## Details

Several functions in the RAINLINK package read a data frame with microwave link data. Such a data frame always contains the variables as indicated below, i.e. the variables in the data set supplied to PreprocessingMinMaxRSL.

For each link and time interval the following variables are provided:

- Frequency: microwave frequency  $f$  (GHz)
- DateTime: date and end time of observation (YYYYMMDDhhmm, i.e. year (2011), month (09), day (11), hour (08), minutes (00): 201109110800)
- Pmin: minimum received power  $P_{\min}$  (dBm)
- Pmax: maximum received power  $P_{\max}$  (dBm)
- PathLength: length of microwave link path (km)
- XStart: Longitude of start of links ( $^{\circ}$ ; WGS84)
- YStart: Latitude of start of links ( $^{\circ}$ ; WGS84)
- Xend: Longitude of end of links ( $^{\circ}$ ; WGS84)

- YEnd: Latitude of end of links (°; WGS84)
- ID: Link identifier

---

MinMaxRSLToMeanR	<i>Subfunction for path-averaged rainfall estimation from minimum and maximum attenuations from microwave links.</i>
------------------	--

---

### Description

Subfunction for path-averaged rainfall estimation using microwave links. Compute minimum and maximum attenuation over the link path. Convert these to minimum and maximum path-averaged rainfall intensities. Convert minimum and maximum path-averaged rainfall intensities to mean path-averaged rainfall intensities.

Works for a sampling strategy where minimum and maximum received signal powers are provided, and the transmitted power levels are constant.

### Usage

```
MinMaxRSLToMeanR(a, Aa, alpha, b, PathLength, PmaxCor, PminCor, Pref)
```

### Arguments

a	Coefficients in relationship between rainfall intensity and specific attenuation ( $\text{mm h}^{-1} \text{ dB}^{-b} \text{ km}^b$ )
Aa	Wet antenna attenuation correction $A_a$ (dB)
alpha	Coefficient ( $\alpha$ ) determining contribution of minimum and maximum path-averaged rainfall intensity to mean path-averaged rainfall intensity (-)
b	Exponents in relationship between rainfall intensity and specific attenuation (-)
PathLength	Lengths of link paths (km)

### Value

Data frame with mean path-averaged rainfall intensities ( $\text{mm h}^{-1}$ )

### Author(s)

Aart Overeem & Hidde Leijnse

### References

"ManualRAINLINK.pdf"

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

### Examples

```
MinMaxRSLToMeanR(a=a, Aa=Aa, alpha=alpha, b=b, PathLength=Data$PathLength,
PmaxCor=PmaxCor, PminCor=PminCor, Pref=Pref)
```



---

OrdinaryKriging	<i>Subfunction for ordinary kriging interpolation of point values using spherical variogram model with predefined parameters sill, range, and nugget.</i>
-----------------	---

---

## Description

Subfunction for ordinary kriging interpolation of point values using spherical variogram model with predefined parameters sill, range, and nugget.

## Usage

```
OrdinaryKriging(nmax, Nugget, rain.grid, Rainlink, Range, Sill)
```

## Arguments

nmax	The number of nearest observations that should be used for a kriging prediction or simulation, where nearest is defined in terms of the space of the spatial locations
Nugget	Nugget of spherical variogram model (mm)
rain.grid	Interpolation grid in Azimuthal Equidistant Cartesian coordinate system
Rainlink	Coordinates of links in Azimuthal Equidistant Cartesian coordinate system and rainfall intensity (latitude in km, longitude in km, intensity in mm h <sup>-1</sup> )
Range	Range of spherical variogram model (km)
Sill	Sill of spherical variogram model (mm <sup>2</sup> )

## Value

Interpolated field of rainfall intensities

## Author(s)

Aart Overeem & Hidde Leijnse

## References

”ManualRAINLINK.pdf”

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

## Examples

```
OrdinaryKriging(nmax=50,Nugget=0.37,rain.grid=rain.grid,Rainlink=Rainlink,
Range=18.7,Sill=3.7)
```

---

OutlierFilterMinMaxRSL

*Function to apply filter to remove outliers in path-averaged microwave link attenuations.*

---

## Description

Function to apply filter to remove outliers in link-based rainfall estimates. Malfunctioning link antennas can cause outliers in rainfall retrievals (especially for daily accumulations). These outliers can be removed by using a filter that is based on the assumption that rainfall is correlated in space. The filter discards a time interval of a link for which the cumulative difference between its specific attenuation and that of the surrounding links over the previous 24 h (including the present time interval) becomes lower than a threshold value in  $\text{dB h km}^{-1}$ .

The outlier filter has been tested on minimum received signal powers, i.e. for a sampling strategy where minimum and maximum received signal powers are provided, and the transmitted power levels are constant. This function can also be applied for other sampling strategies, because it does not explicitly require minimum and maximum received signal powers. It just applies the selection on all rows in a data frame. Whether the outlier filter will give good results when applied to link data obtained from other sampling strategies would need to be tested. Hence, "MinMaxRSL" is kept in this function name to stress that it has been tested for a sampling strategy where minimum and maximum received powers are provided.

Can only be applied when function WetDryNearbyLinkApMinMaxRSL has been executed.

## Usage

```
OutlierFilterMinMaxRSL(Data, F, FilterThreshold)
```

## Arguments

Data	Data frame with microwave link data
F	Values for filter to remove outliers ( $\text{dB km}^{-1} \text{ h}$ )
FilterThreshold	Outlier filter threshold ( $\text{dB h km}^{-1}$ )

## Value

Data frame with microwave link data

## Author(s)

Aart Overeem & Hidde Leijnse

## References

"ManualRAINLINK.pdf"

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

**Examples**

```
OutlierFilterMinMaxRSL(Data=DataPreprocessed,F=WetDry$F,FilterThreshold=-32.5)
```

---

PlotLinkLocations	<i>Function which visualises microwave link paths on a map.</i>
-------------------	---

---

**Description**

Function which visualises microwave link paths on a map.

**Usage**

```
PlotLinkLocations(AlphaLinkLocations, BBoxOSMAuto, OSMBottom, ColourLinks,
  ColourType, dataf, DateTime, ExtraTextLinkLocations, FigFileLinkLocations,
  FigHeight, FigWidth, FolderFigures, FontFamily, GoogleLocDegSpecified,
  GoogleLocLat, GoogleLocLon, GoogleLocName, GoogleLocNameSpecified,
  GoogleMapType, GoogleZoomlevel, LabelAxisLat, LabelAxisLonGoogle,
  LabelAxisLonOSM, OSMLLeft, MapBackground, OSMLRight, OSMScale, SizeLinks,
  SizePlotTitle, TitleLinkLocations, OSMTop)
```

**Arguments**

AlphaLinkLocations	Transparency of link paths
BBoxOSMAuto	Compute bounding box from input data or used bounding box defined above? (for OpenStreetMap only). Use "yes" if bounding box is to be computed from interpolation grid.
OSMBottom	Latitude in degrees (WGS84) for bottom side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
ColourLinks	Colour of plotted link paths
ColourType	Colour or black-and-white background map? Use "color" for colour and "bw" for black-and-white background map.
dataf	data frame which contains (at least) locations of microwave links in Azimuthal Equidistant Cartesian coordinate system
DateTime	Date and time for which link locations are plotted. This is used in the title caption of the figure and in the file name
ExtraTextLinkLocations	Second part of title of plot
FigFileLinkLocations	Part of figure output file name
FigHeight	Figure height. 1280 times 1280 pixels seems maximum graphical resolution for downloaded Google Maps. Because also axes and legend are plotted, it is advised to use e.g. 1450 times 1450 pixels. Then the Google Map will remain approximately 1280 times 1280 pixels. Using higher values is not a problem (e.g. 2000). In this way it is tried to get the highest possible resolution. For OpenStreetMap the maps may reach resolutions of 1500 - 2000 pixels. Hence, using FigWidth and FigHeight of 2000 pixels or higher is advised. The OpenStreetMap itself is stored in file "ggmapTemp.png". From this file the resolution of the background map can be obtained. This can be useful for determining an appropriate FigWidth and FigHeight above.

FigWidth	Figure width. 1280 times 1280 pixels seems maximum graphical resolution for downloaded Google Maps. Because also axes and legend are plotted, it is advised to use e.g. 1450 times 1450 pixels. Then the Google Map will remain approximately 1280 times 1280 pixels. Using higher values is not a problem (e.g. 2000). In this way it is tried to get the highest possible resolution. For OpenStreetMap the maps may reach resolutions of 1500 - 2000 pixels. Hence, using FigWidth and FigHeight of 2000 pixels or higher is advised. The OpenStreetMap itself is stored in file "ggmapTemp.png". From this file the resolution of the background map can be obtained. This can be useful for determining an appropriate FigWidth and FigHeight above.
FolderFigures	Folder name of figures
FontFamily	Specify font family of text in figures. To select the default font use "". Using "Times" may give warnings when executing the visualisation. In that case the font is not installed on the computer. This can be solved by using the default font ("").
GoogleLocDegSpecified	If GoogleLocDegSpecified is "yes" then the specified location in degrees is used as the centre of the Google Map. If both GoogleLocNameSpecified and GoogleLocDegSpecified are not equal to "yes", the bounding box of the map is determined from the provided grid and used as centre of the Google Map.
GoogleLocLat	Latitude of middle of Google Map (degrees)
GoogleLocLon	Longitude of middle of Google Map (degrees).
GoogleLocName	Location of middle of Google Map, provided as text, e.g. name of city, street name, country
GoogleLocNameSpecified	If GoogleLocNameSpecified is "yes" then the specified location name GoogleLocName is used as the centre of the Google Map. If both GoogleLocNameSpecified and GoogleLocDegSpecified are not equal to "yes", the bounding box of the map is determined from the provided grid and used as centre of the Google Map.
GoogleMapType	In case of Google Maps: which map type should be used? Available map types: "terrain", "satellite", "roadmap", and "hybrid".
GoogleZoomlevel	Which zoom level to use for the Google Maps?
LabelAxisLat	Label name of vertical axis
LabelAxisLonGoogle	Label name of horizontal axis (for Google Maps only)
LabelAxisLonOSM	Label name of horizontal axis (for OpenStreetMap only)
OSMLeft	Longitude in degrees (WGS84) for left side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
MapBackground	Google Maps or OpenStreetMap as background? Use "Google" for Google Maps and "OSM" for OpenStreetMap. Note that Google Maps will only plot on a square figure.
OSMRight	Longitude in degrees (WGS84) for right side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
OSMScale	Give value of scale (for OpenStreetMap only). A proper choice of the scale parameter in get_openstreetmap is difficult. It cannot be computed automatically.

Hence, a scale parameter value should be provided below. The scale parameter should be as small as possible to get the highest graphical resolution. However, a too low value may result in a map not being downloaded. Hence, the user should manually supply `get_openstreetmap` with a scale. It may require some iterations to find the appropriate value for scale. The file "ggmapTemp.png" is written to disk when an `OpenStreetMap` is loaded. The highest possible resolution for a square area is about 2000 x 2000 pixels.

SizeLinks	Size of plotted link paths
SizePlotTitle	Size of plot title
TitleLinkLocations	First part of title of plot
OSMTop	Latitude in degrees (WGS84) for top side of the area for which rainfall depths are to be plotted (for <code>OpenStreetMap</code> only)

### Author(s)

Aart Overeem & Hidde Leijnse

### References

"ManualRAINLINK.pdf"

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, *Atmospheric Measurement Techniques*, under review.

### Examples

```
PlotLinkLocations(AlphaLinkLocations=AlphaLinkLocations,
  BBoxOSMAuto=BBoxOSMAuto,OSMBottom=OSMBottom,
  ColourLinks=ColourLinks,ColourType=ColourType,
  dataf=dataf,DateTime=DateTime,ExtraTextLinkLocations=ExtraTextLinkLocations,
  FigFileLinkLocations=FigFileLinkLocations,FigHeight=FigHeight,
  FigWidth=FigWidth,FolderFigures=FolderFigures,FontFamily=FontFamily,
  GoogleLocDegSpecified=GoogleLocDegSpecified,GoogleLocLat=GoogleLocLat,
  GoogleLocLon=GoogleLocLon,GoogleLocName=GoogleLocName,
  GoogleLocNameSpecified=GoogleLocNameSpecified,
  GoogleMapType=GoogleMapType,GoogleZoomlevel=GoogleZoomlevel,
  LabelAxisLat=LabelAxisLat,LabelAxisLonGoogle=LabelAxisLonGoogle,
  LabelAxisLonOSM=LabelAxisLonOSM,OSMLeft=OSMLeft,
  MapBackground=MapBackground,OSMRight=OSMRight,OSMScale=OSMScale,
  SizeLinks=SizeLinks,SizePlotTitle=SizePlotTitle,
  TitleLinkLocations=TitleLinkLocations,OSMTop=OSMTop)
```

---

Polygons

*Subfunction which makes dataframe for polygons with rainfall estimates in specific rainfall class.*

---

### Description

Subfunction which makes dataframe for polygons with rainfall estimates in specific rainfall class.

**Usage**

```
Polygons(cond, Selected)
```

**Arguments**

cond	Row numbers of dataframe which fall in specific rainfall class
Selected	Coordinates of polygons and their assigned rainfall values

**Value**

Data frame

**Author(s)**

Aart Overeem & Hidde Leijnse

**References**

"ManualRAINLINK.pdf"

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

**Examples**

```
Polygons(cond=cond, Selected=Selected)
```

---

PreprocessingMinMaxRSL

*Function for preprocessing of microwave link data.*

---

**Description**

Function for preprocessing of microwave link data. This function performs the following tasks:

1. Link data are selected for microwave frequencies within chosen range.
2. Data selection criteria are applied.

Works for a sampling strategy where minimum and maximum received signal powers are provided, and the transmitted power levels are constant.

**Usage**

```
PreprocessingMinMaxRSL(Data, MaxFrequency = Inf, MinFrequency = 0,
  verbose = TRUE)
```

**Arguments**

Data	Data frame with microwave link data (use data(Linkdata) to load example data)
MaxFrequency	Maximum allowed microwave frequency of link in output (GHz; default infinite)
MinFrequency	Minimum allowed microwave frequency of link in output (GHz; default 0)

**Value**

Data frame with microwave link data

**Author(s)**

Aart Overeem & Hidde Leijnse

**References**

"ManualRAINLINK.pdf"

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

**Examples**

```
data(Linkdata)
PreprocessingMinMaxRSL(Data=Linkdata,MaxFrequency=40.5,MinFrequency=12.5)
```

---

RainMapsLinksDaily	<i>Function which visualises daily link-based rainfall depths.</i>
--------------------	--

---

**Description**

Function which visualises daily link-based rainfall depths. Requires interpolation grid and file with polygons of pixels. Daily rainfall depths are computed irrespective of the number of available files. If, for instance, only one out of 96 files is available, the daily rainfall depth is still computed and visualised. The data availability is plotted as a percentage in the title caption of the graph. Function will also plot accumulations for other aggregation intervals. Note that the data availability, plotted in the figure caption is only correctly computed for daily intervals.

**Usage**

```
RainMapsLinksDaily(AlphaLinksDaily, AlphaPlotLocation, AlphaPolygon, AlphaScale,
  AutDefineLegendTop, BBoxOSMAuto, ColourLinks, ColoursNumber,
  ColourPlotLocation, ColourPlotLocationText, ColourType, ColourHighestClass,
  ConversionDepthToIntensity, CoordSystemInputData, DateTimeEndRainMaps,
  DateTimeStartRainMaps, ExtraDeg, ExtraText, FigFileLinksDaily, FigHeight,
  FigWidth, FileGrid, FilePolygonsGrid, FolderFigures, FolderRainMaps,
  FolderRainEstimates, FontFamily, GoogleLocDegSpecified, GoogleLocLat,
  GoogleLocLon, GoogleLocName, GoogleLocNameSpecified, GoogleMapType,
  GoogleZoomlevel, LabelAxisLat, LabelAxisLonGoogle, LabelAxisLonOSM,
  LatLocation, LatText, LegendTitleLinksDaily, LonLocation, LonText,
  ManualScale, MapBackground, OSMBottom, OSMLeft, OSMRight, OSMScale, OSMTop,
  Palette, PERIOD, PlotLocation, PixelBorderCol, PlotBelowScaleBottom,
  PlotLocLinks, ScaleBottomDaily, ScaleHigh, ScaleLow, ScaleTopDaily, SizeLinks,
  SizePixelBorder, SizePlotLocation, SizePlotTitle, SymbolPlotLocation,
  TIMESTEP, TitleLinks, XMiddle, YMiddle)
```

**Arguments**

AlphaLinksDaily	Transparency of link paths
AlphaPlotLocation	Transparency of plotted symbol for specified location on map
AlphaPolygon	Transparency of polygons
AlphaScale	Transparency of legend
AutDefineLegendTop	Let R automatically define highest value of legend in case of "yes". Then the highest class, i.e. the one plotted separately above the other classes, is not plotted anymore.
BBoxOSMauto	Compute bounding box from input data or used bounding box defined above? (for OpenStreetMap only). Use "yes" if bounding box is to be computed from interpolation grid.
ColourLinks	Colour of plotted link paths
ColoursNumber	Number of colour classes in legend
ColourPlotLocation	Colour of plotted symbol for specified location on map
ColourPlotLocationText	Colour of plotted rainfall depth for specified location on map
ColourType	Colour or black-and-white background map? Use "color" for colour and "bw" for black-and-white background map.
ColourHighestClass	Colour of highest class
ConversionDepthToIntensity	Conversion factor from rainfall depth (mm) to intensity (mm/h)
CoorSystemInputData	Define coordinate system of input data (e.g. "+init=epsg:4326" for WGS84 in degrees)
DateTimeEndRainMaps	Date and time at which rainfall mapping ends
DateTimeStartRainMaps	Date and time at which rainfall mapping starts
ExtraDeg	To reduce computational time, it is automatically determined which grid cells fall within the plotted region. To also plot grid cell values which partly fall outside the plotted region, a positive number for ExtraDeg should be specified (degrees). This should typically be at least the size of one grid cell in degrees.
ExtraText	Second part of title of plot
FigFileLinksDaily	Part of figure output file name
FigHeight	Figure height. 1280 times 1280 pixels seems maximum graphical resolution for downloaded Google Maps. Because also axes and legend are plotted, it is advised to use e.g. 1450 times 1450 pixels. Then the Google Map will remain approximately 1280 times 1280 pixels. Using higher values is not a problem (e.g. 2000). In this way it is tried to get the highest possible resolution. For OpenStreetMap the maps may reach resolutions of 1500 - 2000 pixels. Hence, using FigWidth and FigHeight of 2000 pixels or higher is advised. The OpenStreetMap itself is stored in file "ggmapTemp.png". From this file the resolution



	of the background map can be obtained. This can be useful for determining an appropriate FigWidth and FigHeight above.
FigWidth	Figure width. 1280 times 1280 pixels seems maximum graphical resolution for downloaded Google Maps. Because also axes and legend are plotted, it is advised to use e.g. 1450 times 1450 pixels. Then the Google Map will remain approximately 1280 times 1280 pixels. Using higher values is not a problem (e.g. 2000). In this way it is tried to get the highest possible resolution. For OpenStreetMap the maps may reach resolutions of 1500 - 2000 pixels. Hence, using FigWidth and FigHeight of 2000 pixels or higher is advised. The OpenStreetMap itself is stored in file "ggmapTemp.png". From this file the resolution of the background map can be obtained. This can be useful for determining an appropriate FigWidth and FigHeight above.
FileGrid	File with interpolation grid in same coordinate system as CoordSystemInputData
FilePolygonsGrid	Name of file with polygons of interpolation grid
FolderFigures	Folder name of figures
FolderRainMaps	Folder name of interpolated link data (input)
FolderRainEstimates	Folder name of input link path data
FontFamily	Specify font family of text in figures. To select the default font use "". Using "Times" may give warnings when executing the visualisation. In that case the font is not installed on the computer. This can be solved by using the default font ("").
GoogleLocDegSpecified	If GoogleLocDegSpecified is "yes" then the specified location in degrees is used as the centre of the Google Map. If both GoogleLocNameSpecified and GoogleLocDegSpecified are not equal to "yes", the bounding box of the map is determined from the provided grid and used as centre of the Google Map.
GoogleLocLat	Latitude of middle of Google Map (degrees)
GoogleLocLon	Longitude of middle of Google Map (degrees).
GoogleLocName	Location of middle of Google Map, provided as text, e.g. name of city, street name, country
GoogleLocNameSpecified	If GoogleLocNameSpecified is "yes" then the specified location name GoogleLocName is used as the centre of the Google Map. If both GoogleLocNameSpecified and GoogleLocDegSpecified are not equal to "yes", the bounding box of the map is determined from the provided grid and used as centre of the Google Map.
GoogleMapType	In case of Google Maps: which map type should be used? Available map types: "terrain", "satellite", "roadmap", and "hybrid".
GoogleZoomlevel	Which zoom level to use for the Google Maps?
LabelAxisLat	Label name of vertical axis
LabelAxisLonGoogle	Label name of horizontal axis (for Google Maps only)
LabelAxisLonOSM	Label name of horizontal axis (for OpenStreetMap only)
LatLocation	Latitude of location on map (degrees)

LatText	Latitude of text (rainfall depth) of location on map (degrees)
LegendTitleLinksDaily	Title of legend
LonLocation	Longitude of location on map (degrees)
LonText	Longitude of text (rainfall depth) of location on map (degrees)
ManualScale	Manually supply the legend breaks if ManualScale is not equal to "no". Interval breaks are determined manually from ScaleLow and ScaleHigh. If ManualScale is "no" interval breaks are determined automatically.
MapBackground	Google Maps or OpenStreetMap as background? Use "Google" for Google Maps and "OSM" for OpenStreetMap. Note that Google Maps will only plot on a square figure.
OSMBottom	Latitude in degrees (WGS84) for bottom side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
OSMLeft	Longitude in degrees (WGS84) for left side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
OSMRight	Longitude in degrees (WGS84) for right side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
OSMScale	Give value of scale (for OpenStreetMap only). A proper choice of the scale parameter in get_openstreetmap is difficult. It cannot be computed automatically. Hence, a scale parameter value should be provided below. The scale parameter should be as small as possible to get the highest graphical resolution. However, a too low value may result in a map not being downloaded. Hence, the user should manually supply get_openstreetmap with a scale. It may require some iterations to find the appropriate value for scale. The file "ggmapTemp.png" is written to disk when an OpenStreetMap is loaded. The highest possible resolution for a square area is about 2000 x 2000 pixels.
OSMTop	Latitude in degrees (WGS84) for top side of the area for which rainfall depths are to be plotted (for OpenStreetMap only)
Palette	Choose (RColorBrewer) palette. "Blues", "YlGnBu", "GnBu": sequential. "Spectral", "RdYlBu", "BrBG": diverging. Unfortunately, it seems not possible to select those colours from the full range of the palette. For 6 or less classes we get a reasonable set of colours though.
PERIOD	Select daily time interval, i.e. "0800" implies 0800 UTC previous day - 0800 UTC present day (use 2400 for 0000 UTC)
PlotLocation	A location is plotted on map if PlotLocation is "yes"
PixelBorderCol	Choose colour of pixel borders. Use NA (without quotes) to not plot pixel borders. If the pixels are relatively small with respect to the plotted region, the graphical quality of the pixel borders deteriorates due to low number of pixels (low resolution).
PlotBelowScaleBottom	Plot grid lines for polygons below threshold ScaleBottomTimeStep or ScaleBottomDaily? If "yes" grid lines are plotted, otherwise they are not plotted.
PlotLocLinks	Plot locations of links in plot? If "yes" then locations of links are plotted in the plot. Note that full-duplex links are plotted twice.
ScaleBottomDaily	Lowest class starts at this threshold (minimum rainfall accumulation (mm) to be plotted). Using a value clearly above 0 mm can save a lot of computation time if the polygons belonging to values below the threshold are not plotted.

ScaleHigh	ScaleHigh Highest value per class interval, i.e. the highest legend breaks, if these are manually chosen. Please note that in case of x values in ColoursNumber, ScaleHigh should also contain x values.
ScaleLow	ScaleLow Lowest value per class interval, i.e. the lowest legend breaks, if these are manually chosen. Please note that in case of x values in ColoursNumber, ScaleLow should also contain x values.
ScaleTopDaily	Highest colour class ends here (maximum rainfall accumulation (mm) to be plotted). Sometimes the legend is not correctly plotted. In that case try other values for ScaleTopDaily and/or ScaleBottomDaily For instance, if the highest class (> x mm) is plotted below instead of above the other classes. Or if the number of classes does not match the number of chosen classes. Another way to prevent this is to manually give the legend breaks (ManualScale not equal to "no").
SizeLinks	Size of plotted link paths
SizePixelBorder	Size of pixel borders
SizePlotLocation	Size of symbol and and accompanied text for specified location on map
SizePlotTitle	Size of plot title
SymbolPlotLocation	Symbol to be plotted for specified location on map
TIMESTEP	Duration of time interval of sampling strategy (min)
TitleLinks	First part of title of plot
XMiddle	The longitude of the centre of the Azimuthal Equidistant Cartesian coordinate system, given in the coordinate system of the input data
YMiddle	The latitude of the centre of the Azimuthal Equidistant Cartesian coordinate system, given in the coordinate system of the input data

### Author(s)

Aart Overeem & Hidde Leijnse

### References

"ManualRAINLINK.pdf"

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

### Examples

```
RainMapsLinksDaily <- function(AlphaLinksDaily=AlphaLinksDaily,
AlphaPlotLocation=AlphaPlotLocation,AlphaPolygon=AlphaPolygon,
AlphaScale=AlphaScale,AutDefineLegendTop=AutDefineLegendTop,
BBoxOSMAuto=BBoxOSMAuto,ColourLinks=ColourLinks,
ColoursNumber=ColoursNumber,ColourPlotLocation=ColourPlotLocation,
ColourPlotLocationText=ColourPlotLocationText,ColourType=ColourType,
ColourHighestClass=ColourHighestClass,
ConversionDepthToIntensity=ConversionDepthToIntensity,
CoorSystemInputData=CoorSystemInputData,
DateTimeEndRainMaps=DateTimeEndRainMaps,
DateTimeStartRainMaps=DateTimeStartRainMaps,
```

```

ExtraDeg=ExtraDeg,ExtraText=ExtraText,
FigFileLinksDaily=FigFileLinksDaily,FigHeight=FigHeight,
FigWidth=FigWidth,FileGrid=FileGrid,FilePolygonsGrid=FilePolygonsGrid,
FolderFigures=FolderFigures,FolderRainMaps=FolderRainMaps,
FolderRainEstimates=FolderRainEstimates,FontFamily=FontFamily,
GoogleLocDegSpecified=GoogleLocDegSpecified,GoogleLocLat=GoogleLocLat,
GoogleLocLon=GoogleLocLon,GoogleLocName=GoogleLocName,
GoogleLocNameSpecified=GoogleLocNameSpecified,
GoogleMapType=GoogleMapType,GoogleZoomlevel=GoogleZoomlevel,
LabelAxisLat=LabelAxisLat,LabelAxisLonGoogle=LabelAxisLonGoogle,
LabelAxisLonOSM=LabelAxisLonOSM,LatLocation=LatLocation,
LatText=LatText,LegendTitleLinksDaily=LegendTitleLinksDaily,
LonLocation=LonLocation,LonText=LonText,ManualScale=ManualScale,
MapBackground=MapBackground,OSMBottom=OSMBottom,OSMLeft=OSMLeft,
OSMRight=OSMRight,OSMScale=OSMScale,OSMTop=OSMTop,Palette=Palette,
PERIOD=PERIOD,PlotLocation=PlotLocation,PixelBorderCol=PixelBorderCol,
PlotBelowScaleBottom=PlotBelowScaleBottom,PlotLocLinks=PlotLocLinks,
ScaleBottomDaily=ScaleBottomDaily,ScaleHigh=ScaleHigh,ScaleLow=ScaleLow,
ScaleTopDaily=ScaleTopDaily,SizeLinks=SizeLinks,
SizePixelBorder=SizePixelBorder,SizePlotLocation=SizePlotLocation,
SizePlotTitle=SizePlotTitle,SymbolPlotLocation=SymbolPlotLocation,
TIMESTEP=TIMESTEP,TitleLinks=TitleLinks,
XMiddle=XMiddle,YMiddle=YMiddle)

```

---

**RainMapsLinksTimeStep** *Function which visualises link-based rainfall depths for each time interval in a supplied period.*

---

## Description

Function which visualises link-based rainfall depths for each time interval in a supplied period. Requires interpolation grid and file with polygons of pixels, the polygons having four angular points. Note that the zoom level for Google Maps can be chosen. This zoom level will not always match with the area to be plotted. Downloading a GoogleMaps background map is very fast, but downloading an OpenStreetMap may require tenths of seconds. Note that such a map is downloaded only once, which saves time in case of multiple rainfall maps.

## Usage

```

RainMapsLinksTimeStep(AlphaLinksTimeStep, AlphaPlotLocation, AlphaPolygon,
AlphaScale, AutDefineLegendTop, BBoxOSMAuto, ColourLinks, ColoursNumber,
ColourPlotLocation, ColourPlotLocationText, ColourType, ColourHighestClass,
ConversionDepthToIntensity, CoorSystemInputData, DateTimeEndRainMaps,
DateTimeStartRainMaps, ExtraDeg, ExtraText, FigFileLinksTimeStep, FigHeight,
FigWidth, FileGrid, FilePolygonsGrid, FolderFigures, FolderRainMaps,
FolderRainEstimates, FontFamily, GoogleLocDegSpecified, GoogleLocLat,
GoogleLocLon, GoogleLocName, GoogleLocNameSpecified, GoogleMapType,
GoogleZoomlevel, LabelAxisLat, LabelAxisLonGoogle, LabelAxisLonOSM,
LatLocation, LatText, LegendTitleLinksTimeStep, LonLocation, LonText,
ManualScale, MapBackground, OSMBottom, OSMLeft, OSMRight, OSMScale, OSMTop,
Palette, PlotLocation, PixelBorderCol, PlotBelowScaleBottom, PlotLocLinks,
ScaleBottomTimeStep, ScaleHigh, ScaleLow, ScaleTopTimeStep, SizeLinks,
SizePixelBorder, SizePlotLocation, SizePlotTitle, SymbolPlotLocation,
TitleLinks, XMiddle, YMiddle)

```

**Arguments**

AlphaLinksTimeStep	Transparency of link paths
AlphaPlotLocation	Transparency of plotted symbol for specified location on map
AlphaPolygon	Transparency of polygons
AlphaScale	Transparency of legend
AutDefineLegendTop	Let R automatically define highest value of legend in case of "yes". Then the highest class, i.e. the one plotted separately above the other classes, is not plotted anymore.
BBoxOSMauto	Compute bounding box from input data or used bounding box defined above? (for OpenStreetMap only). Use "yes" if bounding box is to be computed from interpolation grid.
ColourLinks	Colour of plotted link paths
ColoursNumber	Number of colour classes in legend
ColourPlotLocation	Colour of plotted symbol for specified location on map
ColourPlotLocationText	Colour of plotted rainfall depth for specified location on map
ColourType	Colour or black-and-white background map? Use "color" for colour and "bw" for black-and-white background map.
ColourHighestClass	Colour of highest class
ConversionDepthToIntensity	Conversion factor from rainfall depth (mm) to intensity (mm/h)
CoorSystemInputData	Define coordinate system of input data (e.g. "+init=epsg:4326" for WGS84 in degrees)
DateTimeEndRainMaps	Date and time at which rainfall mapping ends
DateTimeStartRainMaps	Date and time at which rainfall mapping starts
ExtraDeg	To reduce computational time, it is automatically determined which grid cells fall within the plotted region. To also plot grid cell values which partly fall outside the plotted region, a positive number for ExtraDeg should be specified (degrees). This should typically be at least the size of one grid cell in degrees.
ExtraText	Second part of title of plot
FigFileLinksTimeStep	Part of figure output file name
FigHeight	Figure height. 1280 times 1280 pixels seems maximum graphical resolution for downloaded Google Maps. Because also axes and legend are plotted, it is advised to use e.g. 1450 times 1450 pixels. Then the Google Map will remain approximately 1280 times 1280 pixels. Using higher values is not a problem (e.g. 2000). In this way it is tried to get the highest possible resolution. For OpenStreetMap the maps may reach resolutions of 1500 - 2000 pixels. Hence, using FigWidth and FigHeight of 2000 pixels or higher is advised. The OpenStreetMap itself is stored in file "ggmapTemp.png". From this file the resolution

	of the background map can be obtained. This can be useful for determining an appropriate FigWidth and FigHeight above.
FigWidth	Figure width. 1280 times 1280 pixels seems maximum graphical resolution for downloaded Google Maps. Because also axes and legend are plotted, it is advised to use e.g. 1450 times 1450 pixels. Then the Google Map will remain approximately 1280 times 1280 pixels. Using higher values is not a problem (e.g. 2000). In this way it is tried to get the highest possible resolution. For OpenStreetMap the maps may reach resolutions of 1500 - 2000 pixels. Hence, using FigWidth and FigHeight of 2000 pixels or higher is advised. The OpenStreetMap itself is stored in file "ggmapTemp.png". From this file the resolution of the background map can be obtained. This can be useful for determining an appropriate FigWidth and FigHeight above.
FileGrid	File with interpolation grid in same coordinate system as CoordSystemInputData
FilePolygonsGrid	Name of file with polygons of interpolation grid
FolderFigures	Folder name of figures
FolderRainMaps	Folder name of interpolated link data (input)
FolderRainEstimates	Folder name of input link path data
FontFamily	Specify font family of text in figures. To select the default font use "". Using "Times" may give warnings when executing the visualisation. In that case the font is not installed on the computer. This can be solved by using the default font ("").
GoogleLocDegSpecified	If GoogleLocDegSpecified is "yes" then the specified location in degrees is used as the centre of the Google Map. If both GoogleLocNameSpecified and GoogleLocDegSpecified are not equal to "yes", the bounding box of the map is determined from the provided grid and used as centre of the Google Map.
GoogleLocLat	Latitude of middle of Google Map (degrees)
GoogleLocLon	Longitude of middle of Google Map (degrees).
GoogleLocName	Location of middle of Google Map, provided as text, e.g. name of city, street name, country
GoogleLocNameSpecified	If GoogleLocNameSpecified is "yes" then the specified location name GoogleLocName is used as the centre of the Google Map. If both GoogleLocNameSpecified and GoogleLocDegSpecified are not equal to "yes", the bounding box of the map is determined from the provided grid and used as centre of the Google Map.
GoogleMapType	In case of Google Maps: which map type should be used? Available map types: "terrain", "satellite", "roadmap", and "hybrid".
GoogleZoomlevel	Which zoom level to use for the Google Maps?
LabelAxisLat	Label name of vertical axis
LabelAxisLonGoogle	Label name of horizontal axis (for Google Maps only)
LabelAxisLonOSM	Label name of horizontal axis (for OpenStreetMap only)
LatLocation	Latitude of location on map (degrees)

LatText	Latitude of text (rainfall depth) of location on map (degrees)
LegendTitleLinksTimeStep	Title of legend
LonLocation	Longitude of location on map (degrees)
LonText	Longitude of text (rainfall depth) of location on map (degrees)
ManualScale	Manually supply the legend breaks if ManualScale is not equal to "no". Interval breaks are determined manually from ScaleLow and ScaleHigh. If ManualScale is "no" interval breaks are determined automatically.
MapBackground	Google Maps or OpenStreetMap as background? Use "Google" for Google Maps and "OSM" for OpenStreetMap. Note that Google Maps will only plot on a square figure.
OSMBottom	Latitude in degrees (WGS84) for bottom side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
OSMLeft	Longitude in degrees (WGS84) for left side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
OSMRight	Longitude in degrees (WGS84) for right side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
OSMScale	Give value of scale (for OpenStreetMap only). A proper choice of the scale parameter in get_openstreetmap is difficult. It cannot be computed automatically. Hence, a scale parameter value should be provided below. The scale parameter should be as small as possible to get the highest graphical resolution. However, a too low value may result in a map not being downloaded. Hence, the user should manually supply get_openstreetmap with a scale. It may require some iterations to find the appropriate value for scale. The file "ggmapTemp.png" is written to disk when an OpenStreetMap is loaded. The highest possible resolution for a square area is about 2000 x 2000 pixels.
OSMTop	Latitude in degrees (WGS84) for top side of the area for which rainfall depths are to be plotted (for OpenStreetMap only)
Palette	Choose (RColorBrewer) palette. "Blues", "YlGnBu", "GnBu": sequential. "Spectral", "RdYlBu", "BrBG": diverging. Unfortunately, it seems not possible to select those colours from the full range of the palette. For 6 or less classes we get a reasonable set of colours though.
PlotLocation	A location is plotted on map if PlotLocation is "yes"
PixelBorderCol	Choose colour of pixel borders. Use NA (without quotes) to not plot pixel borders. If the pixels are relatively small with respect to the plotted region, the graphical quality of the pixel borders deteriorates due to low number of pixels (low resolution).
PlotBelowScaleBottom	Plot grid lines for polygons below threshold ScaleBottomTimeStep or ScaleBottomDaily? If "yes" grid lines are plotted, otherwise they are not plotted.
PlotLocLinks	Plot locations of links in plot? If "yes" then locations of links are plotted in the plot. Note that full-duplex links are plotted twice.
ScaleBottomTimeStep	ScaleBottomDaily Lowest class starts at this threshold (minimum rainfall accumulation (mm) to be plotted). Using a value clearly above 0 mm can save a lot of computation time if the polygons belonging to values below the threshold are not plotted.

ScaleHigh	ScaleHigh Highest value per class interval, i.e. the highest legend breaks, if these are manually chosen. Please note that in case of x values in ColoursNumber, ScaleHigh should also contain x values.
ScaleLow	ScaleLow Lowest value per class interval, i.e. the lowest legend breaks, if these are manually chosen. Please note that in case of x values in ColoursNumber, ScaleLow should also contain x values.
ScaleTopTimeStep	Highest colour class ends here (maximum rainfall accumulation (mm) to be plotted). Sometimes the legend is not correctly plotted. In that case try other values for ScaleTopTimeStep and/or ScaleBottomTimeStep For instance, if the highest class (> x mm) is plotted below instead of above the other classes. Or if the number of classes does not match the number of chosen classes. Another way to prevent this is to manually give the legend breaks (ManualScale not equal to "no").
SizeLinks	Size of plotted link paths
SizePixelBorder	Size of pixel borders
SizePlotLocation	Size of symbol and and accompanied text for specified location on map
SizePlotTitle	Size of plot title
SymbolPlotLocation	Symbol to be plotted for specified location on map
TitleLinks	First part of title of plot
XMiddle	The longitude of the centre of the Azimuthal Equidistant Cartesian coordinate system, given in the coordinate system of the input data
YMiddle	The latitude of the centre of the Azimuthal Equidistant Cartesian coordinate system, given in the coordinate system of the input data

### Author(s)

Aart Overeem & Hidde Leijnse

### References

"ManualRAINLINK.pdf"

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

### Examples

```
RainMapsRadarsTimeStep(AlphaLinksTimeStep=AlphaLinksTimeStep,
AlphaPlotLocation=AlphaPlotLocation,AlphaPolygon=AlphaPolygon,
AlphaScale=AlphaScale,AutDefineLegendTop=AutDefineLegendTop,
BBoxOSMAuto=BBoxOSMAuto,ColourLinks=ColourLinks,
ColoursNumber=ColoursNumber,ColourPlotLocation=ColourPlotLocation,
ColourPlotLocationText=ColourPlotLocationText,
ColourType=ColourType,ColourHighestClass=ColourHighestClass,
ConversionDepthToIntensity=ConversionDepthToIntensity,
CoorSystemInputData=CoorSystemInputData,
DateTimeEndRainMaps=DateTimeEndRainMaps,
```



```

DateTimeStartRainMaps=DateTimeStartRainMaps,ExtraDeg=ExtraDeg,
ExtraText=ExtraText,FigFileLinksTimeStep=FigFileLinksTimeStep,
FigHeight=FigHeight,FigWidth=FigWidth,FileGrid=FileGrid,
FilePolygonsGrid=FilePolygonsGrid,FolderFigures=FolderFigures,
FolderRainMaps=FolderRainMaps,FolderRainEstimates=FolderRainEstimates,
FontFamily=FontFamily,GoogleLocDegSpecified=GoogleLocDegSpecified,
GoogleLocLat=GoogleLocLat,GoogleLocLon=GoogleLocLon,
GoogleLocName=GoogleLocName, GoogleLocNameSpecified=GoogleLocNameSpecified,
GoogleMapType=GoogleMapType,GoogleZoomlevel=GoogleZoomlevel,
LabelAxisLat=LabelAxisLat,LabelAxisLonGoogle=LabelAxisLonGoogle,
LabelAxisLonOSM=LabelAxisLonOSM,LatLocation=LatLocation,LatText=LatText,
LegendTitleLinksTimeStep=LegendTitleLinksTimeStep,LonLocation=LonLocation,
LonText=LonText,ManualScale=ManualScale,MapBackground=MapBackground,
OSMBottom=OSMBottom,OSMLeft=OSMLeft,OSMRight=OSMRight,OSMScale=OSMScale,
OSMTop=OSMTop,Palette=Palette,PlotLocation=PlotLocation,
PixelBorderCol=PixelBorderCol,PlotBelowScaleBottom=PlotBelowScaleBottom,
PlotLocLinks=PlotLocLinks,ScaleBottomTimeStep=ScaleBottomTimeStep,
ScaleHigh=ScaleHigh,ScaleLow=ScaleLow,ScaleTopTimeStep=ScaleTopTimeStep,
SizeLinks=SizeLinks,SizePixelBorder=SizePixelBorder,
SizePlotLocation=SizePlotLocation,
SizePlotTitle=SizePlotTitle,SymbolPlotLocation=SymbolPlotLocation,
TitleLinks=TitleLinks,XMiddle=XMiddle,YMiddle=YMiddle)

```

---

RainMapsRadarsDaily      *Function which visualises daily radar rainfall depths.*

---

## Description

Function which visualises daily radar rainfall depths. Requires interpolation grid and file with polygons of pixels. The radar data have been obtained from <http://climate4impact.eu> (catalog “Radar precipitation climatology”) and are freely available.

## Usage

```

RainMapsRadarsDaily(AlphaPlotLocation, AlphaPolygon, AlphaScale,
  AutDefineLegendTop, BBoxOSMauto, ColoursNumber, ColourPlotLocation,
  ColourPlotLocationText, ColourType, ColourHighestClass, CoorSystemInputData,
  DateMap, ExtraDeg, ExtraText, FigFileRadarsDaily, FigHeight, FigWidth,
  FileGrid, FileNameRadarDaily, FilePolygonsGrid, FolderFigures,
  FolderRadarRainMapsDaily, FontFamily, GoogleLocDegSpecified, GoogleLocLat,
  GoogleLocLon, GoogleLocName, GoogleLocNameSpecified, GoogleMapType,
  GoogleZoomlevel, LabelAxisLat, LabelAxisLonGoogle, LabelAxisLonOSM,
  LatLocation, LatText, LegendTitleRadarsDaily, LonLocation, LonText,
  ManualScale, MapBackground, OSMBottom, OSMLeft, OSMRight, OSMScale, OSMTop,
  Palette, PathRadarRainfallDepth, PERIOD, PlotLocation, PixelBorderCol,
  PlotBelowScaleBottom, ScaleBottomDaily, ScaleHigh, ScaleLow, ScaleTopDaily,
  SizePixelBorder, SizePlotLocation, SizePlotTitle, SymbolPlotLocation,
  TIMESTEP, TitleRadars, XMiddle, YMiddle)

```

## Arguments

AlphaPlotLocation

Transparency of plotted symbol for specified location on map

AlphaPolygon	Transparency of polygons
AlphaScale	Transparency of legend
AutDefineLegendTop	Let R automatically define highest value of legend in case of "yes". Then the highest class, i.e. the one plotted separately above the other classes, is not plotted anymore.
BBoxOSMauto	Compute bounding box from input data or used bounding box defined above? (for OpenStreetMap only). Use "yes" if bounding box is to be computed from interpolation grid.
ColoursNumber	Number of colour classes in legend
ColourPlotLocation	Colour of plotted symbol for specified location on map
ColourPlotLocationText	Colour of plotted rainfall depth for specified location on map
ColourType	Colour or black-and-white background map? Use "color" for colour and "bw" for black-and-white background map.
ColourHighestClass	Colour of highest class
CoorSystemInputData	Define coordinate system of input data (e.g. "+init=epsg:4326" for WGS84 in degrees)
DateMap	End date of daily period for which rainfall map should be plotted
ExtraDeg	To reduce computational time, it is automatically determined which grid cells fall within the plotted region. To also plot grid cell values which partly fall outside the plotted region, a positive number for ExtraDeg should be specified (degrees). This should typically be at least the size of one grid cell in degrees.
ExtraText	Second part of title of plot
FigFileRadarsDaily	Part of figure output file name
FigHeight	Figure height. 1280 times 1280 pixels seems maximum graphical resolution for downloaded Google Maps. Because also axes and legend are plotted, it is advised to use e.g. 1450 times 1450 pixels. Then the Google Map will remain approximately 1280 times 1280 pixels. Using higher values is not a problem (e.g. 2000). In this way it is tried to get the highest possible resolution. For OpenStreetMap the maps may reach resolutions of 1500 - 2000 pixels. Hence, using FigWidth and FigHeight of 2000 pixels or higher is advised. The OpenStreetMap itself is stored in file "ggmapTemp.png". From this file the resolution of the background map can be obtained. This can be useful for determining an appropriate FigWidth and FigHeight above.
FigWidth	Figure width. 1280 times 1280 pixels seems maximum graphical resolution for downloaded Google Maps. Because also axes and legend are plotted, it is advised to use e.g. 1450 times 1450 pixels. Then the Google Map will remain approximately 1280 times 1280 pixels. Using higher values is not a problem (e.g. 2000). In this way it is tried to get the highest possible resolution. For OpenStreetMap the maps may reach resolutions of 1500 - 2000 pixels. Hence, using FigWidth and FigHeight of 2000 pixels or higher is advised. The OpenStreetMap itself is stored in file "ggmapTemp.png". From this file the resolution of the background map can be obtained. This can be useful for determining an appropriate FigWidth and FigHeight above.

FileGrid	File with interpolation grid in same coordinate system as CoorSystemInputData
FileNameRadarDaily	Filename of radar file of rainfall depths to be visualised (NetCDF4 format).
FilePolygonsGrid	Name of file with polygons of interpolation grid
FolderFigures	Folder name of figures
FolderRadarRainMapsDaily	Name of folder which contains daily radar rainfall files (input data)
FontFamily	Specify font family of text in figures. To select the default font use "". Using "Times" may give warnings when executing the visualisation. In that case the font is not installed on the computer. This can be solved by using the default font ("").
GoogleLocDegSpecified	If GoogleLocDegSpecified is "yes" then the specified location in degrees is used as the centre of the Google Map. If both GoogleLocNameSpecified and GoogleLocDegSpecified are not equal to "yes", the bounding box of the map is determined from the provided grid and used as centre of the Google Map.
GoogleLocLat	Latitude of middle of Google Map (degrees)
GoogleLocLon	Longitude of middle of Google Map (degrees).
GoogleLocName	Location of middle of Google Map, provided as text, e.g. name of city, street name, country
GoogleLocNameSpecified	If GoogleLocNameSpecified is "yes" then the specified location name GoogleLocName is used as the centre of the Google Map. If both GoogleLocNameSpecified and GoogleLocDegSpecified are not equal to "yes", the bounding box of the map is determined from the provided grid and used as centre of the Google Map.
GoogleMapType	In case of Google Maps: which map type should be used? Available map types: "terrain", "satellite", "roadmap", and "hybrid".
GoogleZoomlevel	Which zoom level to use for the Google Maps?
LabelAxisLat	Label name of vertical axis
LabelAxisLonGoogle	Label name of horizontal axis (for Google Maps only)
LabelAxisLonOSM	Label name of horizontal axis (for OpenStreetMap only)
LatLocation	Latitude of location on map (degrees)
LatText	Latitude of text (rainfall depth) of location on map (degrees)
LegendTitleRadarsDaily	Title of legend
LonLocation	Longitude of location on map (degrees)
LonText	Longitude of text (rainfall depth) of location on map (degrees)
ManualScale	Manually supply the legend breaks if ManualScale is not equal to "no". Interval breaks are determined manually from ScaleLow and ScaleHigh. If ManualScale is "no" interval breaks are determined automatically.
MapBackground	Google Maps or OpenStreetMap as background? Use "Google" for Google Maps and "OSM" for OpenStreetMap. Note that Google Maps will only plot on a square figure.

OSMBottom	Latitude in degrees (WGS84) for bottom side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
OSMLeft	Longitude in degrees (WGS84) for left side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
OSMRight	Longitude in degrees (WGS84) for right side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
OSMScale	Give value of scale (for OpenStreetMap only). A proper choice of the scale parameter in <code>get_openstreetmap</code> is difficult. It cannot be computed automatically. Hence, a scale parameter value should be provided below. The scale parameter should be as small as possible to get the highest graphical resolution. However, a too low value may result in a map not being downloaded. Hence, the user should manually supply <code>get_openstreetmap</code> with a scale. It may require some iterations to find the appropriate value for scale. The file "ggmapTemp.png" is written to disk when an OpenStreetMap is loaded. The highest possible resolution for a square area is about 2000 x 2000 pixels.
OSMTop	Latitude in degrees (WGS84) for top side of the area for which rainfall depths are to be plotted (for OpenStreetMap only)
Palette	Choose (RColorBrewer) palette. "Blues", "YlGnBu", "GnBu": sequential. "Spectral", "RdYlBu", "BrBG": diverging. Unfortunately, it seems not possible to select those colours from the full range of the palette. For 6 or less classes we get a reasonable set of colours though.
PathRadarRainfallDepth	Path in NetCDF4 file with radar data
PERIOD	Select daily time interval, i.e. "0800" implies 0800 UTC previous day - 0800 UTC present day (use 2400 for 0000 UTC)
PlotLocation	A location is plotted on map if PlotLocation is "yes"
PixelBorderCol	Choose colour of pixel borders. Use NA (without quotes) to not plot pixel borders. If the pixels are relatively small with respect to the plotted region, the graphical quality of the pixel borders deteriorates due to low number of pixels (low resolution).
PlotBelowScaleBottom	Plot grid lines for polygons below threshold ScaleBottomTimeStep or ScaleBottomDaily? If "yes" grid lines are plotted, otherwise they are not plotted.
ScaleBottomDaily	ScaleBottomDaily Lowest class starts at this threshold (minimum rainfall accumulation (mm) to be plotted). Using a value clearly above 0 mm can save a lot of computation time if the polygons belonging to values below the threshold are not plotted.
ScaleHigh	ScaleHigh Highest value per class interval, i.e. the highest legend breaks, if these are manually chosen. Please note that in case of x values in ColoursNumber, ScaleHigh should also contain x values.
ScaleLow	ScaleLow Lowest value per class interval, i.e. the lowest legend breaks, if these are manually chosen. Please note that in case of x values in ColoursNumber, ScaleLow should also contain x values.
ScaleTopDaily	Highest colour class ends here (maximum rainfall accumulation (mm) to be plotted). Sometimes the legend is not correctly plotted. In that case try other values for ScaleTopDaily and/or ScaleBottomDaily For instance, if the highest class (> x mm) is plotted below instead of above the other classes. Or if the number of classes does not match the number of chosen classes. Another way to prevent this is to manually give the legend breaks (ManualScale not equal to "no").

SizePixelBorder	Size of pixel borders
SizePlotLocation	Size of symbol and accompanied text for specified location on map
SizePlotTitle	Size of plot title
SymbolPlotLocation	Symbol to be plotted for specified location on map
TitleRadars	First part of title of plot
XMiddle	The longitude of the centre of the Azimuthal Equidistant Cartesian coordinate system, given in the coordinate system of the input data
YMiddle	The latitude of the centre of the Azimuthal Equidistant Cartesian coordinate system, given in the coordinate system of the input data

**Author(s)**

Aart Overeem & Hidde Leijnse

**References**

”ManualRAINLINK.pdf”

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

**Examples**

```
RainMapsRadarsDaily(20110911) # To plot daily radar rainfall map ending at 11 September 2011.
```

---

RainMapsRadarsTimeStep

*Function which visualises radar rainfall depths for chosen TIMESTEP in configuration file.*

---

**Description**

Function which visualises radar rainfall depths for chosen TIMESTEP. Requires interpolation grid and file with polygons of pixels.

**Usage**

```
RainMapsRadarsTimeStep(AlphaPlotLocation, AlphaPolygon, AlphaScale,
  AutDefineLegendTop, BBoxOSMAuto, ColoursNumber, ColourPlotLocation,
  ColourPlotLocationText, ColourType, ColourHighestClass, CoordSystemInputData,
  ExtraDeg, ExtraText, FigFileRadarsTimeStep, FigHeight, FigWidth, FileGrid,
  FilePolygonsGrid, FolderFigures, FolderRadarRainMapsTimeStep, FontFamily,
  GoogleLocDegSpecified, GoogleLocLat, GoogleLocLon, GoogleLocName,
  GoogleLocNameSpecified, GoogleMapType, GoogleZoomlevel, LabelAxisLat,
  LabelAxisLonGoogle, LabelAxisLonOSM, LatLocation, LatText,
  LegendTitleRadarsTimeStep, LonLocation, LonText, ManualScale, MapBackground,
  OSMBottom, OSMLeft, OSMRight, OSMscale, OSMTop, Palette,
```

PathRadarRainfallDepth, PERIOD, PlotLocation, PixelBorderCol,  
 PlotBelowScaleBottom, ScaleBottomTimeStep, ScaleHigh, ScaleLow,  
 ScaleTopTimeStep, SizePixelBorder, SizePlotLocation, SizePlotTitle,  
 SymbolPlotLocation, TIMESTEP, TimeZone, TitleRadars, XMiddle, YMiddle)

## Arguments

AlphaPlotLocation	Transparency of plotted symbol for specified location on map
AlphaPolygon	Transparency of polygons
AlphaScale	Transparency of legend
AutDefineLegendTop	Let R automatically define highest value of legend in case of "yes". Then the highest class, i.e. the one plotted separately above the other classes, is not plotted anymore.
BBoxOSMauto	Compute bounding box from input data or used bounding box defined above? (for OpenStreetMap only). Use "yes" if bounding box is to be computed from interpolation grid.
ColoursNumber	Number of colour classes in legend
ColourPlotLocation	Colour of plotted symbol for specified location on map
ColourPlotLocationText	Colour of plotted rainfall depth for specified location on map
ColourType	Colour or black-and-white background map? Use "color" for colour and "bw" for black-and-white background map.
ColourHighestClass	Colour of highest class
CoorSystemInputData	Define coordinate system of input data (e.g. "+init=epsg:4326" for WGS84 in degrees)
ExtraDeg	To reduce computational time, it is automatically determined which grid cells fall within the plotted region. To also plot grid cell values which partly fall outside the plotted region, a positive number for ExtraDeg should be specified (degrees). This should typically be at least the size of one grid cell in degrees.
ExtraText	Second part of title of plot
FigFileRadarsTimeStep	Part of figure output file name
FigHeight	Figure height. 1280 times 1280 pixels seems maximum graphical resolution for downloaded Google Maps. Because also axes and legend are plotted, it is advised to use e.g. 1450 times 1450 pixels. Then the Google Map will remain approximately 1280 times 1280 pixels. Using higher values is not a problem (e.g. 2000). In this way it is tried to get the highest possible resolution. For OpenStreetMap the maps may reach resolutions of 1500 - 2000 pixels. Hence, using FigWidth and FigHeight of 2000 pixels or higher is advised. The OpenStreetMap itself is stored in file "ggmapTemp.png". From this file the resolution of the background map can be obtained. This can be useful for determining an appropriate FigWidth and FigHeight above.

FigWidth	Figure width. 1280 times 1280 pixels seems maximum graphical resolution for downloaded Google Maps. Because also axes and legend are plotted, it is advised to use e.g. 1450 times 1450 pixels. Then the Google Map will remain approximately 1280 times 1280 pixels. Using higher values is not a problem (e.g. 2000). In this way it is tried to get the highest possible resolution. For OpenStreetMap the maps may reach resolutions of 1500 - 2000 pixels. Hence, using FigWidth and FigHeight of 2000 pixels or higher is advised. The OpenStreetMap itself is stored in file "ggmapTemp.png". From this file the resolution of the background map can be obtained. This can be useful for determining an appropriate FigWidth and FigHeight above.
FileGrid	File with interpolation grid in same coordinate system as CoordSystemInputData
FilePolygonsGrid	Name of file with polygons of interpolation grid
FolderFigures	Folder name of figures
FolderRadarRainMapsTimeStep	Name of folder which contains 5-min radar rainfall files (input data)
FontFamily	Specify font family of text in figures. To select the default font use "". Using "Times" may give warnings when executing the visualisation. In that case the font is not installed on the computer. This can be solved by using the default font ("").
GoogleLocDegSpecified	If GoogleLocDegSpecified is "yes" then the specified location in degrees is used as the centre of the Google Map. If both GoogleLocNameSpecified and GoogleLocDegSpecified are not equal to "yes", the bounding box of the map is determined from the provided grid and used as centre of the Google Map.
GoogleLocLat	Latitude of middle of Google Map (degrees)
GoogleLocLon	Longitude of middle of Google Map (degrees).
GoogleLocName	Location of middle of Google Map, provided as text, e.g. name of city, street name, country
GoogleLocNameSpecified	If GoogleLocNameSpecified is "yes" then the specified location name GoogleLocName is used as the centre of the Google Map. If both GoogleLocNameSpecified and GoogleLocDegSpecified are not equal to "yes", the bounding box of the map is determined from the provided grid and used as centre of the Google Map.
GoogleMapType	In case of Google Maps: which map type should be used? Available map types: "terrain", "satellite", "roadmap", and "hybrid".
GoogleZoomlevel	Which zoom level to use for the Google Maps?
LabelAxisLat	Label name of vertical axis
LabelAxisLonGoogle	Label name of horizontal axis (for Google Maps only)
LabelAxisLonOSM	Label name of horizontal axis (for OpenStreetMap only)
LatLocation	Latitude of location on map (degrees)
LatText	Latitude of text (rainfall depth) of location on map (degrees)
LegendTitleRadarsTimeStep	Title of legend

LonLocation	Longitude of location on map (degrees)
LonText	Longitude of text (rainfall depth) of location on map (degrees)
ManualScale	Manually supply the legend breaks if ManualScale is not equal to "no". Interval breaks are determined manually from ScaleLow and ScaleHigh. If ManualScale is "no" interval breaks are determined automatically.
MapBackground	Google Maps or OpenStreetMap as background? Use "Google" for Google Maps and "OSM" for OpenStreetMap. Note that Google Maps will only plot on a square figure.
OSMBottom	Latitude in degrees (WGS84) for bottom side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
OSMLeft	Longitude in degrees (WGS84) for left side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
OSMRight	Longitude in degrees (WGS84) for right side of the area for which rainfall depths are to be plotted (for OpenStreetMap only).
OSMScale	Give value of scale (for OpenStreetMap only). A proper choice of the scale parameter in get_openstreetmap is difficult. It cannot be computed automatically. Hence, a scale parameter value should be provided below. The scale parameter should be as small as possible to get the highest graphical resolution. However, a too low value may result in a map not being downloaded. Hence, the user should manually supply get_openstreetmap with a scale. It may require some iterations to find the appropriate value for scale. The file "ggmapTemp.png" is written to disk when an OpenStreetMap is loaded. The highest possible resolution for a square area is about 2000 x 2000 pixels.
OSMTop	Latitude in degrees (WGS84) for top side of the area for which rainfall depths are to be plotted (for OpenStreetMap only)
Palette	Choose (RColorBrewer) palette. "Blues", "YlGnBu", "GnBu": sequential. "Spectral", "RdYlBu", "BrBG": diverging. Unfortunately, it seems not possible to select those colours from the full range of the palette. For 6 or less classes we get a reasonable set of colours though.
PathRadarRainfallDepth	Path in NetCDF4 file with radar data
PERIOD	Select daily time interval, i.e. "0800" implies 0800 UTC previous day - 0800 UTC present day (use 2400 for 0000 UTC)
PlotLocation	A location is plotted on map if PlotLocation is "yes"
PixelBorderCol	Choose colour of pixel borders. Use NA (without quotes) to not plot pixel borders. If the pixels are relatively small with respect to the plotted region, the graphical quality of the pixel borders deteriorates due to low number of pixels (low resolution).
PlotBelowScaleBottom	Plot grid lines for polygons below threshold ScaleBottomTimeStep or ScaleBottomDaily? If "yes" grid lines are plotted, otherwise they are not plotted.
ScaleBottomTimeStep	ScaleBottomDaily Lowest class starts at this threshold (minimum rainfall accumulation (mm) to be plotted). Using a value clearly above 0 mm can save a lot of computation time if the polygons belonging to values below the threshold are not plotted.
ScaleHigh	ScaleHigh Highest value per class interval, i.e. the highest legend breaks, if these are manually chosen. Please note that in case of x values in ColoursNumber, ScaleHigh should also contain x values.



ScaleLow	ScaleLow Lowest value per class interval, i.e. the lowest legend breaks, if these are manually chosen. Please note that in case of x values in ColoursNumber, ScaleLow should also contain x values.
ScaleTopTimeStep	Highest colour class ends here (maximum rainfall accumulation (mm) to be plotted). Sometimes the legend is not correctly plotted. In that case try other values for ScaleTopTimeStep and/or ScaleBottomTimeStep For instance, if the highest class (> x mm) is plotted below instead of above the other classes. Or if the number of classes does not match the number of chosen classes. Another way to prevent this is to manually give the legend breaks (ManualScale not equal to "no").
SizePixelBorder	Size of pixel borders
SizePlotLocation	Size of symbol and and accompanied text for specified location on map
SizePlotTitle	Size of plot title
SymbolPlotLocation	Symbol to be plotted for specified location on map
TIMESTEP	Duration of time interval of sampling strategy (min)
TimeZone	Time zone of data (e.g. "UTC")
TitleRadars	First part of title of plot
XMiddle	The longitude of the centre of the Azimuthal Equidistant Cartesian coordinate system, given in the coordinate system of the input data
YMiddle	The latitude of the centre of the Azimuthal Equidistant Cartesian coordinate system, given in the coordinate system of the input data

### Author(s)

Aart Overeem & Hidde Leijnse

### References

"ManualRAINLINK.pdf"

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

### Examples

RainMapsRadarsTimeStep()

---

RainRetrievalMinMaxRSL

*Function for path-averaged rainfall estimation using microwave links.*


---

### Description

Function for path-averaged rainfall estimation using microwave links. Maximum and minimum path-averaged rainfall intensities are computed in subfunction “MinMaxRSLToMeanR”, where a fixed correction factor is applied to remove wet antenna attenuation.

Works for a sampling strategy where minimum and maximum received signal powers are provided, and the transmitted power levels are constant.

### Usage

```
RainRetrievalMinMaxRSL(Aa = 2.3, alpha = 0.33, Data, kRPowerLawData,
  PmaxCor, PminCor, Pref)
```

### Arguments

Aa	Wet antenna attenuation correction $A_a$ (dB)
alpha	Coefficient ( $\alpha$ ) determining contribution of minimum and maximum path-averaged rainfall intensity to mean path-averaged rainfall intensity (-)
Data	Data frame with microwave link data
kRPowerLawData	Values of coefficients a and b employed to convert specific attenuation to path-averaged rainfall intensity for a range of microwave frequencies
PmaxCor	Data frame with corrected maximum received powers (dB)
PminCor	Data frame with corrected minimum received powers (dB)
Pref	Reference level (dB)

### Value

Mean path-averaged rainfall intensity ( $\text{mm h}^{-1}$ )

### Author(s)

Aart Overeem & Hidde Leijnse

### References

”ManualRAINLINK.pdf”

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

### Examples

```
RainRetrievalMinMaxRSL(Aa=2.3,alpha=0.33,Data=DataOutlierFiltered,
  kRPowerLawData=kRPowerLawData,PmaxCor=Pcor$PmaxCor,PminCor=Pcor$PminCor,Pref=Pref)
```

---

ReadRainLocation	<i>Function for finding (interpolated) rainfall value for a given latitude and longitude.</i>
------------------	---

---

## Description

Function for finding (interpolated) rainfall value for a given latitude and longitude. I.e. find the grid cell which belongs to the location for which latitude and longitude are provided.

## Usage

```
ReadRainLocation(CoorSystemInputData, dataf, FileGrid, Lat, Lon, XMiddle,
                 YMiddle)
```

## Arguments

CoorSystemInputData	Coordinate system of the input data (e.g. "+init=epsg:4326" for WGS84 in degrees).
dataf	Data frame of (interpolated) rainfall values
FileGrid	File with interpolation grid in same coordinate system as CoorSystemInputData
Lat	Latitude of location for which (interpolated) rainfall value is to be extracted (in coordinate system CoorSystemInputData)
XMiddle	The longitude of the centre of the Azimuthal Equidistant Cartesian coordinate system, given in the coordinate system of the input data
YMiddle	The latitude of the centre of the Azimuthal Equidistant Cartesian coordinate system, given in the coordinate system of the input data
Lot	Longitude of location for which (interpolated) rainfall value is to be extracted (in coordinate system CoorSystemInputData)

## Value

Rainfall value for selected location (in unit of provided input rainfall data)

## Author(s)

Aart Overeem & Hidde Leijnse

## References

"ManualRAINLINK.pdf"

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

## Examples

```
ReadRainLocation(CoorSystemInputData=CoorSystemInputData,dataf=dataf,FileGrid=FileGrid,
                 Lat=Lat,Lon=Lon,XMiddle=XMiddle,YMiddle=YMiddle)
```

---

RefLevelMinMaxRSL	<i>Function for determination of reference signal level, which is representative of dry weather.</i>
-------------------	--

---

### Description

Function for determination of reference signal level, which is representative of dry weather.

Works for a sampling strategy where minimum and maximum received signal powers are provided, and the transmitted power levels are constant.

### Usage

```
RefLevelMinMaxRSL(Data, Dry = NULL, HoursRefLevel = 2.5,
  PeriodHoursRefLevel = 24)
```

### Arguments

Data	Data frame with microwave link data.
Dry	Data frame: Should interval be considered dry for reference level determination? (0 = wet; 1 = dry)
HoursRefLevel	Minimum number of hours that should be dry in preceding PeriodHoursRefLevel hours for computing reference level (h)
PeriodHoursRefLevel	Period over which reference level is to be determined (h)

### Value

Reference level (dB)

### Author(s)

Aart Overeem & Hidde Leijnse

### References

"ManualRAINLINK.pdf"

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

### Examples

```
RefLevelMinMaxRSL(Data=DataPreprocessed,Dry=NULL,HoursRefLevel=2.5,
  PeriodHoursRefLevel=24)
```

---

ToPolygonsRain	<i>Subfunction which assigns values of rainfall grid to polygons.</i>
----------------	---

---

**Description**

Subfunction which assigns values of rainfall grid to polygons.

**Usage**

ToPolygonsRain(Data)

**Arguments**

Data	Field of rainfall depths at the chosen grid
------	---

**Value**

Field of rainfall depths for the polygons at the chosen grid

**Author(s)**

Aart Overeem & Hidde Leijnse

**References**

”ManualRAINLINK.pdf”

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

**Examples**

ToPolygonsRain(Data=Data)

---

WetDryNearbyLinkApMinMaxRSL

*Function for classifying wet and dry periods according to the nearby link approach. Function also prepares link data for determination of reference signal level and for computing corrected received powers.*

---

**Description**

The received signal powers often decrease during non-rainy periods, resulting in non-zero rainfall estimates, e.g. caused by reflection of the beam or dew formation on the antennas. To prevent this rainfall overestimation a reliable classification of wet and dry periods is needed. This is also beneficial for determining an appropriate reference signal level, representative for dry weather. In order to define wet and dry periods, we assume that rain is correlated in space, and hence that several links in a given area should experience a decrease in received signal level in the case of rain. A time interval is labeled as wet if at least half of the links in the vicinity (for chosen radius) of the selected link experience such a decrease. This so called nearby link approach is applied in this

function. The function also prepares link data for determination of reference signal level and for computing corrected received powers.

Works for a sampling strategy where minimum and maximum received signal powers are provided, and the transmitted power levels are constant.

### Usage

```
WetDryNearbyLinkApMinMaxRSL(Data, CoordSystemInputData = NULL,
  MinHoursPmin = 6, PeriodHoursPmin = 24, Radius = 15, Step8 = TRUE,
  ThresholdMedian = -1.4, ThresholdMedianL = -0.7,
  ThresholdNumberLinks = 3, ThresholdWetDry = 2)
```

### Arguments

Data	Data frame with microwave link data
CoordSystemInputData	Define coordinate system of input data (in case of WGS84 provide NULL)
MinHoursPmin	Minimum number of hours in the previous PeriodHoursPmin hours needed for computing $\max(P_{\min})$ (h)
PeriodHoursPmin	Number of hours that is considered for computation of $\max(P_{\min})$ (h)
Radius	Radius in wet-dry classification (km)
Step8	If TRUE step 8 in the wet-dry classification is performed, else it is not executed
ThresholdMedian	Threshold value (dB)
ThresholdMedianL	Threshold value (dB km <sup>-1</sup> )
ThresholdNumberLinks	Only use data if number of available links is at least larger than this threshold for the time interval under consideration. The selected link is also counted.

### Value

Data frame: Should interval be considered dry for reference level determination? (0 = wet; 1 = dry)  
 Values for filter to remove outliers (dB km<sup>-1</sup> h)

### Author(s)

Aart Overeem & Hidde Leijnse

### References

"ManualRAINLINK.pdf"

Overeem, A., Leijnse, H., and Uijlenhoet, R. (2016): Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, Atmospheric Measurement Techniques, under review.

### Examples

```
WetDryNearbyLinkApMinMaxRSL(Data=DataPreprocessed, CoordSystemInputData=NULL,
  MinHoursPmin=6, PeriodHoursPmin=24, Radius=15, Step8=TRUE, ThresholdMedian=-1.4,
  ThresholdMedianL=-0.7, ThresholdNumberLinks=3, ThresholdWetDry=2)
```

# Index

## \*Topic **datasets**

Linkdata, [7](#)

ClimVarParam, [2](#)

CorrectMinMaxRSL, [3](#)

IDW, [4](#)

Interpolation, [4](#)

IntpPathToPoint, [6](#)

Linkdata, [7](#)

MinMaxRSLToMeanR, [8](#)

OrdinaryKriging, [9](#)

OutlierFilterMinMaxRSL, [10](#)

PlotLinkLocations, [11](#)

Polygons, [13](#)

PreprocessingMinMaxRSL, [14](#)

RainMapsLinksDaily, [15](#)

RainMapsLinksTimeStep, [20](#)

RainMapsRadarsDaily, [25](#)

RainMapsRadarsTimeStep, [29](#)

RainRetrievalMinMaxRSL, [34](#)

ReadRainLocation, [35](#)

RefLevelMinMaxRSL, [36](#)

ToPolygonsRain, [37](#)

WetDryNearbyLinkApMinMaxRSL, [37](#)