

CMPS 2200 Assignment 1

Name: _____

Name: _____

In this assignment, you will learn more about asymptotic notation, parallelism, functional languages, and algorithmic cost models. As in the recitation, some of your answer will go here and some will go in `main.py`. You are welcome to edit this `assignment-01.md` file directly, or print and fill in by hand. If you do the latter, please scan to a file `assignment-01.pdf` and push to your github repository.

1. Asymptotic notation

- 1a. Is $2^{n+1} \in O(2^n)$? Why or why not?

Enter your answer in `answers.md` .

.
.
.
.

- 1b. Is $2^{2^n} \in O(2^n)$? Why or why not?

Enter your answer in `answers.md` .

.
.
.
.

- 1c. Is $n^{1.01} \in O(\log^2 n)$?

Enter your answer in `answers.md` .

.
.
.

- 1d. Is $n^{1.01} \in \Omega(\log^2 n)$?

Enter your answer in `answers.md` .

.
.
.

- 1e. Is $\sqrt{n} \in O((\log n)^3)$?

Enter your answer in `answers.md` .

.
.
.

- 1f. Is $\sqrt{n} \in \Omega((\log n)^3)$?

Enter your answer in `answers.md` .

.
.
.

- 1g. Consider the definition of “Little o” notation:

$g(n) \in o(f(n))$ means that for **every** positive constant c , there exists a constant n_0 such that $g(n) \leq c \cdot f(n)$ for all $n \geq n_0$. There is an analogous definition for “little omega” $\omega(f(n))$. The distinction between $o(f(n))$ and $O(f(n))$ is that the former requires the condition to be met for **every** c , not just for some c . For example, $10x \in o(x^2)$, but $10x^2 \notin o(x^2)$.

.

Prove that $o(g(n)) \cap \omega(g(n))$ is the empty set.

Enter your answer in answers.md .

.
.
.
.
.
.
.
.
.
.
.
.
.

2. SPARC to Python

Consider the following SPARC code:

```
foo x =
  if x ≤ 1 then
    x
  else
    let (ra,rb) = (foo (x - 1)) , (foo (x - 2)) in
      ra + rb
  end.
```

- 2a. Translate this to Python code – fill in the `def foo` method in `main.py`
- 2b. What does this function do, in your own words?

Enter your answer in answers.md .

.
.
.
.
.

3. Parallelism and recursion

Consider the following function:

```
def longest_run(myarray, key)
    """
    Input:
        `myarray`: a list of ints
        `key`: an int
    Return:
        the longest continuous sequence of `key` in `myarray`
    """
```

E.g., `longest_run([2,12,12,8,12,12,12,0,12,1], 12) == 3`

- 3a. First, implement an iterative, sequential version of `longest_run` in `main.py`.

- 3b. What is the Work and Span of this implementation?

Enter your answer in answers.md

.

.

.

.

.

.

.

.

.

.

- 3c. Next, implement a `longest_run_recursive`, a recursive, divide and conquer implementation. This is analogous to our implementation of `sum_list_recursive`. To do so, you will need to think about how to combine partial solutions from each recursive call. Make use of the provided class `Result`.
- 3d. What is the Work and Span of this recursive algorithm?

Enter your answer in answers.md .

.

.

.

.

.

.

.

.

.

.

- 3e. Assume that we parallelize in a similar way we did with `sum_list_recursive`. That is, each recursive call spawns a new thread. What is the Work and Span of this algorithm?

Enter your answer in answers.md .

.

.

.

.

.

.

.