

Discrete Structures: Programming Constructs CMPSC 102

Oliver BONHAM-CARTER

Spring 2024

Week 3

Slides 02

Let's Discuss

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's

Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

Key Questions


How do I use **iteration** and **conditional logic** in a Python program to perform computational tasks like processing a file's contents and mathematical tasks like using Newton's method to approximate the square root of a number?

Learning Objectives

To **remember** and **understand** some discrete mathematics and Python programming concepts, setting the stage for exploring of discrete structures.

Loops for Iteration

A loop is a way to reuse code blocks



Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While
For
Newton's
Method
Cube Roots
Quadruple Roots
Quadratic Roots

Solutions

The While Loop

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's

Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

```
index = 0
while (index < 10): # condition
    print(f"Count :{index}")
    index += 1 # add one to index
```

Output

Count :0
Count :1
Count :2
Count :3
Count :4
Count :5
Count :6
Count :7
Count :8
Count :9

The for ... in range() Loop

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's

Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

```
for index in range(10):  
    print(f"Count :{index}")
```

Output

Count :0
Count :1
Count :2
Count :3
Count :4
Count :5
Count :6
Count :7
Count :8
Count :9

Square Roots

Mathematical loops to find quadruple roots

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's
Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

How to compute : \sqrt{x} ?

Method

The function initializes the guess for the square root and iteratively refines it using an approximation formula until the approximation is within the specified tolerance.

Newton's Method

Mathematical loops to find square roots

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For


Newton's
Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions



The While Loop Application

Finding a Square Root

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's
Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

```
n = 4
guess = 1.0
while abs(n - guess*guess) > 0.0001:
    guess = guess - (guess*guess - n)/(2*guess)
print(f"n = {n} : guess = {guess}")
```

- Iteratively **guesses** the square root until **within tolerance**
- The while loop uses 'abs' for computing an absolute value
- This loop computes the root as 2.0000000929222947
- The `math.sqrt(n)` function confirms this approximation!
- Any questions about this way to approximate a square root?

The While Loop Application

Finding a Square Root

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's
Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

```
n = 4
guess = 1.0
while abs(n - guess*guess) > 0.0001:
    guess = guess - (guess*guess - n)/(2*guess)
print(f"n = {n} : guess = {guess}")
```

Output

```
n = 4 : guess = 2.5
n = 4 : guess = 2.05
n = 4 : guess = 2.000609756097561
n = 4 : guess = 2.0000000929222947
```

The For Loop Application

Finding a Square Root

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's
Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

```
n = 4
guess = 1.0
for i in range(5):
    abs(n - guess*guess) > 0.0001
    guess = guess - (guess*guess - n)/(2*guess)
print(f"n = {n} : guess = {guess}")
```

Output

```
n = 4 : guess = 2.5
n = 4 : guess = 2.05
n = 4 : guess = 2.000609756097561
n = 4 : guess = 2.0000000929222947
```

Cube Roots

Mathematical loops to find cube roots

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's
Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

How to compute : $\sqrt[3]{x}$?

Method

The function initializes the guess for the cube root and iteratively refines it using an approximation formula until the approximation is within the specified tolerance.

Cube Roots

Approximations to find cube roots; result = 31

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For


Newton's
Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions




Cube Roots

Approximations to find cube roots; result = 31

Approximations

Approximations to Cube Root of 29791



400.5466666666667,
267.0930063983859,
178.2012041240575,
119.11351331724008,
80.10891816753315,
54.95334366560159,
39.923893861643855,
32.846072628479256,
31.101812384645754,
31.00033292113973,
31.00000000357532,
31.0

Cube Roots

Code

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's

Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

```
def cube_root_approximation(number, tolerance=1e-6):  
    # Initial guess for the cube root  
    # guess = number / 2.0 # one way to start  
    guess = 5  
    # Iterate until the approximation  
    # is within the specified tolerance  
    while abs(guess**3 - number) > tolerance:  
        # Update the guess using the approximation formula  
        guess = (2 * guess + number / (guess**2)) / 3.0  
        print(f" guess = {guess}")  
    return guess  
  
# Example: Calculate the cube root of 29791  
input_number = 29791  
result = cube_root_approximation(input_number)  
  
# Display the result  
print(f"The cube root of {input_number}")  
print(f" is approximately: {result}")
```

Quadruple Roots

Mathematical loops to find quadruple roots

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's
Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

How to compute : $\sqrt[4]{x}$?

Method

The function initializes the guess for the quadruple root and iteratively refines it using an approximation formula until the approximation is within the specified tolerance.

Quadruple Roots

Approximations to find quadruple roots, Result = 7

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's

Method


Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

Approximations to Quadruple Root of 2401



Quadruple Root Approximations

Approximations to find quadruple roots, Result = 7

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's
Method

Cube Roots


Quadruple Roots

Quadratic Roots

Solutions

Approximations

Approximations to Quadruple Root of 2401



900.375000346933,
675.2812510825596,
506.46094026121705,
379.8457098164694,
284.8842933147822,
213.66324594739956,
160.24749599845413,
120.18576786629791,
90.13967165836334,
67.60557331037666,
50.70612258852655,
38.03419610727984,
28.5365566959587,
21.428247703754217,
16.132191727838684,
12.242116142093641,
9.508748977118197,
7.82973307939813,
7.122821698405513,
7.00314043464742,
7.000002111777238,
7.000000000000956

Quadruple Roots

Code

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's

Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

```
def quadruple_root_approximation(number, tolerance=1e-6):
    # Initial guess for the fourth root
    guess = number / 2.0
    # Iterate until the approximation
    # is within the specified tolerance
    while abs(guess**4 - number) > tolerance:
        # Update the guess using the approximation formula
        guess = (3 * guess + number / (guess**3)) / 4.0
        print(f" guess = {guess}")
    return guess

# Example: Calculate the fourth root of 2401
input_number = 2401
result = quadruple_root_approximation(input_number)

# Display the result
print(f"The fourth root of {input_number}")
print(f" is approximately: {result}")
```

Quadratic Roots

The Problem Defined

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's
Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

To solve

$$x^2 + 3x - 4 = 0 \quad (1)$$

Want to have roots

$$x_1 = ? \text{ and } x_2 = ?$$

THINK

Quadratic Root Calculation

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's
Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

Quadratic Equation

$$ax^2 + bx + c = 0 \quad (2)$$

Quadratic Formula

$$x_{1,2} = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a} \quad (3)$$

Special Note

Note the $x_{1,2}$ to imply that there are **two** solutions (i.e., x_1 and x_2) to find for a second degree equation as observed from the x^2 .

Programmed Solution

Function `calc_quad_eqn_roots()`

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's

Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

```
def calc_quad_eqn_roots(  
    a: float, b: float, c: float) -> float:  
    """Calculate roots of quadratic equation."""  
    D = (b * b - 4 * a * c) ** 0.5  
    x_one = (-b + D) / (2 * a)  
    x_two = (-b - D) / (2 * a)  
    return x_one, x_two  
  
print(f"{calc_quad_eqn_roots(1,2,1)}")
```

- Three floating-point inputs: a , b , and c
- Two floating-point outputs: x_{one} and x_{two}
- How does it calculate the roots of a quadratic equation?

- **Wait, how do we test functions to ensure correctness??**

Creating Solutions

Discrete
Structures:
Programming
Constructs
CMPSC 102

Oliver
BONHAM-
CARTER

Let's Discuss

Loops

While

For

Newton's
Method

Cube Roots

Quadruple Roots

Quadratic Roots

Solutions

