

# Introduction to Database Systems: CS305

## Updating Tables

Oliver Bonham-Carter  
Hang Zhao

17 October 2023

# Updated Database

Introduction  
to Database  
Systems:  
CS305  
Updating  
Tables

Oliver  
Bonham-  
Carter  
Hang Zhao

Modifying  
Tables

Copying  
Tables

Removing  
Data

Deleting  
Tuples

Deleting  
Entries

DB Browser

- We will be using this database to showcase these commands.

```
cat campusDB_build.txt | sqlite3 myCampusDB.sqlite3
```

# Alter a Table's Name

Introduction  
to Database  
Systems:  
CS305  
Updating  
Tables

Oliver  
Bonham-  
Carter  
Hang Zhao

Modifying  
Tables

Copying  
Tables

Removing  
Data

Deleting  
Tuples

Deleting  
Entries

DB Browser

- ALTER TABLE command modifies an existing table without performing a full dump and reload of the data.
- Rename an existing table

```
ALTER TABLE database_name.table_name  
    RENAME TO new_table_name;
```

# Alter a Table's Name

Introduction  
to Database  
Systems:  
CS305  
Updating  
Tables

Oliver  
Bonham-  
Carter  
Hang Zhao

Modifying  
Tables

Copying  
Tables

Removing  
Data

Deleting  
Tuples

Deleting  
Entries

DB Browser

- Create a new table using *Insert*.

```
INSERT INTO first_table_name  
[(column1, column2, ... columnN)]  
    SELECT column1, column2, ...columnN  
FROM second_table_name  
    [WHERE condition];
```

# Alter a Table's Name

Introduction  
to Database  
Systems:  
CS305  
Updating  
Tables

Oliver  
Bonham-  
Carter  
Hang Zhao

Modifying  
Tables

Copying  
Tables

Removing  
Data

Deleting  
Tuples

Deleting  
Entries

DB Browser

- Add a new table to try this on ...

```
CREATE TABLE myStuff(  
    Id varchar,  
    name varchar,  
    totCred numeric  
);
```

.tables

- Change table's name

```
ALTER TABLE myStuff RENAME TO myNewStuff;
```

.tables

# Create and Populate New Table From Another: AS

- Used to create a table from an existing table by copying the existing table's columns with data structures

```
CREATE TABLE new_table AS SELECT expressions  
FROM existing_tables  
[WHERE conditions];
```

```
CREATE TABLE TeachesIDs AS SELECT id FROM Teaches;
```

```
DROP TABLE IF EXISTS sTable;  
CREATE TABLE sTable AS  
SELECT id, name, totCred  
FROM student  
WHERE ID in ("S1","S2","S3","S4","S5");
```

# Removing Tables or Table Data

Introduction  
to Database  
Systems:  
CS305  
Updating  
Tables

Oliver  
Bonham-  
Carter  
Hang Zhao

Modifying  
Tables

Copying  
Tables

Removing  
Data

Deleting  
Tuples

Deleting  
Entries

DB Browser

- Remove only table's data but leave the empty table in the DB

```
DELETE FROM tableName;
```

- Remove entire table *and* its data too

```
DROP TABLE IF EXISTS tableName;
```

# Delete Tuples From a Table

First, let's add a row (i.e., a tuple) to delete ...

- Used to delete data in a table

```
DELETE FROM table_name  
WHERE [condition];
```

- Add a record to erase for this example

```
select * from instructor;
```

```
INSERT INTO instructor  
VALUES ( "E10101", "Potter",  
        "ES1", "English", 90000.00 );
```

```
/* Did the tuple arrive into the table?*/  
select * from instructor;
```



# Delete Tuples From a Table

Second, we delete the recently added row (i.e., a tuple)

Introduction  
to Database  
Systems:  
CS305  
Updating  
Tables

Oliver  
Bonham-  
Carter  
Hang Zhao

Modifying  
Tables

Copying  
Tables

Removing  
Data

Deleting  
Tuples

Deleting  
Entries

DB Browser

- Delete all tuples in the Instructor for a particular condition

```
delete from instructor where name == "Potter";
```

- Be more specific: add to the conditional part:

```
delete from instructor where name == "Potter"  
and deptName == "English";
```

# Update an Entry

Introduction  
to Database  
Systems:  
CS305  
Updating  
Tables

Oliver  
Bonham-  
Carter  
Hang Zhao

Modifying  
Tables

Copying  
Tables

Removing  
Data

Deleting  
Tuples

Deleting  
Entries

DB Browser

- Create a new table using *Update*.


```
UPDATE table_name  
    SET column1 = value1,  
        column2 = value2....,  
        columnN = valueN  
    WHERE [condition];
```

- Add an update to the Student table: Replace the ID and credits belonging to "Beuller"


```
UPDATE student SET ID = "XS5" where name == "Beuller";
```

```
UPDATE student SET ID = "S5", totCred = 55  
WHERE name == "Beuller";
```

# New database: Chinook's Schema



- Ref: <http://www.sqlitetutorial.net/sqlite-sample-database/>



## About

This program was developed originally by Mauricio Piacentini (@piacentini) from Tabuleiro Producoes, as the Arca Database Browser. The original version was used as a free companion tool to the Arca Database Xtra, a commercial product that embeds SQLite databases with some additional extensions to handle compressed and binary data.

The original code was trimmed and adjusted to be compatible with standard SQLite 2.x databases. The resulting program was renamed SQLite Database Browser, and released into the Public Domain by Mauricio. Icons were contributed by Raquel Ravanini, also from Tabuleiro. Jens Miltner (@jmiltner) contributed the code to support SQLite 3.x databases for the 1.2 release.

- Main: <https://sqlitebrowser.org/>
- Download: <https://sqlitebrowser.org/dl/>
- Linux: command:  
`sudo apt-get install sqlitebrowser`

## Let's Try It Out!

- Locate the sandbox database called `sandbox/media_chinook/chinook.sqlite3`
- Test-out the SQLite tool

**THINK**