

Block Ciphers

Recall: Symmetric-Key Encryption Algorithms

- ◆ Both parties share the key needed to encrypt and decrypt messages, hence both parties are equal
- ◆ Symmetric key ciphers developed from product ciphers include DES, Blowfish, IDEA, LOKI, RC5, Rijndael (AES) and others

Block Ciphers

- ◆ One of the most widely used types of cryptographic algorithms
 - For encrypting data to ensure secrecy
 - As a cryptographic checksum to ensure integrity
 - For authentication services

Block Ciphers

- ◆ Used because they are comparatively fast, and we know how to design them
- ◆ We'll look at both DES (Data Encryption Standard) and AES (Advanced Encryption Standard)
 - Focus on DES in this slideset, though AES has been the default standard for at least 20 years

Block vs Stream Ciphers

- ◆ Block ciphers process messages in blocks, each of which is then en/decrypted
 - So all bits of block must be available before processing
- ◆ Like a substitution on very big characters
 - 64-bits or more

Block vs Stream Ciphers

- ◆ Stream ciphers process messages a byte at a time when en/decrypting
 - Though technically the only difference here is block size, there are significant differences in how stream and block ciphers are designed.
 - Typically, a “blinding stream” is created, which is then XORed with the plaintext stream to create ciphertext stream

Claude Shannon

- ◆ Wrote some of the pivotal papers on modern cryptology theory
 - C E Shannon, "Communication Theory of Secrecy Systems", Bell System Technical Journal, Vol 28, Oct 1949, pp 656-715
 - C E Shannon, "Prediction and Entropy of printed English", Bell System Technical Journal, Vol 30, Jan 1951, pp 50-64

Claude Shannon

- ◆ Among other things, he developed the concepts of:
 - Entropy of a message
 - Redundancy in a language
 - Theories about how much information is needed to break a cipher
 - Defined the concepts of computationally secure vs unconditionally secure ciphers
 - Introduced the idea of substitution-permutation (S-P) networks, basis of current product ciphers

Shannon S-P Network

- ◆ cipher needs to completely obscure statistical properties of original message
 - E.g., a one-time pad does this
- ◆ more practically Shannon suggested combining elements to obtain:
 - **diffusion** – dissipates statistical structure of plaintext over bulk of ciphertext
 - **confusion** – makes relationship between ciphertext and key as complex as possible
- ◆ S-P networks designed to provide these

Block Cipher Requirements

- ◆ Must be reasonably efficient
- ◆ Must be able to *efficiently* decrypt ciphertext to recover plaintext
- ◆ Must have a reasonable key length
- ◆ First attempt: Arbitrary reversible substitution
 - For a large block size this is not practical for implementation and performance reasons

Why Not Arbitrary Reversible Substitution?

◆ Well, let's think about this: If we're going from n bit plaintext to n bit ciphertext:

- How many possible plaintext blocks?
- How many total unique reversible transformations?
- What is the key length?

Why Not Arbitrary Reversible Substitution?

- ◆ If we're going from n bit plaintext to n bit ciphertext:
 - There are 2^n possible plaintext blocks.
 - Each must map to a unique output block, so total of $2^n!$ reversible transformations
 - ◆ List all n -bit binary (plaintext) strings. First one can go to any of 2^n n -bit binary strings, next to any of $2^n - 1$ output strings, etc.

Why Not Arbitrary Reversible Substitution?

- ◆ If we're going from n bit plaintext to n bit ciphertext:
 - So, to specify a specific transformation, essentially need to provide the list of ciphertext outputs for each input block.

Why Not Arbitrary Reversible Substitution?


- ◆ If we're going from n bit plaintext to n bit ciphertext:
 - How many? Well, 2^n inputs, so 2^n outputs, each n bits long implies an effective key size of $n(2^n)$ bits.
 - ◆ For blocks of size 128 this amounts to a key of length $128(2^{128}) = 2^{135} = 2^{132}$ bytes $\sim 5.44 \times 10^{39}$ bytes = 5.44×10^{27} **TB**

Feistel Cipher Structure

- ◆ Horst Feistel devised the **Feistel cipher**
 - based on concept of invertible product cipher
 - His main contribution was invention of structure that adapted Shannon's S-P network into easily inverted structure.

Feistel Cipher Structure

- ◆ Process consists of several rounds. In each round:
 - partitions input block into two halves
 - Perform substitution on left half by a *round function* based on right half of data and subkey
 - then have permutation swapping halves
- ◆ implements Shannon's substitution-permutation network concept



Feistel Cipher Design Principles

◆ block size

- increasing size improves security, but slows cipher
- 64 bits reasonable tradeoff. Some use 128 bits
 - ◆ All variants of AES use 128 bit blocks

◆ key size

- increasing size improves security, makes exhaustive key searching harder, but may slow cipher
- 64 bit considered inadequate. 256 bit is common size (for now)
 - ◆ AES has variants based on key size: AES-128, AES-192, AES-256

◆ number of rounds

- increasing number improves security, but slows cipher
- AES-128 (10 rounds), AES-192 (12 rounds), AES-256 (14 rounds), DES (16 rounds)

Feistel Cipher Design Principles

- ◆ **subkey generation**

- greater complexity can make analysis harder, but slows cipher


- ◆ **round function**

- greater complexity can make analysis harder, but slows cipher

- ◆ **fast software en/decryption & ease of analysis**

- are more recent concerns for practical use and testing
- Making algorithms easy to analyze helps determine cipher effectiveness (DES functionality is not easily analyzed)


Feistel Cipher Decryption



Data Encryption Standard (DES)

- ◆ Was once the most widely used block cipher in world
- ◆ Adopted in 1977 by NBS (now NIST)
 - as FIPS PUB 46
- ◆ Encrypts 64-bit data using 56-bit key
- ◆ No longer in use
 - Withdrawn by NIST in 2005

DES Encryption



Initial Permutation IP

- ◆ first step of the data computation
- ◆ IP reorders the input data bits
 - Permutation specified by tables (See FIPS 46-3)
- ◆ even bits to LH half, odd bits to RH half
- ◆ quite regular in structure (easy in h/w)

DES Round Structure

- ◆ uses two 32-bit L & R halves
- ◆ as for any Feistel cipher can describe as:

$$L_i = R_{i-1}$$

$$R_i = L_{i-1} \text{ xor } F(R_{i-1}, K_i)$$

DES Round Structure

- ◆ takes 32-bit R half and 48-bit subkey and:
 - expands R to 48-bits using perm E
 - adds to subkey (XOR)
 - passes through 8 S-boxes to get 32-bit result
 - ◆ Each S-box takes 6 bits as input and produces 4 as output
 - finally permutes this using 32-bit perm P




Figure 3.8 Single Round of DES Algorithm

S-boxes



S_1

14	4	13	1	2	15	11	8	3	10	6	12	5	9	0	7
0	15	7	4	14	2	13	1	10	6	12	11	9	5	3	8
4	1	14	8	13	6	2	11	15	12	9	7	3	10	5	0
15	12	8	2	4	9	1	7	5	11	3	14	10	0	6	13

S_2

15	1	8	14	6	11	3	4	9	7	2	13	12	0	5	10
3	13	4	7	15	2	8	14	12	0	1	10	6	9	11	5
0	14	7	11	10	4	13	1	5	8	12	6	9	3	2	15
13	8	10	1	3	15	4	2	11	6	7	12	0	5	14	9

S_3


10	0	9	14	6	3	15	5	1	13	12	7	11	4	2	8
13	7	0	9	3	4	6	10	2	8	5	14	12	11	15	1
13	6	4	9	8	15	3	0	11	1	2	12	5	10	14	7
1	10	13	0	6	9	8	7	4	15	14	3	11	5	2	12

S_4

7	13	14	3	0	6	9	10	1	2	8	5	11	12	4	15
13	8	11	5	6	15	0	3	4	7	2	12	1	10	14	9
10	6	9	0	12	11	7	13	15	1	3	14	5	2	8	4
3	15	0	6	10	1	13	8	9	4	5	11	12	7	2	14

CS 334: Computer Security There are four more

DES Round Structure



Substitution Boxes S

- ◆ have eight S-boxes which map 6 to 4 bits
- ◆ each S-box is actually 4 little 4 bit boxes
 - outer bits 1 & 6 (**row** bits) considered 2-bit number that selects row
 - inner bits 2-5 (**col** bits) considered 4-bit number that selects column.
 - Decimal number in table is converted to binary and that gives the four output bits
 - result is 8 sets of 4 bits, or 32 bits
- ◆ row selection depends on both data & key
 - feature known as autoclaving (autokeying)

DES Key Schedule

- ◆ forms subkeys used in each round
- ◆ consists of:
 - initial permutation of the key (PC1) which selects 56-bits in two 28-bit halves
 - 16 stages consisting of:
 - ◆ selecting 24-bits from each half
 - ◆ permuting them by PC2 for use in function f ,
 - ◆ rotating **each half** separately either 1 or 2 places depending on the **key rotation schedule K**

Table 3.4 DES Key Schedule Calculation

(a) Input Key

1	2	3	4	5	6	7	8
9	10	11	12	13	14	15	16
17	18	19	20	21	22	23	24
25	26	27	28	29	30	31	32
33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48
49	50	51	52	53	54	55	56
57	58	59	60	61	62	63	64

(b) Permuted Choice One (PC-1)

57	49	41	33	25	17	9
1	58	50	42	34	26	18
10	2	59	51	43	35	27
19	11	3	60	52	44	36
63	55	47	39	31	23	15
7	62	54	46	38	30	22
14	6	61	53	45	37	29
21	13	5	28	20	12	4

(c) Permuted Choice Two (PC-2)

14	17	11	24	1	5	3	28
15	6	21	10	23	19	12	4
26	8	16	7	27	20	13	2
41	52	31	37	47	55	30	40
51	45	33	48	44	49	39	56
34	53	46	42	50	36	29	32

(d) Schedule of Left Shifts

Round number	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Bits rotated	1	1	2	2	2	2	2	2	1	2	2	2	2	2	2	1

DES Decryption

- ◆ decrypt must unwind steps of data computation
- ◆ with Feistel design, do encryption steps again
- ◆ using subkeys in reverse order (SK16 ... SK1)
- ◆ note that IP undoes final FP step of encryption

DES Decryption

- ◆ 1st round with SK16 undoes 16th encrypt round
- ◆
- ◆ 16th round with SK1 undoes 1st encrypt round
- ◆ then final FP undoes initial encryption IP
- ◆ thus recovering original data value

Avalanche Effect

- ◆ Desirable property for an encryption algorithm
- ◆ A change of **one** input or key bit results in changing approx **half** output bits
- ◆ This makes attempts to “home-in” by guessing keys impossible
- ◆ DES exhibits strong avalanche

Strength of DES – Key Size

- ◆ 56-bit keys have $2^{56} = 7.2 \times 10^{16}$ values
- ◆ brute force search looks hard
- ◆ As we've discussed, it's not

Strength of DES – Timing Attacks

- ◆ attacks actual implementation of cipher
- ◆ use knowledge of consequences of implementation to derive knowledge of some/all subkey bits
- ◆ specifically use fact that calculations can take varying times depending on the value of the inputs to it
- ◆ particularly problematic on smartcards

Strength of DES – Analytic Attacks

- ◆ now have several analytic attacks on DES
- ◆ these utilize some deep structure of the cipher
 - by gathering information about encryptions
 - can eventually recover some/all of the sub-key bits
 - if necessary then exhaustively search for the rest

Strength of DES – Analytic Attacks

◆ Generally these are statistical attacks

◆ Include


- differential cryptanalysis
- linear cryptanalysis
- related key attacks

Why Not Double DES?

- ◆ That is, why not just use $C = E_{K_1}[E_{K_2}[P]]$?
 - Proven that it's NOT same as $C = E_{K_3}[P]$

- ◆ Susceptible to *Meet-in-the-Middle Attack*

- Described by Diffie & Hellman in 1977
- Based on observation that if $C = E_{K_2}[E_{K_1}[P]]$, then $X = E_{K_1}[P] = D_{K_2}[C]$



(a) Double Encryption

Meet-in-the-Middle Attack

- ◆ Given a known plaintext-ciphertext pair, proceed as follows:
 - Encrypt P for all possible values of K1
 - ◆ Cost is on order of 2^{56}
 - Store results in table and sort by value of X
 - Decrypt C for all possible values of K2
 - ◆ During each decryption, check table for match. If find one, test two keys against another known plaintext-ciphertext pair

Meet-in-the-Middle Attack

- For any given plaintext P , there are 2^{64} possible ciphertexts produced by Double DES.
- But Double DES effectively has 112 bit key, so there are 2^{112} possible keys.
- On average then, for a given plaintext, the number of different 112 bit keys that will produce a given ciphertext is $2^{112}/2^{64}=2^{48}$
- Thus, first (P,C) pair will produce about 2^{48} false alarms
- Second (P,C) pair, however, reduces false alarm rate to $2^{48-64} = 2^{-16}$. So for two (P,C) pairs, the probability that correct key is determined is $1-(1/2^{16})$.
- Bottom line: a known plaintext attack will succeed against Double DES with an effort on order of 2^{56} , not much more than the 2^{55} required to crack single DES

Triple-DES with Two-Keys

◆ Would think Triple DES must use 3 encryptions but can use 2 keys with E-D-E sequence

$$C = E_{K1}[D_{K2}[E_{K1}[P]]]$$

- N.b. encrypt & decrypt equivalent in security
- if $K1=K2$ then can work with single DES

Modes of Operation

Modes of Operation


- ◆ Block ciphers encrypt fixed size blocks
- ◆ We need way to use these in practice, given that we usually have arbitrary amount of information to encrypt
- ◆ There are currently five modes of operation (first defined in FIPS PUB 81 in 1981)
- ◆ There are **block** and **stream** modes

Electronic Codebook Book (ECB)


- ◆ message is broken into independent blocks which are encrypted
 - Pad last block if necessary to make message length multiple of block size bits (e.g., 128 bits)
- ◆ each block is a value which is substituted, like a codebook, hence name
- ◆ each block is encoded independently of the other blocks

$$C_i = \text{DES}_{K1}(P_i)$$

Electronic Codebook Book (ECB)



Electronic Codebook (ECB) mode encryption



Electronic Codebook (ECB) mode decryption

Problem (Example from Applied Cryptography by B. Schneier)

- ◆ Adversary can modify encrypted messages without knowing the key or even the algorithm in manner that fools recipient
- ◆ Example: Money transfer between banks
 - Assume an agreed standard message format (below)

Bank One: Sending	1.5 blocks
Bank Two: Receiving	1.5 blocks
Depositor's Name	6 blocks
Depositor's Account	2 blocks
Amount of Deposit	1 block

Problem (cont.)

- ◆ Transfers encrypted using some block cipher in ECB mode
- ◆ Trudy, listens on communication lines between Bank of Alice and Bank of Bob
- ◆ She opens accounts at both banks, and transfers \$100 from her account at Bank of Alice to her account at Bank of Bob. Twice.
- ◆ Checks communication records to find two identical messages (presumably her transfer)
- ◆ Inserts copies of her transfer into communication link at will!
 - If clever, done with large amounts and many banks!
 - Assumes same key used (which is not a bad assumption in general)

Solution? Timestamp

- ◆ Bank adds timestamp to messages so they can't be replayed:

Date/Time Stamp:	1 block
Bank One: Sending	1.5 blocks
Bank Two: Receiving	1.5 blocks
Depositor's Name	6 blocks
Depositor's Account	2 blocks
Amount of Deposit	1 block

Block Number												
1	2	3	4	5	6	7	8	9	10	11	12	13
Time-stamp	Sending Bank	Receiving Bank	Depositor's Name							Depositor's Account	Amount	
Field												


Solution? Timestamp

- ◆ Trudy then sends multiple messages, this time examining blocks 5 through 12
- ◆ She replaces blocks 5 - 12 of many transfers with her ciphertext blocks 5 - 12!

Block Number												
1	2	3	4	5	6	7	8	9	10	11	12	13
Time-stamp	Sending Bank	Receiving Bank	Depositor's Name							Depositor's Account	Amount	
Field												

Graphics Issue with ECB

- ◆ Why does this happen (thanks to unknown colleague at San Jose State)?



Bottom Line:

- ◆ repetitions in message may show in ciphertext
 - if aligned with message block
 - particularly with data such as graphics
 - or with messages that change very little, which become a code-book analysis problem
- ◆ weakness due to encrypted message blocks being independent (i.e., not dependent on each other)

Bottom Line:

- ◆ Attacker can reorder cipher blocks in transit
 - or perhaps even insert or replace a block
- ◆ main use is sending a few blocks of data
 - E.g. Transmitting an encryption key

ECB: Advantages

- ◆ Encryption is not serial, so it can be done on individual blocks regardless of location in file
 - E.g., large data file
- ◆ Encryption/Decryption can be parallelized
- ◆ bit error in one ciphertext block does not prevent decryption of other blocks


Cipher Block Chaining (CBC)

- ◆ Wanted a method in which repeated blocks of plaintext (and whole messages) are encrypted differently each time
- ◆ Like ECB, message is broken into blocks, but these are linked together in the encryption operation
- ◆ Each previous cipher blocks is chained with current plaintext block, hence name
 - This makes the ciphertext of a block dependent on **all** blocks before it.


Cipher Block Chaining (CBC)

- ◆ Encryption: use Initial Vector (IV) to start process
 - $C_i = E_K(P_i \oplus C_{i-1}), C_{-1} = IV$
 - IV doesn't need to be secret (if derived and used properly)
- ◆ Decryption: start from last block of ciphertext
 - $P_i = D_K(C_i) \oplus C_{i-1}$
- ◆ Used for bulk data encryption, authentication

Cipher Block Chaining (CBC)



Cipher Block Chaining (CBC) mode encryption



Cipher Block Chaining (CBC) mode decryption

CBC Decryption

$$C_j = E_K[C_{j-1} \oplus P_j]$$


Encryption step
Decryption step
(with justification)

$$D_K[C_j] = D_K[E_K(C_{j-1} \oplus P_j)]$$


$$D_K[C_j] = (C_{j-1} \oplus P_j)$$

$$C_{j-1} \oplus D_K[C_j] = C_{j-1} \oplus C_{j-1} \oplus P_j = P_j$$

Graphics with CBC



Another Graphics Example (thanks Wikipedia)



Advantages and Limitations of CBC

- ◆ Good: each ciphertext block depends on **all** message blocks, thus a change in the message affects all ciphertext blocks after the change as well as the original block
- ◆ need **Initial Value** (IV) known to sender & receiver
 - however if IV is sent in the clear, an attacker can change bits of the first block, and change IV to compensate
 - hence either IV must be a fixed value or it must be sent encrypted in ECB mode before rest of message
 - Note that randomly chosen IV means attacker cannot supply known plaintext to underlying cipher even if they can supply plaintext to CBC
 - Weak IV was cause of weakness of WEP


Counter Mode

- ◆ In this mode, a cipher is used to generate a sequence of pseudorandom blocks that are XORed with the plaintext blocks
- ◆ Assume plaintext $P = P_1 || P_2 || P_3 || \dots || P_L$
- ◆ When I use this, I think of the method as follows:
 - Choose key K and initial counter value IV
 - ◆ IV is the state that prevents the same plaintext from encrypting to the same ciphertext if it's encrypted multiple times with K .
 - Create a sequence of pseudorandom blocks as follows:
 $E_K(IV), E_K(IV+1), E_K(IV+2), \dots, E_K(IV+L)$
- ◆ Ciphertext is $C = (E_K(IV) \oplus P_1) || \dots || (E_K(IV+L) \oplus P_L)$
 - That is $C_i = E_K(IV+i) \oplus P_i$


Counter Mode: Notes

- ◆ Ciphertext is $C = (E_K(IV) \oplus P_1) || \dots || (E_K(IV+L) \oplus P_L)$
- ◆ Note that IV is supposed to be pseudorandom. Thus by choosing a different value each time we encrypt P , we get different ciphertexts, even if we use the same key K
- ◆ IV does not need to be kept **secret**, but IV must be cryptographically secure pseudorandom, and same (IV, K) pair must not be used twice. (Why?)
- ◆ Advantages:
 - Can be parallelized
 - Can encrypt or decrypt a single block without having to do same to other blocks
- ◆ Note that in this formulation, IV needs to be known by both encrypting and decrypting parties.

There are Other Modes...



Cipher Feedback (CFB) mode encryption



Cipher Feedback (CFB) mode decryption

Recall: Chosen-ciphertext attacks

- ◆ Adversary is able to choose ciphertexts and receive the corresponding plaintexts
- ◆ We now know the material we need to see an example of one of these: Padding-Oracle Attacks!
- ◆ This attack has been shown to work in practice on various deployed protocols
- ◆ Thanks: Introduction to Modern Cryptography (3rd Edition) by J. Katz and Y. Lindell
 - A really nice crypto text/reference, by the way

Recall: Chosen-ciphertext attacks

◆ The setting:

- Clients send messages encrypted using CBC-mode to server
- We assume the attacker can impersonate a client and send ciphertexts of its choice to the server, which the server will decrypt
- We assume only that the attacker can tell when resulting decrypted messages are valid
 - ◆ So attacker does not need the resulting plaintext
- This is realistic: when receiving ciphertexts that don't decrypt correctly, servers do things like send retransmission requests or terminate the connection, both observable by the adversary

OK, So I Lied

- ◆ We actually need one more piece of background info:
PKCS #7
 - This is a padding scheme standard
 - So I lied twice: we don't always pad with zeros
- ◆ PKCS #7
 - Assume the block length of our cipher is L
 - If length of plaintext is not a multiple of L bytes, we might have to pad (added padding is called *encoded data*)
 - Any padding scheme must be such that receiver can unambiguously distinguish original message from encoded data

PKCS #7

- ◆ Let $b > 0$ be the number of bytes that need to be padded to the original message to make the total length a multiple of block length L
- ◆ Append to message the integer b , represented as one byte (i.e. two hex digits) exactly b times.
 - Ex. If one byte needed, pad with the byte `0x1`
 - Ex. If four bytes needed, pad with the four bytes `0x4 0x4 0x4 0x4`

PKCS #7

- ◆ b must be an integer between 1 and L inclusive – can't have $b = 0$ (it would lead to ambiguous padding)
 - So if original message length is a multiple of L , then $b = L$ and the message is padded with a whole block of bytes that are integer representation (in one byte) of L
 - E.g., if block length is 128, get a whole block of 0x80 bytes

PKCS #7

- ◆ When decrypting, server uses CBC-mode as usual, then checks the last byte of the resulting plaintext.
 - If the last byte has value b , then verify that the final b bytes all have value b
- ◆ If this check fails, server returns some kind of “bad padding” error (as mentioned above)
 - So server acts as a “padding oracle” – it tells adversary whether a ciphertext corresponds to a message that was correctly padded

Padding-Oracle Attack

- ◆ We describe the attack on three block ciphertext: Let IV, c_1, c_2 be a ciphertext that corresponds to a message padded using PKCS #7 and observed by the attacker, and m_1, m_2 the underlying plaintext (including encoded data)
- ◆ Recall formula for decrypting data encrypted using CBC mode: $P_i = D_K(C_i) \oplus C_{i-1}$
 - So $m_2 = D_K(c_2) \oplus c_1$
 - The second block, m_2 , ends in b bytes of value $0xb$

Padding-Oracle Attack

- ◆ The key issue (pardon the pun): Certain changes to the ciphertext yield predictable changes in the encoded data after CBC-decryption
- ◆ So, let c_1' be identical to c_1 except for modification of the final byte, and consider decrypting the ciphertext IV, c_1' , c_2
 - Result is m_1' , m_2' where $m_2' = D_K(c_2) \oplus c_1'$
 - So m_2' differs from m_2 only by modification of final byte
 - Similarly if c_1' differs only from c_1 in the i th byte, same will be true of m_2' and m_2

Padding-Oracle Attack

- ◆ More generally, if $c_1' = c_1 \oplus \Delta$ for any string Δ , then $m_2' = m_2 \oplus \Delta$
- ◆ Bottom line: adversary has significant control over final block of encoded data

Padding-Oracle Attack

- ◆ Use this to learn b , the amount of padding (which also yields length of the original message):
 - Attacker modifies **first** byte of c_1 and sends resulting IV, c_1', c_2 to server
 - If this fails, then the server must be checking ALL bytes of m_2 for padding, so therefor $b = L$.
 - Otherwise, $b < L$, so attack repeats the process, but this time changing only the second byte of c_1
 - Left most byte for which decryption fails reveals exactly left most byte being checked by server, and thus the value of b