
cmta.

Rules Overview

Overview of the functional specifications for the Rules for CMTAT and RuleEngine on Ethereum and EVM compatible blockchains.

Rules version: v0.6.0
First published: August 2026



RuleEngine - Rules

Rules is a collection of on-chain compliance and transfer-restriction rules for security tokens built on
the CMTAT token standard and the CMTA RuleEngine, including ERC-3643-compatible tokens.

Each rule enforces one transfer restriction. A rule can be plugged **directly** into a token, or several can be composed behind a **RuleEngine**.

> This project has not undergone an audit and is provided as-is without any warranties.

Compatibility

Rules	Contracts report `version()`	CMTAT	RuleEngine	OpenZeppelin
v0.6.0 (current)	`"0.6.0"`	**≥ v3.0.0**, validated against `v3.3.0-rc3`	`v3.0.0-rc6`	`v5.7.0`

One rule needs more than the baseline, because it reads the **spender** the token forwards on mint:

Rule	Minimum CMTAT	Why
`RuleMintAllowance`	**v3.3**	Debits the minter's quota from the 4-argument `transferred(spender, from, to, value)` / `canTransferFrom`. A token that does not forward the spender cannot drive it.
Every other rule	v3.0.0	Uses the 3-argument path only.

The submodules in `lib/` are pinned to the validated versions (CMTAT `v3.3.0-rc3`, RuleEngine `v3.0.0-rc6`), so
a `git submodule update --init --recursive` checkout builds and tests against exactly what this release was verified with.

📖 **Full documentation →** — the complete reference: every rule in detail, the API, access-control model, restriction codes, deployment guide, and security findings. This page is a summary.

What a rule does

A rule answers two questions about a proposed token movement.

Path	Functions	Behaviour
Read	`detectTransferRestriction`, `canTransfer` (and their `…From` variants)	Views returning an ERC-1404 restriction code (`0` = OK). They **must not revert**.

Path	Functions	Behaviour
Write	`transferred`, `created`, `destroyed`	Called by the token *after* it decides to move value. A rule **reverts** to block, and may update state.

Architecture

Two integration topologies, and the choice determines what `msg.sender` is inside a rule:




Diagram source: *doc/schema/architecture-topologies.puml*.

Behind a RuleEngine the engine returns the **first non-zero** restriction code, so rule order decides which
code a rejection reports. In direct mode the rule is installed with `token.setRuleEngine(rule)`.

Operation rules keep state keyed on the caller, so the two are not interchangeable for them: `RuleConditionalTransferLightMultiToken` is direct-binding only, and `RuleMintAllowance` requires the engine path. Validation rules work under either.

Layout

Path	Contents
`src/rules/validation/`	Read-only rules: no state change during a transfer
`src/rules/operation/`	Read-write rules: mutate state on transfer
`src/registry/`	Fills a token's **identity registry** slot, not its compliance slot (`IdentityRegistryWhitelist`). Not rules
`src/modules/`	Reusable modules (access control, meta-tx, versioning)
`script/`	Deployment scripts
`test/`	Foundry tests, one folder per rule

Each rule splits into a `*Base` contract holding the logic and a deployable variant supplying the access-control policy, in either an `AccessControl` or an `Ownable2Step` flavour.

The rules

Rule	Enforces	Codes
`RuleWhitelist`	Transfers only between whitelisted addresses	21–25
`RuleReceiverWhitelist`	Receiver only, reproducing ERC-3643 eligibility	81
`RuleSpenderWhitelist`	`transferFrom` only when the spender is whitelisted	66
`RuleWhitelistWrapper`	Aggregates several whitelists with OR logic	21–23
`RuleBlacklist`	Blocks blacklisted participants	36–38
`RuleSanctionsList`	Blocks sanctioned addresses via a Chainalysis oracle	30–32
`RuleERC2980`	ERC-2980 whitelist plus frozenlist	60–65
`RuleIdentityRegistry`	Consults an ERC-3643 identity registry	55–57
`RuleMaxTotalSupply`	Caps total supply on mint	50, 51
`RuleMaxTotalSupplyERC3643`	Caps total supply on mint, for tokens that mint *first* and call the rule after	50, 51
`RuleMaxBalance`	Caps how many tokens one address may hold	82, 83
`RuleChainlinkPoR`	Caps minting at Chainlink Proof of Reserve reserves	75–79
`RuleChainlinkPoRERC3643`	Caps minting at reported reserves, for tokens that mint *first* and call the rule after	75–79
`RuleConditionalTransferLight`	Requires operator approval per transfer	46
`RuleMintAllowance`	Per-minter mint quota	70

Codes must stay unique across rules, since a RuleEngine returns the first non-zero one.

The two `…ERC3643` variants differ only in *when* they expect to be called, and that is what to pick them by. CMTAT asks the rule before it moves the value, so the stock rule adds the pending amount to the supply it reads; ERC-3643 / T-REX mints first, so the variant must not add it again. Both mismatches are silent: the stock rule on an ERC-3643 token counts the amount twice and rejects mints that are inside the cap, and a variant on a CMTAT token stops enforcing the ceiling on the write path.

Per-rule detail is in `doc/technical/`; the semantics that differ between rules (who is screened, mint/burn handling, unset-oracle behaviour) are tabulated in `RULE_SEMANTICS.md`.

ERC-3643

An ERC-3643 token has **two** pluggable slots, and this library fills both, from opposite directions.

Slot	Filled with	Direction
Compliance (`ICompliance`)	A `RuleEngine` holding rules	The token asks the rules whether a transfer may proceed
Identity registry (`IIdentityRegistry`)	`IdentityRegistryWhitelist`	The token asks it whether a wallet is a verified investor




Diagram source: doc/schema/erc3643-slots.puml.

Compliance: go through a RuleEngine

Use `RuleEngine`, not a bare rule. ERC-3643 drives mint and burn through `created` and `destroyed`, which the **validation rules do not implement** — they only expose `canTransfer` / `transferred`.

`RuleEngine` implements the full `ICompliance` surface and forwards to the rules, so it is the supported path.

The operation rules do implement `created` / `destroyed`, but they are bound to a single token and are not a compliance contract on
their own.

Not every rule behaves the same on this path. ERC-3643 never forwards a spender (both `transfer` and `transferFrom` call the
3-argument `transferred`) and calls compliance *after* it moves the value. Some rules are therefore inert, and the two supply-cap
rules need their `…ERC3643` variant. The per-rule matrix is
[RULE_SEMANTICS.md §6](RULE_SEMANTICS.md).

Identity verification

ERC-3643 decides who may hold a token by asking an **identity registry** one question: `isVerified(wallet)` — is this a verified investor? A normal registry answers it by checking the wallet's
on-chain identity contract (ONCHAINID) for the required claims.

This library provides **both sides of that exchange**:

Contract	What it is	Where it plugs in

Contract	What it is	Where it plugs in
`RuleIdentityRegistry`	The side that **asks the question**: a transfer rule that calls `isVerified` on whatever registry the token uses, and blocks the transfer when the answer is no.	Added to a RuleEngine, like any other rule
`IdentityRegistryWhitelist`	The side that **answers it**: a registry implementation that replies from a whitelist instead of reading ONCHAINIDs, so no identity contracts need deploying.	`token.setIdentityRegistry(...)`. It is **not** a rule, implements no `IRule`, and must never be added to a RuleEngine




Diagram source: [`doc/schema/erc3643-identity-directions.puml`](doc/schema/erc3643-identity-directions.puml).

Which one you need is decided by the token, not by preference.

- **On an ERC-3643 token**, plug `IdentityRegistryWhitelist` straight into the identity slot with
  `setIdentityRegistry`. The token screens every transfer itself. Do **not** also add `RuleIdentityRegistry`
  behind a RuleEngine: the token already consults the registry, so the rule would screen the same wallets a
  second time for no added restriction.
- **On a CMTAT token there is no identity slot at all** — `setIdentityRegistry` is an ERC-3643 concept, and
  CMTAT has no equivalent. So `RuleIdentityRegistry` behind a RuleEngine is not one option among several, it
  is the only way to apply identity-registry screening. It consults whichever registry you point it at:
  your own ONCHAINID-backed one, or `IdentityRegistryWhitelist` if you have none.

That second case is why the two contracts compose at all, and it is pinned by `test/IdentityRegistryWhitelist/CMTATRuleIdentityRegistryComposition.t.sol`. They are wired by interface
rather than inheritance: the rule holds an `IIdentityRegistryVerified` and only ever calls `isVerified`.

Matching the spec's semantics

`RuleReceiverWhitelist` reproduces ERC-3643 eligibility exactly: **only the receiver** is screened. The spec
checks the receiver alone on purpose, so a de-listed holder can still exit a position; screening the sender
would trap them. `RuleIdentityRegistry` follows the same default, with sender and spender checks available as
explicit opt-ins.

Every rule and the registry implement `IERC3643Version`, so `version()` is queryable on-chain.

Tested against a real ERC-3643 token

`test/ERC3643Real/` runs against the actual ERC-3643 `Token.sol` and `IdentityRegistry.sol`, not mocks: the
RuleEngine integration, the identity rule against a real registry, and receiver-whitelist parity with the
spec's eligibility. 31 tests, run with `FOUNDRY_PROFILE=erc3643 forge test`.

Quick start

```
forge build                              # compile
forge test                               # run the suite
FOUNDRY_PROFILE=erc3643 forge test       # the real-ERC-3643-token suite
```

Both commands are required: the vendored ERC-3643 `Token.sol` pins solc `0.8.30` exactly and cannot share a
compilation unit with our `0.8.36`, so `test/ERC3643Real/**` builds under its own profile.

Deploying a token with rules attached:

```
forge script script/DeployCMTATWithBlacklist.s.sol:DeployCMTATWithBlacklist --
rpc-url <RPC> --broadcast
```

Four scripts cover the common combinations. See
`DEPLOYMENT_SCRIPTS.md` for configuration and limitations.

Documentation

Topic	Document
Full reference	`doc/README.md`
Per-rule detail	`doc/technical/`

Topic	Document
Cross-rule semantics	`RULE_SEMANTICS.md`
Deployment scripts	`DEPLOYMENT_SCRIPTS.md`
Invariant tests	`INVARIANT_TESTS.md`
Audits and static analysis	`doc/security/audits/`
Release history	`CHANGELOG.md`

Security

No formal third-party audit has been carried out. The code has had automated static analysis and AI-assisted review, each triaged by the project team:

Type	Tool	Latest run
Static analysis	Slither 0.11.5	v0.6.0
Static analysis	Aderyn 0.6.5	v0.6.0
AI automated scan	Nethermind AuditAgent	v0.5.0
AI-assisted review	Claude Code (Anthropic)	v0.5.0
AI-assisted review	Claude + custom security-audit skills	v0.4.0
AI-assisted review	Wake Arena (Ackee Blockchain Security)	v0.2.0

Scope is the production contracts under `src/`; mocks, tests and vendored dependencies are excluded.

Every finding carries a written triage, including the ones dismissed as false positives or by-design. Nothing is outstanding as of `v0.6.0`: the static analysers report nothing to fix (Slither 46 results, Aderyn 346 Low instances — all false-positive, by-design, environmental or cosmetic), and the AuditAgent scan is fully dispositioned.

Nethermind AuditAgent (v0.5.0)

Scan	High	Medium	Low	Info	Anything to fix?
2026-08-17, commit `01632da`	0	13	11	0	**Nothing exploitable** — 7 fixed in `v0.6.0`, 16 accepted as design, 1 declined; nothing left open

> Note: This scan was performed by an AI-powered automated tool, not a formal human-led audit.

No false positives, but 17 of the 24 findings restate design positions already documented in the source and in the previous audit, so the set collapses to about 11 distinct claims. Seven were fixed in `v0.6.0`; the substantive ones:

- **NM-3** — the identity-registry rule's `transferFrom` path now always delegates to the direct restriction check. A subclass extending only that hook could previously have its check applied to `transfer` but silently skipped on `transferFrom` and `burnFrom`.
- **NM-6** — the ERC-7943 overloads now read an owner-initiated transfer (`spender == from`) as direct, matching the `ITransferContext` entrypoints, so `RuleSpenderWhitelist` no longer blocks an owner moving their own tokens.
- **NM-10** — a Proof-of-Reserve round stamped in the future is rejected as a malformed answer instead of being accepted as fresh.
- **NM-11** — the cap rules assume the token calls the compliance hook *before* moving value. CMTAT does; ERC-3643 / T-REX does not, so the stock rule counted the amount twice and reverted mints that were within the cap. `RuleChainlinkPoRERC3643` and `RuleMaxTotalSupplyERC3643` now ship for that path, verified against the vendored T-REX token; `RuleMaxBalance` stays CMTAT-only by design.

Report (PDF) · feedback.

Reports, triage and the threat model live in `doc/security/audits/`, indexed by `AUDIT_OVERVIEW.md`.

Development

Parts of this project were written with the help of AI coding assistants, principally **Claude Code** (Anthropic) and **Codex** (OpenAI).

Intellectual property

The code is copyright (c) Capital Market and Technology Association, 2022-2026, and is released under Mozilla Public License 2.0.