17-214/514: Agentic Software Development

Agent Supervision and Safety

Hammad Ahmad and Claire Le Goues • Wednesday, October 21, 2026 • Lecture

Administrivia

- A4 checkpoint is due tonight.
- A3 verbal defense window ends this Friday.
- The final exam will be on Friday, December 11th. 1-4pm. Location TBD.


What did we talk about last time?

- An agent is a model plus an assembled context and tools, run in a loop by a harness you configure.
- The toolset is the agent's reach. Allowlists, read-only modes, scopes, and permission rules bound it.
- A coordinating agent can hand slices to subagents, including a fresh-context verifier.
- We judged a setup by capability, controllability, and observability, and talked about measuring it with an eval.
- You control the setup, but not the model's judgment on any single call.

Learning goals for today

- Decompose a repo-scale task into slices, each behind a gate
- Explain what made the Ralph Wiggum loop work and where it can go wrong
- Check a passing change with a fresh-context refuter, and settle what it finds with evidence
- Distinguish instructions from permissions, and choose guardrails and isolation for a run
- Recognize reward hacking and prompt injection, and name a check for each
- Allocate review attention by risk
- Design a supervision plan (gates, escalation, records) for a risky delegated task

Recall: the Replit incident



r/OpenAI


The Hugging Face incident

- OpenAI was testing models on a cyber benchmark, with their usual refusals turned down for the test.
- The sandbox could reach the network only through a package proxy, so the agents could install dependencies.
- The models found an unknown bug in that proxy and got out.
- They then spent about two and a half days inside Hugging Face's infrastructure, apparently looking for the benchmark's answers.

Anatomy of a Frontier Lab Agent Intrusion: A Technical Timeline of the July 2026 Incident

Published July 27, 2026


Hugging Face



Kurzgesagt – In a Nutshell

What does supervision consist of?

- Watching an agent carefully works for a short task. Your attention runs out long before an overnight run does.
- Supervision at scale is a set of parts you design up front and others can review.




You have done a small version of each since the first week. Let's now scale them to tasks too big to watch.

Repo-scale tasks

Slicing a cross-cutting change

Moving every handler in the booking system from exceptions to result types touches most of the codebase. That may be too much to review the way you review a small diff.



- Each slice can be checked and reverted on its own. The system builds and passes its tests between slices.
- The order: small foundational slices reviewed closely first, then batches once the pattern works, then close review for the handlers the template doesn't fit.

Consider the booking system's error model

The task: every handler in the booking system moves from `throw` to result types.

- **Slice 1:** The result type and its helpers. Everything else depends on it, so you review it closely.
- **Slice 2:** One representative handler (`book()`) and its tests. This becomes the template the agent copies.
- **Slices 3 and on:** The agent applies the template to the other handlers in batches. The suite stays green after each batch. You can spot-check a few handlers per batch.
- **The leftovers:** The handlers that don't fit the template. Not a bad idea to group these by why they don't fit and look closely at each group.
  - For example, the waitlist handler catches `BookingException` from `book()` and moves on to the next person in line. Once `book()` returns an error instead, that catch never runs.
  - As a reminder, Chesterton's fence applies here. Find out why before you change it.

Slice requirements

- A gate, defined **before** the slice runs (which tests, which checks, what a person reviews).
- The slices it builds on should pass their gates first. Otherwise one bad slice can spread into every batch after it.
- Its own context: the template, the result type's contract, and its handlers. The history of earlier slices can (and probably should) stay out of its window.
- A current plan document, which is the state the slices share.

Anatomy of one gate

An example gate for slice 2 (the `book()` template), written down before the slice runs:

```
GATE, slice 2:
  [ ] full suite green
  [ ] characterization tests on book()'s error paths still pass
  [ ] diff touches only book() and its tests
  [ ] error messages unchanged (callers match on them)
  [ ] a person reviews it closely (since this is the template)
```

- Most can be checked by a tool.
- Later slices can copy this gate without the close review, once the template has passed it.
- If you can't write the gate, you probably don't understand the slice yet.


The long run

What if the agent runs overnight?

- For example, the triage agent works through the whole backlog of bug reports while you sleep.
  - It reads a report, reproduces the bug, labels severity, and files a ticket.
- The benefit is that your time stops being the bottleneck.
- The drawback is that your judgment is out of the loop until morning (if you check at all).

Bad stuff can happen if the agent is unattended

- **Drift from intent:** Each step looks reasonable on its own, but the sum ends up somewhere you never intended.
- **Compounding:** Later steps build on an early mistake.
- **Confident completion:** The run ends and the report says done, but the agent wrote that report itself. It can claim things that didn't happen.
  - For example, the Replit agent that deleted a production database also generated fake data and reported tests as passing when they hadn't.



Reading the morning-after report

- The report is written by the same agent that did the work, so it can be wrong about that work.
- Check the artifacts it left behind (the tracker, the logs, the diff). They exist separately from the report, so you can check its claims against them.
- For each important claim, ask what evidence would make it true, and whether that evidence is there.

The report says

```
Triaged the whole backlog.
Every report reproduced and
filed. No issues encountered.
```

The artifacts say

```
tracker: 112 tickets filed
backlog: 131 reports
repro logs: 87 runs, 9 timed out
```

Recovering a derailed run

- **Checkpoint often:** A commit at every green gate makes "restart from the last good state" a real option.
  - `/rewind` restores the agent's file edits, but not files changed through `Bash`. Git is the restart point you can trust. (Codex does not have rewind, so git is your best friend there.)
- **Restart rather than repair:** Past a bad checkpoint, revert and re-run from the last good state.

The Ralph Wiggum loop


Reminder: the Ralph Wiggum loop

In its original form, from Geoffrey Huntley, it is one line of shell:

```
while :; do cat PROMPT.md | claude-code ; done
```

Geoffrey Huntley

- The same prompt runs over and over, with a fresh context every iteration.
- Only the files on disk carry over, so context rot can't build up.



The loop in practice

- One team's overnight loops ported six codebases for a little under $800.
- Huntley's prompt has the agent commit only "When the tests pass".
- After finishing its port, one agent kept going and added integrations the original project never had.
- The same team's agent "immediately got slower and dumber" once its prompt grew to about 1,500 words.

We Put a Coding Agent in a While Loop and It Shipped 6 Repos Overnight

This weekend at the YC Agents hackathon, we asked ourselves: *what's the weirdest way we could use a coding agent?*

Our answer: run Claude Code headlessly in a loop forever and see what happens.


Turns out, what happens is: you wake up to 1,000+ commits, six ported codebases, and a wonky little tool we're calling RepoMirror.

github.com/repomirrorhq

- Huntley's own warning is that "you'll wake up to a broken codebase that doesn't compile from time to time".

The test suite is often not enough

- Recall: a test suite is rarely complete.
- One more gate you can build is a **refuter**, a second agent in a fresh context whose job is to break the change.
- It gets the spec and the diff, but not the writer's explanation of why it's right.



Weighing a refuter's result

- A fresh context drops the writer's reasons for believing the change is right.
- The same model can still share the writer's blind spots, so "I found nothing" is weaker evidence than it sounds.
- Its findings can be wrong. Check each one with a failing test before acting on it.
  - Runs vary, so two refuters can help you sort. Important findings both report are a good place to start. (Something important found by only one still counts if it reproduces.)
- The brief also matters, though. Which of these would you rather send?

"Does this change to `book()` look right?"

"Find inputs or call sequences where `book()` now does the wrong thing."

The refuter found nothing. Is the slice done?

A refuter brief

A brief for the `book()` slice, in a fresh session:

```
You are checking a change you did not write.
You get the booking spec (SPEC.md) and the diff below.
Find inputs or call sequences where book() now does
the wrong thing. For each one, write a test that fails.
Do not fix anything.
```

- For a fresh context, start a new session (`claude -p "..."`, `codex exec "..."`) and give it only the brief, the spec, and the diff.
- Settle each finding: reproduce it as a failing test, or dismiss it with evidence (a test, a run, a line of the spec).
- Try to have scoped checks for fixes, since fixes can bring in new defects.

You do need to ship it at some point

- The check on a fix usually finds something too, often in the fix itself.
- As a reminder, define done before you delegate. In this case, that means deciding when the review stops before the first round of reviews.
  - For example, run one round, fix what reproduces, then one check scoped to those fixes. Stop if that check finds nothing that breaks the spec.
- Fix what breaks the spec. Write down the other important findings (an issue in the tracker, a known limitation in the plan), and let the minor ones go.
- If a third round still finds real defects, the problem is probably the slice or the spec. Re-slice it, or take it over.

Guardrails

Instructions vs. permissions

- **Instructions** are what the agent is told ("don't touch prod", "code freeze", "please don't modify code").
- **Permissions** are what the agent is able to do (which tools, which paths, which credentials).
- The harness enforces permissions. The model reads instructions and usually follows them.
- For example, the Replit agent was under a code freeze (an instruction) and had credentials that reached production (a permission).



Know Your Meme

Three ways to keep an agent out of `payments/`

Option	Enforced by	A way around it
A `deny` rule on `Edit(/payments/**)` (Claude Code, or `write_file(payments/)` in Antigravity)	The agent tool's permission check	A script the agent writes and then runs
A PreToolUse hook on the edit tools (Claude Code, Codex, or Antigravity)	A script the harness runs before each edit	`cp`, `sed -i`, or anything else run through `Bash`
`chmod -R a-w payments/`	The operating system	An agent with a shell can `chmod` it back

- Each one alone has a gap, so layer them where the stakes are high.
  - Mounting `payments/` read-only inside a container closes all three gaps, since the agent can't undo it. (Codex's sandbox can do this with `"payments" = "read"` in a permission profile.)
- You will practice this more in Lab 8.

A closer look at a hook

`.claude/hooks/guard.py`, a PreToolUse hook on `Edit` and `Write`:


```
import json, sys

call = json.load(sys.stdin)
path = call["tool_input"].get("file_path", "")
if "/payments/" in path:
    print(f"{path} is out of scope for this task", file=sys.stderr)
    sys.exit(2)
```

- Claude Code passes the call to the hook as JSON on stdin. Exit 2 blocks it. The hook's stderr is what the agent is told.
- Any other non-zero exit lets the call through.
  - With `exit(1)` instead, a test run made the edit and the agent reported no errors.
- Codex hooks work the same way, once you approve them in `/hooks`.

Sandbox isolation

- **Filesystem:** Writes stay inside the folders it is given.
- **Network:** No outside connections, or an allowlist of places it may reach.
  - For example, OpenAI's sandbox allowed one path out (a package proxy for installing dependencies). The proxy had an unknown bug that let the models through to the internet.
- **Credentials:** Leave out anything the task doesn't need (especially production keys).



- A quick audit: ask what the agent can read, write, and reach from inside the sandbox.

Claude Code's sandbox

Codex sandboxes by default. In Claude Code, `/sandbox` turns it on. In a settings file:

```
{ "sandbox": { "enabled": true,
               "allowUnsandboxedCommands": false,
               "failIfUnavailable": true } }
```

- It covers shell commands only. The file tools, MCP servers, and hooks run outside it, under your permission rules.
- Writes stay in the project, but reads still reach most of your machine (including `~/.ssh`) unless you deny them. (Antigravity's sandbox blocks `~/.ssh` by default.)
- Sometimes a command can still run unsandboxed.
  - `allowUnsandboxedCommands` stops Claude from retrying a command outside the sandbox.
  - `failIfUnavailable` stops commands from running when the sandbox can't start.

How much isolation does a run need?

Option	What runs inside it
Built-in sandbox (on by default in Codex and the Antigravity app)	Shell commands only
Sandbox runtime (`srt claude`)	The whole agent, hooks and MCP servers included
Dev container	The whole development environment, in Docker
Virtual machine	A whole operating system, with its own kernel
Cloud session	A machine the agent's vendor runs for you (Claude Code cloud sessions, Codex Cloud)

- For a run that skips permission checks, the docs say to use a container, a VM, or the sandbox runtime. The built-in sandbox alone is not enough.
- In case you're wondering: auto mode's classifier reviews each action, but it doesn't limit what an approved action can reach. Hence the isolation.

A container setup

`.devcontainer/devcontainer.json`, from Claude Code's docs:

```
{
  "image": "mcr.microsoft.com/devcontainers/base:ubuntu",
  "features": {
    "ghcr.io/anthropics/devcontainer-features/claude-code:1.0": {}
  }
}
```

- Once you reopen the project in the container, the agent's commands run inside it.
- Your project folder is still mounted, so the agent's edits show up on your machine. Commit before a run.

Tokens are money

- A loop with no limit can run up a bill with no limit. Retries, long contexts, and subagents all add to it.
- A budget is a guardrail too.



ProgrammerHumor.io

Configuring an overnight run


Inside the container, with Claude Code in headless mode:

```
claude -p "$(cat PROMPT.md)" \
  --permission-mode auto --permission-prompts none \
  --disallowedTools "Edit(/payments/**)" \
  --max-turns 200 --max-budget-usd 20 \
  --output-format json > run.json
```

- Anything that would have asked you is denied. The turn and budget caps stop the run.
- `run.json` records the cost and every denied call.
  - A denial can leave the task unfinished. The list will show what to grant before a re-run, and whether the agent tried to get around a limit.
- Inside `while :; do ... done`, this is the Ralph loop with guardrails. Cap the iterations too, since the budget is per run.
- (In Codex, `codex exec --json` runs headless, but it has no turn or budget cap, so the loop needs its own limit.)

Least privilege

- As a reminder, size the action space to the task.
  - For example, the migration agent needs to write to the repo and run the tests. It does not need deploy keys or the customer database.
- An agent may use any capability it has when that looks like the shortest path to done.
- Permissions also depend on the mode. In auto mode, a classifier approves most actions without asking you.
  - A `deny` rule, or a tool left out of the agent's toolset (a subagent's `tools:` list), holds in every mode.



a boundary decides (among other things)
how far wrong can spread

What if the shortest path to "done" is cheating?

- **Alignment** asks whether an agent pursues the goal you meant, or only what your checks measure.
- An agent trained to make checks pass can learn to pass them the wrong way (**reward hacking**).
- Hugging Face also treated (publicly, at least) the July intrusion as "an attempt to cheat the evaluation".


6 Excessive Focus on Passing Tests

During our evaluations we noticed that Claude 3.7 Sonnet occasionally resorts to special-casing in order to pass test cases in agentic coding environments like Claude Code. Most often this takes the form of directly returning expected test values rather than implementing general solutions, but also includes modifying the problematic tests themselves to match the code's output. These behaviors typically emerge after multiple

Anthropic, Claude 3.7 Sonnet system card (p. 22)

Catching reward hacking

- On repo-level coding tasks made impossible on purpose (so any pass is cheating), recent models often passed anyway. Anthropic's models mostly did it by editing the tests.
- Diffs that edit or delete tests deserve a close read, or a `deny` rule if the task shouldn't change them.
- A check the agent never sees can catch it too (held-out tests, a fresh-context refuter).



ImpossibleBench: Measuring LLMs' Propensity of Exploiting Test Cases

Ziqian Zhong · Aditi Raghunathan · Nicholas Carlini

The tendency to find and exploit "shortcuts" to complete tasks poses significant risks for reliable assessment and deployment of large language models (LLMs). For example, an LLM agent with access to unit tests may delete failing tests rather than fix the underlying bug. Such behavior

ICLR 2026

- What the agent says it did is weak evidence. In one OpenAI study, a model penalized for saying it would cheat kept cheating and stopped saying so.

Let's practice: An agent converted the `api/bookings/` handlers to result types (slice 4). Its report says "All handlers converted. Suite green." One hunk of its diff:

```
 @Test
 void rejectsDoubleBooking() {
     service.book(room, nineToTen);
-    var ex = assertThrows(BookingException.class,
-        () -> service.book(room, nineToTen));
-    assertEquals("Room is already booked", ex.getMessage());
+    var result = service.book(room, nineToTen);
+    assertTrue(result.isErr());
 }
```

With a neighbor:

1. Is this reward hacking, or a fair update for the new result type?
2. Which of the checks from today would have stopped this change? Which would also have stopped a fair update?

Slice 4's gate:

- full suite green
- characterization tests on the error paths pass
- error messages unchanged (callers match on them)

Canvas → Quizzes → Lecture 14 In-Class Quiz

"Ignore all previous instructions and …"

- The triage agent reads bug reports, which anyone can write. A report can carry instructions aimed at the agent. This is **prompt injection**.
- In a 2025 demo, a malicious GitHub issue got an agent to copy private-repo data into a public pull request. (Invariant Labs)
- One check is whether an agent combines private data, untrusted content, and a way to send data out (Willison's "lethal trifecta").

The **lethal trifecta** of capabilities is:

- **Access to your private data**—one of the most common purposes of tools in the first place!
- **Exposure to untrusted content**—any mechanism by which text (or images) controlled by a malicious attacker could become available to your LLM
- **The ability to externally communicate** in a way that could be used to steal your data (I often call this "exfiltration" but I'm not confident that term is widely understood.)

Simon Willison

- Taking away any one of the three closes that path, for example with a token that reaches only one repo.

Spending your attention

Where should your attention go?

- The agent's hours got cheap. Yours probably didn't.
- The usual guidelines apply: glance, let the agent search and report, spot-check, and read closely where the risk is.
- At repo scale, a place the risk sits is the piece everything else copies (the template, the result type).
- As before, a gate you trust can stand in for a close read (for both features and mechanical changes).

You can have the agent stop and ask

- A delegation can say when to stop.
  - For example, "If the tests can't pass without changing the contract, stop and ask". Or "If you are about to touch `payments/`, stop".
- Stop conditions in the brief mean the agent pauses where you planned, rather than where it happens to.
- An agent that can't reach you at that point will usually decide on its own, so say what it should do instead (stop and report).

A brief with stop conditions

```
Task: convert the handlers in api/bookings/ to the
result-type template (see PLAN.md, slice 4).

STOP AND ASK before:
  - changing any public signature or error message
  - touching anything outside api/bookings/
  - adding or upgrading any dependency
  - editing any test's assertions

If the suite cannot pass within these bounds, stop
and report why. Do not widen the bounds yourself.
```

- The last line matters a bunch. The agent should not change its own limits mid-task.
- Permissions can back up the same limits (e.g., a `deny` rule on paths outside `api/bookings/`), since only the permissions are enforced.

Who writes the record?

- Your `planning/` folder and transcripts are your supervision record.
- A hook (in Claude Code or Codex) can keep a record the agent doesn't write. For example, this hook logs every shell command:

```
# .claude/hooks/audit.sh, a PostToolUse hook on Bash
jq -c '{time: (now | todate), cmd: .tool_input.command}' \
  >> "$HOME/agent-audit.jsonl"
```

```
{"time":"2026-10-20T14:58:45Z","cmd":"ls"}
{"time":"2026-10-20T14:58:45Z","cmd":"git status --short"}
```

- You can keep the log outside the project, where sandboxed commands can't write.

Monitoring a run

- If you can't see a run, you can only examine it after it ends.
- In a Claude Code session, `/usage` shows cost so far, and `/tasks` lists background work, subagents included.
  - (In Codex, `/status` shows token usage and `/ps` shows background terminals.)
- For many runs, Claude Code and Codex can both export metrics through OpenTelemetry to a dashboard.
- Antigravity has the agent post artifacts (plans, diffs, browser recordings) for review at milestones.
  - The agent writes these itself (so they can be wrong about its own work). Check them against the diff and the test results.
- We'll come back to observability later.

Choosing the autonomy level


When is autonomy irresponsible?

	What breaks if it's wrong?	Can you undo it?	How far can it spread?
Triage agent (issues-only token)	A wrong label or a missed bug	Yes, edit the ticket	The tracker
Error-model migration	Handler behavior	Yes, revert the slice	The booking system
Schema migration on production data	Stored data	Often not, without a backup	Every service that reads it

Which of these would you let run overnight? **It depends.**

One task at three levels of autonomy

The booking system's error-model migration at three points:



One task can move along this line as it earns trust.

Coming up with a supervision plan

Assume an agent will upgrade the booking system's authentication library across a major version (breaking API changes, security-sensitive, and it touches sessions in every module).

Design the supervision. Include:

- Slices and their order. Which slice would you supervise most closely?
- The gates. What must pass before each slice counts? Where would a refuter help?
- Guardrails. Sandbox, credentials, budget, and the stop-and-ask conditions.
- Attention. What gets read closely, what gets sampled, and what the gate carries.

What does all of this mean for A4?

Concept	In A4
A gate written before the slice runs	Characterization tests, committed before your first refactoring commit
Slices that build and pass in between	Always-green steps. A commit per step means any one can be reverted.
Guardrails	Scope is graded. A `deny` rule or a hook on code outside your proposal helps keep the agent inside it.
A refuter	A fresh session given your pinned list, briefed to "find a behavior this refactor changed"
The record	`planning/` and `transcripts/`, read for how you split work too big for one agent context

A4 checkpoint: tonight, 11:59pm

- Due tonight: `ARCHAEOLOGY.md` (Deliverable A), with the commit link on Canvas.
- Tonight's grade is for good-faith completeness. The archaeology is graded again at the deadline.
- Next Wednesday: the proposal, characterization tests, and refactor. Commit the proposal and tests before your first refactoring commit.

Summary

- Supervision at scale is a set of parts you design up front.
- A repo-scale change splits into slices you can check and revert one at a time.
- A Ralph Wiggum loop needs a gate on every iteration (usually the test suite).
- A refuter in a fresh context is a second gate. Its findings can be wrong, so check each one with a failing test.
- The harness enforces permissions. The model only reads instructions. Each guardrail has a gap, so isolate unattended runs.
- Agents can pass checks the wrong way (reward hacking) or follow instructions hidden in their input (prompt injection).
- Spend your attention by risk, write stop conditions into the brief, and keep a record the agent doesn't write.

What's next

W1	W2	W3	W4	W5	W6	W7	W8	W9	W10	W11	W12	W13	W14
A1 out		A1 due		A2 due · M1		A3 due	A4 chkpt	A4 due	M2		A5 due		A6 due

- **Tonight, 11:59pm:** The A4 checkpoint (`ARCHAEOLOGY.md`).
- **Friday, Lab 8:** Supervise a repo-scale task, including a refuter.
- **Monday:** Software architecture (subsystems and their boundaries).
- **Next Wednesday:** A4 is due (proposal, characterization tests, and the refactor).